DELPHIX MASKING · PROFILE SET

Argentina — Ley 25.326

Discovery and masking of Argentine personal data: DNI, CUIT and CUIL with a valid check digit, CBU and CVU, quasi-identifiers, the sensitive data of articles 2 and 7, genetic and biometric data, gender identity, health data, financial data and criminal records.

83	150	116
DOMAINS	CLASSIFIERS	ALGORITHMS

Profile set `AR – Ley 25.326 – v2`

Version 2 of October 11, 2026 · Assignment threshold 60%

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	**About this profile set**	
2	**Ley 25.326 in brief**	
3	**Dissociation, pseudonymization and non-production copies**	
4	**How sensitive data is discovered**	
5	**How data is masked**	
6	**Essential and extended packs**	
7	**Domains at a glance**	

PART 8 · DIRECT IDENTIFIERS

8.1	**DNI and libretas**	AR_L1_DNI
8.2	**CUIT, CUIL and CDI**	AR_L1_CUIT
8.3	**DNI tramit number**	AR_L1_TRAMITE_DNI
8.4	**Foreigner documents**	AR_L1_DOCUMENTO_EXTRANJERO
8.5	**Passport**	AR_L1_PASAPORTE
8.6	**Civil registry**	AR_L1_REGISTRO_CIVIL
8.7	**Professional registration**	AR_L1_MATRICULA_PROFESIONAL
8.8	**Given name**	AR_L1_NOMBRE
8.9	**Surname**	AR_L1_APELLIDO
8.10	**Full name**	AR_L1_NOMBRE_COMPLETO
8.11	**Company name**	AR_L1_RAZON_SOCIAL
8.12	**E-mail**	AR_L1_EMAIL
8.13	**Phone**	AR_L1_TELEFONO
8.14	**Address**	AR_L1_DIRECCION
8.15	**Address complement**	AR_L1_DIRECCION_COMPLEMENTO
8.16	**CBU and CVU**	AR_L1_CBU
8.17	**CBU alias**	AR_L1_ALIAS_CBU
8.18	**Bank account**	AR_L1_CUENTA_BANCARIA
8.19	**Payment card**	AR_L1_TARJETA
8.20	**IP address**	AR_L1_IP
8.21	**Device identifier**	AR_L1_DISPOSITIVO
8.22	**Vehicle plate**	AR_L1_DOMINIO
8.23	**Vehicle and licence**	AR_L1_VEHICULO
8.24	**Property**	AR_L1_INMUEBLE

8.25	Customer, employee and contract numbers	AR_L1_CONTRATO
8.26	User and social media	AR_L1_USUARIO
8.27	Credentials	AR_L1_CREDENCIAL
8.28	Geolocation	AR_L1_GEOLOCALIZACION
8.29	Free text	AR_L1_TEXTO_LIBRE

PART 9 · QUASI-IDENTIFIERS

9.1	Birth date	AR_L2_FECHA_NACIMIENTO
9.2	Birth year and clase	AR_L2_ANIO_NACIMIENTO
9.3	Age	AR_L2_EDAD
9.4	Personal event dates	AR_L2_FECHA_EVENTO
9.5	Sex	AR_L2_SEXO
9.6	Localidad and municipality	AR_L2_LOCALIDAD
9.7	Partido and departamento	AR_L2_DEPARTAMENTO
9.8	INDEC geographic codes	AR_L2_CODIGO_GEOGRAFICO
9.9	Postal code	AR_L2_CODIGO_POSTAL
9.10	Neighbourhood	AR_L2_BARRIO
9.11	Nationality	AR_L2_NACIONALIDAD
9.12	Marital status	AR_L2_ESTADO_CIVIL
9.13	Occupation	AR_L2_OCUPACION
9.14	Employer	AR_L2_EMPLEADOR
9.15	Education	AR_L2_NIVEL_EDUCATIVO
9.16	School	AR_L2_ESTABLECIMIENTO_EDUCATIVO
9.17	Children and dependants	AR_L2_PERSONAS_A_CARGO

PART 10 · SENSITIVE DATA

10.1	Ethnic origin	AR_L3_ORIGEN_ETNICO
10.2	Indigenous people	AR_L3_PUEBLO_INDIGENA
10.3	Indigenous language	AR_L3_LENGUA_INDIGENA
10.4	Religion	AR_L3_RELIGION
10.5	Philosophical or moral convictions	AR_L3_CONVICCION_FILOSOFICA
10.6	Political opinions	AR_L3_OPINION_POLITICA
10.7	Party membership	AR_L3_AFILIACION_PARTIDARIA
10.8	Trade union membership	AR_L3_AFILIACION_SINDICAL
10.9	Biometric data	AR_L3_BIOMETRICO
10.10	Genetic data	AR_L3_GENETICO
10.11	Sexual orientation	AR_L3_ORIENTACION_SEXUAL
10.12	Sexual life	AR_L3_VIDA_SEXUAL

10.13	Gender identity	AR_L3_IDENTIDAD_GENERO
10.14	Victims of violence	AR_L3_VICTIMA

PART 11 · HEALTH DATA

11.1	Health identifiers	AR_SALUD_IDENTIFICADOR
11.2	Obra social and prepaid plan	AR_SALUD_COBERTURA
11.3	Diagnosis and ICD-10	AR_SALUD_DIAGNOSTICO
11.4	Procedures and services	AR_SALUD_PROCEDIMIENTO
11.5	Medicines	AR_SALUD_MEDICAMENTO
11.6	Clinical text	AR_SALUD_TEXTO_CLINICO
11.7	Test results	AR_SALUD_RESULTADO_ESTUDIO
11.8	HIV, hepatitis, tuberculosis and STIs	AR_SALUD_VIH
11.9	Blood group	AR_SALUD_GRUPO_SANGUINEO
11.10	Disability and CUD	AR_SALUD_DISCAPACIDAD
11.11	Occupational health	AR_SALUD_OCUPACIONAL
11.12	Sexual and reproductive health	AR_SALUD_REPRODUCTIVA
11.13	Mental health	AR_SALUD_MENTAL

PART 12 · FINANCIAL AND SOCIOECONOMIC DATA

12.1	Debtor situation	AR_FIN_SITUACION_CREDITICIA
12.2	Debt	AR_FIN_DEUDA
12.3	Income and pay	AR_FIN_INGRESOS
12.4	Assets	AR_FIN_PATRIMONIO
12.5	Pensions and benefits	AR_FIN_JUBILACION
12.6	Social benefits and programmes	AR_FIN_PROGRAMA_SOCIAL
12.7	Monotributo category	AR_FIN_MONOTRIBUTO
12.8	Housing tenure	AR_FIN_VIVIENDA

PART 13 · CRIMINAL RECORDS AND COURT FILES

13.1	Records	AR_PENAL_ANTECEDENTES
13.2	Court file	AR_PENAL_EXPEDIENTE
14	The CUIT check digit	
15	Where people live: localidades, partidos and postal code	
16	Limits	
17	Verification	
18	Sources	
A	Algorithms	
B	Files	

C	**Exclusion lists**
D	**Profile set and classifiers**

1

About this profile set

This profile set finds the personal data in an Argentine database and masks it, so that a non-production copy — for testing, development, training or analysis — no longer identifies anyone.

Masking names and DNIs alone is not enough: a birth date, a sex and a small town already point at one person. The set works in the layers where the risk is:

- **Direct identifiers** — DNI and the older libretas, CUIT, CUIL and CDI, the DNI tramit number, foreigner documents, passport, civil registry certificates, professional registration, names, company names, contact, address, CBU, CVU and alias, accounts and cards, devices, vehicle plates, property, free text.
- **Quasi-identifiers** — birth date, age, sex, localidad, partido or departamento and their INDEC codes, postal code, neighbourhood, nationality, marital status, occupation, employer, education.
- **Sensitive data** — those of article 2: racial and ethnic origin, political opinions, religious, philosophical or moral convictions, trade union membership and sexual life; the genetic and biometric data of Convention 108+; gender identity (Law 26.743) and being a victim of gender violence or trafficking.
- **Health data** — sensitive under article 2 and governed by article 8, in a group of their own: medical record and affiliation, obra social or prepaid plan, ICD-10, procedures, medicines, test results, HIV, blood group, disability, occupational, sexual and reproductive and mental health.
- **Financial data** — those of the credit information services of article 26: debtor situation in the BCRA Central de Deudores, debt, income, assets, pensions; and those that reveal a person's socioeconomic situation: ANSES benefits and social programmes, monotributo category, housing tenure.
- **Criminal records** — those that article 7.4 reserves to public authorities, and court file numbers.

In a Masking Engine, the set is a profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those rely on — and the lookup files they read. The appendices list each of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it on its own; an ambiguous one — `NOMBRE`, `DOCUMENTO`, `PARTIDO`, `DEPARTAMENTO` — needs the values to agree. A column with a meaningless name (`CAMPO1`, `OBS`) is still found when its values have a recognizable shape or vocabulary: a DNI with dots, a CUIT, a CBU, an address with floor and flat, a plate, a localidad.

Column names are recognized in Spanish, in the abbreviations of Argentine systems (`NRO_DOC`, `APYNOM`, `FEC_NAC`, `COD_LOCALIDAD`, `OBRA_SOCIAL`, `SITUACION_BCRA`) and in English.

> Before masking, inventory the binary columns (BLOB, images, PDF). Onboarding processes often keep photos of the front and back of the DNI and a selfie validated against RENAPER. Report those columns as residual risk.

2

Ley 25.326 in brief

Law 25.326 on the Protection of Personal Data — passed on 4 October 2000 and partially promulgated on 30 October — develops the habeas data of article 43 of the National Constitution, and Decree 1558/2001 implements it. The enforcement authority is the **Agencia de Acceso a la Información Pública (AAIP)**, which absorbed the former National Directorate for Personal Data Protection in 2017. The European Union has recognized Argentina as providing an adequate level of protection since 2003, and confirmed it in its 2024 review.

What matters for a copy of production data:

- **Personal data** is information of any kind about identified or identifiable natural persons **or legal persons** (art. 2). The law protects legal persons too: that is why the set masks company names and companies' CUITs.
- **Sensitive data** is data revealing racial and ethnic origin, political opinions, religious, philosophical or moral convictions, trade union membership, and information about health or sexual life (art. 2). Nobody can be forced to provide it, and **forming files that store information directly or indirectly revealing it is prohibited**, save for exceptions (art. 7). Health data also has the regime of article 8 and professional secrecy.
- **Criminal or misdemeanour records** may only be processed by the competent public authorities (art. 7.4).
- **Dissociation.** The law defines *disociación de datos* as any processing of personal data such that the information obtained cannot be associated with an identified or identifiable person (art. 2). With dissociated data, disclosure needs no consent (art. 11.3.e), and surveys and statistics must use it (art. 28).
- **Security and confidentiality.** The controller must adopt the technical and organizational measures that ensure the security and confidentiality of the data (art. 9), and everyone involved in processing is bound by professional secrecy, even after their relationship with the controller ends (art. 10). The security measures recommended by the AAIP (Resolution 47/2018, Annex I) say, in item H.1.1: *use masking or dissociation techniques for the information in development, test and QA environments*; whoever uses personal data in those environments must apply every other measure of the annex to them.
- **Credit information.** Only data relevant to assess solvency over the last five years may be kept, or two if the debtor paid off the debt (art. 26).
- **Sanctions.** Warning, suspension, fine, and closure or cancellation of the file (art. 31); AAIP Resolution 126/2024 classifies infringements as minor, serious and very serious and grades the sanctions from 1 June 2024. The law also added articles 117 bis and 157 bis to the Criminal Code: inserting false data into a personal data file and illegitimately accessing a data bank or disclosing information recorded in it are crimes (art. 32).

Convention 108. Argentina approved Council of Europe Convention 108 and its additional protocol (Law 27.483) and the protocol that modernizes it, Convention 108+ (Law 27.699, 2022). 108+ adds genetic data, biometric data that uniquely identify a person, and data on offences, criminal proceedings and convictions to the special categories, and requires serious data breaches to be notified to the authority. The protocol enters into force once 38 Parties ratify it: in May 2026 there were 34. This set treats those categories as sensitive regardless.

Reform under way. Congress has several bills to replace Law 25.326 — among them files 644-S-2025 and 1948-D-2025, and 3397-D-2026, introduced on 16 July 2026, which takes up the bill the Executive sent in 2023 and sets 16 as the age to consent to the processing of one's own data. None has been passed. This set follows the law in force.

3

Dissociation, pseudonymization and non-production copies

The consequence of dissociation follows from the definitions: data that can no longer be associated with an identified or identifiable person is not personal data. The law does not speak of pseudonymization, but the question is the same as under any regime: **can anyone associate the data with the person again?**

The algorithms of this set are deterministic for the Masking Engine's key: the same DNI masks the same way in every table, which keeps joins working. So, for whoever holds the key **and** production, the masked copy can be linked back — it is not dissociated in the sense of article 2 and is still personal data. For whoever holds only the copy, direct identifiers have been replaced and quasi-identifiers generalized.

- Keep the engine key out of reach of the users of the masked copy.

- Do not hand the copy to people who also access production without need.
- Review the quasi-identifiers the set does not know, and measure the re-identification risk before publishing or disclosing the copy as dissociated.

4

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Databases pad values: a CHAR column fills them with spaces up to its length, and a numeric code kept as text often comes with zeros on the left. The profiler tests values as they come, so every format pattern first removes the spaces around the value, patterns of digits also accept zeros on the left, lists of single words are looked up word by word, and lists of names made of several words (places, categories) are held as a single value-format pattern. A column whose name says nothing — `CAMPO1`, `FLD_07`, the short names of packaged systems — is found by its values alone wherever their format is distinctive: documents with a check digit, e-mail addresses, telephone numbers, cards, places, names.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

> Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

5

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

Where an algorithm that comes with the Masking Engine already does the job — CM Numeric for amounts, Credit Card, the blood group lookup — the set names it instead of creating one of its own. Those algorithms

appear in the trees by their `dlpx-core:` name; they are on every engine and are not listed in Appendix A.

Padding stays where it is: the spaces around a value are kept, and zeros on the left of a number are not masked — `0012345678` becomes `00` followed by what `12345678` becomes. A value kept in a zero-filled CHAR column still joins the same value kept as a number.

> The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

6

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	12	25	21	5
Extended	83	150	116	59

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- DNI and libretas — `AR_L1_DNI`
- CUIT, CUIL and CDI — `AR_L1_CUIT`
- Foreigner documents — `AR_L1_DOCUMENTO_EXTRANJERO`
- Passport — `AR_L1_PASAPORTE`
- Given name — `AR_L1_NOMBRE`
- Surname — `AR_L1_APELLIDO`
- Full name — `AR_L1_NOMBRE_COMPLETO`
- E-mail — `AR_L1_EMAIL`
- Phone — `AR_L1_TELEFONO`
- Address — `AR_L1_DIRECCION`
- Address complement — `AR_L1_DIRECCION_COMPLEMENTO`
- Birth date — `AR_L2_FECHA_NACIMIENTO`

> With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

7

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY	ALGORITHM
DIRECT IDENTIFIERS		
DNI and libretas ESSENTIAL `AR_L1_DNI`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`AR_DOCUMENTO`
CUIT, CUIL and CDI ESSENTIAL `AR_L1_CUIT`	COLUMN NAME · VALUE FORMAT	`AR_CUIT`
DNI tramit number `AR_L1_TRAMITE_DNI`	COLUMN NAME · VALUE FORMAT	`AR_CM_ALFANUM`
Foreigner documents ESSENTIAL `AR_L1_DOCUMENTO_EXTRANJERO`	COLUMN NAME	`AR_CM_ALFANUM`
Passport ESSENTIAL `AR_L1_PASAPORTE`	COLUMN NAME · VALUE FORMAT	`AR_CM_ALFANUM`
Civil registry `AR_L1_REGISTRO_CIVIL`	COLUMN NAME	`AR_CM_ALFANUM`
Professional registration `AR_L1_MATRICULA_PROFESIONAL`	COLUMN NAME	`AR_CM_ALFANUM`
Given name ESSENTIAL `AR_L1_NOMBRE`	COLUMN NAME · KNOWN VALUES	`AR_NOMBRES`
Surname ESSENTIAL `AR_L1_APELLIDO`	COLUMN NAME · KNOWN VALUES	`AR_APELLIDOS`
Full name ESSENTIAL `AR_L1_NOMBRE_COMPLETO`	COLUMN NAME · KNOWN VALUES	`AR_NOMBRE_COMPLETO`
Company name `AR_L1_RAZON_SOCIAL`	COLUMN NAME · VALUE FORMAT	`AR_EMPRESA`
E-mail ESSENTIAL `AR_L1_EMAIL`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`AR_EMAIL`
Phone ESSENTIAL `AR_L1_TELEFONO`	COLUMN NAME · VALUE FORMAT	`AR_TELEFONO`
Address ESSENTIAL `AR_L1_DIRECCION`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`AR_DIRECCION`
Address complement ESSENTIAL `AR_L1_DIRECCION_COMPLEMENTO`	COLUMN NAME	`AR_CM_ALFANUM`
CBU and CVU `AR_L1_CBU`	COLUMN NAME · VALUE FORMAT	`AR_CBU`
CBU alias `AR_L1_ALIAS_CBU`	COLUMN NAME · VALUE FORMAT	`AR_CM_ALFANUM`
Bank account `AR_L1_CUENTA_BANCARIA`	COLUMN NAME	`AR_CM_DIGITOS`
Payment card `AR_L1_TARJETA`	COLUMN NAME · VALUE FORMAT	`AR_TARJETA`

DOMAIN	FOUND BY	ALGORITHM
IP address `AR_L1_IP`	COLUMN NAME · VALUE FORMAT	`AR_IP`
Device identifier `AR_L1_DISPOSITIVO`	COLUMN NAME · VALUE FORMAT	`AR_CM_HEX`
Vehicle plate `AR_L1_DOMINIO`	COLUMN NAME · VALUE FORMAT	`AR_CM_DIGITOS_LETRAS`
Vehicle and licence `AR_L1_VEHICULO`	COLUMN NAME · VALUE FORMAT	`AR_CM_ALFANUM`
Property `AR_L1_INMUEBLE`	COLUMN NAME	`AR_CM_ALFANUM`
Customer, employee and contract numbers `AR_L1_CONTRATO`	COLUMN NAME	`AR_CM_ALFANUM`
User and social media `AR_L1_USUARIO`	COLUMN NAME	`AR_CM_ALFANUM`
Credentials `AR_L1_CREDENCIAL`	COLUMN NAME · VALUE FORMAT	`AR_REDACTAR`
Geolocation `AR_L1_GEOLOCALIZACION`	COLUMN NAME · VALUE FORMAT	`AR_COORDENADA`
Free text `AR_L1_TEXTO_LIBRE`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`AR_TEXTO_LIBRE`
QUASI-IDENTIFIERS		
Birth date ESSENTIAL `AR_L2_FECHA_NACIMIENTO`	COLUMN NAME · DATA TYPE	`AR_FECHA_NACIMIENTO`
Birth year and clase `AR_L2_ANIO_NACIMIENTO`	COLUMN NAME · DATA TYPE	`AR_ANIO`
Age `AR_L2_EDAD`	COLUMN NAME · DATA TYPE	`AR_EDAD`
Personal event dates `AR_L2_FECHA_EVENTO`	COLUMN NAME · DATA TYPE	`AR_FECHA_EVENTO`
Sex `AR_L2_SEXO`	COLUMN NAME · VALUE FORMAT	`AR_SEXO`
Localidad and municipality `AR_L2_LOCALIDAD`	COLUMN NAME · VALUE FORMAT	`AR_LOCALIDAD`
Partido and departamento `AR_L2_DEPARTAMENTO`	COLUMN NAME · VALUE FORMAT	`AR_DEPARTAMENTO`
INDEC geographic codes `AR_L2_CODIGO_GEOGRAFICO`	COLUMN NAME · VALUE FORMAT	`AR_CODIGO_GEOGRAFICO`
Postal code `AR_L2_CODIGO_POSTAL`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`AR_CODIGO_POSTAL`
Neighbourhood `AR_L2_BARRIO`	COLUMN NAME	`AR_BARRIO`
Nationality `AR_L2_NACIONALIDAD`	COLUMN NAME · KNOWN VALUES	`AR_NACIONALIDAD`
Marital status `AR_L2_ESTADO_CIVIL`	COLUMN NAME · VALUE FORMAT	`AR_ESTADO_CIVIL`

DOMAIN	FOUND BY	ALGORITHM
Occupation AR_L2_OCUPACION	COLUMN NAME	AR_OCUPACION_O_CODIGO
Employer AR_L2_EMPLEADOR	COLUMN NAME	AR_EMPLEADOR
Education AR_L2_NIVEL_EDUCATIVO	COLUMN NAME VALUE FORMAT	AR_NIVEL_EDUCATIVO
School AR_L2_ESTABLECIMIENTO_EDUCATIVO	COLUMN NAME	AR_ESTABLECIMIENTO_EDUCATIVO
Children and dependants AR_L2_PERSONAS_A_CARGO	COLUMN NAME DATA TYPE	AR_CONTEO_LIMITADO
SENSITIVE DATA		
Ethnic origin AR_L3_ORIGEN_ETNICO	COLUMN NAME VALUE FORMAT	AR_ORIGEN_ETNICO
Indigenous people AR_L3_PUEBLO_INDIGENA	COLUMN NAME VALUE FORMAT	AR_PUEBLO_INDIGENA
Indigenous language AR_L3_LENGUA_INDIGENA	COLUMN NAME VALUE FORMAT	AR_LENGUA
Religion AR_L3_RELIGION	COLUMN NAME VALUE FORMAT	AR_RELIGION
Philosophical or moral convictions AR_L3_CONVICCION_FILOSOFICA	COLUMN NAME	AR_CATEGORIA_SUPRIMIDA
Political opinions AR_L3_OPINION_POLITICA	COLUMN NAME VALUE FORMAT	AR_OPINION_POLITICA
Party membership AR_L3_AFILIACION_PARTIDARIA	COLUMN NAME VALUE FORMAT	AR_PARTIDO_POLITICO
Trade union membership AR_L3_AFILIACION_SINDICAL	COLUMN NAME VALUE FORMAT	AR_CATEGORIA_SUPRIMIDA
Biometric data AR_L3_BIOMETRICO	COLUMN NAME DATA TYPE	AR_REDACTAR
Genetic data AR_L3_GENETICO	COLUMN NAME VALUE FORMAT	AR_REDACTAR
Sexual orientation AR_L3_ORIENTACION_SEXUAL	COLUMN NAME VALUE FORMAT	AR_ORIENTACION_SEXUAL
Sexual life AR_L3_VIDA_SEXUAL	COLUMN NAME	AR_CATEGORIA_SUPRIMIDA
Gender identity AR_L3_IDENTIDAD_GENERO	COLUMN NAME VALUE FORMAT	AR_IDENTIDAD_GENERO
Victims of violence AR_L3_VICTIMA	COLUMN NAME	AR_CATEGORIA_SUPRIMIDA
HEALTH DATA		
Health identifiers AR_SALUD_IDENTIFICADOR	COLUMN NAME	AR_CM_ALFANUM
Obra social and prepaid plan AR_SALUD_COBERTURA	COLUMN NAME VALUE FORMAT	AR_COBERTURA_SALUD

DOMAIN	FOUND BY	ALGORITHM
Diagnosis and ICD-10 AR_SALUD_DIAGNOSTICO	COLUMN NAME VALUE FORMAT	AR_DIAGNOSTICO
Procedures and services AR_SALUD_PROCEDIMIENTO	COLUMN NAME	AR_PROCEDIMIENTO
Medicines AR_SALUD_MEDICAMENTO	COLUMN NAME VALUE FORMAT	AR_MEDICAMENTO
Clinical text AR_SALUD_TEXTO_CLINICO	COLUMN NAME DATA TYPE	AR_TEXTO_LIBRE
Test results AR_SALUD_RESULTADO_ESTUDIO	COLUMN NAME	AR_CM_ALFANUM
HIV, hepatitis, tuberculosis and STIs AR_SALUD_VIH	COLUMN NAME	AR_CATEGORIA_SUPRIMIDA
Blood group AR_SALUD_GRUPO_SANGUINEO	COLUMN NAME VALUE FORMAT	AR_GRUPO_SANGUINEO
Disability and CUD AR_SALUD_DISCAPACIDAD	COLUMN NAME VALUE FORMAT	AR_DISCAPACIDAD
Occupational health AR_SALUD_OCUPACIONAL	COLUMN NAME VALUE FORMAT	AR_SALUD_LABORAL
Sexual and reproductive health AR_SALUD_REPRODUCTIVA	COLUMN NAME	AR_CATEGORIA_SUPRIMIDA
Mental health AR_SALUD_MENTAL	COLUMN NAME	AR_CATEGORIA_SUPRIMIDA
FINANCIAL AND SOCIOECONOMIC DATA		
Debtor situation AR_FIN_SITUACION_CREDITICIA	COLUMN NAME VALUE FORMAT	AR_SITUACION_CREDITICIA
Debt AR_FIN_DEUDA	COLUMN NAME DATA TYPE	dlpx-core:CM Numeric
Income and pay AR_FIN_INGRESOS	COLUMN NAME DATA TYPE	dlpx-core:CM Numeric
Assets AR_FIN_PATRIMONIO	COLUMN NAME DATA TYPE	dlpx-core:CM Numeric
Pensions and benefits AR_FIN_JUBILACION	COLUMN NAME DATA TYPE	dlpx-core:CM Numeric
Social benefits and programmes AR_FIN_PROGRAMA_SOCIAL	COLUMN NAME VALUE FORMAT	AR_PROGRAMA_SOCIAL
Monotributo category AR_FIN_MONOTRIBUTO	COLUMN NAME DATA TYPE	AR_MONOTRIBUTO
Housing tenure AR_FIN_VIVIENDA	COLUMN NAME VALUE FORMAT	AR_TENENCIA_VIVIENDA
CRIMINAL RECORDS AND COURT FILES		
Records AR_PENAL_ANTECEDENTES	COLUMN NAME	AR_ANTECEDENTES
Court file AR_PENAL_EXPEDIENTE	COLUMN NAME VALUE FORMAT	AR_EXPEDIENTE

PART 8

Direct identifiers

Data that identifies a person on its own. The DNI is the key of almost every Argentine record, and the same number sits inside every worker's CUIL and every taxpayer's CUIT. It masks the same way everywhere, and CUIT, CUIL, CBU and CVU come out with a valid check digit, because applications validate it.

8.1 DNI and libretas

AR_L1_DNI

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The number of the National Identity Document issued by RENAPER — seven or eight digits, written with thousands dots, `28.456.789` —, the same for life, and that of the Libreta de Enrolamiento and Libreta Cívica that preceded it. The DNIs of foreign residents start at 90 million.

`NRO_DOCUMENTO` columns often mix DNIs, CUITs or CUILs and passports: each value is masked by its shape.

HOW IT IS FOUND

COLUMN NAME AR_L1_DNI — Path

90% `dni` `d_n_i` `n(o|ro|um|umero)_?(de_?)?(doc|documento|dni|le|lc)` `documento_?(nacional|de_?identidad|identidad)` `doc_?(identidad|nro|num|numero)` `nro_?doc` `numdoc` `nrodoc` `libreta_?(de_?)?(enrolamiento|c[ií]vica)` `(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|agente|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietario|inquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciudadano|votante|elector|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|jubilado|pensionado)_?(dni|doc|documento|nro_?doc)` `dni_?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|agente|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietario|inquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciudadano|votante|elector|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|jubilado|pensionado)` `c[eé]dula(_?(de_?)?identidad)?`

60% `documento` `doc` `tipo_?y_?n(ro|umero)_?(de_?)?doc`

DATA TYPE AR_L1_DNI — Type

Accepts text (length 6 or more) or number (length 6 or more); any other type rules the domain out.

VALUE FORMAT AR_L1_DNI — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{1,2}\.\d{3}\.\d{3})`	80%	
`0*(?:[1-9]\d{6,7})`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Digit by digit, keeping the length and the dots. The mapping is one-to-one: a DNI used as a key does not collide. A CUIT-shaped value is masked as a CUIT; one with letters, character by character.

`AR_DOCUMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM` .

> `AR_CUIT_CADENA` **STRING ALGORITHM CHAIN**
>
> Applies `AR_CUIT_AUX` → `AR_CUIT_AJUSTE` , in this order.
>
> > `AR_CUIT_AUX` **CHECK DIGIT**
> >
> > Masks the digits with `AR_CUIT_CUERPO` and recomputes a modulus 11 check digit with weights `4 6 8 10 12 14 4 6 8 10` from the right.
> >
> > > `AR_CUIT_CUERPO` **REGEX DECOMPOSE**
> > >
> > > Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_DIGITOS` .
> > >
> > > > `AR_CM_DIGITOS` **CHARACTER MAPPING**
> > > >
> > > > Maps each character to another of its group (1 groups), keeping length and format.
> >
> > `AR_CUIT_AJUSTE` **REGEX DECOMPOSE**
> >
> > Tries 7 patterns in order and gives each part of the value its own action; when none matches: `AR_CUIT_DV` .
> >
> > > `AR_CUIT_DV` **CHECK DIGIT**
> > >
> > > Masks the digits with `AR_IDENTIDAD` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 2 3 4 5` from the right.
> > >
> > > > `AR_IDENTIDAD` **REGEX DECOMPOSE**
> > > >
> > > > Matches one pattern and gives each part of the value its own action; when none matches: keep.
>
> `AR_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`28.456.789`	→	**`82.036.250`**
`5123456`	→	**`9064408`**
`20-28456789-1`	→	**`20-82036250-1`**

8.2 CUIT, CUIL and CDI

`AR_L1_CUIT`

ESSENTIAL **COLUMN NAME** **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

The tax identification key of ARCA (formerly AFIP), the labour identification key of ANSES and the identification key: eleven digits, `20-28456789-1` . The first two give the type — 20 man, 27 woman, 23 and 24 either, 30, 33 and 34 legal persons —; the eight in the middle are a natural person's DNI; the last is the check digit.

The digit uses weights 5, 4, 3, 2, 7, 6, 5, 4, 3 and 2 from the left, modulus 11: eleven minus the remainder, and 0 when the remainder is 0. When the remainder is 1 no digit is possible and the type changes: 20 and 27 become 23, 30 becomes 33, 23 becomes 24 and 33 becomes 34.

HOW IT IS FOUND

COLUMN NAME AR_L1_CUIT — Path

90% `cuit[a-z0-9_]*` `cuil[a-z0-9_]*` `cdi` `n(o|ro|um|umero)_?(de_?)?(cuit|cuil|cdi)` `clave_?[uú]nica_?(de_?)?(identificaci[oó]n_?)?(tributaria|laboral)` `(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|agente|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietario|inquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciudadano|votante|elector|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|jubilado|pensionado)_?(cuit|cuil)` `id_?(tributario|fiscal)` `identificaci[oó]n_?(tributaria|fiscal)` `nro_?afip` `tax_?id`

VALUE FORMAT AR_L1_CUIT — Regex

PATTERN	STRENGTH	NOTES
`0*(?:(20|2[347]|3[034])-\d{8}-\d)`	95%	
`0*(?:(20|2[347]|3[034])\d{9})`	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The type stays, the eight digits are mapped with the same algorithm as the DNI — a person's CUIL still holds their masked DNI — and the digit is recomputed; when the remainder comes out as 1, the type changes as ARCA would change it. Every masked CUIT is valid and the mapping is one-to-one. See *The CUIT check digit*.

`AR_CUIT` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_DIGITOS` .

> `AR_CUIT_CADENA` **STRING ALGORITHM CHAIN**
>
> Applies `AR_CUIT_AUX` → `AR_CUIT_AJUSTE` , in this order.
>
> > `AR_CUIT_AUX` **CHECK DIGIT**
> >
> > Masks the digits with `AR_CUIT_CUERPO` and recomputes a modulus 11 check digit with weights `4 6 8 10 12 14 4 6 8 10` from the right.
> >
> > > `AR_CUIT_CUERPO` **REGEX DECOMPOSE**
> > >
> > > Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_DIGITOS` .
> > >
> > > > `AR_CM_DIGITOS` **CHARACTER MAPPING**
> > > >
> > > > Maps each character to another of its group (1 groups), keeping length and format.
>
> > `AR_CUIT_AJUSTE` **REGEX DECOMPOSE**
> >
> > Tries 7 patterns in order and gives each part of the value its own action; when none matches: `AR_CUIT_DV` .
> >
> > > `AR_CUIT_DV` **CHECK DIGIT**
> > >
> > > Masks the digits with `AR_IDENTIDAD` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 2 3 4 5` from the right.
> > >
> > > > `AR_IDENTIDAD` **REGEX DECOMPOSE**
> > > >
> > > > Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
20-28456789-1	→	**20-82036250-1**
30500010912	→	**30518024651**

8.3 DNI tramit number

AR_L1_TRAMITE_DNI

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

The eleven-digit tramit number and the copy letter printed on the DNI. Online services ask for them to check that whoever signs up holds the card.

HOW IT IS FOUND

COLUMN NAME — AR_L1_TRAMITE_DNI — Path

85% `n(o|ro|um|umero)_?(de_?)?tr[aá]mite(_?dni)?` `tramite_?dni` `id_?tr[aá]mite` `ejemplar(_?dni)?` `n(ro|umero)_?ejemplar`

VALUE FORMAT — AR_L1_TRAMITE_DNI — Regex

PATTERN	STRENGTH	NOTES
`0*(?:00\d{9})`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
00123456789	→	**00110858568**

8.4 Foreigner documents

AR_L1_DOCUMENTO_EXTRANJERO

ESSENTIAL | COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The precarious residence and the residence certificate of the National Directorate of Migration, the residence file number, the foreign identity card and the visa number.

HOW IT IS FOUND

COLUMN NAME — AR_L1_DOCUMENTO_EXTRANJERO — Path

85% `residencia_?precaria` `certificado_?(de_?)?residencia` `radicaci[oó]n(_?(n(o|ro|um|umero)|expediente))?` `expediente_?migratorio` `documento_?extranjero` `doc_?extranjero` `c[eé]dula_?extranjera` `n(o|ro|um|umero)_?(visa|residencia)` `visa(_?(n(o|ro|um|umero)))?` `dnm_?(expediente|n(ro|umero))`

HOW IT IS MASKED

Character by character, keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456/2021	→	**773455/6889**

8.5 Passport

AR_L1_PASAPORTE

ESSENTIAL · COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

Argentine passport numbers — three letters and six digits, `AAA123456` — and foreign ones.

HOW IT IS FOUND

COLUMN NAME AR_L1_PASAPORTE — Path

90% `pasaporte[a-z0-9_]*` `n(o|ro|um|umero)_?pasaporte` `passport[a-z0-9_]*`

VALUE FORMAT AR_L1_PASAPORTE — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{3}\d{6}`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
AAA123456	→	**IE0166988**

8.6 Civil registry

AR_L1_REGISTRO_CIVIL

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

The number, volume and folio of birth, marriage, civil union and death certificates, and certificates of vital events.

HOW IT IS FOUND

COLUMN NAME AR_L1_REGISTRO_CIVIL — Path

85% `acta_?(de_?)?(nacimiento|matrimonio|defunci[oó]n|uni[oó]n_?convivencial)(_?(n(o|ro|um|umero)|tomo|folio))?` `n(o|ro|um|umero)_?acta` `partida_?(de_?)?(nacimiento|defunci[oó]n|matrimonio)` `certificado_?(de_?)?(nacimiento|defunci[oó]n|hecho_?vital)` `tomo_?(acta|partida)` `folio_?(acta|partida)`

HOW IT IS MASKED

Character by character, keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1234 Tomo 2A	→	**3049 Jova 3U**

8.7 Professional registration

AR_L1_MATRICULA_PROFESIONAL

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

The national (MN) or provincial (MP) registration of doctors, lawyers, accountants and other chartered professions, and the REFEPS register of health professionals. Professional associations publish their rolls with names.

HOW IT IS FOUND

COLUMN NAME AR_L1_MATRICULA_PROFESIONAL – Path

80% `matr[ií]cula(_?(profesional|nacional|provincial|m[eé]dica|colegio))?` `mat_?(prof|nac|prov)` `m_?n` `m_?p` `n(o|ro|um|umero)_?matr[ií]cula` `refeps` `registro_?profesional`

HOW IT IS MASKED

Character by character, keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
MN 123456	→	**KW 614053**

8.8 Given name

AR_L1_NOMBRE

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

The given name, one or more: `Soledad`, `Juan Carlos`, `María del Carmen`. Also the self-perceived name of Law 26.743.

HOW IT IS FOUND

COLUMN NAME AR_L1_NOMBRE – Path

85% `primer_?nombre` `segundo_?nombre` `nombres?_?(de_?)?pila` `pri(mer)?_?nom` `seg(undo)?_?nom` `nombre_?1` `nombre_?2` `first_?names?` `given_?names?` `fname` `middle_?names?` `nombres` *(except when followed by `completos?`, `y_?apellidos?`, `apellidos?`)*

50% `nombre` *(except when followed by list E1)* `nom` *(except when followed by list E2)* `name` *(except when followed by list E3)*

KNOWN VALUES AR_L1_NOMBRE – List

LIST	VALUES	STRENGTH	FIRST VALUES
`ar-detectar-nombres.txt`	876	70%	María, Maria, Juan, José, Jose, Carlos

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, replacing each name with one from the list — the most frequent of RENAPER's historical register of names. `de`, `del` and `la` stay in place. More than four words are masked character by character.

`AR_NOMBRES` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

> `AR_PALABRA_NOMBRE` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `AR_NOMBRE`.
>
> > `AR_NOMBRE` NAME
> >
> > Replaces the name with one of the 756 names in `ar-nombres.txt`.
>
> `AR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
María del Carmen	→	**Lucía del Reinaldo**
JUAN CARLOS	→	**VERÓNICA GISEL**

8.9 Surname

AR_L1_APELLIDO

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

The surname — one, or the father's and the mother's —, and the married name: `López de Rossi`.

HOW IT IS FOUND

> COLUMN NAME AR_L1_APELLIDO – Path
>
> 85% `apellidos?` `primer_?apellido` `segundo_?apellido` `apellido_?(1|2|paterno|materno|casada)` `ape_?(1|2)` `last_?names?` `surnames?` `family_?names?` `lname`

> KNOWN VALUES AR_L1_APELLIDO – List
>
LIST	VALUES	STRENGTH	FIRST VALUES
`ar-detectar-apellidos.txt`	477	70%	González, Gonzalez, Rodríguez, Rodriguez, Gómez, Gomez
>
> Values are split into words, and each word is looked up.
>
> A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, replacing each surname with one from the list — of Spanish, Italian, Guaraní, Andean and other origins —; particles stay in place.

`AR_APELLIDOS` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

> `AR_PALABRA_APELLIDO` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `AR_APELLIDO`.
>
> > `AR_APELLIDO` NAME
> >
> > Replaces the name with one of the 408 names in `ar-apellidos.txt`.
>
> `AR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
López de Rossi	→	**Guevara de Morelli**

8.10 Full name

AR_L1_NOMBRE_COMPLETO

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

Given names and surnames in one column: `Juan Carlos Fernández`, `FERNÁNDEZ, JUAN CARLOS`. Also those of the father, mother, guardian, spouse or partner, guarantor and personal reference.

A column named just `NOMBRE` may hold given names or full names: the values decide between the two domains.

HOW IT IS FOUND

COLUMN NAME AR_L1_NOMBRE_COMPLETO — Path

90%

`nombres?_?(completos?|y_?apellidos?|apellidos?)` `apellidos?_?(y_?)?nombres?` `ape_?nom` `apeynom` `apynom` `apenom` `ayn` `nombre_?(del_?|de_?la_?)?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|agente|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietario|inquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|concubino|conviviente|contacto|referencia|victima|denunciante|denunciado|imputado|procesado|testigo|medico|docente|socio|heredero|causante|donante|curador|jubilado|pensionado|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)` `(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|agente|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietario|inquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|concubino|conviviente|contacto|referencia|victima|denunciante|denunciado|imputado|procesado|testigo|medico|docente|socio|heredero|causante|donante|curador|jubilado|pensionado|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)_?(nombre|nom|apynom)` `nom_?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|agente|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietario|inquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|concubino|conviviente|contacto|referencia|victima|denunciante|denunciado|imputado|procesado|testigo|medico|docente|socio|heredero|causante|donante|curador|jubilado|pensionado|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)` `nombre_?(madre|padre|tutor|conyuge|contacto_?emergencia|referencia)` `full_?name` `person_?name`

60%

`madre` `padre` `tutor` `conyuge` `conviviente` `concubin[oa]` `representante_?legal` `apoderado` `garante` `fiador` `beneficiario` `heredero` `titular` `referencia_?(personal|familiar)`

50%

`nombre` *(except when followed by list E1)* `nom` *(except when followed by list E2)* `name` *(except when followed by list E3)*

KNOWN VALUES AR_L1_NOMBRE_COMPLETO — List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-nombres.txt	876	65%	María, Maria, Juan, José, Jose, Carlos
ar-detectar-apellidos.txt	477	65%	González, Gonzalez, Rodríguez, Rodriguez, Gómez, Gomez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

In Argentine order, with a single surname as the most common: two words are a given name and a surname; three, two given names and a surname; four, two and two; five, three and two. `APELLIDO, NOMBRES` with a comma, as in lists and electoral rolls, is recognized too. The result is a plausible name, never the original.

`AR_NOMBRE_COMPLETO` REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

> `AR_APELLIDOS` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.
>
> > `AR_PALABRA_APELLIDO` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `AR_APELLIDO`.
> >
> > > `AR_APELLIDO` NAME
> > >
> > > Replaces the name with one of the 408 names in `ar-apellidos.txt`.
> >
> > `AR_CM_ALFANUM` CHARACTER MAPPING
> >
> > Maps each character to another of its group (7 groups), keeping length and format.
>
> `AR_NOMBRES` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.
>
> > `AR_PALABRA_NOMBRE` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `AR_NOMBRE`.
> >
> > > `AR_NOMBRE` NAME
> > >
> > > Replaces the name with one of the 756 names in `ar-nombres.txt`.

EXAMPLES

VALUE		MASKED
Juan Carlos Fernández	→	**Verónica Gisel Moyano**
Soledad Gómez	→	**Catalino Fontana**
FERNÁNDEZ, JUAN CARLOS	→	**MOYANO, VERÓNICA GISEL**

8.11 Company name

AR_L1_RAZON_SOCIAL

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

The registered name or trade name of a company, supplier or shop. Law 25.326 also protects the data of legal persons, and in a one-person company or an SAS the company name is often the owner's name.

HOW IT IS FOUND

COLUMN NAME AR_L1_RAZON_SOCIAL — Path

85% `raz[oó]n_?social` `denominaci[oó]n_?social` `nombre_?(de_?)?fantas[ií]a` `nombre_?(empresa|comercio|proveedor|sociedad|persona_?jur[ií]dica|comercial)` `(empresa|proveedor|sociedad)_?(nombre|razon_?social)` `legal_?name` `company_?name` `business_?name` `trade_?name`

VALUE FORMAT AR_L1_RAZON_SOCIAL — Regex

PATTERN	STRENGTH	NOTES
`.*\b(S\.?\s?A\.?(\s?S\.?)?|S\.?\s?R\.?\s?L\.?|S\.?\s?C\.?\s?S\.?|S\.?\s?A\.?\s?U\.?|Ltda\.?|Coop(erativa)?\.?)\s*$`	80%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a fictitious company from the list.

`AR_EMPRESA` SECURE LOOKUP

Replaces the value with one of the 24 values in `ar-empresas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Arcos Dorados Argentina S.A.`	→	**`Construcciones Andinas S.R.L.`**

8.12 E-mail

AR_L1_EMAIL

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Personal and corporate e-mail addresses.

HOW IT IS FOUND

COLUMN NAME AR_L1_EMAIL — Path

85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `correo(_?electr[oó]nico)?[a-z0-9_]*` `dir_?correo` `direcci[oó]n_?(de_?)?correo` `direcci[oó]n_?electr[oó]nica`

DATA TYPE AR_L1_EMAIL — Type

Accepts text (length 5 or more); any other type rules the domain out.

VALUE FORMAT AR_L1_EMAIL — Regex

PATTERN	STRENGTH	NOTES
`[\p{L}\p{N}._%+'\-]+@[\p{L}\p{N}.\-]+\.[A-Za-z]{2,24}`	100%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

User and domain are mapped character by character, and the top-level domain — `.com`, `.com.ar` — becomes `.test`, reserved for testing: a masked address never delivers a message.

`AR_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

> `AR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`soledad.fernandez@hotmail.com.ar`	→	**`femuhus.wunfilmac@zugyiay.zen.test`**

8.13 Phone

AR_L1_TELEFONO

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Ten-digit national numbers: an area code of two to four digits — `11` Buenos Aires, `351` Córdoba, `2966` Río Gallegos — and the subscriber number. Mobiles add 9 after `+54`, or 15 after the area code when dialled within the country: `+54 9 11 4567-8901`, `(0351) 15-456-7890`. Also local numbers without an area code, `4567-8901`.

HOW IT IS FOUND

COLUMN NAME AR_L1_TELEFONO — Path

85% `tel` `tel[eé]fono[a-z0-9_]*` `tel_?(fijo|particular|laboral|m[oó]vil|celular|casa|oficina|contacto|alternativo)` `celular[a-z0-9_]*` `cel` `m[oó]vil` `whats_?app` `n(o|ro|um|umero)_?(tel|tel[eé]fono|celular|cel|contacto|movil)` `caracter[ií]stica_?tel` `fax` `phone[a-z0-9_]*` `mobile[a-z0-9_]*`

VALUE FORMAT AR_L1_TELEFONO — Regex

PATTERN	STRENGTH	NOTES
`0*(?:(\+?54[\s\-]?9?[\s\-]?)?\(?0?(11|[23]\d{2,3})\)?[\s\-]?(15[\s\-]?)?\d{3,4}[\s\-]?\d{4})`	90%	
`0*(?:(15[\s\-]?)?\d{4}-\d{4})`	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

`+54`, 9, the area code, 15 and the separators stay; the subscriber number — at least six digits — is mapped.

`AR_TELEFONO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_DIGITOS`.

> `AR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`+54 9 11 4567-8901`	→	**`+54 9 11 9910-5048`**
`(0351) 15-456-7890`	→	**`(0351) 15-047-9607`**

8.14 Address

AR_L1_DIRECCION

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

The address with street and height — `Av. Corrientes 1234 Piso 5 Dto. B` —, with a numbered street as in La Plata (`Calle 7 N° 1234`), or with block and lot in neighbourhoods and housing plans (`Mz. 12 Lote 5`), and routes with a kilometre.

HOW IT IS FOUND

COLUMN NAME AR_L1_DIRECCION — Path

80% `direcci[oó]n[a-z0-9_]*` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`, `correo`; except when followed by list E4)* `domicilio[a-z0-9_]*` *(except when followed by `fiscal_?electr[oó]nico`, `electr[oó]nico`)* `dom_?(real|legal|fiscal|particular|laboral|postal|cliente|paciente)` `calle(_?y_?(n(ro|umero)|altura))?` `residencia` `lugar_?(de_?)?residencia` `address[a-z0-9_]*` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`; except when followed by list E5)*

DATA TYPE AR_L1_DIRECCION — Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT AR_L1_DIRECCION — Regex

PATTERN	STRENGTH	NOTES
`(?i)(av|avda|avenida|bv|bvard|boulevard|diag|diagonal|pje|pasaje|calle)\.?\s+[a-záéíóúñü0-9.' ]{1,40}\s+(n[°º]\s*)?\d{1,5}.*`	80%	
`(?i)[a-záéíóúñü0-9.' ]{3,40}\s+(n[°º]\s*)?\d{1,5}\s*,?\s*(piso|p\.|pb|dto|depto|dpto|departamento)\b.*`	80%	
`(?i)[a-záéíóúñü.' ]{3,40}\s+\d{2,5}`	40%	
`(?i).*\b(mz|mza|manzana)\.?\s*\d+.*\b(lote|casa|lt)\.?\s*\d+.*`	70%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The whole line is replaced by a fictitious Argentine address of the same forms. Neighbourhood, localidad, partido and postal code in columns of their own are handled by their domains.

`AR_DIRECCION` SECURE LOOKUP

Replaces the value with one of the 4,000 values in `ar-direcciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Av. Corrientes 1234 Piso 5 Dto. B`	→	**25 de Mayo 2808**

8.15 Address complement

AR_L1_DIRECCION_COMPLEMENTO

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Floor, flat, functional unit, tower, block, lot, house, height and cross streets in columns of their own.

HOW IT IS FOUND

COLUMN NAME AR_L1_DIRECCION_COMPLEMENTO — Path

70% `piso` `dto` `depto` `dpto` `departamento_?(dom|domicilio|n(ro|umero))` `unidad_?funcional` `uf` `torre` `manzana` `mz` `mza` `lote` `casa_?(n(o|ro|um|umero))?` `altura` `n(ro|umero)_?(puerta|calle|domicilio)` `puerta` `entre_?calles?` `monoblock` `block` `oficina` `local`

HOW IT IS MASKED

Character by character, keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Piso 3 Dto. B	→	**Vara 0 Pqi. M**

8.16 CBU and CVU

AR_L1_CBU

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The Clave Bancaria Uniforme of a bank account and the Clave Virtual Uniforme of a payment account: 22 digits in two blocks. The first — bank and branch, or 000 and the payment service provider — carries a check digit with weights 7, 1, 3, 9, 7, 1, 3; the second, the account number, one with weights 3, 9, 7, 1 repeated.

HOW IT IS FOUND

COLUMN NAME AR_L1_CBU — Path

90% `cbu[a-z0-9_]*` `cvu[a-z0-9_]*` `clave_?bancaria_?uniforme` `clave_?virtual_?uniforme`

`n(o|ro|um|umero)_?(cbu|cvu)` `(cbu|cvu)_?(destino|origen|acreditaci[oó]n|cliente|proveedor)`

VALUE FORMAT AR_L1_CBU — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{8}[\s\-]?\d{14})`	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The first block stays — the bank identifies nobody —; the thirteen account digits are mapped and their check digit recomputed with Check Digit. Every masked CBU and CVU is valid and the mapping is one-to-one.

`AR_CBU` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_DIGITOS`.

> `AR_CBU_CUENTA` CHECK DIGIT
>
> Masks the digits with `AR_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 10 check digit with weights `3 1 7 9 3 1 7 9 3 1 7 9 3` from the right.
>
> > `AR_CM_DIGITOS_ANCHO_FIJO` CHARACTER MAPPING
> >
> > Maps each character to another of its group (1 groups), keeping length and format.
>
> `AR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
2850590940090418135201	→	**2850590917727168338551**

8.17 CBU alias

AR_L1_ALIAS_CBU

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

An account's alias, 6 to 20 characters with dots: `gato.mesa.lluvia`. Many holders build it from their name.

HOW IT IS FOUND

COLUMN NAME AR_L1_ALIAS_CBU — Path

90% `alias_?(cbu|cvu|bancario|cuenta|transferencia)` `(cbu|cvu)_?alias`

VALUE FORMAT AR_L1_ALIAS_CBU — Regex

PATTERN	STRENGTH	NOTES
`[a-z0-9\-]{2,12}\.[a-z0-9\-]{2,12}\.[a-z0-9\-]{2,12}`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the dots and the length.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`gato.mesa.lluvia`	→	**`xupa.vutu.jxajue`**

8.18 Bank account

AR_L1_CUENTA_BANCARIA

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Savings, current and salary account numbers, and digital wallets. The bank code is not personal data and has no domain.

HOW IT IS FOUND

COLUMN NAME AR_L1_CUENTA_BANCARIA — Path

85% `cuenta_?(bancaria|banco|corriente|sueldo|haberes|acreditaci[oó]n|destino|origen)` `caja_?(de_?)?ahorros?` `n(o|ro|um|umero)_?(de_?)?(cuenta|cta)` `nro_?cta` `num_?cta` `cta_?(cte|corriente|ahorro|bancaria|sueldo)` `tipo_?y_?n(o|ro|um|umero)_?cuenta` `iban` `account_?(no|num|number)` `bank_?account` `billetera(_?virtual)?`

HOW IT IS MASKED

Digits are mapped; separators stay.

`AR_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`123-456789/0`	→	**`171-367811/5`**

8.19 Payment card

AR_L1_TARJETA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers, recognized by the Luhn algorithm.

HOW IT IS FOUND

COLUMN NAME AR_L1_TARJETA – Path

85% `tarjeta(_?(cr[eé]dito|d[eé]bito|n(o|ro|um|umero)))?` `n(o|ro|um|umero)_?tarjeta` `pan` `card_?(no|num|number)` `credit_?card` `tc_?(numero|num|nro)` `td_?(numero|num|nro)`

VALUE FORMAT AR_L1_TARJETA – Regex

PATTERN	STRENGTH	NOTES
`0*(?:3[47]\d{13}|[1-9]\d{12,13}|[1-9]\d{15,18})`	90%	LUHN check digit; after removing `[\s\-]`

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Credit Card, which comes with the Masking Engine: another number that passes the Luhn check, keeping the first six digits — the issuer, not the holder. Only values shaped like a card reach it; the others pass unchanged instead of failing the row.

`AR_TARJETA` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

`dlpx-core:Credit Card` PAYMENT CARD

Comes with the Masking Engine and is used as it ships. Replaces the card number with another that passes the Luhn check, keeping the first six digits — the issuer, not the holder.

EXAMPLES

VALUE		MASKED
4509 9535 6623 3704	→	**4509 9599 2466 4464**

8.20 IP address

AR_L1_IP

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses from access logs and transactions.

HOW IT IS FOUND

COLUMN NAME AR_L1_IP – Path

85% `ip` `ip_?(address|addr|origen|destino|cliente|usuario|acceso|login|remota|publica)` `direcci[oó]n_?ip` `dir_?ip` `ipv[46]` `remote_?addr(ess)?` `client_?ip` `host_?ip`

VALUE FORMAT AR_L1_IP – Regex

PATTERN	STRENGTH	NOTES
`0*(?:((25[0-5]|2[0-4]\d|1?\d?\d)\.){3}(25[0-5]|2[0-4]\d|1?\d?\d))`	100%	
`0*(?:[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7})`	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet is mapped to 1–254; an IPv6 address is mapped keeping its hex characters.

`AR_IP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_HEX`.

`AR_OCTETO` NUMERIC MAPPING

Maps the number to another between 1 and 254.

`AR_CM_HEX` **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
181.47.132.21	→	**250.89.176.95**

8.21 Device identifier

AR_L1_DISPOSITIVO

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

IMEI, IMSI, ICCID, MAC address, advertising identifiers, cookies and sessions.

HOW IT IS FOUND

COLUMN NAME AR_L1_DISPOSITIVO — Path

80% `imei` `imsi` `iccid` `mac` `mac_?address` `direcci[oó]n_?mac` `device_?(id|uuid|serial)` `id_?(dispositivo|equipo|celular)` `serial_?(equipo|celular|dispositivo)` `advertising_?id` `idfa` `gaid` `cookie(_?id)?` `session_?id` `id_?sesi[oó]n`

VALUE FORMAT AR_L1_DISPOSITIVO — Regex

PATTERN	STRENGTH	NOTES
`0*(?:([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2})`	100%	
`0*(?:\d{15})`	80%	LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, with hex digits kept hex: a MAC stays a MAC.

`AR_CM_HEX` **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3c:22:fb:9a:10:e4	→	**5e:83:bb:3c:31:f9**

8.22 Vehicle plate

AR_L1_DOMINIO

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The plate (dominio): the Mercosur one, two letters, three digits and two letters for cars (`AE 123 KD`) and one letter, three digits and three letters for motorcycles (`A123BCD`); the one before 2016, three letters and three digits (`ABC 123`) or three digits and three letters for motorcycles. The Motor Vehicle Registry leads from the plate to the owner.

HOW IT IS FOUND

COLUMN NAME AR_L1_DOMINIO — Path

85% `dominio(_?(veh[ií]culo|automotor|auto|moto|rodado))?` `patente(_?(veh[ií]culo|auto|moto))?` `n(o|ro|um|umero)_?(dominio|patente)` `placa` `license_?plate` `plate(_?(no|number))?`

VALUE FORMAT AR_L1_DOMINIO — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{2}\s?\d{3}\s?[A-Z]{2}`	80%	
`[A-Z]{3}\s?\d{3}`	70%	
`[A-Z]\d{3}[A-Z]{3}`	70%	
`0*(?:\d{3}\s?[A-Z]{3})`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Letters to letters and digits to digits, position by position, with the spaces: the plate format stays.

`AR_CM_DIGITOS_LETRAS` CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
AE 123 KD	→	**YQ 812 TI**
ABC123	→	**AFJ775**

8.23 Vehicle and licence

AR_L1_VEHICULO

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The VIN or chassis number, the engine number, the vehicle identification card and the driving licence number.

HOW IT IS FOUND

COLUMN NAME AR_L1_VEHICULO — Path

85% `vin` `chasis` `n(o|ro|um|umero)_?(chasis|motor|cuadro|serie|vin)` `motor_?n(o|ro|um|umero)` `c[eé]dula_?(verde|azul|(de_?)?identificaci[oó]n_?(del_?)?automotor)` `t[ií]tulo_?(del_?)?automotor` `dnrpa` `registro_?automotor` `licencia_?(de_?)?conducir(_?(n(o|ro|um|umero)))?` `carnet_?(de_?)?conducir`

VALUE FORMAT AR_L1_VEHICULO — Regex

PATTERN	STRENGTH	NOTES
`[A-HJ-NPR-Z0-9]{17}`	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
8AJFB8CD1K1234567	→	**9IBKD9YL8Y3173278**

8.24 Property

AR_L1_INMUEBLE

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The property tax number (partida inmobiliaria), the cadastral nomenclature, the Real Estate Registry number and the municipal or revenue account. They lead to the home and the owner.

HOW IT IS FOUND

COLUMN NAME AR_L1_INMUEBLE — Path

80% `partida_?(inmobiliaria|municipal|arba|abl|catastral)?` `n(o|ro|um|umero)_?partida` `nomenclatura_?catastral` `nomenclatura` `catastro` `circunscripci[oó]n` `parcela` `matr[ií]cula_?(registral|inmueble|folio_?real)` `folio_?real` `n(o|ro|um|umero)_?(abl|inmobiliario|arba|rentas)` `cuenta_?(rentas|municipal|abl|inmobiliaria)` `padr[oó]n_?(inmobiliario|municipal)`

HOW IT IS MASKED

Character by character, keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123–456789	→	**110–858568**

8.25 Customer, employee and contract numbers

AR_L1_CONTRATO

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Contract, policy, operation, loan, member, subscriber and meter numbers, employee and student file numbers (legajo), and customer or affiliate codes.

HOW IT IS FOUND

COLUMN NAME AR_L1_CONTRATO — Path

70% `n(o|ro|um|umero)_?(contrato|p[oó]liza|operaci[oó]n|cr[eé]dito|pr[eé]stamo|solicitud|afiliado|afiliaci[oó]n|socio|suscriptor|cliente|medidor|servicio|suministro|legajo|expediente_?(administrativo|interno)|beneficio|carnet)` `contrato_?(n(o|ro|um|umero))` `legajo(_?(personal|empleado|agente|alumno))?` `c[oó]digo_?(cliente|socio|afiliado|empleado|alumno)` `id_?(cliente|socio|afiliado|empleado|agente|alumno)` `n(o|ro)_?socio` `n(ro|umero)_?libreta_?universitaria`

HOW IT IS MASKED

Character by character, keeping length and format. The mapping is deterministic, so joins keep working.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
LEG–12345	→	**FIW–25839**

8.26 User and social media

AR_L1_USUARIO

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Login, nickname and social media profiles.

HOW IT IS FOUND

> COLUMN NAME AR_L1_USUARIO – Path
>
> 70% `usuario` `user_?name` `username` `login` `apodo` `nick(_?name)?` `perfil_?(instagram|facebook|twitter|tiktok|linkedin|x)` `instagram` `facebook` `twitter` `tiktok` `linkedin` `red_?social` `handle`

HOW IT IS MASKED

Character by character, keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`@sole_fernandez`	→	**`@tixi_zilwatfaj`**

8.27 Credentials

AR_L1_CREDENCIAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Passwords and their hashes, the tax password (clave fiscal), PIN, security and OTP codes, CVV, tokens, API keys and secret answers.

HOW IT IS FOUND

> COLUMN NAME AR_L1_CREDENCIAL – Path
>
> 90% `contrase[nñ]a` `clave` *(except when followed by list E6)* `clave_?fiscal` `password` `passwd` `pwd` `pass` `hash_?(clave|contrasena|password)` `pin` `c[oó]digo_?(seguridad|verificaci[oó]n|acceso|otp)` `cvv` `cvc` `token(_?(acceso|refresh|api))?` `access_?token` `refresh_?token` `api_?key` `secreto` `secret` `otp` `pregunta_?secreta` `respuesta_?secreta`

VALUE FORMAT AR_L1_CREDENCIAL — Regex

PATTERN	STRENGTH	NOTES
`\$2[abxy]?\$\d{2}\$[./A-Za-z0-9]{53}`	95%	
`\$(1|5|6)\$(rounds=\d+\$)?[./A-Za-z0-9]{1,16}\$[./A-Za-z0-9]{22,86}`	95%	
`\$argon2(id|i|d)\$v=\d+\$m=\d+,t=\d+,p=\d+\$\S+`	95%	
`pbkdf2_sha(1|256|512)\$\d+\$\S+\$\S+`	95%	
`\{(SSHA|SHA|SSHA256|SSHA512|SMD5|MD5|CRYPT)\}\S+`	95%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Every character becomes `X`. A credential has no use in a test copy, and a hash masked character by character could still be attacked.

`AR_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
`Clave#2024`	→	XXXXXXXXXX

8.28 Geolocation

AR_L1_GEOLOCALIZACION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Latitude and longitud, together or in separate columns, from apps, visits, addresses and deliveries.

HOW IT IS FOUND

COLUMN NAME AR_L1_GEOLOCALIZACION — Path

85%	`lat` `latitud` `lon` `lng` `longitud` `coordenadas?` `coord_?[xy]` `geo_?(lat|lon|lng|loc|localizacion|posicion)` `georreferenciaci[oó]n` `geolocalizaci[oó]n` `gps(_?(ubicaci[oó]n|posici[oó]n|coordenadas))?` `ubicaci[oó]n_?gps`
50%	`long`

VALUE FORMAT AR_L1_GEOLOCALIZACION — Regex

PATTERN	STRENGTH	NOTES
`-(2[1-9]|[34]\d|5[0-5])\.\d{3,}\s*,\s*-(5[3-9]|6\d|7[0-3])\.\d{3,}`	90%	
`-(2[1-9]|[34]\d|5[0-5]|6\d|7[0-3])\.\d{4,}`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the other decimals are mapped: the place is generalized, not moved far.

`AR_COORDENADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `AR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
−34.603722,−58.381592	→	**−34.604476,−58.386711**

8.29 Free text

AR_L1_TEXTO_LIBRE

COLUMN NAME · DATA TYPE · VALUE FORMAT · FREE TEXT REDACTION

WHAT IT IS

Remarks, complaint descriptions, accounts of events and messages where anything gets written — DNI, CUIL, mobile and name included.

HOW IT IS FOUND

COLUMN NAME AR_L1_TEXTO_LIBRE – Path

60% `observaci[oó]n(es)?` `obs` `comentarios?` `notas?` `anotaci[oó]n(es)?` `descripci[oó]n_?` `(reclamo|queja|solicitud|caso|hechos|novedad|atenci[oó]n|incidente)` `detalle_?` `(reclamo|solicitud|caso|atenci[oó]n)` `hechos` `relato` `justificaci[oó]n` `mensaje` *(except when preceded by list E7; except when followed by list E8)* `texto(_?libre)?` `resumen_?(caso|atenci[oó]n)` `queja` `reclamo` `motivo_?(reclamo|contacto|llamado)` `remarks?` `comments?` `notes?` `free_?text` `memo`

DATA TYPE AR_L1_TEXTO_LIBRE – Type

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT AR_L1_TEXTO_LIBRE – Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{1,2}\.\d{3}\.\d{3})`	60%	anywhere in the value
`[\w.+\-]+@[\w\-]+\.[A-Za-z]{2,}`	70%	anywhere in the value
`0*(?:(20|2[347]|3[034])-\d{8}-\d)`	70%	anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

Free Text Redaction: DNIs with dots, CUITs and CUILs, 7- or 8-digit numbers, CBUs, e-mail, mobiles, cards, plates and IPs become `[DATO]`; given names and surnames from the list become `[NOMBRE]`. The rest of the text stays.

`AR_TEXTO_LIBRE` **FREE TEXT REDACTION**

Replaces the text matching 10 patterns with `[DATO]`, and the 2,670 terms of `ar-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
Cliente Fernández, DNI 28.456.789, correo s.fernandez@hotmail.com, cel 1145678901.	→	**Cliente [NOMBRE], DNI [DATO], correo [DATO], cel [DATO].**

PART 9

Quasi-identifiers

Data that identifies nobody on its own, but does in combination. The 2022 census counts 2,280 gobiernos locales — municipios, comunas, comisiones de fomento and municipales —; 1,952 have fewer than 20,000 inhabitants and more than a thousand fewer than 2,000. A birth date, a sex and one of those towns point at a handful of people. These attributes are generalized or shifted rather than replaced, and the data keeps its analytical value.

9.1 Birth date

AR_L2_FECHA_NACIMIENTO

ESSENTIAL · COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

The birth date, as a date, timestamp or text.

HOW IT IS FOUND

COLUMN NAME AR_L2_FECHA_NACIMIENTO — Path

90% `(fecha|fec|fch|f)_?(de_?)?nac(imiento)?` `fnac` `fechanac(imiento)?` `cumplea[ñn]os` `dob` `date_?of_?birth` `birth_?date` `birthday`

DATA TYPE AR_L2_FECHA_NACIMIENTO — Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 60 days either way. Ages and school years change for few people; the date stays plausible and the same birth shifts the same way in every table.

`AR_FECHA_NACIMIENTO` DATE SHIFT
Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	**1985-08-05T00:00**

9.2 Birth year and clase

AR_L2_ANIO_NACIMIENTO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The birth year in a column of its own, also called *clase*.

HOW IT IS FOUND

COLUMN NAME AR_L2_ANIO_NACIMIENTO — Path

90% `a[ñn]o_?(de_?)?nac(imiento)?` `anio_?nac(imiento)?` `year_?of_?birth` `birth_?year` `yob` `clase`

DATA TYPE AR_L2_ANIO_NACIMIENTO — Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit is mapped: `1985` becomes a year from 1980 to 1989.

`AR_ANIO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `AR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	**1980**

9.3 Age

AR_L2_EDAD

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

Age in years, also age group or five-year band.

HOW IT IS FOUND

> COLUMN NAME AR_L2_EDAD — Path
>
> 85% `edad(_?(actual|a[nñ]os|anios|paciente|afiliado|cliente|al_?(ingreso|diagn[oó]stico|fallecimiento)))?` `grupo_?etario` `rango_?(de_?)?edad` `quinquenio` `age(_?(years|group))?`

> DATA TYPE AR_L2_EDAD — Type
>
> Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The tens digit stays and the unit is mapped (37 becomes 30–39). A hundred or more becomes 90: rare ages identify.

`AR_EDAD` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `AR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	**35**
104	→	**90**

9.4 Personal event dates

AR_L2_FECHA_EVENTO

COLUMN NAME | DATA TYPE | DATE SHIFT

WHAT IT IS

Dates that say something about the person: death, marriage and civil union, hiring, leaving and dismissal, retirement, admission and discharge, diagnosis, childbirth, arrest, conviction, DNI issue, residence filing, leave.

HOW IT IS FOUND

COLUMN NAME AR_L2_FECHA_EVENTO — Path

80% `(fecha|fec|fch|f)_?(de_?)?(defunci[oó]n|fallecimiento|muerte|matrimonio|uni[oó]n_?convivencial|divorcio|ingreso|egreso|alta|baja|retiro|contrataci[oó]n|desvinculaci[oó]n|despido|jubilaci[oó]n|internaci[oó]n|diagn[oó]stico|atenci[oó]n|consulta|parto|detenci[oó]n|condena|emisi[oó]n(_?(dni|documento))?|vencimiento_?dni|radicaci[oó]n|vacunaci[oó]n|cirug[ií]a|accidente|licencia)` `fec_?(emision|defuncion|ingreso|egreso|baja)` `date_?of_?(death|marriage|hire|admission|discharge)`

DATA TYPE AR_L2_FECHA_EVENTO — Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 30 days either way.

`AR_FECHA_EVENTO` DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	**2021-03-05T00:00**

9.5 Sex

AR_L2_SEXO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Sex as the system records it: `F` / `M`, `Femenino` / `Masculino`, `Mujer` / `Varón` or the codes 1 and 2. Since Decree 476/2021 the DNI also admits `X`.

HOW IT IS FOUND

COLUMN NAME AR_L2_SEXO — Path

85% `sexo(_?(biol[oó]gico|al_?nacer|registral|dni|paciente|afiliado|cliente))?` `(tp|tipo|cod|cd|id)_?sexo` `g[eé]nero` *(except when followed by* ***identidad****,* ***autopercibido****)* `sex` `gender` *(except when followed by* ***identity****)*

VALUE FORMAT AR_L2_SEXO — Values

PATTERN	STRENGTH	NOTES
One of 8 known values, ignoring case — femenino, masculino, mujer, varón, hombre, no binario, …	80%	
One of 3 known values, ignoring case — f, m, x	60%	

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary: `F` stays `F` or `M`, `1` stays `1` or `2`. An `X` becomes `F` or `M`: a few thousand people hold it, and the mark would identify them.

`AR_SEXO` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_SEXO_FEMENINO_MASCULINO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-sexo-femenino-masculino.txt`, chosen by a keyed hash.

`AR_SEXO_MUJER_VARON` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-sexo-mujer-varon.txt`, chosen by a keyed hash.

`AR_SEXO_FEMALE_MALE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-sexo-female-male.txt`, chosen by a keyed hash.

`AR_SEXO_F_M` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-sexo-f-m.txt`, chosen by a keyed hash.

`AR_SEXO_1_2` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-sexo-1-2.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	**M**
X	→	**F**
Varón	→	**Mujer**

9.6 Localidad and municipality

AR_L2_LOCALIDAD

COLUMN NAME **VALUE FORMAT** **DATA CLEANSING**

WHAT IT IS

The localidad, city or municipality of residence, birth or document issue, by name — alone or with the province, `Tres Lagos - Santa Cruz`, `Tres Lagos (Santa Cruz)`.

HOW IT IS FOUND

COLUMN NAME AR_L2_LOCALIDAD — Path

85% `localidad(_?(residencia|nacimiento|domicilio|paciente|cliente|origen|emisi[oó]n))?` *(except when followed by* `cod`, `codigo`, `id`, `indec`*)* `loc(_?(res|nac|dom))?` `municipio(_?(residencia|domicilio))?` *(except when followed by* `cod`, `codigo`, `id`, `indec`*)* `ciudad(_?(residencia|nacimiento|domicilio|cliente|origen))?` `(nom|nombre|desc)_?(localidad|municipio|ciudad)` `lugar_?(de_?)?nacimiento` `pueblo_?(residencia|natal)` `city` `town`

VALUE FORMAT AR_L2_LOCALIDAD — Values

PATTERN	STRENGTH	NOTES
One of 3,883 known values, ignoring case — Adolfo Alsina, Adolfo Gonzales Chaves, Alberti, Almirante Brown, Avellaneda, Ayacucho, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A localidad of a gobierno local with fewer than 20,000 inhabitants — or outside any gobierno local — becomes the nearest gobierno local of the same province with at least 20,000; the others stay. See *Where people live*.

`AR_LOCALIDAD` **DATA CLEANSING**

Replaces each value found in `ar-localidades-generalizadas.txt` (55,794 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
El Chaltén	→	**El Calafate**
Tres Lagos — Santa Cruz	→	**El Calafate — Santa Cruz**
Rosario	→	**Rosario**

9.7 Partido and departamento

AR_L2_DEPARTAMENTO

COLUMN NAME · VALUE FORMAT · DATA CLEANSING

WHAT IT IS

The partido of Buenos Aires province, the departamento of the other provinces or the comuna of the City of Buenos Aires, by name.

HOW IT IS FOUND

COLUMN NAME AR_L2_DEPARTAMENTO — Path

85% `partido(_?(residencia|domicilio))?` *(except when followed by* `pol[ií]tico`, `afiliaci[oó]n`, `cod`, `codigo`, `id`*)* `departamento_?(geogr[aá]fico|residencia|provincial|indec)` `(nom|nombre|desc)_?(partido|departamento|depto|dpto)`

50% `departamento` *(except when followed by* `n(o|ro|umero)`, `piso`, `cod`, `codigo`, `id`*)* `depto` `dpto`

VALUE FORMAT AR_L2_DEPARTAMENTO — Values

PATTERN	STRENGTH	NOTES
One of 405 known values, ignoring case — Adolfo Alsina, Adolfo Gonzales Chaves, Alberti, Almirante Brown, Avellaneda, Ayacucho, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A partido or departamento with fewer than 20,000 inhabitants becomes the nearest one of the same province with at least 20,000: `Iruya` becomes `Orán`. The larger ones stay.

`AR_DEPARTAMENTO` DATA CLEANSING

Replaces each value found in `ar-departamentos-generalizados.txt` (3,254 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Iruya	→	**Orán**
La Matanza	→	**La Matanza**

9.8 INDEC geographic codes

AR_L2_CODIGO_GEOGRAFICO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

INDEC codes: five digits for a partido or departamento, six for a gobierno local and eight for a localidad censal. The first two are the province.

HOW IT IS FOUND

COLUMN NAME AR_L2_CODIGO_GEOGRAFICO — Path

85% `(cod|codigo|cd|id)_?(localidad|loc|municipio|gobierno_?local|departamento|depto|dpto|partido)` `(_?(indec|censal|res|residencia|nac|nacimiento))?` `(cod|codigo)_?indec` `indec_?` `(cod|codigo|localidad|departamento)` `codloc` `coddepto` `cod_?gl` `localidad_?censal_?(id|cod)`

VALUE FORMAT AR_L2_CODIGO_GEOGRAFICO — Regex

PATTERN	STRENGTH	NOTES
`0*(?:(0[26]|1[0480]|2[26]|3[0484]|4[26]|5[048]|6[26]|7[048]|8[26]|9[04])\d{3}(\d|\d{3})?)`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The same generalization as the names: a small place's code becomes the code of the place that replaces its name; a localidad's, the code of the main localidad of that gobierno local.

`AR_CODIGO_GEOGRAFICO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `AR_CODIGO_GEOGRAFICO_TABLA` DATA CLEANSING
>
> Replaces each value found in `ar-codigos-geograficos-generalizados.txt` (5,330 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
10014	→	**10112**
785035	→	**780070**

9.9 Postal code

AR_L2_CODIGO_POSTAL

COLUMN NAME DATA TYPE VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The Código Postal Argentino — a letter for the province, four digits and three letters that narrow it to a block face, `C1043AAZ` — and the older four-digit code, which names a town.

HOW IT IS FOUND

COLUMN NAME AR_L2_CODIGO_POSTAL — Path

85% `c[oó]digo_?postal` `cod_?postal` `codpostal` `cpa` `zip(_?code)?` `postal_?code` `cp`

DATA TYPE AR_L2_CODIGO_POSTAL — Type

Accepts text (length 4 to 8) or number (length up to 4); any other type rules the domain out.

VALUE FORMAT AR_L2_CODIGO_POSTAL — Regex

PATTERN	STRENGTH	NOTES
`[A-HJ-NP-Z]\d{4}[A-Z]{3}`	80%	
`[A-HJ-NP-Z]?[1-9]\d{3}`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The letter and the first two digits stay, the other two become zeros and the final letters `AAA` : `C1043AAZ` becomes `C1000AAA` and `1636` becomes `1600` .

`AR_CODIGO_POSTAL` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
C1043AAZ	→	**C1000AAA**
1636	→	**1600**

9.10 Neighbourhood

AR_L2_BARRIO

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The neighbourhood, the gated community or country club, the informal settlement registered in RENABAP and the rural paraje.

HOW IT IS FOUND

COLUMN NAME AR_L2_BARRIO – Path

80% `barrio(_?(residencia|domicilio|cliente|cerrado|privado))?` `(nom|nombre)_?barrio` `country club_?de_?campo` `villa_?(de_?)?emergencia` `asentamiento(_?informal)?` `renabap` `neighbou?rhood` `paraje`

HOW IT IS MASKED

Replaced by a common Argentine neighbourhood name, unrelated to the original.

`AR_BARRIO` SECURE LOOKUP

Replaces the value with one of the 124 values in `ar-barrios.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Barrio Parque Los Andes	→	**Barracas**

9.11 Nationality

AR_L2_NACIONALIDAD

COLUMN NAME KNOWN VALUES SECURE LOOKUP

WHAT IT IS

Nationality or country of birth. Paraguayans and Bolivians are the largest foreign communities.

HOW IT IS FOUND

COLUMN NAME AR_L2_NACIONALIDAD – Path

80% `nacionalidad` `pa[ií]s_?(de_?)?(nacimiento|origen|nacionalidad)` `ciudadan[ií]a` `nationality` `citizenship` `country_?of_?birth`

KNOWN VALUES AR_L2_NACIONALIDAD — List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-nacionalidades.txt	45	70%	Argentina, Paraguaya, Boliviana, Venezolana, Peruana, Chilena

Values are split into words, and each word is looked up.

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a nationality from the list: Argentine and the largest foreign communities.

AR_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 14 values in ar-nacionalidades.txt, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Senegalesa	→	China

9.12 Marital status

AR_L2_ESTADO_CIVIL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Single, married, civil union — from the 2015 Civil and Commercial Code —, separated, divorced or widowed, in words or as a code.

HOW IT IS FOUND

COLUMN NAME AR_L2_ESTADO_CIVIL — Path

85% estado_?civil est_?civil (cod|tipo|id)_?estado_?civil situaci[oó]n_?conyugal marital_?status civil_?status

VALUE FORMAT AR_L2_ESTADO_CIVIL — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — Soltero a, Casado a, Unión convivencial, Separado a de hecho, Divorciado a, Viudo a, ...	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another status from the list; a code stays a code.

AR_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_ESTADO_CIVIL_LISTA.

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-si-no.txt, chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-true-false.txt, chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt, chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-s-n.txt, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_ESTADO_CIVIL_CODIGO` SECURE LOOKUP

Replaces the value with one of the 6 values in `ar-estado-civil-codigos.txt`, chosen by a keyed hash.

`AR_ESTADO_CIVIL_LISTA` SECURE LOOKUP

Replaces the value with one of the 6 values in `ar-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Concubinato	→	**Unión convivencial**

9.13 Occupation

AR_L2_OCUPACION

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Occupation, profession, trade or position, in words or by the code of INDEC's National Classification of Occupations. A rare occupation in a small town identifies.

HOW IT IS FOUND

COLUMN NAME AR_L2_OCUPACION — Path

80% `ocupaci[oó]n` `profesi[oó]n` `oficio` `cno` `(cod|codigo)_?(ocupacion|cno|profesion)` `puesto_?(de_?)?trabajo` `categor[ií]a_?laboral` `cargo_?(actual|empleado|agente)` `occupation` `profession` `job_?title`

50% `cargo` `puesto`

HOW IT IS MASKED

Text is replaced by a common occupation; a code is mapped digit by digit.

`AR_OCUPACION_O_CODIGO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_OCUPACION`.

`AR_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`AR_OCUPACION` SECURE LOOKUP

Replaces the value with one of the 35 values in `ar-ocupaciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Gerente regional de operaciones	→	**Electricista**

9.14 Employer

AR_L2_EMPLEADOR

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The name of the company or public body where the person works.

HOW IT IS FOUND

COLUMN NAME AR_L2_EMPLEADOR — Path

90% `empleador(_?(nombre|raz[oó]n_?social|cuit))?` `(nombre|nom)_?(empleador|empresa_?donde_?trabaja)` `empresa_?(donde_?)?(trabaja|labora)` `lugar_?(de_?)?trabajo` `patr[oó]n` `employer(_?name)?` `workplace`

HOW IT IS MASKED

Replaced by a fictitious company.

`AR_EMPLEADOR` SECURE LOOKUP

Replaces the value with one of the 24 values in `ar-empleadores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Mercado Libre S.R.L.`	→	**`Autopartes del Oeste S.R.L.`**

9.15 Education

AR_L2_NIVEL_EDUCATIVO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The highest level attained — from no schooling to postgraduate, complete or incomplete —, in words or as a code.

HOW IT IS FOUND

COLUMN NAME AR_L2_NIVEL_EDUCATIVO — Path

80% `nivel_?(educativo|de_?instrucci[oó]n|de_?estudios|acad[eé]mico|alcanzado)` `m[aá]ximo_?nivel(_?educativo)?` `estudios_?(alcanzados|cursados)` `instrucci[oó]n` `escolaridad` `education(_?level)?`

VALUE FORMAT AR_L2_NIVEL_EDUCATIVO — Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Sin instrucción, Primario incompleto, Primario completo, Secundario incompleto, Secundario completo, Terciario no universitario incompleto, …	60%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another level from the list; a code stays a code.

`AR_NIVEL_EDUCATIVO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_NIVEL_EDUCATIVO_LISTA`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_NIVEL_EDUCATIVO_CODIGO` SECURE LOOKUP

Replaces the value with one of the 10 values in `ar-nivel-educativo-codigos.txt`, chosen by a keyed hash.

`AR_NIVEL_EDUCATIVO_LISTA` SECURE LOOKUP

Replaces the value with one of the 10 values in `ar-nivel-educativo.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Doctorado	→	**Universitario completo**

9.16 School

AR_L2_ESTABLECIMIENTO_EDUCATIVO

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The school, college, institute or university, by name or by its Clave Única de Establecimiento (CUE).

HOW IT IS FOUND

COLUMN NAME AR_L2_ESTABLECIMIENTO_EDUCATIVO — Path

75% `escuela(_?(nombre|egreso))?` `colegio(_?(nombre|egreso))?` `(nombre|nom)_?(escuela|colegio|establecimiento_?educativo|universidad|instituto)` `establecimiento_?educativo` `instituci[oó]n_?educativa` `universidad` `cue(_?anexo)?` `school(_?name)?` `university`

HOW IT IS MASKED

Replaced by a fictitious school.

`AR_ESTABLECIMIENTO_EDUCATIVO` SECURE LOOKUP

Replaces the value with one of the 12 values in `ar-establecimientos-educativos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Colegio Nacional de Buenos Aires	→	**Instituto Superior de Formación Docente N° 21**

9.17 Children and dependants

AR_L2_PERSONAS_A_CARGO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

Number of children, dependants or household members.

HOW IT IS FOUND

COLUMN NAME AR_L2_PERSONAS_A_CARGO — Path

80% `personas_?a_?cargo` `familiares_?a_?cargo` `n(o|ro|um|umero)_?(de_?)?(hijos|dependientes|personas_?a_?cargo)` `cant(idad)?_?(hijos|dependientes|personas_?hogar|convivientes)` `hijos` `cargas_?de_?familia` `dependientes` `personas_?(en_?el_?)?hogar` `tama[nñ]o_?hogar` `number_?of_?children` `dependents`

DATA TYPE AR_L2_PERSONAS_A_CARGO — Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Values from 0 to 5 stay; above 5 they become 5. Very large families are rare, and a rare count identifies.

`AR_CONTEO_LIMITADO` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	**5**

PART 10

Sensitive data

The categories of article 2 other than health — which has its own group: racial and ethnic origin, political opinions, religious, philosophical or moral convictions, trade union membership and sexual life. The set adds the special categories of Convention 108+ — genetic and biometric data —, sexual orientation, **gender identity**, whose registry correction is confidential (Law 26.743, art. 9), and being a **victim** of gender violence (Law 26.485), trafficking (Law 26.364) or sexual crimes, whose identity the law orders protected. Categorical columns keep their shape: a Y/N flag stays a flag, a code is replaced by another code and any other value by one from the list of its category. Where the values share no vocabulary, they are suppressed to `Sin información`.

10.1 Ethnic origin

AR_L3_ORIGEN_ETNICO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Self-recognition as indigenous or descendant of indigenous peoples and as Afro-descendant, the two questions of the 2022 census, in words, as a code or as a flag.

HOW IT IS FOUND

COLUMN NAME — AR_L3_ORIGEN_ETNICO — Path

95%

`etnia` `origen_?([eé]tnico|racial)` `grupo_?[eé]tnico` `pertenencia_?[eé]tnica` `autorreconocimiento(_?[eé]tnico)?` `auto_?reconocimiento` `(cod|codigo|tipo|id)_?(etnia|origen_?etnico)` `raza` `afrodescendiente` `afroargentin[oa]` `ind[ií]gena` `originario` `ethnicity` `race`

VALUE FORMAT — AR_L3_ORIGEN_ETNICO — Values

PATTERN	STRENGTH	NOTES
One of 16 known values, ignoring case — Indígena o descendiente de pueblos indígenas u originarios, Afrodescendiente, Ninguno, Prefiere no responder, indígena, originario, …	90%	
One of 10 known values, ignoring case — s, n, sí, no, 1, 2, …	30%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a category from the list.

`AR_ORIGEN_ETNICO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_ORIGEN_ETNICO_LISTA`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_ORIGEN_ETNICO_LISTA` SECURE LOOKUP

Replaces the value with one of the 4 values in `ar-origen-etnico.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Afroargentino	→	**Ninguno**
S	→	**S**

10.2 Indigenous people

AR_L3_PUEBLO_INDIGENA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The indigenous people — Mapuche, Guaraní, Diaguita, Kolla, Qom, Wichí, among the dozens recorded by the 2022 census — and the community with legal personality registered in RENACI.

HOW IT IS FOUND

COLUMN NAME AR_L3_PUEBLO_INDIGENA — Path

90% `pueblo(_?(ind[ií]gena|originario))?` `(cod|codigo|nombre|nom)_?pueblo` `comunidad_?(ind[ií]gena|originaria|aborigen)` `personer[ií]a_?jur[ií]dica_?(comunidad|ind[ií]gena)` `renaci` `inai` `aborigen` `indigenous_?people`

VALUE FORMAT AR_L3_PUEBLO_INDIGENA — Values

PATTERN	STRENGTH	NOTES
One of 66 known values, ignoring case — Mapuche, Guaraní, Diaguita, Kolla, Qom, Wichí, …	90%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by one of the most numerous peoples; a code stays a code.

`AR_PUEBLO_INDIGENA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_PUEBLO_INDIGENA_LISTA`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_PUEBLO_INDIGENA_LISTA` SECURE LOOKUP

Replaces the value with one of the 20 values in `ar-pueblos-indigenas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Selk'nam`	→	**Tonokoté**

10.3 Indigenous language

AR_L3_LENGUA_INDIGENA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The indigenous language the person speaks or understands — Guaraní, Quechua, Mapuzungun, Qom, Wichí. It reveals the people of origin.

HOW IT IS FOUND

COLUMN NAME AR_L3_LENGUA_INDIGENA — Path

90% `lengua_?(ind[ií]gena|originaria|materna|nativa)` `idioma_?(ind[ií]gena|originario|materno|nativo)` `habla_?(lengua|idioma)_?(ind[ií]gena|originari[oa])` `mother_?tongue` `native_?language`

VALUE FORMAT AR_L3_LENGUA_INDIGENA — Values

PATTERN	STRENGTH	NOTES
One of 26 known values, ignoring case — Español, Guaraní, Quechua, Mapuzungun, Qom toba, Wichí, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a language from the list; a flag stays a flag.

`AR_LENGUA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_LENGUA_LISTA`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_LENGUA_LISTA` SECURE LOOKUP

Replaces the value with one of the 12 values in `ar-lenguas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Tapiete	→	**Pilagá**

10.4 Religion

AR_L3_RELIGION

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The religion, church or faith the person belongs to.

HOW IT IS FOUND

COLUMN NAME AR_L3_RELIGION — Path

95% `religi[oó]n` `creencia_?religiosa` `convicci[oó]n_?religiosa` `credo` `confesi[oó]n_?religiosa` `culto` `iglesia(_?(a_?la_?que_?pertenece|nombre))?` `denominaci[oó]n_?religiosa` `(cod|codigo|tipo)_?religion` `religion` `church`

VALUE FORMAT AR_L3_RELIGION — Values

PATTERN	STRENGTH	NOTES
One of 29 known values, ignoring case — Católica, Evangélica, Pentecostal, Testigo de Jehová, Iglesia de Jesucristo de los Santos de los Últimos Días, Judía, …	90%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a religion from the list.

`AR_RELIGION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_RELIGION_LISTA`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_RELIGION_LISTA` SECURE LOOKUP

Replaces the value with one of the 11 values in `ar-religiones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Ortodoxa	→	**Pentecostal**

10.5 Philosophical or moral convictions

AR_L3_CONVICCION_FILOSOFICA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The philosophical or moral convictions that article 2 names apart from religious ones: conscientious objection — invoked, for instance, against terminating a pregnancy or a transfusion — and membership of lodges.

HOW IT IS FOUND

COLUMN NAME AR_L3_CONVICCION_FILOSOFICA – Path

90% `convicci[oó]n(es)?_?(filos[oó]ficas?|morales?|personales?)` `creencias?_?(filos[oó]ficas?|morales?|personales?)` `objeci[oó]n_?(de_?)?conciencia` `objetor_?(de_?)?conciencia` `masoner[ií]a` `logia` `beliefs?` `philosophical_?beliefs?`

HOW IT IS MASKED

The values share no vocabulary: they are suppressed to `Sin información`. Flags and codes keep their shape.

`AR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `ar-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Se niega a transfusiones	→	**Sin información**

10.6 Political opinions

AR_L3_OPINION_POLITICA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Political orientation and ideology, sympathy and voting intention, from surveys and records.

HOW IT IS FOUND

COLUMN NAME AR_L3_OPINION_POLITICA — Path

90% `opini[oó]n_?pol[ií]tica` `orientaci[oó]n_?pol[ií]tica` `tendencia_?pol[ií]tica` `ideolog[ií]a(_?pol[ií]tica)?` `preferencia_?(pol[ií]tica|partidaria|electoral)` `intenci[oó]n_?(de_?)?voto` `simpat[ií]a_?pol[ií]tica` `political_?(opinion|orientation|view)` `voting_?intention`

VALUE FORMAT AR_L3_OPINION_POLITICA — Values

PATTERN	STRENGTH	NOTES
One of 22 known values, ignoring case — Izquierda, Centroizquierda, Centro, Centroderecha, Derecha, Independiente, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a position from the list — left to right, independent.

`AR_OPINION_POLITICA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_OPINION_POLITICA_LISTA` .

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt` , chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_OPINION_POLITICA_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `ar-opiniones-politicas.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Libertario	→	**Centro**

10.7 Party membership

AR_L3_AFILIACION_PARTIDARIA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The political party the person is a member or activist of. A column named just `PARTIDO` may also be the partido of a Buenos Aires address: the values decide.

HOW IT IS FOUND

COLUMN NAME — AR_L3_AFILIACION_PARTIDARIA – Path

95%	`partido_?pol[ií]tico(_?(afiliaci[oó]n|nombre))?` `afiliaci[oó]n_?(pol[ií]tica|partidaria|partido)` `afiliado_?partido` `militancia(_?pol[ií]tica)?` `militante(cod|codigo|nombre|nom)_?partido_?pol` `agrupaci[oó]n_?pol[ií]tica` `fuerza_?pol[ií]tica` `political_?party` `party_?membership`
50%	`partido`

VALUE FORMAT — AR_L3_AFILIACION_PARTIDARIA – Values

PATTERN	STRENGTH	NOTES
One of 47 known values, ignoring case — Partido Justicialista, Unión Cívica Radical, Propuesta Republicana PRO, La Libertad Avanza, Coalición Cívica ARI, Frente Renovador, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another party from the list of national parties; a flag stays a flag.

`AR_PARTIDO_POLITICO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_PARTIDO_POLITICO_LISTA`.

> `AR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `AR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.
>
> `AR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `AR_PARTIDO_POLITICO_LISTA` SECURE LOOKUP

Replaces the value with one of the 29 values in `ar-partidos-politicos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Movimiento Popular Neuquino	→	**Izquierda Socialista**

10.8 Trade union membership

AR_L3_AFILIACION_SINDICAL

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The union, membership, the union dues deducted on the payslip, the union delegate and union protection — UOM, Comercio, UOCRA, Camioneros, ATE, UPCN.

HOW IT IS FOUND

COLUMN NAME AR_L3_AFILIACION_SINDICAL — Path

95% `sindicato(_?(nombre|afiliado|afiliaci[oó]n|codigo))?` `gremio(_?(nombre|afiliado|codigo))?` `sindicalizado` `afiliado_?(sindicato|gremio)` `afiliaci[oó]n_?(sindical|gremial)` `cuota_?(sindical|gremial)` `aporte_?(sindical|gremial)` `descuento_?(sindical|gremial)` `asociaci[oó]n_?sindical` `delegado_?(gremial|sindical)` `comisi[oó]n_?interna` `tutela_?sindical` `convenio_?colectivo_?(de_?trabajo)?` `cct` `trade_?union` `union_?member(ship)?`

VALUE FORMAT AR_L3_AFILIACION_SINDICAL — Values

PATTERN	STRENGTH	NOTES
One of 33 known values, ignoring case — CGT, CTA, CTA-T, CTA-A, UOM, UOCRA, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`AR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_SUPRIMIR` SECURE LOOKUP

> Replaces the value with one of the 1 values in `ar-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
UOM	→	**Sin información**
S	→	**S**

10.9 Biometric data

AR_L3_BIOMETRICO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

Fingerprint and face templates — validation against RENAPER is routine in banks and digital wallets —, iris, voice and digitized signature.

HOW IT IS FOUND

> **COLUMN NAME** AR_L3_BIOMETRICO — Path
>
> **90%** `biometr[ií]a[a-z_]*` `biom[eé]trico[a-z_]*` `huella(_?dactilar)?(_?(template|plantilla|imagen|hash))?` `huellas` `dactilar` `template_?(facial|huella|biometrico)` `plantilla_?(facial|biom[eé]trica)` `rostro_?(hash|template)` `reconocimiento_?facial` `validaci[oó]n_?(facial|biom[eé]trica|renaper)` `firma_?(biom[eé]trica|digitalizada|ol[oó]grafa)` `iris` `voz_?(biom[eé]trica|template)` `fingerprints?` `face_?(template|hash|encoding)` `biometric[a-z_]*`

> **DATA TYPE** AR_L3_BIOMETRICO — Type
>
> Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character becomes `X`. A masked template authenticates nobody.

`AR_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	**XXXXXXXXXXXX**

10.10 Genetic data

AR_L3_GENETICO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Results of genetic, DNA and parentage tests, genetic profiles, mutations, karyotype and newborn screening. Convention 108+ counts them among the special categories.

HOW IT IS FOUND

COLUMN NAME AR_L3_GENETICO — Path

90% `adn` `dna` `gen[eé]tic[oa]s?` `datos?_?gen[eé]ticos?` `genoma` `genotip[a-z_]*` `prueba_?` `(gen[eé]tica|de_?adn|de_?filiaci[oó]n|de_?paternidad)` `perfil_?gen[eé]tico` `mutaci[oó]n` `brca[12]?` `cariotipo` `pesquisa_?neonatal` `bndg` `genetic[a-z_]*`

VALUE FORMAT AR_L3_GENETICO — Regex

PATTERN	STRENGTH	NOTES
`[ACGTUN]{24,}`	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Every character becomes `X`.

`AR_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
BRCA1 positivo	→	XXXXXXXXXXXXXX

10.11 Sexual orientation

AR_L3_ORIENTACION_SEXUAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Self-declared sexual orientation, in health and diversity records. It is information about sexual life.

HOW IT IS FOUND

COLUMN NAME AR_L3_ORIENTACION_SEXUAL — Path

95% `orientaci[oó]n_?sexual` `orient_?sexual` `(cod|codigo|tipo)_?orientacion_?sexual` `preferencia_?sexual` `sexual_?orientation`

VALUE FORMAT AR_L3_ORIENTACION_SEXUAL — Values

PATTERN	STRENGTH	NOTES
One of 14 known values, ignoring case — Heterosexual, Gay, Lesbiana, Bisexual, Pansexual, Asexual, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a category from the list.

`AR_ORIENTACION_SEXUAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_ORIENTACION_SEXUAL_LISTA`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_ORIENTACION_SEXUAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 8 values in `ar-orientaciones-sexuales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Homosexual	→	**Pansexual**

10.12 Sexual life

AR_L3_VIDA_SEXUAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Sexual activity and behaviour, number of partners, age at first intercourse.

HOW IT IS FOUND

COLUMN NAME AR_L3_VIDA_SEXUAL — Path

90% `vida_?sexual` `actividad_?sexual` `conducta_?sexual` `pr[aá]cticas?_?sexuales?` `parejas?_?sexuales?` `n(o|ro|um|umero)_?parejas` `sexualmente_?activ[oa]` `inicio_?(de_?)?(las_?)?relaciones_?sexuales` `relaciones_?sexuales` `sex(ual)?_?life` `sexual_?(activity|behavio(u)?r|partners)`

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`AR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `ar-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Activa	→	**Sin información**

10.13 Gender identity

AR_L3_IDENTIDAD_GENERO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Self-perceived gender identity, the registry correction and the change of registered sex under Law 26.743, which forbids publicizing the correction and the original birth record without the person's authorization (art. 9). The self-perceived name falls under the given name domain.

HOW IT IS FOUND

COLUMN NAME AR_L3_IDENTIDAD_GENERO — Path

95% `identidad_?(de_?)?g[eé]nero` `(cod|codigo|tipo)_?identidad_?genero` `g[eé]nero_?(autopercibido|identitario)` `rectificaci[oó]n_?registral` `cambio_?(de_?)?(g[eé]nero|sexo_?registral)` `ley_?26743` `transg[eé]nero` `persona_?trans` `travesti` `pronombres?` `gender_?identity`

VALUE FORMAT AR_L3_IDENTIDAD_GENERO — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — Mujer cis, Varón cis, Mujer trans travesti, Varón trans masculinidad trans, No binario, Otra, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a category from the list.

`AR_IDENTIDAD_GENERO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_IDENTIDAD_GENERO_LISTA`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_IDENTIDAD_GENERO_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `ar-identidades-genero.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Transgénero	→	**Varón trans / masculinidad trans**

10.14 Victims of violence

AR_L3_VICTIMA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Being a victim of gender, family or sexual violence, of trafficking or exploitation, the type of violence, protection and restraining orders, the panic button, and the identity restitution of children of the disappeared. Revealing it exposes the person to their aggressor.

HOW IT IS FOUND

COLUMN NAME AR_L3_VICTIMA – Path

90% `v[ií]ctima(_?(de_?)?(violencia(_?(de_?)?g[eé]nero|_?familiar|_?dom[eé]stica)?|trata|abuso(_?sexual)?|delito(_?sexual)?|explotaci[oó]n))?` `violencia_?(de_?)?g[eé]nero` `violencia_?(familiar|dom[eé]stica|sexual)` `tipo_?(de_?)?violencia` `medida_?(de_?)?(protecci[oó]n|restricci[oó]n|exclusi[oó]n)` `perimetral` `restricci[oó]n_?(de_?)?acercamiento` `bot[oó]n_?antip[aá]nico` `linea_?144` `trata(_?(de_?)?personas)?` `restituci[oó]n_?(de_?)?identidad` `conadi` `hij[oa]_?(de_?)?desaparecid[oa]s?`

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`AR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

> Maps each character to another of its group (7 groups), keeping length and format.
>
> `AR_SUPRIMIR` **SECURE LOOKUP**
>
> Replaces the value with one of the 1 values in `ar-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Violencia física y psicológica	→	**Sin información**
S	→	**S**

PART 11

Health data

Information about health is sensitive (art. 2), and the medical record is confidential (Law 26.529 on Patients' Rights). Several laws add their own secrecy: the law on HIV, viral hepatitis, tuberculosis and STIs (Law 27.675), the law on voluntary termination of pregnancy (Law 27.610) and the mental health law (Law 26.657). The group covers what clinics, obras sociales, prepaid plans, laboratories, occupational risk insurers (ART) and occupational medicine keep.

11.1 Health identifiers

AR_SALUD_IDENTIFICADOR

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Medical record numbers, affiliate numbers of the obra social, prepaid plan or PAMI, membership card, admission, authorization, order and prescription numbers.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_IDENTIFICADOR — Path

85% `n(o|ro|um|umero)_?(historia(_?cl[ií]nica)?|hc|afiliado(_?(obra_?social|os|pami|prepaga))?|beneficio_?pami|credencial|internaci[oó]n|autorizaci[oó]n|orden|receta|prescripci[oó]n)` `historia_?cl[ií]nica` `hc_?(n(o|ro|um|umero))?` `afiliado_?(obra_?social|os|pami|prepaga)` `n(ro|umero)_?(os|pami)` `credencial_?(obra_?social|prepaga|pami)` `c[oó]digo_?(paciente|afiliado)` `id_?paciente` `hce`

55% `afiliado` `internaci[oó]n` `autorizaci[oó]n` `episodio`

HOW IT IS MASKED

Character by character, keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
15012345678/00	→	**11560473467/18**

11.2 Obra social and prepaid plan

AR_SALUD_COBERTURA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The obra social, the prepaid plan, PAMI or Incluir Salud, by name or by the code of the National Register of Obras Sociales (RNOS). Most obras sociales are run by unions: the code tells the trade and the union. Incluir Salud covers people who receive a non-contributory pension.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_COBERTURA — Path

85% `obra_?social(_?(nombre|codigo|afiliado))?` `os` `(cod|codigo|nombre|nom)_?(obra_?social|os|prepaga|rnos)` `rnos` `prepaga` `medicina_?prepaga` `cobertura(_?(m[eé]dica|de_?salud|social))?` `financiador` `plan_?(de_?)?salud` `pami` `incluir_?salud` `profe`

VALUE FORMAT AR_SALUD_COBERTURA — Values

PATTERN	STRENGTH	NOTES
One of 38 known values, ignoring case — PAMI, IOMA, OSDE, Swiss Medical, Galeno, Medifé, …	80%	

A value that matches none counts 40% against the domain.

VALUE FORMAT AR_SALUD_COBERTURA — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d-\d{4}-\d)`	70%	

A value that matches none does not count against the domain.

HOW IT IS MASKED

A name is replaced by another coverage from the list; an RNOS code is mapped digit by digit; a flag stays a flag.

`AR_COBERTURA_SALUD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_OBRA_SOCIAL`.

> `AR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `AR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.
>
> `AR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `AR_OBRA_SOCIAL` SECURE LOOKUP
>
> Replaces the value with one of the 19 values in `ar-obras-sociales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
OSUOMRA	→	**IOSFA**
1-0020-4	→	**7-9242-5**

11.3 Diagnosis and ICD-10

AR_SALUD_DIAGNOSTICO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Diagnoses in words or by ICD-10 code, with a dot (`F33.1`) or without (`F331`); causes of death, of leave and of admission, history and allergies.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_DIAGNOSTICO — Path

85% `diagn[oó]stico[a-z_]*` `dx(_?(principal|secundario|ingreso|egreso)[0-9]?)?` `cie_?10` `cie(_?(10|11|principal))?` `(cod|codigo)_?(diagnostico|dx|cie)` `impresi[oó]n_?diagn[oó]stica` `enfermedad(es)?[a-z_]*` `patolog[ií]a` `comorbilidad(es)?` `antecedentes?_?(m[eé]dicos|patol[oó]gicos|familiares|personales|cl[ií]nicos)` `causa_?(de_?)?` `(muerte|defunci[oó]n|licencia|internaci[oó]n|consulta)` `motivo_?(de_?)?` `(consulta|licencia|internaci[oó]n)` `alergias?` `diagnos(is|es)` `icd_?(10|11)?`

VALUE FORMAT AR_SALUD_DIAGNOSTICO — Regex

PATTERN	STRENGTH	NOTES
`[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d|X)?`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code becomes another common code in the same format, and text a common diagnosis: an HIV or mental disorder diagnosis does not survive as a category.

`AR_DIAGNOSTICO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `AR_DIAGNOSTICO_TEXTO` .

`AR_CIE10_DECIMAL` SECURE LOOKUP

Replaces the value with one of the 33 values in `ar-cie10-decimal.txt` , chosen by a keyed hash.

`AR_CIE10` SECURE LOOKUP

Replaces the value with one of the 37 values in `ar-cie10.txt` , chosen by a keyed hash.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt` , chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.

`AR_DIAGNOSTICO_TEXTO` SECURE LOOKUP

Replaces the value with one of the 30 values in `ar-diagnosticos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F33.1	→	K21.9
B24X	→	R51

11.4 Procedures and services

AR_SALUD_PROCEDIMIENTO

COLUMN NAME · REGEX DECOMPOSE

WHAT IT IS

Procedures, tests and surgeries, in words or by the code of the National or a provincial nomenclator. A viral load or a pregnancy termination reveals the diagnosis.

HOW IT IS FOUND

> COLUMN NAME AR_SALUD_PROCEDIMIENTO – Path
>
> 85% `nomenclador` `(cod|codigo)_?(nomenclador|prestaci[oó]n|pr[aá]ctica|procedimiento)` `procedimiento(_?(m[eé]dico|quir[uú]rgico|realizado|autorizado))?` `pr[aá]ctica(_?(m[eé]dica|realizada|autorizada))?` `prestaci[oó]n_?(m[eé]dica|realizada|autorizada)` `estudio_?(solicitado|realizado)` `cirug[ií]a(_?realizada)?` `intervenci[oó]n_?quir[uú]rgica` `medical_?procedure`

HOW IT IS MASKED

A code is mapped digit by digit; text is replaced by a common procedure.

`AR_PROCEDIMIENTO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_PROCEDIMIENTO_TEXTO`.

> `AR_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `AR_PROCEDIMIENTO_TEXTO` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `ar-procedimientos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
420101	→	349877

11.5 Medicines

AR_SALUD_MEDICAMENTO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Prescribed or dispensed medicines, by brand, active ingredient or pack code (troquel). An antiretroviral, an antipsychotic or misoprostol reveals a diagnosis.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_MEDICAMENTO — Path

85% `medicamentos?(_?(recetado|prescrito|dispensado|nombre|uso))?` `f[aá]rmacos?` `droga(_?(gen[eé]rica|principal))?` `monodroga` `principio_?activo` `troquel` `gtin` `(cod|codigo)_?(medicamento|troquel|alfabeta|kairos)` `receta(_?(m[eé]dica|electr[oó]nica|archivada))?` `prescripci[oó]n_?(medicamento)?` `posolog[ií]a` `tratamiento_?farmacol[oó]gico` `medications?` `drugs?_?prescribed`

VALUE FORMAT AR_SALUD_MEDICAMENTO — Values

PATTERN	STRENGTH	NOTES
One of 52 known values, ignoring case — Paracetamol, Ibuprofeno, Diclofenac, Dipirona, Metformina, Glibenclamida, …	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a common medicine from the list; a flag stays a flag.

`AR_MEDICAMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_MEDICAMENTO_LISTA`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_MEDICAMENTO_LISTA` SECURE LOOKUP

Replaces the value with one of the 24 values in `ar-medicamentos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Sertralina 50 mg`	→	**`Ibuprofeno`**

11.6 Clinical text

AR_SALUD_TEXTO_CLINICO

COLUMN NAME DATA TYPE FREE TEXT REDACTION

WHAT IT IS

History, present illness, progress notes, physical examination, orders, discharge summaries and reports.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_TEXTO_CLINICO — Path

85% `anamnesis` `evoluci[oó]n(_?(m[eé]dica|cl[ií]nica|enfermer[ií]a))?` `enfermedad_?actual` `examen_?f[ií]sico` `plan_?(de_?)?(tratamiento|manejo)` `indicaciones_?m[eé]dicas` `conducta(_?m[eé]dica)?` `epicrisis` `resumen_?(de_?)?(alta|internaci[oó]n|atenci[oó]n)` `nota_?(m[eé]dica|de_?enfermer[ií]a|cl[ií]nica)` `notas?_?(m[eé]dicas|cl[ií]nicas)` `triage(_?texto)?` `informe_?(anatomopatol[oó]gico|patolog[ií]a|radiol[oó]gico|m[eé]dico)` `clinical_?notes?` `discharge_?summary`

DATA TYPE AR_SALUD_TEXTO_CLINICO — Type

Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

The same Free Text Redaction as free text: documents, contacts and names from the list are redacted. The clinical content stays — if it must not be in the copy, suppress the column.

`AR_TEXTO_LIBRE` FREE TEXT REDACTION

Replaces the text matching 10 patterns with `[DATO]`, and the 2,670 terms of `ar-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
`Paciente Fernández, DNI 28.456.789, consulta por cefalea.`	→	**`Paciente [NOMBRE], DNI [DATO], consulta por cefalea.`**

11.7 Test results

AR_SALUD_RESULTADO_ESTUDIO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Laboratory and test results — glucose, Pap smear, pregnancy, toxicology, blood alcohol —, also as numeric values.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_RESULTADO_ESTUDIO — Path

80% `resultado_?(del_?)?(estudio|an[aá]lisis|laboratorio|pcr|serolog[ií]a|biopsia|glucemia|papanicolaou|pap|hisopado|covid)` `(estudio|an[aá]lisis)_?(resultado|laboratorio)` `glucemia` `hemoglobina_?glicosilada` `hba1c` `colesterol` `imc` `presi[oó]n_?arterial` `tensi[oó]n_?arterial` `test_?(de_?)?embarazo` `toxicol[oó]gico` `alcoholemia` `test_?(de_?)?drogas` `lab_?results?` `test_?results?`

50% `resultado`

HOW IT IS MASKED

Character by character, keeping the format: a number stays a number.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Alterado	→	**Urjecipi**

11.8 HIV, hepatitis, tuberculosis and STIs

AR_SALUD_VIH

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Serological status, viral load and antiretroviral treatment, viral hepatitis, tuberculosis and sexually transmitted infections. Law 27.675 guarantees confidentiality and forbids discrimination on these grounds.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_VIH – Path

90% `vih(_?(estado|resultado|test|diagn[oó]stico|positivo))?` `hiv` `sida` `aids` `serolog[ií]a_?(vih|hiv)` `estado_?serol[oó]gico` `carga_?viral` `cd4` `tarv` `antirretroviral(es)?` `hepatitis_?(b|c|viral)` `hbsag` `tuberculosis` `tbc` `its` `ets` `infecci[oó]n(es)?_?(de_?)?transmisi[oó]n_?sexual` `s[ií]filis` `vdrl`

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`AR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR`.

> `AR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `AR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.
>
> `AR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `AR_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `ar-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Reactivo	→	**Sin información**
S	→	**S**

11.9 Blood group

AR_SALUD_GRUPO_SANGUINEO

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

Blood group and Rh factor.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_GRUPO_SANGUINEO — Path

90% `grupo_?sangu[ií]neo` `grupo_?y_?factor` `tipo_?(de_?)?sangre` `rh` `factor_?rh` `gs_?rh` `grupo_?rh` `abo(_?rh)?` `blood_?(type|group)`

VALUE FORMAT AR_SALUD_GRUPO_SANGUINEO — Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — A, A-, B, B-, AB, AB-, …	90%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another group from the list.

`AR_GRUPO_SANGUINEO` SECURE LOOKUP

Replaces the value with one of the 8 values in `ar-grupos-sanguineos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`0+`	→	**A−**

11.10 Disability and CUD

AR_SALUD_DISCAPACIDAD

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Disability status, its type — motor, hearing, visual, visceral, intellectual, mental — and the number of the Certificado Único de Discapacidad (Law 22.431), and the non-contributory disability pension.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_DISCAPACIDAD — Path

90% `discapacidad[a-z_]*` `(tipo|cod|codigo|categoria)_?discapacidad` `persona_?con_?discapacidad` `pcd` `cud` `certificado_?([uú]nico_?)?(de_?)?discapacidad` `n(o|ro|um|umero)_?cud` `condici[oó]n_?(de_?)?discapacidad` `pensi[oó]n_?(no_?contributiva_?)?(por_?)?invalidez` `movilidad_?reducida` `disabilit(y|ies)`

VALUE FORMAT AR_SALUD_DISCAPACIDAD — Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Motora, Auditiva, Visual, Visceral, Intelectual, Mental, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag, a CUD number is mapped character by character and any other value is replaced by a type from the list.

`AR_DISCAPACIDAD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_DISCAPACIDAD_TIPO` .

> `AR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `AR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `AR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `AR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `AR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `AR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `AR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.
>
> `AR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `AR_DISCAPACIDAD_TIPO` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `ar-discapacidades.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno del espectro autista	→	**Ninguna**

11.11 Occupational health

AR_SALUD_OCUPACIONAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The result of the pre-employment and periodic exams, pre-existing conditions, work and commuting accidents and occupational diseases reported to the ART (Law 24.557), sick leave and absenteeism, and the incapacity set by the medical boards.

HOW IT IS FOUND

> COLUMN NAME AR_SALUD_OCUPACIONAL — Path
>
> 85% `aptitud_?(laboral|m[eé]dica|psicof[ií]sica)` `examen_?(preocupacional|peri[oó]dico|de_?egreso|psicot[eé]cnico)` `preocupacional` `accidente_?(de_?)?trabajo` `accidente_?in_?itinere` `enfermedad_?profesional` `siniestro_?art` `denuncia_?art` `art_?(siniestro|denuncia)` `licencia_?(m[eé]dica|por_?enfermedad|psiqui[aá]trica|por_?maternidad)` `d[ií]as_?(de_?)?licencia` `ausentismo` `carpeta_?m[eé]dica` `incapacidad(_?(laboral|laborativa|porcentaje))?` `comisi[oó]n_?m[eé]dica` `preexistencias?`

VALUE FORMAT AR_SALUD_OCUPACIONAL — Values

PATTERN	STRENGTH	NOTES
One of 5 known values, ignoring case — apto, no apto, apto con preexistencias, pendiente, apto condicional	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A result is replaced by another from the list — fit, unfit —; a flag stays a flag; the diagnosis falls under its domain.

`AR_SALUD_LABORAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SALUD_LABORAL_LISTA`.

> `AR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `AR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.
>
> `AR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `AR_SALUD_LABORAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 4 values in `ar-aptitud-laboral.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`No apto temporariamente`	→	**Pendiente**

11.12 Sexual and reproductive health

AR_SALUD_REPRODUCTIVA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy, last menstrual period, prenatal care, childbirth, voluntary or legal termination of pregnancy (Law 27.610), contraceptive method, fertility and assisted reproduction.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_REPRODUCTIVA — Path

90% `embarazo` `embarazada` `gestante` `gestaci[oó]n` `edad_?gestacional` `semanas_?(de_?)?gestaci[oó]n` `fum` `fecha_?[uú]ltima_?menstruaci[oó]n` `control_?prenatal` `prenatal` `parto(_?tipo)?` `ces[aá]rea` `aborto` `ive` `ile` `interrupci[oó]n_?(voluntaria|legal)(_?del_?embarazo)?` `m[eé]todo_?anticonceptivo` `anticoncepci[oó]n` `anticonceptivo` `salud_?(sexual|reproductiva)` `fertilidad` `fertilizaci[oó]n_?asistida` `reproducci[oó]n_?asistida` `pregnan(t|cy)` `contracepti(on|ve)`

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Sin información`.

`AR_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR`.

> `AR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `AR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.
>
> `AR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `AR_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `ar-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
12 semanas de gestación	→	**Sin información**
S	→	**S**

11.13 Mental health

AR_SALUD_MENTAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Mental disorders, psychiatric or psychological care, involuntary admission, suicide attempts and problematic substance use (Law 26.657).

HOW IT IS FOUND

COLUMN NAME AR_SALUD_MENTAL — Path

90% `salud_?mental` `trastorno[a-z_]*` `psiqui[aá]tri[a-z_]*` `psicol[oó]gi[a-z_]*` `depresi[oó]n` `ansiedad` `suicid[a-z_]*` `intento_?(de_?)?suicidio` `autolesi[oó]n` `internaci[oó]n_?involuntaria` `consumo_?(problem[aá]tico|de_?(sustancias|alcohol|drogas))` `adicci[oó]n(es)?` `sedronar` `alcoholismo` `tabaquismo` `mental_?health`

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Sin información`.

`AR_CATEGORIA_SUPRIMIDA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR`.

> `AR_BANDERA` **REGEX DECOMPOSE**
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `AR_BANDERA_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_YES_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.
>
> `AR_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `AR_SUPRIMIR` **SECURE LOOKUP**
>
> Replaces the value with one of the 1 values in `ar-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno bipolar	→	**Sin información**

PART 12

Financial and socioeconomic data

Credit information has its own rules in article 26, and a person's situation in the **BCRA Central de Deudores** — from 1, normal, to 6, unrecoverable by technical disposition — is among the data with the heaviest consequences. ANSES benefits and the monotributo category tell how much someone earns, whether they have children or a disability. Categories are replaced within their own notation and band; amounts are mapped to a plausible range with no relation to the real value.

12.1 Debtor situation

AR_FIN_SITUACION_CREDITICIA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The debtor's situation in the BCRA Central de Deudores — 1 normal, 2 low risk or special monitoring, 3 medium risk or with problems, 4 high risk, 5 unrecoverable, 6 unrecoverable by technical disposition —, bounced cheques, days in arrears, legal collection and credit bureau scores.

HOW IT IS FOUND

COLUMN NAME AR_FIN_SITUACION_CREDITICIA — Path

90% `situaci[oó]n_?(crediticia|bcra|deudor|central_?deudores)` `sit_?(bcra|deudor|cred)` `central_?(de_?)?deudores` `cendeu` `clasificaci[oó]n_?(del_?)?deudor` `score(_?(crediticio|veraz|nosis|equifax|interno))?` `puntaje_?crediticio` `veraz` `nosis` `equifax` `informe_?comercial` `cheques_?rechazados` `d[ií]as_?(de_?)?(atraso|mora)` `morosidad` `moroso` `en_?mora` `gesti[oó]n_?judicial` `credit_?score` `credit_?rating`

VALUE FORMAT AR_FIN_SITUACION_CREDITICIA — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — normal, riesgo bajo, riesgo medio, riesgo alto, irrecuperable, con seguimiento especial, …	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The situation is replaced within its band — 1–2, 3–4, 5–6 —, so the analysis by band keeps its shape; `Situación 4` stays written the same way. A score gets other digits of the same length; a status in words, another from the list; a flag stays a flag.

`AR_SITUACION_CREDITICIA` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `AR_ESTADO_CREDITO`.

`AR_SITUACION_1_2` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-situacion-1-2.txt`, chosen by a keyed hash.

`AR_SITUACION_3_4` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-situacion-3-4.txt`, chosen by a keyed hash.

`AR_SITUACION_5_6` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-situacion-5-6.txt`, chosen by a keyed hash.

`AR_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_ESTADO_CREDITO` SECURE LOOKUP

Replaces the value with one of the 10 values in `ar-estados-credito.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
4	→	**3**
Situación 6	→	**Situación 5**
Irrecuperable	→	**Con problemas**

12.2 Debt

AR_FIN_DEUDA

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Outstanding balances, loan and instalment amounts, amounts in arrears and spending limits.

HOW IT IS FOUND

COLUMN NAME AR_FIN_DEUDA – Path

85% `saldo_?(deudor|deuda|cr[eé]dito|capital|pr[eé]stamo|adeudado|tarjeta)` `monto_?(de_?la_?)?(deuda|cuota|cr[eé]dito|pr[eé]stamo|adeudado|en_?mora|financiado)` `importe_?(deuda|cuota|adeudado|mora)` `deuda(_?total)?` `l[ií]mite_?(de_?)?(cr[eé]dito|compra|tarjeta)` `cuota_?mensual` `loan_?(amount|balance)` `outstanding_?balance` `debt`

DATA TYPE AR_FIN_DEUDA – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
1850000	→	**4398071**

12.3 Income and pay

AR_FIN_INGRESOS

COLUMN NAME · DATA TYPE · NUMERIC MAPPING

WHAT IT IS

Basic, gross or net salary, taxable pay, earnings, household income and annual turnover.

HOW IT IS FOUND

COLUMN NAME AR_FIN_INGRESOS – Path

85% `salario(_?(b[aá]sico|mensual|bruto|neto))?` `sueldo(_?(b[aá]sico|bruto|neto|mensual))?` `remuneraci[oó]n(_?(bruta|neta|total|imponible))?` `haberes?` `ingresos?(_?(mensuales?|totales?|familiares?|declarados?|netos?|brutos?))?` `neto_?a_?cobrar` `bruto_?mensual` `facturaci[oó]n_?anual` `salary` `income` `wages?`

DATA TYPE AR_FIN_INGRESOS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
1450000	→	**4140719**

12.4 Assets

AR_FIN_PATRIMONIO

COLUMN NAME · DATA TYPE · NUMERIC MAPPING

WHAT IT IS

Net worth, personal assets, tax and market valuations, account and fixed-term deposit balances, foreign currency holdings.

HOW IT IS FOUND

COLUMN NAME AR_FIN_PATRIMONIO – Path

85% `patrimonio(_?(neto|total))?` `bienes_?personales` `activos?_?(totales?)?` `valuaci[oó]n_?(fiscal|inmueble|veh[ií]culo)` `valor_?(del_?)?(inmueble|veh[ií]culo|bienes|tasaci[oó]n|mercado)` `tasaci[oó]n` `saldo_?(cuenta|caja_?ahorro|plazo_?fijo|inversi[oó]n)` `plazo_?fijo(_?monto)?` `tenencia_?(d[oó]lares|moneda_?extranjera|cripto)` `net_?worth` `account_?balance`

DATA TYPE AR_FIN_PATRIMONIO — Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
85000000	→	**51593117**

12.5 Pensions and benefits

AR_FIN_JUBILACION

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

The retirement or survivor pension, the amount of an allowance or benefit, and child support.

HOW IT IS FOUND

COLUMN NAME AR_FIN_JUBILACION — Path

90% `haber_?(jubilatorio|previsional|mensual)` `jubilaci[oó]n_?(monto|haber|importe)` `pensi[oó]n_?(monto|haber|importe)` `monto_?(jubilaci[oó]n|pensi[oó]n|asignaci[oó]n|prestaci[oó]n|beneficio)` `importe_?(asignaci[oó]n|beneficio|prestaci[oó]n)` `cuota_?alimentaria` `pension_?amount`

DATA TYPE AR_FIN_JUBILACION — Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
420000	→	**646464**

12.6 Social benefits and programmes

AR_FIN_PROGRAMA_SOCIAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

ANSES benefits and national programmes — Universal Child and Pregnancy Allowance, Prestación Alimentar, Progresar, non-contributory pensions, PUAM, family allowances — and the income level of the energy subsidy segmentation, often as a flag. Receiving the AUH says the person has children and works informally; a non-contributory pension, that they have a disability.

HOW IT IS FOUND

COLUMN NAME AR_FIN_PROGRAMA_SOCIAL – Path

90% `programa_?social` `plan_?social` `beneficiario_?(programa|plan|asignaci[oó]n|auh|anses)` `prestaci[oó]n_?(social|anses|alimentar)` `asignaci[oó]n_?(universal|por_?hijo|por_?embarazo|familiar)` `auh` `aue` `tarjeta_?alimentar` `progresar` `potenciar_?trabajo` `volver_?al_?trabajo` `puam` `pnc` `pensi[oó]n_?no_?contributiva` `beneficio_?anses` `tipo_?(de_?)?beneficio` `segmentaci[oó]n_?(energ[eé]tica|subsidios?)` `nivel_?(de_?)?(subsidio|ingresos_?rase)` `rase` `social_?programme`

VALUE FORMAT AR_FIN_PROGRAMA_SOCIAL – Values

PATTERN	STRENGTH	NOTES
One of 27 known values, ignoring case — Asignación Universal por Hijo, Asignación por Embarazo, Prestación Alimentar, Progresar, Asignaciones familiares, Jubilación, …	80%	
One of 10 known values, ignoring case — s, n, sí, no, 1, 2, …	30%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a benefit from the list.

`AR_PROGRAMA_SOCIAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_PROGRAMA_SOCIAL_LISTA`.

`AR_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`AR_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

`AR_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

`AR_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

`AR_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

`AR_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

`AR_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`AR_PROGRAMA_SOCIAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 13 values in `ar-programas-sociales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Potenciar Trabajo	→	**Acompañamiento Social**
S	→	**S**

12.7 Monotributo category

AR_FIN_MONOTRIBUTO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The category of the Simplified Regime, A to K, which ARCA assigns by gross annual income.

HOW IT IS FOUND

> COLUMN NAME AR_FIN_MONOTRIBUTO — Path
>
> 90% `categor[ií]a_?(de_?)?monotributo` `monotributo(_?categor[ií]a)?` `cat_?monotributo` `categor[ií]a_?(afip|arca)` `r[eé]gimen_?simplificado`

> DATA TYPE AR_FIN_MONOTRIBUTO — Type
>
> Accepts text (length 1 to 12); any other type rules the domain out.

HOW IT IS MASKED

The category is replaced within its tier — A–D, E–H, I–K —; `Categoría C` stays written the same way.

`AR_MONOTRIBUTO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

> `AR_MONOTRIBUTO_A_D` SECURE LOOKUP
>
> Replaces the value with one of the 4 values in `ar-monotributo-a-d.txt`, chosen by a keyed hash.
>
> `AR_MONOTRIBUTO_E_H` SECURE LOOKUP
>
> Replaces the value with one of the 4 values in `ar-monotributo-e-h.txt`, chosen by a keyed hash.
>
> `AR_MONOTRIBUTO_I_K` SECURE LOOKUP
>
> Replaces the value with one of the 3 values in `ar-monotributo-i-k.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
C	→	**D**
Categoría H	→	**Categoría E**

12.8 Housing tenure

AR_FIN_VIVIENDA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Housing tenure as the 2022 census asks it: owner of the dwelling and the land or of the dwelling only, tenant, occupant on loan or through work.

HOW IT IS FOUND

COLUMN NAME AR_FIN_VIVIENDA — Path

90% `tenencia_?(de_?)?(la_?)?vivienda` `r[eé]gimen_?(de_?)?tenencia` `tipo_?(de_?)?tenencia` `vivienda_?(propia|alquilada|tipo_?tenencia)` `condici[oó]n_?(de_?)?ocupaci[oó]n` `housing_?tenure`

VALUE FORMAT AR_FIN_VIVIENDA — Values

PATTERN	STRENGTH	NOTES
One of 16 known values, ignoring case — Propietario de la vivienda y el terreno, Propietario solo de la vivienda, Inquilino, Ocupante por préstamo, Ocupante por trabajo, Otra situación, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another tenure from the list.

`AR_TENENCIA_VIVIENDA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_TENENCIA_VIVIENDA_LISTA`.

> `AR_BANDERA` **REGEX DECOMPOSE**
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `AR_BANDERA_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_YES_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.
>
> `AR_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `AR_TENENCIA_VIVIENDA_LISTA` **SECURE LOOKUP**
>
> Replaces the value with one of the 6 values in `ar-tenencia-vivienda.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Ocupante de hecho	→	**Otra situación**

PART 13

Criminal records and court files

Data on criminal or misdemeanour records may only be processed by the competent public authorities (art. 7.4), and Convention 108+ counts it among the special categories. A company that keeps it — a criminal record certificate requested in recruitment — must protect it with the care of sensitive data.

13.1 Records

AR_PENAL_ANTECEDENTES

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

The criminal record certificate of the National Recidivism Registry, misdemeanours, type of offence, procedural situation, pre-trial detention, detainee status and arrest warrants.

HOW IT IS FOUND

COLUMN NAME — AR_PENAL_ANTECEDENTES – Path

95% `antecedentes?(_?(penales|judiciales|policiales|contravencionales))?` `certificado_?(de_?)?` `(antecedentes|reincidencia|buena_?conducta)` `reincidencia` `registro_?nacional_?(de_?)?` `reincidencia` `rnr` `condena(_?(penal|tipo))?` `delito(_?(tipo|imputado))?` `tipo_?(de_?)?` `delito` `contravenci[oó]n(es)?` `situaci[oó]n_?procesal` `prisi[oó]n_?preventiva` `detenido` `privad[oa]_?(de_?)?(la_?)?libertad` `interno_?(spf|penitenciario)` `reincidente` `pedido_?(de_?)?captura` `rebeld[ií]a` `criminal_?record`

55% `estado_?(del_?)?proceso` `sentencia` `fallo`

HOW IT IS MASKED

Replaced by a generic status from the list — no record, convicted, dismissed —, whatever the outcome; a flag stays a flag.

`AR_ANTECEDENTES` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_ANTECEDENTES_LISTA`.

> `AR_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `AR_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `AR_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.
>
> `AR_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `AR_ANTECEDENTES_LISTA` SECURE LOOKUP

Replaces the value with one of the 8 values in `ar-antecedentes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Condenado por robo en 2019`	→	**`Absuelto`**

13.2 Court file

AR_PENAL_EXPEDIENTE

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The file number of the national and federal courts — the chamber's code, the number and the year, `CCC 12345/2023` —, the criminal investigation number (IPP) of Buenos Aires province (`PP-07-00-012345-23/00`) and case, police report and complaint numbers. Cases can be looked up online and lead to the parties.

HOW IT IS FOUND

COLUMN NAME AR_PENAL_EXPEDIENTE — Path

90%	`n(o|ro|um|umero)_?(de_?)?(expediente|causa|legajo_?penal|ipp|sumario|denuncia|carpeta_?judicial)(_?(judicial|penal))?` `expediente_?(judicial|penal)` `causa_?(penal|judicial|n(o|ro|um|umero))` `ipp` `cuij` `sumario_?policial` `denuncia_?(penal|policial)`
50%	`expediente` `causa`

VALUE FORMAT AR_PENAL_EXPEDIENTE — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{2,4}\s?\d{1,6}\/\d{4}`	70%	
`PP-\d{2}-\d{2}-\d{6}-\d{2}(\/\d{2})?`	80%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The number is mapped digit by digit; code, judicial district, prosecutor's office and year stay. Other numbers are masked character by character.

`AR_EXPEDIENTE` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

`AR_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`AR_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`CCC 12345/2023`	→	**`CCC 31564/2023`**
`PP-07-00-012345-23/00`	→	**`PP-07-00-031564-23/00`**

14

The CUIT check digit

The Masking Engine's Check Digit algorithm computes a modulus-11 digit as *eleven minus the remainder* and writes 10 as 0. For the CUIT that is right for ten of the eleven possible remainders: when the remainder is 1, ARCA uses no digit but changes the type — 20 and 27 become 23, 30 becomes 33, 23 becomes 24, 33 becomes 34 —, and Check Digit would write 0. One masked CUIT in eleven would be invalid.

The set solves it in two steps, with no tables:

- A Check Digit with **doubled weights** keeps the type, maps the eight DNI digits and writes an auxiliary digit in place of the check digit. Since $2 \times 1 \equiv 2$ modulo 11, the auxiliary digit is 9 exactly when the remainder of the masked body under the true weights is 1.
- A Regex Decompose, when the auxiliary digit is 9, rewrites type and digit: changing the type adds a known multiple of the weights, and the new digit follows — 23 and 9 for a 20, 23 and 4 for a 27, 33 and 9 for a 30, 24 and 6 for a 23, 34 and 6 for a 33. In any other case it applies a Check Digit with the true weights over the body, which it leaves as it is, and recomputes the digit.

The body is mapped with the same Character Mapping as the DNI: a natural person's CUIL still holds their masked DNI. CBU and CVU do not have the problem — their modulus is 10 — and are solved with a single Check Digit over the account.

15

Where people live: localidades, partidos and postal code

With the 2022 census population by gobierno local and by departamento, and the location of each from the Georef service, the set knows the size, province and position of 528 partidos, departamentos and comunas, of 2,280 gobiernos locales and of the 4,027 INDEC localidades censales.

- A **gobierno local** with fewer than 20,000 inhabitants becomes the nearest gobierno local of the same province with at least 20,000. There are 1,952 of them, with 7 million inhabitants — 15% of the population. El Chaltén (Santa Cruz) becomes El Calafate; Tilcara (Jujuy), Libertador General San Martín; Ancasti (Catamarca), Valle Viejo.
- A **localidad** follows its gobierno local. Those outside any gobierno local — rural areas of Santiago del Estero, Córdoba or Patagonia — are generalized too, to the nearest large gobierno local.
- A **partido or departamento** with fewer than 20,000 inhabitants becomes the nearest one of the same province with at least 20,000. There are 203, with 2 million inhabitants.
- The **province** stays. Every province has at least one gobierno local of 20,000 inhabitants.
- Distance is measured between the Georef centroids, in a straight line.
- Names repeat — San José, San Martín, Villa Nueva, 25 de Mayo — and some differ only by an accent. A name is generalized only when every place bearing it is small, and then follows the largest of them. With the province (`San José – Entre Ríos` , `San José (Entre Ríos)` , `San José, Entre Ríos`) the same rule applies within the province.
- The **INDEC codes** follow the same table, and a person's name and code still agree.
- In Buenos Aires province the gobierno local is the partido: a small localidad becomes the name of the nearest partido, which is not always the name of its main town — `Carhué` becomes `Saavedra` , whose main town is Pigüé.
- The **postal code** keeps the province and the first two digits.

Place names that are also given names or surnames, and province names, are left out of the detection list, so that a surname column is not taken for localidades.

16

Limits

- **Binary columns** — DNI photos, biometric validation selfies, fingerprints, clinical PDFs in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **A small localidad inside a large gobierno local** stays: the census publishes population by gobierno local, not by localidad. A rural paraje of a large partido keeps its name.
- **A seven-digit DNI** is masked with seven digits; inside the CUIL it has a leading zero and is masked with eight. That person's DNI and CUIL no longer agree.
- **A check digit in a column of its own** is not recomputed: it is masked and no longer matches the masked CUIT.
- **Province, the CBU's bank and the phone area code stay.**
- **Data Cleansing leaves unknown values as they are**: a localidad written in a way the table does not have — abbreviated, misspelled — passes unchanged.
- **Free text** is redacted word by word: a mobile written with spaces is not found, and a name that is also a common word (`Luz` , `Rosa` , `Paz`) is redacted wherever it appears.
- **Children and adolescents** — a birth date moves at most 60 days, so few people cross their 13th, 16th or 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, height, neighbourhood, localidad and postal code in separate columns are masked independently and no longer form a coherent address.
- **The engine key** links masked values back to production for whoever holds both: in that case the result is not dissociated and is still personal data. Keep the key away from the users of the copy.

17

Verification

Before publication, the set was checked outside a Masking Engine:

- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 160 columns with the whole set at its assignment threshold — well named, badly named and 31 columns that are not personal data — and again with only the classifiers of the essential pack.
- The tables that generalize places were audited for the 528 partidos and departamentos and for the 2,280 gobiernos locales and 4,027 localidades: by name, by name with the province and by code.
- The algorithms, run with the Delphix algorithm plugin, masked each domain's sample values and placeholders such as `N/A` , checking every output against its vocabulary; 240 CUITs of every type — including those that change type — and 150 CBUs for validity and collisions; 150 DNIs for collisions; and 20 people whose DNI and CUIL must still agree. Every algorithm also masked its own sample value.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

Sources

- Law 25.326 on the Protection of Personal Data and Decree 1558/2001 (InfoLEG). National Constitution, art. 43. Law 27.483 (Convention 108) and Law 27.699 (Convention 108+). Criminal Code, arts. 117 bis and 157 bis.
- Agencia de Acceso a la Información Pública: Resolution 47/2018, recommended security measures (Annex I, item H); Resolution 126/2024, classification of infringements and grading of sanctions. Bills 644-S-2025, 1948-D-2025 and 3397-D-2026. European Commission, Decision 2003/490/EC and 2024 review report.
- Laws 26.529 (patients' rights), 26.657 (mental health), 27.675 (HIV, hepatitis, tuberculosis and STIs), 27.610 (voluntary termination of pregnancy), 26.743 (gender identity), 26.485 (violence against women), 26.364 (human trafficking), 22.431 (disability), 24.557 (occupational risks). Decree 476/2021 (DNI with X).
- INDEC: 2022 National Census of Population, Households and Dwellings, final results by departamento and by gobierno local; localidades censales. Georef geographic data normalization service (datos.gob.ar). RENAPER: names of natural persons (datos.gob.ar).
- ARCA (formerly AFIP): CUIT, CUIL and simplified regime. BCRA: Central de Deudores and debtor classification; Clave Bancaria Uniforme and Clave Virtual Uniforme. ANSES: benefits. Correo Argentino: Código Postal Argentino. Superintendencia de Servicios de Salud: National Register of Obras Sociales.

APPENDIX A

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

AR_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `AR_L2_ANIO_NACIMIENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{3})(\d))`	keep · keep · `AR_CM_DIGITOS`
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

AR_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_ANTECEDENTES_LISTA`.

Used by: `AR_PENAL_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
`otherwise`	`AR_ANTECEDENTES_LISTA`

CONFIGURATION

`trimInput`	yes
`requireMask`	no

AR_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `ar-antecedentes.txt`, chosen by a keyed hash.

Used by: `AR_ANTECEDENTES`

CONFIGURATION

`lookupFile`	`ar-antecedentes.txt`
`hashMethod`	`SHA256`
`maskedValueCase`	`PRESERVE_INPUT`
`inputCaseSensitive`	no
`trimWhitespaceFromInput`	yes
`trimWhitespaceInLookupFile`	yes

AR_APELLIDO NAME

Replaces the name with one of the 408 names in `ar-apellidos.txt`.

Used by: `AR_PALABRA_APELLIDO`

CONFIGURATION

lookupFile	ar-apellidos.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

AR_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: AR_CM_ALFANUM .

Used by: AR_L1_APELLIDO , AR_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(\S+)	AR_PALABRA_APELLIDO
(\S+)\s+(\S+)	AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO
otherwise	AR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: AR_CATEGORIA_SUPRIMIDA , AR_ESTADO_CIVIL , AR_NIVEL_EDUCATIVO , AR_ORIGEN_ETNICO , AR_PUEBLO_INDIGENA , AR_LENGUA , AR_RELIGION , AR_OPINION_POLITICA , AR_PARTIDO_POLITICO , AR_ORIENTACION_SEXUAL , AR_IDENTIDAD_GENERO , AR_COBERTURA_SALUD , AR_DIAGNOSTICO , AR_MEDICAMENTO , AR_DISCAPACIDAD , AR_SALUD_LABORAL , AR_SITUACION_CREDITICIA , AR_PROGRAMA_SOCIAL , AR_TENENCIA_VIVIENDA , AR_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no)	AR_BANDERA_SI_NO
(?i)(true|false)	AR_BANDERA_TRUE_FALSE
(?i)(yes)	AR_BANDERA_YES_NO
(?i)([sn])	AR_BANDERA_S_N
(?i)([yx])	AR_BANDERA_Y_N
([01])	AR_BANDERA_0_1
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.

Used by: AR_BANDERA

CONFIGURATION

lookupFile	ar-bandera-0-1.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

Used by: `AR_BANDERA`

CONFIGURATION

lookupFile	`ar-bandera-s-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

Used by: `AR_BANDERA`

CONFIGURATION

lookupFile	`ar-bandera-si-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

Used by: `AR_BANDERA`

CONFIGURATION

lookupFile	`ar-bandera-true-false.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

Used by: `AR_BANDERA`

CONFIGURATION

lookupFile	`ar-bandera-y-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

Used by: `AR_BANDERA`

CONFIGURATION

lookupFile	`ar-bandera-yes-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BARRIO SECURE LOOKUP

Replaces the value with one of the 124 values in `ar-barrios.txt`, chosen by a keyed hash.

Used by: `AR_L2_BARRIO`

CONFIGURATION

lookupFile	`ar-barrios.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR`.

Used by: `AR_L3_CONVICCION_FILOSOFICA`, `AR_L3_AFILIACION_SINDICAL`, `AR_L3_VIDA_SEXUAL`, `AR_L3_VICTIMA`, `AR_SALUD_VIH`, `AR_SALUD_REPRODUCTIVA`, `AR_SALUD_MENTAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(\d{1,6})))))))))`	keep · keep · keep · keep · keep · keep · keep · `AR_CM_ALFANUM`
otherwise	`AR_SUPRIMIR`

CONFIGURATION

trimInput	yes
requireMask	no

AR_CBU REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_DIGITOS`.

Used by: `AR_L1_CBU`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{8})([\s\-]?)(\d{14}))`	keep · keep · keep · `AR_CBU_CUENTA`

otherwise	`AR_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

AR_CBU_CUENTA CHECK DIGIT

Masks the digits with `AR_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 10 check digit with weights `3 1 7 9 3 1 7 9 3 1 7 9 3` from the right.

Used by: `AR_CBU`

CONFIGURATION

weightList	`3 1 7 9 3 1 7 9 3 1 7 9 3`
modulusNumber	`10`
checkDigitIndex	`13`
numDigitsForCheckdigitCalculation	`13`
calculateChecksumRightToLeft	yes
numericAlgorithm	`AR_CM_DIGITOS_ANCHO_FIJO`
alphaNumericAlgorithm	`AR_CM_DIGITOS_ANCHO_FIJO`
preserveRegex	
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

AR_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in `ar-cie10.txt`, chosen by a keyed hash.

Used by: `AR_DIAGNOSTICO`

CONFIGURATION

lookupFile	`ar-cie10.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `ar-cie10-decimal.txt`, chosen by a keyed hash.

Used by: `AR_DIAGNOSTICO`

CONFIGURATION

lookupFile	`ar-cie10-decimal.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: AR_L1_TRAMITE_DNI, AR_L1_DOCUMENTO_EXTRANJERO, AR_L1_PASAPORTE, AR_L1_REGISTRO_CIVIL, AR_L1_MATRICULA_PROFESIONAL, AR_L1_DIRECCION_COMPLEMENTO, AR_L1_ALIAS_CBU, AR_L1_VEHICULO, AR_L1_INMUEBLE, AR_L1_CONTRATO, AR_L1_USUARIO, AR_SALUD_IDENTIFICADOR, AR_SALUD_RESULTADO_ESTUDIO, AR_CATEGORIA_SUPRIMIDA, AR_DOCUMENTO, AR_NOMBRES, AR_APELLIDOS, AR_NOMBRE_COMPLETO, AR_EMAIL, AR_ORIGEN_ETNICO, AR_PUEBLO_INDIGENA, AR_LENGUA, AR_RELIGION, AR_OPINION_POLITICA, AR_PARTIDO_POLITICO, AR_ORIENTACION_SEXUAL, AR_IDENTIDAD_GENERO, AR_MEDICAMENTO, AR_DISCAPACIDAD, AR_SALUD_LABORAL, AR_PROGRAMA_SOCIAL, AR_TENENCIA_VIVIENDA, AR_ANTECEDENTES, AR_EXPEDIENTE

CONFIGURATION

characterGroups	0123456789 AEIOU BCDFGHJKLMNPQRSTVWXYZ aeiou bcdfghjklmnpqrstvwxyz ÁÉÍÓÚÜ áéíóúü
caseSensitive	yes
minMaskedPositions	0
preserveLeadingZeros	yes

AR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: AR_L1_CUENTA_BANCARIA, AR_CUIT_CUERPO, AR_CUIT, AR_DOCUMENTO, AR_TELEFONO, AR_CBU, AR_COORDENADA, AR_ANIO, AR_EDAD, AR_OCUPACION_O_CODIGO, AR_COBERTURA_SALUD, AR_PROCEDIMIENTO, AR_SITUACION_CREDITICIA, AR_EXPEDIENTE

CONFIGURATION

characterGroups	0123456789
caseSensitive	yes
minMaskedPositions	0
preserveLeadingZeros	yes

AR_CM_DIGITOS_ANCHO_FIJO CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: AR_CBU_CUENTA

CONFIGURATION

characterGroups	0123456789
caseSensitive	yes
minMaskedPositions	0

AR_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: AR_L1_DOMINIO

CONFIGURATION

characterGroups	0123456789 ABCDEFGHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0
preserveLeadingZeros	yes

AR_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `AR_L1_DISPOSITIVO` , `AR_IP`

CONFIGURATION

characterGroups	`0123456789` `abcdef` `ABCDEF` `ghijklmnopqrstuvwxyz` `GHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

AR_COBERTURA_SALUD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_OBRA_SOCIAL` .

Used by: `AR_SALUD_COBERTURA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d[\d\-]{3,8}\d))`	keep · `AR_CM_DIGITOS`
otherwise	`AR_OBRA_SOCIAL`

CONFIGURATION

trimInput	yes
requireMask	no

AR_CODIGO_GEOGRAFICO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `AR_L2_CODIGO_GEOGRAFICO`

PATTERNS, TRIED IN ORDER

`(0*)([1-9]\d*)`	keep · `AR_CODIGO_GEOGRAFICO_TABLA`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_CODIGO_GEOGRAFICO_TABLA DATA CLEANSING

Replaces each value found in `ar-codigos-geograficos-generalizados.txt` (5,330 pairs) by its counterpart; values not in the file stay as they are.

Used by: `AR_CODIGO_GEOGRAFICO`

CONFIGURATION

lookupFile	`ar-codigos-geograficos-generalizados.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

AR_CODIGO_POSTAL REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `AR_L2_CODIGO_POSTAL`

PATTERNS, TRIED IN ORDER

`([A-Za-z])(\d{2})(\d{2})([A-Za-z]{3})`	keep · keep · replace with `00` · replace with `AAA`
`([A-Za-z]?)(\d{2})(\d{2})`	keep · keep · replace with `00`
`(0+)([1-9]\d)(\d{2})`	keep · keep · replace with `00`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_CONTEO_LIMITADO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `AR_L2_PERSONAS_A_CARGO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([0-5]))`	keep · keep
`(0*?)(?:(\d+))`	keep · replace with `5`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `AR_L1_GEOLOCALIZACION`

PATTERNS, TRIED IN ORDER

`(-?\d{1,3}[.,]\d)(\d+)\s*([,;])\s*(-?\d{1,3}[.,]\d)(\d+)`	keep · `AR_CM_DIGITOS` · keep · keep · `AR_CM_DIGITOS`
`(-?\d{1,3}[.,]\d)(\d+)`	keep · `AR_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_CUIT REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_DIGITOS`.

Used by: `AR_L1_CUIT`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2}[\s\-./]?\d{8}[\s\-./]?\d))`	keep · `AR_CUIT_CADENA`
otherwise	`AR_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

AR_CUIT_AJUSTE REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `AR_CUIT_DV`.

Used by: `AR_CUIT_CADENA`

PATTERNS, TRIED IN ORDER

`(20)([\s\-./]?\d{8}[\s\-./]?)(9)`	replace with `23` · keep · replace with `9`
`(27)([\s\-./]?\d{8}[\s\-./]?)(9)`	replace with `23` · keep · replace with `4`
`(23)([\s\-./]?\d{8}[\s\-./]?)(9)`	replace with `24` · keep · replace with `6`
`(24)([\s\-./]?\d{8}[\s\-./]?)(9)`	replace with `23` · keep · replace with `3`
`(30)([\s\-./]?\d{8}[\s\-./]?)(9)`	replace with `33` · keep · replace with `9`
`(33)([\s\-./]?\d{8}[\s\-./]?)(9)`	replace with `34` · keep · replace with `6`
`(34)([\s\-./]?\d{8}[\s\-./]?)(9)`	replace with `33` · keep · replace with `3`
otherwise	`AR_CUIT_DV`

CONFIGURATION

trimInput	yes
requireMask	no

AR_CUIT_AUX CHECK DIGIT

Masks the digits with `AR_CUIT_CUERPO` and recomputes a modulus 11 check digit with weights `4 6 8 10 12 14 4 6 8 10` from the right.

Used by: `AR_CUIT_CADENA`

CONFIGURATION

weightList	`4 6 8 10 12 14 4 6 8 10`
modulusNumber	`11`
checkDigitIndex	`10`
numDigitsForCheckdigitCalculation	`10`
calculateChecksumRightToLeft	yes
numericAlgorithm	`AR_CUIT_CUERPO`
alphaNumericAlgorithm	`AR_CUIT_CUERPO`
preserveRegex	`[.\-\s/]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

AR_CUIT_CADENA STRING ALGORITHM CHAIN

Applies `AR_CUIT_AUX` → `AR_CUIT_AJUSTE`, in this order.

Used by: `AR_CUIT`, `AR_DOCUMENTO`

CONFIGURATION

algorithmReferences[1]	`AR_CUIT_AUX`
algorithmReferences[2]	`AR_CUIT_AJUSTE`

AR_CUIT_CUERPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_DIGITOS`.

Used by: `AR_CUIT_AUX`

PATTERNS, TRIED IN ORDER

`(\d{2})(\d{8})`	keep · `AR_CM_DIGITOS`
otherwise	`AR_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

AR_CUIT_DV CHECK DIGIT

Masks the digits with `AR_IDENTIDAD` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 2 3 4 5` from the right.

Used by: `AR_CUIT_AJUSTE`

CONFIGURATION

weightList	`2 3 4 5 6 7 2 3 4 5`
modulusNumber	`11`
checkDigitIndex	`10`
numDigitsForCheckdigitCalculation	`10`
calculateChecksumRightToLeft	yes
numericAlgorithm	`AR_IDENTIDAD`
alphaNumericAlgorithm	`AR_IDENTIDAD`
preserveRegex	`[.\-\s/]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

AR_DEPARTAMENTO DATA CLEANSING

Replaces each value found in `ar-departamentos-generalizados.txt` (3,254 pairs) by its counterpart; values not in the file stay as they are.

Used by: `AR_L2_DEPARTAMENTO`

CONFIGURATION

lookupFile	`ar-departamentos-generalizados.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

AR_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `AR_DIAGNOSTICO_TEXTO` .

Used by: `AR_SALUD_DIAGNOSTICO`

PATTERNS, TRIED IN ORDER

`([A-TV-Za-tv-z]\d{2}\.\d{1,2})`	`AR_CIE10_DECIMAL`
`([A-TV-Za-tv-z]\d{2,3}X?)`	`AR_CIE10`

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
otherwise	`AR_DIAGNOSTICO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

AR_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in `ar-diagnosticos.txt`, chosen by a keyed hash.

Used by: `AR_DIAGNOSTICO`

CONFIGURATION

lookupFile	`ar-diagnosticos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in `ar-direcciones.txt`, chosen by a keyed hash.

Used by: `AR_L1_DIRECCION`

CONFIGURATION

lookupFile	`ar-direcciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_DISCAPACIDAD_TIPO`.

Used by: `AR_SALUD_DISCAPACIDAD`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`([A-Za-z0-9\-/]*\d{4,}[A-Za-z0-9\-/]*)`	`AR_CM_ALFANUM`
otherwise	`AR_DISCAPACIDAD_TIPO`

CONFIGURATION

trimInput	yes
requireMask	no

AR_DISCAPACIDAD_TIPO SECURE LOOKUP

Replaces the value with one of the 8 values in `ar-discapacidades.txt`, chosen by a keyed hash.

Used by: `AR_DISCAPACIDAD`

CONFIGURATION

lookupFile	`ar-discapacidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_DOCUMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

Used by: `AR_L1_DNI`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2}[\s\-./]?\d{8}[\s\-./]?\d))`	keep · `AR_CUIT_CADENA`
`(0*?)(?:(\d{1,3}(?:\.\d{3}){1,2}|\d{6,8}))`	keep · `AR_CM_DIGITOS`
otherwise	`AR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

AR_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `AR_L2_EDAD`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-9]\d{2,}))`	keep · replace with `90`
`(0*?)(?:([1-9])(\d)([.,]\d+))`	keep · keep · `AR_CM_DIGITOS` · keep
`(0*?)(?:([1-9])(\d))`	keep · keep · `AR_CM_DIGITOS`
`(0*?)(?:(\d))`	keep · `AR_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

Used by: `AR_L1_EMAIL`

PATTERNS, TRIED IN ORDER

`([^@\s]+)@([^@\s]+)\.([A-Za-z]{2,24}(?:\.[A-Za-z]{2})?)`	`AR_CM_ALFANUM` · `AR_CM_ALFANUM` · replace with `test`
otherwise	`AR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

AR_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 24 values in `ar-empleadores.txt`, chosen by a keyed hash.

Used by: `AR_L2_EMPLEADOR`

CONFIGURATION

lookupFile	`ar-empleadores.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_EMPRESA SECURE LOOKUP

Replaces the value with one of the 24 values in `ar-empresas.txt`, chosen by a keyed hash.

Used by: `AR_L1_RAZON_SOCIAL`

CONFIGURATION

lookupFile	`ar-empresas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_ESTABLECIMIENTO_EDUCATIVO SECURE LOOKUP

Replaces the value with one of the 12 values in `ar-establecimientos-educativos.txt`, chosen by a keyed hash.

Used by: `AR_L2_ESTABLECIMIENTO_EDUCATIVO`

CONFIGURATION

lookupFile	`ar-establecimientos-educativos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_ESTADO_CIVIL_LISTA`.

Used by: `AR_L2_ESTADO_CIVIL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `AR_ESTADO_CIVIL_CODIGO`
otherwise	`AR_ESTADO_CIVIL_LISTA`

CONFIGURATION

trimInput	yes

requireMask	no

AR_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in `ar-estado-civil-codigos.txt`, chosen by a keyed hash.

Used by: `AR_ESTADO_CIVIL`

CONFIGURATION

lookupFile	`ar-estado-civil-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `ar-estado-civil.txt`, chosen by a keyed hash.

Used by: `AR_ESTADO_CIVIL`

CONFIGURATION

lookupFile	`ar-estado-civil.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 10 values in `ar-estados-credito.txt`, chosen by a keyed hash.

Used by: `AR_SITUACION_CREDITICIA`

CONFIGURATION

lookupFile	`ar-estados-credito.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_EXPEDIENTE REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

Used by: `AR_PENAL_EXPEDIENTE`

PATTERNS, TRIED IN ORDER

`([A-Za-z]{2,4}[\s\-]?)(\d{1,6})(\/\d{2,4}(?:\/[A-Za-z0-9]{1,6})*)`	keep · `AR_CM_DIGITOS` · keep
`((?:PP|IPP)[\s\-]?\d{2}[\s\-]\d{2}[\s\-])(\d{6})([\s\-]\d{2}(?:\/\d{2})?)`	keep · `AR_CM_DIGITOS` · keep
`(0*?)(?:(\d{1,6})(\/\d{2,4}))`	keep · `AR_CM_DIGITOS` · keep
otherwise	`AR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

AR_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `AR_L2_FECHA_EVENTO`

CONFIGURATION

minRange	`-30`
maxRange	`30`
unit	`DAYS`
roll	no

AR_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `AR_L2_FECHA_NACIMIENTO`

CONFIGURATION

minRange	`-60`
maxRange	`60`
unit	`DAYS`
roll	no

AR_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in `ar-grupos-sanguineos.txt` , chosen by a keyed hash.

Used by: `AR_SALUD_GRUPO_SANGUINEO`

CONFIGURATION

lookupFile	`ar-grupos-sanguineos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_IDENTIDAD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `AR_CUIT_DV`

PATTERNS, TRIED IN ORDER

`(.*)`	keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_IDENTIDAD_GENERO_LISTA`.

Used by: `AR_L3_IDENTIDAD_GENERO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
otherwise	`AR_IDENTIDAD_GENERO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

AR_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `ar-identidades-genero.txt`, chosen by a keyed hash.

Used by: `AR_IDENTIDAD_GENERO`

CONFIGURATION

lookupFile	`ar-identidades-genero.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_HEX`.

Used by: `AR_L1_IP`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}))`	keep · `AR_OCTETO` · `AR_OCTETO` · `AR_OCTETO` · `AR_OCTETO`
otherwise	`AR_CM_HEX`

CONFIGURATION

trimInput	yes
requireMask	no

AR_LENGUA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_LENGUA_LISTA`.

Used by: `AR_L3_LENGUA_INDIGENA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
otherwise	`AR_LENGUA_LISTA`

CONFIGURATION

trimInput	yes

requireMask	no

AR_LENGUA_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in `ar-lenguas.txt`, chosen by a keyed hash.

Used by: `AR_LENGUA`

CONFIGURATION

lookupFile	`ar-lenguas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_LOCALIDAD DATA CLEANSING

Replaces each value found in `ar-localidades-generalizadas.txt` (55,794 pairs) by its counterpart; values not in the file stay as they are.

Used by: `AR_L2_LOCALIDAD`

CONFIGURATION

lookupFile	`ar-localidades-generalizadas.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

AR_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_MEDICAMENTO_LISTA`.

Used by: `AR_SALUD_MEDICAMENTO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
otherwise	`AR_MEDICAMENTO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

AR_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 24 values in `ar-medicamentos.txt`, chosen by a keyed hash.

Used by: `AR_MEDICAMENTO`

CONFIGURATION

lookupFile	`ar-medicamentos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

AR_MONOTRIBUTO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: AR_FIN_MONOTRIBUTO

PATTERNS, TRIED IN ORDER

(?i)(categor[ií]a\s*)?([A-D])	keep · AR_MONOTRIBUTO_A_D
(?i)(categor[ií]a\s*)?([E-H])	keep · AR_MONOTRIBUTO_E_H
(?i)(categor[ií]a\s*)?([I-K])	keep · AR_MONOTRIBUTO_I_K
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_MONOTRIBUTO_A_D SECURE LOOKUP

Replaces the value with one of the 4 values in ar-monotributo-a-d.txt, chosen by a keyed hash.

Used by: AR_MONOTRIBUTO

CONFIGURATION

lookupFile	ar-monotributo-a-d.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_MONOTRIBUTO_E_H SECURE LOOKUP

Replaces the value with one of the 4 values in ar-monotributo-e-h.txt, chosen by a keyed hash.

Used by: AR_MONOTRIBUTO

CONFIGURATION

lookupFile	ar-monotributo-e-h.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_MONOTRIBUTO_I_K SECURE LOOKUP

Replaces the value with one of the 3 values in ar-monotributo-i-k.txt, chosen by a keyed hash.

Used by: AR_MONOTRIBUTO

CONFIGURATION

lookupFile	ar-monotributo-i-k.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 14 values in `ar-nacionalidades.txt`, chosen by a keyed hash.

Used by: `AR_L2_NACIONALIDAD`

CONFIGURATION

lookupFile	`ar-nacionalidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_NIVEL_EDUCATIVO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_NIVEL_EDUCATIVO_LISTA`.

Used by: `AR_L2_NIVEL_EDUCATIVO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `AR_NIVEL_EDUCATIVO_CODIGO`
otherwise	`AR_NIVEL_EDUCATIVO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

AR_NIVEL_EDUCATIVO_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in `ar-nivel-educativo-codigos.txt`, chosen by a keyed hash.

Used by: `AR_NIVEL_EDUCATIVO`

CONFIGURATION

lookupFile	`ar-nivel-educativo-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_NIVEL_EDUCATIVO_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `ar-nivel-educativo.txt`, chosen by a keyed hash.

Used by: `AR_NIVEL_EDUCATIVO`

CONFIGURATION

lookupFile	`ar-nivel-educativo.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_NOMBRE NAME

Replaces the name with one of the 756 names in `ar-nombres.txt`.

Used by: `AR_PALABRA_NOMBRE`

CONFIGURATION

lookupFile	`ar-nombres.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

AR_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

Used by: `AR_L1_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`([^,]+),\s*(.+)`	`AR_APELLIDOS` · `AR_NOMBRES`
`(\S+)`	`AR_PALABRA_NOMBRE`
`(\S+)\s+(\S+)`	`AR_PALABRA_NOMBRE` · `AR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE` · `AR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE` · `AR_PALABRA_APELLIDO` · `AR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE` · `AR_PALABRA_APELLIDO` · `AR_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE` · `AR_PALABRA_APELLIDO` · `AR_PALABRA_APELLIDO` · `AR_PALABRA_APELLIDO`
otherwise	`AR_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

AR_NOMBRES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

Used by: `AR_L1_NOMBRE`, `AR_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`AR_PALABRA_NOMBRE`
`(\S+)\s+(\S+)`	`AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE`
`(\S+)\s+(\S+)\s+(\S+)`	`AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE` · `AR_PALABRA_NOMBRE`
otherwise	`AR_CM_ALFANUM`

CONFIGURATION

trimInput	yes

requireMask	no

AR_OBRA_SOCIAL SECURE LOOKUP

Replaces the value with one of the 19 values in `ar-obras-sociales.txt`, chosen by a keyed hash.

Used by: `AR_COBERTURA_SALUD`

CONFIGURATION

lookupFile	`ar-obras-sociales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `AR_IP`

CONFIGURATION

minValue	`1`
maxValue	`254`

AR_OCUPACION SECURE LOOKUP

Replaces the value with one of the 35 values in `ar-ocupaciones.txt`, chosen by a keyed hash.

Used by: `AR_OCUPACION_O_CODIGO`

CONFIGURATION

lookupFile	`ar-ocupaciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_OCUPACION_O_CODIGO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_OCUPACION`.

Used by: `AR_L2_OCUPACION`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2,5}))`	keep · `AR_CM_DIGITOS`
otherwise	`AR_OCUPACION`

CONFIGURATION

trimInput	yes
requireMask	no

AR_OPINION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_OPINION_POLITICA_LISTA`.

Used by: `AR_L3_OPINION_POLITICA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
otherwise	`AR_OPINION_POLITICA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

AR_OPINION_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `ar-opiniones-politicas.txt`, chosen by a keyed hash.

Used by: `AR_OPINION_POLITICA`

CONFIGURATION

lookupFile	`ar-opiniones-politicas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_ORIENTACION_SEXUAL_LISTA`.

Used by: `AR_L3_ORIENTACION_SEXUAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
otherwise	`AR_ORIENTACION_SEXUAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

AR_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `ar-orientaciones-sexuales.txt`, chosen by a keyed hash.

Used by: `AR_ORIENTACION_SEXUAL`

CONFIGURATION

lookupFile	`ar-orientaciones-sexuales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_ORIGEN_ETNICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_ORIGEN_ETNICO_LISTA`.

Used by: `AR_L3_ORIGEN_ETNICO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
otherwise	`AR_ORIGEN_ETNICO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

AR_ORIGEN_ETNICO_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in `ar-origen-etnico.txt`, chosen by a keyed hash.

Used by: `AR_ORIGEN_ETNICO`

CONFIGURATION

lookupFile	`ar-origen-etnico.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_APELLIDO`.

Used by: `AR_APELLIDOS`, `AR_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(?i)(de|del|la|las|los|y|e|san|santa|van|von|di|da|dos)`	keep
otherwise	`AR_APELLIDO`

CONFIGURATION

trimInput	yes
requireMask	no

AR_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_NOMBRE`.

Used by: `AR_NOMBRES`, `AR_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(?i)(de|del|la|las|los|y|e|san|santa|van|von|di|da|dos)`	keep
otherwise	`AR_NOMBRE`

CONFIGURATION

trimInput	yes
requireMask	no

AR_PARTIDO_POLITICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_PARTIDO_POLITICO_LISTA`.

Used by: `AR_L3_AFILIACION_PARTIDARIA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
otherwise	`AR_PARTIDO_POLITICO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

AR_PARTIDO_POLITICO_LISTA SECURE LOOKUP

Replaces the value with one of the 29 values in `ar-partidos-politicos.txt`, chosen by a keyed hash.

Used by: `AR_PARTIDO_POLITICO`

CONFIGURATION

lookupFile	`ar-partidos-politicos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_PROCEDIMIENTO_TEXTO`.

Used by: `AR_SALUD_PROCEDIMIENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2}\.?\d{2}\.?\d{2}))`	keep · `AR_CM_DIGITOS`
otherwise	`AR_PROCEDIMIENTO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

AR_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in `ar-procedimientos.txt`, chosen by a keyed hash.

Used by: `AR_PROCEDIMIENTO`

CONFIGURATION

lookupFile	`ar-procedimientos.txt`
hashMethod	`SHA256`

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_PROGRAMA_SOCIAL_LISTA.

Used by: AR_FIN_PROGRAMA_SOCIAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|yes|[snyx01])	AR_BANDERA
(0*?)(?:(\d{1,6}))	keep · AR_CM_ALFANUM
otherwise	AR_PROGRAMA_SOCIAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in ar-programas-sociales.txt, chosen by a keyed hash.

Used by: AR_PROGRAMA_SOCIAL

CONFIGURATION

lookupFile	ar-programas-sociales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_PUEBLO_INDIGENA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_PUEBLO_INDIGENA_LISTA.

Used by: AR_L3_PUEBLO_INDIGENA

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|yes|[snyx01])	AR_BANDERA
(0*?)(?:(\d{1,6}))	keep · AR_CM_ALFANUM
otherwise	AR_PUEBLO_INDIGENA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_PUEBLO_INDIGENA_LISTA SECURE LOOKUP

Replaces the value with one of the 20 values in ar-pueblos-indigenas.txt, chosen by a keyed hash.

Used by: AR_PUEBLO_INDIGENA

CONFIGURATION

lookupFile	`ar-pueblos-indigenas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `AR_L1_CREDENCIAL` , `AR_L3_BIOMETRICO` , `AR_L3_GENETICO`

PATTERNS, TRIED IN ORDER

`(.+)`	each character → `X`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_RELIGION_LISTA` .

Used by: `AR_L3_RELIGION`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
otherwise	`AR_RELIGION_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

AR_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `ar-religiones.txt` , chosen by a keyed hash.

Used by: `AR_RELIGION`

CONFIGURATION

lookupFile	`ar-religiones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SALUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SALUD_LABORAL_LISTA` .

Used by: `AR_SALUD_OCUPACIONAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
otherwise	`AR_SALUD_LABORAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

AR_SALUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in `ar-aptitud-laboral.txt`, chosen by a keyed hash.

Used by: `AR_SALUD_LABORAL`

CONFIGURATION

lookupFile	`ar-aptitud-laboral.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SEXO REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `AR_L2_SEXO`

PATTERNS, TRIED IN ORDER

`(?i)(femenino|masculino|no\s+binario)`	`AR_SEXO_FEMENINO_MASCULINO`
`(?i)(mujer|var[oó]n|hombre)`	`AR_SEXO_MUJER_VARON`
`(?i)(female|male)`	`AR_SEXO_FEMALE_MALE`
`(?i)([fmx])`	`AR_SEXO_F_M`
`(0*?)(?:([12]))`	keep · `AR_SEXO_1_2`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_SEXO_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-sexo-1-2.txt`, chosen by a keyed hash.

Used by: `AR_SEXO`

CONFIGURATION

lookupFile	`ar-sexo-1-2.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SEXO_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-sexo-f-m.txt`, chosen by a keyed hash.

Used by: `AR_SEXO`

CONFIGURATION

lookupFile	`ar-sexo-f-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SEXO_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-sexo-female-male.txt`, chosen by a keyed hash.

Used by: `AR_SEXO`

CONFIGURATION

lookupFile	`ar-sexo-female-male.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SEXO_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-sexo-femenino-masculino.txt`, chosen by a keyed hash.

Used by: `AR_SEXO`

CONFIGURATION

lookupFile	`ar-sexo-femenino-masculino.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SEXO_MUJER_VARON SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-sexo-mujer-varon.txt`, chosen by a keyed hash.

Used by: `AR_SEXO`

CONFIGURATION

lookupFile	`ar-sexo-mujer-varon.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SITUACION_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-situacion-1-2.txt`, chosen by a keyed hash.

Used by: `AR_SITUACION_CREDITICIA`

CONFIGURATION

lookupFile	`ar-situacion-1-2.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SITUACION_3_4 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-situacion-3-4.txt`, chosen by a keyed hash.

Used by: `AR_SITUACION_CREDITICIA`

CONFIGURATION

lookupFile	`ar-situacion-3-4.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SITUACION_5_6 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-situacion-5-6.txt`, chosen by a keyed hash.

Used by: `AR_SITUACION_CREDITICIA`

CONFIGURATION

lookupFile	`ar-situacion-5-6.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SITUACION_CREDITICIA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `AR_ESTADO_CREDITO`.

Used by: `AR_FIN_SITUACION_CREDITICIA`

PATTERNS, TRIED IN ORDER

`(?i)(situaci[oó]n\s*)?([12])`	keep · `AR_SITUACION_1_2`
`(?i)(situaci[oó]n\s*)?([34])`	keep · `AR_SITUACION_3_4`
`(?i)(situaci[oó]n\s*)?([56])`	keep · `AR_SITUACION_5_6`
`(0*?)(?:(\d{2,4}))`	keep · `AR_CM_DIGITOS`
`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
otherwise	`AR_ESTADO_CREDITO`

CONFIGURATION

trimInput	yes
requireMask	no

AR_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `ar-sin-informacion.txt`, chosen by a keyed hash.

Used by: `AR_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	`ar-sin-informacion.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `AR_L1_TARJETA`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d[\d\s\-]{11,22}\d))`	keep · `dlpx-core:Credit Card`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_DIGITOS`.

Used by: `AR_L1_TELEFONO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\+?54[\s\-]?(?:9[\s\-]?)?)?(\(?0?(?:11|[23]\d{1,3})\)?[\s\-]+)(15[\s\-]?)?(\d{2,4})([\s\-]?)(\d{4}))`	keep · keep · keep · keep · `AR_CM_DIGITOS` · keep · `AR_CM_DIGITOS`
`(0*?)(?:(\+?54[\s\-]?(?:9[\s\-]?)?|0)?(11|[23]\d{2,3})(\d{6,8}))`	keep · keep · keep · `AR_CM_DIGITOS`
`(0*?)(?:(15[\s\-]?)?(\d{3,4})([\s\-]?)(\d{4}))`	keep · keep · `AR_CM_DIGITOS` · keep · `AR_CM_DIGITOS`
otherwise	`AR_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

AR_TENENCIA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_TENENCIA_VIVIENDA_LISTA`.

Used by: `AR_FIN_VIVIENDA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`AR_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `AR_CM_ALFANUM`
otherwise	`AR_TENENCIA_VIVIENDA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

AR_TENENCIA_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `ar-tenencia-vivienda.txt`, chosen by a keyed hash.

Used by: `AR_TENENCIA_VIVIENDA`

CONFIGURATION

lookupFile	`ar-tenencia-vivienda.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 10 patterns with `[DATO]`, and the 2,670 terms of `ar-texto-nombres.txt` with `[NOMBRE]`.

Used by: `AR_L1_TEXTO_LIBRE`, `AR_SALUD_TEXTO_CLINICO`

PATTERNS, TRIED IN ORDER

`(?<![\d.])\d{1,2}\.\d{3}\.\d{3}(?![\d.])`
`(?<!\d)(20|2[347]|3[034])-?\d{8}-?\d(?!\d)`
`(?<!\d)\d{7,8}(?!\d)`
`(?<!\d)\d{22}(?!\d)`
`[\w.+\-]+@[\w\-]+(\.[\w\-]+)+`
`(?<![\d\-])(\+?549?)?(11|[23]\d{2,3})(15)?\d{6,8}(?![\d\-])`
`(?<![\d\-])(15-?)?\d{4}-\d{4}(?![\d\-])`
`(?<!\d)\d{13,19}(?!\d)`
`(?<![A-Za-z])([A-Z]{2}\d{3}[A-Z]{2}|[A-Z]{3}\d{3}|[A-Z]\d{3}[A-Z]{3})(?![A-Za-z\d])`
`(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\d)`

CONFIGURATION

regExRedactValue	`[DATO]`
lookupFile	`ar-texto-nombres.txt`
lookupFileRedactValue	`[NOMBRE]`
isDenyList	yes

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
`ar-antecedentes.txt`	8	`AR_ANTECEDENTES_LISTA`	No registra antecedentes · Registra antecedentes · Imputado · Procesado
`ar-apellidos.txt`	408	`AR_APELLIDO`	González · Rodríguez · Gómez · Fernández
`ar-aptitud-laboral.txt`	4	`AR_SALUD_LABORAL_LISTA`	Apto · Apto con preexistencias · No apto · Pendiente
`ar-bandera-0-1.txt`	2	`AR_BANDERA_0_1`	0 · 1
`ar-bandera-s-n.txt`	2	`AR_BANDERA_S_N`	S · N
`ar-bandera-si-no.txt`	2	`AR_BANDERA_SI_NO`	Sí · No
`ar-bandera-true-false.txt`	2	`AR_BANDERA_TRUE_FALSE`	true · false
`ar-bandera-y-n.txt`	2	`AR_BANDERA_Y_N`	Y · N
`ar-bandera-yes-no.txt`	2	`AR_BANDERA_YES_NO`	Yes · No
`ar-barrios.txt`	124	`AR_BARRIO`	Agronomía · Almagro · Balvanera · Barracas
`ar-cie10-decimal.txt`	33	`AR_CIE10_DECIMAL`	E11.9 · E78.5 · J45.9 · J06.9
`ar-cie10.txt`	37	`AR_CIE10`	I10 · E11 · E78 · J45
`ar-codigos-geograficos-generalizados.txt`	5,330	`AR_CODIGO_GEOGRAFICO_TABLA`	06007|06700 · 06014|06084 · 06021|06112 · 06140|06077
`ar-departamentos-generalizados.txt`	3,254	`AR_DEPARTAMENTO`	Adolfo Gonzales Chaves|Benito Juárez · Alberti|Bragado · Capitán Sarmiento|Arrecifes · Carlos Tejedor|Pehuajó
`ar-detectar-apellidos.txt`	477	`AR_L1_APELLIDO – List` `AR_L1_NOMBRE_COMPLETO – List`	González · Gonzalez · Rodríguez · Rodriguez
`ar-detectar-nacionalidades.txt`	45	`AR_L2_NACIONALIDAD – List`	Argentina · Paraguaya · Boliviana · Venezolana
`ar-detectar-nombres.txt`	876	`AR_L1_NOMBRE – List` `AR_L1_NOMBRE_COMPLETO – List`	María · Maria · Juan · José
`ar-diagnosticos.txt`	30	`AR_DIAGNOSTICO_TEXTO`	Hipertensión arterial · Diabetes mellitus tipo 2 · Asma · Lumbalgia
`ar-direcciones.txt`	4,000	`AR_DIRECCION`	Calle 130 N° 1082 · Estrada 335 PB 1 · Calle 23 N° 2702 · Estrada 765
`ar-discapacidades.txt`	8	`AR_DISCAPACIDAD_TIPO`	Motora · Auditiva · Visual · Visceral
`ar-empleadores.txt`	24	`AR_EMPLEADOR`	Comercializadora del Plata S.A. · Construcciones Andinas S.R.L. · Transportes La Pampa S.A. · Supermercados El Hornero S.A.

FILE	LINES	USED BY	FIRST LINES
ar-empresas.txt	24	AR_EMPRESA	Comercializadora del Plata S.A. · Construcciones Andinas S.R.L. · Transportes La Pampa S.A. · Supermercados El Hornero S.A.
ar-establecimientos-educativos.txt	12	AR_ESTABLECIMIENTO_EDUCATIVO	Escuela N° 12 Domingo F. Sarmiento · Escuela Primaria N° 45 · Escuela de Educación Secundaria N° 3 · Escuela Técnica N° 8
ar-estado-civil-codigos.txt	6	AR_ESTADO_CIVIL_CODIGO	1 · 2 · 3 · 4
ar-estado-civil.txt	6	AR_ESTADO_CIVIL_LISTA	Soltero/a · Casado/a · Unión convivencial · Separado/a de hecho
ar-estados-credito.txt	10	AR_ESTADO_CREDITO	Normal · Riesgo bajo · Riesgo medio · Riesgo alto
ar-grupos-sanguineos.txt	8	AR_GRUPO_SANGUINEO	A+ · A- · B+ · B-
ar-identidades-genero.txt	7	AR_IDENTIDAD_GENERO_LISTA	Mujer cis · Varón cis · Mujer trans / travesti · Varón trans / masculinidad trans
ar-lenguas.txt	12	AR_LENGUA_LISTA	Español · Guaraní · Quechua · Mapuzungun
ar-localidades-generalizadas.txt	55,794	AR_LOCALIDAD	Adolfo Alsina|Saavedra · Adolfo Gonzales Chaves|Benito Juárez · Alberti|Bragado · Capitán Sarmiento|Arrecifes
ar-medicamentos.txt	24	AR_MEDICAMENTO_LISTA	Paracetamol · Ibuprofeno · Diclofenac · Dipirona
ar-monotributo-a-d.txt	4	AR_MONOTRIBUTO_A_D	A · B · C · D
ar-monotributo-e-h.txt	4	AR_MONOTRIBUTO_E_H	E · F · G · H
ar-monotributo-i-k.txt	3	AR_MONOTRIBUTO_I_K	I · J · K
ar-nacionalidades.txt	14	AR_NACIONALIDAD	Argentina · Paraguaya · Boliviana · Venezolana
ar-nivel-educativo-codigos.txt	10	AR_NIVEL_EDUCATIVO_CODIGO	1 · 2 · 3 · 4
ar-nivel-educativo.txt	10	AR_NIVEL_EDUCATIVO_LISTA	Sin instrucción · Primario incompleto · Primario completo · Secundario incompleto
ar-nombres.txt	756	AR_NOMBRE	María · Juan · José · Carlos
ar-obras-sociales.txt	19	AR_OBRA_SOCIAL	PAMI · IOMA · OSDE · Swiss Medical
ar-ocupaciones.txt	35	AR_OCUPACION	Empleado administrativo · Vendedor · Cajero · Chofer
ar-opiniones-politicas.txt	7	AR_OPINION_POLITICA_LISTA	Izquierda · Centroizquierda · Centro · Centroderecha
ar-orientaciones-sexuales.txt	8	AR_ORIENTACION_SEXUAL_LISTA	Heterosexual · Gay · Lesbiana · Bisexual
ar-origen-etnico.txt	4	AR_ORIGEN_ETNICO_LISTA	Indígena o descendiente de pueblos indígenas u originarios · Afrodescendiente · Ninguno · Prefiere no responder
ar-partidos-politicos.txt	29	AR_PARTIDO_POLITICO_LISTA	Partido Justicialista · Unión Cívica Radical · Propuesta Republicana (PRO) · La Libertad Avanza
ar-procedimientos.txt	10	AR_PROCEDIMIENTO_TEXTO	Consulta médica en consultorio · Consulta de guardia · Hemograma completo · Glucemia

FILE	LINES	USED BY	FIRST LINES
ar-programas-sociales.txt	13	AR_PROGRAMA_SOCIAL_LISTA	Asignación Universal por Hijo · Asignación por Embarazo · Prestación Alimentar · Progresar
ar-pueblos-indigenas.txt	20	AR_PUEBLO_INDIGENA_LISTA	Mapuche · Guaraní · Diaguita · Kolla
ar-religiones.txt	11	AR_RELIGION_LISTA	Católica · Evangélica · Pentecostal · Testigo de Jehová
ar-sexo-1-2.txt	2	AR_SEXO_1_2	1 · 2
ar-sexo-f-m.txt	2	AR_SEXO_F_M	F · M
ar-sexo-female-male.txt	2	AR_SEXO_FEMALE_MALE	Female · Male
ar-sexo-femenino-masculino.txt	2	AR_SEXO_FEMENINO_MASCULINO	Femenino · Masculino
ar-sexo-mujer-varon.txt	2	AR_SEXO_MUJER_VARON	Mujer · Varón
ar-sin-informacion.txt	1	AR_SUPRIMIR	Sin información
ar-situacion-1-2.txt	2	AR_SITUACION_1_2	1 · 2
ar-situacion-3-4.txt	2	AR_SITUACION_3_4	3 · 4
ar-situacion-5-6.txt	2	AR_SITUACION_5_6	5 · 6
ar-tenencia-vivienda.txt	6	AR_TENENCIA_VIVIENDA_LISTA	Propietario de la vivienda y el terreno · Propietario solo de la vivienda · Inquilino · Ocupante por préstamo
ar-texto-nombres.txt	2,670	AR_TEXTO_LIBRE	María · MARÍA · Maria · MARIA

APPENDIX C

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 `producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `fantasia` `comercial` `archivo` `calle` `via` `barrio` `localidad` `municipio` `ciudad` `partido` `departamento` `depto` `dpto` `provincia` `pais` `banco` `sucursal` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `establecimiento` `institucion` `curso` `materia` `documento` `doc` `centro` `unidad` `clinica` `hospital` `sanatorio` `obra` `prepaga` `area` `dependencia` `reparticion` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `sindicato` `gremio` `religion` `pueblo` `lengua` `lugar` `sede` `local` `tienda` `deposito` `proveedor` `convenio` `contrato` `poliza` `seguro` `aseguradora` `entidad` `organismo` `organizacion` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `comprobante` `pago` `forma` `zona` `ruta` `linea` `actividad` `rubro` `sector` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `agente` `trabajador` `contratado` `alumno` `estudiante` `deudor` `codeudor` `garante` `fiador` `tomador` `propietario` `inquilino` `locatario` `locador` `conductor` `tutor` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `concubino` `conviviente` `contacto` `referencia` `victima` `denunciante` `denunciado` `imputado` `procesado` `testigo` `medico` `docente` `socio` `heredero` `causante` `donante` `curador` `jubilado` `pensionado` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner` `completo` `apellidos?` `usuario` `corto` `largo`

E2 `producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `fantasia` `comercial` `archivo` `calle` `via` `barrio` `localidad` `municipio` `ciudad` `partido` `departamento` `depto` `dpto` `provincia` `pais` `banco` `sucursal` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `establecimiento` `institucion` `curso` `materia` `documento` `doc` `centro` `unidad` `clinica` `hospital` `sanatorio` `obra` `prepaga` `area` `dependencia` `reparticion` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `sindicato` `gremio` `religion` `pueblo` `lengua` `lugar` `sede` `local` `tienda` `deposito` `proveedor` `convenio` `contrato` `poliza` `seguro` `aseguradora` `entidad` `organismo` `organizacion` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `comprobante` `pago` `forma` `zona` `ruta` `linea` `actividad` `rubro` `sector` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `agente` `trabajador` `contratado` `alumno` `estudiante` `deudor` `codeudor` `garante` `fiador` `tomador` `propietario` `inquilino` `locatario` `locador` `conductor` `tutor` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `concubino` `conviviente` `contacto` `referencia` `victima` `denunciante` `denunciado` `imputado` `procesado` `testigo` `medico` `docente` `socio` `heredero` `causante` `donante` `curador` `jubilado` `pensionado` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner`

E3	`producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `fantasia` `comercial` `archivo` `calle` `via` `barrio` `localidad` `municipio` `ciudad` `partido` `departamento` `depto` `dpto` `provincia` `pais` `banco` `sucursal` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `colegio` `escuela` `establecimiento` `institucion` `curso` `materia` `documento` `doc` `centro` `unidad` `clinica` `hospital` `sanatorio` `obra` `prepaga` `area` `dependencia` `reparticion` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `sindicato` `gremio` `religion` `pueblo` `lengua` `lugar` `sede` `local` `tienda` `deposito` `proveedor` `convenio` `contrato` `poliza` `seguro` `aseguradora` `entidad` `organismo` `organizacion` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `comprobante` `pago` `forma` `zona` `ruta` `linea` `actividad` `rubro` `sector` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `agente` `trabajador` `contratado` `alumno` `estudiante` `deudor` `codeudor` `garante` `fiador` `tomador` `propietario` `inquilino` `locatario` `locador` `conductor` `tutor` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `concubino` `conviviente` `contacto` `referencia` `victima` `denunciante` `denunciado` `imputado` `procesado` `testigo` `medico` `docente` `socio` `heredero` `causante` `donante` `curador` `jubilado` `pensionado` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner` `full` `complete` `last` `first`
E4	`ip` `mac` `email` `e_?mail` `correo` `electr[oó]nica` `web` `url` `tipo` `id` `general` `nacional` `provincial` `t[eé]cnica` `regional`
E5	`ip` `mac` `email` `e_?mail` `web` `url` `type` `id`
E6	`producto` `catastral` `primaria` `for[aá]nea` `valor` `bancaria` `virtual` `[uú]nica`
E7	`id` `cd` `cod` `codigo` `tipo` `fecha` `estado` `num` `nro`
E8	`id` `tipo` `codigo` `fecha` `estado` `cola` `log`

APPENDIX D

Profile set and classifiers

The profile set `AR – Ley 25.326 – v2` runs these 150 classifiers, with an assignment threshold of 60%.

Ley 25.326 - datos personales y sensibles

CLASSIFIER	KIND	DOMAIN
AR_L1_DNI – Path	COLUMN NAME	AR_L1_DNI
AR_L1_DNI – Type	DATA TYPE	AR_L1_DNI
AR_L1_DNI – Regex	VALUE FORMAT	AR_L1_DNI
AR_L1_CUIT – Path	COLUMN NAME	AR_L1_CUIT
AR_L1_CUIT – Regex	VALUE FORMAT	AR_L1_CUIT
AR_L1_TRAMITE_DNI – Path	COLUMN NAME	AR_L1_TRAMITE_DNI
AR_L1_TRAMITE_DNI – Regex	VALUE FORMAT	AR_L1_TRAMITE_DNI
AR_L1_DOCUMENTO_EXTRANJERO – Path	COLUMN NAME	AR_L1_DOCUMENTO_EXTRANJERO
AR_L1_PASAPORTE – Path	COLUMN NAME	AR_L1_PASAPORTE
AR_L1_PASAPORTE – Regex	VALUE FORMAT	AR_L1_PASAPORTE
AR_L1_REGISTRO_CIVIL – Path	COLUMN NAME	AR_L1_REGISTRO_CIVIL
AR_L1_MATRICULA_PROFESIONAL – Path	COLUMN NAME	AR_L1_MATRICULA_PROFESIONAL
AR_L1_NOMBRE – Path	COLUMN NAME	AR_L1_NOMBRE
AR_L1_NOMBRE – List	KNOWN VALUES	AR_L1_NOMBRE
AR_L1_APELLIDO – Path	COLUMN NAME	AR_L1_APELLIDO
AR_L1_APELLIDO – List	KNOWN VALUES	AR_L1_APELLIDO
AR_L1_NOMBRE_COMPLETO – Path	COLUMN NAME	AR_L1_NOMBRE_COMPLETO
AR_L1_NOMBRE_COMPLETO – List	KNOWN VALUES	AR_L1_NOMBRE_COMPLETO
AR_L1_RAZON_SOCIAL – Path	COLUMN NAME	AR_L1_RAZON_SOCIAL
AR_L1_RAZON_SOCIAL – Regex	VALUE FORMAT	AR_L1_RAZON_SOCIAL
AR_L1_EMAIL – Path	COLUMN NAME	AR_L1_EMAIL
AR_L1_EMAIL – Type	DATA TYPE	AR_L1_EMAIL
AR_L1_EMAIL – Regex	VALUE FORMAT	AR_L1_EMAIL
AR_L1_TELEFONO – Path	COLUMN NAME	AR_L1_TELEFONO
AR_L1_TELEFONO – Regex	VALUE FORMAT	AR_L1_TELEFONO
AR_L1_DIRECCION – Path	COLUMN NAME	AR_L1_DIRECCION
AR_L1_DIRECCION – Type	DATA TYPE	AR_L1_DIRECCION
AR_L1_DIRECCION – Regex	VALUE FORMAT	AR_L1_DIRECCION
AR_L1_DIRECCION_COMPLEMENTO – Path	COLUMN NAME	AR_L1_DIRECCION_COMPLEMENTO
AR_L1_CBU – Path	COLUMN NAME	AR_L1_CBU
AR_L1_CBU – Regex	VALUE FORMAT	AR_L1_CBU
AR_L1_ALIAS_CBU – Path	COLUMN NAME	AR_L1_ALIAS_CBU

CLASSIFIER	KIND	DOMAIN
AR_L1_ALIAS_CBU – Regex	VALUE FORMAT	AR_L1_ALIAS_CBU
AR_L1_CUENTA_BANCARIA – Path	COLUMN NAME	AR_L1_CUENTA_BANCARIA
AR_L1_TARJETA – Path	COLUMN NAME	AR_L1_TARJETA
AR_L1_TARJETA – Regex	VALUE FORMAT	AR_L1_TARJETA
AR_L1_IP – Path	COLUMN NAME	AR_L1_IP
AR_L1_IP – Regex	VALUE FORMAT	AR_L1_IP
AR_L1_DISPOSITIVO – Path	COLUMN NAME	AR_L1_DISPOSITIVO
AR_L1_DISPOSITIVO – Regex	VALUE FORMAT	AR_L1_DISPOSITIVO
AR_L1_DOMINIO – Path	COLUMN NAME	AR_L1_DOMINIO
AR_L1_DOMINIO – Regex	VALUE FORMAT	AR_L1_DOMINIO
AR_L1_VEHICULO – Path	COLUMN NAME	AR_L1_VEHICULO
AR_L1_VEHICULO – Regex	VALUE FORMAT	AR_L1_VEHICULO
AR_L1_INMUEBLE – Path	COLUMN NAME	AR_L1_INMUEBLE
AR_L1_CONTRATO – Path	COLUMN NAME	AR_L1_CONTRATO
AR_L1_USUARIO – Path	COLUMN NAME	AR_L1_USUARIO
AR_L1_CREDENCIAL – Path	COLUMN NAME	AR_L1_CREDENCIAL
AR_L1_CREDENCIAL – Regex	VALUE FORMAT	AR_L1_CREDENCIAL
AR_L1_GEOLOCALIZACION – Path	COLUMN NAME	AR_L1_GEOLOCALIZACION
AR_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	AR_L1_GEOLOCALIZACION
AR_L1_TEXTO_LIBRE – Path	COLUMN NAME	AR_L1_TEXTO_LIBRE
AR_L1_TEXTO_LIBRE – Type	DATA TYPE	AR_L1_TEXTO_LIBRE
AR_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	AR_L1_TEXTO_LIBRE
AR_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	AR_L2_FECHA_NACIMIENTO
AR_L2_FECHA_NACIMIENTO – Type	DATA TYPE	AR_L2_FECHA_NACIMIENTO
AR_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	AR_L2_ANIO_NACIMIENTO
AR_L2_ANIO_NACIMIENTO – Type	DATA TYPE	AR_L2_ANIO_NACIMIENTO
AR_L2_EDAD – Path	COLUMN NAME	AR_L2_EDAD
AR_L2_EDAD – Type	DATA TYPE	AR_L2_EDAD
AR_L2_FECHA_EVENTO – Path	COLUMN NAME	AR_L2_FECHA_EVENTO
AR_L2_FECHA_EVENTO – Type	DATA TYPE	AR_L2_FECHA_EVENTO
AR_L2_SEXO – Path	COLUMN NAME	AR_L2_SEXO
AR_L2_SEXO – Values	VALUE FORMAT	AR_L2_SEXO
AR_L2_LOCALIDAD – Path	COLUMN NAME	AR_L2_LOCALIDAD
AR_L2_LOCALIDAD – Values	VALUE FORMAT	AR_L2_LOCALIDAD
AR_L2_DEPARTAMENTO – Path	COLUMN NAME	AR_L2_DEPARTAMENTO
AR_L2_DEPARTAMENTO – Values	VALUE FORMAT	AR_L2_DEPARTAMENTO
AR_L2_CODIGO_GEOGRAFICO – Path	COLUMN NAME	AR_L2_CODIGO_GEOGRAFICO

CLASSIFIER	KIND	DOMAIN
AR_L2_CODIGO_GEOGRAFICO – Regex	VALUE FORMAT	AR_L2_CODIGO_GEOGRAFICO
AR_L2_CODIGO_POSTAL – Path	COLUMN NAME	AR_L2_CODIGO_POSTAL
AR_L2_CODIGO_POSTAL – Type	DATA TYPE	AR_L2_CODIGO_POSTAL
AR_L2_CODIGO_POSTAL – Regex	VALUE FORMAT	AR_L2_CODIGO_POSTAL
AR_L2_BARRIO – Path	COLUMN NAME	AR_L2_BARRIO
AR_L2_NACIONALIDAD – Path	COLUMN NAME	AR_L2_NACIONALIDAD
AR_L2_NACIONALIDAD – List	KNOWN VALUES	AR_L2_NACIONALIDAD
AR_L2_ESTADO_CIVIL – Path	COLUMN NAME	AR_L2_ESTADO_CIVIL
AR_L2_ESTADO_CIVIL – Values	VALUE FORMAT	AR_L2_ESTADO_CIVIL
AR_L2_OCUPACION – Path	COLUMN NAME	AR_L2_OCUPACION
AR_L2_EMPLEADOR – Path	COLUMN NAME	AR_L2_EMPLEADOR
AR_L2_NIVEL_EDUCATIVO – Path	COLUMN NAME	AR_L2_NIVEL_EDUCATIVO
AR_L2_NIVEL_EDUCATIVO – Values	VALUE FORMAT	AR_L2_NIVEL_EDUCATIVO
AR_L2_ESTABLECIMIENTO_EDUCATIVO – Path	COLUMN NAME	AR_L2_ESTABLECIMIENTO_EDUCATIVO
AR_L2_PERSONAS_A_CARGO – Path	COLUMN NAME	AR_L2_PERSONAS_A_CARGO
AR_L2_PERSONAS_A_CARGO – Type	DATA TYPE	AR_L2_PERSONAS_A_CARGO
AR_L3_ORIGEN_ETNICO – Path	COLUMN NAME	AR_L3_ORIGEN_ETNICO
AR_L3_ORIGEN_ETNICO – Values	VALUE FORMAT	AR_L3_ORIGEN_ETNICO
AR_L3_PUEBLO_INDIGENA – Path	COLUMN NAME	AR_L3_PUEBLO_INDIGENA
AR_L3_PUEBLO_INDIGENA – Values	VALUE FORMAT	AR_L3_PUEBLO_INDIGENA
AR_L3_LENGUA_INDIGENA – Path	COLUMN NAME	AR_L3_LENGUA_INDIGENA
AR_L3_LENGUA_INDIGENA – Values	VALUE FORMAT	AR_L3_LENGUA_INDIGENA
AR_L3_RELIGION – Path	COLUMN NAME	AR_L3_RELIGION
AR_L3_RELIGION – Values	VALUE FORMAT	AR_L3_RELIGION
AR_L3_CONVICCION_FILOSOFICA – Path	COLUMN NAME	AR_L3_CONVICCION_FILOSOFICA
AR_L3_OPINION_POLITICA – Path	COLUMN NAME	AR_L3_OPINION_POLITICA
AR_L3_OPINION_POLITICA – Values	VALUE FORMAT	AR_L3_OPINION_POLITICA
AR_L3_AFILIACION_PARTIDARIA – Path	COLUMN NAME	AR_L3_AFILIACION_PARTIDARIA
AR_L3_AFILIACION_PARTIDARIA – Values	VALUE FORMAT	AR_L3_AFILIACION_PARTIDARIA
AR_L3_AFILIACION_SINDICAL – Path	COLUMN NAME	AR_L3_AFILIACION_SINDICAL
AR_L3_AFILIACION_SINDICAL – Values	VALUE FORMAT	AR_L3_AFILIACION_SINDICAL
AR_L3_BIOMETRICO – Path	COLUMN NAME	AR_L3_BIOMETRICO
AR_L3_BIOMETRICO – Type	DATA TYPE	AR_L3_BIOMETRICO
AR_L3_GENETICO – Path	COLUMN NAME	AR_L3_GENETICO
AR_L3_GENETICO – Regex	VALUE FORMAT	AR_L3_GENETICO
AR_L3_ORIENTACION_SEXUAL – Path	COLUMN NAME	AR_L3_ORIENTACION_SEXUAL
AR_L3_ORIENTACION_SEXUAL – Values	VALUE FORMAT	AR_L3_ORIENTACION_SEXUAL

CLASSIFIER	KIND	DOMAIN
AR_L3_VIDA_SEXUAL – Path	COLUMN NAME	AR_L3_VIDA_SEXUAL
AR_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	AR_L3_IDENTIDAD_GENERO
AR_L3_IDENTIDAD_GENERO – Values	VALUE FORMAT	AR_L3_IDENTIDAD_GENERO
AR_L3_VICTIMA – Path	COLUMN NAME	AR_L3_VICTIMA
AR_SALUD_IDENTIFICADOR – Path	COLUMN NAME	AR_SALUD_IDENTIFICADOR
AR_SALUD_COBERTURA – Path	COLUMN NAME	AR_SALUD_COBERTURA
AR_SALUD_COBERTURA – Values	VALUE FORMAT	AR_SALUD_COBERTURA
AR_SALUD_COBERTURA – Regex	VALUE FORMAT	AR_SALUD_COBERTURA
AR_SALUD_DIAGNOSTICO – Path	COLUMN NAME	AR_SALUD_DIAGNOSTICO
AR_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	AR_SALUD_DIAGNOSTICO
AR_SALUD_PROCEDIMIENTO – Path	COLUMN NAME	AR_SALUD_PROCEDIMIENTO
AR_SALUD_MEDICAMENTO – Path	COLUMN NAME	AR_SALUD_MEDICAMENTO
AR_SALUD_MEDICAMENTO – Values	VALUE FORMAT	AR_SALUD_MEDICAMENTO
AR_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	AR_SALUD_TEXTO_CLINICO
AR_SALUD_TEXTO_CLINICO – Type	DATA TYPE	AR_SALUD_TEXTO_CLINICO
AR_SALUD_RESULTADO_ESTUDIO – Path	COLUMN NAME	AR_SALUD_RESULTADO_ESTUDIO
AR_SALUD_VIH – Path	COLUMN NAME	AR_SALUD_VIH
AR_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	AR_SALUD_GRUPO_SANGUINEO
AR_SALUD_GRUPO_SANGUINEO – Values	VALUE FORMAT	AR_SALUD_GRUPO_SANGUINEO
AR_SALUD_DISCAPACIDAD – Path	COLUMN NAME	AR_SALUD_DISCAPACIDAD
AR_SALUD_DISCAPACIDAD – Values	VALUE FORMAT	AR_SALUD_DISCAPACIDAD
AR_SALUD_OCUPACIONAL – Path	COLUMN NAME	AR_SALUD_OCUPACIONAL
AR_SALUD_OCUPACIONAL – Values	VALUE FORMAT	AR_SALUD_OCUPACIONAL
AR_SALUD_REPRODUCTIVA – Path	COLUMN NAME	AR_SALUD_REPRODUCTIVA
AR_SALUD_MENTAL – Path	COLUMN NAME	AR_SALUD_MENTAL
AR_FIN_SITUACION_CREDITICIA – Path	COLUMN NAME	AR_FIN_SITUACION_CREDITICIA
AR_FIN_SITUACION_CREDITICIA – Values	VALUE FORMAT	AR_FIN_SITUACION_CREDITICIA
AR_FIN_DEUDA – Path	COLUMN NAME	AR_FIN_DEUDA
AR_FIN_DEUDA – Type	DATA TYPE	AR_FIN_DEUDA
AR_FIN_INGRESOS – Path	COLUMN NAME	AR_FIN_INGRESOS
AR_FIN_INGRESOS – Type	DATA TYPE	AR_FIN_INGRESOS
AR_FIN_PATRIMONIO – Path	COLUMN NAME	AR_FIN_PATRIMONIO
AR_FIN_PATRIMONIO – Type	DATA TYPE	AR_FIN_PATRIMONIO
AR_FIN_JUBILACION – Path	COLUMN NAME	AR_FIN_JUBILACION
AR_FIN_JUBILACION – Type	DATA TYPE	AR_FIN_JUBILACION
AR_FIN_PROGRAMA_SOCIAL – Path	COLUMN NAME	AR_FIN_PROGRAMA_SOCIAL
AR_FIN_PROGRAMA_SOCIAL – Values	VALUE FORMAT	AR_FIN_PROGRAMA_SOCIAL

CLASSIFIER	KIND	DOMAIN
AR_FIN_MONOTRIBUTO – Path	COLUMN NAME	AR_FIN_MONOTRIBUTO
AR_FIN_MONOTRIBUTO – Type	DATA TYPE	AR_FIN_MONOTRIBUTO
AR_FIN_VIVIENDA – Path	COLUMN NAME	AR_FIN_VIVIENDA
AR_FIN_VIVIENDA – Values	VALUE FORMAT	AR_FIN_VIVIENDA
AR_PENAL_ANTECEDENTES – Path	COLUMN NAME	AR_PENAL_ANTECEDENTES
AR_PENAL_EXPEDIENTE – Path	COLUMN NAME	AR_PENAL_EXPEDIENTE
AR_PENAL_EXPEDIENTE – Regex	VALUE FORMAT	AR_PENAL_EXPEDIENTE