DELPHIX MASKING · PROFILE SET

Jamaica — Data Protection Act, 2020

Discovery and masking of Jamaican personal data: the TRN and other identity numbers, names and contact, quasi-identifiers, the sensitive personal data of section 2 — biometric data, filiation, beliefs, health, sex life and offences among them — and financial data.

74	129	83
DOMAINS	CLASSIFIERS	ALGORITHMS

Profile set `JM – Data Protection Act 2020 – v1`

Version 1 of October 11, 2026 · Assignment threshold 60%

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	**About this profile set**	
2	**The Data Protection Act, 2020 at a glance**	
3	**How sensitive data is discovered**	
4	**How data is masked**	
5	**Essential and extended packs**	
6	**Domains at a glance**	

PART 7 · DIRECT IDENTIFIERS

7.1	**Taxpayer Registration Number (TRN)**	JM_L1_TRN
7.2	**NIS number**	JM_L1_NIS_NUMBER
7.3	**Passport**	JM_L1_PASSPORT
7.4	**Voter ID**	JM_L1_VOTER_ID
7.5	**Driver's licence**	JM_L1_DRIVERS_LICENCE
7.6	**Immigration documents**	JM_L1_IMMIGRATION_DOCUMENT
7.7	**Civil registry entry**	JM_L1_VITAL_RECORD
7.8	**Given names**	JM_L1_GIVEN_NAME
7.9	**Surnames**	JM_L1_SURNAME
7.10	**Full name**	JM_L1_FULL_NAME
7.11	**E-mail**	JM_L1_EMAIL
7.12	**Phone**	JM_L1_PHONE
7.13	**Address**	JM_L1_ADDRESS
7.14	**Address detail**	JM_L1_ADDRESS_DETAIL
7.15	**Bank account**	JM_L1_BANK_ACCOUNT
7.16	**Payment card**	JM_L1_PAYMENT_CARD
7.17	**IP address**	JM_L1_IP_ADDRESS
7.18	**Device identifier**	JM_L1_DEVICE_ID
7.19	**Licence plate**	JM_L1_LICENCE_PLATE
7.20	**VIN and engine number**	JM_L1_VIN
7.21	**Land title and valuation number**	JM_L1_LAND_TITLE
7.22	**Customer, contract or account number**	JM_L1_CONTRACT_NUMBER
7.23	**Username and social media**	JM_L1_USERNAME
7.24	**Credential**	JM_L1_CREDENTIAL
7.25	**Geolocation**	JM_L1_GEOLOCATION

7.26	Free text	JM_L1_FREE_TEXT

PART 8 · QUASI-IDENTIFIERS

8.1	Birth date	JM_L2_BIRTH_DATE
8.2	Year of birth	JM_L2_BIRTH_YEAR
8.3	Age	JM_L2_AGE
8.4	Life event dates	JM_L2_EVENT_DATE
8.5	Sex	JM_L2_SEX
8.6	Town	JM_L2_TOWN
8.7	Neighbourhood or housing scheme	JM_L2_NEIGHBOURHOOD
8.8	Nationality	JM_L2_NATIONALITY
8.9	Marital and union status	JM_L2_MARITAL_STATUS
8.10	Occupation	JM_L2_OCCUPATION
8.11	Employer	JM_L2_EMPLOYER
8.12	Education	JM_L2_EDUCATION
8.13	School	JM_L2_SCHOOL
8.14	Children and dependants	JM_L2_DEPENDANTS

PART 9 · SENSITIVE PERSONAL DATA

9.1	Genetic data	JM_L3_GENETIC
9.2	Biometric data	JM_L3_BIOMETRIC
9.3	Height	JM_L3_HEIGHT
9.4	Eye colour	JM_L3_EYE_COLOUR
9.5	Filiation	JM_L3_FILIATION
9.6	Racial or ethnic origin	JM_L3_ETHNICITY
9.7	Religious beliefs	JM_L3_RELIGION
9.8	Philosophical and similar beliefs	JM_L3_BELIEF
9.9	Political opinions	JM_L3_POLITICAL_OPINION
9.10	Party preference or membership	JM_L3_POLITICAL_AFFILIATION
9.11	Trade union membership	JM_L3_TRADE_UNION
9.12	Sexual orientation	JM_L3_SEXUAL_ORIENTATION
9.13	Sex life	JM_L3_SEXUAL_LIFE
9.14	Gender identity	JM_L3_GENDER_IDENTITY

PART 10 · PHYSICAL OR MENTAL HEALTH OR CONDITION

10.1	Health identifiers	JM_HEALTH_ID
10.2	Diagnosis	JM_HEALTH_DIAGNOSIS
10.3	Medication	JM_HEALTH_MEDICATION

10.4	Clinical notes	JM_HEALTH_CLINICAL_TEXT
10.5	Test results	JM_HEALTH_TEST_RESULT
10.6	Blood group	JM_HEALTH_BLOOD_GROUP
10.7	Disability	JM_HEALTH_DISABILITY
10.8	Reproductive health	JM_HEALTH_REPRODUCTIVE
10.9	Mental health	JM_HEALTH_MENTAL

PART 11 · FINANCIAL DATA

11.1	Credit reference	JM_FIN_CREDIT_REFERENCE
11.2	Debt amount	JM_FIN_DEBT
11.3	Income	JM_FIN_INCOME
11.4	Assets	JM_FIN_ASSETS
11.5	Pension amount	JM_FIN_PENSION
11.6	NIS benefit	JM_FIN_NIS_BENEFIT
11.7	Social programme	JM_FIN_SOCIAL_PROGRAMME
11.8	Poverty and socio-economic status	JM_FIN_POVERTY
11.9	Housing tenure	JM_FIN_HOUSING

PART 12 · OFFENCES AND PROCEEDINGS

12.1	Offences and proceedings	JM_PENAL_CRIMINAL_RECORD
12.2	Case number	JM_PENAL_CASE_NUMBER
13	Where people live: towns	
14	Limits	
15	Verification	
16	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	
D	Profile set and classifiers	

1

About this profile set

This profile set finds the personal data in a Jamaican database and masks it, so that a non-production copy — for testing, development, training or analytics — no longer identifies anyone.

Masking only names and TRNs does not get there: a birth date, a sex and a town of a few thousand people are enough to point at one person. The set works on the layers where the risk is:

- **Direct identifiers** — TRN, NIS number, passport, voter ID, driver's licence, immigration documents, civil registry entries, names, contact, accounts and cards, land titles, devices, vehicles, free text.
- **Quasi-identifiers** — birth date, age, sex, town, neighbourhood, nationality, marital and union status, occupation, employer, education.
- **Sensitive personal data** — the categories of section 2: genetic and biometric data (which the Act extends to photographs, height, eye colour and blood type), filiation, racial or ethnic origin, political opinions, religious, philosophical and similar beliefs, trade union membership and sex life — and, beyond the list, gender identity.
- **Health** — physical or mental health or condition, also sensitive: health identifiers, diagnoses, medications, clinical notes, test results, blood group, disability, reproductive and mental health.
- **Financial data** — credit references, debt, income, assets, pensions, NIS benefits, social programmes, poverty and housing tenure. Not sensitive under the Act, but kept confidential by banking and credit reporting law.
- **Offences and proceedings** — records, charges, outcomes and case numbers: section 2 makes the alleged commission of an offence sensitive, not only a conviction.

On a Masking Engine the set is one profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those build on — and the lookup files they read. The appendices list every one of them with its full configuration. Some domains use algorithms that come with the Masking Engine — CM Numeric, Credit Card, BloodType SL — and those are named but not included.

The assignment threshold is 60%. An unambiguous column name reaches it alone; an ambiguous one — `NAME`, `RESULT`, `CITY` — needs the values to agree. A column with a meaningless name (`FIELD1`, `PFNOM`, `REMARKS`) is still found when its values have a recognizable shape or vocabulary: a TRN, an 876 phone number, a plate, a town, a full name.

Column names are recognized in English and in the abbreviations of Jamaican systems (`TRN`, `NIS_NO`, `NIN`, `NHF_CARD_NO`, `NHT_NUMBER`, `DOB`).

> Before masking, inventory the binary columns (BLOBs, images, PDFs). Onboarding processes often store a scan of the TRN card, the driver's licence or the passport — and a photograph is biometric data under section 2. Report those columns as residual risk.

2

The Data Protection Act, 2020 at a glance

The Data Protection Act, 2020 was passed by the Parliament of Jamaica in 2020 and came into operation on 1 December 2023, on a day the Minister appointed by notice in the Gazette (s. 1). Data controllers were given until 31 May 2024 to register with the Information Commissioner. It follows the structure of the United Kingdom's Data Protection Act 1998, with eight data protection standards, and borrows from the GDPR its security measures, its breach reporting and its fines.

What matters for a copy of production data:

- **Personal data** is information, however stored, relating to a living individual — or to one who died less than thirty years ago — who can be identified from that information alone or together with other information in the possession of, or likely to come into the possession of, the data controller, including any opinion about the individual (s. 2).
- **Processing** includes adapting, altering, combining and "rendering the data anonymous" (s. 2). Copying production data to a test environment is processing; so is masking it.
- **Sensitive personal data** is: (a) genetic data or biometric data; (b) filiation, or racial or ethnic origin; (c) political opinions, philosophical beliefs, religious beliefs or other beliefs of a similar nature; (d) membership in any trade union; (e) physical or mental health or condition; (f) sex life; (g) the alleged commission of any offence, or any proceedings for an offence alleged to have been committed (s. 2).
- **Biometric data** includes physical characteristics — the photograph or other facial image, finger, palm, toe and foot prints, iris and retina scans, **blood type, height**, vein pattern and **eye colour** — and behavioural ones: gait, signature, keystrokes and voice (s. 2). An identity photograph or a height column in a personnel file is sensitive data.
- **Eight standards** (ss. 22–31): fair and lawful processing, with at least one condition of section 23 and, for sensitive data, one of section 24; specified and lawful purposes, and no further processing incompatible with them (s. 25); data adequate, relevant and limited to what is necessary (s. 26); accurate (s. 27); not kept longer than necessary (s. 28); processed in accordance with the data subject's rights (s. 29); kept secure (s. 30); not transferred out of Jamaica without adequate protection (s. 31).
- **Security.** The seventh standard requires appropriate technical and organisational measures, and these include **pseudonymisation and encryption of personal data** and a process for regularly testing their effectiveness (s. 30(6)). A data processor acts only under a written contract and on the controller's instructions (s. 30(5)).
- **Breaking pseudonymisation is an offence.** A person who, wilfully and without lawful authority, uses any means to breach the pseudonymisation or encryption applied to personal data commits an offence — up to two million dollars in a Parish Court, or a fine without limit in a Circuit Court (s. 30(7)).
- **Breaches** of the standards or of security are reported to the Commissioner within seventy-two hours after the controller becomes aware of them (s. 21(3)). Processing in contravention of the standards is an offence punishable by a fine of up to two million dollars or two years' imprisonment in a Parish Court, or a fine or seven years in a Circuit Court (s. 21(2)); a body corporate is also liable to a fine of up to **four percent of its annual gross worldwide turnover** (s. 68).
- **Registration and officers.** Controllers register with the Commissioner before processing (s. 15); those that process sensitive personal data, or process on a large scale, appoint a data protection officer (s. 20), and every controller submits a data protection impact assessment each year (s. 45).
- **Research, history and statistics.** Further processing only for research purposes is not incompatible with the original purpose when the data does not support measures or decisions about particular individuals and causes no substantial damage or distress (s. 37).
- **Minors.** A minor is an individual under eighteen (s. 2).
- **Supervision.** The Information Commissioner, an office established by section 4, administers the Act.

A test environment with production data is processing for purposes the data was not collected for, by people who have no need to see it, and it holds sensitive data — biometric, health and criminal data among them — outside the controls built for it. Masking is the pseudonymisation the seventh standard names: what goes to the test environment no longer identifies anyone without the key, and using means to break it is an offence of its own.

The list of sensitive data in section 2 is closed, but the set goes further where the risk is the same: it treats gender identity with the same care as sex life, and masks financial data, which banks and credit bureaus must keep confidential under other laws.

> The definition of personal data counts what the controller holds or is likely to hold. Masking is deterministic for the engine key, so whoever has both the production data and the key can link a masked row back to its source. Keep the key, and access to production, away from the people who use the masked copy. Whether a copy counts as anonymised is a legal assessment of the whole environment, not of the profile set alone.

3

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Databases pad values: a CHAR column fills them with spaces up to its length, and a numeric code kept as text often comes with zeros on the left. The profiler tests values as they come, so every format pattern first removes the spaces around the value, patterns of digits also accept zeros on the left, lists of single words are looked up word by word, and lists of names made of several words (places, categories) are held as a single value-format pattern. A column whose name says nothing — `CAMP01`, `FLD_07`, the short names of packaged systems — is found by its values alone wherever their format is distinctive: documents with a check digit, e-mail addresses, telephone numbers, cards, places, names.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

> Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

4

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

Where an algorithm that comes with the Masking Engine already does the job — CM Numeric for amounts, Credit Card, the blood group lookup — the set names it instead of creating one of its own. Those algorithms appear in the trees by their `dlpx-core:` name; they are on every engine and are not listed in Appendix A.

Padding stays where it is: the spaces around a value are kept, and zeros on the left of a number are not masked — `0012345678` becomes `00` followed by what `12345678` becomes. A value kept in a zero-filled CHAR column still joins the same value kept as a number.

> The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

5

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	12	23	10	5
Extended	74	129	83	47

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- Taxpayer Registration Number (TRN) — `JM_L1_TRN`
- NIS number — `JM_L1_NIS_NUMBER`
- Passport — `JM_L1_PASSPORT`
- Driver's licence — `JM_L1_DRIVERS_LICENCE`
- Given names — `JM_L1_GIVEN_NAME`
- Surnames — `JM_L1_SURNAME`
- Full name — `JM_L1_FULL_NAME`
- E-mail — `JM_L1_EMAIL`
- Phone — `JM_L1_PHONE`
- Address — `JM_L1_ADDRESS`
- Address detail — `JM_L1_ADDRESS_DETAIL`
- Birth date — `JM_L2_BIRTH_DATE`

> With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

6

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY	ALGORITHM
DIRECT IDENTIFIERS		
Taxpayer Registration Number (TRN) ESSENTIAL `JM_L1_TRN`	COLUMN NAME · VALUE FORMAT	`JM_CM_ALNUM`
NIS number ESSENTIAL `JM_L1_NIS_NUMBER`	COLUMN NAME	`JM_CM_ALNUM`
Passport ESSENTIAL `JM_L1_PASSPORT`	COLUMN NAME · VALUE FORMAT	`JM_CM_ALNUM`
Voter ID `JM_L1_VOTER_ID`	COLUMN NAME	`JM_CM_ALNUM`
Driver's licence ESSENTIAL `JM_L1_DRIVERS_LICENCE`	COLUMN NAME	`JM_CM_ALNUM`
Immigration documents `JM_L1_IMMIGRATION_DOCUMENT`	COLUMN NAME	`JM_CM_ALNUM`
Civil registry entry `JM_L1_VITAL_RECORD`	COLUMN NAME	`JM_CM_ALNUM`
Given names ESSENTIAL `JM_L1_GIVEN_NAME`	COLUMN NAME · KNOWN VALUES	`JM_GIVEN_NAMES`
Surnames ESSENTIAL `JM_L1_SURNAME`	COLUMN NAME · KNOWN VALUES	`JM_SURNAMES`
Full name ESSENTIAL `JM_L1_FULL_NAME`	COLUMN NAME · KNOWN VALUES	`JM_FULL_NAME`
E-mail ESSENTIAL `JM_L1_EMAIL`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`JM_EMAIL`
Phone ESSENTIAL `JM_L1_PHONE`	COLUMN NAME · VALUE FORMAT	`JM_PHONE`
Address ESSENTIAL `JM_L1_ADDRESS`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`JM_ADDRESS`
Address detail ESSENTIAL `JM_L1_ADDRESS_DETAIL`	COLUMN NAME	`JM_CM_ALNUM`
Bank account `JM_L1_BANK_ACCOUNT`	COLUMN NAME	`JM_CM_ALNUM`
Payment card `JM_L1_PAYMENT_CARD`	COLUMN NAME · VALUE FORMAT	`JM_CARD`
IP address `JM_L1_IP_ADDRESS`	COLUMN NAME · VALUE FORMAT	`JM_IP`
Device identifier `JM_L1_DEVICE_ID`	COLUMN NAME · VALUE FORMAT	`JM_CM_HEX`
Licence plate `JM_L1_LICENCE_PLATE`	COLUMN NAME · VALUE FORMAT	`JM_PLATE`

DOMAIN	FOUND BY	ALGORITHM
VIN and engine number `JM_L1_VIN`	COLUMN NAME · VALUE FORMAT	`JM_CM_ALNUM`
Land title and valuation number `JM_L1_LAND_TITLE`	COLUMN NAME · VALUE FORMAT	`JM_LAND_TITLE`
Customer, contract or account number `JM_L1_CONTRACT_NUMBER`	COLUMN NAME	`JM_CM_ALNUM`
Username and social media `JM_L1_USERNAME`	COLUMN NAME	`JM_CM_ALNUM`
Credential `JM_L1_CREDENTIAL`	COLUMN NAME · VALUE FORMAT	`JM_REDACT`
Geolocation `JM_L1_GEOLOCATION`	COLUMN NAME · VALUE FORMAT	`JM_COORDINATE`
Free text `JM_L1_FREE_TEXT`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`JM_FREE_TEXT`
QUASI-IDENTIFIERS		
Birth date ESSENTIAL `JM_L2_BIRTH_DATE`	COLUMN NAME · DATA TYPE	`JM_BIRTH_DATE`
Year of birth `JM_L2_BIRTH_YEAR`	COLUMN NAME · DATA TYPE	`JM_YEAR`
Age `JM_L2_AGE`	COLUMN NAME · DATA TYPE	`JM_AGE`
Life event dates `JM_L2_EVENT_DATE`	COLUMN NAME · DATA TYPE	`JM_EVENT_DATE`
Sex `JM_L2_SEX`	COLUMN NAME · KNOWN VALUES	`JM_SEX`
Town `JM_L2_TOWN`	COLUMN NAME · VALUE FORMAT	`JM_TOWN`
Neighbourhood or housing scheme `JM_L2_NEIGHBOURHOOD`	COLUMN NAME	`JM_NEIGHBOURHOOD`
Nationality `JM_L2_NATIONALITY`	COLUMN NAME · VALUE FORMAT	`JM_NATIONALITY`
Marital and union status `JM_L2_MARITAL_STATUS`	COLUMN NAME · VALUE FORMAT	`JM_MARITAL_STATUS`
Occupation `JM_L2_OCCUPATION`	COLUMN NAME	`JM_OCCUPATION`
Employer `JM_L2_EMPLOYER`	COLUMN NAME	`JM_EMPLOYER`
Education `JM_L2_EDUCATION`	COLUMN NAME · VALUE FORMAT	`JM_EDUCATION`
School `JM_L2_SCHOOL`	COLUMN NAME	`JM_SCHOOL`
Children and dependants `JM_L2_DEPENDANTS`	COLUMN NAME · DATA TYPE	`JM_CAPPED_COUNT`
SENSITIVE PERSONAL DATA		

DOMAIN	FOUND BY	ALGORITHM
Genetic data `JM_L3_GENETIC`	COLUMN NAME VALUE FORMAT	`JM_REDACT`
Biometric data `JM_L3_BIOMETRIC`	COLUMN NAME DATA TYPE	`JM_REDACT`
Height `JM_L3_HEIGHT`	COLUMN NAME	`JM_HEIGHT`
Eye colour `JM_L3_EYE_COLOUR`	COLUMN NAME VALUE FORMAT	`JM_EYE_COLOUR`
Filiation `JM_L3_FILIATION`	COLUMN NAME VALUE FORMAT	`JM_FILIATION`
Racial or ethnic origin `JM_L3_ETHNICITY`	COLUMN NAME VALUE FORMAT	`JM_ETHNICITY`
Religious beliefs `JM_L3_RELIGION`	COLUMN NAME VALUE FORMAT	`JM_RELIGION`
Philosophical and similar beliefs `JM_L3_BELIEF`	COLUMN NAME	`JM_SUPPRESSED_CATEGORY`
Political opinions `JM_L3_POLITICAL_OPINION`	COLUMN NAME VALUE FORMAT	`JM_POLITICAL_OPINION`
Party preference or membership `JM_L3_POLITICAL_AFFILIATION`	COLUMN NAME VALUE FORMAT	`JM_POLITICAL_PARTY`
Trade union membership `JM_L3_TRADE_UNION`	COLUMN NAME VALUE FORMAT	`JM_SUPPRESSED_CATEGORY`
Sexual orientation `JM_L3_SEXUAL_ORIENTATION`	COLUMN NAME VALUE FORMAT	`JM_SEXUAL_ORIENTATION`
Sex life `JM_L3_SEXUAL_LIFE`	COLUMN NAME	`JM_SUPPRESSED_CATEGORY`
Gender identity `JM_L3_GENDER_IDENTITY`	COLUMN NAME VALUE FORMAT	`JM_GENDER_IDENTITY`
PHYSICAL OR MENTAL HEALTH OR CONDITION		
Health identifiers `JM_HEALTH_ID`	COLUMN NAME	`JM_CM_ALNUM`
Diagnosis `JM_HEALTH_DIAGNOSIS`	COLUMN NAME VALUE FORMAT	`JM_DIAGNOSIS`
Medication `JM_HEALTH_MEDICATION`	COLUMN NAME VALUE FORMAT	`JM_MEDICATION`
Clinical notes `JM_HEALTH_CLINICAL_TEXT`	COLUMN NAME DATA TYPE	`JM_FREE_TEXT`
Test results `JM_HEALTH_TEST_RESULT`	COLUMN NAME	`JM_CM_ALNUM`
Blood group `JM_HEALTH_BLOOD_GROUP`	COLUMN NAME VALUE FORMAT	`dlpx-core:BloodType SL`
Disability `JM_HEALTH_DISABILITY`	COLUMN NAME VALUE FORMAT	`JM_DISABILITY`
Reproductive health `JM_HEALTH_REPRODUCTIVE`	COLUMN NAME	`JM_SUPPRESSED_CATEGORY`

DOMAIN	FOUND BY	ALGORITHM
Mental health `JM_HEALTH_MENTAL`	COLUMN NAME	`JM_SUPPRESSED_CATEGORY`
FINANCIAL DATA		
Credit reference `JM_FIN_CREDIT_REFERENCE`	COLUMN NAME	`JM_CREDIT`
Debt amount `JM_FIN_DEBT`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Income `JM_FIN_INCOME`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Assets `JM_FIN_ASSETS`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
Pension amount `JM_FIN_PENSION`	COLUMN NAME DATA TYPE	`dlpx-core:CM Numeric`
NIS benefit `JM_FIN_NIS_BENEFIT`	COLUMN NAME VALUE FORMAT	`JM_NIS_BENEFIT`
Social programme `JM_FIN_SOCIAL_PROGRAMME`	COLUMN NAME VALUE FORMAT	`JM_SOCIAL_PROGRAMME`
Poverty and socio-economic status `JM_FIN_POVERTY`	COLUMN NAME VALUE FORMAT	`JM_POVERTY`
Housing tenure `JM_FIN_HOUSING`	COLUMN NAME VALUE FORMAT	`JM_HOUSING`
OFFENCES AND PROCEEDINGS		
Offences and proceedings `JM_PENAL_CRIMINAL_RECORD`	COLUMN NAME	`JM_CRIMINAL_RECORD`
Case number `JM_PENAL_CASE_NUMBER`	COLUMN NAME VALUE FORMAT	`JM_CM_ALNUM`

PART 7

Direct identifiers

Data that identifies a person on its own. In Jamaica one number does most of the work: the Taxpayer Registration Number, which banks, employers, the NIS and the NHT ask for, which the driver's licence carries, and which the National Identification and Registration Act makes the national identification number of NIDS. It is masked the same way everywhere, keeping its nine digits, so a TRN still joins its tables after masking.

7.1 Taxpayer Registration Number (TRN)

JM_L1_TRN

ESSENTIAL · COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

The nine-digit number of Tax Administration Jamaica, usually written `123–456–789`. Every adult who works, banks, drives or pays tax has one; the driver's licence is issued under it, and the National Identification and Registration Act, 2021 makes it the National Identification Number (NIN) of the National Identification System. Companies have TRNs too. No check digit is published.

HOW IT IS FOUND

COLUMN NAME JM_L1_TRN — Path

90% `trn` `trn_?(no|num|number|nbr)` `taxpayer_?(registration_?)?(no|num|number|id)` `tax_?(payer_?)?reg(istration)?_?(no|num|number)` `tax_?(id|identification)(_?(no|num|number))?` `nin` `nin_?(no|number)` `nids(_?(no|num|number|id))?` `national_?(id|identification)(_?(no|num|number|card))?`

VALUE FORMAT JM_L1_TRN — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{3}[\s\-]\d{3}[\s\-]\d{3})`	70%	
`0*(?:\d{9})`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each digit is mapped to another digit, keeping the length and any separators. The mapping is one-to-one: a TRN used as a key does not collide, and the same number masks the same way in every table — also when it appears as a driver's licence number.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123–456–789	→	**110–858–568**
000123456	→	**000904292**

7.2 NIS number

JM_L1_NIS_NUMBER

ESSENTIAL · COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

The number of the National Insurance Scheme, the social security scheme of the Ministry of Labour and Social Security, on contribution records, benefit claims and payroll files.

HOW IT IS FOUND

COLUMN NAME JM_L1_NIS_NUMBER — Path

90% `nis` `nis_?(no|num|number|nbr|id|card)` `national_?insurance(_?(no|num|number|scheme_?(no|number))?` `ni_?(no|num|number)` `insured_?(person_?)?(no|num|number)` `social_?security(_?(no|num|number))?` `ssn`

HOW IT IS MASKED

Character by character, keeping length, letters and separators.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A123456	→	**E854099**

7.3 Passport

JM_L1_PASSPORT

ESSENTIAL · COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

Passport numbers, Jamaican or foreign — Jamaican passports are issued by the Passport, Immigration and Citizenship Agency (PICA).

HOW IT IS FOUND

COLUMN NAME JM_L1_PASSPORT — Path

85% `passport[a-z_]*` `pass_?port_?(no|num|number)` `pp_?(no|num|number)` `travel_?document(_?(no|num|number))?`

VALUE FORMAT JM_L1_PASSPORT — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{1,2}\d{6,8}`	30%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character: letters stay letters and digits stay digits.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A0123456	→	**I3805459**

7.4 Voter ID

JM_L1_VOTER_ID

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The number of the voter identification card of the Electoral Office of Jamaica, widely accepted as identification, and the voter's registration details.

HOW IT IS FOUND

> **COLUMN NAME** JM_L1_VOTER_ID — Path
>
> **85%** `voter_?(id|card|reg|registration)(_?(no|num|number|card))?` `voters_?(id|card|reg|registration)(_?(no|num|number))?` `elector(al)?_?(id|no|num|number|card|reg|registration)(_?(no|num|number))?` `eoj_?(no|id|reg|number)` `polling_?(division|station)_?(no|number)?`

HOW IT IS MASKED

Character by character, keeping the format.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456	→	**904292**

7.5 Driver's licence

JM_L1_DRIVERS_LICENCE

ESSENTIAL | COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The driver's licence number, which in Jamaica is the holder's TRN.

HOW IT IS FOUND

> **COLUMN NAME** JM_L1_DRIVERS_LICENCE — Path
>
> **85%** `drivers?_?licen[cs]e(_?(no|num|number))?` `driving_?licen[cs]e(_?(no|num|number))?` `dl_?(no|num|number)` `licen[cs]e_?(no|num|number)` *(except when followed by list E1)* `permit_?(no|number)_?driver`

HOW IT IS MASKED

Character by character with the same mapping as the TRN: a licence number and the TRN of the same person still match after masking.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123–456–789	→	**110–858–568**

7.6 Immigration documents

JM_L1_IMMIGRATION_DOCUMENT

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Work permits, permanent residence, visas, citizenship and naturalisation certificates, CSME skills certificates, PICA file numbers.

HOW IT IS FOUND

COLUMN NAME — JM_L1_IMMIGRATION_DOCUMENT — Path

85% `permanent_?residen(ce|cy|t)(_?(permit|card|no|num|number|id))?` `work_?permit(_?(no|num|number))?` `immigration_?(permit|document|card|file|status_?no|no|num|number)` `visa_?(no|num|number)` `residen(ce|cy)_?permit(_?(no|number))?` `pica_?(no|number|file|ref)` `citizenship_?certificate(_?(no|number))?` `naturali[sz]ation_?(certificate|cert|no|number)` `csme_?(certificate|skills_?certificate)(_?(no|number))?` `skills_?certificate(_?(no|number))?` `refugee_?(id|card|no|number)` `asylum_?(id|no|number)` `alien_?(no|number|registration)`

HOW IT IS MASKED

Character by character, keeping the format.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
WP 12345	→	**PG 25117**

7.7 Civil registry entry

JM_L1_VITAL_RECORD

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Birth, death and marriage certificate and entry numbers of the Registrar General's Department.

HOW IT IS FOUND

COLUMN NAME — JM_L1_VITAL_RECORD — Path

85% `birth_?cert(ificate)?(_?(no|num|number|entry|pin))?` `death_?cert(ificate)?(_?(no|num|number))?` `marriage_?cert(ificate)?(_?(no|num|number))?` `registry_?entry(_?(no|number))?` `rgd_?(no|number|entry|pin|ref)` `vital_?(record|statistics)_?(no|num|number)` `registration_?(no|number)_?(birth|death|marriage)`

55% `entry_?(no|number)`

HOW IT IS MASKED

Character by character, keeping the format (`1234/1985` stays `dddd/dddd`).

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1234/1985	→	**1092/4201**

7.8 Given names

JM_L1_GIVEN_NAME

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

First and middle names (`FIRST_NAME` , `MIDDLE_NAME`), including two given names in one column such as `Shelly-Ann Novelette` .

HOW IT IS FOUND

COLUMN NAME JM_L1_GIVEN_NAME — Path

85% `first_?names?` `given_?names?` `fore_?names?` `christian_?name` `fname` `name_?first` `middle_?names?` `mname` `name_?middle`

50% `name` *(except when followed by list E2)*

KNOWN VALUES JM_L1_GIVEN_NAME — List

LIST	VALUES	STRENGTH	FIRST VALUES
`jm-detect-given-names.txt`	1,004	70%	George, Joseph, David, James, John, Michael

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each word is replaced by a name from a list of a thousand names used in Jamaica, keeping the number of words and the case. More than three words are masked character by character.

`JM_GIVEN_NAMES` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM` .

> `JM_GIVEN_NAME` NAME
>
> Replaces the name with one of the 1,004 names in `jm-given-names.txt` .
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Delroy	→	**Virginia**
Shelly-Ann Novelette	→	**Shauna Melbourne**

7.9 Surnames

JM_L1_SURNAME

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

Surnames, maiden and married names, including double-barrelled surnames joined by a hyphen (`Fraser-Pryce`).

HOW IT IS FOUND

COLUMN NAME JM_L1_SURNAME – Path

85% `last_?names?` `surnames?` `family_?names?` `lname` `name_?last` `maiden_?name` `mothers?_?maiden_?name` `maiden` `married_?name` `former_?(sur)?name`

KNOWN VALUES JM_L1_SURNAME – List

LIST	VALUES	STRENGTH	FIRST VALUES
`jm-detect-surnames.txt`	996	70%	Brown, Williams, Smith, Campbell, Johnson, Thompson

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each part becomes a surname from a list of a thousand Jamaican surnames; the hyphen stays.

`JM_SURNAMES` **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM`.

> `JM_SURNAME` **NAME**
>
> Replaces the name with one of the 996 names in `jm-surnames.txt`.
>
> `JM_CM_ALNUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`Beckford`	→	**`Case`**
`Fraser-Pryce`	→	**`Kong-Hosang`**

7.10 Full name

JM_L1_FULL_NAME

ESSENTIAL **COLUMN NAME** **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

Given names and surname in one column, in the English order — given name, middle names, surname — or written as `SURNAME, GIVEN NAMES`. Also the name of an account holder, beneficiary, guardian, next of kin or nominee.

HOW IT IS FOUND

COLUMN NAME `JM_L1_FULL_NAME – Path`

90% `full_?name` `fullname` `complete_?name` `person_?name` `name_?of_?(customer|cust|client|patient|employee|emp|staff|worker|member|student|pupil|insured|beneficiary|holder|account_?holder|policy_?holder|mother|father|parent|guardian|spouse|partner|next_?of_?kin|doctor|physician|nurse|contact|emergency_?contact|guarantor|debtor|borrower|applicant|signatory|witness|representative|owner|tenant|landlord|victim|complainant|accused|defendant|donor|heir|person|driver|agent|citizen|elector|voter|taxpayer|child|dependant|dependent|relative|officer|teacher|contributor|pensioner|claimant)` `(customer|cust|client|patient|employee|emp|staff|worker|member|student|pupil|insured|beneficiary|holder|account_?holder|policy_?holder|mother|father|parent|guardian|spouse|partner|next_?of_?kin|doctor|physician|nurse|contact|emergency_?contact|guarantor|debtor|borrower|applicant|signatory|witness|representative|owner|tenant|landlord|victim|complainant|accused|defendant|donor|heir|person|driver|agent|citizen|elector|voter|taxpayer|child|dependant|dependent|relative|officer|teacher|contributor|pensioner|claimant)_?name`

60% `beneficiary` `guardian` `next_?of_?kin` `spouse` `emergency_?contact` `guarantor` `account_?holder` `policy_?holder` `legal_?representative` `attorney` `patient` `victim` `complainant` `accused` `defendant` `insured_?person` `nominee` `executor` `justice_?of_?the_?peace`

50% `name` *(except when followed by list E2)*

KNOWN VALUES `JM_L1_FULL_NAME – List`

LIST	VALUES	STRENGTH	FIRST VALUES
`jm-detect-given-names.txt`	1,004	65%	George, Joseph, David, James, John, Michael
`jm-detect-surnames.txt`	996	65%	Brown, Williams, Smith, Campbell, Johnson, Thompson

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Given names become given names and the surname becomes a surname, by position: the last word is the surname, hyphenated or not. A middle initial stays an initial (`Delroy A. Beckford`), and a comma separates the surname from the given names.

`JM_FULL_NAME` **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM` .

> `JM_SURNAMES` **REGEX DECOMPOSE**
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM` .
>
> > `JM_SURNAME` **NAME**
> >
> > Replaces the name with one of the 996 names in `jm-surnames.txt` .
> >
> > `JM_CM_ALNUM` **CHARACTER MAPPING**
> >
> > Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_GIVEN_NAMES` **REGEX DECOMPOSE**
>
> Tries 3 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM` .
>
> > `JM_GIVEN_NAME` **NAME**
> >
> > Replaces the name with one of the 1,004 names in `jm-given-names.txt` .

EXAMPLES

VALUE		MASKED
Delroy A. Beckford	→	**Virginia A. Case**
Marcia Ann Campbell	→	**Althea Alecia Bacchas**
BECKFORD, DELROY	→	**CASE, VIRGINIA**

7.11 E-mail

JM_L1_EMAIL

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Personal and work e-mail addresses.

HOW IT IS FOUND

> COLUMN NAME JM_L1_EMAIL – Path
>
> 85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `email_?address`

> DATA TYPE JM_L1_EMAIL – Type
>
> Accepts text (length 5 or more); any other type rules the domain out.

> VALUE FORMAT JM_L1_EMAIL – Regex
>
> | PATTERN | STRENGTH | NOTES |
> |---|---|---|
> | `[\p{L}\p{N}._%+'\-]+@[\p{L}\p{N}.\-]+\.[A-Za-z]{2,24}` | 100% | |
>
> A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The name and domain are mapped character by character and the top-level domain becomes `.test`, reserved for testing: a masked address never receives mail.

`JM_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `JM_CM_ALNUM`.

> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
delroy.beckford@gmail.com	→	**yaskop.yoqwmosh@pgoeb.test**

7.12 Phone

JM_L1_PHONE

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Numbers of the North American plan with the Jamaican area codes 876 and 658 — `876-555-0123`, `(876) 555-0123`, `+1 876 555 0123` — and seven-digit local numbers.

HOW IT IS FOUND

COLUMN NAME JM_L1_PHONE — Path

85% `tel` `telephone[a-z0-9_]*` `tel_?(no|num|number|home|work|mobile|cell)` `phone[a-z0-9_]*` `ph_?(no|num|number)` `mobile[a-z0-9_]*` `cell` `cell_?(phone|no|number)` `cellphone` `cellular` `contact_?(no|num|number)` `fax` `whatsapp`

VALUE FORMAT JM_L1_PHONE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:(\+?1[\s\-.]?)?\(?(876|658)\)?[\s\-.]?\d{3}[\s\-.]?\d{4})`	100%	
`0*(?:[2-9]\d{2}[\s\-.]\d{4})`	50%	
`0*(?:\+?\d[\d\s()\-.]{6,15})`	30%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

`+1`, the area code and the separators stay; the seven digits are masked. A number not shaped like a Jamaican number is masked whole.

`JM_PHONE` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM`.

> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`+1 876-555-0123`	→	**`+1 876-962-0957`**
`(876) 555-0123`	→	**`(876) 962-0957`**
`555-0123`	→	**`962-0957`**

7.13 Address

JM_L1_ADDRESS

ESSENTIAL COLUMN NAME DATA TYPE VALUE FORMAT SECURE LOOKUP

WHAT IT IS

The address line as written in Jamaica, where postcodes are not in use: a house number and street, with the postal zone in Kingston and St. Andrew (`12 Hope Road, Kingston 6`); a lot in a housing scheme; or, in the country, the district and the post office (`Content District, Linstead P.O., St. Catherine`).

HOW IT IS FOUND

COLUMN NAME JM_L1_ADDRESS — Path

80% `address[a-z0-9_]*` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`; except when followed by list E3)*

`addr(ess)?_?(line|1|2)?[a-z0-9_]*` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`)* `street(_?(address|name))?` `residential_?address` `home_?address` `mailing_?address` `postal_?address` `physical_?address` `residence` `place_?of_?residence` `domicile` `post_?office` `p_?o_?box`

DATA TYPE JM_L1_ADDRESS — Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT JM_L1_ADDRESS — Regex

PATTERN	STRENGTH	NOTES
`(?i)#?\s*\d+[A-Z]?\s+.*\b(street|st\.?|avenue|ave\.?|road|rd\.?|drive|dr\.?|lane|boulevard|blvd\.?|crescent|close|terrace|way|highway|hwy)\b.*`	80%	
`(?i).*\bkingston\s+\d{1,2}\b.*`	80%	
`(?i).+\bdistrict\b.*\bp\.?\s?o\.?(\W.*)?`	90%	
`(?i).*\blot\s*(no\.?\s*|#\s*)?\d+\s*,.+`	60%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

It is replaced by one of 3,000 fictitious Jamaican addresses — real streets of Kingston and the towns, lots in real housing schemes, rural districts with their post offices.

`JM_ADDRESS` SECURE LOOKUP

Replaces the value with one of the 3,000 values in `jm-addresses.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`12 Hope Road, Kingston 6`	→	**`Lot 108, Ironshore, Montego Bay`**

7.14 Address detail

JM_L1_ADDRESS_DETAIL

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

House, lot, apartment, unit, floor or building number in separate columns.

HOW IT IS FOUND

COLUMN NAME JM_L1_ADDRESS_DETAIL — Path

70% `house_?(no|num|number)` `apt(_?(no|number))?` `apartment(_?(no|number))?` `unit_?(no|num|number)` `flat_?(no|number)` `lot_?(no|num|number)` `floor_?(no|number)?` `suite(_?no)?` `building_?(no|number)`

HOW IT IS MASKED

Character by character, keeping the format.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`Apt. 4B`	→	**`Adv. 9W`**

7.15 Bank account

JM_L1_BANK_ACCOUNT

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Bank, building society and credit union account numbers, savings and chequing.

HOW IT IS FOUND

COLUMN NAME JM_L1_BANK_ACCOUNT — Path

85% `account_?(no|num|number|nbr)` `acct_?(no|num|number|nbr)?` `acc_?(no|num|number)` `bank_?(account|acct)(_?(no|num|number))?` `savings_?(account|acct)(_?(no|number))?` `chequing_?(account|acct)(_?(no|number))?` `checking_?(account|acct)(_?(no|number))?` `share_?account(_?no)?` `iban`

HOW IT IS MASKED

Digit by digit, keeping length and separators.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
351–001–234	→	**816–280–792**

7.16 Payment card

JM_L1_PAYMENT_CARD

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Credit, debit and prepaid card numbers.

HOW IT IS FOUND

COLUMN NAME JM_L1_PAYMENT_CARD — Path

85% `card_?(no|num|number)` `credit_?card(_?(no|num|number))?` `debit_?card(_?(no|num|number))?` `keycard(_?(no|number))?` `cc_?(no|num|number)` `pan` `card_?pan` `masked_?pan`

VALUE FORMAT JM_L1_PAYMENT_CARD — Regex

PATTERN	STRENGTH	NOTES
`0*(?:3[47]\d{13}|[1–9]\d{12,13}|[1–9]\d{15,18})`	90%	LUHN check digit; after removing `[\s\-]`

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Credit Card, which comes with the Masking Engine: another number that passes the Luhn check, keeping the first six digits — the issuer, not the holder. Only values shaped like a card reach it; the others pass unchanged instead of failing the row.

`JM_CARD` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `dlpx-core:Credit Card` PAYMENT CARD
>
> Comes with the Masking Engine and is used as it ships. Replaces the card number with another that passes the Luhn check, keeping the first six digits — the issuer, not the holder.

EXAMPLES

VALUE		MASKED
4916 3131 2345 6780	→	**4916 3196 4606 3896**

7.17 IP address

JM_L1_IP_ADDRESS

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses in access logs, sessions and transactions.

HOW IT IS FOUND

COLUMN NAME JM_L1_IP_ADDRESS — Path

85% `ip` `ip_?(address|addr|origin|source|destination|client|user|remote|public|private|login)` `ipv[46]` `remote_?addr(ess)?` `client_?ip` `host_?ip` `source_?ip`

VALUE FORMAT JM_L1_IP_ADDRESS — Regex

PATTERN	STRENGTH	NOTES
`0*(?:((25[0-5]|2[0-4]\d|1?\d?\d)\.){3}(25[0-5]|2[0-4]\d|1?\d?\d))`	100%	
`0*(?:[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7})`	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet is mapped into 1–254, so the address stays valid; an IPv6 address is mapped digit by digit in hexadecimal.

`JM_IP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `JM_CM_HEX`.

> `JM_OCTET` NUMERIC MAPPING
>
> Maps the number to another between 1 and 254.
>
> `JM_CM_HEX` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`72.27.211.10`	→	**`99.92.143.16`**

7.18 Device identifier

JM_L1_DEVICE_ID

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

IMEI, IMSI, ICCID, MAC addresses, advertising identifiers and session cookies.

HOW IT IS FOUND

COLUMN NAME JM_L1_DEVICE_ID — Path

80% `imei` `imsi` `iccid` `mac` `mac_?address` `device_?(id|uuid|serial)` `advertising_?id` `idfa` `gaid` `cookie(_?id)?` `session_?id` `serial_?(no|number)_?(device|phone|handset)` `handset_?serial`

VALUE FORMAT JM_L1_DEVICE_ID — Regex

PATTERN	STRENGTH	NOTES
`0*(?:([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2})`	100%	
`0*(?:\d{15})`	80%	LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character in hexadecimal: a MAC stays a MAC, an IMEI stays fifteen digits.

`JM_CM_HEX` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3c:22:fb:9a:10:e4	→	**5e:83:bb:3c:31:f9**

7.19 Licence plate

JM_L1_LICENCE_PLATE

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Vehicle registration plates: private plates are four digits and two letters (`1234 AB`); public passenger, commercial and rental vehicles put two letters first (`PP 1234` , `CA 1234` , `RR 1234`); government plates are digits only.

HOW IT IS FOUND

COLUMN NAME JM_L1_LICENCE_PLATE — Path

85% `licen[cs]e_?plates?(_?(no|num|number))?` `plates?(_?(no|num|number))?` `vehicle_?(reg|registration|plate|licen[cs]e)(_?(no|num|number))?` `registration_?plate` `number_?plate` `reg_?plate` `tag_?(no|number)`

VALUE FORMAT JM_L1_LICENCE_PLATE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{4}[\s\-]?[A-Z]{2})`	80%	
`(P[A-HJ-NP]|C[A-HJ-N]|RR|DA|MA|MB)[\s\-]?\d{4}`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The letters, which tell the category, stay; the digits are masked.

`JM_PLATE` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM` .

> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1234 AB	→	**9707 AB**
PP 1234	→	**PP 9707**

7.20 VIN and engine number

JM_L1_VIN

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

Vehicle identification, chassis and engine numbers.

HOW IT IS FOUND

COLUMN NAME — JM_L1_VIN — Path

80% `vin` `vin_?(no|number)` `vehicle_?identification_?(no|number)` `chassis(_?(no|number))?` `engine_?(no|number|serial)` `motor_?(no|number)` `serial_?(no|number)_?vehicle`

VALUE FORMAT — JM_L1_VIN — Regex

PATTERN	STRENGTH	NOTES
`[A-HJ-NPR-Z0-9]{17}`	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the 17-character format.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1HGCM82633A004352	→	**1JTRL73362E132318**

7.21 Land title and valuation number

JM_L1_LAND_TITLE

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The volume and folio of a registered title (`Volume 1234 Folio 567`), the valuation number of the National Land Agency, strata lots, deeds and leases. Each leads to a proprietor in the Register Book of Titles.

HOW IT IS FOUND

COLUMN NAME — JM_L1_LAND_TITLE — Path

85% `vol(ume)?_?(and_?)?fol(io)?` `title_?(deed_?)?(no|number|vol|volume|ref)` `certificate_?of_?title` `land_?(title|registry|register|certificate|parcel)(_?(no|num|number))?` `valuation_?(no|num|number|roll)` `nla_?(no|number|valuation)` `parcel(_?(no|num|number|id))?` `deed_?(no|number)` `lease_?(no|number)` `strata_?(plan|lot)(_?(no|number))?` `folio(_?(no|number))?`

VALUE FORMAT — JM_L1_LAND_TITLE — Regex

PATTERN	STRENGTH	NOTES
`(?i).*vol(ume)?\.?\s*\d+.*fol(io)?\.?\s*\d+.*`	90%	

A value that matches none does not count against the domain.

HOW IT IS MASKED

The words and separators stay and the numbers are masked digit by digit: `Volume 1234 Folio 567` stays a volume and a folio.

`JM_LAND_TITLE` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `JM_CM_ALNUM` .

> `JM_CM_ALNUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Volume 1234 Folio 567	→	**Volume 9707 Folio 253**

7.22 Customer, contract or account number

`JM_L1_CONTRACT_NUMBER`

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Customer, member, employee, policy, loan, claim and meter numbers, JPS and NWC accounts, NHT contributor numbers, student numbers.

HOW IT IS FOUND

> **COLUMN NAME** `JM_L1_CONTRACT_NUMBER` – Path
>
> **70%** `contract_?(no|num|number)` `policy_?(no|num|number)` `loan_?(no|num|number|id)` `mortgage_?(no|number)` `member(ship)?_?(no|num|number|id)` `customer_?(no|num|number|id)` `client_?(no|num|number|id)` `cust_?(no|num|id)` `employee_?(no|num|number|id)` `emp_?(no|num|id)` `staff_?(no|num|number|id)` `payroll_?(no|number)` `claim_?(no|num|number)` `meter_?(no|number)` `jps_?account(_?no)?` `nwc_?account(_?no)?` `nht_?(no|number|contributor_?(no|number)?)` `student_?(no|num|number|id)` `pupil_?(no|number|id)`

HOW IT IS MASKED

Character by character, keeping the format, so references between tables still match.

`JM_CM_ALNUM` **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
POL–123456	→	**MIF–194239**

7.23 Username and social media

`JM_L1_USERNAME`

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Logins, nicknames and handles on social networks.

HOW IT IS FOUND

> **COLUMN NAME** `JM_L1_USERNAME` – Path
>
> **70%** `user_?name` `username` `login(_?(name|id))?` `user_?id_?login` `nick_?name` `nickname` `alias` `screen_?name` `handle` `facebook` `instagram` `twitter` `tiktok` `linkedin` `social_?media(_?(handle|account|profile))?` `telegram`

HOW IT IS MASKED

Character by character.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`@delroy_b`	→	**`@dextuv_j`**

7.24 Credential

JM_L1_CREDENTIAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Passwords, PINs, password hashes, security answers, tokens and API keys. A hash is also found by its scheme — bcrypt, crypt, Argon2, PBKDF2, LDAP — under any column name.

HOW IT IS FOUND

COLUMN NAME JM_L1_CREDENTIAL — Path

90% `password` `passwd` `pwd` `pass_?word` `pass` `pin(_?(code|no|number))?` `passcode` `hash_?password` `password_?hash` `secret` `secret_?(answer|question)` `security_?(answer|question)` `access_?token` `refresh_?token` `api_?key` `otp`

VALUE FORMAT JM_L1_CREDENTIAL — Regex

PATTERN	STRENGTH	NOTES
`\$2[abxy]?\$\d{2}\$[./A-Za-z0-9]{53}`	95%	
`\$(1|5|6)\$(rounds=\d+\$)?[./A-Za-z0-9]{1,16}\$[./A-Za-z0-9]{22,86}`	95%	
`\$argon2(id|i|d)\$v=\d+\$m=\d+,t=\d+,p=\d+\$\S+`	95%	
`pbkdf2_sha(1|256|512)\$\d+\$\S+\$\S+`	95%	
`\{(SSHA|SHA|SSHA256|SSHA512|SMD5|MD5|CRYPT)\}\S+`	95%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Every character becomes `X`. A credential has no reason to look real in a test environment.

`JM_REDACT` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
`Secret#2024`	→	**`XXXXXXXXXX`**

7.25 Geolocation

JM_L1_GEOLOCATION

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in separate columns. Jamaica lies between 17.7° and 18.5° north and 76.2° and 78.4° west.

HOW IT IS FOUND

COLUMN NAME JM_L1_GEOLOCATION — Path

85% `lat` `latitude` `lon` `lng` `longitude` `coordinates?` `coord_?[xy]` `geo_?(lat|lon|lng|loc|location|position)` `geolocation` `gps(_?(location|position|coordinates))?`

50% `long`

VALUE FORMAT JM_L1_GEOLOCATION — Regex

PATTERN	STRENGTH	NOTES
`0*(?:1[78]\.\d{3,}\s*,\s*-7[678]\.\d{3,})`	90%	
`0*(?:1[78]\.\d{3,})`	50%	
`-7[678]\.\d{3,}`	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the rest is masked: the place is generalized, not moved.

`JM_COORDINATE` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`18.012345,-76.798765`	→	**`18.031564,-76.799199`**

7.26 Free text

JM_L1_FREE_TEXT

COLUMN NAME | DATA TYPE | VALUE FORMAT | FREE TEXT REDACTION

WHAT IT IS

Remarks, comments, complaints, case notes and statements where personal data is written without structure.

HOW IT IS FOUND

COLUMN NAME JM_L1_FREE_TEXT — Path

60% `remarks?` `comments?` `notes?` `observations?` `narrative` `free_?text` `memo` `messages?` *(except when followed by list E4)* `complaint(_?(text|details|description))?` `description_?(of_?)?(case|complaint|incident|request|issue|problem|events)` `incident_?(details|description|narrative)` `case_?(notes?|summary|details)` `statement` `details` `summary`

DATA TYPE `JM_L1_FREE_TEXT – Type`

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT `JM_L1_FREE_TEXT – Regex`

PATTERN	STRENGTH	NOTES
`0*(?:\d{3}–?\d{3}–?\d{3})`	60%	anywhere in the value
`[\w.+\-]+@[\w\-]+\.[A-Za-z]{2,}`	70%	anywhere in the value
`0*(?:(876|658)[\s\-.]?\d{3}[\s\-.]?\d{4})`	60%	anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

Free Text Redaction: TRNs, e-mails, phone numbers, card numbers, plates and IPs become `[DATA]`, and the given names and surnames of the lists become `[NAME]`.

`JM_FREE_TEXT` **FREE TEXT REDACTION**

Replaces the text matching 8 patterns with `[DATA]`, and the 3,790 terms of `jm-text-names.txt` with `[NAME]`.

EXAMPLES

VALUE		MASKED
`Customer Beckford, TRN 123-456-789, email d.beckford@gmail.com, tel 876-555-0123.`	→	**`Customer [NAME], TRN [DATA], email [DATA], tel [DATA].`**

PART 8

Quasi-identifiers

Data that identifies no one on its own, but does in combination. Jamaica had about 2.8 million people in the 2022 census, in fourteen parishes; 116 of the 140 towns of the census list had fewer than 10,000 inhabitants. A birth date, a sex and one of those towns point at a handful of people. These attributes are generalized or shifted rather than replaced, and the data keeps its analytical value.

8.1 Birth date

JM_L2_BIRTH_DATE

ESSENTIAL · COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

The birth date, in date, timestamp or text columns.

HOW IT IS FOUND

COLUMN NAME JM_L2_BIRTH_DATE – Path

90% `dob` `d_?o_?b` `date_?of_?birth` `birth_?date` `birthdate` `birthday` `born_?(on|date)` `bdate`

DATA TYPE JM_L2_BIRTH_DATE – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 60 days back or forward: it breaks the link to the person and keeps ages and cohorts almost intact.

`JM_BIRTH_DATE` DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	**1985-08-05T00:00**

8.2 Year of birth

JM_L2_BIRTH_YEAR

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The year of birth on its own.

HOW IT IS FOUND

COLUMN NAME JM_L2_BIRTH_YEAR – Path

90% `birth_?year` `year_?of_?birth` `yob` `yr_?of_?birth`

DATA TYPE JM_L2_BIRTH_YEAR – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit is mapped.

`JM_YEAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

`JM_CM_ALNUM` CHARACTER MAPPING

> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	**1980**

8.3 Age

JM_L2_AGE

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

Ages in years, whole or with decimals.

HOW IT IS FOUND

> COLUMN NAME JM_L2_AGE — Path
>
> 85% `age(_?(years|yrs|in_?years|at_?(admission|death|entry|diagnosis|registration)|group|range|band|bracket|last_?birthday))?years_?old`

> DATA TYPE JM_L2_AGE — Type
>
> Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The tens digit stays and the units digit is mapped (37 becomes 3x). From 100 on, 90: extreme ages identify on their own.

`JM_AGE` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	**35**
104	→	**90**

8.4 Life event dates

JM_L2_EVENT_DATE

COLUMN NAME DATA TYPE DATE SHIFT

WHAT IT IS

Dates of death, marriage, divorce, hiring, termination, admission, discharge, diagnosis, arrest, conviction and naturalisation.

HOW IT IS FOUND

COLUMN NAME JM_L2_EVENT_DATE – Path

80% `date_?of_?(death|marriage|divorce|hire|hiring|employment|engagement|termination|dismissal|resignation|retirement|admission|discharge|diagnosis|visit|consultation|delivery|arrest|conviction|sentence|sentencing|naturali[sz]ation|injury|surgery)` `(death|marriage|divorce|hire|hiring|employment|employment_?start|start_?of_?employment|termination|separation|resignation|retirement|admission|discharge|diagnosis|visit|delivery|arrest|conviction|sentencing|naturali[sz]ation|pension_?start|injury|vaccination|surgery|immigration)_?date` `dod`

DATA TYPE JM_L2_EVENT_DATE – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 30 days: they combine with the birth date, and a smaller shift keeps intervals plausible.

`JM_EVENT_DATE` DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	**2021-03-05T00:00**

8.5 Sex

JM_L2_SEX

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Registered sex in any notation: `F` / `M`, `Female` / `Male`, `Woman` / `Man`.

HOW IT IS FOUND

COLUMN NAME JM_L2_SEX – Path

85% `sex(_?(code|at_?birth|registered))?` `gender(_?code)?` *(except when followed by `identity`, `expression`)*

KNOWN VALUES JM_L2_SEX – List

LIST	VALUES	STRENGTH	FIRST VALUES
`jm-detect-sex.txt`	5	80%	female, male, woman, man, fem
`jm-detect-sex-letter.txt`	2	60%	f, m

Values are split into words, and each word is looked up.

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary: `F` / `M` stays `F` / `M`.

`JM_SEX` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

`JM_SEX_FEMALE_MALE` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-sex-female-male.txt`, chosen by a keyed hash.

`JM_SEX_WOMAN_MAN` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-sex-woman-man.txt`, chosen by a keyed hash.

`JM_SEX_F_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-sex-f-m.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	**M**
Male	→	**Female**

8.6 Town

JM_L2_TOWN

COLUMN NAME | VALUE FORMAT | DATA CLEANSING

WHAT IT IS

The town or community where a person lives or was born. The census list has 140 towns; 116 of them had fewer than 10,000 inhabitants.

HOW IT IS FOUND

COLUMN NAME JM_L2_TOWN — Path

85%	`town` `village` `community` *(except when followed by* `service`, `group`, `organi[sz]ation`, `work`, `council`*)* `locality` `settlement` `home_?town` `hometown` `place_?of_?birth` `birth_?place` `birthplace` `residence_?(town|village|community|district)` `town_?of_?residence` `post_?office_?(name|town)` `postal_?town`
50%	`city` `municipality`

VALUE FORMAT JM_L2_TOWN — Values

PATTERN	STRENGTH	NOTES
One of 153 known values, ignoring case — Portmore, Montego Bay, Mobay, Mo Bay, Spanish Town, May Pen, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A town under 10,000 inhabitants becomes the capital of its parish; larger towns and the capitals stay. See *Where people live*.

`JM_TOWN` DATA CLEANSING

Replaces each value found in `jm-town-generalized.txt` (315 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Port Royal	→	**Kingston**
Ocho Rios	→	**Saint Ann's Bay**
Montego Bay	→	**Montego Bay**

8.7 Neighbourhood or housing scheme

JM_L2_NEIGHBOURHOOD

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

The neighbourhood of Kingston and St. Andrew (Barbican, Havendale, Duhaney Park…), the housing scheme or the district name within a town.

HOW IT IS FOUND

COLUMN NAME JM_L2_NEIGHBOURHOOD — Path

85% `neighbou?rhood` `subdivision` `housing_?(area|scheme|estate|development)` `residential_?area` `area_?of_?residence` `scheme_?name` `community_?name` `district_?name`

HOW IT IS MASKED

Replaced by one of 77 neighbourhoods of Kingston and St. Andrew: a real place still, no longer theirs.

`JM_NEIGHBOURHOOD` SECURE LOOKUP

Replaces the value with one of the 77 values in `jm-neighbourhoods.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Barbican	→	**Vineyard Town**

8.8 Nationality

JM_L2_NATIONALITY

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

Nationality, citizenship and country of birth.

HOW IT IS FOUND

COLUMN NAME JM_L2_NATIONALITY — Path

80% `nationality` `citizenship` `country_?of_?(birth|origin|citizenship|nationality)` `birth_?country`

VALUE FORMAT JM_L2_NATIONALITY — Values

PATTERN	STRENGTH	NOTES
One of 36 known values, ignoring case — Jamaican, American, British, Canadian, Chinese, Indian, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a nationality from a list of those most often found in Jamaica.

`JM_NATIONALITY` SECURE LOOKUP

Replaces the value with one of the 16 values in `jm-nationalities.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Guyanese	→	**Indian**

8.9 Marital and union status

JM_L2_MARITAL_STATUS

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

Marital status and the type of union the census asks about — married, common-law and visiting unions are all common.

HOW IT IS FOUND

COLUMN NAME JM_L2_MARITAL_STATUS – Path

85%	`marital_?status` `civil_?status` `union_?status` `union_?type` `marriage_?status` `relationship_?status` `conjugal_?status`

VALUE FORMAT JM_L2_MARITAL_STATUS – Values

PATTERN	STRENGTH	NOTES
One of 17 known values, ignoring case — Never married, Married, Common-law union, Visiting union, Divorced, Widowed, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another status of the census list.

`JM_MARITAL_STATUS` SECURE LOOKUP

Replaces the value with one of the 7 values in `jm-marital-status.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Visiting union`	→	**`Widowed`**

8.10 Occupation

JM_L2_OCCUPATION

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

Occupation, profession, job title and position. A rare title in a small employer identifies.

HOW IT IS FOUND

COLUMN NAME JM_L2_OCCUPATION – Path

80%	`occupation` `profession` `job_?title` `designation` `post_?title` `position_?title`
50%	`job` `position` `post` `trade` *(except when followed by `name`, `mark`, `licen[cs]e`)*

HOW IT IS MASKED

Replaced by a common occupation.

`JM_OCCUPATION` SECURE LOOKUP

Replaces the value with one of the 41 values in `jm-occupations.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Regional Operations Manager, Western Division`	→	**`Retired`**

8.11 Employer

JM_L2_EMPLOYER

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

The employer's name and the place of work.

HOW IT IS FOUND

COLUMN NAME JM_L2_EMPLOYER — Path

80% `employer(_?name)?` `name_?of_?employer` `employer_?business_?name` `company_?of_?employment` `workplace` `work_?place` `place_?of_?(work|employment)` `employed_?(at|by|with)` `current_?employer`

HOW IT IS MASKED

Replaced by one of a list of fictitious companies.

`JM_EMPLOYER` SECURE LOOKUP

Replaces the value with one of the 25 values in `jm-employers.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Jamaica Public Service Company Limited	→	**North Coast Hotels Ltd.**

8.12 Education

JM_L2_EDUCATION

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

Highest level attained in the Jamaican system — primary, secondary to grade 11 and the CSEC examinations, sixth form and CAPE, HEART/NSTA Trust vocational training (NVQ-J), tertiary — and examination results.

HOW IT IS FOUND

COLUMN NAME JM_L2_EDUCATION — Path

80% `education(_?(level|attainment|status|completed))?` `educational_?(level|attainment)` `highest_?(level_?(of_?)?)?(education|qualification|grade)` `level_?of_?education` `qualification` `schooling` `grade_?completed` `csec_?(subjects|passes|grades)` `cape_?(subjects|passes|grades)` `cxc_?(subjects|passes|grades)`

VALUE FORMAT JM_L2_EDUCATION — Values

PATTERN	STRENGTH	NOTES
One of 30 known values, ignoring case — No schooling, Early childhood, Primary, Lower secondary grade 9, Secondary CSEC, Sixth form CAPE, …	60%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another level of the list.

`JM_EDUCATION` SECURE LOOKUP

Replaces the value with one of the 11 values in `jm-education.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Secondary (CSEC)	→	**Primary**

8.13 School

JM_L2_SCHOOL

COLUMN NAME SECURE LOOKUP

WHAT IT IS

Primary and high school, college and university attended.

HOW IT IS FOUND

> COLUMN NAME JM_L2_SCHOOL — Path
>
> 75% `school(_?name)?` `name_?of_?school` `high_?school` `primary_?school` `secondary_?school` `prep_?school` `sixth_?form` `college(_?name)?` `university(_?name)?` `institution_?attended` `alma_?mater`

HOW IT IS MASKED

Replaced by a fictitious school.

`JM_SCHOOL` SECURE LOOKUP

Replaces the value with one of the 15 values in `jm-schools.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Jamaica College	→	**Riverside College of Technology**

8.14 Children and dependants

JM_L2_DEPENDANTS

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

Number of children, dependants or household members.

HOW IT IS FOUND

> COLUMN NAME JM_L2_DEPENDANTS — Path
>
> 80% `dependants?` `dependents?` `no_?of_?(children|dependants|dependents|kids)` `num(ber)?_?(of_?)?(children|dependants|dependents|kids)` `children` `household_?(size|members)` `persons_?in_?household`

> DATA TYPE JM_L2_DEPENDANTS — Type
>
> Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Capped at 5: large households are rare, and a rare count identifies.

`JM_CAPPED_COUNT` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	**5**

PART 9

Sensitive personal data

The categories of section 2 that are not health or offences — which have groups of their own: genetic and biometric data, filiation, racial or ethnic origin, political opinions, religious, philosophical and similar beliefs, trade union membership and sex life — and, beyond the list, gender identity. The Jamaican definition of biometric data is unusually wide: besides prints and scans it names the photograph, height, eye colour and blood type, so the set gives height and eye colour domains of their own. Categorical columns keep their shape: a yes/no flag stays a flag, a numeric code gets other digits and any other value is replaced by one from its category's list. Where the values share no vocabulary, they are suppressed to `Not stated`.

9.1 Genetic data

JM_L3_GENETIC

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

DNA profiles and samples, genetic tests and markers, paternity tests, sickle cell genotype, newborn screening. Found also by its values: a long sequence of nucleotides.

HOW IT IS FOUND

COLUMN NAME — JM_L3_GENETIC — Path

90%

`dna` `genetic[a-z_]*` `genome` `genotyp[a-z_]*` `gene_?(test|result|marker|panel)` `genetic_?(test|marker|profile|result)` `mutation` `brca[12]?` `karyotype` `paternity_?test` `dna_?(profile|sample|index)` `snp` `haplotype` `newborn_?screening` `sickle_?cell_?(genotype|trait)`

VALUE FORMAT — JM_L3_GENETIC — Regex

PATTERN	STRENGTH	NOTES
`[ACGTUN]{24,}`	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Every character becomes `X`.

`JM_REDACT` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
`HbSS sickle cell`	→	`XXXXXXXXXXXXXXX`

9.2 Biometric data

JM_L3_BIOMETRIC

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

What section 2 names: the photograph and other facial images, finger, palm, toe and foot prints, iris and retina scans, vein patterns, and the behavioural characteristics — gait, signature, keystrokes, voice — as templates, images, paths or hashes.

HOW IT IS FOUND

COLUMN NAME JM_L3_BIOMETRIC — Path

90% `fingerprints?` `finger_?prints?` `thumb_?prints?` `biometric[a-z_]*` `face_?(template|encoding|id|print|hash|image)` `facial_?(template|recognition|id|image|image_?hash)` `photo(graph)?(_?(image|file|path|blob|data|url))?` `passport_?photo` `selfie` `headshot` `mugshot` `iris(_?(scan|template|code))?` `retina(_?scan)?` `vein_?(pattern|scan)` `palm_?(print|vein)` `toe_?print` `foot_?print` `voice_?(print|template|sample|recording)` `signature_?(image|biometric|capture|pad|specimen|scan)` `specimen_?signature` `handwritten_?signature` `keystroke(_?(dynamics|pattern))?` `typing_?pattern` `gait(_?(pattern|analysis))?` `minutiae`

DATA TYPE JM_L3_BIOMETRIC — Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character becomes `X`. A path to an image file is redacted too; the image itself, in a binary column, is out of reach of these algorithms.

`JM_REDACT` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	XXXXXXXXXXXX

9.3 Height

JM_L3_HEIGHT

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

A person's height — biometric data by name in section 2 — in centimetres, metres or feet and inches, as an identity document or a personnel or medical file records it.

HOW IT IS FOUND

COLUMN NAME JM_L3_HEIGHT — Path

85% `height(_?(cm|m|in|inches|ft|feet|metres?|meters?))?` `stature` `ht_?(cm|in)`

HOW IT IS MASKED

The unit and the first figure stay and the rest is masked: `172` stays `1xx`, `1.72` stays `1.xx`, `5'8"` stays five feet with other inches.

`JM_HEIGHT` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

`JM_INCHES` SECURE LOOKUP

Replaces the value with one of the 12 values in `jm-inches.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
172	→	**167**
5'8"	→	**5'7"**

9.4 Eye colour

JM_L3_EYE_COLOUR

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Eye colour, also biometric data by name in section 2, as identity and driver's licence records carry it.

HOW IT IS FOUND

COLUMN NAME JM_L3_EYE_COLOUR — Path

90% `eye_?colou?r` `eyes_?colou?r` `colou?r_?of_?eyes` `eyes`

VALUE FORMAT JM_L3_EYE_COLOUR — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Brown, Dark brown, Light brown, Black, Hazel, Green, …	60%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another colour of the list; a flag stays a flag.

`JM_EYE_COLOUR` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_EYE_COLOUR_LIST`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_EYE_COLOUR_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `jm-eye-colours.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Amber	→	**Grey**

9.5 Filiation

JM_L3_FILIATION

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Who a person descends from and how that is recorded: born in or out of wedlock, legitimated, adopted, father named or not on the birth entry, affiliation orders, birth parents. The Status of Children Act abolished illegitimacy in 1976, but older registers and benefit files keep the mark.

HOW IT IS FOUND

COLUMN NAME JM_L3_FILIATION — Path

90% `filiation` `legitimacy` `legitimate` `illegitimate` `legitimated` `born_?(in|out_?of)_?wedlock` `wedlock(_?status)?` `parentage` `paternity(_?(status|acknowledged|declared|established|order))?` *(except when followed by* `test`, `leave`*)* `father_?(unknown|named|recorded|on_?record|acknowledged)` `affiliation_?order` `adopt(ed|ion)(_?(status|order|flag|date))?` `birth_?parents?` `biological_?(mother|father|parents?)`

VALUE FORMAT JM_L3_FILIATION — Values

PATTERN	STRENGTH	NOTES
One of 13 known values, ignoring case — Born in wedlock, Born out of wedlock, Legitimated, Adopted, Father not recorded, Not stated, …	80%	
One of 6 known values, ignoring case — y, n, yes, no, 0, 1	30%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag in its vocabulary, a code gets other digits and any other value is replaced by one from the list.

`JM_FILIATION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_FILIATION_LIST`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_FILIATION_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 6 values in `jm-filiation.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Father unknown`	→	**`Born out of wedlock`**
Y	→	**N**

9.6 Racial or ethnic origin

JM_L3_ETHNICITY

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Race or ethnic group in the terms of the census — Black (about nine in ten), Mixed, East Indian, Chinese, White and others — and Maroon identity, a people of their own.

HOW IT IS FOUND

> **COLUMN NAME** JM_L3_ETHNICITY — Path
>
> **90%** `ethnic(ity|_?group|_?origin|_?background|_?identity)?` `race` `racial_?(origin|group|background)` `indigenous(_?(status|group|people|peoples))?` `maroon(_?(community|status))?`

> **VALUE FORMAT** JM_L3_ETHNICITY — Values
>
PATTERN	STRENGTH	NOTES
One of 26 known values, ignoring case — Black, East Indian, Chinese, White, Mixed, Maroon, …	90%	
One of 6 known values, ignoring case — y, n, yes, no, 0, 1	30%	
>
> A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag in its vocabulary, a code gets other digits and any other value is replaced by one from the census list.

`JM_ETHNICITY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_ETHNICITY_LIST`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_ETHNICITY_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `jm-ethnic-groups.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Syrian/Lebanese	→	**Other**
Y	→	**N**

9.7 Religious beliefs

JM_L3_RELIGION

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Religion or denomination, in the terms of the census: Church of God, Seventh-day Adventist, Pentecostal, Baptist, Anglican, Roman Catholic, Revivalist, Rastafarian and others.

HOW IT IS FOUND

COLUMN NAME — JM_L3_RELIGION — Path

95% `religion[a-z_]*` `religious_?(affiliation|denomination|belief|beliefs|preference|group)` `denomination` `faith` `church(_?(name|affiliation|member|membership|attended))?` `creed` `congregation`

VALUE FORMAT — JM_L3_RELIGION — Values

PATTERN	STRENGTH	NOTES
One of 50 known values, ignoring case — Church of God, Seventh-day Adventist, Pentecostal, Baptist, Anglican, Roman Catholic, …	90%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag in its vocabulary, a code gets other digits and any other value is replaced by one from the census list.

`JM_RELIGION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_RELIGION_LIST`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_RELIGION_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 19 values in `jm-religions.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Salvation Army	→	**Jehovah's Witness**

9.8 Philosophical and similar beliefs

JM_L3_BELIEF

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Philosophical or moral convictions, conscientious objection and other beliefs of a similar nature to religious ones.

HOW IT IS FOUND

COLUMN NAME — JM_L3_BELIEF — Path

90% `beliefs?` `philosophical_?(beliefs?|convictions?)` `conscientious_?objection` `conscientious_?objector` `moral_?(beliefs?|convictions?)` `personal_?convictions?` `worldview`

HOW IT IS MASKED

Suppressed to `Not stated`.

`JM_SUPPRESSED_CATEGORY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_SUPPRESS`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_SUPPRESS` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `jm-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Refuses blood transfusions`	→	**`Not stated`**

9.9 Political opinions

JM_L3_POLITICAL_OPINION

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Political leaning, ideology, voting intention and swing-voter flags.

HOW IT IS FOUND

COLUMN NAME — JM_L3_POLITICAL_OPINION — Path

90% `political_?(opinion|opinions|view|views|orientation|leaning|leanings|preference|ideology)` `ideology` `voting_?intention` `vote_?intention` `intended_?vote` `swing_?voter`

VALUE FORMAT JM_L3_POLITICAL_OPINION — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — Left, Centre-left, Centre, Centre-right, Right, No preference, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another position on the list.

`JM_POLITICAL_OPINION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_POLITICAL_OPINION_LIST`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_POLITICAL_OPINION_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `jm-political-opinions.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Centre-right`	→	**`Right`**

9.10 Party preference or membership

JM_L3_POLITICAL_AFFILIATION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The party a person supports or belongs to — the Jamaica Labour Party and the People's National Party, which have alternated in government since 1944 — and its colours, green and orange. A political opinion under section 2 (c).

HOW IT IS FOUND

COLUMN NAME JM_L3_POLITICAL_AFFILIATION — Path

95%	`political_?(party|body|membership|affiliation|group)` `party_?(membership|member|affiliation|card|group|supporter|preference)` `preferred_?party` `member_?of_?(party|political_?(party|body))` `party_?(of_?)?choice`
50%	`party` *(except when followed by list E5)*

VALUE FORMAT JM_L3_POLITICAL_AFFILIATION — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Jamaica Labour Party, People s National Party, Independent, No party, JLP, PNP, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag in its vocabulary and any other value is replaced by one from the list.

`JM_POLITICAL_PARTY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_POLITICAL_PARTY_LIST`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_POLITICAL_PARTY_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 4 values in `jm-political-parties.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`People's National Party`	→	**`People's National Party`**

9.11 Trade union membership

JM_L3_TRADE_UNION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Union membership, dues, delegates and bargaining units: BITU, NWU, UAWU, the JTA, the Nurses Association of Jamaica, the JCSA and others.

HOW IT IS FOUND

COLUMN NAME JM_L3_TRADE_UNION — Path

95% `trade_?union(_?(member|membership|name|dues))?` `union_?(member|membership|affiliation|name|dues|fees|code|branch|local|delegate|representative)` `unioni[sz]ed` `labou?r_?union` `bargaining_?unit` `collective_?(agreement|bargaining)` `staff_?association` `shop_?steward`

VALUE FORMAT JM_L3_TRADE_UNION — Values

PATTERN	STRENGTH	NOTES
One of 24 known values, ignoring case — BITU, NWU, UAWU, JCTU, JTA, NAJ, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag in its vocabulary; any other value is suppressed to `Not stated`.

`JM_SUPPRESSED_CATEGORY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_SUPPRESS`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_SUPPRESS` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `jm-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
BITU	→	**Not stated**

9.12 Sexual orientation

JM_L3_SEXUAL_ORIENTATION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Sexual orientation, which reveals the sex life section 2 (f) protects. In Jamaica it also exposes people to the criminal law: the Offences Against the Person Act still punishes sex between men.

HOW IT IS FOUND

COLUMN NAME JM_L3_SEXUAL_ORIENTATION — Path

95% `sexual_?(orientation|preference)` `orientation_?sexual` `orient_?sexual` `msm(_?(status|flag))?`

VALUE FORMAT JM_L3_SEXUAL_ORIENTATION — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Heterosexual, Gay, Lesbian, Bisexual, Pansexual, Asexual, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another value of the list.

`JM_SEXUAL_ORIENTATION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_SEXUAL_ORIENTATION_LIST`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_SEXUAL_ORIENTATION_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `jm-sexual-orientations.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Bisexual	→	**Other**

9.13 Sex life

JM_L3_SEXUAL_LIFE

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Sexual activity, behaviour, partners and history, and sex work.

HOW IT IS FOUND

> COLUMN NAME JM_L3_SEXUAL_LIFE — Path
>
> 90% `sex(ual)?_?life` `sexual_?(activity|behavio(u)?r|history|partners?|practices?)` `sexually_?active` `number_?of_?sexual_?partners` `age_?(at_?)?first_?(sex|intercourse)` `transactional_?sex` `sex_?work(er)?`

HOW IT IS MASKED

Suppressed to `Not stated`.

`JM_SUPPRESSED_CATEGORY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_SUPPRESS`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

`JM_SUPPRESS` SECURE LOOKUP

Replaces the value with one of the 1 values in `jm-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Active	→	**Not stated**

9.14 Gender identity

JM_L3_GENDER_IDENTITY

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Gender identity and expression, pronouns, transgender status. Not on the list of section 2, but treated as sensitive because it exposes people to the same discrimination.

HOW IT IS FOUND

COLUMN NAME JM_L3_GENDER_IDENTITY — Path

95% `gender_?(identity|expression)` `preferred_?pronouns?` `pronouns?` `transgender` `trans_?status`

VALUE FORMAT JM_L3_GENDER_IDENTITY — Values

PATTERN	STRENGTH	NOTES
One of 14 known values, ignoring case — Woman, Man, Trans woman, Trans man, Non-binary, Gender fluid, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another value of the list.

`JM_GENDER_IDENTITY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_GENDER_IDENTITY_LIST`.

`JM_FLAG` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

`JM_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.

`JM_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.

`JM_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.

`JM_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

`JM_GENDER_IDENTITY_LIST` SECURE LOOKUP

Replaces the value with one of the 8 values in `jm-gender-identities.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trans man	→	**Gender fluid**

PART 10

Physical or mental health or condition

Sensitive under section 2 (e). The Act also defines health records and health information widely — payments for and eligibility to health services included — and voids any contract term that requires a person to hand over a copy of their health record (s. 64). A diagnosis, a sickle cell result, an antiretroviral or a pregnancy exposes a person as much as any other category; the blood group is, besides, biometric data by name.

10.1 Health identifiers

JM_HEALTH_ID

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

National Health Fund and JADEP card numbers, medical record and patient numbers, admissions, prescriptions, medical certificates.

HOW IT IS FOUND

COLUMN NAME — JM_HEALTH_ID – Path

85%

`nhf(_?(card|no|num|number|id|member_?(no|id)))?` `jadep(_?(card|no|number|id))?` `drug_?serv(_?(no|number|card))?` `medical_?record(_?(no|num|number))?` `mrn` `patient_?(id|no|num|number)` `docket_?(no|num|number)_?(patient|hospital|clinic)` `chart_?(no|num|number)` `health_?(record|card|id|insurance)(_?(no|num|number))?` `hospital_?(no|num|number)` `admission_?(no|num|number)` `prescription_?(no|num|number)` `sick_?(note|leave|certificate)_?(no|num|number)` `medical_?certificate_?(no|num|number)`

55%

`chart` `admission` `episode`

HOW IT IS MASKED

Character by character, keeping the format.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
NHF-2024-00123	→	YSG-5528-69825

10.2 Diagnosis

JM_HEALTH_DIAGNOSIS

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Diagnoses, as ICD-10 codes (`D57.1` , `B20`) or text, and medical history, allergies and chronic conditions.

HOW IT IS FOUND

COLUMN NAME JM_HEALTH_DIAGNOSIS – Path

85% `diagnos(is|es|tic)[a-z_]*` `dx` `icd_?(10|11)?(_?code)?` `medical_?(condition|history|problem|diagnosis)` `health_?(condition|problem)` `chronic_?(condition|disease|illness)` `illness(es)?` `disease[a-z_]*` `comorbidit(y|ies)` `allerg(y|ies)` `cause_?of_?(death|admission|illness|injury|sick_?leave)` `reason_?for_?(visit|admission|consultation|sick_?leave)` `presenting_?complaint` `chief_?complaint` `pre_?existing_?conditions?`

VALUE FORMAT JM_HEALTH_DIAGNOSIS – Regex

PATTERN	STRENGTH	NOTES
`[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d)?`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code is replaced by another common code of the same format, with or without a decimal; text, by a common diagnosis. The real diagnosis does not survive.

`JM_DIAGNOSIS` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `JM_DIAGNOSIS_TEXT`.

> `JM_ICD10_DECIMAL` SECURE LOOKUP
>
> Replaces the value with one of the 33 values in `jm-icd10-decimal.txt`, chosen by a keyed hash.
>
> `JM_ICD10` SECURE LOOKUP
>
> Replaces the value with one of the 37 values in `jm-icd10.txt`, chosen by a keyed hash.
>
> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_DIAGNOSIS_TEXT` SECURE LOOKUP
>
> Replaces the value with one of the 30 values in `jm-diagnoses.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
D57.1	→	**J32.9**
Sickle cell anaemia	→	**Acute gastroenteritis**

10.3 Medication

JM_HEALTH_MEDICATION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Medications and prescriptions: an antiretroviral, hydroxyurea or an antipsychotic reveals the condition.

HOW IT IS FOUND

COLUMN NAME JM_HEALTH_MEDICATION – Path

85% `medications?` `medicines?` `drugs?_?(name|prescribed)` `prescribed_?(drugs?|medications?)` `prescription_?(drug|medication|item)s?` `active_?ingredient` `dosage` `treatment_?(drug|medication)`

VALUE FORMAT JM_HEALTH_MEDICATION – Values

PATTERN	STRENGTH	NOTES
One of 52 known values, ignoring case — Paracetamol, Ibuprofen, Naproxen, Diclofenac, Metformin, Glibenclamide, …	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag; any other value is replaced by a common medication.

`JM_MEDICATION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_MEDICATION_LIST`.

`JM_FLAG` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

`JM_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.

`JM_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.

`JM_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.

`JM_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

`JM_MEDICATION_LIST` SECURE LOOKUP

Replaces the value with one of the 26 values in `jm-medications.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Hydroxyurea 500 mg`	→	**`Ibuprofen`**

10.4 Clinical notes

JM_HEALTH_CLINICAL_TEXT

COLUMN NAME DATA TYPE FREE TEXT REDACTION

WHAT IT IS

Progress notes, nursing notes, discharge summaries, care plans.

HOW IT IS FOUND

COLUMN NAME JM_HEALTH_CLINICAL_TEXT – Path

85% `clinical_?notes?` `progress_?notes?` `nurs(e|ing)_?notes?` `doctors?_?notes?` `physician_?notes?` `medical_?notes?` `discharge_?(summary|notes?)` `clinical_?summary` `history_?of_?present(ing)?_?illness` `hpi` `physical_?exam(ination)?` `assessment_?(and_?)?plan` `treatment_?plan` `care_?plan` `triage_?notes?` `soap_?notes?` `anamnesis`

DATA TYPE JM_HEALTH_CLINICAL_TEXT – Type

Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

Free Text Redaction, as in *Free text*: identifiers become `[DATA]` and names `[NAME]`. The clinical content stays — the column remains sensitive and must not be used outside the health environment.

`JM_FREE_TEXT` FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATA]`, and the 3,790 terms of `jm-text-names.txt` with `[NAME]`.

EXAMPLES

VALUE		MASKED
`Patient Beckford, TRN 123-456-789, seen for headache.`	→	**`Patient [NAME], TRN [DATA], seen for headache.`**

10.5 Test results

JM_HEALTH_TEST_RESULT

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Laboratory results, HIV status, viral load, glucose, cholesterol, pregnancy tests, drug screens.

HOW IT IS FOUND

COLUMN NAME JM_HEALTH_TEST_RESULT – Path

80% `lab_?(result|test|value)s?` `test_?results?` `laboratory_?(result|test)s?` `hiv(_?(status|test|result))?` `viral_?load` `cd4(_?count)?` `blood_?(sugar|glucose|pressure)` `glucose` `hba1c` `cholesterol` `bmi` `pregnancy_?test` `drug_?(test|screen)` `covid_?(test|result)` `pcr_?result` `pap_?(smear|test)(_?result)?` `mammogram_?result` `x_?ray_?result` `psa(_?result)?`

50% `result` `test`

HOW IT IS MASKED

Character by character: numbers stay numbers, words stay words of the same shape.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Reactive	→	**Muikyaya**

10.6 Blood group

JM_HEALTH_BLOOD_GROUP

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

ABO group and Rh factor — health data, and biometric data by name in section 2.

HOW IT IS FOUND

COLUMN NAME JM_HEALTH_BLOOD_GROUP — Path

90% `blood_?(type|group)` `abo(_?rh)?` `rh_?factor` `rh`

VALUE FORMAT JM_HEALTH_BLOOD_GROUP — Values

PATTERN	STRENGTH	NOTES
One of 26 known values, ignoring case — A, A-, B, B-, AB, AB-, …	90%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

BloodType SL, which comes with the Masking Engine: replaced by another of the eight groups.

`dlpx-core:BloodType SL` SECURE LOOKUP

Comes with the Masking Engine and is used as it ships. Replaces the blood group with one of the eight groups, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
0+	→	**0−**

10.7 Disability

JM_HEALTH_DISABILITY

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Disability type and status, functional difficulties as the census asks about them, registration with the Jamaica Council for Persons with Disabilities.

HOW IT IS FOUND

COLUMN NAME JM_HEALTH_DISABILITY — Path

90% `disabilit(y|ies)[a-z_]*` `disabled` `impairments?` `handicap(ped)?` `special_?needs` `functional_?limitations?` `difficulty_?(seeing|hearing|walking|remembering|concentrating|self_?care|communicating)` `invalidity(_?(status|grade))?` `jcpd_?(no|number|registered|registration)`

VALUE FORMAT JM_HEALTH_DISABILITY — Values

PATTERN	STRENGTH	NOTES
One of 22 known values, ignoring case — Seeing, Hearing, Walking or climbing steps, Remembering or concentrating, Self-care, Communicating, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag; any other value is replaced by a category of the census list.

`JM_DISABILITY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_DISABILITY_LIST`.

`JM_FLAG` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

`JM_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.

`JM_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.

`JM_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.

`JM_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

`JM_DISABILITY_LIST` SECURE LOOKUP

Replaces the value with one of the 8 values in `jm-disabilities.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Severe psychosocial disability`	→	**`Communicating`**

10.8 Reproductive health

`JM_HEALTH_REPRODUCTIVE`

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy, gestation, abortions and miscarriages, contraception, fertility, antenatal and postnatal care, sexually transmitted infections.

HOW IT IS FOUND

COLUMN NAME `JM_HEALTH_REPRODUCTIVE – Path`

90% `pregnan(t|cy)[a-z_]*` `gestation(al)?(_?age)?` `weeks_?(of_?)?(pregnancy|gestation)` `lmp` `last_?menstrual_?period` `abortions?` `miscarriages?` `contracepti(on|ve)[a-z_]*` `family_?planning(_?method)?` `fertility` `infertility` `ivf` `gravida` `antenatal` `prenatal` `postnatal` `postpartum` `sti` `sexually_?transmitted(_?infection)?`

HOW IT IS MASKED

A flag stays a flag and a number gets other digits; any other value is suppressed to `Not stated`.

`JM_SUPPRESSED_CATEGORY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_SUPPRESS`.

`JM_FLAG` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

`JM_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.

`JM_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.

`JM_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.

`JM_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

`JM_SUPPRESS` SECURE LOOKUP

Replaces the value with one of the 1 values in `jm-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`12 weeks pregnant`	→	**`Not stated`**

10.9 Mental health

JM_HEALTH_MENTAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Mental health conditions, psychiatric and psychological care, suicide and self-harm, substance use and rehabilitation.

HOW IT IS FOUND

COLUMN NAME JM_HEALTH_MENTAL — Path

90% `mental_?(health|illness|disorder|condition)` `psychiatr[a-z_]*` `psycholog[a-z_]*` `depression` `anxiety` `suicid[a-z_]*` `self_?harm` `substance_?(use|abuse|misuse)` `alcohol(ism|_?use|_?abuse|_?dependence)` `drug_?(use|abuse|addiction|dependence)` `ganja_?use` `cannabis_?use` `addiction[a-z_]*` `rehab(ilitation)?_?(programme|program|centre|center|status)`

HOW IT IS MASKED

A flag stays a flag; any other value is suppressed to `Not stated`.

`JM_SUPPRESSED_CATEGORY` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_SUPPRESS`.

`JM_FLAG` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

`JM_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.

`JM_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.

`JM_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.

`JM_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

`JM_SUPPRESS` SECURE LOOKUP

Replaces the value with one of the 1 values in `jm-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Bipolar disorder`	→	**`Not stated`**

PART 11

Financial data

The Act does not list financial data as sensitive. It is personal data all the same, and other laws close it further: banks and other licensees keep their customers' information under the duty of confidentiality of the Banking Services Act, 2014, and credit information circulates only among the credit bureaus licensed under the Credit Reporting Act, 2010. In a test copy a salary, a loan in arrears, an NIS benefit or a PATH flag says a great deal about a person. Categories are replaced within their own notation; amounts keep their number of digits, with no link to the real value.

11.1 Credit reference

JM_FIN_CREDIT_REFERENCE

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Credit scores and reports, days past due, arrears, loan classification, written-off and non-performing loans — what the credit bureaus licensed under the Credit Reporting Act, 2010 gather from lenders.

HOW IT IS FOUND

COLUMN NAME JM_FIN_CREDIT_REFERENCE — Path

90% `credit_?(score|rating|history|report|status|bureau|reference|risk|grade|standing)` `crif(_?(score|report|status))?` `creditinfo(_?(score|report|status))?` `delinquen(cy|t)(_?(status|days))?` `days_?(past_?due|in_?arrears|overdue)` `dpd` `arrears(_?(status|days))?` `past_?due(_?(days|status))?` `overdue_?(days|status)` `default_?(status|flag|indicator)` `defaulted` `written_?off` `write_?off(_?(status|flag))?` `collections?_?status` `bad_?debt` `loan_?(status|classification|grade)` `non_?performing` `npl`

HOW IT IS MASKED

A score gets other digits, a flag stays a flag and any status is replaced by another credit status.

`JM_CREDIT` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_CREDIT_STATUS`.

> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CREDIT_STATUS` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `jm-credit-statuses.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
90 days past due	→	**no credit history**
745	→	**471**

11.2 Debt amount

JM_FIN_DEBT

COLUMN NAME · DATA TYPE · NUMERIC MAPPING

WHAT IT IS

Loan, mortgage and card balances, amounts in arrears, credit limits, instalments.

HOW IT IS FOUND

> COLUMN NAME JM_FIN_DEBT – Path
>
> 85% `loan_?(amount|balance|principal|outstanding)` `outstanding_?(balance|amount|debt|loan|principal)` `debt(_?(amount|total|balance))?` `amount_?(owed|due|outstanding|in_?arrears|overdue)` `balance_?(owed|outstanding|due)` `arrears_?amount` `credit_?limit` `mortgage_?(balance|amount)` `instal?lment(_?amount)?` `monthly_?(payment|repayment)`

> DATA TYPE JM_FIN_DEBT – Type
>
> Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
850000	→	**847556**

11.3 Income

JM_FIN_INCOME

COLUMN NAME · DATA TYPE · NUMERIC MAPPING

WHAT IT IS

Salary, wages, emoluments, insurable earnings, household income.

HOW IT IS FOUND

> COLUMN NAME JM_FIN_INCOME – Path
>
> 85% `salary` `salaries` `wages?` `income[a-z_]*` `gross_?(pay|salary|income|earnings)` `net_?(pay|salary|income|earnings)` `(monthly|annual|weekly|fortnightly)_?(income|salary|earnings|pay|wage)` `earnings` `remuneration` `basic_?(pay|salary)` `emoluments?` `insurable_?earnings` `household_?income` `take_?home_?pay`

DATA TYPE JM_FIN_INCOME – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
240000.50	→	**903205.60**

11.4 Assets

JM_FIN_ASSETS

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Property and land values, savings and deposit balances, investments, unit trusts, net worth.

HOW IT IS FOUND

COLUMN NAME JM_FIN_ASSETS – Path

85% `net_?worth` `assets?_?(value|total)` `total_?assets` `property_?value` `land_?value` `market_?value` `appraised_?value` `valuation_?amount` `savings(_?balance)?` `account_?balance` `deposit_?balance` `fixed_?deposit(_?amount)?` `investment_?(balance|value|amount)` `share_?(balance|capital)` `unit_?trust_?(balance|value)`

DATA TYPE JM_FIN_ASSETS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
18500000	→	**26017706**

11.5 Pension amount

JM_FIN_PENSION

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

NIS pensions, occupational and superannuation pensions, survivors' and invalidity pensions, gratuities.

HOW IT IS FOUND

COLUMN NAME JM_FIN_PENSION – Path

90% `pension(_?(amount|payment|monthly|benefit_?amount|balance))?` `monthly_?pension` `retirement_?(pension|benefit|amount|balance)` `nis_?pension(_?amount)?` `survivors?_?pension(_?amount)?` `widow(er)?s?_?pension(_?amount)?` `invalidity_?pension(_?amount)?` `gratuity(_?amount)?` `superannuation(_?(balance|amount))?` `provident_?fund(_?balance)?`

DATA TYPE JM_FIN_PENSION – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
6800	→	8189

11.6 NIS benefit

JM_FIN_NIS_BENEFIT

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The benefit the National Insurance Scheme pays: old age pension, invalidity, widow's or widower's and orphan's benefits, special child benefit, employment injury and disablement, maternity allowance, funeral grant. Most reveal a health event or a death in the family.

HOW IT IS FOUND

COLUMN NAME JM_FIN_NIS_BENEFIT – Path

90% `nis_?(benefit|claim)(_?(type|status|category))?` `benefit_?(type|claim|category|name|code)` `claim_?type` `(sickness|maternity|funeral|invalidity|survivors?|widow(er)?s?|orphans?|employment_?injury|disablement|old_?age)_?(benefit|allowance|grant|claim)` `national_?insurance_?(benefit|claim)(_?type)?`

VALUE FORMAT JM_FIN_NIS_BENEFIT – Values

PATTERN	STRENGTH	NOTES
One of 23 known values, ignoring case — Old age pension, Invalidity benefit, Widow s or widower s benefit, Orphan s benefit, Special child benefit, Employment injury benefit, ...	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag; any other value is replaced by another benefit of the list.

`JM_NIS_BENEFIT` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_NIS_BENEFIT_LIST`.

`JM_FLAG` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `JM_FLAG_YES_NO` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
>
> `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
>
> `JM_FLAG_Y_N` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
>
> `JM_FLAG_0_1` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

`JM_NIS_BENEFIT_LIST` SECURE LOOKUP

Replaces the value with one of the 11 values in `jm-nis-benefits.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Special child benefit`	→	**`Old age pension`**

11.7 Social programme

`JM_FIN_SOCIAL_PROGRAMME`

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Beneficiaries of PATH — the Programme of Advancement Through Health and Education —, the social pension, the Rehabilitation Programme, poor relief and the NHF and JADEP subsidies. Being a beneficiary reveals poverty.

HOW IT IS FOUND

> COLUMN NAME `JM_FIN_SOCIAL_PROGRAMME – Path`
>
> 90% `path(_?(beneficiary|programme|program|member|recipient|status|family))?` `programme_?of_?advancement` `social_?(programme|program|assistance|welfare|benefit|transfer|pension)s?` `welfare_?(programme|program|recipient|status)` `cash_?transfer` `poor_?relief` `beneficiary_?of_?(programme|program)` `programme_?beneficiary` `rehabilitation_?(grant|programme|program)` `compassionate_?grant`

> VALUE FORMAT `JM_FIN_SOCIAL_PROGRAMME – Values`
>
PATTERN	STRENGTH	NOTES
One of 17 known values, ignoring case — PATH, Social Pension, Rehabilitation Programme, Poor Relief, NHF subsidy, JADEP, …	80%	
One of 6 known values, ignoring case — y, n, yes, no, 0, 1	30%	
>
> A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag; any other value is replaced by another programme of the list.

`JM_SOCIAL_PROGRAMME` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_SOCIAL_PROGRAMME_LIST`.

`JM_FLAG` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `JM_FLAG_YES_NO` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
>
> `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
>
> `JM_FLAG_Y_N` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
>
> `JM_FLAG_0_1` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

`JM_SOCIAL_PROGRAMME_LIST` SECURE LOOKUP

Replaces the value with one of the 8 values in `jm-social-programmes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
School feeding programme	→	**Poor Relief**

11.8 Poverty and socio-economic status

JM_FIN_POVERTY

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Poverty status, consumption quintiles and deciles of the Jamaica Survey of Living Conditions, means-test and Beneficiary Identification System scores.

HOW IT IS FOUND

> COLUMN NAME JM_FIN_POVERTY – Path
>
> 90% `poverty(_?(status|level|line|index|score|category))?` `food_?poor` `socio_?economic_?(status|level|index|group|class|score)` `wealth_?(index|quintile)` `consumption_?(quintile|decile)` `income_?(quintile|decile|bracket|band)` `quintile` `decile` `vulnerability_?(index|score)` `mpi` `means_?test(_?(score|result))?` `beneficiary_?identification_?(score|system)` `bis_?score`

> VALUE FORMAT JM_FIN_POVERTY – Values
>
PATTERN	STRENGTH	NOTES
One of 9 known values, ignoring case — food poor, indigent, poor, not poor, vulnerable, non poor, …	40%	
>
> A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A quintile stays a quintile, a decile a decile, and a status is replaced by another status.

`JM_POVERTY` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `JM_POVERTY_STATUS`.

> `JM_QUINTILE` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `jm-quintile.txt`, chosen by a keyed hash.
>
> `JM_DECILE_HIGH` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `jm-decile-high.txt`, chosen by a keyed hash.

`JM_DECILE` SECURE LOOKUP

Replaces the value with one of the 10 values in `jm-decile.txt`, chosen by a keyed hash.

`JM_POVERTY_STATUS` SECURE LOOKUP

Replaces the value with one of the 4 values in `jm-poverty-statuses.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Food poor	→	**Food poor**
Quintile 2	→	**Quintile 4**

11.9 Housing tenure

JM_FIN_HOUSING

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Ownership of the dwelling as the census asks for it — owned, rented, leased, rent free, family land, squatted — and the land tenure.

HOW IT IS FOUND

COLUMN NAME JM_FIN_HOUSING – Path

95%	`housing_?(tenure|status|type|situation)` `dwelling_?(tenure|ownership|type)` `home_?ownership` `own_?or_?rent` `rent_?or_?own` `owns_?(home|house)` `squatt(er|ing)(_?status)?` `land_?tenure` `captured_?land` `family_?land`
55%	`tenure`

VALUE FORMAT JM_FIN_HOUSING – Values

PATTERN	STRENGTH	NOTES
One of 21 known values, ignoring case — Owned, Owned with mortgage, Rented, Leased, Rent free, Family land, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another tenure of the list.

`JM_HOUSING` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_HOUSING_LIST`.

`JM_FLAG` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

`JM_FLAG_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.

`JM_FLAG_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.

`JM_FLAG_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.

`JM_FLAG_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

`JM_HOUSING_LIST` SECURE LOOKUP

> Replaces the value with one of the 8 values in `jm-housing-tenure.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Captured land`	→	**Leased**

PART 12

Offences and proceedings

Section 2 (g) makes sensitive the alleged commission of any offence and the proceedings for it — so a charge that ended in acquittal is as protected as a conviction. The Criminal Records (Rehabilitation of Offenders) Act lets old convictions be expunged; a test copy that keeps them undoes that.

12.1 Offences and proceedings

JM_PENAL_CRIMINAL_RECORD

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Criminal record, police record or certificate, convictions, offences, charges, arrests, remand, bail, verdicts, sentences and expungements — the allegation and the proceedings, whatever their outcome.

HOW IT IS FOUND

COLUMN NAME JM_PENAL_CRIMINAL_RECORD – Path

95% `criminal_?(record|history|conviction|convictions|status|background|charges?|proceedings|case_?(status|outcome))` `police_?(record|certificate|clearance|report_?status)` `convictions?(_?(status|record|details))?` `convicted` `previous_?convictions` `offen[cs]es?(_?(type|committed|code|description|details))?` `charged_?with` `arrests?(_?(record|history))?` `sentence(_?(imposed|type|length|details))?` `incarcerat(ed|ion)` `imprisonment` `remand(ed)?(_?status)?` `bail(_?status)?` `probation(_?status)?` `parole` `verdict` `acquitt(al|ed)` `expunge(d|ment)`

55% `court_?(outcome|disposal|decision|status)` `case_?(outcome|disposal)` `disposal`

HOW IT IS MASKED

A flag stays a flag; any other value becomes a generic status: no criminal record, has criminal record, charged, case dismissed, acquitted, convicted, record expunged or not stated.

`JM_CRIMINAL_RECORD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_CRIMINAL_RECORD_LIST`.

> `JM_FLAG` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `JM_FLAG_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.
> >
> > `JM_FLAG_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.
>
> `JM_CM_ALNUM` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.
>
> `JM_CRIMINAL_RECORD_LIST` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `jm-criminal-record.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Convicted of larceny, 2019`	→	**`Acquitted`**

12.2 Case number

JM_PENAL_CASE_NUMBER

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

Court case, indictment, information and charge sheet numbers, police report and station diary numbers (`HCC 123/2023` , `456 of 2022`).

HOW IT IS FOUND

COLUMN NAME JM_PENAL_CASE_NUMBER — Path

90%	`court_?case_?(no|num|number)` `criminal_?case_?(no|num|number)` `indictment_?(no|num|number)` `information_?(no|num|number)` `charge_?sheet_?(no|num|number)` `police_?(report|station_?diary|case)_?(no|num|number)` `station_?diary_?(no|number|entry)` `docket_?(no|num|number)` `inquest_?(no|number)`
55%	`case_?(no|num|number|ref|reference)`

VALUE FORMAT JM_PENAL_CASE_NUMBER — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{1,4}\s?\d{1,5}/\d{4}`	50%	
`(?i)\d{1,6}\s+of\s+\d{4}`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the format.

`JM_CM_ALNUM` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`HCC 123/2023`	→	**`YVJ 968/6016`**

13

Where people live: towns

With the towns of the 2022 Population and Housing Census and their populations, the set knows the size and parish of all 140 towns the census list counts.

- A **town** under 10,000 inhabitants becomes the **capital of its parish**: Kingston; Half Way Tree for St. Andrew; Spanish Town; May Pen; Mandeville; Black River; Savanna-la-Mar; Lucea; Montego Bay; Falmouth; St. Ann's Bay; Port Maria; Port Antonio; Morant Bay. 111 of the 140 towns are generalized.
- The **parish** stays: the smallest, Hanover, has about 70,000 inhabitants.
- The capitals keep their names, even the small ones — Morant Bay, Black River, Port Antonio. A capital in a masked column says the parish, no more: it is the place that stands for the whole parish.
- Twenty-four towns of 10,000 or more stay as they are, Portmore, Montego Bay, Spanish Town, May Pen, Mandeville and Old Harbour among them.
- Names are also recognized as they are commonly written: `St. Ann's Bay` and `St Anns Bay`, `Savanna la Mar` and `Sav-la-Mar`, `Halfway Tree`, `Mobay`.

The result is always a real place in the same parish, and every group of people who end up sharing a name is the population of a parish or of a large town. Names that are also given names or surnames, and the parish names, are left out of the detection list, so that a surname column is not taken for towns.

14

Limits

- **Binary columns** — scans of the TRN card, licence or passport, photographs, fingerprint images, clinical PDFs in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **Communities smaller than a town stay out of the table.** The census list stops at 140 towns; a column of rural districts (`Content`, `Mocho`) is detected by its name, but values the table does not know pass unchanged. Where such a column sits next to a birth date and sex, generalize it to the parish.
- **Identity numbers keep no check digit.** None is published for the TRN or the NIS number, so none is recomputed; applications that validate one may reject masked values.
- **Company TRNs are masked too.** They cannot be told apart from a person's.
- **Passport, NIS, permit and voter numbers** have no public format and are masked character by character.
- **Data Cleansing leaves unknown values as they are**: a town spelled in a way the list does not have passes unchanged.
- **Free text** is redacted token by token: a phone written with spaces is not found, and a given name that is also a common word (`Joy`, `Hope`, `Grace`) is redacted wherever it appears.
- **Colour words are surnames.** Brown, Black, Green and Grey are among the most common Jamaican surnames: with only the essential pack loaded, a column of eye colours is taken for names.
- **Minors** — the Act counts anyone under 18. A birth date moves at most 60 days, so few people cross their 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, district, town and parish in separate columns are masked independently and no longer form a coherent address.
- **Plates and VINs** keep their format, but not the VIN check digit.

15

Verification

Before publication the set was checked outside a Masking Engine:

- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 157 columns with the whole set at its assignment threshold — well named, badly named, eight with the short names of packaged systems and 33 columns that are not personal data — again on 148 of them padded with spaces or zeros, and again with the classifiers of the essential pack alone.
- The table that generalizes towns was audited for all 140 towns.
- The algorithms, run with the Delphix algorithm plugin, masked 153 sample values and 204 placeholders such as `N/A`, checking each output against its vocabulary; the same values again padded with spaces or zeros (314), which had to mask as their bare value; 150 TRNs for collisions, and twenty TRNs as driver's licence numbers, which had to mask alike. Each of the 83 algorithms also masked its own sample input.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

16

Sources

- The Data Protection Act, 2020 — Parliament of Jamaica; text published by the Ministry of Justice and the Office of the Information Commissioner, with the notice of commencement of 1 December 2023.
- Population by town and parish — 2022 Population and Housing Census, Statistical Institute of Jamaica (STATIN). Ethnic origin, religion, union status and dwelling tenure — 2011 Census, STATIN.
- Taxpayer Registration Number — Tax Administration Jamaica. National Identification and Registration Act, 2021 — National Identification System (NIDS).
- National Insurance Scheme and its benefits, PATH and the social pension — Ministry of Labour and Social Security. NHF and JADEP — National Health Fund.
- Voter identification card — Electoral Office of Jamaica. Passports and immigration — Passport, Immigration and Citizenship Agency.
- Banking Services Act, 2014 — Bank of Jamaica. Credit Reporting Act, 2010 — Bank of Jamaica. Poverty measures — Jamaica Survey of Living Conditions, Planning Institute of Jamaica.
- Status of Children Act; Offences Against the Person Act; Criminal Records (Rehabilitation of Offenders) Act; DNA Evidence Act, 2016 — Laws of Jamaica, Ministry of Justice.
- Frequency of surnames and given names — Forebears, and the Registrar General's Department lists of baby names. Telephone numbering — North American Numbering Plan. Licence plates — Island Traffic Authority and Tax Administration Jamaica.

APPENDIX A

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

JM_ADDRESS SECURE LOOKUP

Replaces the value with one of the 3,000 values in `jm-addresses.txt`, chosen by a keyed hash.

Used by: `JM_L1_ADDRESS`

CONFIGURATION

lookupFile	`jm-addresses.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_AGE REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `JM_L2_AGE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-9]\d{2,}))`	keep · replace with `90`
`(0*?)(?:([1-9])(\d)(\.\d+))`	keep · keep · `JM_CM_ALNUM` · keep
`(0*?)(?:([1-9])(\d))`	keep · keep · `JM_CM_ALNUM`
`(0*?)(?:(\d))`	keep · `JM_CM_ALNUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

JM_BIRTH_DATE DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `JM_L2_BIRTH_DATE`

CONFIGURATION

minRange	`-60`
maxRange	`60`
unit	`DAYS`
roll	no

JM_CAPPED_COUNT REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `JM_L2_DEPENDANTS`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([0-5]))`	keep · keep
`(0*?)(?:(\d+))`	keep · replace with `5`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

JM_CARD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `JM_L1_PAYMENT_CARD`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d[\d\s\-]{11,22}\d))`	keep · `dlpx-core:Credit Card`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

JM_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `JM_L1_TRN`, `JM_L1_NIS_NUMBER`, `JM_L1_PASSPORT`, `JM_L1_VOTER_ID`, `JM_L1_DRIVERS_LICENCE`, `JM_L1_IMMIGRATION_DOCUMENT`, `JM_L1_VITAL_RECORD`, `JM_L1_ADDRESS_DETAIL`, `JM_L1_BANK_ACCOUNT`, `JM_L1_VIN`, `JM_L1_CONTRACT_NUMBER`, `JM_L1_USERNAME`, `JM_HEALTH_ID`, `JM_HEALTH_TEST_RESULT`, `JM_PENAL_CASE_NUMBER`, `JM_SUPPRESSED_CATEGORY`, `JM_GIVEN_NAMES`, `JM_SURNAMES`, `JM_FULL_NAME`, `JM_EMAIL`, `JM_PHONE`, `JM_PLATE`, `JM_LAND_TITLE`, `JM_COORDINATE`, `JM_YEAR`, `JM_AGE`, `JM_HEIGHT`, `JM_EYE_COLOUR`, `JM_FILIATION`, `JM_ETHNICITY`, `JM_RELIGION`, `JM_POLITICAL_OPINION`, `JM_POLITICAL_PARTY`, `JM_SEXUAL_ORIENTATION`, `JM_GENDER_IDENTITY`, `JM_MEDICATION`, `JM_DISABILITY`, `JM_CREDIT`, `JM_NIS_BENEFIT`, `JM_SOCIAL_PROGRAMME`, `JM_HOUSING`, `JM_CRIMINAL_RECORD`

CONFIGURATION

characterGroups	`0123456789` `AEIOU` `BCDFGHJKLMNPQRSTVWXYZ` `aeiou` `bcdfghjklmnpqrstvwxyz`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

JM_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `JM_L1_DEVICE_ID`, `JM_IP`

CONFIGURATION

characterGroups	`0123456789` `abcdef` `ABCDEF` `ghijklmnopqrstuvwxyz` `GHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

JM_COORDINATE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `JM_L1_GEOLOCATION`

PATTERNS, TRIED IN ORDER

`(-?\d{1,3}\.\d)(\d+)\s*,\s*(-?\d{1,3}\.\d)(\d+)`	keep · `JM_CM_ALNUM` · keep · `JM_CM_ALNUM`
`(-?\d{1,3}\.\d)(\d+)`	keep · `JM_CM_ALNUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

JM_CREDIT REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_CREDIT_STATUS`.

Used by: `JM_FIN_CREDIT_REFERENCE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2,3}))`	keep · `JM_CM_ALNUM`
`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
otherwise	`JM_CREDIT_STATUS`

CONFIGURATION

trimInput	yes
requireMask	no

JM_CREDIT_STATUS SECURE LOOKUP

Replaces the value with one of the 10 values in `jm-credit-statuses.txt`, chosen by a keyed hash.

Used by: `JM_CREDIT`

CONFIGURATION

lookupFile	`jm-credit-statuses.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_CRIMINAL_RECORD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_CRIMINAL_RECORD_LIST`.

Used by: `JM_PENAL_CRIMINAL_RECORD`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_CRIMINAL_RECORD_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

JM_CRIMINAL_RECORD_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `jm-criminal-record.txt`, chosen by a keyed hash.

Used by: `JM_CRIMINAL_RECORD`

CONFIGURATION

lookupFile	`jm-criminal-record.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_DECILE SECURE LOOKUP

Replaces the value with one of the 10 values in `jm-decile.txt`, chosen by a keyed hash.

Used by: `JM_POVERTY`

CONFIGURATION

lookupFile	`jm-decile.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_DECILE_HIGH SECURE LOOKUP

Replaces the value with one of the 5 values in `jm-decile-high.txt`, chosen by a keyed hash.

Used by: `JM_POVERTY`

CONFIGURATION

lookupFile	`jm-decile-high.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_DIAGNOSIS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `JM_DIAGNOSIS_TEXT`.

Used by: `JM_HEALTH_DIAGNOSIS`

PATTERNS, TRIED IN ORDER

`([A-TV-Za-tv-z]\d{2}\.\d{1,2})`	`JM_ICD10_DECIMAL`
`([A-TV-Za-tv-z]\d{2,3})`	`JM_ICD10`
`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
otherwise	`JM_DIAGNOSIS_TEXT`

CONFIGURATION

trimInput	yes

requireMask	no

JM_DIAGNOSIS_TEXT SECURE LOOKUP

Replaces the value with one of the 30 values in `jm-diagnoses.txt`, chosen by a keyed hash.

Used by: `JM_DIAGNOSIS`

CONFIGURATION

lookupFile	`jm-diagnoses.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_DISABILITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_DISABILITY_LIST`.

Used by: `JM_HEALTH_DISABILITY`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_DISABILITY_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

JM_DISABILITY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `jm-disabilities.txt`, chosen by a keyed hash.

Used by: `JM_DISABILITY`

CONFIGURATION

lookupFile	`jm-disabilities.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_EDUCATION SECURE LOOKUP

Replaces the value with one of the 11 values in `jm-education.txt`, chosen by a keyed hash.

Used by: `JM_L2_EDUCATION`

CONFIGURATION

lookupFile	`jm-education.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: JM_CM_ALNUM.

Used by: JM_L1_EMAIL

PATTERNS, TRIED IN ORDER

([^@\s]+)@([^@\s]+)\.([A-Za-z]{2,24})	JM_CM_ALNUM · JM_CM_ALNUM · replace with test
otherwise	JM_CM_ALNUM

CONFIGURATION

trimInput	yes
requireMask	no

JM_EMPLOYER SECURE LOOKUP

Replaces the value with one of the 25 values in jm-employers.txt, chosen by a keyed hash.

Used by: JM_L2_EMPLOYER

CONFIGURATION

lookupFile	jm-employers.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_ETHNICITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: JM_ETHNICITY_LIST.

Used by: JM_L3_ETHNICITY

PATTERNS, TRIED IN ORDER

(?i)(yes|no|true|false|[yn01])	JM_FLAG
(0*?)(?:(\d{1,6}))	keep · JM_CM_ALNUM
otherwise	JM_ETHNICITY_LIST

CONFIGURATION

trimInput	yes
requireMask	no

JM_ETHNICITY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in jm-ethnic-groups.txt, chosen by a keyed hash.

Used by: JM_ETHNICITY

CONFIGURATION

lookupFile	jm-ethnic-groups.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_EVENT_DATE DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `JM_L2_EVENT_DATE`

CONFIGURATION

minRange	`-30`
maxRange	`30`
unit	`DAYS`
roll	no

JM_EYE_COLOUR REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_EYE_COLOUR_LIST`.

Used by: `JM_L3_EYE_COLOUR`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_EYE_COLOUR_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

JM_EYE_COLOUR_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `jm-eye-colours.txt`, chosen by a keyed hash.

Used by: `JM_EYE_COLOUR`

CONFIGURATION

lookupFile	`jm-eye-colours.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_FILIATION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_FILIATION_LIST`.

Used by: `JM_L3_FILIATION`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_FILIATION_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

JM_FILIATION_LIST SECURE LOOKUP

Replaces the value with one of the 6 values in `jm-filiation.txt`, chosen by a keyed hash.

Used by: `JM_FILIATION`

CONFIGURATION

lookupFile	`jm-filiation.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_FLAG REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `JM_SUPPRESSED_CATEGORY`, `JM_EYE_COLOUR`, `JM_FILIATION`, `JM_ETHNICITY`, `JM_RELIGION`, `JM_POLITICAL_OPINION`, `JM_POLITICAL_PARTY`, `JM_SEXUAL_ORIENTATION`, `JM_GENDER_IDENTITY`, `JM_DIAGNOSIS`, `JM_MEDICATION`, `JM_DISABILITY`, `JM_CREDIT`, `JM_NIS_BENEFIT`, `JM_SOCIAL_PROGRAMME`, `JM_HOUSING`, `JM_CRIMINAL_RECORD`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no)`	`JM_FLAG_YES_NO`
`(?i)(true|false)`	`JM_FLAG_TRUE_FALSE`
`(?i)([yn])`	`JM_FLAG_Y_N`
`([01])`	`JM_FLAG_0_1`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

JM_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-0-1.txt`, chosen by a keyed hash.

Used by: `JM_FLAG`

CONFIGURATION

lookupFile	`jm-flag-0-1.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-true-false.txt`, chosen by a keyed hash.

Used by: `JM_FLAG`

CONFIGURATION

lookupFile	`jm-flag-true-false.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-y-n.txt`, chosen by a keyed hash.

Used by: `JM_FLAG`

CONFIGURATION

lookupFile	`jm-flag-y-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `jm-flag-yes-no.txt`, chosen by a keyed hash.

Used by: `JM_FLAG`

CONFIGURATION

lookupFile	`jm-flag-yes-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_FREE_TEXT FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATA]`, and the 3,790 terms of `jm-text-names.txt` with `[NAME]`.

Used by: `JM_L1_FREE_TEXT`, `JM_HEALTH_CLINICAL_TEXT`

PATTERNS, TRIED IN ORDER

`(?<![\d\-])\d{3}-\d{3}-\d{3}(?![\d\-])`

`(?<!\d)\d{9}(?!\d)`

`[\w.+\-]+@[\w\-]+(\.[\w\-]+)+`

`(?<![\d\-])(\+?1[\s\-.]?)?\(?(876|658)\)?[\s\-.]?\d{3}[\s\-.]?\d{4}(?![\d\-])`

`(?<![\d\-])[2-9]\d{2}-\d{4}(?![\d\-])`

`(?<!\d)\d{13,19}(?!\d)`

`(?<![A-Za-z\d])\d{4}\s?[A-Z]{2}(?![A-Za-z\d])`

`(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\d)`

CONFIGURATION

regExRedactValue	`[DATA]`

lookupFile	jm-text-names.txt
lookupFileRedactValue	[NAME]
isDenyList	yes

JM_FULL_NAME REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: JM_CM_ALNUM .

Used by: JM_L1_FULL_NAME

PATTERNS, TRIED IN ORDER

([^,]+),\s*(.+)	JM_SURNAMES · JM_GIVEN_NAMES
(\S+)	JM_GIVEN_NAME
(\S+)\s+(\S+)	JM_GIVEN_NAME · JM_SURNAMES
(\S+)(\s+)([A-Za-z]\.?)(\s+)(\S+)	JM_GIVEN_NAME · keep · keep · keep · JM_SURNAMES
(\S+)\s+(\S+)\s+(\S+)	JM_GIVEN_NAME · JM_GIVEN_NAME · JM_SURNAMES
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	JM_GIVEN_NAME · JM_GIVEN_NAME · JM_GIVEN_NAME · JM_SURNAMES
otherwise	JM_CM_ALNUM

CONFIGURATION

trimInput	yes
requireMask	no

JM_GENDER_IDENTITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: JM_GENDER_IDENTITY_LIST .

Used by: JM_L3_GENDER_IDENTITY

PATTERNS, TRIED IN ORDER

(?i)(yes|no|true|false|[yn01])	JM_FLAG
(0*?)(?:(\d{1,6}))	keep · JM_CM_ALNUM
otherwise	JM_GENDER_IDENTITY_LIST

CONFIGURATION

trimInput	yes
requireMask	no

JM_GENDER_IDENTITY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in jm-gender-identities.txt , chosen by a keyed hash.

Used by: JM_GENDER_IDENTITY

CONFIGURATION

lookupFile	jm-gender-identities.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_GIVEN_NAME NAME

Replaces the name with one of the 1,004 names in jm-given-names.txt .

Used by: `JM_GIVEN_NAMES` , `JM_FULL_NAME`

CONFIGURATION

lookupFile	`jm-given-names.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

JM_GIVEN_NAMES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM` .

Used by: `JM_L1_GIVEN_NAME` , `JM_FULL_NAME`

PATTERNS, TRIED IN ORDER

`(\S+)`	`JM_GIVEN_NAME`
`(\S+)\s+(\S+)`	`JM_GIVEN_NAME` · `JM_GIVEN_NAME`
`(\S+)\s+(\S+)\s+(\S+)`	`JM_GIVEN_NAME` · `JM_GIVEN_NAME` · `JM_GIVEN_NAME`
otherwise	`JM_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

JM_HEIGHT REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `JM_L3_HEIGHT`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(1|2)(\d{2})(\s*cm)?)`	keep · keep · `JM_CM_ALNUM` · keep
`(0*?)(?:([12]\.)(\d{1,2})(\s*m)?)`	keep · keep · `JM_CM_ALNUM` · keep
`(0*?)(?:([4-7])(\s*(?:'|ft\.?|feet)\s*)(\d{1,2})(\s*(?:"|''|in\.?|inches)?))`	keep · keep · keep · `JM_INCHES` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

JM_HOUSING REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_HOUSING_LIST` .

Used by: `JM_FIN_HOUSING`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_HOUSING_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

JM_HOUSING_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `jm-housing-tenure.txt`, chosen by a keyed hash.

Used by: `JM_HOUSING`

CONFIGURATION

lookupFile	`jm-housing-tenure.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_ICD10 SECURE LOOKUP

Replaces the value with one of the 37 values in `jm-icd10.txt`, chosen by a keyed hash.

Used by: `JM_DIAGNOSIS`

CONFIGURATION

lookupFile	`jm-icd10.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_ICD10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `jm-icd10-decimal.txt`, chosen by a keyed hash.

Used by: `JM_DIAGNOSIS`

CONFIGURATION

lookupFile	`jm-icd10-decimal.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_INCHES SECURE LOOKUP

Replaces the value with one of the 12 values in `jm-inches.txt`, chosen by a keyed hash.

Used by: `JM_HEIGHT`

CONFIGURATION

lookupFile	`jm-inches.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `JM_CM_HEX`.

Used by: `JM_L1_IP_ADDRESS`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}))`	keep · `JM_OCTET` · `JM_OCTET` · `JM_OCTET` · `JM_OCTET`
otherwise	`JM_CM_HEX`

CONFIGURATION

trimInput	yes
requireMask	no

JM_LAND_TITLE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `JM_CM_ALNUM`.

Used by: `JM_L1_LAND_TITLE`

PATTERNS, TRIED IN ORDER

`(?i)(.*?vol(?:ume)?\.?\s*)(\d+)(.*?fol(?:io)?\.?\s*)(\d+)(.*)`	keep · `JM_CM_ALNUM` · keep · `JM_CM_ALNUM` · keep
otherwise	`JM_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

JM_MARITAL_STATUS SECURE LOOKUP

Replaces the value with one of the 7 values in `jm-marital-status.txt`, chosen by a keyed hash.

Used by: `JM_L2_MARITAL_STATUS`

CONFIGURATION

lookupFile	`jm-marital-status.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_MEDICATION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_MEDICATION_LIST`.

Used by: `JM_HEALTH_MEDICATION`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_MEDICATION_LIST`

CONFIGURATION

trimInput	yes

requireMask	no

JM_MEDICATION_LIST SECURE LOOKUP

Replaces the value with one of the 26 values in `jm-medications.txt`, chosen by a keyed hash.

Used by: `JM_MEDICATION`

CONFIGURATION

lookupFile	`jm-medications.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_NATIONALITY SECURE LOOKUP

Replaces the value with one of the 16 values in `jm-nationalities.txt`, chosen by a keyed hash.

Used by: `JM_L2_NATIONALITY`

CONFIGURATION

lookupFile	`jm-nationalities.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_NEIGHBOURHOOD SECURE LOOKUP

Replaces the value with one of the 77 values in `jm-neighbourhoods.txt`, chosen by a keyed hash.

Used by: `JM_L2_NEIGHBOURHOOD`

CONFIGURATION

lookupFile	`jm-neighbourhoods.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_NIS_BENEFIT REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_NIS_BENEFIT_LIST`.

Used by: `JM_FIN_NIS_BENEFIT`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_NIS_BENEFIT_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

JM_NIS_BENEFIT_LIST SECURE LOOKUP

Replaces the value with one of the 11 values in `jm-nis-benefits.txt`, chosen by a keyed hash.

Used by: `JM_NIS_BENEFIT`

CONFIGURATION

lookupFile	`jm-nis-benefits.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_OCCUPATION SECURE LOOKUP

Replaces the value with one of the 41 values in `jm-occupations.txt`, chosen by a keyed hash.

Used by: `JM_L2_OCCUPATION`

CONFIGURATION

lookupFile	`jm-occupations.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_OCTET NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `JM_IP`

CONFIGURATION

minValue	`1`
maxValue	`254`

JM_PHONE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM`.

Used by: `JM_L1_PHONE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\+?1[\s\-.]?)?(\(?(?:876|658)\)?[\s\-.]?)(\d{3})([\s\-.]?)(\d{4}))`	keep · keep · keep · `JM_CM_ALNUM` · keep · `JM_CM_ALNUM`
`(0*?)(?:(\d{3})([\s\-.]?)(\d{4}))`	keep · `JM_CM_ALNUM` · keep · `JM_CM_ALNUM`
otherwise	`JM_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

JM_PLATE REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM`.

Used by: `JM_L1_LICENCE_PLATE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{4})([\s\-]?)([A-Z]{2}))`	keep · `JM_CM_ALNUM` · keep · keep
`([A-Z]{2})([\s\-]?)(\d{4})`	keep · keep · `JM_CM_ALNUM`
`(0*?)(?:(\d{2})([\s\-]?)(\d{4}))`	keep · `JM_CM_ALNUM` · keep · `JM_CM_ALNUM`
otherwise	`JM_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

JM_POLITICAL_OPINION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_POLITICAL_OPINION_LIST`.

Used by: `JM_L3_POLITICAL_OPINION`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_POLITICAL_OPINION_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

JM_POLITICAL_OPINION_LIST SECURE LOOKUP

Replaces the value with one of the 7 values in `jm-political-opinions.txt`, chosen by a keyed hash.

Used by: `JM_POLITICAL_OPINION`

CONFIGURATION

lookupFile	`jm-political-opinions.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_POLITICAL_PARTY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_POLITICAL_PARTY_LIST`.

Used by: `JM_L3_POLITICAL_AFFILIATION`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_POLITICAL_PARTY_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

JM_POLITICAL_PARTY_LIST SECURE LOOKUP

Replaces the value with one of the 4 values in `jm-political-parties.txt`, chosen by a keyed hash.

Used by: `JM_POLITICAL_PARTY`

CONFIGURATION

lookupFile	`jm-political-parties.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_POVERTY REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `JM_POVERTY_STATUS`.

Used by: `JM_FIN_POVERTY`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-5]))`	keep · `JM_QUINTILE`
`(0*?)(?:([6-9]|10))`	keep · `JM_DECILE_HIGH`
`(?i)(decile\s*)(\d{1,2})`	keep · `JM_DECILE`
`(?i)(quintile\s*)([1-5])`	keep · `JM_QUINTILE`
otherwise	`JM_POVERTY_STATUS`

CONFIGURATION

trimInput	yes
requireMask	no

JM_POVERTY_STATUS SECURE LOOKUP

Replaces the value with one of the 4 values in `jm-poverty-statuses.txt`, chosen by a keyed hash.

Used by: `JM_POVERTY`

CONFIGURATION

lookupFile	`jm-poverty-statuses.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_QUINTILE SECURE LOOKUP

Replaces the value with one of the 5 values in `jm-quintile.txt`, chosen by a keyed hash.

Used by: `JM_POVERTY`

CONFIGURATION

lookupFile	`jm-quintile.txt`

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_REDACT REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: JM_L1_CREDENTIAL, JM_L3_GENETIC, JM_L3_BIOMETRIC

PATTERNS, TRIED IN ORDER

(.+)	each character → X
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

JM_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: JM_RELIGION_LIST.

Used by: JM_L3_RELIGION

PATTERNS, TRIED IN ORDER

(?i)(yes|no|true|false|[yn01])	JM_FLAG
(0*?)(?:(\d{1,6}))	keep · JM_CM_ALNUM
otherwise	JM_RELIGION_LIST

CONFIGURATION

trimInput	yes
requireMask	no

JM_RELIGION_LIST SECURE LOOKUP

Replaces the value with one of the 19 values in jm-religions.txt, chosen by a keyed hash.

Used by: JM_RELIGION

CONFIGURATION

lookupFile	jm-religions.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_SCHOOL SECURE LOOKUP

Replaces the value with one of the 15 values in jm-schools.txt, chosen by a keyed hash.

Used by: JM_L2_SCHOOL

CONFIGURATION

lookupFile	jm-schools.txt

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_SEX REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: JM_L2_SEX

PATTERNS, TRIED IN ORDER

(?i)(female|male)	JM_SEX_FEMALE_MALE
(?i)(woman|man)	JM_SEX_WOMAN_MAN
(?i)([fm])	JM_SEX_F_M
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

JM_SEX_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in jm-sex-f-m.txt, chosen by a keyed hash.

Used by: JM_SEX

CONFIGURATION

lookupFile	jm-sex-f-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_SEX_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in jm-sex-female-male.txt, chosen by a keyed hash.

Used by: JM_SEX

CONFIGURATION

lookupFile	jm-sex-female-male.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_SEX_WOMAN_MAN SECURE LOOKUP

Replaces the value with one of the 2 values in jm-sex-woman-man.txt, chosen by a keyed hash.

Used by: JM_SEX

CONFIGURATION

lookupFile	`jm-sex-woman-man.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_SEXUAL_ORIENTATION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_SEXUAL_ORIENTATION_LIST`.

Used by: `JM_L3_SEXUAL_ORIENTATION`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_SEXUAL_ORIENTATION_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

JM_SEXUAL_ORIENTATION_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `jm-sexual-orientations.txt`, chosen by a keyed hash.

Used by: `JM_SEXUAL_ORIENTATION`

CONFIGURATION

lookupFile	`jm-sexual-orientations.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_SOCIAL_PROGRAMME REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_SOCIAL_PROGRAMME_LIST`.

Used by: `JM_FIN_SOCIAL_PROGRAMME`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(\d{1,6}))`	keep · `JM_CM_ALNUM`
otherwise	`JM_SOCIAL_PROGRAMME_LIST`

CONFIGURATION

trimInput	yes
requireMask	no

JM_SOCIAL_PROGRAMME_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `jm-social-programmes.txt`, chosen by a keyed hash.

Used by: `JM_SOCIAL_PROGRAMME`

CONFIGURATION

lookupFile	`jm-social-programmes.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_SUPPRESS SECURE LOOKUP

Replaces the value with one of the 1 values in `jm-not-stated.txt`, chosen by a keyed hash.

Used by: `JM_SUPPRESSED_CATEGORY`

CONFIGURATION

lookupFile	`jm-not-stated.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

JM_SUPPRESSED_CATEGORY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `JM_SUPPRESS`.

Used by: `JM_L3_BELIEF`, `JM_L3_TRADE_UNION`, `JM_L3_SEXUAL_LIFE`, `JM_HEALTH_REPRODUCTIVE`, `JM_HEALTH_MENTAL`

PATTERNS, TRIED IN ORDER

`(?i)(yes|no|true|false|[yn01])`	`JM_FLAG`
`(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(\d{1,6})))))))`	keep · keep · keep · keep · keep · `JM_CM_ALNUM`
otherwise	`JM_SUPPRESS`

CONFIGURATION

trimInput	yes
requireMask	no

JM_SURNAME NAME

Replaces the name with one of the 996 names in `jm-surnames.txt`.

Used by: `JM_SURNAMES`

CONFIGURATION

lookupFile	`jm-surnames.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

JM_SURNAMES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `JM_CM_ALNUM`.

Used by: `JM_L1_SURNAME`, `JM_FULL_NAME`

PATTERNS, TRIED IN ORDER

`([^\s\-]+)(\-)([^\s\-]+)`	`JM_SURNAME` · keep · `JM_SURNAME`
`(\S+)`	`JM_SURNAME`
`(\S+)\s+(\S+)`	`JM_SURNAME` · `JM_SURNAME`
`(\S+)\s+(\S+)\s+(\S+)`	`JM_SURNAME` · `JM_SURNAME` · `JM_SURNAME`
otherwise	`JM_CM_ALNUM`

CONFIGURATION

trimInput	yes
requireMask	no

JM_TOWN DATA CLEANSING

Replaces each value found in `jm-town-generalized.txt` (315 pairs) by its counterpart; values not in the file stay as they are.

Used by: `JM_L2_TOWN`

CONFIGURATION

lookupFile	`jm-town-generalized.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

JM_YEAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `JM_L2_BIRTH_YEAR`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{3})(\d))`	keep · keep · `JM_CM_ALNUM`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
`jm-addresses.txt`	3,000	`JM_ADDRESS`	Gordon Town District, Kingston 6 P.O., St. Andrew · 99 King Street, Kingston · 60 Glenmuir Road, May Pen · 2 Constant Spring Road, Kingston 10
`jm-credit-statuses.txt`	10	`JM_CREDIT_STATUS`	Current · 30 days past due · 60 days past due · 90 days past due
`jm-criminal-record.txt`	8	`JM_CRIMINAL_RECORD_LIST`	No criminal record · Has criminal record · Charged · Case dismissed
`jm-decile-high.txt`	5	`JM_DECILE_HIGH`	6 · 7 · 8 · 9
`jm-decile.txt`	10	`JM_DECILE`	1 · 2 · 3 · 4
`jm-detect-given-names.txt`	1,004	`JM_L1_GIVEN_NAME – List` `JM_L1_FULL_NAME – List`	George · Joseph · David · James
`jm-detect-sex-letter.txt`	2	`JM_L2_SEX – List`	f · m
`jm-detect-sex.txt`	5	`JM_L2_SEX – List`	female · male · woman · man
`jm-detect-surnames.txt`	996	`JM_L1_SURNAME – List` `JM_L1_FULL_NAME – List`	Brown · Williams · Smith · Campbell
`jm-diagnoses.txt`	30	`JM_DIAGNOSIS_TEXT`	Essential hypertension · Type 2 diabetes mellitus · Asthma · Low back pain
`jm-disabilities.txt`	8	`JM_DISABILITY_LIST`	Seeing · Hearing · Walking or climbing steps · Remembering or concentrating
`jm-education.txt`	11	`JM_EDUCATION`	No schooling · Early childhood · Primary · Lower secondary (grade 9)
`jm-employers.txt`	25	`JM_EMPLOYER`	Blue Mountain Trading Company Ltd. · Rio Cobre Services Ltd. · Island Construction Ltd. · Coastal Transport Ltd.
`jm-ethnic-groups.txt`	8	`JM_ETHNICITY_LIST`	Black · East Indian · Chinese · White
`jm-eye-colours.txt`	8	`JM_EYE_COLOUR_LIST`	Brown · Dark brown · Light brown · Black
`jm-filiation.txt`	6	`JM_FILIATION_LIST`	Born in wedlock · Born out of wedlock · Legitimated · Adopted
`jm-flag-0-1.txt`	2	`JM_FLAG_0_1`	0 · 1
`jm-flag-true-false.txt`	2	`JM_FLAG_TRUE_FALSE`	true · false

FILE	LINES	USED BY	FIRST LINES
jm-flag-y-n.txt	2	JM_FLAG_Y_N	Y · N
jm-flag-yes-no.txt	2	JM_FLAG_YES_NO	Yes · No
jm-gender-identities.txt	8	JM_GENDER_IDENTITY_LIST	Woman · Man · Trans woman · Trans man
jm-given-names.txt	1,004	JM_GIVEN_NAME	George · Joseph · David · James
jm-housing-tenure.txt	8	JM_HOUSING_LIST	Owned · Owned with mortgage · Rented · Leased
jm-icd10-decimal.txt	33	JM_ICD10_DECIMAL	E11.9 · E78.5 · J45.9 · J06.9
jm-icd10.txt	37	JM_ICD10	I10 · E11 · E78 · J45
jm-inches.txt	12	JM_INCHES	0 · 1 · 2 · 3
jm-marital-status.txt	7	JM_MARITAL_STATUS	Never married · Married · Common-law union · Visiting union
jm-medications.txt	26	JM_MEDICATION_LIST	Paracetamol · Ibuprofen · Naproxen · Diclofenac
jm-nationalities.txt	16	JM_NATIONALITY	Jamaican · American · British · Canadian
jm-neighbourhoods.txt	77	JM_NEIGHBOURHOOD	Allman Town · Arcadia · Barbican · Beverly Hills
jm-nis-benefits.txt	11	JM_NIS_BENEFIT_LIST	Old age pension · Invalidity benefit · Widow's or widower's benefit · Orphan's benefit
jm-not-stated.txt	1	JM_SUPPRESS	Not stated
jm-occupations.txt	41	JM_OCCUPATION	Clerk · Sales clerk · Shop assistant · Construction worker
jm-political-opinions.txt	7	JM_POLITICAL_OPINION_LIST	Left · Centre-left · Centre · Centre-right
jm-political-parties.txt	4	JM_POLITICAL_PARTY_LIST	Jamaica Labour Party · People's National Party · Independent · No party
jm-poverty-statuses.txt	4	JM_POVERTY_STATUS	Food poor · Poor · Vulnerable · Not poor
jm-quintile.txt	5	JM_QUINTILE	1 · 2 · 3 · 4
jm-religions.txt	19	JM_RELIGION_LIST	Church of God · Seventh-day Adventist · Pentecostal · Baptist
jm-schools.txt	15	JM_SCHOOL	Mount Olive Primary School · St. Mark's Anglican Primary School · Sacred Heart Preparatory School · Holy Family Primary School

FILE	LINES	USED BY	FIRST LINES
jm-sex-f-m.txt	2	JM_SEX_F_M	F · M
jm-sex-female-male.txt	2	JM_SEX_FEMALE_MALE	Female · Male
jm-sex-woman-man.txt	2	JM_SEX_WOMAN_MAN	Woman · Man
jm-sexual-orientations.txt	8	JM_SEXUAL_ORIENTATION_LIST	Heterosexual · Gay · Lesbian · Bisexual
jm-social-programmes.txt	8	JM_SOCIAL_PROGRAMME_LIST	PATH · Social Pension · Rehabilitation Programme · Poor Relief
jm-surnames.txt	996	JM_SURNAME	Brown · Williams · Smith · Campbell
jm-text-names.txt	3,790	JM_FREE_TEXT	George · GEORGE · Joseph · JOSEPH
jm-town-generalized.txt	315	JM_TOWN	Kingston|Kingston · KINGSTON|KINGSTON · Portmore|Portmore · PORTMORE|PORTMORE

APPENDIX C

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 `plate` `vehicle` `business` `trade` `liquor` `professional` `firearm`

E2 `product` `prod` `item` `article` `company` `business` `trade` `brand` `file` `street` `road` `avenue` `village` `town` `city` `district` `parish` `country` `bank` `branch` `plan` `campaign` `project` `service` `table` `column` `field` `user` `host` `server` `domain` `model` `category` `type` `school` `college` `institution` `course` `programme` `program` `subject` `document` `doc` `centre` `center` `unit` `clinic` `hospital` `area` `department` `dept` `position` `system` `app` `application` `group` `list` `report` `process` `event` `task` `profile` `role` `class` `object` `account` `drug` `medication` `diagnosis` `study` `benefit` `party` `union` `religion` `ethnicity` `language` `place` `store` `shop` `warehouse` `supplier` `vendor` `contract` `policy` `insurance` `org` `organi[sz]ation` `entity` `parameter` `variable` `method` `function` `index` `job` `script` `queue` `resource` `network` `device` `template` `image` `photo` `page` `site` `module` `menu` `option` `action` `permission` `tax` `currency` `issuer` `invoice` `payment` `form` `zone` `route` `line` `sector` `building` `display` `key` `tag` `label` `title` `code` `config` `setting` `firm` `employer` `estate` `parcel` `scheme` `community` `customer` `cust` `client` `patient` `employee` `emp` `staff` `worker` `member` `student` `pupil` `insured` `beneficiary` `holder` `account_?holder` `policy_?holder` `mother` `father` `parent` `guardian` `spouse` `partner` `next_?of_?kin` `doctor` `physician` `nurse` `contact` `emergency_?contact` `guarantor` `debtor` `borrower` `applicant` `signatory` `witness` `representative` `owner` `tenant` `landlord` `victim` `complainant` `accused` `defendant` `donor` `heir` `person` `driver` `agent` `citizen` `elector` `voter` `taxpayer` `child` `dependant` `dependent` `relative` `officer` `teacher` `contributor` `pensioner` `claimant` `full` `complete` `last` `first`

E3 `ip` `mac` `email` `e_?mail` `web` `url` `book` `type` `id`

E4 `id` `type` `code` `key` `no` `num` `number` `date` `status` `queue` `count` `log`

E5 `id` `key` `type` `role` `site` `ref` `code` `number` `no` `size`

APPENDIX D

Profile set and classifiers

The profile set `JM – Data Protection Act 2020 – v1` runs these 129 classifiers, with an assignment threshold of 60%.

Data Protection Act 2020 - personal data

CLASSIFIER	KIND	DOMAIN
JM_L1_TRN – Path	COLUMN NAME	JM_L1_TRN
JM_L1_TRN – Regex	VALUE FORMAT	JM_L1_TRN
JM_L1_NIS_NUMBER – Path	COLUMN NAME	JM_L1_NIS_NUMBER
JM_L1_PASSPORT – Path	COLUMN NAME	JM_L1_PASSPORT
JM_L1_PASSPORT – Regex	VALUE FORMAT	JM_L1_PASSPORT
JM_L1_VOTER_ID – Path	COLUMN NAME	JM_L1_VOTER_ID
JM_L1_DRIVERS_LICENCE – Path	COLUMN NAME	JM_L1_DRIVERS_LICENCE
JM_L1_IMMIGRATION_DOCUMENT – Path	COLUMN NAME	JM_L1_IMMIGRATION_DOCUMENT
JM_L1_VITAL_RECORD – Path	COLUMN NAME	JM_L1_VITAL_RECORD
JM_L1_GIVEN_NAME – Path	COLUMN NAME	JM_L1_GIVEN_NAME
JM_L1_GIVEN_NAME – List	KNOWN VALUES	JM_L1_GIVEN_NAME
JM_L1_SURNAME – Path	COLUMN NAME	JM_L1_SURNAME
JM_L1_SURNAME – List	KNOWN VALUES	JM_L1_SURNAME
JM_L1_FULL_NAME – Path	COLUMN NAME	JM_L1_FULL_NAME
JM_L1_FULL_NAME – List	KNOWN VALUES	JM_L1_FULL_NAME
JM_L1_EMAIL – Path	COLUMN NAME	JM_L1_EMAIL
JM_L1_EMAIL – Type	DATA TYPE	JM_L1_EMAIL
JM_L1_EMAIL – Regex	VALUE FORMAT	JM_L1_EMAIL
JM_L1_PHONE – Path	COLUMN NAME	JM_L1_PHONE
JM_L1_PHONE – Regex	VALUE FORMAT	JM_L1_PHONE
JM_L1_ADDRESS – Path	COLUMN NAME	JM_L1_ADDRESS
JM_L1_ADDRESS – Type	DATA TYPE	JM_L1_ADDRESS
JM_L1_ADDRESS – Regex	VALUE FORMAT	JM_L1_ADDRESS
JM_L1_ADDRESS_DETAIL – Path	COLUMN NAME	JM_L1_ADDRESS_DETAIL
JM_L1_BANK_ACCOUNT – Path	COLUMN NAME	JM_L1_BANK_ACCOUNT
JM_L1_PAYMENT_CARD – Path	COLUMN NAME	JM_L1_PAYMENT_CARD
JM_L1_PAYMENT_CARD – Regex	VALUE FORMAT	JM_L1_PAYMENT_CARD
JM_L1_IP_ADDRESS – Path	COLUMN NAME	JM_L1_IP_ADDRESS
JM_L1_IP_ADDRESS – Regex	VALUE FORMAT	JM_L1_IP_ADDRESS
JM_L1_DEVICE_ID – Path	COLUMN NAME	JM_L1_DEVICE_ID
JM_L1_DEVICE_ID – Regex	VALUE FORMAT	JM_L1_DEVICE_ID

CLASSIFIER	KIND	DOMAIN
JM_L1_LICENCE_PLATE – Path	COLUMN NAME	JM_L1_LICENCE_PLATE
JM_L1_LICENCE_PLATE – Regex	VALUE FORMAT	JM_L1_LICENCE_PLATE
JM_L1_VIN – Path	COLUMN NAME	JM_L1_VIN
JM_L1_VIN – Regex	VALUE FORMAT	JM_L1_VIN
JM_L1_LAND_TITLE – Path	COLUMN NAME	JM_L1_LAND_TITLE
JM_L1_LAND_TITLE – Regex	VALUE FORMAT	JM_L1_LAND_TITLE
JM_L1_CONTRACT_NUMBER – Path	COLUMN NAME	JM_L1_CONTRACT_NUMBER
JM_L1_USERNAME – Path	COLUMN NAME	JM_L1_USERNAME
JM_L1_CREDENTIAL – Path	COLUMN NAME	JM_L1_CREDENTIAL
JM_L1_CREDENTIAL – Regex	VALUE FORMAT	JM_L1_CREDENTIAL
JM_L1_GEOLOCATION – Path	COLUMN NAME	JM_L1_GEOLOCATION
JM_L1_GEOLOCATION – Regex	VALUE FORMAT	JM_L1_GEOLOCATION
JM_L1_FREE_TEXT – Path	COLUMN NAME	JM_L1_FREE_TEXT
JM_L1_FREE_TEXT – Type	DATA TYPE	JM_L1_FREE_TEXT
JM_L1_FREE_TEXT – Regex	VALUE FORMAT	JM_L1_FREE_TEXT
JM_L2_BIRTH_DATE – Path	COLUMN NAME	JM_L2_BIRTH_DATE
JM_L2_BIRTH_DATE – Type	DATA TYPE	JM_L2_BIRTH_DATE
JM_L2_BIRTH_YEAR – Path	COLUMN NAME	JM_L2_BIRTH_YEAR
JM_L2_BIRTH_YEAR – Type	DATA TYPE	JM_L2_BIRTH_YEAR
JM_L2_AGE – Path	COLUMN NAME	JM_L2_AGE
JM_L2_AGE – Type	DATA TYPE	JM_L2_AGE
JM_L2_EVENT_DATE – Path	COLUMN NAME	JM_L2_EVENT_DATE
JM_L2_EVENT_DATE – Type	DATA TYPE	JM_L2_EVENT_DATE
JM_L2_SEX – Path	COLUMN NAME	JM_L2_SEX
JM_L2_SEX – List	KNOWN VALUES	JM_L2_SEX
JM_L2_TOWN – Path	COLUMN NAME	JM_L2_TOWN
JM_L2_TOWN – Values	VALUE FORMAT	JM_L2_TOWN
JM_L2_NEIGHBOURHOOD – Path	COLUMN NAME	JM_L2_NEIGHBOURHOOD
JM_L2_NATIONALITY – Path	COLUMN NAME	JM_L2_NATIONALITY
JM_L2_NATIONALITY – Values	VALUE FORMAT	JM_L2_NATIONALITY
JM_L2_MARITAL_STATUS – Path	COLUMN NAME	JM_L2_MARITAL_STATUS
JM_L2_MARITAL_STATUS – Values	VALUE FORMAT	JM_L2_MARITAL_STATUS
JM_L2_OCCUPATION – Path	COLUMN NAME	JM_L2_OCCUPATION
JM_L2_EMPLOYER – Path	COLUMN NAME	JM_L2_EMPLOYER
JM_L2_EDUCATION – Path	COLUMN NAME	JM_L2_EDUCATION
JM_L2_EDUCATION – Values	VALUE FORMAT	JM_L2_EDUCATION
JM_L2_SCHOOL – Path	COLUMN NAME	JM_L2_SCHOOL

CLASSIFIER	KIND	DOMAIN
JM_L2_DEPENDANTS – Path	COLUMN NAME	JM_L2_DEPENDANTS
JM_L2_DEPENDANTS – Type	DATA TYPE	JM_L2_DEPENDANTS
JM_L3_GENETIC – Path	COLUMN NAME	JM_L3_GENETIC
JM_L3_GENETIC – Regex	VALUE FORMAT	JM_L3_GENETIC
JM_L3_BIOMETRIC – Path	COLUMN NAME	JM_L3_BIOMETRIC
JM_L3_BIOMETRIC – Type	DATA TYPE	JM_L3_BIOMETRIC
JM_L3_HEIGHT – Path	COLUMN NAME	JM_L3_HEIGHT
JM_L3_EYE_COLOUR – Path	COLUMN NAME	JM_L3_EYE_COLOUR
JM_L3_EYE_COLOUR – Values	VALUE FORMAT	JM_L3_EYE_COLOUR
JM_L3_FILIATION – Path	COLUMN NAME	JM_L3_FILIATION
JM_L3_FILIATION – Values	VALUE FORMAT	JM_L3_FILIATION
JM_L3_ETHNICITY – Path	COLUMN NAME	JM_L3_ETHNICITY
JM_L3_ETHNICITY – Values	VALUE FORMAT	JM_L3_ETHNICITY
JM_L3_RELIGION – Path	COLUMN NAME	JM_L3_RELIGION
JM_L3_RELIGION – Values	VALUE FORMAT	JM_L3_RELIGION
JM_L3_BELIEF – Path	COLUMN NAME	JM_L3_BELIEF
JM_L3_POLITICAL_OPINION – Path	COLUMN NAME	JM_L3_POLITICAL_OPINION
JM_L3_POLITICAL_OPINION – Values	VALUE FORMAT	JM_L3_POLITICAL_OPINION
JM_L3_POLITICAL_AFFILIATION – Path	COLUMN NAME	JM_L3_POLITICAL_AFFILIATION
JM_L3_POLITICAL_AFFILIATION – Values	VALUE FORMAT	JM_L3_POLITICAL_AFFILIATION
JM_L3_TRADE_UNION – Path	COLUMN NAME	JM_L3_TRADE_UNION
JM_L3_TRADE_UNION – Values	VALUE FORMAT	JM_L3_TRADE_UNION
JM_L3_SEXUAL_ORIENTATION – Path	COLUMN NAME	JM_L3_SEXUAL_ORIENTATION
JM_L3_SEXUAL_ORIENTATION – Values	VALUE FORMAT	JM_L3_SEXUAL_ORIENTATION
JM_L3_SEXUAL_LIFE – Path	COLUMN NAME	JM_L3_SEXUAL_LIFE
JM_L3_GENDER_IDENTITY – Path	COLUMN NAME	JM_L3_GENDER_IDENTITY
JM_L3_GENDER_IDENTITY – Values	VALUE FORMAT	JM_L3_GENDER_IDENTITY
JM_HEALTH_ID – Path	COLUMN NAME	JM_HEALTH_ID
JM_HEALTH_DIAGNOSIS – Path	COLUMN NAME	JM_HEALTH_DIAGNOSIS
JM_HEALTH_DIAGNOSIS – Regex	VALUE FORMAT	JM_HEALTH_DIAGNOSIS
JM_HEALTH_MEDICATION – Path	COLUMN NAME	JM_HEALTH_MEDICATION
JM_HEALTH_MEDICATION – Values	VALUE FORMAT	JM_HEALTH_MEDICATION
JM_HEALTH_CLINICAL_TEXT – Path	COLUMN NAME	JM_HEALTH_CLINICAL_TEXT
JM_HEALTH_CLINICAL_TEXT – Type	DATA TYPE	JM_HEALTH_CLINICAL_TEXT
JM_HEALTH_TEST_RESULT – Path	COLUMN NAME	JM_HEALTH_TEST_RESULT
JM_HEALTH_BLOOD_GROUP – Path	COLUMN NAME	JM_HEALTH_BLOOD_GROUP
JM_HEALTH_BLOOD_GROUP – Values	VALUE FORMAT	JM_HEALTH_BLOOD_GROUP

CLASSIFIER	KIND	DOMAIN
JM_HEALTH_DISABILITY – Path	COLUMN NAME	JM_HEALTH_DISABILITY
JM_HEALTH_DISABILITY – Values	VALUE FORMAT	JM_HEALTH_DISABILITY
JM_HEALTH_REPRODUCTIVE – Path	COLUMN NAME	JM_HEALTH_REPRODUCTIVE
JM_HEALTH_MENTAL – Path	COLUMN NAME	JM_HEALTH_MENTAL
JM_FIN_CREDIT_REFERENCE – Path	COLUMN NAME	JM_FIN_CREDIT_REFERENCE
JM_FIN_DEBT – Path	COLUMN NAME	JM_FIN_DEBT
JM_FIN_DEBT – Type	DATA TYPE	JM_FIN_DEBT
JM_FIN_INCOME – Path	COLUMN NAME	JM_FIN_INCOME
JM_FIN_INCOME – Type	DATA TYPE	JM_FIN_INCOME
JM_FIN_ASSETS – Path	COLUMN NAME	JM_FIN_ASSETS
JM_FIN_ASSETS – Type	DATA TYPE	JM_FIN_ASSETS
JM_FIN_PENSION – Path	COLUMN NAME	JM_FIN_PENSION
JM_FIN_PENSION – Type	DATA TYPE	JM_FIN_PENSION
JM_FIN_NIS_BENEFIT – Path	COLUMN NAME	JM_FIN_NIS_BENEFIT
JM_FIN_NIS_BENEFIT – Values	VALUE FORMAT	JM_FIN_NIS_BENEFIT
JM_FIN_SOCIAL_PROGRAMME – Path	COLUMN NAME	JM_FIN_SOCIAL_PROGRAMME
JM_FIN_SOCIAL_PROGRAMME – Values	VALUE FORMAT	JM_FIN_SOCIAL_PROGRAMME
JM_FIN_POVERTY – Path	COLUMN NAME	JM_FIN_POVERTY
JM_FIN_POVERTY – Values	VALUE FORMAT	JM_FIN_POVERTY
JM_FIN_HOUSING – Path	COLUMN NAME	JM_FIN_HOUSING
JM_FIN_HOUSING – Values	VALUE FORMAT	JM_FIN_HOUSING
JM_PENAL_CRIMINAL_RECORD – Path	COLUMN NAME	JM_PENAL_CRIMINAL_RECORD
JM_PENAL_CASE_NUMBER – Path	COLUMN NAME	JM_PENAL_CASE_NUMBER
JM_PENAL_CASE_NUMBER – Regex	VALUE FORMAT	JM_PENAL_CASE_NUMBER