DELPHIX MASKING · PROFILE SET

Uruguay — Ley 18.331 de Protección de Datos Personales

Discovery and masking of Uruguayan personal data: cédula de identidad and RUT with a valid check digit, the razón social of a legal person — a data subject in Uruguay —, quasi-identifiers, the sensitive data of article 4 E), health data, the commercial and credit data of article 22 and the offence data of article 18.

83	143	111
DOMAINS	CLASSIFIERS	ALGORITHMS

Profile set `UY – Ley 18.331 – v2`

Version 2 of October 11, 2026 · Assignment threshold 60%

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	**About this profile set**	
2	**Ley 18.331 in brief**	
3	**Dissociation, pseudonymization and non-production copies**	
4	**How sensitive data is discovered**	
5	**How data is masked**	
6	**Essential and extended packs**	
7	**Domains at a glance**	

PART 8 · DIRECT IDENTIFIERS

8.1	**Cédula de identidad**	UY_L1_CEDULA
8.2	**RUT**	UY_L1_RUT
8.3	**Foreigner documents**	UY_L1_DOCUMENTO_EXTRANJERO
8.4	**Passport**	UY_L1_PASAPORTE
8.5	**Credencial cívica**	UY_L1_CREDENCIAL_CIVICA
8.6	**Civil registry records**	UY_L1_PARTIDA
8.7	**BPS and the professional funds**	UY_L1_SEGURO_SOCIAL
8.8	**Student code**	UY_L1_CODIGO_ESTUDIANTE
8.9	**Professional registration**	UY_L1_MATRICULA_PROFESIONAL
8.10	**Given name**	UY_L1_NOMBRE
8.11	**Surname**	UY_L1_APELLIDO
8.12	**Full name**	UY_L1_NOMBRE_COMPLETO
8.13	**Razón social and nombre de fantasía**	UY_L1_RAZON_SOCIAL
8.14	**E-mail**	UY_L1_EMAIL
8.15	**Phone**	UY_L1_TELEFONO
8.16	**Address**	UY_L1_DIRECCION
8.17	**Address complement**	UY_L1_DIRECCION_COMPLEMENTO
8.18	**Bank account**	UY_L1_CUENTA_BANCARIA
8.19	**Payment card**	UY_L1_TARJETA
8.20	**Digital wallet**	UY_L1_BILLETERA
8.21	**IP address**	UY_L1_IP
8.22	**Device identifier**	UY_L1_DISPOSITIVO
8.23	**Cookies and tracking identifiers**	UY_L1_COOKIE
8.24	**Vehicle plate**	UY_L1_PLACA

8.25	Vehicle and licence	UY_L1_VEHICULO
8.26	Property	UY_L1_INMUEBLE
8.27	Customer and contract numbers	UY_L1_CONTRATO
8.28	User and social media	UY_L1_USUARIO
8.29	Credentials	UY_L1_CREDENCIAL
8.30	Geolocation	UY_L1_GEOLOCALIZACION
8.31	Free text	UY_L1_TEXTO_LIBRE

PART 9 · QUASI-IDENTIFIERS

9.1	Birth date	UY_L2_FECHA_NACIMIENTO
9.2	Birth year	UY_L2_ANIO_NACIMIENTO
9.3	Age	UY_L2_EDAD
9.4	Personal event dates	UY_L2_FECHA_EVENTO
9.5	Sex	UY_L2_SEXO
9.6	Localidad	UY_L2_LOCALIDAD
9.7	INE code	UY_L2_CODIGO_INE
9.8	Barrio and balneario	UY_L2_BARRIO
9.9	Postal code	UY_L2_CODIGO_POSTAL
9.10	Marital status	UY_L2_ESTADO_CIVIL
9.11	Occupation	UY_L2_OCUPACION
9.12	Employer	UY_L2_EMPLEADOR
9.13	Education	UY_L2_NIVEL_EDUCATIVO
9.14	School	UY_L2_INSTITUCION_EDUCATIVA
9.15	Dependants and children	UY_L2_PERSONAS_A_CARGO

PART 10 · SENSITIVE DATA (ART. 4 E AND ART. 4 Ñ)

10.1	Racial and ethnic origin	UY_L3_ASCENDENCIA
10.2	Indigenous people	UY_L3_PUEBLO_ORIGINARIO
10.3	Nationality	UY_L3_NACIONALIDAD
10.4	Religion	UY_L3_RELIGION
10.5	Moral and philosophical convictions	UY_L3_CONVICCION_MORAL
10.6	Political preferences	UY_L3_PREFERENCIA_POLITICA
10.7	Party membership	UY_L3_AFILIACION_PARTIDARIA
10.8	Trade union membership	UY_L3_AFILIACION_SINDICAL
10.9	Biometric data	UY_L3_BIOMETRICO
10.10	Genetic data	UY_L3_GENETICO
10.11	Sexual orientation	UY_L3_ORIENTACION_SEXUAL
10.12	Sexual life	UY_L3_VIDA_SEXUAL

10.13	Gender identity	UY_L3_IDENTIDAD_GENERO
10.14	Victims of violence	UY_L3_VICTIMA

PART 11 · HEALTH DATA

11.1	Health identifiers	UY_SALUD_IDENTIFICADOR
11.2	Health coverage	UY_SALUD_COBERTURA
11.3	Diagnosis and ICD-10	UY_SALUD_DIAGNOSTICO
11.4	Procedures	UY_SALUD_PROCEDIMIENTO
11.5	Medicines	UY_SALUD_MEDICAMENTO
11.6	Clinical text	UY_SALUD_TEXTO_CLINICO
11.7	Test results	UY_SALUD_RESULTADO_EXAMEN
11.8	HIV and sexually transmitted infections	UY_SALUD_VIH
11.9	Blood group and Rh	UY_SALUD_GRUPO_SANGUINEO
11.10	Disability	UY_SALUD_DISCAPACIDAD
11.11	Carné de salud and occupational health	UY_SALUD_OCUPACIONAL
11.12	Sexual and reproductive health	UY_SALUD_REPRODUCTIVA
11.13	Mental health	UY_SALUD_MENTAL

PART 12 · COMMERCIAL AND CREDIT DATA (ART. 22)

12.1	Credit history	UY_FIN_HISTORIAL_CREDITICIO
12.2	Debt	UY_FIN_DEUDA
12.3	Income and pay	UY_FIN_INGRESOS
12.4	Assets	UY_FIN_PATRIMONIO
12.5	Pasividad and benefits	UY_FIN_PENSION
12.6	Social programmes	UY_FIN_PROGRAMA_SOCIAL
12.7	Índice de Carencias Críticas	UY_FIN_NIVEL_SOCIOECONOMICO
12.8	Housing tenure	UY_FIN_VIVIENDA

PART 13 · OFFENCES (ART. 18)

13.1	Offences and records	UY_PENAL_ANTECEDENTES
13.2	Court file	UY_PENAL_EXPEDIENTE
14	The cédula and RUT check digits	
15	Where people live: localidades, INE code and postal code	
16	Limits	
17	Verification	
18	Sources	
A	Algorithms	
B	Files	

C	**Exclusion lists**
D	**Profile set and classifiers**

1

About this profile set

This profile set finds the personal data in a Uruguayan database and masks it, so that a non-production copy — for testing, development, training or analysis — no longer identifies anyone.

Masking names and cédulas alone is not enough: a birth date, a sex and a small localidad already point at one person. The set works in the layers where the risk is:

- **Direct identifiers** — cédula de identidad and RUT, foreigner documents, passport, credencial cívica, civil registry, BPS numbers, student code, professional registration, names, **razón social and nombre de fantasía**, contact, address, accounts, cards, devices, cookies, plates, property, free text.
- **Quasi-identifiers** — birth date, age, sex, localidad with its INE code, barrio, postal code, marital status, occupation, employer, education.
- **Sensitive data** — those of article 4 E): racial and ethnic origin, political preferences, religious **or moral** convictions, trade union membership and sexual life; plus the biometric data article 4 Ñ) added in 2020, genetic data, gender identity, the indigenous people and the victim status other Uruguayan statutes protect.
- **Health data** — sensitive by article 4 E), with a regime of its own in article 19 and a dissociation clause in article 17 C): clinical record, coverage, ICD-10, procedures, medicines, HIV, blood group, disability, the compulsory carné de salud, reproductive and mental health.
- **Commercial and credit data** — the *actividad comercial o crediticia* of article 22, with its five-year limit, plus debt, income, assets, pensions, social programmes and housing tenure.
- **Offences** — the data on criminal, civil or administrative offences that the final paragraph of article 18 reserves to the competent public authorities.

In a Masking Engine, the set is a profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those rely on — and the lookup files they read. The appendices list each of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it on its own; an ambiguous one — `NOMBRE`, `DOCUMENTO`, `EXPEDIENTE`, `CARGO` — needs the values to agree. A column with a meaningless name (`CAMPO1`, `OBS`) is still found when its values have a recognizable shape or vocabulary: a cédula written `1.234.567-2`, a twelve-digit RUT, a mobile starting 09, an address with a door number and an apartamento, a plate, a localidad.

Column names are recognized in Spanish, in the abbreviations of Uruguayan systems (`CI`, `FEC_NAC`, `RUT`, `BPS`, `IUE`, `PADRON`) and in English.

> Before masking, inventory the binary columns (BLOB, images, PDF). Onboarding processes often keep a photo of the cédula — with the fingerprint and the signature — and a validation selfie. Report those columns as residual risk.

2

Ley 18.331 in brief

The **Ley 18.331 de Protección de Datos Personales y Acción de Habeas Data** was passed on 11 August 2008 and regulated by Decree 414/009. It has been amended several times — Ley 18.719 (2010), Ley 18.996 (2012), Ley 19.355 (2015), **Ley 19.670 (2018)**, which added extraterritorial reach, breach notification and the data protection officer, and **Ley 19.924 (2020)**, which defined the biometric datum — and those additions were

regulated by **Decree 64/020**. The authority is the **Unidad Reguladora y de Control de Datos Personales (URCDP)**, inside AGESIC. Uruguay is one of only two Latin American countries the European Union has recognized as providing an adequate level of protection, and a party to Convention 108.

What matters for a copy of production data:

- **Personal data** is information of any kind about determinate or determinable **natural or legal** persons (art. 4 D). Uruguay is one of the few countries whose law makes a **company** a data subject: the razón social, the nombre de fantasía and the RUT of a legal person are personal data, and article 9 C) names them.
- **Sensitive data** (art. 4 E) is data that reveals racial and ethnic origin, political preferences, religious **or moral** convictions, trade union membership, and information on health or sexual life. Article 18 forbids building databases that store information which **directly or indirectly** reveals it, and allows treatment for statistical or scientific purposes only "cuando se disocien de sus titulares".
- **Dissociation** is any processing of personal data such that the information obtained **cannot be linked to a determinate or determinable person** (art. 4 G). Article 17 D) is the clause this set is written for: the prior consent of the data subject is not needed to communicate data when "se hubiera aplicado un procedimiento de disociación de la información, de modo que los titulares de los datos no sean identificables".
- **Where dissociation appears.** Article 9-BIS D) allows a register whose publication is not of general interest to be used "mediante técnicas de disociación u ocultamiento de los datos personales"; article 17 C) requires "mecanismos de disociación adecuados" when health data travels for sanitary or epidemiological reasons; article 18 requires dissociation for statistics and science. And **article 8 a) of Decree 64/020** lists, first among the privacy-by-design measures, the "**técnicas de disociación, seudonimización y minimización de datos**".
- **Security.** Article 10 makes the controller adopt the measures needed to guarantee the security and confidentiality of the data, and forbids registering personal data in databases that do not meet technical conditions of integrity and security. Article 38 of Ley 19.670 has a breach notified to the subjects and to the URCDP **immediately**, and the URCDP coordinates with CERTuy. Articles 6 and 7 of Decree 64/020 require an impact assessment where the risk is high — among the triggers, a permanent treatment of the data of Chapter IV or of data on offences.
- **Biometric data.** Article 4 Ñ), added by Ley 19.924 in 2020, defines it as the datum obtained from a specific technical processing that permits or confirms the unique identification of a person; article 18-BIS allows processing it only after a **data protection impact assessment**.
- **Sanctions.** Article 35 lets the URCDP observe, warn, fine up to **500,000 unidades indexadas**, suspend the database for five days or close it down through the courts.

Credit data have a clock. Article 22 authorizes the processing of data on patrimonial or credit solvency obtained from public sources or from the creditor, but the data on a natural person's commercial obligations may be registered for **five years**, renewable once for five more; a settled obligation stays for five years, not renewable. A copy of such a database carries the clock with it.

3

Dissociation, pseudonymization and non-production copies

Ley 18.331 is from 2008 and uses one word, **disociación**: processing such that the information obtained cannot be linked to a determinate or determinable person (art. 4 G). It does not define pseudonymization — but **article 8 a) of Decree 64/020**, from 2020, names the two side by side as privacy-by-design measures: "técnicas de disociación, seudonimización y minimización de datos".

The algorithms of this set are deterministic for the Masking Engine's key: the same cédula masks the same way in every table, which keeps joins working. Whoever holds that key and production can link the two back,

so the masked copy is **pseudonymized** in the sense of the decree, not dissociated in the sense of article 4 G), and it remains personal data for them.

- Keep the engine key apart from the copy, and treat whoever holds both as processing personal data subject to the whole law.
- Article 17 D) excuses the consent for a communication only when a dissociation procedure leaves the subjects **not identifiable**. If you rely on it, the key must not travel with the copy, and the quasi-identifiers that remain have to be measured.
- Article 18 lets sensitive data be processed for statistics or science when it is dissociated from its subjects — the same standard, and a higher one than a masked copy with its key meets.

4

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Databases pad values: a CHAR column fills them with spaces up to its length, and a numeric code kept as text often comes with zeros on the left. The profiler tests values as they come, so every format pattern first removes the spaces around the value, patterns of digits also accept zeros on the left, lists of single words are looked up word by word, and lists of names made of several words (places, categories) are held as a single value-format pattern. A column whose name says nothing — `CAMPO1`, `FLD_07`, the short names of packaged systems — is found by its values alone wherever their format is distinctive: documents with a check digit, e-mail addresses, telephone numbers, cards, places, names.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

> Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

5

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its

own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

Where an algorithm that comes with the Masking Engine already does the job — CM Numeric for amounts, Credit Card, the blood group lookup — the set names it instead of creating one of its own. Those algorithms appear in the trees by their `dlpx-core:` name; they are on every engine and are not listed in Appendix A.

Padding stays where it is: the spaces around a value are kept, and zeros on the left of a number are not masked — `0012345678` becomes `00` followed by what `12345678` becomes. A value kept in a zero-filled CHAR column still joins the same value kept as a number.

> The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

6

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	13	26	26	6
Extended	83	143	111	56

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- Cédula de identidad — `UY_L1_CEDULA`
- RUT — `UY_L1_RUT`
- Foreigner documents — `UY_L1_DOCUMENTO_EXTRANJERO`
- Passport — `UY_L1_PASAPORTE`
- Given name — `UY_L1_NOMBRE`
- Surname — `UY_L1_APELLIDO`
- Full name — `UY_L1_NOMBRE_COMPLETO`
- Razón social and nombre de fantasía — `UY_L1_RAZON_SOCIAL`
- E-mail — `UY_L1_EMAIL`
- Phone — `UY_L1_TELEFONO`
- Address — `UY_L1_DIRECCION`
- Address complement — `UY_L1_DIRECCION_COMPLEMENTO`
- Birth date — `UY_L2_FECHA_NACIMIENTO`

> With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

7

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY	ALGORITHM
DIRECT IDENTIFIERS		
Cédula de identidad ESSENTIAL `UY_L1_CEDULA`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`UY_DOCUMENTO`
RUT ESSENTIAL `UY_L1_RUT`	COLUMN NAME · VALUE FORMAT	`UY_RUT_COLUMNA`
Foreigner documents ESSENTIAL `UY_L1_DOCUMENTO_EXTRANJERO`	COLUMN NAME	`UY_CM_ALFANUM`
Passport ESSENTIAL `UY_L1_PASAPORTE`	COLUMN NAME · VALUE FORMAT	`UY_CM_ALFANUM`
Credencial cívica `UY_L1_CREDENCIAL_CIVICA`	COLUMN NAME · VALUE FORMAT	`UY_CM_DIGITOS_LETRAS`
Civil registry records `UY_L1_PARTIDA`	COLUMN NAME	`UY_CM_ALFANUM`
BPS and the professional funds `UY_L1_SEGURO_SOCIAL`	COLUMN NAME	`UY_CM_ALFANUM`
Student code `UY_L1_CODIGO_ESTUDIANTE`	COLUMN NAME	`UY_CM_ALFANUM`
Professional registration `UY_L1_MATRICULA_PROFESIONAL`	COLUMN NAME	`UY_CM_ALFANUM`
Given name ESSENTIAL `UY_L1_NOMBRE`	COLUMN NAME · KNOWN VALUES	`UY_NOMBRES`
Surname ESSENTIAL `UY_L1_APELLIDO`	COLUMN NAME · KNOWN VALUES	`UY_APELLIDOS`
Full name ESSENTIAL `UY_L1_NOMBRE_COMPLETO`	COLUMN NAME · KNOWN VALUES	`UY_NOMBRE_COMPLETO`
Razón social and nombre de fantasía ESSENTIAL `UY_L1_RAZON_SOCIAL`	COLUMN NAME	`UY_RAZON_SOCIAL`
E-mail ESSENTIAL `UY_L1_EMAIL`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`UY_EMAIL`
Phone ESSENTIAL `UY_L1_TELEFONO`	COLUMN NAME · VALUE FORMAT	`UY_TELEFONO`
Address ESSENTIAL `UY_L1_DIRECCION`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`UY_DIRECCION`
Address complement ESSENTIAL `UY_L1_DIRECCION_COMPLEMENTO`	COLUMN NAME	`UY_CM_ALFANUM`
Bank account `UY_L1_CUENTA_BANCARIA`	COLUMN NAME	`UY_CM_DIGITOS`
Payment card `UY_L1_TARJETA`	COLUMN NAME · VALUE FORMAT	`UY_TARJETA`

DOMAIN	FOUND BY	ALGORITHM
Digital wallet `UY_L1_BILLETERA`	COLUMN NAME · VALUE FORMAT	`UY_CM_ALFANUM`
IP address `UY_L1_IP`	COLUMN NAME · VALUE FORMAT	`UY_IP`
Device identifier `UY_L1_DISPOSITIVO`	COLUMN NAME · VALUE FORMAT	`UY_CM_HEX`
Cookies and tracking identifiers `UY_L1_COOKIE`	COLUMN NAME	`UY_CM_ALFANUM`
Vehicle plate `UY_L1_PLACA`	COLUMN NAME · VALUE FORMAT	`UY_CM_DIGITOS_LETRAS`
Vehicle and licence `UY_L1_VEHICULO`	COLUMN NAME · VALUE FORMAT	`UY_CM_ALFANUM`
Property `UY_L1_INMUEBLE`	COLUMN NAME	`UY_CM_ALFANUM`
Customer and contract numbers `UY_L1_CONTRATO`	COLUMN NAME	`UY_CM_ALFANUM`
User and social media `UY_L1_USUARIO`	COLUMN NAME	`UY_CM_ALFANUM`
Credentials `UY_L1_CREDENCIAL`	COLUMN NAME · VALUE FORMAT	`UY_REDACTAR`
Geolocation `UY_L1_GEOLOCALIZACION`	COLUMN NAME · VALUE FORMAT	`UY_COORDENADA`
Free text `UY_L1_TEXTO_LIBRE`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`UY_TEXTO_LIBRE`
QUASI-IDENTIFIERS		
Birth date ESSENTIAL `UY_L2_FECHA_NACIMIENTO`	COLUMN NAME · DATA TYPE	`UY_FECHA_NACIMIENTO`
Birth year `UY_L2_ANIO_NACIMIENTO`	COLUMN NAME · DATA TYPE	`UY_ANIO`
Age `UY_L2_EDAD`	COLUMN NAME · DATA TYPE	`UY_EDAD`
Personal event dates `UY_L2_FECHA_EVENTO`	COLUMN NAME · DATA TYPE	`UY_FECHA_EVENTO`
Sex `UY_L2_SEXO`	COLUMN NAME · KNOWN VALUES	`UY_SEXO`
Localidad `UY_L2_LOCALIDAD`	COLUMN NAME · VALUE FORMAT	`UY_LOCALIDAD`
INE code `UY_L2_CODIGO_INE`	COLUMN NAME · VALUE FORMAT	`UY_CODIGO_INE`
Barrio and balneario `UY_L2_BARRIO`	COLUMN NAME	`UY_BARRIO`
Postal code `UY_L2_CODIGO_POSTAL`	COLUMN NAME · DATA TYPE	`UY_CODIGO_POSTAL`
Marital status `UY_L2_ESTADO_CIVIL`	COLUMN NAME · VALUE FORMAT	`UY_ESTADO_CIVIL`

DOMAIN	FOUND BY	ALGORITHM
Occupation `UY_L2_OCUPACION`	COLUMN NAME	UY_OCUPACION_O_CODIGO
Employer `UY_L2_EMPLEADOR`	COLUMN NAME	UY_EMPLEADOR
Education `UY_L2_NIVEL_EDUCATIVO`	COLUMN NAME VALUE FORMAT	UY_NIVEL_EDUCATIVO
School `UY_L2_INSTITUCION_EDUCATIVA`	COLUMN NAME	UY_INSTITUCION_EDUCATIVA
Dependants and children `UY_L2_PERSONAS_A_CARGO`	COLUMN NAME DATA TYPE	UY_CONTEO_LIMITADO
SENSITIVE DATA (ART. 4 E AND ART. 4 Ñ)		
Racial and ethnic origin `UY_L3_ASCENDENCIA`	COLUMN NAME VALUE FORMAT	UY_ASCENDENCIA
Indigenous people `UY_L3_PUEBLO_ORIGINARIO`	COLUMN NAME VALUE FORMAT	UY_PUEBLO
Nationality `UY_L3_NACIONALIDAD`	COLUMN NAME KNOWN VALUES	UY_NACIONALIDAD
Religion `UY_L3_RELIGION`	COLUMN NAME VALUE FORMAT	UY_RELIGION
Moral and philosophical convictions `UY_L3_CONVICCION_MORAL`	COLUMN NAME	UY_CATEGORIA_SUPRIMIDA
Political preferences `UY_L3_PREFERENCIA_POLITICA`	COLUMN NAME VALUE FORMAT	UY_PREFERENCIA_POLITICA
Party membership `UY_L3_AFILIACION_PARTIDARIA`	COLUMN NAME VALUE FORMAT	UY_PARTIDO
Trade union membership `UY_L3_AFILIACION_SINDICAL`	COLUMN NAME VALUE FORMAT	UY_CATEGORIA_SUPRIMIDA
Biometric data `UY_L3_BIOMETRICO`	COLUMN NAME DATA TYPE	UY_REDACTAR
Genetic data `UY_L3_GENETICO`	COLUMN NAME VALUE FORMAT	UY_REDACTAR
Sexual orientation `UY_L3_ORIENTACION_SEXUAL`	COLUMN NAME VALUE FORMAT	UY_ORIENTACION_SEXUAL
Sexual life `UY_L3_VIDA_SEXUAL`	COLUMN NAME	UY_CATEGORIA_SUPRIMIDA
Gender identity `UY_L3_IDENTIDAD_GENERO`	COLUMN NAME VALUE FORMAT	UY_IDENTIDAD_GENERO
Victims of violence `UY_L3_VICTIMA`	COLUMN NAME	UY_CATEGORIA_SUPRIMIDA
HEALTH DATA		
Health identifiers `UY_SALUD_IDENTIFICADOR`	COLUMN NAME	UY_CM_ALFANUM
Health coverage `UY_SALUD_COBERTURA`	COLUMN NAME VALUE FORMAT	UY_COBERTURA_SALUD

DOMAIN	FOUND BY	ALGORITHM
Diagnosis and ICD-10 UY_SALUD_DIAGNOSTICO	COLUMN NAME · VALUE FORMAT	UY_DIAGNOSTICO
Procedures UY_SALUD_PROCEDIMIENTO	COLUMN NAME	UY_PROCEDIMIENTO
Medicines UY_SALUD_MEDICAMENTO	COLUMN NAME · VALUE FORMAT	UY_MEDICAMENTO
Clinical text UY_SALUD_TEXTO_CLINICO	COLUMN NAME · DATA TYPE	UY_TEXTO_LIBRE
Test results UY_SALUD_RESULTADO_EXAMEN	COLUMN NAME	UY_CM_ALFANUM
HIV and sexually transmitted infections UY_SALUD_VIH	COLUMN NAME	UY_CATEGORIA_SUPRIMIDA
Blood group and Rh UY_SALUD_GRUPO_SANGUINEO	COLUMN NAME · VALUE FORMAT	dlpx-core:BloodType SL
Disability UY_SALUD_DISCAPACIDAD	COLUMN NAME · VALUE FORMAT	UY_DISCAPACIDAD
Carné de salud and occupational health UY_SALUD_OCUPACIONAL	COLUMN NAME · VALUE FORMAT	UY_APTITUD_LABORAL
Sexual and reproductive health UY_SALUD_REPRODUCTIVA	COLUMN NAME	UY_CATEGORIA_SUPRIMIDA
Mental health UY_SALUD_MENTAL	COLUMN NAME	UY_CATEGORIA_SUPRIMIDA
COMMERCIAL AND CREDIT DATA (ART. 22)		
Credit history UY_FIN_HISTORIAL_CREDITICIO	COLUMN NAME	UY_HISTORIAL_CREDITICIO
Debt UY_FIN_DEUDA	COLUMN NAME · DATA TYPE	dlpx-core:CM Numeric
Income and pay UY_FIN_INGRESOS	COLUMN NAME · DATA TYPE	dlpx-core:CM Numeric
Assets UY_FIN_PATRIMONIO	COLUMN NAME · DATA TYPE	dlpx-core:CM Numeric
Pasividad and benefits UY_FIN_PENSION	COLUMN NAME · DATA TYPE	dlpx-core:CM Numeric
Social programmes UY_FIN_PROGRAMA_SOCIAL	COLUMN NAME · VALUE FORMAT	UY_PROGRAMA_SOCIAL
Índice de Carencias Críticas UY_FIN_NIVEL_SOCIOECONOMICO	COLUMN NAME · VALUE FORMAT	UY_NIVEL_SOCIOECONOMICO
Housing tenure UY_FIN_VIVIENDA	COLUMN NAME · VALUE FORMAT	UY_TENENCIA_VIVIENDA
OFFENCES (ART. 18)		
Offences and records UY_PENAL_ANTECEDENTES	COLUMN NAME	UY_ANTECEDENTES
Court file UY_PENAL_EXPEDIENTE	COLUMN NAME · VALUE FORMAT	UY_EXPEDIENTE_JUDICIAL

PART 8

Direct identifiers

Data that identifies a person on its own. The cédula de identidad is the key of every Uruguayan record, and both it and the RUT come out with a valid check digit, because applications validate them. Uruguay is one of the few countries whose law makes a **legal person** a data subject (art. 4 D), so the razón social, the nombre de fantasía and a company RUT are masked here like any other identifier.

8.1 Cédula de identidad

UY_L1_CEDULA

ESSENTIAL | COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The number of the Dirección Nacional de Identificación Civil, the key of every Uruguayan record: seven digits and a check digit, written `1.234.567-2`, and also plain.

The same domain takes RUTs: a document column often holds both.

HOW IT IS FOUND

COLUMN NAME UY_L1_CEDULA – Path

90%	`c[eé]dula(_?(de_?)?identidad)?` `ci` `c_?i` `n(o|ro|um|umero)_?(c[eé]dula|documento|doc|identificaci[oó]n|id(ent)?)` `doc_?identidad` `nro_?doc` `num_?doc` `identificacion` `(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|elector|votante|contribuyente|proveedor|socio|conyuge|concubino|padre|madre|hijo|familiar|jubilado|pensionista|aportante)_?(cedula|ci|doc|documento)` `cedula_?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|elector|votante|contribuyente|proveedor|socio|conyuge|concubino|padre|madre|hijo|familiar|jubilado|pensionista|aportante)`
60%	`documento` `doc`

DATA TYPE UY_L1_CEDULA – Type

Accepts text (length 6 or more) or number (length 6 or more); any other type rules the domain out.

VALUE FORMAT UY_L1_CEDULA – Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d\.\d{3}\.\d{3}-\d)`	95%	
`0*(?:\d{1,3}\.?\d{3}\.?\d{3}-\d)`	80%	
`0*(?:\d{8})`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Digit by digit, with the check digit recomputed: weights 2 9 8 7 6 3 4 from the left, modulus 10, ten minus the remainder — exactly what Check Digit computes. The dots and the hyphen stay where they are.

`UY_DOCUMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM` .

> `UY_RUT` STRING ALGORITHM CHAIN
>
> Applies `UY_RUT_CD` → `UY_RUT_ESPACIO` → `UY_RUT_AUX` → `UY_RUT_VERIFICADOR` , in this order.
>
> > `UY_RUT_CD` CHECK DIGIT
> >
> > Masks the digits with `UY_RUT_CUERPO` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 8 9 2 3 4` from the right.
> >
> > > `UY_RUT_CUERPO` REGEX DECOMPOSE
> > >
> > > Matches one pattern and gives each part of the value its own action; when none matches: `UY_CM_DIGITOS` .
> > >
> > > > `UY_CM_DIGITOS` CHARACTER MAPPING
> > > >
> > > > Maps each character to another of its group (1 groups), keeping length and format.
> >
> > `UY_RUT_ESPACIO` REGEX DECOMPOSE
> >
> > Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.
> >
> > `UY_RUT_AUX` CHECK DIGIT
> >
> > Masks the digits with `UY_IDENTIDAD` and recomputes a modulus 11 check digit with weights `0 4 6 8 10 1 3 5 7 4 6 8` from the right.
> >
> > > `UY_IDENTIDAD` REGEX DECOMPOSE
> > >
> > > Matches one pattern and gives each part of the value its own action; when none matches: keep.
> >
> > `UY_RUT_VERIFICADOR` REGEX DECOMPOSE
> >
> > Tries 11 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> `UY_CEDULA` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `UY_CM_DIGITOS` .
>
> > `UY_CEDULA_CD` CHECK DIGIT
> >
> > Masks the digits with `UY_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 10 check digit with weights `4 3 6 7 8 9 2` from the right.
> >
> > > `UY_CM_DIGITOS_ANCHO_FIJO` CHARACTER MAPPING
> > >
> > > Maps each character to another of its group (1 groups), keeping length and format.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1.234.567-2	→	**5.649.285-5**
12345672	→	**56492855**
211003420017	→	**212774060014**

8.2 RUT

UY_L1_RUT

ESSENTIAL COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The twelve-digit taxpayer number of the Dirección General Impositiva: two digits for the kind of taxpayer, six for the number, three for the branch and one check digit — `21-100342-001-7` .

Article 4 D) makes the data of a **legal person** personal data too, so a company RUT is masked like any other identifier — unlike the sets of countries whose law reaches only natural persons.

HOW IT IS FOUND

COLUMN NAME UY_L1_RUT — Path

90% `rut[a-z0-9_]*` *(except when followed by* `a` *)* `n(o|ro|um|umero)_?rut` `registro_?[uú]nico_?tributario` `(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|elector|votante|contribuyente|proveedor|socio|conyuge|concubino|padre|madre|hijo|familiar|jubilado|pensionista|aportante)_?rut` `rut_?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|elector|votante|contribuyente|proveedor|socio|conyuge|concubino|padre|madre|hijo|familiar|jubilado|pensionista|aportante)` `id_?tributario` `tax_?id` `n(o|ro|um|umero)_?(de_?)?contribuyente`

VALUE FORMAT UY_L1_RUT — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{12})`	70%	
`0*(?:\d{2}[\s\-.]?\d{6}[\s\-.]?\d{3}[\s\-.]?\d)`	80%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The kind of taxpayer and the branch stay, the six digits of the number are mapped and the check digit is recomputed.

`UY_RUT_COLUMNA` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `UY_RUT` .

> `UY_RUT` **STRING ALGORITHM CHAIN**
>
> Applies `UY_RUT_CD` → `UY_RUT_ESPACIO` → `UY_RUT_AUX` → `UY_RUT_VERIFICADOR` , in this order.
>
> > `UY_RUT_CD` **CHECK DIGIT**
> >
> > Masks the digits with `UY_RUT_CUERPO` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 8 9 2 3 4` from the right.
> >
> > > `UY_RUT_CUERPO` **REGEX DECOMPOSE**
> > >
> > > Matches one pattern and gives each part of the value its own action; when none matches: `UY_CM_DIGITOS` .
> > >
> > > > `UY_CM_DIGITOS` **CHARACTER MAPPING**
> > > >
> > > > Maps each character to another of its group (1 groups), keeping length and format.
> >
> > `UY_RUT_ESPACIO` **REGEX DECOMPOSE**
> >
> > Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.
> >
> > `UY_RUT_AUX` **CHECK DIGIT**
> >
> > Masks the digits with `UY_IDENTIDAD` and recomputes a modulus 11 check digit with weights `0 4 6 8 10 1 3 5 7 4 6 8` from the right.
> >
> > > `UY_IDENTIDAD` **REGEX DECOMPOSE**
> > >
> > > Matches one pattern and gives each part of the value its own action; when none matches: keep.
> >
> > `UY_RUT_VERIFICADOR` **REGEX DECOMPOSE**
> >
> > Tries 11 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
211003420017	→	**212774060014**

8.3 Foreigner documents

UY_L1_DOCUMENTO_EXTRANJERO

ESSENTIAL · COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

The cédula de extranjería, the refugee card, the residence and work permits, the visa and the migratory status.

HOW IT IS FOUND

COLUMN NAME UY_L1_DOCUMENTO_EXTRANJERO — Path

85% `c[eé]dula_?(de_?)?extranjer[ií]a` `documento_?(de_?)?extranjer[oa]` `doc_?extranjero` `n(o|ro|um|umero)_?(extranjer[ií]a|refugiado)` `carn[eé]_?(de_?)?(extranjer[ií]a|refugiado)` `residencia_?(legal|permanente|temporaria)` `permiso_?(de_?)?(residencia|trabajo)` `visa(_?(n(o|ro|um|umero)|tipo))?` `condici[oó]n_?migratoria` `c[eé]dula_?mercosur`

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
R123456	→	**Q801473**

8.4 Passport

UY_L1_PASAPORTE

ESSENTIAL · COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

Uruguayan passport numbers and foreign ones.

HOW IT IS FOUND

COLUMN NAME UY_L1_PASAPORTE — Path

90% `pasaporte[a-z0-9_]*` `n(o|ro|um|umero)_?pasaporte` `passport[a-z0-9_]*`

VALUE FORMAT UY_L1_PASAPORTE — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]\d{6,7}`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A123456	→	**E854099**

8.5 Credencial cívica

UY_L1_CREDENCIAL_CIVICA

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

The series of three letters and the number the Corte Electoral gives every voter — `ABC 12345`. Voting is compulsory in Uruguay, so almost every adult has one, and the internal elections put party membership beside it.

HOW IT IS FOUND

COLUMN NAME UY_L1_CREDENCIAL_CIVICA – Path

85% `credencial(_?c[ií]vica)?` `serie_?(y_?)?n(o|ro|um|umero)?(_?credencial)?` `n(o|ro|um|umero)_?(credencial|c[ií]vico)` `inscripci[oó]n_?c[ií]vica` `registro_?c[ií]vico` `padr[oó]n_?electoral`

VALUE FORMAT UY_L1_CREDENCIAL_CIVICA – Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{3}[\s\-]?\d{4,5}`	45%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Letters to letters and digits to digits, position by position.

`UY_CM_DIGITOS_LETRAS` CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
ABC 12345	→	**BKM 40380**

8.6 Civil registry records

UY_L1_PARTIDA

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

The partida, tomo, folio and acta of the birth, marriage, concubinage and death records the Dirección General de Registro de Estado Civil keeps.

HOW IT IS FOUND

COLUMN NAME UY_L1_PARTIDA – Path

85% `partida_?(de_?)?(nacimiento|matrimonio|defunci[oó]n|uni[oó]n_?concubinaria)(_?(n(o|ro|um|umero)|folio|tomo|acta))?` `n(o|ro|um|umero)_?(partida|acta)` `acta_?(de_?)?(nacimiento|matrimonio|defunci[oó]n)` `tomo(_?(partida|registro))?` `folio(_?(partida|registro))?` `registro_?(de_?)?estado_?civil` `testimonio_?(de_?)?partida`

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123/1985	→	**091/7273**

8.7 BPS and the professional funds

UY_L1_SEGURO_SOCIAL

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The Banco de Previsión Social numbers of the worker and of the employer, the historia laboral, the FONASA affiliation and the numbers of the notarial, banking, professional, military and police funds.

HOW IT IS FOUND

> COLUMN NAME UY_L1_SEGURO_SOCIAL — Path
>
> 85% `bps[a-z0-9_]*` `n(o|ro|um|umero)_?(bps|afiliaci[oó]n|afiliado|empresa_?bps|aportante|historia_?laboral)` `c[oó]digo_?(de_?)?(afiliado|empresa_?bps)` `n(o|ro|um|umero)_?(de_?)?(empresa|obra)` `afiliaci[oó]n_?bps` `caja_?(profesional|notarial|bancaria|militar|policial)` `fonasa`

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456789	→	**110858568**

8.8 Student code

UY_L1_CODIGO_ESTUDIANTE

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

The student code, the enrolment number and the university card.

HOW IT IS FOUND

> COLUMN NAME UY_L1_CODIGO_ESTUDIANTE — Path
>
> 80% `c[oó]digo_?(de_?)?(estudiante|alumno|matr[ií]cula)` `cod_?(alumno|estudiante)` `n(o|ro|um|umero)_?(de_?)?(matr[ií]cula|estudiante)` `carn[eé]_?(de_?)?(estudiante|universitario)` `id_?(alumno|estudiante)` `c[eé]dula_?estudiantil` `gurí` `gur[ií]_?(id|codigo)`

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
202012345	→	**239159952**

8.9 Professional registration

UY_L1_MATRICULA_PROFESIONAL

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The professional registration number and the number of the professional fund, published together with the name.

HOW IT IS FOUND

COLUMN NAME UY_L1_MATRICULA_PROFESIONAL – Path

85% `matr[ií]cula_?(profesional|m[eé]dica|de_?abogado)` `n(o|ro|um|umero)_?(de_?)?(matr[ií]cula|registro_?profesional|caja_?profesional)` `registro_?(m[eé]dico|profesional)` `n(o|ro|um|umero)_?(de_?)?t[ií]tulo` `habilitaci[oó]n_?profesional`

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
MP–12345	→	**WX–51031**

8.10 Given name

UY_L1_NOMBRE

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The given name, one or two: `Washington`, `Juan Pablo`, `María de los Ángeles`.

HOW IT IS FOUND

COLUMN NAME UY_L1_NOMBRE – Path

85% `primer_?nombre` `segundo_?nombre` `nombres?_?(de_?)?pila` `pri(mer)?_?nom` `seg(undo)?_?nom` `nombre_?1` `nombre_?2` `first_?names?` `given_?names?` `fname` `middle_?names?` `nombres` *(except when followed by `completos?`, `y_?apellidos?`, `apellidos?`)*

50% `nombre` *(except when followed by list E1)* `nom` *(except when followed by list E2)* `name` *(except when followed by list E3)*

KNOWN VALUES UY_L1_NOMBRE — List

LIST	VALUES	STRENGTH	FIRST VALUES
uy-detectar-nombres.txt	345	70%	Juan, José, Jose, Carlos, Luis, Jorge

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, replacing each name with one from the list. `de`, `del` and `la` stay in place. More than four words are masked character by character.

`UY_NOMBRES` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.

`UY_PALABRA_NOMBRE` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_NOMBRE`.

`UY_NOMBRE` NAME

Replaces the name with one of the 287 names in `uy-nombres.txt`.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
María de los Ángeles	→	**Viviana de los Washington**
JUAN PABLO	→	**DIONISIO LUIS**

8.11 Surname

UY_L1_APELLIDO

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The surnames — the father's and the mother's —, in separate columns or together: `Rodríguez Techera`. The set carries the Uruguayan ones, Spanish, Italian, Basque and Portuguese alike, with `Da Silva` and `De León` kept whole.

HOW IT IS FOUND

COLUMN NAME UY_L1_APELLIDO — Path

85% `apellidos?` `primer_?apellido` `segundo_?apellido` `apellido_?(1|2|paterno|materno)` `ape_?(1|2|pat|mat)` `ap_?(paterno|materno)` `last_?names?` `surnames?` `family_?names?` `lname`

KNOWN VALUES UY_L1_APELLIDO — List

LIST	VALUES	STRENGTH	FIRST VALUES
uy-detectar-apellidos.txt	427	70%	Rodríguez, Rodriguez, González, Gonzalez, Fernández, Fernandez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, replacing each surname with one from the list; particles stay in place.

`UY_APELLIDOS` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.

`UY_PALABRA_APELLIDO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_APELLIDO`.

`UY_APELLIDO` NAME

Replaces the name with one of the 356 names in `uy-apellidos.txt`.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Rodríguez Techera	→	**Bauzá Nicola**

8.12 Full name

UY_L1_NOMBRE_COMPLETO

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

Given names and surnames in one column: `Juan Pablo Rodríguez Techera`. Also those of the mother, father, guardian, spouse, concubino, emergency contact and reference.

HOW IT IS FOUND

COLUMN NAME — UY_L1_NOMBRE_COMPLETO — Path

90% `nombres?_?(completos?|y_?apellidos?|apellidos?)` `apellidos?_?(y_?)?nombres?` `nombre_?(del_?|de_?la_?)?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|concubino|contacto|referencia|victima|denunciante|imputado|testigo|medico|docente|socio|heredero|donante|tutor|jubilado|pensionista|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)` `(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|concubino|contacto|referencia|victima|denunciante|imputado|testigo|medico|docente|socio|heredero|donante|tutor|jubilado|pensionista|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)_?(nombre|nom)` `nom_?(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|trabajador|funcionario|colaborador|alumno|estudiante|deudor|codeudor|garante|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madre|padre|conyuge|concubino|contacto|referencia|victima|denunciante|imputado|testigo|medico|docente|socio|heredero|donante|tutor|jubilado|pensionista|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)` `nombre_?(madre|padre|tutor|conyuge|concubino|contacto_?emergencia|referencia)` `full_?name` `person_?name`

60% `madre` `padre` `tutor` `conyuge` `concubino` `representante_?legal` `apoderado` `garante` `beneficiario` `heredero` `titular` `referencia_?(personal|familiar)`

50% `nombre` *(except when followed by list E1)* `nom` *(except when followed by list E2)* `name` *(except when followed by list E3)*

KNOWN VALUES UY_L1_NOMBRE_COMPLETO — List

LIST	VALUES	STRENGTH	FIRST VALUES
uy-detectar-nombres.txt	345	65%	Juan, José, Jose, Carlos, Luis, Jorge
uy-detectar-apellidos.txt	427	65%	Rodríguez, Rodriguez, González, Gonzalez, Fernández, Fernandez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

In Uruguayan order: two words are a given name and a surname; three, a given name and two surnames; four, two and two. `APELLIDOS, NOMBRES` with a comma is masked keeping the comma.

`UY_NOMBRE_COMPLETO` REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.

> `UY_APELLIDOS` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.
>
> > `UY_PALABRA_APELLIDO` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `UY_APELLIDO`.
> >
> > > `UY_APELLIDO` NAME
> > >
> > > Replaces the name with one of the 356 names in `uy-apellidos.txt`.
> >
> > `UY_CM_ALFANUM` CHARACTER MAPPING
> >
> > Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_NOMBRES` REGEX DECOMPOSE
>
> Tries 4 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.
>
> > `UY_PALABRA_NOMBRE` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `UY_NOMBRE`.
> >
> > > `UY_NOMBRE` NAME
> > >
> > > Replaces the name with one of the 287 names in `uy-nombres.txt`.

EXAMPLES

VALUE		MASKED
Juan Pablo Rodríguez Techera	→	**Dionisio Luis Bauzá Nicola**
Serrana Rodríguez	→	**Selva Bauzá**
RODRÍGUEZ TECHERA, JUAN PABLO	→	**BAUZÁ NICOLA, DIONISIO LUIS**

8.13 Razón social and nombre de fantasía

UY_L1_RAZON_SOCIAL

ESSENTIAL COLUMN NAME SECURE LOOKUP

WHAT IT IS

The legal and the trading name of a company. In Uruguay this is not a courtesy: article 4 D) makes a **legal person** a data subject, and article 9 C) names the razón social, the nombre de fantasía and the RUT among the data a listing may hold without consent.

HOW IT IS FOUND

COLUMN NAME UY_L1_RAZON_SOCIAL — Path

85% `raz[oó]n_?social` `razonsocial` `nombre_?(de_?)?fantas[ií]a` `nombre_?(comercial|de_?la_?empresa|empresa)` `denominaci[oó]n_?social` `nombre_?legal` `business_?name` `company_?name` `legal_?name`

HOW IT IS MASKED

Replaced by a fictitious company name.

`UY_RAZON_SOCIAL` SECURE LOOKUP

Replaces the value with one of the 20 values in `uy-razones-sociales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Corporación Comercial Oriental S.A.`	→	**`Hotel Mirador del Cerro S.A.`**

8.14 E-mail

UY_L1_EMAIL

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Personal and corporate e-mail addresses.

HOW IT IS FOUND

> COLUMN NAME — UY_L1_EMAIL — Path
>
> 85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `correo(_?electr[oó]nico)?[a-z0-9_]*` `dir_?correo` `direcci[oó]n_?(de_?)?correo` `direcci[oó]n_?electr[oó]nica`

> DATA TYPE — UY_L1_EMAIL — Type
>
> Accepts text (length 5 or more); any other type rules the domain out.

> VALUE FORMAT — UY_L1_EMAIL — Regex
>
PATTERN	STRENGTH	NOTES
`[\p{L}\p{N}._%+'\-]+@[\p{L}\p{N}.\-]+\.[A-Za-z]{2,24}`	100%	
>
> A value that matches none counts 20% against the domain.

HOW IT IS MASKED

User and domain are mapped character by character, and the top-level domain — `.com`, `.com.uy` — becomes `.test`, reserved for tests: a masked address can never deliver.

`UY_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.

> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`serrana.rodriguez@gmail.com`	→	**`kebsube.sustajoot@pgoeb.test`**

8.15 Phone

UY_L1_TELEFONO

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Mobiles of nine digits starting `09`, and landlines of eight starting with 2 in Montevideo and with 4 in the interior.

HOW IT IS FOUND

COLUMN NAME — UY_L1_TELEFONO — Path

85% `tel` `tel[eé]fono[a-z0-9_]*` `tel_?(fijo|casa|oficina|trabajo|contacto|celular|m[oó]vil)` `celular[a-z0-9_]*` `cel` `m[oó]vil` `whats_?app` `n(o|ro|um|umero)_?` `(tel|tel[eé]fono|celular|cel|contacto)` `fax` `phone[a-z0-9_]*` `mobile[a-z0-9_]*`

VALUE FORMAT — UY_L1_TELEFONO — Regex

PATTERN	STRENGTH	NOTES
`0*(?:(\+?598[\s\-]?)?0?9\d[\s\-]?\d{3}[\s\-]?\d{3})`	90%	
`\(?0?[24]\)?[\s\-]?\d{3}[\s\-]?\d{4}`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

`+598` and the prefix stay; the rest of the digits are mapped and the spacing of the original is kept, so the number still says mobile or landline and which region.

`UY_TELEFONO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_DIGITOS`.

`UY_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`+598 99 123 456`	→	**`+598 99 904 292`**
`099123456`	→	**`099904292`**
`2 400 12 34`	→	**`2 727 07 18`**

8.16 Address

UY_L1_DIRECCION

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

The address with the street and the door number, the apartamento and often the corner — `Av. 18 de Julio 1234 apto. 501`, `Calle Mercedes 900 esq. Río Branco`.

HOW IT IS FOUND

COLUMN NAME — UY_L1_DIRECCION — Path

80% `direcci[oó]n[a-z0-9_]*` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`, `correo`; except when followed by list E4)* `domicilio[a-z0-9_]*` `dom_?(residencia|particular|laboral|cliente|fiscal|constituido)` `residencia` `lugar_?(de_?)?residencia` `calle(_?(y_?n[uú]mero|esquina))?` `address[a-z0-9_]*` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`; except when followed by list E5)*

DATA TYPE — UY_L1_DIRECCION — Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT UY_L1_DIRECCION — Regex

PATTERN	STRENGTH	NOTES
`(?i)(av|avenida|bv|bulevar|calle|camino|cno|pasaje|rambla|ruta)\.?\s+[a-záéíóúñ0-9.' ]{2,40}\s*\d{1,5}.*`	80%	
`(?i).*\b(apto|apartamento|esq|esquina|padr[oó]n|bis|piso|puerta)\.?\s*[a-z0-9]{1,6}.*`	60%	
`(?i)ruta\s*\d{1,3}\s*(km|kil[oó]metro)\.?\s*\d{1,3}.*`	70%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The whole line is replaced by a fictitious Uruguayan address of the same form. Barrio, localidad and postal code have domains of their own for when they live in separate columns.

`UY_DIRECCION` SECURE LOOKUP

Replaces the value with one of the 4,000 values in `uy-direcciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Av. 18 de Julio 1234 apto. 501`	→	**`Camino Piedras 2345 apto. 340`**

8.17 Address complement

UY_L1_DIRECCION_COMPLEMENTO

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Apartamento, piso, block, torre, puerta, manzana, solar or the corner in columns of their own.

HOW IT IS FOUND

COLUMN NAME UY_L1_DIRECCION_COMPLEMENTO — Path

70% `apartamento` `apto` `apto_?n(o|ro|um|umero)` `piso` `block` `bloque` `torre` `puerta` `unidad_?(habitacional|padron)` `esquina` `esq` `entre_?calles` `manzana` `solar` `n(o|ro|um|umero)_?(puerta|apto|apartamento)` `complemento(_?direcci[oó]n)?` `referencia_?(de_?)?(direcci[oó]n|domicilio)`

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`apto. 501`	→	**`ovja. 153`**

8.18 Bank account

UY_L1_CUENTA_BANCARIA

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Savings, current and payroll account numbers. The bank code is not personal data and has no domain.

HOW IT IS FOUND

COLUMN NAME UY_L1_CUENTA_BANCARIA — Path

85% `cuenta_?(bancaria|banco|corriente|ahorros?|sueldo|n[oó]mina|abono|dep[oó]sito|destino|origen)` `n(o|ro|um|umero)_?(de_?)?(cuenta|cta)` `nro_?cta` `num_?cta` `cta_?(cte|corriente|ahorros?|bancaria)` `iban` `account_?(no|num|number)` `bank_?account`

HOW IT IS MASKED

Digits are mapped; separators stay.

`UY_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
001234567890	→	**001713678115**

8.19 Payment card

UY_L1_TARJETA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers, recognized by the Luhn algorithm.

HOW IT IS FOUND

COLUMN NAME UY_L1_TARJETA — Path

85% `tarjeta(_?(cr[eé]dito|d[eé]bito|n(o|ro|um|umero)))?` `n(o|ro|um|umero)_?tarjeta` `pan` `card_?(no|num|number)` `credit_?card` `tc_?(numero|num|nro)`

VALUE FORMAT UY_L1_TARJETA — Regex

PATTERN	STRENGTH	NOTES
`0*(?:3[47]\d{13}|[1–9]\d{12,13}|[1–9]\d{15,18})`	90%	LUHN check digit; after removing `[\s\-]`

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Credit Card, which comes with the Masking Engine: another number that passes the Luhn check, keeping the first six digits — the issuer, not the holder. Only values shaped like a card reach it; the others pass unchanged instead of failing the row.

`UY_TARJETA` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `dlpx-core:Credit Card` PAYMENT CARD
>
> Comes with the Masking Engine and is used as it ships. Replaces the card number with another that passes the Luhn check, keeping the first six digits — the issuer, not the holder.

EXAMPLES

VALUE		MASKED
4093 8200 0000 0001	→	**4093 8286 1298 3134**

8.20 Digital wallet

UY_L1_BILLETERA

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

Prex, Mi Dinero, OCA Blue and other wallet identifiers, and the bitcoin addresses some systems keep.

HOW IT IS FOUND

COLUMN NAME UY_L1_BILLETERA — Path

85% `billetera(_?(digital|electr[oó]nica|m[oó]vil))?` `wallet(_?(id|address|direccion))?` `prex` `mi_?dinero` `midinero` `oca_?blue` `dinero_?electr[oó]nico` `c[oó]digo_?qr` `qr_?(id|codigo)` `direcci[oó]n_?(bitcoin|btc|wallet)` `btc_?(address|direccion)`

VALUE FORMAT UY_L1_BILLETERA — Regex

PATTERN	STRENGTH	NOTES
`(bc1|[13])[a-zA-HJ-NP-Z0-9]{25,59}`	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the shape. A masked bitcoin address no longer passes its own checksum, which is what a test copy wants.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`bc1qar0srrr7xfkvy5l643lydnw9re59gtzzwf5mdq`	→	`mh2wis8tsdm0pdjdv8v511yqxqg4ze53qkjbvp7dgf`

8.21 IP address

UY_L1_IP

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses from access logs and transactions. Article 20 binds the telecommunications operators that produce them.

HOW IT IS FOUND

COLUMN NAME UY_L1_IP — Path

85% `ip` `ip_?(address|addr|origen|destino|cliente|usuario|acceso|login|remota|publica)` `direcci[oó]n_?ip` `dir_?ip` `ipv[46]` `remote_?addr(ess)?` `client_?ip` `host_?ip`

VALUE FORMAT UY_L1_IP — Regex

PATTERN	STRENGTH	NOTES
`0*(?:((25[0-5]|2[0-4]\d|1?\d?\d)\.){3}(25[0-5]|2[0-4]\d|1?\d?\d))`	100%	
`0*(?:[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7})`	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet is mapped to 1–254; an IPv6 address is mapped keeping its hex characters.

`UY_IP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_CM_HEX`.

> `UY_OCTETO` NUMERIC MAPPING
>
> Maps the number to another between 1 and 254.
>
> `UY_CM_HEX` CHARACTER MAPPING
>
> Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
164.73.45.12	→	**181.34.51.94**

8.22 Device identifier

UY_L1_DISPOSITIVO

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

IMEI, IMSI, ICCID, MAC address, advertising and session identifiers.

HOW IT IS FOUND

> COLUMN NAME UY_L1_DISPOSITIVO — Path
>
> **80%** `imei` `imsi` `iccid` `mac` `mac_?address` `direcci[oó]n_?mac` `device_?(id|uuid|serial)` `id_?(dispositivo|equipo|celular)` `serial_?(equipo|celular|dispositivo)` `advertising_?id` `idfa` `gaid` `session_?id` `id_?sesi[oó]n`

> VALUE FORMAT UY_L1_DISPOSITIVO — Regex
>
PATTERN	STRENGTH	NOTES
`0*(?:([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2})`	100%	
`0*(?:\d{15})`	80%	LUHN check digit
>
> A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, with hex digits kept hex: a MAC stays a MAC.

`UY_CM_HEX` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3c:22:fb:9a:10:e4	→	**5e:83:bb:3c:31:f9**

8.23 Cookies and tracking identifiers

UY_L1_COOKIE

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

The identifier a site stores in the browser and the campaign parameters that travel with it. Article 21 allows profiles built for advertising only from public sources or with consent, and names the *hábitos de consumo* these identifiers build.

HOW IT IS FOUND

COLUMN NAME UY_L1_COOKIE — Path

80% `cookie(_?(id|value|valor|nombre))?` `cookies` `_?ga` `_?gid` `fbp` `fbclid` `utm_?(source|medium|campaign|term|content)` `id_?(navegador|browser|visitante)` `visitor_?id` `tracking_?id` `client_?id`

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
GA1.2.123456789.1700000000	→	**ZE0.5.891552838.7889916184**

8.24 Vehicle plate

UY_L1_PLACA

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The plate with three letters and four digits since 2015, `SAB 1234`; the first letter is the departamento — A Montevideo, B Artigas, C Canelones, and so on to S Treinta y Tres.

HOW IT IS FOUND

COLUMN NAME UY_L1_PLACA — Path

85% `matr[ií]cula(_?(veh[ií]culo|auto|moto))?` *(except when preceded by `cod`, `codigo`, `tipo`; except when followed by `profesional`, `m[eé]dica`, `estudiante`, `de_?abogado`)* `placa(_?(veh[ií]culo|auto|moto))?` `n(o|ro|um|umero)_?(matr[ií]cula|placa|chapa)` `chapa(_?veh[ií]culo)?` `license_?plate` `plate(_?(no|number))?`

VALUE FORMAT UY_L1_PLACA — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{3}[\s\-]?\d{4}`	70%	
`[A-Z]{3}[\s\-]?\d{3}`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Letters to letters and digits to digits, position by position: the plate format stays.

`UY_CM_DIGITOS_LETRAS` CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
SAB 1234	→	**VVW 9348**

8.25 Vehicle and licence

UY_L1_VEHICULO

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

The VIN or chassis number, the engine number, the libreta de circulación and the driving licence.

HOW IT IS FOUND

COLUMN NAME UY_L1_VEHICULO — Path

85% `vin` `chasis` `n(o|ro|um|umero)_?(chasis|motor|serie|vin)` `motor_?n(o|ro|um|umero)` `libreta_?(de_?)?circulaci[oó]n` `licencia_?(de_?)?conducir(_?(n(o|ro|um|umero)|categor[ií]a))?` `n(o|ro|um|umero)_?licencia` `permiso_?[uú]nico_?nacional_?(de_?)?conducir` `punc`

VALUE FORMAT UY_L1_VEHICULO — Regex

PATTERN	STRENGTH	NOTES
`[A-HJ-NPR-Z0-9]{17}`	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
8AJHA8CD3J1234567	→	**8EWKE1QN1T0772894**

8.26 Property

UY_L1_INMUEBLE

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

The padrón the Dirección Nacional de Catastro gives every parcel, the cadastral code and the entry in the Registro de la Propiedad: they lead to the home and its owner.

HOW IT IS FOUND

COLUMN NAME UY_L1_INMUEBLE — Path

80% `padr[oó]n(_?(inmueble|rural|urbano|n(o|ro|um|umero)))?` `n(o|ro|um|umero)_?(de_?)?(padr[oó]n|inmueble|predio|catastral)` `c[oó]digo_?catastral` `catastro` `inscripci[oó]n_?registral` `registro_?(de_?la_?)?propiedad` `n(o|ro|um|umero)_?(de_?)?(unidad|contador|medidor)`

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
12345	→	**31564**

8.27 Customer and contract numbers

UY_L1_CONTRATO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Contract, policy, loan, application, member, subscriber, supply, case, claim or administrative file numbers, and customer or employee codes.

HOW IT IS FOUND

COLUMN NAME UY_L1_CONTRATO – Path

70% `n(o|ro|um|umero)_?(contrato|p[oó]liza|cr[eé]dito|pr[eé]stamo|solicitud|expediente_?(administrativo|interno)|tr[aá]mite|referencia|cliente|socio|suscriptor|suministro|servicio|caso|ticket|beneficio|siniestro)` `contrato_?(n(o|ro|um|umero))` `c[oó]digo_?(cliente|socio|empleado|afiliado|suministro)` `id_?(cliente|socio|empleado|afiliado)` `n(o|ro)_?(empleado|funcionario)` `c[oó]digo_?(de_?)?(empleado|funcionario|planilla)`

HOW IT IS MASKED

Character by character, keeping length and format. The mapping is deterministic, so joins keep working.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
CT-123456	→	**NG-557411**

8.28 User and social media

UY_L1_USUARIO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Login, alias and social media profiles.

HOW IT IS FOUND

COLUMN NAME UY_L1_USUARIO – Path

70% `usuario` `user_?name` `username` `login` `alias` `apodo` `nick(_?name)?` `perfil_?(instagram|facebook|twitter|tiktok|linkedin|x)` `instagram` `facebook` `twitter` `tiktok` `linkedin` `red_?social` `handle`

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`@serrana_rodriguez`	→	**`@kebsube_sustajoot`**

8.29 Credentials

UY_L1_CREDENCIAL

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Passwords and their hashes, PIN, security and OTP codes, CVV, tokens, API keys, the key of an electronic signature, private keys and seed phrases.

HOW IT IS FOUND

COLUMN NAME — UY_L1_CREDENCIAL — Path

90% `contrase[nñ]a` `clave` *(except when followed by* `catastral`, `primaria`, `for[aá]nea`, `valor`, `producto`*)* `password` `passwd` `pwd` `pass` `hash_?(clave|contrasena|password)` `pin` `c[oó]digo_?(seguridad|verificaci[oó]n|acceso|otp)` `cvv` `cvc` `token(_?(acceso|refresh|api))?` `access_?token` `refresh_?token` `api_?key` `llave_?(api|privada)` `secreto` `secret` `otp` `firma_?(electr[oó]nica|digital)_?(clave|pin)` `pregunta_?secreta` `respuesta_?secreta` `frase_?semilla` `seed_?phrase`

VALUE FORMAT — UY_L1_CREDENCIAL — Regex

PATTERN	STRENGTH	NOTES
`\$2[abxy]?\$\d{2}\$[./A-Za-z0-9]{53}`	95%	
`\$(1|5|6)\$(rounds=\d+\$)?[./A-Za-z0-9]{1,16}\$[./A-Za-z0-9]{22,86}`	95%	
`\$argon2(id|i|d)\$v=\d+\$m=\d+,t=\d+,p=\d+\$\S+`	95%	
`pbkdf2_sha(1|256|512)\$\d+\$\S+\$\S+`	95%	
`\{(SSHA|SHA|SSHA256|SSHA512|SMD5|MD5|CRYPT)\}\S+`	95%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Every character becomes `X`. A credential has no use in a test copy, and a hash masked character by character could still be cracked.

`UY_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
`Clave#2024`	→	**`XXXXXXXXXX`**

8.30 Geolocation

UY_L1_GEOLOCALIZACION

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in separate columns, from apps, visits, addresses and deliveries.

HOW IT IS FOUND

COLUMN NAME UY_L1_GEOLOCALIZACION — Path

85% `lat` `latitud` `lon` `lng` `longitud` `coordenadas?` `coord_?[xy]` `geo_?(lat|lon|lng|loc|localizacion|posicion)` `georreferenciaci[oó]n` `geolocalizaci[oó]n` `gps(_?(ubicaci[oó]n|posici[oó]n|coordenadas))?` `ubicaci[oó]n_?gps`

50% `long`

VALUE FORMAT UY_L1_GEOLOCALIZACION — Regex

PATTERN	STRENGTH	NOTES
`-3[0-5]\.\d{3,}\s*,\s*-5[3-8]\.\d{3,}`	90%	
`-5[3-8]\.\d{4,}`	50%	
`-3[0-5]\.\d{4,}`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the other decimals are mapped: the place is generalized, not moved.

`UY_COORDENADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `UY_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`-34.903280,-56.188160`	→	**`-34.908238,-56.116469`**

8.31 Free text

UY_L1_TEXTO_LIBRE

COLUMN NAME DATA TYPE VALUE FORMAT FREE TEXT REDACTION

WHAT IT IS

Remarks, complaint descriptions, accounts of events and messages where anything gets written — cédula, RUT, phone and names in the middle of a sentence.

HOW IT IS FOUND

COLUMN NAME UY_L1_TEXTO_LIBRE — Path

60% `observaci[oó]n(es)?` `obs` `comentarios?` `notas?` `anotaci[oó]n(es)?` `glosa` `descripci[oó]n_?(queja|reclamo|solicitud|caso|hechos|novedad|atenci[oó]n|denuncia)` `detalle_?(reclamo|solicitud|caso|atenci[oó]n)` `hechos` `relato` `justificaci[oó]n` `mensaje` *(except when preceded by list E6; except when followed by list E7)* `texto(_?libre)?` `resumen_?(caso|atenci[oó]n)` `queja` `reclamo` `denuncia_?texto` `remarks?` `comments?` `notes?` `free_?text` `memo`

DATA TYPE UY_L1_TEXTO_LIBRE — Type

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT UY_L1_TEXTO_LIBRE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d\.\d{3}\.\d{3}-\d)`	80%	anywhere in the value
`[\w.+\-]+@[\w\-]+\.[A-Za-z]{2,}`	70%	anywhere in the value
`0*(?:0?9\d[\s\-]?\d{3}[\s\-]?\d{3})`	60%	anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

Free Text Redaction: cédulas, RUTs, e-mail, mobiles, cards, plates and IPs become `[DATO]`, and the names of the lists `[NOMBRE]`.

`UY_TEXTO_LIBRE` **FREE TEXT REDACTION**

Replaces the text matching 8 patterns with `[DATO]`, and the 1,494 terms of `uy-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
`Cliente Rodríguez, CI 1.234.567-2, correo s.rodriguez@gmail.com, cel 099123456.`	→	**`Cliente [NOMBRE], CI [DATO], correo [DATO], cel [DATO].`**

PART 9

Quasi-identifiers

Data that identifies nobody on its own, but does in combination. Uruguay has 3.4 million inhabitants and, for the census, 652 localidades: 624 of them had fewer than 20,000 in 2023 — 873,000 people, a quarter of the country — and Montevideo holds 1.28 million of the rest. A birth date, a sex and one of those localidades point at a handful of people. These attributes are generalized or shifted rather than replaced, and the data keeps its analytical value.

9.1 Birth date

UY_L2_FECHA_NACIMIENTO

ESSENTIAL | COLUMN NAME | DATA TYPE | DATE SHIFT

WHAT IT IS

The birth date, as a date, timestamp or text.

HOW IT IS FOUND

COLUMN NAME — UY_L2_FECHA_NACIMIENTO – Path

90% `(fecha|fec|fch|f)_?(de_?)?nac(imiento)?` `fnac` `fechanac(imiento)?` `cumplea[ñn]os` `dob` `date_?of_?birth` `birth_?date` `birthday`

DATA TYPE — UY_L2_FECHA_NACIMIENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 60 days either way. Ages and school years change for few people; the date stays plausible and the same birth date always moves the same way.

`UY_FECHA_NACIMIENTO` DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	**1985-08-05T00:00**

9.2 Birth year

UY_L2_ANIO_NACIMIENTO

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

The birth year in a column of its own.

HOW IT IS FOUND

COLUMN NAME — UY_L2_ANIO_NACIMIENTO – Path

90% `a[ñn]o_?(de_?)?nac(imiento)?` `anio_?nac(imiento)?` `year_?of_?birth` `birth_?year` `yob`

DATA TYPE — UY_L2_ANIO_NACIMIENTO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit is mapped: `1985` becomes a year from 1980 to 1989.

`UY_ANIO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `UY_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	**1980**

9.3 Age

UY_L2_EDAD

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

Age in years, also age group or five-year band. Uruguay is the oldest country of the region, so a very high age is less rare here — but still rare.

HOW IT IS FOUND

> COLUMN NAME UY_L2_EDAD — Path
>
> 85% `edad(_?(actual|a[nñ]os|anios|paciente|afiliado|cliente|al_?(ingreso|diagn[oó]stico|fallecimiento)))?` `grupo_?etario` `tramo_?(de_?)?edad` `rango_?(de_?)?edad` `quinquenio` `age(_?(years|group))?`

> DATA TYPE UY_L2_EDAD — Type
>
> Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The tens digit stays and the unit is mapped (37 becomes 30–39). A hundred or more becomes 90: rare ages identify.

`UY_EDAD` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `UY_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	**35**
104	→	**90**

9.4 Personal event dates

UY_L2_FECHA_EVENTO

COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

Dates that say something about the person: death, marriage, hiring and leaving, retirement, admission, diagnosis, arrest, sentence, sick leave, cédula issue.

HOW IT IS FOUND

COLUMN NAME UY_L2_FECHA_EVENTO – Path

80% `(fecha|fec|fch|f)_?(de_?)?(defunci[oó]n|fallecimiento|muerte|matrimonio|divorcio|ingreso|egreso|alta|baja|cese|retiro|contrataci[oó]n|despido|jubilaci[oó]n|internaci[oó]n|hospitalizaci[oó]n|diagn[oó]stico|atenci[oó]n|consulta|parto|detenci[oó]n|sentencia|expedici[oó]n(_?(cedula|documento))?|vencimiento_?c[eé]dula|vacunaci[oó]n|cirug[ií]a|accidente|certificaci[oó]n) fec_?(exp|expedicion|defuncion|ingreso|egreso|baja) date_?of_?(death|marriage|hire|admission|discharge)`

DATA TYPE UY_L2_FECHA_EVENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 30 days either way.

`UY_FECHA_EVENTO` DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	**2021-03-05T00:00**

9.5 Sex

UY_L2_SEXO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Sex as the system records it: `F` / `M`, `Femenino` / `Masculino`, `Mujer` / `Hombre` or the codes 1 and 2.

HOW IT IS FOUND

COLUMN NAME UY_L2_SEXO – Path

85% `sexo(_?(biol[oó]gico|al_?nacer|paciente|afiliado|cliente))?` `(tp|tipo|cod|cd|id)_?sexo` `g[eé]nero` *(except when followed by* ***identidad****,* ***autopercibido****)* `sex` `gender` *(except when followed by* ***identity****)*

KNOWN VALUES UY_L2_SEXO – List

LIST	VALUES	STRENGTH	FIRST VALUES
`uy-detectar-sexo.txt`	6	80%	femenino, masculino, mujer, hombre, female, male
`uy-detectar-sexo-letra.txt`	3	60%	f, m, h

Values are split into words, and each word is looked up.

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary: `F` stays `F` or `M`, `1` stays `1` or `2`. Gender identity has its own domain among the sensitive data.

`UY_SEXO` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_SEXO_FEMENINO_MASCULINO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-femenino-masculino.txt`, chosen by a keyed hash.

`UY_SEXO_MUJER_HOMBRE` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-mujer-hombre.txt`, chosen by a keyed hash.

`UY_SEXO_FEMALE_MALE` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-female-male.txt`, chosen by a keyed hash.

`UY_SEXO_F_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-f-m.txt`, chosen by a keyed hash.

`UY_SEXO_H_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-h-m.txt`, chosen by a keyed hash.

`UY_SEXO_1_2` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-1-2.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	**M**
Femenino	→	**Femenino**

9.6 Localidad

UY_L2_LOCALIDAD

COLUMN NAME VALUE FORMAT DATA CLEANSING

WHAT IT IS

The localidad of residence, birth or care, by name — alone or with the departamento, `Piriápolis – Maldonado`.

HOW IT IS FOUND

COLUMN NAME UY_L2_LOCALIDAD – Path

85% `localidad(_?(residencia|nacimiento|domicilio))?` *(except when followed by `cod`, `codigo`, `id`)* `ciudad(_?(residencia|nacimiento|domicilio|cliente))?` `pueblo` *(except when followed by `indigena`, `originario`)* `(nom|nombre|desc)_?(localidad|ciudad|pueblo)` `lugar_?(de_?)?nacimiento` `city` `town`

VALUE FORMAT UY_L2_LOCALIDAD – Values

PATTERN	STRENGTH	NOTES
One of 586 known values, ignoring case — Baltasar Brum, Bella Unión, Bernabé Rivera, Cainsa, Calnu, Colonia Palma, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A localidad with fewer than 20,000 inhabitants becomes the nearest one of at least 20,000 in the same departamento. Every departamento has one, so the value never leaves it, and the 19 departamentos stay.

`UY_LOCALIDAD` DATA CLEANSING

Replaces each value found in `uy-localidades-generalizadas.txt` (9,772 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Baltasar Brum	→	**Artigas**
Montevideo	→	**Montevideo**
Piriápolis – Maldonado	→	**Maldonado – Maldonado**

9.7 INE code

UY_L2_CODIGO_INE

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The five-digit code of the Instituto Nacional de Estadística: two digits for the departamento and three for the localidad.

HOW IT IS FOUND

COLUMN NAME UY_L2_CODIGO_INE – Path

85% `(cod|codigo|cd|id)_?(localidad|ciudad|lugar|ine)(_?(ine|censo|res|residencia|nac|nacimiento))?` `c[oó]digo_?(ine|localidad|geogr[aá]fico)` `codloc` `cod_?dpto_?loc`

VALUE FORMAT UY_L2_CODIGO_INE – Regex

PATTERN	STRENGTH	NOTES
`0*(?:(0[1-9]|1[0-9])\d{3})`	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The same generalization as the name: a small localidad's code becomes the code of the localidad that replaces its name. The code of a large one does not change.

`UY_CODIGO_INE` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `UY_CODIGO_INE_TABLA` DATA CLEANSING
>
> Replaces each value found in `uy-codigos-ine-generalizados.txt` (929 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
02621	→	**02020**
02020	→	**02020**

9.8 Barrio and balneario

UY_L2_BARRIO

COLUMN NAME · SECURE LOOKUP

WHAT IT IS

The barrio, balneario, zona or asentamiento of residence — the unit below the localidad, and the one that tells Pocitos from Casavalle inside Montevideo.

HOW IT IS FOUND

> COLUMN NAME UY_L2_BARRIO – Path
>
> 80% `barrio(_?(residencia|domicilio|nombre))?` `balneario` `zona(_?(residencia|domicilio))?` `urbanizaci[oó]n` `complejo(_?habitacional)?` `asentamiento` `(nom|nombre)_?` `(barrio|balneario|zona)` `neighbou?rhood`

HOW IT IS MASKED

Replaced by a common Uruguayan one, unrelated to the original.

`UY_BARRIO` SECURE LOOKUP

Replaces the value with one of the 111 values in `uy-barrios.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Pocitos	→	**Flor de Maroñas**

9.9 Postal code

UY_L2_CODIGO_POSTAL

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The five-digit postal code: the first two are the departamento and the postal zone.

HOW IT IS FOUND

> COLUMN NAME UY_L2_CODIGO_POSTAL – Path
>
> 85% `c[oó]digo_?postal` `cod_?postal` `codpostal` `zip(_?code)?` `postal_?code` `cp`

> DATA TYPE UY_L2_CODIGO_POSTAL – Type
>
> Accepts text (length 5 to 5) or number (length up to 5); any other type rules the domain out.

HOW IT IS MASKED

The first two digits stay and the others become zeros: `11300` becomes `11000`.

`UY_CODIGO_POSTAL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
11300	→	**11000**

9.10 Marital status

UY_L2_ESTADO_CIVIL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Single, married, in unión libre or concubinato — which the Ley 18.246 recognizes —, separated, divorced or widowed, in words or as a code.

HOW IT IS FOUND

COLUMN NAME UY_L2_ESTADO_CIVIL – Path

85% `estado_?civil` `est_?civil` `(cod|tipo|id)_?estado_?civil` `situaci[oó]n_?conyugal` `uni[oó]n_?(libre|concubinaria)` `concubinato` `marital_?status` `civil_?status`

VALUE FORMAT UY_L2_ESTADO_CIVIL – Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Soltero a, Casado a, Unión libre o concubinato, Separado a, Divorciado a, Viudo a, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another status from the list; a code stays a code.

`UY_ESTADO_CIVIL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_ESTADO_CIVIL_LISTA`.

`UY_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.

`UY_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.

`UY_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.

`UY_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.

`UY_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.

`UY_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

`UY_ESTADO_CIVIL_CODIGO` SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-estado-civil-codigos.txt`, chosen by a keyed hash.

`UY_ESTADO_CIVIL_LISTA` SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Unión concubinaria`	→	**`Soltero/a`**

9.11 Occupation

UY_L2_OCUPACION

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Occupation, profession or trade, in words or by the national occupation classification code. A rare occupation in a small localidad identifies on its own.

HOW IT IS FOUND

COLUMN NAME UY_L2_OCUPACION — Path

80% `ocupaci[oó]n` `profesi[oó]n` `oficio` `cno` `ciuo` `(cod|codigo)_?(ocupacion|profesion|cno|ciuo)` `puesto_?(de_?)?trabajo` `categor[ií]a_?ocupacional` `cargo_?(actual|empleado)` `occupation` `profession` `job_?title`

50% `cargo` `puesto`

HOW IT IS MASKED

Text is replaced by a common occupation; a code is mapped digit by digit.

`UY_OCUPACION_O_CODIGO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_OCUPACION`.

`UY_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`UY_OCUPACION` SECURE LOOKUP

Replaces the value with one of the 38 values in `uy-ocupaciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Gerente de operaciones	→	**Contador**
2221	→	**1980**

9.12 Employer

UY_L2_EMPLEADOR

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The name of the company or institution where the person works.

HOW IT IS FOUND

COLUMN NAME UY_L2_EMPLEADOR — Path

90% `empleador(_?(nombre|raz[oó]n_?social|rut))?` `(nombre|nom)_?(empleador|empresa_?donde_?trabaja|patrono)` `empresa_?(donde_?)?(trabaja|labora)` `lugar_?(de_?)?trabajo` `centro_?(de_?)?trabajo` `entidad_?empleadora` `employer(_?name)?` `workplace`

HOW IT IS MASKED

Replaced by a fictitious company.

`UY_EMPLEADOR` SECURE LOOKUP

Replaces the value with one of the 24 values in `uy-empleadores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Corporación Comercial Oriental S.A.	→	**Restaurante Sabor Criollo S.R.L.**

9.13 Education

UY_L2_NIVEL_EDUCATIVO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The education level attained — from none to a postgraduate degree — in the categories the census uses, in words or as a code.

HOW IT IS FOUND

COLUMN NAME UY_L2_NIVEL_EDUCATIVO — Path

80% `escolaridad` `nivel_?(educativo|de_?estudios|acad[eé]mico|alcanzado|de_?instrucci[oó]n)` `instrucci[oó]n(_?formal)?` `grado_?(de_?)?(estudio|instrucci[oó]n|escolaridad)` `m[aá]ximo_?nivel` `a[nñ]os_?(de_?)?estudio` `education(_?level)?`

VALUE FORMAT UY_L2_NIVEL_EDUCATIVO — Values

PATTERN	STRENGTH	NOTES
One of 21 known values, ignoring case — Sin instrucción, Preescolar, Primaria, Ciclo básico, Bachillerato, Enseñanza técnica UTU, …	60%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another level from the list; a code stays a code.

`UY_NIVEL_EDUCATIVO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_NIVEL_EDUCATIVO_LISTA`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_NIVEL_EDUCATIVO_CODIGO` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `uy-nivel-educativo-codigos.txt`, chosen by a keyed hash.
>
> `UY_NIVEL_EDUCATIVO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `uy-nivel-educativo.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Educación terciaria en curso	→	**Ciclo básico**

9.14 School

UY_L2_INSTITUCION_EDUCATIVA

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

The escuela, liceo, UTU school, institute or university, by name or by its number — and a numbered escuela in a small localidad is one school.

HOW IT IS FOUND

> **COLUMN NAME** UY_L2_INSTITUCION_EDUCATIVA – Path
>
> 75% `instituci[oó]n_?educativa` `centro_?(educativo|de_?estudios)` `escuela` `liceo` `colegio` `instituto` `universidad` `utu` `(nombre|nom)_?(escuela|liceo|colegio|universidad|institucion_?educativa)` `c[oó]digo_?(de_?)?(escuela|liceo|centro)` `school(_?name)?` `university`

HOW IT IS MASKED

Replaced by a fictitious school.

`UY_INSTITUCION_EDUCATIVA` SECURE LOOKUP

Replaces the value with one of the 12 values in `uy-instituciones-educativas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Universidad de la República	→	**Centro Educativo Asociado**

9.15 Dependants and children

UY_L2_PERSONAS_A_CARGO

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

Number of dependants, children, cargas familiares or household members.

HOW IT IS FOUND

> **COLUMN NAME** UY_L2_PERSONAS_A_CARGO – Path
>
> 80% `personas_?a_?cargo` `n(o|ro|um|umero)_?(de_?)?(hijos|dependientes|personas_?a_?cargo|beneficiarios)` `cant(idad)?_?(hijos|dependientes|personas_?hogar|integrantes|miembros)` `hijos` `dependientes` `integrantes_?(del_?)?hogar` `personas_?(en_?el_?)?hogar` `tama[nñ]o_?(del_?)?hogar` `number_?of_?children` `dependents`

> **DATA TYPE** UY_L2_PERSONAS_A_CARGO – Type
>
> Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Values from 0 to 5 stay; above 5 they become 5. Very large households are rare, and a rare count identifies.

`UY_CONTEO_LIMITADO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	**5**

PART 10

Sensitive data (art. 4 E and art. 4 Ñ)

Article 4 E) is short and from 2008: data that reveals racial and ethnic origin, political preferences, religious **or moral** convictions, trade union membership, and information on health or sexual life. Article 18 forbids building databases that store information which **directly or indirectly** reveals it. Article 4 Ñ), added in 2020, brought the biometric datum in, and article 18-BIS put an impact assessment in front of it. Health has a group of its own below; the rest is here, with the genetic data, the gender identity, the indigenous people and the victim status other Uruguayan statutes protect.

10.1 Racial and ethnic origin

UY_L3_ASCENDENCIA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The ascendencia étnico-racial the census asks about — afro or black, asian, white, indigenous — which article 4 E) names first among the sensitive data.

HOW IT IS FOUND

COLUMN NAME UY_L3_ASCENDENCIA – Path

95% `ascendencia(_?[eé]tnico?_?racial)?` `etnia` `origen_?([eé]tnico|racial)` `grupo_?[eé]tnico` `pertenencia_?[eé]tnica` `autoidentificaci[oó]n(_?[eé]tnica)?` `autodefinici[oó]n` `(cod|codigo|tipo|id)_?(etnia|ascendencia)` `raza` `afrodescendiente` `afro` `ind[ií]gena` `ethnicity` `race`

VALUE FORMAT UY_L3_ASCENDENCIA – Values

PATTERN	STRENGTH	NOTES
One of 18 known values, ignoring case — Afro o negra, Asiática o amarilla, Blanca, Indígena, Otra, Ninguna, …	90%	
One of 10 known values, ignoring case — s, n, sí, no, 1, 2, …	30%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag, a code is replaced by another code and any other value by a category from the list.

`UY_ASCENDENCIA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_ASCENDENCIA_LISTA` .

`UY_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt` , chosen by a keyed hash.

`UY_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt` , chosen by a keyed hash.

`UY_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt` , chosen by a keyed hash.

`UY_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt` , chosen by a keyed hash.

`UY_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt` , chosen by a keyed hash.

`UY_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

`UY_ASCENDENCIA_CODIGO` SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-ascendencia-codigos.txt`, chosen by a keyed hash.

`UY_ASCENDENCIA_LISTA` SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-ascendencia.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Afrodescendiente	→	**Asiática o amarilla**
S	→	**S**

10.2 Indigenous people

UY_L3_PUEBLO_ORIGINARIO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The pueblo originario a person claims. Uruguay treated its indigenous peoples as extinct for a century; the census brought the charrúa descendants back into the count, and there are a few thousand of them — naming the people names a very small group.

HOW IT IS FOUND

COLUMN NAME UY_L3_PUEBLO_ORIGINARIO – Path

90% `pueblo_?(ind[ií]gena|originario)` `nacionalidad_?ind[ií]gena` `pertenece_?(a_?)?` `(pueblo|comunidad)` `comunidad_?(ind[ií]gena|originaria)` `charr[uú]a` `indigenous_?people`

VALUE FORMAT UY_L3_PUEBLO_ORIGINARIO – Values

PATTERN	STRENGTH	NOTES
One of 12 known values, ignoring case — Charrúa, Guaraní, Chaná, Minuán, Otro pueblo originario, No pertenece a ningún pueblo, …	85%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another people from the list; a flag stays a flag.

`UY_PUEBLO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_PUEBLO_LISTA`.

`UY_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.

`UY_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.

`UY_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.

`UY_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.

`UY_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.

`UY_BANDERA_0_1` SECURE LOOKUP

> Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`UY_PUEBLO_LISTA` SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-pueblos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Pueblo originario	→	**Charrúa**

10.3 Nationality

UY_L3_NACIONALIDAD

COLUMN NAME · KNOWN VALUES · SECURE LOOKUP

WHAT IT IS

Nationality, country of birth or origin, and migratory status. Article 9 C) names nationality among the data a listing may hold, so the law treats it as ordinary personal data — but it sits beside the racial and ethnic origin it does call sensitive, and in Uruguay it separates the nationals from the Venezuelan and Cuban communities.

HOW IT IS FOUND

COLUMN NAME UY_L3_NACIONALIDAD — Path

85% `nacionalidad` `pa[ií]s_?(de_?)?(nacimiento|origen|nacionalidad|procedencia)` `ciudadan[ií]a(_?(legal|natural))?` `nationality` `citizenship` `country_?of_?birth` `condici[oó]n_?(de_?)?(migratoria|refugiado)` `persona_?(migrante|refugiada)`

KNOWN VALUES UY_L3_NACIONALIDAD — List

LIST	VALUES	STRENGTH	FIRST VALUES
`uy-detectar-nacionalidades.txt`	38	70%	Uruguaya, Argentina, Brasileña, Brasilena, Venezolana, Cubana

Values are split into words, and each word is looked up.

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a nationality from the list: the Uruguayan one and the largest foreign communities.

`UY_NACIONALIDAD` SECURE LOOKUP

Replaces the value with one of the 14 values in `uy-nacionalidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Panameña	→	**Italiana**

10.4 Religion

UY_L3_RELIGION

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The religion, church or congregation the person belongs to. Uruguay is the most secular country of the region — "creyente sin religión" and "ateo o agnóstico" are among the largest answers, and the umbandista faith is counted on its own — so a declared religion says a great deal here.

HOW IT IS FOUND

COLUMN NAME UY_L3_RELIGION — Path

95% `religi[oó]n` `creencia_?(religiosa|espiritual)` `convicci[oó]n(es)?_?(religiosa|espiritual)` `credo` `confesi[oó]n_?religiosa` `culto` `iglesia(_?(a_?la_?que_?pertenece|nombre))?` `denominaci[oó]n_?religiosa` `(cod|codigo|tipo)_?religion` `religion` `church`

VALUE FORMAT UY_L3_RELIGION — Values

PATTERN	STRENGTH	NOTES
One of 23 known values, ignoring case — Católica, Cristiana no católica, Evangélica, Umbandista o afroumbandista, Testigo de Jehová, Judía, …	90%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a religion from the list.

`UY_RELIGION` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_RELIGION_LISTA`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_RELIGION_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `uy-religiones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Ortodoxa	→	**Ateo o agnóstico**

10.5 Moral and philosophical convictions

UY_L3_CONVICCION_MORAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The **convicciones morales** article 4 E) names in the same breath as the religious ones, conscientious objection and belonging to a lodge. Only a handful of laws in the region list this.

HOW IT IS FOUND

COLUMN NAME UY_L3_CONVICCION_MORAL — Path

90% `convicci[oó]n(es)?_?(morales?|filos[oó]ficas?|personales?|[eé]ticas?)` `creencias?_?(morales?|filos[oó]ficas?|personales?)` `objeci[oó]n_?(de_?)?conciencia` `objetor_?(de_?)?conciencia` `masoner[ií]a` `logia` `beliefs?` `moral_?beliefs?`

HOW IT IS MASKED

The values share no vocabulary: they are suppressed to `Sin información`. Flags and codes keep their shape.

`UY_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_SUPRIMIR`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `uy-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Se niega a transfusiones`	→	**`Sin información`**

10.6 Political preferences

UY_L3_PREFERENCIA_POLITICA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The **preferencias políticas** article 4 E) names: leaning, sympathy and voting intention, from surveys and records.

HOW IT IS FOUND

COLUMN NAME UY_L3_PREFERENCIA_POLITICA — Path

95% `preferencias?_?(pol[ií]tica|partidaria|electoral)` `ideolog[ií]a(_?pol[ií]tica)?` `opini[oó]n_?pol[ií]tica` `orientaci[oó]n_?pol[ií]tica` `tendencia_?pol[ií]tica` `intenci[oó]n_?(de_?)?voto` `simpat[ií]a_?pol[ií]tica` `political_?(opinion|orientation|view|preference)` `voting_?intention`

VALUE FORMAT UY_L3_PREFERENCIA_POLITICA — Values

PATTERN	STRENGTH	NOTES
One of 16 known values, ignoring case — Izquierda, Centroizquierda, Centro, Centroderecha, Derecha, Independiente, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a position from the list — left to right, independent.

`UY_PREFERENCIA_POLITICA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_PREFERENCIA_POLITICA_LISTA`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_PREFERENCIA_POLITICA_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `uy-preferencias-politicas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Oficialista`	→	**`Centro`**

10.7 Party membership

UY_L3_AFILIACION_PARTIDARIA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The party, lema or sublema the person belongs to, from the register of the Corte Electoral. Uruguay votes its party internals, so membership is a recorded fact rather than an opinion.

HOW IT IS FOUND

COLUMN NAME UY_L3_AFILIACION_PARTIDARIA — Path

95% `partido(_?pol[ií]tico)?(_?(afiliaci[oó]n|nombre))?` `lema(_?partidario)?` `sublema` `agrupaci[oó]n_?pol[ií]tica` `afiliaci[oó]n_?(pol[ií]tica|partidaria|partido)` `militancia(_?pol[ií]tica)?` `militante` `(cod|codigo|nombre|nom)_?partido` `hoja_?de_?votaci[oó]n` `political_?party` `party_?membership`

VALUE FORMAT UY_L3_AFILIACION_PARTIDARIA — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Frente Amplio, Partido Nacional, Partido Colorado, Cabildo Abierto, Partido Independiente, Identidad Soberana, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another party from the list; a flag stays a flag.

`UY_PARTIDO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_PARTIDO_LISTA`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_PARTIDO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `uy-partidos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Partido Socialista`	→	**`Partido Independiente`**
`S`	→	**`S`**

10.8 Trade union membership

UY_L3_AFILIACION_SINDICAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The union, the membership, the dues deducted on the payroll and the consejo de salarios. Article 4 E) names it, and article 18 lets a union keep the data of its own members — which is exactly the database this domain protects.

HOW IT IS FOUND

COLUMN NAME UY_L3_AFILIACION_SINDICAL — Path

95% `sindicato(_?(nombre|afiliado|afiliaci[oó]n|codigo))?` `sindicalizado` `afiliado_?sindicato` `afiliaci[oó]n_?sindical` `cuota_?sindical` `descuento_?sindical` `aporte_?sindical` `asociaci[oó]n_?(sindical|de_?funcionarios)` `gremio` `consejo_?de_?salarios` `fuero_?sindical` `dirigente_?sindical` `trade_?union` `union_?member(ship)?`

VALUE FORMAT UY_L3_AFILIACION_SINDICAL — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — PIT-CNT, PIT CNT, FUECYS, SUNCA, AEBU, FFOSE, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`UY_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_SUPRIMIR`.

`UY_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.

`UY_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.

`UY_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.

`UY_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.

`UY_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.

`UY_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`UY_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `uy-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
SUNCA	→	**`Sin información`**
S	→	**`S`**

10.9 Biometric data

UY_L3_BIOMETRICO

COLUMN NAME **DATA TYPE** **REGEX DECOMPOSE**

WHAT IT IS

Fingerprint templates — the cédula's fingerprint is the country's identification pattern —, face, iris, voice and digitized signature. Article 4 Ñ), added by Ley 19.924 in 2020, defines the biometric datum, and article 18-BIS allows processing it only after an impact assessment.

HOW IT IS FOUND

COLUMN NAME UY_L3_BIOMETRICO — Path

90% `biometr[ií]a[a-z_]*` `biom[eé]trico[a-z_]*` `huella(_?(dactilar|digital))?(_?(template|plantilla|imagen|hash))?` `huellas` `dactilar` `dactilosc[oó]pic[oa]` `template_?(facial|huella|biometrico)` `plantilla_?(facial|biom[eé]trica)` `rostro_?(hash|template)` `reconocimiento_?(facial|de_?voz)` `firma_?(biom[eé]trica|digitalizada|electr[oó]nica)` `iris` `voz_?(biom[eé]trica|template)` `fingerprints?` `face_?(template|hash|encoding)` `biometric[a-z_]*`

DATA TYPE UY_L3_BIOMETRICO — Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character becomes `X`. A masked template authenticates nobody.

`UY_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	XXXXXXXXXXXX

10.10 Genetic data

UY_L3_GENETICO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Results of genetic and DNA tests, paternity tests, genetic profiles, mutations, karyotype and newborn screening. The law does not name them, but they are health data by any reading of article 4 E).

HOW IT IS FOUND

COLUMN NAME UY_L3_GENETICO — Path

90% `adn` `dna` `gen[eé]tic[oa]s?` `datos?_?gen[eé]ticos?` `genoma` `genotip[a-z_]*` `prueba_?(gen[eé]tica|de_?adn|de_?paternidad|de_?filiaci[oó]n)` `perfil_?gen[eé]tico` `mutaci[oó]n` `brca[12]?` `cariotipo` `pesquisa_?neonatal` `genetic[a-z_]*`

VALUE FORMAT UY_L3_GENETICO — Regex

PATTERN	STRENGTH	NOTES
`[ACGTUN]{24,}`	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Every character becomes `X`.

`UY_REDACTAR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
BRCA1 positivo	→	XXXXXXXXXXXXXX

10.11 Sexual orientation

UY_L3_ORIENTACION_SEXUAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Self-declared sexual orientation or preference. It belongs to the *vida sexual* article 4 E) protects.

HOW IT IS FOUND

COLUMN NAME UY_L3_ORIENTACION_SEXUAL — Path

95% `orientaci[oó]n_?sexual` `preferencias?_?sexuales?` `(cod|codigo|tipo)_?orientacion_?sexual` `sexual_?orientation`

VALUE FORMAT UY_L3_ORIENTACION_SEXUAL — Values

PATTERN	STRENGTH	NOTES
One of 13 known values, ignoring case — Heterosexual, Gay, Lesbiana, Bisexual, Pansexual, Asexual, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a category from the list.

`UY_ORIENTACION_SEXUAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_ORIENTACION_SEXUAL_LISTA`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_ORIENTACION_SEXUAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `uy-orientaciones-sexuales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Homosexual	→	Pansexual

10.12 Sexual life

UY_L3_VIDA_SEXUAL

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Sexual activity and behaviour, number of partners, age at first intercourse — the *vida sexual* named word for word in article 4 E).

HOW IT IS FOUND

> COLUMN NAME UY_L3_VIDA_SEXUAL – Path
>
> 90% `vida_?sexual` `actividad_?sexual` `conducta_?sexual` `pr[aá]cticas?_?sexuales?` `parejas?_?sexuales?` `n(o|ro|um|umero)_?parejas` `sexualmente_?activ[oa]` `inicio_?(de_?)?(la_?)?vida_?sexual` `relaciones_?sexuales` `sex(ual)?_?life` `sexual_?(activity|behavio(u)?r|partners)`

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`UY_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_SUPRIMIR`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `uy-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Activa	→	**Sin información**

10.13 Gender identity

UY_L3_IDENTIDAD_GENERO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Self-declared gender identity and the social name. The Ley 19.684 integral para personas trans created a register and a hiring quota, so this is a real column in Uruguayan systems — and one that identifies a very small group.

HOW IT IS FOUND

COLUMN NAME UY_L3_IDENTIDAD_GENERO — Path

95% `identidad_?(de_?)?g[eé]nero` `(cod|codigo|tipo)_?identidad_?genero` `g[eé]nero_?(autopercibido|identitario)` `expresi[oó]n_?de_?g[eé]nero` `transg[eé]nero` `persona_?trans` `registro_?(de_?personas_?)?trans` `nombre_?social` `pronombres?` `gender_?identity`

VALUE FORMAT UY_L3_IDENTIDAD_GENERO — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Mujer cisgénero, Hombre cisgénero, Mujer trans, Hombre trans, Persona no binaria, Otra, …	70%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a category from the list.

`UY_IDENTIDAD_GENERO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_IDENTIDAD_GENERO_LISTA`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_IDENTIDAD_GENERO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 7 values in `uy-identidades-genero.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Transgénero	→	**Hombre trans**

10.14 Victims of violence

UY_L3_VICTIMA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Being a victim of gender, domestic or sexual violence, of trafficking or of enforced disappearance, the type of violence and the protective measures. The Ley 19.580 protects the identity of the victim.

HOW IT IS FOUND

COLUMN NAME UY_L3_VICTIMA – Path

90% `v[ií]ctima(_?(de_?)?(violencia(_?(de_?g[eé]nero|dom[eé]stica|intrafamiliar|sexual|psicol[oó]gica|econ[oó]mica))?|delito|trata|abuso|desaparici[oó]n))?` `violencia_?(de_?)?g[eé]nero` `violencia_?(dom[eé]stica|intrafamiliar|sexual|psicol[oó]gica)` `tipo_?(de_?)?violencia` `medida_?(de_?)?(protecci[oó]n|cautelar)` `tobillera_?electr[oó]nica` `trata_?(de_?)?personas` `denunciante_?violencia`

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`UY_CATEGORIA_SUPRIMIDA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_SUPRIMIR`.

> `UY_BANDERA` **REGEX DECOMPOSE**
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_SUPRIMIR` **SECURE LOOKUP**
>
> Replaces the value with one of the 1 values in `uy-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Violencia doméstica	→	**Sin información**
S	→	**S**

PART 11

Health data

Health data is sensitive by article 4 E) and has a regime of its own in article 19, which lets sanitary establishments and health professionals process the data of their patients "respetando los principios del secreto profesional". Article 17 C) is the clause this group is written for: health data may be communicated for sanitary, emergency or epidemiological reasons while "preservando la identidad de los titulares de los datos mediante **mecanismos de disociación adecuados**".

11.1 Health identifiers

UY_SALUD_IDENTIFICADOR

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Clinical record, episode, admission, care, appointment and prescription numbers, and the affiliate or socio number of ASSE or a mutualista.

HOW IT IS FOUND

COLUMN NAME — UY_SALUD_IDENTIFICADOR — Path

85%

```
n(o|ro|um|umero)_?(historia(_?cl[ií]nica)?|hc|hce|ficha(_?cl[ií]nica)?|episodio|ingreso|atenci[oó]n|consulta|cita|receta)
historia_?cl[ií]nica(_?electr[oó]nica)?
hc_?(n(o|ro|um|umero))?
n(o|ro|um|umero)_?(afiliado|socio|carn[eé]_?asistencia)
c[oó]digo_?(paciente|historia|atenci[oó]n)
id_?paciente
```

55%

```
expediente
atenci[oó]n
ingreso
consulta
episodio
```

HOW IT IS MASKED

Character by character, keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
HC-2024-00123	→	**TW-3389-01317**

11.2 Health coverage

UY_SALUD_COBERTURA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

ASSE, a mutualista (IAMC), a private insurer, military or police health, or none, by name or code. Which one a person has says a great deal about them in a country where FONASA routes everyone somewhere.

HOW IT IS FOUND

COLUMN NAME — UY_SALUD_COBERTURA — Path

85%

```
cobertura(_?(m[eé]dica|de_?salud|asistencial))?
seguro_?(m[eé]dico|salud)
prestador(_?(de_?)?salud)?
r[eé]gimen(_?(de_?)?salud)?
tipo_?(de_?)?(seguro|cobertura)
asse
mutualista
iamc
fonasa
sanidad_?(militar|policial)
emergencia_?m[oó]vil
aseguradora_?(m[eé]dica|salud)
plan_?(m[eé]dico|de_?salud)
```

VALUE FORMAT UY_SALUD_COBERTURA — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — ASSE, Mutualista IAMC, Seguro privado integral, Sanidad Militar, Sanidad Policial, Hospital de Clínicas, …	80%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A name is replaced by another cover from the list; a code is mapped digit by digit; a flag stays a flag.

`UY_COBERTURA_SALUD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_COBERTURA` .

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt` , chosen by a keyed hash.
>
> `UY_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `UY_COBERTURA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `uy-cobertura-salud.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
ASSE	→	**Mutualista (IAMC)**
12345	→	**31564**

11.3 Diagnosis and ICD-10

UY_SALUD_DIAGNOSTICO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Diagnoses in words or by ICD-10 code, with a dot (`F33.1`) or without (`F331`); causes of death, of sick leave and of admission; allergies and comorbidities.

HOW IT IS FOUND

COLUMN NAME UY_SALUD_DIAGNOSTICO — Path

85% `diagn[oó]stico[a-z_]*` `dx(_?(principal|secundario|ingreso|egreso)[0-9]?)?` `cie_?10` `cie(_?(10|11|principal))?` `(cod|codigo)_?(diagnostico|dx|cie)` `impresi[oó]n_?diagn[oó]stica` `enfermedad(es)?[a-z_]*` `patolog[ií]a` `comorbilidad(es)?` `antecedentes?_?(m[eé]dicos|patol[oó]gicos|cl[ií]nicos|personales)` `causa_?(de_?)?(muerte|defunci[oó]n|incapacidad|internaci[oó]n|consulta)` `motivo_?(de_?)?(consulta|certificaci[oó]n|internaci[oó]n)` `alergias?` `diagnos(is|es)` `icd_?(10|11)?`

VALUE FORMAT UY_SALUD_DIAGNOSTICO — Regex

PATTERN	STRENGTH	NOTES
`[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d|X)?`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code becomes another common code in the same format, and text a common diagnosis: an HIV or mental disorder diagnosis does not survive as such.

`UY_DIAGNOSTICO` **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `UY_DIAGNOSTICO_TEXTO`.

`UY_CIE10_DECIMAL` **SECURE LOOKUP**

Replaces the value with one of the 33 values in `uy-cie10-decimal.txt`, chosen by a keyed hash.

`UY_CIE10` **SECURE LOOKUP**

Replaces the value with one of the 37 values in `uy-cie10.txt`, chosen by a keyed hash.

`UY_BANDERA` **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_BANDERA_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.

`UY_BANDERA_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.

`UY_BANDERA_YES_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.

`UY_BANDERA_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.

`UY_BANDERA_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.

`UY_BANDERA_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

`UY_DIAGNOSTICO_TEXTO` **SECURE LOOKUP**

Replaces the value with one of the 30 values in `uy-diagnosticos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F33.1	→	**K21.9**
B24X	→	**R51**

11.4 Procedures

UY_SALUD_PROCEDIMIENTO

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Procedures, tests and surgeries, in words or by code. A viral load or a pregnancy test reveals the diagnosis.

HOW IT IS FOUND

COLUMN NAME — UY_SALUD_PROCEDIMIENTO — Path

85% `procedimiento(_?(m[eé]dico|quir[uú]rgico|realizado|autorizado))?` `(cod|codigo)_?(procedimiento|prestaci[oó]n|servicio_?salud)` `prestaci[oó]n_?(m[eé]dica|de_?salud)` `examen_?(ordenado|realizado)` `cirug[ií]a(_?realizada)?` `intervenci[oó]n_?quir[uú]rgica` `t[eé]cnica_?(diagn[oó]stica|quir[uú]rgica)` `medical_?procedure`

HOW IT IS MASKED

A code is mapped digit by digit; text is replaced by a common procedure.

`UY_PROCEDIMIENTO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_PROCEDIMIENTO_TEXTO`.

> `UY_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `UY_PROCEDIMIENTO_TEXTO` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `uy-procedimientos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
901234	→	**928120**

11.5 Medicines

UY_SALUD_MEDICAMENTO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Prescribed or dispensed medicines, by name or active ingredient. An antiretroviral, an antipsychotic or a contraceptive says what the diagnosis column was masked for.

HOW IT IS FOUND

COLUMN NAME — UY_SALUD_MEDICAMENTO — Path

85% `medicamentos?(_?(recetado|prescrito|entregado|despachado|nombre|uso))?` `f[aá]rmacos?` `principio_?activo` `denominaci[oó]n_?com[uú]n_?internacional` `dci` `receta(_?m[eé]dica)?` `prescripci[oó]n(_?medicamento)?` `posolog[ií]a` `tratamiento_?farmacol[oó]gico` `(cod|codigo)_?medicamento` `formulario_?terap[eé]utico` `medications?` `drugs?_?prescribed`

VALUE FORMAT — UY_SALUD_MEDICAMENTO — Values

PATTERN	STRENGTH	NOTES
One of 46 known values, ignoring case — Paracetamol, Ibuprofeno, Diclofenac, Metformina, Glibenclamida, Losartán, …	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a common medicine from the list; a flag stays a flag.

`UY_MEDICAMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_MEDICAMENTO_LISTA` .

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt` , chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt` , chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt` , chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt` , chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt` , chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt` , chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_MEDICAMENTO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 22 values in `uy-medicamentos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Sertralina 50 mg	→	**Complejo B**

11.6 Clinical text

UY_SALUD_TEXTO_CLINICO

COLUMN NAME | DATA TYPE | FREE TEXT REDACTION

WHAT IT IS

History, present illness, progress notes, physical examination, treatment plan, discharge summaries and nursing notes.

HOW IT IS FOUND

> COLUMN NAME UY_SALUD_TEXTO_CLINICO — Path
>
> 85% `anamnesis` `evoluci[oó]n(_?(m[eé]dica|cl[ií]nica|enfermer[ií]a))?` `enfermedad_?actual` `examen_?f[ií]sico` `plan_?(de_?)?(manejo|tratamiento)` `indicaciones_?m[eé]dicas` `conducta(_?m[eé]dica)?` `epicrisis` `resumen_?(de_?)?(alta|egreso|atenci[oó]n)` `nota_?(m[eé]dica|de_?enfermer[ií]a|cl[ií]nica)` `notas?_?(m[eé]dicas|cl[ií]nicas)` `triaje(_?texto)?` `informe_?(patolog[ií]a|radiolog[ií]a|m[eé]dico)` `clinical_?notes?` `discharge_?summary`

> DATA TYPE UY_SALUD_TEXTO_CLINICO — Type
>
> Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

The same Free Text Redaction as free text: documents, contacts and names from the list are redacted. The clinical content stays, because that is what makes the copy useful.

`UY_TEXTO_LIBRE` FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATO]`, and the 1,494 terms of `uy-texto-nombres.txt` with `[NOMBRE]`.

EXAMPLES

VALUE		MASKED
`Paciente Rodríguez, CI 1.234.567-2, consulta por cefalea.`	→	**`Paciente [NOMBRE], CI [DATO], consulta por cefalea.`**

11.7 Test results

UY_SALUD_RESULTADO_EXAMEN

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Laboratory and test results — glicemia, pregnancy, toxicology, blood alcohol —, also as numeric values.

HOW IT IS FOUND

COLUMN NAME UY_SALUD_RESULTADO_EXAMEN – Path

80% `resultado_?(del_?)?` `(examen|prueba|an[aá]lisis|laboratorio|pcr|serolog[ií]a|biopsia|glicemia|citolog[ií]a|papanicolaou)` `(examen|prueba|an[aá]lisis)_?(resultado|laboratorio)` `glicemia` `hemoglobina(_?glicosilada)?` `hba1c` `colesterol` `imc` `presi[oó]n_?arterial` `test_?(de_?)?embarazo` `espirometr[ií]a` `alcoholemia` `lab_?results?` `test_?results?`

50% `resultado` `prueba` `analisis`

HOW IT IS MASKED

Character by character, keeping the format: a number stays a number.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`Reactivo`	→	**`Quilqaju`**

11.8 HIV and sexually transmitted infections

UY_SALUD_VIH

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Serological status, viral load and antiretroviral treatment, hepatitis, tuberculosis and sexually transmitted infections. The Ley 18.335 de derechos del paciente and medical secrecy — article 302 of the Penal Code, to which article 11 of the law refers — bind the record.

HOW IT IS FOUND

COLUMN NAME UY_SALUD_VIH — Path

90% `vih(_?(estado|resultado|prueba|diagn[oó]stico|positivo))?` `hiv` `sida` `aids` `serolog[ií]a_?(vih|hiv)` `estado_?serol[oó]gico` `carga_?viral` `cd4` `tarv` `antirretroviral(es)?` `its` `ets` `infecci[oó]n(es)?_?(de_?)?transmisi[oó]n_?sexual` `s[ií]filis` `hepatitis_?[bc]` `tuberculosis` `tbc`

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información`.

`UY_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_SUPRIMIR`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `uy-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Reactivo	→	**Sin información**
S	→	**S**

11.9 Blood group and Rh

UY_SALUD_GRUPO_SANGUINEO

COLUMN NAME VALUE FORMAT SECURE LOOKUP

WHAT IT IS

Blood group and Rh factor.

HOW IT IS FOUND

COLUMN NAME UY_SALUD_GRUPO_SANGUINEO — Path

90% `grupo_?sangu[ií]neo` `tipo_?(de_?)?sangre` `rh` `factor_?rh` `gs_?rh` `grupo_?rh` `abo(_?rh)?` `blood_?(type|group)`

VALUE FORMAT UY_SALUD_GRUPO_SANGUINEO — Values

PATTERN	STRENGTH	NOTES
One of 18 known values, ignoring case — A, A-, B, B-, AB, AB-, …	90%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another group from the list.

`dlpx-core:BloodType SL` SECURE LOOKUP

Comes with the Masking Engine and is used as it ships. Replaces the blood group with one of the eight groups, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
0+	→	**0−**

11.10 Disability

UY_SALUD_DISCAPACIDAD

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Disability status, type and degree, the certificate and the BPS disability allowance, under the Ley 18.651.

HOW IT IS FOUND

COLUMN NAME UY_SALUD_DISCAPACIDAD — Path

90% `discapacidad[a-z_]*` `(tipo|cod|codigo|categoria|porcentaje|grado)_?discapacidad` `persona_?con_?discapacidad` `pcd` `certificado_?(de_?)?discapacidad` `bpc_?discapacidad` `pronadis` `condici[oó]n_?(de_?)?discapacidad` `necesidades_?(educativas_?)?especiales` `movilidad_?reducida` `disabilit(y|ies)`

VALUE FORMAT UY_SALUD_DISCAPACIDAD — Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Física o motriz, Auditiva, Visual, Intelectual, Psíquica o mental, Múltiple, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a category from the list.

`UY_DISCAPACIDAD` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_DISCAPACIDAD_LISTA`.

`UY_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.

`UY_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.

`UY_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.

`UY_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.

`UY_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.

`UY_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`UY_DISCAPACIDAD_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `uy-discapacidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno del espectro autista	→	**Psíquica o mental**

11.11 Carné de salud and occupational health

UY_SALUD_OCUPACIONAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The **carné de salud básico** is compulsory for every worker in Uruguay, which puts a health certificate in the personnel table of almost every employer. Also occupational exams, work accidents and occupational diseases, the BSE claim, sick leave and absenteeism.

HOW IT IS FOUND

COLUMN NAME UY_SALUD_OCUPACIONAL – Path

85% `carn[eé]_?(de_?)?salud(_?(basico|b[aá]sico|laboral|vencimiento))?` `aptitud_?(laboral|m[eé]dica)` `certificado_?(de_?)?aptitud` `examen_?(m[eé]dico_?)?(ocupacional|preocupacional|de_?ingreso|de_?egreso|peri[oó]dico)` `accidente_?(de_?)?trabajo` `enfermedad_?(laboral|profesional|ocupacional)` `bse_?(siniestro|accidente)` `incapacidad(_?(m[eé]dica|laboral|d[ií]as))?` `certificaci[oó]n_?m[eé]dica` `d[ií]as_?(de_?)?(incapacidad|certificaci[oó]n)` `licencia_?(m[eé]dica|por_?enfermedad|maternal)` `ausentismo`

VALUE FORMAT UY_SALUD_OCUPACIONAL – Values

PATTERN	STRENGTH	NOTES
One of 5 known values, ignoring case — apto, no apto, apto con restricciones, pendiente, apto con recomendaciones	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An opinion is replaced by another from the list — fit, unfit —; a flag stays a flag; the diagnosis falls under its own domain.

`UY_APTITUD_LABORAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_APTITUD_LABORAL_LISTA`.

`UY_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.

`UY_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.

`UY_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.

`UY_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.

`UY_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.

`UY_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`UY_APTITUD_LABORAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 4 values in `uy-aptitud-laboral.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
No apto temporalmente	→	**Pendiente**

11.12 Sexual and reproductive health

UY_SALUD_REPRODUCTIVA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy, last menstrual period, prenatal care, childbirth, the interruption of pregnancy the Ley 18.987 regulates, family planning, fertility.

HOW IT IS FOUND

COLUMN NAME UY_SALUD_REPRODUCTIVA — Path

90% `embarazo` `embarazada` `gestante` `gestaci[oó]n` `edad_?gestacional` `semanas_?(de_?)?gestaci[oó]n` `fum` `fecha_?[uú]ltima_?(regla|menstruaci[oó]n)` `control_?(obst[eé]trico|prenatal)` `prenatal` `parto(_?tipo)?` `ces[aá]rea` `interrupci[oó]n_?(del_?)?embarazo` `aborto` `m[eé]todo_?(de_?)?anticoncepci[oó]n` `planificaci[oó]n_?familiar` `anticoncepci[oó]n` `anticonceptivo` `fertilidad` `salud_?(sexual|reproductiva)` `pregnan(t|cy)` `contracepti(on|ve)`

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Sin información`.

`UY_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_SUPRIMIR`.

`UY_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.

`UY_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.

`UY_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.

`UY_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.

`UY_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.

`UY_BANDERA_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`UY_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `uy-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
12 semanas de gestación	→	**Sin información**
S	→	**S**

11.13 Mental health

UY_SALUD_MENTAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Mental disorders, psychiatric or psychological care, intentos de autoeliminación and substance use. Article 19 covers the physical **and mental** health of the patient in so many words.

HOW IT IS FOUND

COLUMN NAME UY_SALUD_MENTAL — Path

90% `salud_?mental` `trastorno[a-z_]*` `psiqui[aá]tri[a-z_]*` `psicol[oó]gi[a-z_]*` `depresi[oó]n` `ansiedad` `suicid[a-z_]*` `intento_?(de_?)?autoeliminaci[oó]n` `iae` `intento_?(de_?)?suicidio` `autolesi[oó]n` `consumo_?(de_?)?(sustancias|alcohol|drogas)` `adicci[oó]n(es)?` `alcoholismo` `tabaquismo` `mental_?health`

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Sin información`.

`UY_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_SUPRIMIR`.

`UY_BANDERA` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_BANDERA_SI_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.

`UY_BANDERA_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.

`UY_BANDERA_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.

`UY_BANDERA_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.

`UY_BANDERA_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.

`UY_BANDERA_0_1` SECURE LOOKUP

> Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

`UY_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`UY_SUPRIMIR` **SECURE LOOKUP**

Replaces the value with one of the 1 values in `uy-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno bipolar	→	**Sin información**

PART 12

Commercial and credit data (art. 22)

Article 22 authorizes the processing of data on patrimonial or credit solvency from public sources or from the creditor — and then does something only Uruguay does: it puts a clock on it. The data on a natural person's commercial obligation may be registered for **five years**, renewable once; a settled obligation stays five more, not renewable. Whoever copies such a database into a test environment copies the clock with it, and the rest of the group — debt, income, assets, pasividades, social programmes, the Índice de Carencias Críticas — identifies just as well.

12.1 Credit history

UY_FIN_HISTORIAL_CREDITICIO

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The Clearing de Informes report, the score, days in arrears and the debtor category of the Banco Central — 1C to 5. Article 22 authorizes the processing but caps it: five years for a natural person's commercial obligation, renewable once, and five more for a settled one.

HOW IT IS FOUND

COLUMN NAME UY_FIN_HISTORIAL_CREDITICIO – Path

90% `historial_?(crediticio|de_?cr[eé]dito)` `clearing(_?(de_?)?informes)?` `central_?(de_?)?riesgos?` `bur[oó]_?(de_?)?cr[eé]dito` `equifax` `score(_?(crediticio|interno))?` `puntaje_?(de_?)?cr[eé]dito` `calificaci[oó]n_?(de_?)?(riesgo|cr[eé]dito|cartera|deudor)` `categor[ií]a_?(bcu|de_?riesgo)` `d[ií]as_?(de_?)?(mora|atraso)` `estado_?(de_?)?(cr[eé]dito|cartera|obligaci[oó]n)` `morosidad` `moroso` `deudor_?moroso` `gesti[oó]n_?(de_?)?cobranza` `credit_?score` `credit_?rating`

HOW IT IS MASKED

A score gets other digits of the same length; a flag stays a flag; a category is replaced by another from the list.

`UY_HISTORIAL_CREDITICIO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_ESTADO_CREDITO`.

> `UY_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP

> Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

`UY_ESTADO_CREDITO` SECURE LOOKUP

Replaces the value with one of the 13 values in `uy-estados-credito.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Informado en el Clearing de Informes	→	**En gestión de cobranza**
745	→	**471**

12.2 Debt

UY_FIN_DEUDA

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Credit and portfolio balances, amounts in arrears, instalments, amounts granted and limits.

HOW IT IS FOUND

> COLUMN NAME UY_FIN_DEUDA – Path
>
> 85% `saldo_?(deuda|cr[eé]dito|capital|obligaci[oó]n|cartera|en_?mora|adeudado)` `monto_?(de_?la_?)?(deuda|cuota|obligaci[oó]n|cr[eé]dito|pr[eé]stamo|mora|otorgado)` `deuda(_?total)?` `l[ií]mite_?(de_?)?(cr[eé]dito|tarjeta)` `l[ií]nea_?(de_?)?cr[eé]dito` `cuota_?mensual` `loan_?(amount|balance)` `outstanding_?balance` `debt`

> DATA TYPE UY_FIN_DEUDA – Type
>
> Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
184000	→	**781793**

12.3 Income and pay

UY_FIN_INGRESOS

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Sueldo nominal and líquido, monthly or household income, fees and rents. The national minimum wage was some 23,600 pesos a month in 2025.

HOW IT IS FOUND

COLUMN NAME UY_FIN_INGRESOS – Path

85% `sueldo(_?(nominal|l[ií]quido|mensual|bruto|neto|b[aá]sico))?` `salario(_?(nominal|l[ií]quido|mensual|bruto|neto|b[aá]sico|m[ií]nimo))?` `remuneraci[oó]n(_?(nominal|mensual))?` `ingresos?(_?(mensuales?|totales?|familiares?|declarados?|netos?))?` `haberes` `honorarios` `partida(_?salarial)?` `renta(_?(bruta|neta|mensual|anual))?` `ingreso_?(base|familiar|per_?capita)` `salary` `income` `wages?`

DATA TYPE UY_FIN_INGRESOS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
65000	→	**56713**

12.4 Assets

UY_FIN_PATRIMONIO

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Net worth, assets, tasaciones and the aforo catastral, account, CTS and fund balances, term deposits and the sworn declaration of assets.

HOW IT IS FOUND

COLUMN NAME UY_FIN_PATRIMONIO – Path

85% `patrimonio(_?(neto|l[ií]quido|fiscal))?` `activos?_?(totales?)?` `valor_?(del_?)?(inmueble|padr[oó]n|veh[ií]culo|bienes|tasaci[oó]n|aforo|comercial)` `tasaci[oó]n` `aforo(_?catastral)?` `valor_?real(_?catastral)?` `saldo_?(cuenta|caja_?de_?ahorro|dep[oó]sito|inversi[oó]n|fondo)` `dep[oó]sito_?a_?plazo` `inversiones` `declaraci[oó]n_?jurada_?(de_?)?(bienes|patrimonio)` `net_?worth` `account_?balance`

DATA TYPE UY_FIN_PATRIMONIO – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
3400000	→	**5060257**

12.5 Pasividad and benefits

UY_FIN_PENSION

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

The amount of the pasividad, the pension or the benefit, and child support. One in four Uruguayans draws one.

HOW IT IS FOUND

COLUMN NAME UY_FIN_PENSION – Path

90% `pasividad` `jubilaci[oó]n(_?(monto|mensual|valor))?` `pensi[oó]n(_?(monto|mensual|valor|alimenticia|por_?invalidez|a_?la_?vejez))?` `monto_?(pasividad|jubilaci[oó]n|pensi[oó]n|beneficio|subsidio)` `valor_?(pasividad|pensi[oó]n|subsidio|beneficio)` `haber_?(jubilatorio|pensionario)` `pension_?amount`

DATA TYPE UY_FIN_PENSION – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with the Masking Engine: each digit becomes another, and the amount keeps its number of digits, its sign and its decimal places — the same order of magnitude, with no link to the real value.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with the Masking Engine and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
32000	→	**11585**

12.6 Social programmes

UY_FIN_PROGRAMA_SOCIAL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The Tarjeta Uruguay Social, the Asignaciones Familiares of the Plan de Equidad, the Asistencia a la Vejez, Uruguay Trabaja and the Sistema Nacional de Cuidados, by name or as a flag. Being in one says the household is poor.

HOW IT IS FOUND

COLUMN NAME UY_FIN_PROGRAMA_SOCIAL – Path

90% `programa_?social` `beneficiario_?(programa|subsidio|prestaci[oó]n|tarjeta)` `tarjeta_?uruguay_?social` `tus` `asignaci[oó]n(es)?_?familiar(es)?` `afam(_?pe)?` `plan_?(de_?)?equidad` `asistencia_?(a_?la_?)?vejez` `uruguay_?trabaja` `j[oó]venes_?en_?red` `mides` `canasta(_?(de_?)?servicios)?` `transferencia_?monetaria` `ayuda_?(social|estatal)` `social_?programme`

VALUE FORMAT UY_FIN_PROGRAMA_SOCIAL — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Tarjeta Uruguay Social, Asignaciones Familiares Plan de Equidad, Asistencia a la Vejez, Uruguay Trabaja, Jóvenes en Red, Canasta de servicios, …	80%	
One of 10 known values, ignoring case — s, n, sí, no, 1, 2, …	30%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a programme from the list.

`UY_PROGRAMA_SOCIAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_PROGRAMA_SOCIAL_LISTA`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (7 groups), keeping length and format.
>
> `UY_PROGRAMA_SOCIAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `uy-programas-sociales.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Plan de emergencia`	→	**`Tarjeta Uruguay Social`**

12.7 Índice de Carencias Críticas

UY_FIN_NIVEL_SOCIOECONOMICO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The score the MIDES Índice de Carencias Críticas gives every household, which decides who gets a transfer, and the socioeconomic level or quintile.

HOW IT IS FOUND

COLUMN NAME UY_FIN_NIVEL_SOCIOECONOMICO — Path

90% `[ií]ndice_?(de_?)?carencias?_?cr[ií]ticas?` `icc` `puntaje_?(mides|icc)` `nivel_?socioecon[oó]mico` `nse` `condici[oó]n_?(de_?)?pobreza` `pobreza` `indigencia` `quintil(_?(de_?)?(ingreso|riqueza))?` `decil` `estrato_?socioecon[oó]mico`

VALUE FORMAT UY_FIN_NIVEL_SOCIOECONOMICO — Values

PATTERN	STRENGTH	NOTES
One of 18 known values, ignoring case — Quintil 1, Quintil 2, Quintil 3, Quintil 4, Quintil 5, Bajo la línea de pobreza, …	60%	

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag, a code is replaced by another code and any other value by a class from the list.

`UY_NIVEL_SOCIOECONOMICO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_NIVEL_SOCIOECONOMICO_LISTA`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_NIVEL_SOCIOECONOMICO_CODIGO` SECURE LOOKUP
>
> Replaces the value with one of the 5 values in `uy-nivel-socioeconomico-codigos.txt`, chosen by a keyed hash.
>
> `UY_NIVEL_SOCIOECONOMICO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `uy-nivel-socioeconomico.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Bajo la línea de pobreza	→	**Quintil 3**
2	→	**4**

12.8 Housing tenure

UY_FIN_VIVIENDA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Housing tenure in the categories the census uses: owner of the dwelling and the land, owner of the dwelling only, tenant, occupant by employment, free occupant, occupant without permission.

HOW IT IS FOUND

COLUMN NAME UY_FIN_VIVIENDA — Path

90% `tenencia_?(de_?)?(la_?)?vivienda` `tipo_?(de_?)?tenencia` `vivienda_?(propia|alquilada|tipo_?tenencia)` `condici[oó]n_?(de_?)?(la_?)?vivienda` `ocupaci[oó]n_?vivienda` `r[eé]gimen_?(de_?)?tenencia` `housing_?tenure`

VALUE FORMAT UY_FIN_VIVIENDA — Values

PATTERN	STRENGTH	NOTES
One of 14 known values, ignoring case — Propietario de la vivienda y el terreno, Propietario de la vivienda y no del terreno, Inquilino o arrendatario, Ocupante en relación de dependencia, Ocupante gratuito, Ocupante sin permiso, …	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another tenure from the list.

`UY_TENENCIA_VIVIENDA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_TENENCIA_VIVIENDA_LISTA` .

`UY_BANDERA` **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`UY_BANDERA_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt` , chosen by a keyed hash.

`UY_BANDERA_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt` , chosen by a keyed hash.

`UY_BANDERA_YES_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt` , chosen by a keyed hash.

`UY_BANDERA_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt` , chosen by a keyed hash.

`UY_BANDERA_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt` , chosen by a keyed hash.

`UY_BANDERA_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `uy-bandera-0-1.txt` , chosen by a keyed hash.

`UY_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`UY_TENENCIA_VIVIENDA_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 6 values in `uy-tenencia-vivienda.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Ocupación de hecho	→	**Ocupante gratuito**

PART 13

Offences (art. 18)

The final paragraph of article 18 puts the data on the commission of **criminal, civil or administrative** offences under a regime of its own: it "sólo puede ser objeto de tratamiento por parte de las autoridades públicas competentes". A private company that copies such a column into a test environment is processing data it may not process at all — which is why this group exists, and why article 6 b) of Decree 64/020 makes a permanent treatment of it a trigger for an impact assessment.

13.1 Offences and records

UY_PENAL_ANTECEDENTES

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

The certificate of judicial records, the type of offence, the procedural situation, the boleta de captura, being deprived of liberty and the INR record. The final paragraph of article 18 reserves the data on **criminal, civil or administrative** offences to the competent public authorities.

HOW IT IS FOUND

COLUMN NAME — UY_PENAL_ANTECEDENTES — Path

95% `antecedentes?(_?(penales|policiales|judiciales))?` `certificado_?(de_?)?antecedentes(_?judiciales)?` `itf` `record_?policial` `reincidencia` `condena(_?(penal|tipo))?` `delito(_?(tipo|cometido))?` `tipo_?(de_?)?delito` `situaci[oó]n_?(jur[ií]dica|procesal)` `procesamiento` `privad[oa]_?(de_?)?libertad` `inr` `establecimiento_?(carcelario|penitenciario)` `infracci[oó]n(es)?_?(penal|civil|administrativa)` `criminal_?record`

55% `estado_?(del_?)?proceso` `sentencia` `fallo`

HOW IT IS MASKED

Replaced by a generic status from the list — no record, convicted, acquitted —, whatever the outcome; a flag stays a flag.

`UY_ANTECEDENTES` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_ANTECEDENTES_LISTA`.

> `UY_BANDERA` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `UY_BANDERA_SI_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.
> >
> > `UY_BANDERA_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.
>
> `UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`UY_ANTECEDENTES_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `uy-antecedentes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Condenado por hurto en 2019	→	**Absuelto**

13.2 Court file

UY_PENAL_EXPEDIENTE

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The Identificador Único de Expediente the Poder Judicial gives every case — the office, a correlative and the year, `2-12345/2024` — and the ficha of the Fiscalía.

HOW IT IS FOUND

COLUMN NAME UY_PENAL_EXPEDIENTE — Path

90%	`iue` `identificador_?[uú]nico_?(de_?)?expediente` `n(o|ro|um|umero)_?(de_?)?(expediente_?(judicial|penal|fiscal)|causa|proceso_?(judicial|penal)|denuncia|ficha)` `expediente_?(judicial|penal|fiscal)` `causa_?penal` `n(o|ro|um|umero)_?(de_?)?(ficha|carpeta)_?(fiscal|judicial)`
50%	`expediente` `causa` `proceso` `ficha`

VALUE FORMAT UY_PENAL_EXPEDIENTE — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{1,4}-\d{1,6}/\d{4})`	85%	
`0*(?:\d{1,6}-[A-Z]{2,10}-\d{4})`	50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The office and the correlative are mapped digit by digit; the year stays. Other numbers are masked character by character.

`UY_EXPEDIENTE_JUDICIAL` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.

`UY_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`UY_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
2-12345/2024	→	**3-31564/2024**
1234/2023	→	**9707/2023**

14

The cédula and RUT check digits

The **cédula de identidad** is the simple case: seven digits with the weights 2 9 8 7 6 3 4 from the left, modulus 10, and the digit is ten minus the remainder. That is exactly what the Masking Engine's Check Digit algorithm does, so one step is enough: it maps the seven digits and writes the eighth. The published worked example — 1.234.567 gives 2 — checks out, and the dots and hyphen pass through untouched because Check Digit is told to preserve them.

The **RUT** needs one more turn. Its digit is modulus 11 over the weights 4 3 2 9 8 7 6 5 4 3 2, eleven minus the remainder, written **0 when that is eleven and 1 when it is ten**. Check Digit writes *modulus minus remainder* and writes ten as `0`, so it agrees everywhere except on one remainder: with a remainder of 1 the true digit is 1 and Check Digit writes 0 — and a remainder of 0, whose true digit really is 0, produces the same written zero. The two cases are indistinguishable from the digit alone.

The set resolves it with an **auxiliary Check Digit whose weights are the real ones doubled, modulo 11**. Doubling maps a remainder of 0 to 0 and a remainder of 1 to 2, so the auxiliary writes `0` for the first and `9` for the second — the two cases are told apart. A **Regex Decompose** then reads the pair of digits, writes the true one and drops the auxiliary. Four steps in a chain, no lookup table, and the two digits of the kind of taxpayer and the three of the branch stay where they were.

Uruguay's RUT is not derived from the cédula, so the two are masked independently — unlike Peru or Ecuador, where the taxpayer number carries the identity document inside it.

15

Where people live: localidades, INE code and postal code

With the population the 2023 census counted and a location for each place, the set knows the size, departamento and position of the 652 localidades censales and the 19 departamentos.

- A **localidad** with fewer than 20,000 inhabitants becomes the nearest localidad of at least 20,000 **in the same departamento**. There are 624 of them, with 873,000 inhabitants — a quarter of the country.
- Every one of the 19 departamentos holds at least one localidad above the threshold, so a generalized value never leaves its departamento. The departamentos themselves are all far above it — the smallest, Flores, has some 24,600 inhabitants — and they stay.
- Distance is measured between the locations, in a straight line. In seventeen of the nineteen departamentos there is exactly one localidad above the threshold, so the target is forced whatever the distance says; only Canelones, Maldonado and San José offer a real choice.
- Names repeat — Santa Lucía, San Jorge, Cerro Chato, Tala. A name is generalized only when every localidad bearing it is small, and then follows the most populous of them. Written with the departamento (`Piriápolis – Maldonado` , `Piriápolis (Maldonado)`) the same rule applies inside it. A name that is also a **departamento** — Canelones, Salto, Rivera — is left alone, so that a departamento column is never rewritten; every localidad in that position is itself above the threshold.
- The **INE code** follows the same table, so a person's localidad name and code still agree, and the **barrio** is replaced by another while the **postal code** keeps only the departamento and the zone.

Localidad names that are also given names or surnames, and departamento names, are left out of the detection list, so that a surname column is not taken for localidades.

16

Limits

- **Binary columns** — cédula photos, fingerprints, validation selfies, clinical PDFs in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **The location of 186 of the 652 localidades is approximate**: it is the centre of the localidades of their departamento for which one was found. Because seventeen departamentos have a single target, this changes the outcome for only 84 small localidades, all in Canelones, Maldonado and San José — and the guarantee of at least 20,000 inhabitants in the same departamento holds in every case.
- **The INE publishes the localidad names in capitals without their accents.** The set restores them with a dictionary and writes both spellings into the tables, but a name it could not restore comes out unaccented.
- **A localidad whose name is also a departamento is not generalized**, so that a departamento column is never rewritten. Every localidad in that position is above the threshold, so nothing escapes — but if your data uses a departamento name for a smaller place, give that column a domain of its own.
- **Data Cleansing leaves unknown values as they are**: a localidad spelled in a way that is not in the table — abbreviated, misspelled — passes unchanged.
- **Free text** is redacted word by word: a phone written with spaces inside a sentence may not be found, and a name that is also a common word (`Rosa` , `Cruz` , `Flores`) is redacted wherever it appears.
- **Children and adolescents**: a birth date moves at most 60 days, so few people cross their 18th birthday — but some do. Where that line matters, split the rule by age group with Multi-Column Condition.
- **The five-year clock of article 22 travels with the data.** Masking the amount of a debt does not reset the date on which it became due, and a test copy of a credit database keeps every obligation as old as it was.
- **Addresses** are replaced as a whole line. Street, barrio, localidad and postal code in separate columns are masked independently and no longer form a coherent address.
- **The engine key** links masked values back to production for whoever holds both: the copy is **pseudonymized** in the sense of article 8 a) of Decree 64/020, not dissociated in the sense of article 4 G), and it remains personal data for them. Keep the key apart from the copy.

17

Verification

Before publication, the set was checked outside a Masking Engine:

- The cédula rule was checked against the published worked example, and the RUT rule against the published worked example of a real RUT — Antel's 21-100342-001-7.
- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 144 columns with the whole set at its assignment threshold — well named, badly named and 29 columns that are not personal data — and again with only the classifiers of the essential pack.
- The table that generalizes places was audited for all 652 localidades and 19 departamentos: by name, by name with the departamento, and by INE code, checking that no code leaves its departamento.
- The algorithms, run with the Delphix algorithm plugin, masked each domain's sample values and placeholders such as `N/A` , checking every output against its vocabulary; 200 cédulas for validity, distinctness and the dots and hyphen they keep, and 200 RUTs for validity, distinctness and the kind of taxpayer and branch they keep. Every algorithm also masked its own sample value.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

18

Sources

- Ley 18.331 de Protección de Datos Personales y Acción de Habeas Data (11 August 2008) and Decree 414/009, as amended by Ley 18.719 (2010), Ley 18.996 (2012), Ley 19.355 (2015), Ley 19.670 (2018, arts. 37 to 40) and Ley 19.924 (2020, arts. 86 and 87), and Decree 64/020 of 17 February 2020.
- Unidad Reguladora y de Control de Datos Personales (URCDP), within AGESIC. European Commission adequacy decision 2012/484/EU. Council of Europe Convention 108.
- Ley 18.335 de derechos de los pacientes. Ley 18.651 de personas con discapacidad. Ley 18.987 de interrupción voluntaria del embarazo. Ley 19.580 de violencia hacia las mujeres. Ley 19.684 integral para personas trans. Ley 18.246 de unión concubinaria. Article 302 of the Penal Code (professional secrecy).
- Instituto Nacional de Estadística: Censo de Población, Hogares y Viviendas 2023 — table of localidades censales with the INE code, the population and the density of each one. Dirección Nacional de Identificación Civil (cédula and its check digit). Dirección General Impositiva (RUT and its check digit). Banco Central del Uruguay (debtor categories). BPS. MIDES (Índice de Carencias Críticas and the social programmes). Corte Electoral (credencial cívica and the register of parties). Dirección Nacional de Catastro (padrón). Ministerio de Trabajo (national minimum wage 2025).

APPENDIX A

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

UY_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `UY_L2_ANIO_NACIMIENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{3})(\d))`	keep · keep · `UY_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_ANTECEDENTES_LISTA`.

Used by: `UY_PENAL_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `UY_CM_ALFANUM`
otherwise	`UY_ANTECEDENTES_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `uy-antecedentes.txt`, chosen by a keyed hash.

Used by: `UY_ANTECEDENTES`

CONFIGURATION

lookupFile	`uy-antecedentes.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_APELLIDO NAME

Replaces the name with one of the 356 names in `uy-apellidos.txt`.

Used by: `UY_PALABRA_APELLIDO`

CONFIGURATION

lookupFile	uy-apellidos.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

UY_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: UY_CM_ALFANUM .

Used by: UY_L1_APELLIDO , UY_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(\S+)	UY_PALABRA_APELLIDO
(\S+)\s+(\S+)	UY_PALABRA_APELLIDO · UY_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	UY_PALABRA_APELLIDO · UY_PALABRA_APELLIDO · UY_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	UY_PALABRA_APELLIDO · UY_PALABRA_APELLIDO · UY_PALABRA_APELLIDO · UY_PALABRA_APELLIDO
otherwise	UY_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

UY_APTITUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: UY_APTITUD_LABORAL_LISTA .

Used by: UY_SALUD_OCUPACIONAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|yes|[snyx01])	UY_BANDERA
(0*?)(?:(\d{1,6}))	keep · UY_CM_ALFANUM
otherwise	UY_APTITUD_LABORAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

UY_APTITUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in uy-aptitud-laboral.txt , chosen by a keyed hash.

Used by: UY_APTITUD_LABORAL

CONFIGURATION

lookupFile	uy-aptitud-laboral.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_ASCENDENCIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_ASCENDENCIA_LISTA`.

Used by: `UY_L3_ASCENDENCIA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `UY_ASCENDENCIA_CODIGO`
otherwise	`UY_ASCENDENCIA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_ASCENDENCIA_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-ascendencia-codigos.txt`, chosen by a keyed hash.

Used by: `UY_ASCENDENCIA`

CONFIGURATION

lookupFile	`uy-ascendencia-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_ASCENDENCIA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-ascendencia.txt`, chosen by a keyed hash.

Used by: `UY_ASCENDENCIA`

CONFIGURATION

lookupFile	`uy-ascendencia.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `UY_CATEGORIA_SUPRIMIDA`, `UY_ESTADO_CIVIL`, `UY_NIVEL_EDUCATIVO`, `UY_ASCENDENCIA`, `UY_PUEBLO`, `UY_RELIGION`, `UY_PREFERENCIA_POLITICA`, `UY_PARTIDO`, `UY_ORIENTACION_SEXUAL`, `UY_IDENTIDAD_GENERO`, `UY_COBERTURA_SALUD`, `UY_DIAGNOSTICO`, `UY_MEDICAMENTO`, `UY_DISCAPACIDAD`, `UY_APTITUD_LABORAL`, `UY_HISTORIAL_CREDITICIO`, `UY_PROGRAMA_SOCIAL`, `UY_NIVEL_SOCIOECONOMICO`, `UY_TENENCIA_VIVIENDA`, `UY_ANTECEDENTES`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no)`	`UY_BANDERA_SI_NO`
`(?i)(true|false)`	`UY_BANDERA_TRUE_FALSE`
`(?i)(yes)`	`UY_BANDERA_YES_NO`

`(?i)([sn])`	`UY_BANDERA_S_N`
`(?i)([yx])`	`UY_BANDERA_Y_N`
`([01])`	`UY_BANDERA_0_1`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-0-1.txt`, chosen by a keyed hash.

Used by: `UY_BANDERA`

CONFIGURATION

lookupFile	`uy-bandera-0-1.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-s-n.txt`, chosen by a keyed hash.

Used by: `UY_BANDERA`

CONFIGURATION

lookupFile	`uy-bandera-s-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-si-no.txt`, chosen by a keyed hash.

Used by: `UY_BANDERA`

CONFIGURATION

lookupFile	`uy-bandera-si-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-true-false.txt`, chosen by a keyed hash.

Used by: `UY_BANDERA`

CONFIGURATION

lookupFile	`uy-bandera-true-false.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-y-n.txt`, chosen by a keyed hash.

Used by: `UY_BANDERA`

CONFIGURATION

lookupFile	`uy-bandera-y-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-bandera-yes-no.txt`, chosen by a keyed hash.

Used by: `UY_BANDERA`

CONFIGURATION

lookupFile	`uy-bandera-yes-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_BARRIO SECURE LOOKUP

Replaces the value with one of the 111 values in `uy-barrios.txt`, chosen by a keyed hash.

Used by: `UY_L2_BARRIO`

CONFIGURATION

lookupFile	`uy-barrios.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_SUPRIMIR`.

Used by: `UY_L3_CONVICCION_MORAL`, `UY_L3_AFILIACION_SINDICAL`, `UY_L3_VIDA_SEXUAL`, `UY_L3_VICTIMA`, `UY_SALUD_VIH`, `UY_SALUD_REPRODUCTIVA`, `UY_SALUD_MENTAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(\d{1,6})))))))))`	keep · keep · keep · keep · keep · keep · keep · `UY_CM_ALFANUM`
otherwise	`UY_SUPRIMIR`

CONFIGURATION

trimInput	yes
requireMask	no

UY_CEDULA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_CM_DIGITOS`.

Used by: `UY_DOCUMENTO`

PATTERNS, TRIED IN ORDER

`([1-9]\d{0,2}\.?\d{3}\.?\d{3}[\s\-]?\d|[1-9]\d{5,7})`	`UY_CEDULA_CD`
otherwise	`UY_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

UY_CEDULA_CD CHECK DIGIT

Masks the digits with `UY_CM_DIGITOS_ANCHO_FIJO` and recomputes a modulus 10 check digit with weights `4 3 6 7 8 9 2` from the right.

Used by: `UY_CEDULA`

CONFIGURATION

weightList	`4 3 6 7 8 9 2`
modulusNumber	`10`
checkDigitIndex	`7`
numDigitsForCheckdigitCalculation	`7`
calculateChecksumRightToLeft	yes
numericAlgorithm	`UY_CM_DIGITOS_ANCHO_FIJO`
alphaNumericAlgorithm	`UY_CM_DIGITOS_ANCHO_FIJO`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

UY_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in `uy-cie10.txt`, chosen by a keyed hash.

Used by: `UY_DIAGNOSTICO`

CONFIGURATION

lookupFile	`uy-cie10.txt`

hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `uy-cie10-decimal.txt`, chosen by a keyed hash.

Used by: UY_DIAGNOSTICO

CONFIGURATION

lookupFile	uy-cie10-decimal.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: UY_L1_DOCUMENTO_EXTRANJERO, UY_L1_PASAPORTE, UY_L1_PARTIDA, UY_L1_SEGURO_SOCIAL, UY_L1_CODIGO_ESTUDIANTE, UY_L1_MATRICULA_PROFESIONAL, UY_L1_DIRECCION_COMPLEMENTO, UY_L1_BILLETERA, UY_L1_COOKIE, UY_L1_VEHICULO, UY_L1_INMUEBLE, UY_L1_CONTRATO, UY_L1_USUARIO, UY_SALUD_IDENTIFICADOR, UY_SALUD_RESULTADO_EXAMEN, UY_CATEGORIA_SUPRIMIDA, UY_DOCUMENTO, UY_NOMBRES, UY_APELLIDOS, UY_NOMBRE_COMPLETO, UY_EMAIL, UY_PUEBLO, UY_RELIGION, UY_PREFERENCIA_POLITICA, UY_PARTIDO, UY_ORIENTACION_SEXUAL, UY_IDENTIDAD_GENERO, UY_MEDICAMENTO, UY_DISCAPACIDAD, UY_APTITUD_LABORAL, UY_PROGRAMA_SOCIAL, UY_TENENCIA_VIVIENDA, UY_ANTECEDENTES, UY_EXPEDIENTE_JUDICIAL

CONFIGURATION

characterGroups	0123456789 AEIOU BCDFGHJKLMNPQRSTVWXYZ aeiou bcdfghjklmnpqrstvwxyz ÁÉÍÓÚÜ áéíóúü
caseSensitive	yes
minMaskedPositions	0
preserveLeadingZeros	yes

UY_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: UY_L1_CUENTA_BANCARIA, UY_CEDULA, UY_RUT_CUERPO, UY_TELEFONO, UY_COORDENADA, UY_ANIO, UY_EDAD, UY_OCUPACION_O_CODIGO, UY_COBERTURA_SALUD, UY_PROCEDIMIENTO, UY_HISTORIAL_CREDITICIO, UY_EXPEDIENTE_JUDICIAL

CONFIGURATION

characterGroups	0123456789
caseSensitive	yes
minMaskedPositions	0
preserveLeadingZeros	yes

UY_CM_DIGITOS_ANCHO_FIJO CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: UY_CEDULA_CD

CONFIGURATION

characterGroups	`0123456789`
caseSensitive	yes
minMaskedPositions	`0`

UY_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: `UY_L1_CREDENCIAL_CIVICA` , `UY_L1_PLACA`

CONFIGURATION

characterGroups	`0123456789` `ABCDEFGHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

UY_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `UY_L1_DISPOSITIVO` , `UY_IP`

CONFIGURATION

characterGroups	`0123456789` `abcdef` `ABCDEF` `ghijklmnopqrstuvwxyz` `GHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

UY_COBERTURA SECURE LOOKUP

Replaces the value with one of the 8 values in `uy-cobertura-salud.txt` , chosen by a keyed hash.

Used by: `UY_COBERTURA_SALUD`

CONFIGURATION

lookupFile	`uy-cobertura-salud.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_COBERTURA_SALUD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_COBERTURA` .

Used by: `UY_SALUD_COBERTURA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(\d{1,8}))`	keep · `UY_CM_DIGITOS`
otherwise	`UY_COBERTURA`

CONFIGURATION

trimInput	yes

requireMask	no

UY_CODIGO_INE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: UY_L2_CODIGO_INE

PATTERNS, TRIED IN ORDER

(0*)([1-9]\d*)	keep · UY_CODIGO_INE_TABLA
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_CODIGO_INE_TABLA DATA CLEANSING

Replaces each value found in uy-codigos-ine-generalizados.txt (929 pairs) by its counterpart; values not in the file stay as they are.

Used by: UY_CODIGO_INE

CONFIGURATION

lookupFile	uy-codigos-ine-generalizados.txt
delimiter	|
caseSensitive	yes
trimWhitespace	yes

UY_CODIGO_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: UY_L2_CODIGO_POSTAL

PATTERNS, TRIED IN ORDER

(0*?)(?:(\d{2})(\d{3}))	keep · keep · replace with 000
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_CONTEO_LIMITADO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: UY_L2_PERSONAS_A_CARGO

PATTERNS, TRIED IN ORDER

(0*?)(?:([0-5]))	keep · keep
(0*?)(?:(\d+))	keep · replace with 5
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `UY_L1_GEOLOCALIZACION`

PATTERNS, TRIED IN ORDER

`(-?\d{1,3}[.,]\d)(\d+)\s*([,;])\s*(-?\d{1,3}[.,]\d)(\d+)`	keep · `UY_CM_DIGITOS` · keep · keep · `UY_CM_DIGITOS`
`(-?\d{1,3}[.,]\d)(\d+)`	keep · `UY_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `UY_DIAGNOSTICO_TEXTO`.

Used by: `UY_SALUD_DIAGNOSTICO`

PATTERNS, TRIED IN ORDER

`([A-TV-Za-tv-z]\d{2}\.\d{1,2})`	`UY_CIE10_DECIMAL`
`([A-TV-Za-tv-z]\d{2,3}X?)`	`UY_CIE10`
`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
otherwise	`UY_DIAGNOSTICO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

UY_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in `uy-diagnosticos.txt`, chosen by a keyed hash.

Used by: `UY_DIAGNOSTICO`

CONFIGURATION

lookupFile	`uy-diagnosticos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in `uy-direcciones.txt`, chosen by a keyed hash.

Used by: `UY_L1_DIRECCION`

CONFIGURATION

lookupFile	`uy-direcciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_DISCAPACIDAD_LISTA`.

Used by: `UY_SALUD_DISCAPACIDAD`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `UY_CM_ALFANUM`
otherwise	`UY_DISCAPACIDAD_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `uy-discapacidades.txt`, chosen by a keyed hash.

Used by: `UY_DISCAPACIDAD`

CONFIGURATION

lookupFile	`uy-discapacidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_DOCUMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.

Used by: `UY_L1_CEDULA`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{12}))`	keep · `UY_RUT`
`(0*?)(?:([1-9]\d{0,2}\.?\d{3}\.?\d{3}[\s\-]?\d|[1-9]\d{5,7}))`	keep · `UY_CEDULA`
otherwise	`UY_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

UY_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `UY_L2_EDAD`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-9]\d{2,}))`	keep · replace with `90`

`(0*?)(?:([1-9])(\d)([.,]\d+))`	keep · keep · `UY_CM_DIGITOS` · keep
`(0*?)(?:([1-9])(\d))`	keep · keep · `UY_CM_DIGITOS`
`(0*?)(?:(\d))`	keep · `UY_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.

Used by: `UY_L1_EMAIL`

PATTERNS, TRIED IN ORDER

`([^@\s]+)@([^@\s]+)\.([A-Za-z]{2,24}(?:\.[A-Za-z]{2})?)`	`UY_CM_ALFANUM` · `UY_CM_ALFANUM` · replace with `test`
otherwise	`UY_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

UY_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 24 values in `uy-empleadores.txt`, chosen by a keyed hash.

Used by: `UY_L2_EMPLEADOR`

CONFIGURATION

lookupFile	`uy-empleadores.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_ESTADO_CIVIL_LISTA`.

Used by: `UY_L2_ESTADO_CIVIL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `UY_ESTADO_CIVIL_CODIGO`
otherwise	`UY_ESTADO_CIVIL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-estado-civil-codigos.txt`, chosen by a keyed hash.

Used by: `UY_ESTADO_CIVIL`

CONFIGURATION

lookupFile	`uy-estado-civil-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-estado-civil.txt`, chosen by a keyed hash.

Used by: `UY_ESTADO_CIVIL`

CONFIGURATION

lookupFile	`uy-estado-civil.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 13 values in `uy-estados-credito.txt`, chosen by a keyed hash.

Used by: `UY_HISTORIAL_CREDITICIO`

CONFIGURATION

lookupFile	`uy-estados-credito.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_EXPEDIENTE_JUDICIAL REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.

Used by: `UY_PENAL_EXPEDIENTE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,4})(-)(\d{1,6})(/)(\d{4}))`	keep · `UY_CM_DIGITOS` · keep · `UY_CM_DIGITOS` · keep · keep
`(0*?)(?:(\d{1,6})([\s\-/])([A-Za-z]{2,10})([\s\-/])(\d{4}))`	keep · `UY_CM_DIGITOS` · keep · keep · keep · keep
`([A-Za-z]{1,6}[\s\-]?)(\d{1,6})([\s\-/])(\d{4})`	keep · `UY_CM_DIGITOS` · keep · keep
`(0*?)(?:(\d{1,6})([\s\-/])(\d{4}))`	keep · `UY_CM_DIGITOS` · keep · keep
otherwise	`UY_CM_ALFANUM`

CONFIGURATION

trimInput	yes

requireMask	no

UY_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `UY_L2_FECHA_EVENTO`

CONFIGURATION

minRange	`-30`
maxRange	`30`
unit	`DAYS`
roll	no

UY_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `UY_L2_FECHA_NACIMIENTO`

CONFIGURATION

minRange	`-60`
maxRange	`60`
unit	`DAYS`
roll	no

UY_HISTORIAL_CREDITICIO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_ESTADO_CREDITO`.

Used by: `UY_FIN_HISTORIAL_CREDITICIO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,4}))`	keep · `UY_CM_DIGITOS`
`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
otherwise	`UY_ESTADO_CREDITO`

CONFIGURATION

trimInput	yes
requireMask	no

UY_IDENTIDAD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `UY_RUT_AUX`

PATTERNS, TRIED IN ORDER

`(.*)`	keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_IDENTIDAD_GENERO_LISTA`.

Used by: `UY_L3_IDENTIDAD_GENERO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `UY_CM_ALFANUM`
otherwise	`UY_IDENTIDAD_GENERO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `uy-identidades-genero.txt`, chosen by a keyed hash.

Used by: `UY_IDENTIDAD_GENERO`

CONFIGURATION

lookupFile	`uy-identidades-genero.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_INSTITUCION_EDUCATIVA SECURE LOOKUP

Replaces the value with one of the 12 values in `uy-instituciones-educativas.txt`, chosen by a keyed hash.

Used by: `UY_L2_INSTITUCION_EDUCATIVA`

CONFIGURATION

lookupFile	`uy-instituciones-educativas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_CM_HEX`.

Used by: `UY_L1_IP`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}))`	keep · `UY_OCTETO` · `UY_OCTETO` · `UY_OCTETO` · `UY_OCTETO`
otherwise	`UY_CM_HEX`

CONFIGURATION

trimInput	yes
requireMask	no

UY_LOCALIDAD DATA CLEANSING

Replaces each value found in `uy-localidades-generalizadas.txt` (9,772 pairs) by its counterpart; values not in the file stay as they are.

Used by: `UY_L2_LOCALIDAD`

CONFIGURATION

lookupFile	`uy-localidades-generalizadas.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

UY_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_MEDICAMENTO_LISTA`.

Used by: `UY_SALUD_MEDICAMENTO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `UY_CM_ALFANUM`
otherwise	`UY_MEDICAMENTO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 22 values in `uy-medicamentos.txt`, chosen by a keyed hash.

Used by: `UY_MEDICAMENTO`

CONFIGURATION

lookupFile	`uy-medicamentos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 14 values in `uy-nacionalidades.txt`, chosen by a keyed hash.

Used by: `UY_L3_NACIONALIDAD`

CONFIGURATION

lookupFile	`uy-nacionalidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_NIVEL_EDUCATIVO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_NIVEL_EDUCATIVO_LISTA`.

Used by: `UY_L2_NIVEL_EDUCATIVO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `UY_NIVEL_EDUCATIVO_CODIGO`
otherwise	`UY_NIVEL_EDUCATIVO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_NIVEL_EDUCATIVO_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in `uy-nivel-educativo-codigos.txt`, chosen by a keyed hash.

Used by: `UY_NIVEL_EDUCATIVO`

CONFIGURATION

lookupFile	`uy-nivel-educativo-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_NIVEL_EDUCATIVO_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `uy-nivel-educativo.txt`, chosen by a keyed hash.

Used by: `UY_NIVEL_EDUCATIVO`

CONFIGURATION

lookupFile	`uy-nivel-educativo.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_NIVEL_SOCIOECONOMICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_NIVEL_SOCIOECONOMICO_LISTA`.

Used by: `UY_FIN_NIVEL_SOCIOECONOMICO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*)([1-9]\d{0,5}|0)`	keep · `UY_NIVEL_SOCIOECONOMICO_CODIGO`
otherwise	`UY_NIVEL_SOCIOECONOMICO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_NIVEL_SOCIOECONOMICO_CODIGO SECURE LOOKUP

Replaces the value with one of the 5 values in `uy-nivel-socioeconomico-codigos.txt`, chosen by a keyed hash.

Used by: `UY_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	`uy-nivel-socioeconomico-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_NIVEL_SOCIOECONOMICO_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `uy-nivel-socioeconomico.txt`, chosen by a keyed hash.

Used by: `UY_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	`uy-nivel-socioeconomico.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_NOMBRE NAME

Replaces the name with one of the 287 names in `uy-nombres.txt`.

Used by: `UY_PALABRA_NOMBRE`

CONFIGURATION

lookupFile	`uy-nombres.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

UY_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.

Used by: `UY_L1_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`([^,]+),\s*(.+)`	`UY_APELLIDOS` · `UY_NOMBRES`
`(\S+)`	`UY_PALABRA_NOMBRE`
`(\S+)\s+(\S+)`	`UY_PALABRA_NOMBRE` · `UY_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`UY_PALABRA_NOMBRE` · `UY_PALABRA_APELLIDO` · `UY_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`UY_PALABRA_NOMBRE` · `UY_PALABRA_NOMBRE` · `UY_PALABRA_APELLIDO` · `UY_PALABRA_APELLIDO`

`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`UY_PALABRA_NOMBRE` · `UY_PALABRA_NOMBRE` · `UY_PALABRA_APELLIDO` · `UY_PALABRA_APELLIDO` · `UY_PALABRA_APELLIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`UY_PALABRA_NOMBRE` · `UY_PALABRA_NOMBRE` · `UY_PALABRA_NOMBRE` · `UY_PALABRA_APELLIDO` · `UY_PALABRA_APELLIDO` · `UY_PALABRA_APELLIDO`
otherwise	`UY_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

UY_NOMBRES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_ALFANUM`.

Used by: `UY_L1_NOMBRE`, `UY_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`UY_PALABRA_NOMBRE`
`(\S+)\s+(\S+)`	`UY_PALABRA_NOMBRE` · `UY_PALABRA_NOMBRE`
`(\S+)\s+(\S+)\s+(\S+)`	`UY_PALABRA_NOMBRE` · `UY_PALABRA_NOMBRE` · `UY_PALABRA_NOMBRE`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`UY_PALABRA_NOMBRE` · `UY_PALABRA_NOMBRE` · `UY_PALABRA_NOMBRE` · `UY_PALABRA_NOMBRE`
otherwise	`UY_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

UY_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `UY_IP`

CONFIGURATION

minValue	`1`
maxValue	`254`

UY_OCUPACION SECURE LOOKUP

Replaces the value with one of the 38 values in `uy-ocupaciones.txt`, chosen by a keyed hash.

Used by: `UY_OCUPACION_O_CODIGO`

CONFIGURATION

lookupFile	`uy-ocupaciones.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_OCUPACION_O_CODIGO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_OCUPACION`.

Used by: `UY_L2_OCUPACION`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{2,5}))`	keep · `UY_CM_DIGITOS`
otherwise	`UY_OCUPACION`

CONFIGURATION

trimInput	yes
requireMask	no

UY_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_ORIENTACION_SEXUAL_LISTA`.

Used by: `UY_L3_ORIENTACION_SEXUAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `UY_CM_ALFANUM`
otherwise	`UY_ORIENTACION_SEXUAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `uy-orientaciones-sexuales.txt`, chosen by a keyed hash.

Used by: `UY_ORIENTACION_SEXUAL`

CONFIGURATION

lookupFile	`uy-orientaciones-sexuales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_APELLIDO`.

Used by: `UY_APELLIDOS`, `UY_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(?i)(de|del|la|las|los|y|e|da|do|dos|san|santa|van|von|di|le)`	keep
otherwise	`UY_APELLIDO`

CONFIGURATION

trimInput	yes
requireMask	no

UY_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_NOMBRE`.

Used by: `UY_NOMBRES` , `UY_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

`(?i)(de|del|la|las|los|y|e|da|do|dos|san|santa|van|von|di|le)`	keep
otherwise	`UY_NOMBRE`

CONFIGURATION

trimInput	yes
requireMask	no

UY_PARTIDO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_PARTIDO_LISTA` .

Used by: `UY_L3_AFILIACION_PARTIDARIA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `UY_CM_ALFANUM`
otherwise	`UY_PARTIDO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `uy-partidos.txt` , chosen by a keyed hash.

Used by: `UY_PARTIDO`

CONFIGURATION

lookupFile	`uy-partidos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_PREFERENCIA_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_PREFERENCIA_POLITICA_LISTA` .

Used by: `UY_L3_PREFERENCIA_POLITICA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `UY_CM_ALFANUM`
otherwise	`UY_PREFERENCIA_POLITICA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_PREFERENCIA_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `uy-preferencias-politicas.txt`, chosen by a keyed hash.

Used by: `UY_PREFERENCIA_POLITICA`

CONFIGURATION

lookupFile	`uy-preferencias-politicas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_PROCEDIMIENTO_TEXTO`.

Used by: `UY_SALUD_PROCEDIMIENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{4,6}))`	keep · `UY_CM_DIGITOS`
otherwise	`UY_PROCEDIMIENTO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

UY_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in `uy-procedimientos.txt`, chosen by a keyed hash.

Used by: `UY_PROCEDIMIENTO`

CONFIGURATION

lookupFile	`uy-procedimientos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_PROGRAMA_SOCIAL_LISTA`.

Used by: `UY_FIN_PROGRAMA_SOCIAL`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `UY_CM_ALFANUM`
otherwise	`UY_PROGRAMA_SOCIAL_LISTA`

CONFIGURATION

trimInput	yes

requireMask	no

UY_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `uy-programas-sociales.txt`, chosen by a keyed hash.

Used by: `UY_PROGRAMA_SOCIAL`

CONFIGURATION

lookupFile	`uy-programas-sociales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_PUEBLO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_PUEBLO_LISTA`.

Used by: `UY_L3_PUEBLO_ORIGINARIO`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`
`(0*?)(?:(\d{1,6}))`	keep · `UY_CM_ALFANUM`
otherwise	`UY_PUEBLO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_PUEBLO_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-pueblos.txt`, chosen by a keyed hash.

Used by: `UY_PUEBLO`

CONFIGURATION

lookupFile	`uy-pueblos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_RAZON_SOCIAL SECURE LOOKUP

Replaces the value with one of the 20 values in `uy-razones-sociales.txt`, chosen by a keyed hash.

Used by: `UY_L1_RAZON_SOCIAL`

CONFIGURATION

lookupFile	`uy-razones-sociales.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

UY_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: UY_L1_CREDENCIAL, UY_L3_BIOMETRICO, UY_L3_GENETICO

PATTERNS, TRIED IN ORDER

(.+)	each character → X
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: UY_RELIGION_LISTA.

Used by: UY_L3_RELIGION

PATTERNS, TRIED IN ORDER

(?i)(s[ií]|no|true|false|yes|[snyx01])	UY_BANDERA
(0*?)(?:(\d{1,6}))	keep · UY_CM_ALFANUM
otherwise	UY_RELIGION_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

UY_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in uy-religiones.txt, chosen by a keyed hash.

Used by: UY_RELIGION

CONFIGURATION

lookupFile	uy-religiones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_RUT STRING ALGORITHM CHAIN

Applies UY_RUT_CD → UY_RUT_ESPACIO → UY_RUT_AUX → UY_RUT_VERIFICADOR, in this order.

Used by: UY_RUT_COLUMNA, UY_DOCUMENTO

CONFIGURATION

algorithmReferences[1]	UY_RUT_CD
algorithmReferences[2]	UY_RUT_ESPACIO
algorithmReferences[3]	UY_RUT_AUX
algorithmReferences[4]	UY_RUT_VERIFICADOR

UY_RUT_AUX CHECK DIGIT

Masks the digits with `UY_IDENTIDAD` and recomputes a modulus 11 check digit with weights `0 4 6 8 10 1 3 5 7 4 6 8` from the right.

Used by: `UY_RUT`

CONFIGURATION

weightList	`0 4 6 8 10 1 3 5 7 4 6 8`
modulusNumber	`11`
checkDigitIndex	`12`
numDigitsForCheckdigitCalculation	`12`
calculateChecksumRightToLeft	yes
numericAlgorithm	`UY_IDENTIDAD`
alphaNumericAlgorithm	`UY_IDENTIDAD`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

UY_RUT_CD CHECK DIGIT

Masks the digits with `UY_RUT_CUERPO` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 8 9 2 3 4` from the right.

Used by: `UY_RUT`

CONFIGURATION

weightList	`2 3 4 5 6 7 8 9 2 3 4`
modulusNumber	`11`
checkDigitIndex	`11`
numDigitsForCheckdigitCalculation	`11`
calculateChecksumRightToLeft	yes
numericAlgorithm	`UY_RUT_CUERPO`
alphaNumericAlgorithm	`UY_RUT_CUERPO`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

UY_RUT_COLUMNA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_RUT`.

Used by: `UY_L1_RUT`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{12}))`	keep · `UY_RUT`
otherwise	`UY_RUT`

CONFIGURATION

`trimInput`	yes
`requireMask`	no

UY_RUT_CUERPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `UY_CM_DIGITOS`.

Used by: `UY_RUT_CD`

PATTERNS, TRIED IN ORDER

`(\d{2})(\d{6})(\d{3})`	keep · `UY_CM_DIGITOS` · keep
`otherwise`	`UY_CM_DIGITOS`

CONFIGURATION

`trimInput`	yes
`requireMask`	no

UY_RUT_ESPACIO REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `UY_RUT`

PATTERNS, TRIED IN ORDER

`(\d{11}[\s\-]?)(0)`	keep · replace with `00`
`(\d{11}[\s\-]?)(1)`	keep · replace with `10`
`(\d{11}[\s\-]?)(2)`	keep · replace with `20`
`(\d{11}[\s\-]?)(3)`	keep · replace with `30`
`(\d{11}[\s\-]?)(4)`	keep · replace with `40`
`(\d{11}[\s\-]?)(5)`	keep · replace with `50`
`(\d{11}[\s\-]?)(6)`	keep · replace with `60`
`(\d{11}[\s\-]?)(7)`	keep · replace with `70`
`(\d{11}[\s\-]?)(8)`	keep · replace with `80`
`(\d{11}[\s\-]?)(9)`	keep · replace with `90`
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

UY_RUT_VERIFICADOR REGEX DECOMPOSE

Tries 11 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `UY_RUT`

PATTERNS, TRIED IN ORDER

`(\d{11}[\s\-]?)(00)`	keep · replace with `0`
`(\d{11}[\s\-]?)(0\d)`	keep · replace with `1`
`(\d{11}[\s\-]?)(1\d)`	keep · replace with `1`
`(\d{11}[\s\-]?)(2\d)`	keep · replace with `2`
`(\d{11}[\s\-]?)(3\d)`	keep · replace with `3`
`(\d{11}[\s\-]?)(4\d)`	keep · replace with `4`
`(\d{11}[\s\-]?)(5\d)`	keep · replace with `5`

`(\d{11}[\s\-]?)(6\d)`	keep · replace with `6`
`(\d{11}[\s\-]?)(7\d)`	keep · replace with `7`
`(\d{11}[\s\-]?)(8\d)`	keep · replace with `8`
`(\d{11}[\s\-]?)(9\d)`	keep · replace with `9`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_SEXO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `UY_L2_SEXO`

PATTERNS, TRIED IN ORDER

`(?i)(femenino|masculino)`	`UY_SEXO_FEMENINO_MASCULINO`
`(?i)(mujer|hombre)`	`UY_SEXO_MUJER_HOMBRE`
`(?i)(female|male)`	`UY_SEXO_FEMALE_MALE`
`(?i)([fm])`	`UY_SEXO_F_M`
`(?i)([hm])`	`UY_SEXO_H_M`
`(0*?)(?:([12]))`	keep · `UY_SEXO_1_2`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_SEXO_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-1-2.txt`, chosen by a keyed hash.

Used by: `UY_SEXO`

CONFIGURATION

lookupFile	`uy-sexo-1-2.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_SEXO_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-f-m.txt`, chosen by a keyed hash.

Used by: `UY_SEXO`

CONFIGURATION

lookupFile	`uy-sexo-f-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_SEXO_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-female-male.txt`, chosen by a keyed hash.

Used by: `UY_SEXO`

CONFIGURATION

lookupFile	`uy-sexo-female-male.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_SEXO_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-femenino-masculino.txt`, chosen by a keyed hash.

Used by: `UY_SEXO`

CONFIGURATION

lookupFile	`uy-sexo-femenino-masculino.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-h-m.txt`, chosen by a keyed hash.

Used by: `UY_SEXO`

CONFIGURATION

lookupFile	`uy-sexo-h-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_SEXO_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `uy-sexo-mujer-hombre.txt`, chosen by a keyed hash.

Used by: `UY_SEXO`

CONFIGURATION

lookupFile	`uy-sexo-mujer-hombre.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `uy-sin-informacion.txt`, chosen by a keyed hash.

Used by: `UY_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	`uy-sin-informacion.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `UY_L1_TARJETA`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d[\d\s\-]{11,22}\d))`	keep · `dlpx-core:Credit Card`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

UY_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `UY_CM_DIGITOS`.

Used by: `UY_L1_TELEFONO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\+?598[\s\-]?)(0?9\d)([\s\-]?)([\d\s\-]{6,9}))`	keep · keep · keep · keep · `UY_CM_DIGITOS`
`(0*?)(?:(0?9\d)([\s\-]?)([\d\s\-]{6,9}))`	keep · keep · keep · `UY_CM_DIGITOS`
`(0*?)(?:(\+?598[\s\-]?)?(\(?0?[24]\)?)([\s\-]?)([\d\s\-]{6,10}))`	keep · keep · keep · keep · `UY_CM_DIGITOS`
otherwise	`UY_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

UY_TENENCIA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `UY_TENENCIA_VIVIENDA_LISTA`.

Used by: `UY_FIN_VIVIENDA`

PATTERNS, TRIED IN ORDER

`(?i)(s[ií]|no|true|false|yes|[snyx01])`	`UY_BANDERA`

`(0*?)(?:(\d{1,6}))`	keep · `UY_CM_ALFANUM`
otherwise	`UY_TENENCIA_VIVIENDA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

UY_TENENCIA_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `uy-tenencia-vivienda.txt`, chosen by a keyed hash.

Used by: `UY_TENENCIA_VIVIENDA`

CONFIGURATION

lookupFile	`uy-tenencia-vivienda.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

UY_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATO]`, and the 1,494 terms of `uy-texto-nombres.txt` with `[NOMBRE]`.

Used by: `UY_L1_TEXTO_LIBRE`, `UY_SALUD_TEXTO_CLINICO`

PATTERNS, TRIED IN ORDER

`(?<!\d)\d{1,3}\.\d{3}\.\d{3}-\d(?!\d)`
`(?<!\d)\d{7,8}(?!\d)`
`(?<!\d)\d{12}(?!\d)`
`[\w.+\-]+@[\w\-]+(\.[\w\-]+)+`
`(?<![\d\-])(\+?598[\s\-]?)?0?9\d[\s\-]?\d{3}[\s\-]?\d{3}(?![\d\-])`
`(?<!\d)\d{13,19}(?!\d)`
`(?<![A-Za-z])[A-Z]{3}[\s\-]?\d{4}(?![A-Za-z\d])`
`(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\d)`

CONFIGURATION

regExRedactValue	`[DATO]`
lookupFile	`uy-texto-nombres.txt`
lookupFileRedactValue	`[NOMBRE]`
isDenyList	yes

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
`uy-antecedentes.txt`	7	`UY_ANTECEDENTES_LISTA`	No registra antecedentes judiciales · Registra antecedentes · Procesado · Condenado
`uy-apellidos.txt`	356	`UY_APELLIDO`	Rodríguez · González · Fernández · Pérez
`uy-aptitud-laboral.txt`	4	`UY_APTITUD_LABORAL_LISTA`	Apto · Apto con restricciones · No apto · Pendiente
`uy-ascendencia-codigos.txt`	6	`UY_ASCENDENCIA_CODIGO`	1 · 2 · 3 · 4
`uy-ascendencia.txt`	6	`UY_ASCENDENCIA_LISTA`	Afro o negra · Asiática o amarilla · Blanca · Indígena
`uy-bandera-0-1.txt`	2	`UY_BANDERA_0_1`	0 · 1
`uy-bandera-s-n.txt`	2	`UY_BANDERA_S_N`	S · N
`uy-bandera-si-no.txt`	2	`UY_BANDERA_SI_NO`	Sí · No
`uy-bandera-true-false.txt`	2	`UY_BANDERA_TRUE_FALSE`	true · false
`uy-bandera-y-n.txt`	2	`UY_BANDERA_Y_N`	Y · N
`uy-bandera-yes-no.txt`	2	`UY_BANDERA_YES_NO`	Yes · No
`uy-barrios.txt`	111	`UY_BARRIO`	Ciudad Vieja · Centro · Cordón · Barrio Sur
`uy-cie10-decimal.txt`	33	`UY_CIE10_DECIMAL`	E11.9 · E78.5 · J45.9 · J06.9
`uy-cie10.txt`	37	`UY_CIE10`	I10 · E11 · E78 · J45
`uy-cobertura-salud.txt`	8	`UY_COBERTURA`	ASSE · Mutualista (IAMC) · Seguro privado integral · Sanidad Militar
`uy-codigos-ine-generalizados.txt`	929	`UY_CODIGO_INE_TABLA`	02621|02020 · 02021|02020 · 02721|02020 · 02925|02020
`uy-detectar-apellidos.txt`	427	`UY_L1_APELLIDO – List` `UY_L1_NOMBRE_COMPLETO – List`	Rodríguez · Rodriguez · González · Gonzalez
`uy-detectar-nacionalidades.txt`	38	`UY_L3_NACIONALIDAD – List`	Uruguaya · Argentina · Brasileña · Brasilena
`uy-detectar-nombres.txt`	345	`UY_L1_NOMBRE – List` `UY_L1_NOMBRE_COMPLETO – List`	Juan · José · Jose · Carlos

FILE	LINES	USED BY	FIRST LINES
`uy-detectar-sexo-letra.txt`	3	`UY_L2_SEXO – List`	f · m · h
`uy-detectar-sexo.txt`	6	`UY_L2_SEXO – List`	femenino · masculino · mujer · hombre
`uy-diagnosticos.txt`	30	`UY_DIAGNOSTICO_TEXTO`	Hipertensión arterial · Diabetes mellitus tipo 2 · Asma · Lumbalgia
`uy-direcciones.txt`	4,000	`UY_DIRECCION`	Avenida Maldonado 4402 · Calle Ciudadela 2918 esq. Juan Carlos Gómez · Ruta 25 km 286 · Ruta 48 km 384
`uy-discapacidades.txt`	7	`UY_DISCAPACIDAD_LISTA`	Física o motriz · Auditiva · Visual · Intelectual
`uy-empleadores.txt`	24	`UY_EMPLEADOR`	Distribuidora del Plata S.A. · Constructora Oriental S.A. · Transportes Santa Lucía S.R.L. · Supermercados del Centro S.A.
`uy-estado-civil-codigos.txt`	6	`UY_ESTADO_CIVIL_CODIGO`	1 · 2 · 3 · 4
`uy-estado-civil.txt`	6	`UY_ESTADO_CIVIL_LISTA`	Soltero/a · Casado/a · Unión libre o concubinato · Separado/a
`uy-estados-credito.txt`	13	`UY_ESTADO_CREDITO`	Categoría 1C — riesgo mínimo · Categoría 1A — riesgo bajo · Categoría 2A — riesgo medio · Categoría 2B — riesgo medio alto
`uy-identidades-genero.txt`	7	`UY_IDENTIDAD_GENERO_LISTA`	Mujer cisgénero · Hombre cisgénero · Mujer trans · Hombre trans
`uy-instituciones-educativas.txt`	12	`UY_INSTITUCION_EDUCATIVA`	Escuela N.º 123 Artigas · Escuela N.º 45 José Pedro Varela · Liceo N.º 7 de Montevideo · Liceo Departamental
`uy-localidades-generalizadas.txt`	9,772	`UY_LOCALIDAD`	Baltasar Brum|Artigas · Baltasar Brum - Artigas|Artigas - Artigas · Baltasar Brum, Artigas|Artigas, Artigas · Baltasar Brum (Artigas)|Artigas (Artigas)
`uy-medicamentos.txt`	22	`UY_MEDICAMENTO_LISTA`	Paracetamol · Ibuprofeno · Diclofenac · Metformina
`uy-nacionalidades.txt`	14	`UY_NACIONALIDAD`	Uruguaya · Argentina · Brasileña · Venezolana
`uy-nivel-educativo-codigos.txt`	10	`UY_NIVEL_EDUCATIVO_CODIGO`	1 · 2 · 3 · 4
`uy-nivel-educativo.txt`	10	`UY_NIVEL_EDUCATIVO_LISTA`	Sin instrucción · Preescolar · Primaria · Ciclo básico
`uy-nivel-socioeconomico-codigos.txt`	5	`UY_NIVEL_SOCIOECONOMICO_CODIGO`	1 · 2 · 3 · 4
`uy-nivel-socioeconomico.txt`	8	`UY_NIVEL_SOCIOECONOMICO_LISTA`	Quintil 1 · Quintil 2 · Quintil 3 · Quintil 4
`uy-nombres.txt`	287	`UY_NOMBRE`	Juan · José · Carlos · Luis
`uy-ocupaciones.txt`	38	`UY_OCUPACION`	Empleado administrativo · Vendedor · Cajero · Chofer

FILE	LINES	USED BY	FIRST LINES
uy-orientaciones-sexuales.txt	8	UY_ORIENTACION_SEXUAL_LISTA	Heterosexual · Gay · Lesbiana · Bisexual
uy-partidos.txt	10	UY_PARTIDO_LISTA	Frente Amplio · Partido Nacional · Partido Colorado · Cabildo Abierto
uy-preferencias-politicas.txt	7	UY_PREFERENCIA_POLITICA_LISTA	Izquierda · Centroizquierda · Centro · Centroderecha
uy-procedimientos.txt	10	UY_PROCEDIMIENTO_TEXTO	Consulta médica general · Consulta de emergencia · Hemograma completo · Glicemia
uy-programas-sociales.txt	8	UY_PROGRAMA_SOCIAL_LISTA	Tarjeta Uruguay Social · Asignaciones Familiares Plan de Equidad · Asistencia a la Vejez · Uruguay Trabaja
uy-pueblos.txt	6	UY_PUEBLO_LISTA	Charrúa · Guaraní · Chaná · Minuán
uy-razones-sociales.txt	20	UY_RAZON_SOCIAL	Comercial del Plata S.A. · Distribuidora Oriental S.R.L. · Importadora Rambla S.A. · Transportes Santa Lucía S.R.L.
uy-religiones.txt	10	UY_RELIGION_LISTA	Católica · Cristiana no católica · Evangélica · Umbandista o afroumbandista
uy-sexo-1-2.txt	2	UY_SEXO_1_2	1 · 2
uy-sexo-f-m.txt	2	UY_SEXO_F_M	F · M
uy-sexo-female-male.txt	2	UY_SEXO_FEMALE_MALE	Female · Male
uy-sexo-femenino-masculino.txt	2	UY_SEXO_FEMENINO_MASCULINO	Femenino · Masculino
uy-sexo-h-m.txt	2	UY_SEXO_H_M	H · M
uy-sexo-mujer-hombre.txt	2	UY_SEXO_MUJER_HOMBRE	Mujer · Hombre
uy-sin-informacion.txt	1	UY_SUPRIMIR	Sin información
uy-tenencia-vivienda.txt	6	UY_TENENCIA_VIVIENDA_LISTA	Propietario de la vivienda y el terreno · Propietario de la vivienda y no del terreno · Inquilino o arrendatario · Ocupante en relación de dependencia
uy-texto-nombres.txt	1,494	UY_TEXTO_LIBRE	Juan · JUAN · José · JOSÉ

APPENDIX C

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 `producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `fantasia` `comercial` `archivo` `calle` `avenida` `camino` `pasaje` `rambla` `barrio` `balneario` `localidad` `departamento` `depto` `dpto` `pais` `banco` `sucursal` `agencia` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `escuela` `liceo` `colegio` `institucion` `universidad` `curso` `materia` `documento` `doc` `unidad` `clinica` `hospital` `mutualista` `bps` `seguro` `area` `dependencia` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `lengua` `idioma` `lugar` `sede` `local` `tienda` `deposito` `proveedor` `convenio` `contrato` `poliza` `aseguradora` `entidad` `organismo` `organizacion` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `comprobante` `pago` `forma` `zona` `ruta` `linea` `actividad` `rubro` `sector` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `trabajador` `funcionario` `colaborador` `alumno` `estudiante` `deudor` `codeudor` `garante` `solicitante` `propietario` `arrendatario` `inquilino` `conductor` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `concubino` `contacto` `referencia` `victima` `denunciante` `imputado` `testigo` `medico` `docente` `socio` `heredero` `donante` `tutor` `jubilado` `pensionista` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner` `completo` `apellidos?` `usuario` `corto` `largo`

E2 `producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `fantasia` `comercial` `archivo` `calle` `avenida` `camino` `pasaje` `rambla` `barrio` `balneario` `localidad` `departamento` `depto` `dpto` `pais` `banco` `sucursal` `agencia` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `escuela` `liceo` `colegio` `institucion` `universidad` `curso` `materia` `documento` `doc` `unidad` `clinica` `hospital` `mutualista` `bps` `seguro` `area` `dependencia` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `lengua` `idioma` `lugar` `sede` `local` `tienda` `deposito` `proveedor` `convenio` `contrato` `poliza` `aseguradora` `entidad` `organismo` `organizacion` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `comprobante` `pago` `forma` `zona` `ruta` `linea` `actividad` `rubro` `sector` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `trabajador` `funcionario` `colaborador` `alumno` `estudiante` `deudor` `codeudor` `garante` `solicitante` `propietario` `arrendatario` `inquilino` `conductor` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `concubino` `contacto` `referencia` `victima` `denunciante` `imputado` `testigo` `medico` `docente` `socio` `heredero` `donante` `tutor` `jubilado` `pensionista` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner`

E3	`producto` `prod` `item` `articulo` `empresa` `emp` `razon` `social` `fantasia` `comercial` `archivo` `calle` `avenida` `camino` `pasaje` `rambla` `barrio` `balneario` `localidad` `departamento` `depto` `dpto` `pais` `banco` `sucursal` `agencia` `plan` `campana` `proyecto` `servicio` `tabla` `columna` `campo` `usuario` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `escuela` `liceo` `colegio` `institucion` `universidad` `curso` `materia` `documento` `doc` `unidad` `clinica` `hospital` `mutualista` `bps` `seguro` `area` `dependencia` `cargo` `sistema` `app` `aplicacion` `grupo` `lista` `reporte` `informe` `proceso` `evento` `tarea` `perfil` `rol` `clase` `objeto` `cuenta` `medicamento` `diagnostico` `estudio` `programa` `beneficio` `partido` `sindicato` `religion` `lengua` `idioma` `lugar` `sede` `local` `tienda` `deposito` `proveedor` `convenio` `contrato` `poliza` `aseguradora` `entidad` `organismo` `organizacion` `parametro` `variable` `metodo` `funcion` `indice` `job` `script` `cola` `recurso` `red` `dispositivo` `plantilla` `imagen` `foto` `pagina` `sitio` `modulo` `menu` `opcion` `accion` `permiso` `concepto` `impuesto` `moneda` `emisor` `factura` `comprobante` `pago` `forma` `zona` `ruta` `linea` `actividad` `rubro` `sector` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `paciente` `pac` `usuario` `afiliado` `asegurado` `beneficiario` `benef` `titular` `empleado` `trabajador` `funcionario` `colaborador` `alumno` `estudiante` `deudor` `codeudor` `garante` `solicitante` `propietario` `arrendatario` `inquilino` `conductor` `responsable` `representante` `apoderado` `persona` `ciudadano` `contribuyente` `madre` `padre` `conyuge` `concubino` `contacto` `referencia` `victima` `denunciante` `imputado` `testigo` `medico` `docente` `socio` `heredero` `donante` `tutor` `jubilado` `pensionista` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner` `full` `complete` `last` `first`
E4	`ip` `mac` `email` `e_?mail` `correo` `electr[oó]nica` `web` `url` `tipo` `id` `general` `regional`
E5	`ip` `mac` `email` `e_?mail` `web` `url` `type` `id`
E6	`id` `cd` `cod` `codigo` `tipo` `fecha` `estado` `num` `nro`
E7	`id` `tipo` `codigo` `fecha` `estado` `cola` `log`

APPENDIX D

Profile set and classifiers

The profile set `UY – Ley 18.331 – v2` runs these 143 classifiers, with an assignment threshold of 60%.

Ley 18.331 - datos personales y sensibles

CLASSIFIER	KIND	DOMAIN
UY_L1_CEDULA – Path	COLUMN NAME	UY_L1_CEDULA
UY_L1_CEDULA – Type	DATA TYPE	UY_L1_CEDULA
UY_L1_CEDULA – Regex	VALUE FORMAT	UY_L1_CEDULA
UY_L1_RUT – Path	COLUMN NAME	UY_L1_RUT
UY_L1_RUT – Regex	VALUE FORMAT	UY_L1_RUT
UY_L1_DOCUMENTO_EXTRANJERO – Path	COLUMN NAME	UY_L1_DOCUMENTO_EXTRANJERO
UY_L1_PASAPORTE – Path	COLUMN NAME	UY_L1_PASAPORTE
UY_L1_PASAPORTE – Regex	VALUE FORMAT	UY_L1_PASAPORTE
UY_L1_CREDENCIAL_CIVICA – Path	COLUMN NAME	UY_L1_CREDENCIAL_CIVICA
UY_L1_CREDENCIAL_CIVICA – Regex	VALUE FORMAT	UY_L1_CREDENCIAL_CIVICA
UY_L1_PARTIDA – Path	COLUMN NAME	UY_L1_PARTIDA
UY_L1_SEGURO_SOCIAL – Path	COLUMN NAME	UY_L1_SEGURO_SOCIAL
UY_L1_CODIGO_ESTUDIANTE – Path	COLUMN NAME	UY_L1_CODIGO_ESTUDIANTE
UY_L1_MATRICULA_PROFESIONAL – Path	COLUMN NAME	UY_L1_MATRICULA_PROFESIONAL
UY_L1_NOMBRE – Path	COLUMN NAME	UY_L1_NOMBRE
UY_L1_NOMBRE – List	KNOWN VALUES	UY_L1_NOMBRE
UY_L1_APELLIDO – Path	COLUMN NAME	UY_L1_APELLIDO
UY_L1_APELLIDO – List	KNOWN VALUES	UY_L1_APELLIDO
UY_L1_NOMBRE_COMPLETO – Path	COLUMN NAME	UY_L1_NOMBRE_COMPLETO
UY_L1_NOMBRE_COMPLETO – List	KNOWN VALUES	UY_L1_NOMBRE_COMPLETO
UY_L1_RAZON_SOCIAL – Path	COLUMN NAME	UY_L1_RAZON_SOCIAL
UY_L1_EMAIL – Path	COLUMN NAME	UY_L1_EMAIL
UY_L1_EMAIL – Type	DATA TYPE	UY_L1_EMAIL
UY_L1_EMAIL – Regex	VALUE FORMAT	UY_L1_EMAIL
UY_L1_TELEFONO – Path	COLUMN NAME	UY_L1_TELEFONO
UY_L1_TELEFONO – Regex	VALUE FORMAT	UY_L1_TELEFONO
UY_L1_DIRECCION – Path	COLUMN NAME	UY_L1_DIRECCION
UY_L1_DIRECCION – Type	DATA TYPE	UY_L1_DIRECCION
UY_L1_DIRECCION – Regex	VALUE FORMAT	UY_L1_DIRECCION
UY_L1_DIRECCION_COMPLEMENTO – Path	COLUMN NAME	UY_L1_DIRECCION_COMPLEMENTO
UY_L1_CUENTA_BANCARIA – Path	COLUMN NAME	UY_L1_CUENTA_BANCARIA
UY_L1_TARJETA – Path	COLUMN NAME	UY_L1_TARJETA

CLASSIFIER	KIND	DOMAIN
UY_L1_TARJETA – Regex	VALUE FORMAT	UY_L1_TARJETA
UY_L1_BILLETERA – Path	COLUMN NAME	UY_L1_BILLETERA
UY_L1_BILLETERA – Regex	VALUE FORMAT	UY_L1_BILLETERA
UY_L1_IP – Path	COLUMN NAME	UY_L1_IP
UY_L1_IP – Regex	VALUE FORMAT	UY_L1_IP
UY_L1_DISPOSITIVO – Path	COLUMN NAME	UY_L1_DISPOSITIVO
UY_L1_DISPOSITIVO – Regex	VALUE FORMAT	UY_L1_DISPOSITIVO
UY_L1_COOKIE – Path	COLUMN NAME	UY_L1_COOKIE
UY_L1_PLACA – Path	COLUMN NAME	UY_L1_PLACA
UY_L1_PLACA – Regex	VALUE FORMAT	UY_L1_PLACA
UY_L1_VEHICULO – Path	COLUMN NAME	UY_L1_VEHICULO
UY_L1_VEHICULO – Regex	VALUE FORMAT	UY_L1_VEHICULO
UY_L1_INMUEBLE – Path	COLUMN NAME	UY_L1_INMUEBLE
UY_L1_CONTRATO – Path	COLUMN NAME	UY_L1_CONTRATO
UY_L1_USUARIO – Path	COLUMN NAME	UY_L1_USUARIO
UY_L1_CREDENCIAL – Path	COLUMN NAME	UY_L1_CREDENCIAL
UY_L1_CREDENCIAL – Regex	VALUE FORMAT	UY_L1_CREDENCIAL
UY_L1_GEOLOCALIZACION – Path	COLUMN NAME	UY_L1_GEOLOCALIZACION
UY_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	UY_L1_GEOLOCALIZACION
UY_L1_TEXTO_LIBRE – Path	COLUMN NAME	UY_L1_TEXTO_LIBRE
UY_L1_TEXTO_LIBRE – Type	DATA TYPE	UY_L1_TEXTO_LIBRE
UY_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	UY_L1_TEXTO_LIBRE
UY_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	UY_L2_FECHA_NACIMIENTO
UY_L2_FECHA_NACIMIENTO – Type	DATA TYPE	UY_L2_FECHA_NACIMIENTO
UY_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	UY_L2_ANIO_NACIMIENTO
UY_L2_ANIO_NACIMIENTO – Type	DATA TYPE	UY_L2_ANIO_NACIMIENTO
UY_L2_EDAD – Path	COLUMN NAME	UY_L2_EDAD
UY_L2_EDAD – Type	DATA TYPE	UY_L2_EDAD
UY_L2_FECHA_EVENTO – Path	COLUMN NAME	UY_L2_FECHA_EVENTO
UY_L2_FECHA_EVENTO – Type	DATA TYPE	UY_L2_FECHA_EVENTO
UY_L2_SEXO – Path	COLUMN NAME	UY_L2_SEXO
UY_L2_SEXO – List	KNOWN VALUES	UY_L2_SEXO
UY_L2_LOCALIDAD – Path	COLUMN NAME	UY_L2_LOCALIDAD
UY_L2_LOCALIDAD – Values	VALUE FORMAT	UY_L2_LOCALIDAD
UY_L2_CODIGO_INE – Path	COLUMN NAME	UY_L2_CODIGO_INE
UY_L2_CODIGO_INE – Regex	VALUE FORMAT	UY_L2_CODIGO_INE
UY_L2_BARRIO – Path	COLUMN NAME	UY_L2_BARRIO

CLASSIFIER	KIND	DOMAIN
UY_L2_CODIGO_POSTAL – Path	COLUMN NAME	UY_L2_CODIGO_POSTAL
UY_L2_CODIGO_POSTAL – Type	DATA TYPE	UY_L2_CODIGO_POSTAL
UY_L2_ESTADO_CIVIL – Path	COLUMN NAME	UY_L2_ESTADO_CIVIL
UY_L2_ESTADO_CIVIL – Values	VALUE FORMAT	UY_L2_ESTADO_CIVIL
UY_L2_OCUPACION – Path	COLUMN NAME	UY_L2_OCUPACION
UY_L2_EMPLEADOR – Path	COLUMN NAME	UY_L2_EMPLEADOR
UY_L2_NIVEL_EDUCATIVO – Path	COLUMN NAME	UY_L2_NIVEL_EDUCATIVO
UY_L2_NIVEL_EDUCATIVO – Values	VALUE FORMAT	UY_L2_NIVEL_EDUCATIVO
UY_L2_INSTITUCION_EDUCATIVA – Path	COLUMN NAME	UY_L2_INSTITUCION_EDUCATIVA
UY_L2_PERSONAS_A_CARGO – Path	COLUMN NAME	UY_L2_PERSONAS_A_CARGO
UY_L2_PERSONAS_A_CARGO – Type	DATA TYPE	UY_L2_PERSONAS_A_CARGO
UY_L3_ASCENDENCIA – Path	COLUMN NAME	UY_L3_ASCENDENCIA
UY_L3_ASCENDENCIA – Values	VALUE FORMAT	UY_L3_ASCENDENCIA
UY_L3_PUEBLO_ORIGINARIO – Path	COLUMN NAME	UY_L3_PUEBLO_ORIGINARIO
UY_L3_PUEBLO_ORIGINARIO – Values	VALUE FORMAT	UY_L3_PUEBLO_ORIGINARIO
UY_L3_NACIONALIDAD – Path	COLUMN NAME	UY_L3_NACIONALIDAD
UY_L3_NACIONALIDAD – List	KNOWN VALUES	UY_L3_NACIONALIDAD
UY_L3_RELIGION – Path	COLUMN NAME	UY_L3_RELIGION
UY_L3_RELIGION – Values	VALUE FORMAT	UY_L3_RELIGION
UY_L3_CONVICCION_MORAL – Path	COLUMN NAME	UY_L3_CONVICCION_MORAL
UY_L3_PREFERENCIA_POLITICA – Path	COLUMN NAME	UY_L3_PREFERENCIA_POLITICA
UY_L3_PREFERENCIA_POLITICA – Values	VALUE FORMAT	UY_L3_PREFERENCIA_POLITICA
UY_L3_AFILIACION_PARTIDARIA – Path	COLUMN NAME	UY_L3_AFILIACION_PARTIDARIA
UY_L3_AFILIACION_PARTIDARIA – Values	VALUE FORMAT	UY_L3_AFILIACION_PARTIDARIA
UY_L3_AFILIACION_SINDICAL – Path	COLUMN NAME	UY_L3_AFILIACION_SINDICAL
UY_L3_AFILIACION_SINDICAL – Values	VALUE FORMAT	UY_L3_AFILIACION_SINDICAL
UY_L3_BIOMETRICO – Path	COLUMN NAME	UY_L3_BIOMETRICO
UY_L3_BIOMETRICO – Type	DATA TYPE	UY_L3_BIOMETRICO
UY_L3_GENETICO – Path	COLUMN NAME	UY_L3_GENETICO
UY_L3_GENETICO – Regex	VALUE FORMAT	UY_L3_GENETICO
UY_L3_ORIENTACION_SEXUAL – Path	COLUMN NAME	UY_L3_ORIENTACION_SEXUAL
UY_L3_ORIENTACION_SEXUAL – Values	VALUE FORMAT	UY_L3_ORIENTACION_SEXUAL
UY_L3_VIDA_SEXUAL – Path	COLUMN NAME	UY_L3_VIDA_SEXUAL
UY_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	UY_L3_IDENTIDAD_GENERO
UY_L3_IDENTIDAD_GENERO – Values	VALUE FORMAT	UY_L3_IDENTIDAD_GENERO
UY_L3_VICTIMA – Path	COLUMN NAME	UY_L3_VICTIMA
UY_SALUD_IDENTIFICADOR – Path	COLUMN NAME	UY_SALUD_IDENTIFICADOR

CLASSIFIER	KIND	DOMAIN
UY_SALUD_COBERTURA – Path	COLUMN NAME	UY_SALUD_COBERTURA
UY_SALUD_COBERTURA – Values	VALUE FORMAT	UY_SALUD_COBERTURA
UY_SALUD_DIAGNOSTICO – Path	COLUMN NAME	UY_SALUD_DIAGNOSTICO
UY_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	UY_SALUD_DIAGNOSTICO
UY_SALUD_PROCEDIMIENTO – Path	COLUMN NAME	UY_SALUD_PROCEDIMIENTO
UY_SALUD_MEDICAMENTO – Path	COLUMN NAME	UY_SALUD_MEDICAMENTO
UY_SALUD_MEDICAMENTO – Values	VALUE FORMAT	UY_SALUD_MEDICAMENTO
UY_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	UY_SALUD_TEXTO_CLINICO
UY_SALUD_TEXTO_CLINICO – Type	DATA TYPE	UY_SALUD_TEXTO_CLINICO
UY_SALUD_RESULTADO_EXAMEN – Path	COLUMN NAME	UY_SALUD_RESULTADO_EXAMEN
UY_SALUD_VIH – Path	COLUMN NAME	UY_SALUD_VIH
UY_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	UY_SALUD_GRUPO_SANGUINEO
UY_SALUD_GRUPO_SANGUINEO – Values	VALUE FORMAT	UY_SALUD_GRUPO_SANGUINEO
UY_SALUD_DISCAPACIDAD – Path	COLUMN NAME	UY_SALUD_DISCAPACIDAD
UY_SALUD_DISCAPACIDAD – Values	VALUE FORMAT	UY_SALUD_DISCAPACIDAD
UY_SALUD_OCUPACIONAL – Path	COLUMN NAME	UY_SALUD_OCUPACIONAL
UY_SALUD_OCUPACIONAL – Values	VALUE FORMAT	UY_SALUD_OCUPACIONAL
UY_SALUD_REPRODUCTIVA – Path	COLUMN NAME	UY_SALUD_REPRODUCTIVA
UY_SALUD_MENTAL – Path	COLUMN NAME	UY_SALUD_MENTAL
UY_FIN_HISTORIAL_CREDITICIO – Path	COLUMN NAME	UY_FIN_HISTORIAL_CREDITICIO
UY_FIN_DEUDA – Path	COLUMN NAME	UY_FIN_DEUDA
UY_FIN_DEUDA – Type	DATA TYPE	UY_FIN_DEUDA
UY_FIN_INGRESOS – Path	COLUMN NAME	UY_FIN_INGRESOS
UY_FIN_INGRESOS – Type	DATA TYPE	UY_FIN_INGRESOS
UY_FIN_PATRIMONIO – Path	COLUMN NAME	UY_FIN_PATRIMONIO
UY_FIN_PATRIMONIO – Type	DATA TYPE	UY_FIN_PATRIMONIO
UY_FIN_PENSION – Path	COLUMN NAME	UY_FIN_PENSION
UY_FIN_PENSION – Type	DATA TYPE	UY_FIN_PENSION
UY_FIN_PROGRAMA_SOCIAL – Path	COLUMN NAME	UY_FIN_PROGRAMA_SOCIAL
UY_FIN_PROGRAMA_SOCIAL – Values	VALUE FORMAT	UY_FIN_PROGRAMA_SOCIAL
UY_FIN_NIVEL_SOCIOECONOMICO – Path	COLUMN NAME	UY_FIN_NIVEL_SOCIOECONOMICO
UY_FIN_NIVEL_SOCIOECONOMICO – Values	VALUE FORMAT	UY_FIN_NIVEL_SOCIOECONOMICO
UY_FIN_VIVIENDA – Path	COLUMN NAME	UY_FIN_VIVIENDA
UY_FIN_VIVIENDA – Values	VALUE FORMAT	UY_FIN_VIVIENDA
UY_PENAL_ANTECEDENTES – Path	COLUMN NAME	UY_PENAL_ANTECEDENTES
UY_PENAL_EXPEDIENTE – Path	COLUMN NAME	UY_PENAL_EXPEDIENTE
UY_PENAL_EXPEDIENTE – Regex	VALUE FORMAT	UY_PENAL_EXPEDIENTE