DELPHIX CONTINUOUS COMPLIANCE · DISCOVERY POLICY

Portugal — GDPR and Lei n.º 58/2019

Discovery and masking of Portuguese personal data: the four numbers of the Cartão de Cidadão with valid check characters, the IBAN and NIB, the CPE of a supply point and the prescription number recomputed, concelhos, freguesias and postal codes generalized below 20,000 inhabitants, the special categories of article 9 and of article 35 of the Constitution, health, economic and tax data, and criminal records and contraordenações.

87	155	299
DATA CLASSES	CLASSIFIERS	ALGORITHMS

Discovery policy `PT – Lei 58 de 2019 – v1`

Version 1 of October 12, 2026 · Assignment threshold 60%

Contents

The first sections explain what the policy is for and how it works. The data class chapters then describe every data class: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the policy contains.

1	**About this discovery policy**	
2	**The law in Portugal: the Regulation, Lei n.º 58/2019 and the Constitution**	
3	**Pseudonymisation, anonymisation and copies outside production**	
4	**How sensitive data is discovered**	
5	**How data is masked**	
6	**Essential and extended packs**	
7	**Data classes at a glance**	

PART 8 · DIRECT IDENTIFIERS

8.1	**Cartão de Cidadão and civil identification number**	PT_L1_CARTAO_CIDADAO
8.2	**NIF of a natural person**	PT_L1_NIF
8.3	**Social Security identification number (NISS)**	PT_L1_NISS
8.4	**Passport**	PT_L1_PASSAPORTE
8.5	**Residence permit**	PT_L1_TITULO_RESIDENCIA
8.6	**Driving licence**	PT_L1_CARTA_CONDUCAO
8.7	**Student number**	PT_L1_NUMERO_ESTUDANTE
8.8	**Professional card**	PT_L1_CEDULA_PROFISSIONAL
8.9	**Given name**	PT_L1_NOME
8.10	**Surname**	PT_L1_APELIDO
8.11	**Full name**	PT_L1_NOME_COMPLETO
8.12	**Email address**	PT_L1_EMAIL
8.13	**Telephone**	PT_L1_TELEFONE
8.14	**Address**	PT_L1_MORADA
8.15	**Address detail**	PT_L1_MORADA_COMPLEMENTO
8.16	**IBAN and NIB**	PT_L1_CONTA_BANCARIA
8.17	**Payment card**	PT_L1_CARTAO_PAGAMENTO
8.18	**Digital wallet**	PT_L1_CARTEIRA_DIGITAL
8.19	**IP address**	PT_L1_IP
8.20	**Device identifier**	PT_L1_DISPOSITIVO
8.21	**Cookie and online identifier**	PT_L1_COOKIE
8.22	**Vehicle plate**	PT_L1_MATRICULA
8.23	**Vehicle identification**	PT_L1_VEICULO
8.24	**Property**	PT_L1_IMOVEL

8.25	CPE and CUI	PT_L1_PONTO_ENTREGA
8.26	Contract or customer number	PT_L1_CONTRATO
8.27	User name	PT_L1_UTILIZADOR
8.28	Credential	PT_L1_CREDENCIAL
8.29	Image and voice	PT_L1_IMAGEM
8.30	Geolocation	PT_L1_GEOLOCALIZACAO
8.31	Free text	PT_L1_TEXTO_LIVRE

PART 9 · QUASI-IDENTIFIERS

9.1	Birth date	PT_L2_DATA_NASCIMENTO
9.2	Birth year	PT_L2_ANO_NASCIMENTO
9.3	Age	PT_L2_IDADE
9.4	Date of a personal event	PT_L2_DATA_EVENTO
9.5	Sex	PT_L2_SEXO
9.6	Concelho	PT_L2_CONCELHO
9.7	Freguesia	PT_L2_FREGUESIA
9.8	Concelho or freguesia code (DICO and DICOFRE)	PT_L2_CODIGO_AUTARQUICO
9.9	Postal code	PT_L2_CODIGO_POSTAL
9.10	Nationality	PT_L2_NACIONALIDADE
9.11	Residence status	PT_L2_SITUACAO_RESIDENCIA
9.12	Marital status	PT_L2_ESTADO_CIVIL
9.13	Occupation	PT_L2_PROFISSAO
9.14	Employer	PT_L2_ENTIDADE_EMPREGADORA
9.15	Education	PT_L2_ESCOLARIDADE
9.16	School	PT_L2_ESTABELECIMENTO_ENSINO
9.17	Dependants and household	PT_L2_AGREGADO

PART 10 · SPECIAL CATEGORIES (ART. 9 GDPR AND ART. 35.º, N.º 3 OF THE CONSTITUTION)

10.1	Ethnic origin	PT_L3_ORIGEM_ETNICA
10.2	Religion	PT_L3_RELIGIAO
10.3	Philosophical belief	PT_L3_CONVICCAO_FILOSOFICA
10.4	Political opinion	PT_L3_OPINIAO_POLITICA
10.5	Party membership	PT_L3_FILIACAO_PARTIDARIA
10.6	Trade union membership	PT_L3_FILIACAO_SINDICAL
10.7	Biometric data	PT_L3_BIOMETRICO
10.8	Genetic data	PT_L3_GENETICO
10.9	Sexual orientation	PT_L3_ORIENTACAO_SEXUAL
10.10	Sex life	PT_L3_VIDA_SEXUAL

10.11	Gender identity	PT_L3_IDENTIDADE_GENERO
10.12	Victim of violence	PT_L3_VITIMA

PART 11 · HEALTH DATA (ART. 9 GDPR, ART. 29.º OF LEI N.º 58/2019 AND LEI N.º 12/2005)

11.1	Número de utente of the SNS	PT_SAUDE_NUMERO_UTENTE
11.2	Prescription number	PT_SAUDE_RECEITA
11.3	Clinical or subsystem identifier	PT_SAUDE_IDENTIFICADOR
11.4	Health subsystem and insurance	PT_SAUDE_SUBSISTEMA
11.5	Diagnosis	PT_SAUDE_DIAGNOSTICO
11.6	Procedure	PT_SAUDE_PROCEDIMENTO
11.7	Medicine	PT_SAUDE_MEDICAMENTO
11.8	Clinical text	PT_SAUDE_TEXTO_CLINICO
11.9	Test result	PT_SAUDE_RESULTADO_EXAME
11.10	HIV and sexually transmitted infections	PT_SAUDE_VIH
11.11	Blood group	PT_SAUDE_GRUPO_SANGUINEO
11.12	Disability	PT_SAUDE_INCAPACIDADE
11.13	Dependency	PT_SAUDE_DEPENDENCIA
11.14	Occupational health	PT_SAUDE_TRABALHO
11.15	Reproductive health	PT_SAUDE_REPRODUTIVA
11.16	Mental health	PT_SAUDE_MENTAL

PART 12 · ECONOMIC AND TAX DATA (ART. 64.º LGT)

12.1	Credit history	PT_FIN_CREDITO
12.2	Debt	PT_FIN_DIVIDA
12.3	Income	PT_FIN_RENDIMENTO
12.4	Assets	PT_FIN_PATRIMONIO
12.5	Pension	PT_FIN_PENSAO
12.6	Social benefit	PT_FIN_PRESTACAO_SOCIAL
12.7	Tax data	PT_FIN_FISCAL

PART 13 · CRIMINAL AND ADMINISTRATIVE OFFENCES (ART. 10 GDPR AND ART. 13.º, ALÍNEA B) OF LEI N.º 58/2019)

13.1	Criminal record	PT_PENAL_REGISTO_CRIMINAL
13.2	Certificate for work with minors	PT_PENAL_CERTIFICADO_MENORES
13.3	Case number	PT_PENAL_PROCESSO
13.4	Administrative offence	PT_PENAL_CONTRAORDENACAO
14	Check characters	
15	Where people live: concelhos, freguesias and postal codes	
16	Limits	

17	Verification
18	Sources
A	Algorithms
B	Files
C	Exclusion lists
D	Discovery policy and classifiers

1

About this discovery policy

This discovery policy finds the personal data in a Portuguese database and masks them, so that a copy outside production — for testing, development, training or analytics — no longer identifies anyone.

Masking only names and document numbers is not enough: a birth date, a sex and a small concelho already point at a handful of people, and 188 of Portugal's 308 concelhos have fewer than 20,000 inhabitants. The policy works through the layers where the risk is:

- **Direct identifiers** — the numbers of the Cartão de Cidadão (civil identification number and document number, NIF, NISS; the número de utente is with health), passport, residence permit, driving licence, student number and professional card, names, contact, address, bank accounts, cards, devices, cookies, plates, the artigo matricial of a property, the CPE of an electricity or gas supply, photographs, free text.
- **Quasi-identifiers** — birth date, birth year, age, sex, concelho, freguesia and their codes, postal code, nationality and residence status, marital status, occupation, employer, education, household.
- **Special categories** — the data of article 9 of the Regulation and of article 35, n.º 3 of the Constitution: ethnic origin, political opinions and party membership, religious or philosophical beliefs, trade union membership, genetic and biometric data, sex life and sexual orientation; with gender identity and victims of domestic violence, which Portuguese law protects on their own.
- **Health data** — the número de utente of the SNS, the prescription number, health subsystems such as the ADSE, diagnoses, procedures, medicines, HIV, disability and dependency, occupational health, reproductive and mental health.
- **Economic data** — the Central de Responsabilidades de Crédito and the PERSI, debts, income, assets, pensions, social benefits, and the tax data article 64 of the Lei Geral Tributária keeps confidential.
- **Criminal and contraordenacional offences** — criminal records, the certificate for work with minors, case numbers, and contraordenações such as fines and the points of the driving licence.

Each group below says what each data class is, how it is masked and why. Discovery runs a discovery policy of 155 classifiers at a threshold of 60; masking is 87 data classes with their algorithms. Column names are recognised in European Portuguese and in English; values, in Portuguese spelling — `telemóvel`, `morada`, `apelido`, `freguesia`.

2

The law in Portugal: the Regulation, Lei n.º 58/2019 and the Constitution

Portugal has no data protection law of its own: the law is the **General Data Protection Regulation**, Regulation (EU) 2016/679, which applies directly, and **Lei n.º 58/2019, de 8 de agosto**, which "assegura a execução, na ordem jurídica nacional" of the Regulation and fills the room it leaves to the Member States. Lei n.º 58/2019 has not been amended since it was published. The supervisory authority is the **Comissão Nacional de Proteção de Dados** (CNPD), an independent administrative body attached to the Assembleia da República (arts. 3.º and 4.º).

The right itself is older than the Regulation: **article 35.º of the 1976 Constitution** was one of the first constitutional provisions anywhere on computing. Its n.º 3 says that "a informática não pode ser utilizada para tratamento de dados referentes a convicções filosóficas ou políticas, filiação partidária ou sindical, fé religiosa, vida privada e origem étnica" — computers may not process data on philosophical or political convictions, party or union membership, religious faith, private life and ethnic origin — save express consent,

a legal authorisation with guarantees of non-discrimination, or "dados estatísticos não individualmente identificáveis". Its n.º 4 forbids access to third parties' personal data, and its n.º 5 says: **"É proibida a atribuição de um número nacional único aos cidadãos"** — no single national number. That is why the Cartão de Cidadão carries four numbers from four separate registers, and Lei n.º 7/2007 forbids interconnecting them (art. 16.º, n.º 2); this policy masks each one on its own, and none is derived from another.

The Regulation protects **natural persons** only: article 4.1 defines personal data as information relating to a natural person, and recital 14 leaves legal persons out. So the NIF of a company and the NISS of a legal person pass through this policy untouched, while the NIF of a sole trader is masked like any other.

Lei n.º 58/2019 shapes this policy at several points:

- **Article 21.º, n.º 4** — "Quando cesse a finalidade que motivou o tratamento, inicial ou posterior, de dados pessoais, o responsável pelo tratamento deve proceder à sua destruição ou anonimização": when the purpose ends, destroy or anonymise.
- **Article 29.º** — health and genetic data follow the principle of **need to know** (n.º 1), are accessible only to people bound by secrecy (n.os 2 and 4), and **the data subject must be notified of any access** to their data (n.º 6), with an electronic log of accesses (n.º 7). A development team has no need to know anyone's health.
- **Article 31.º** — processing for archiving, research or statistics must "incluir a anonimização ou a pseudonimização" wherever the purposes can be reached that way (n.º 1), and statistical data must be anonymised or pseudonymised (n.º 5).
- **Article 28.º, n.º 6** — an employer may process workers' biometric data only for attendance and access control, and only as representations whose collection "não permita a reversibilidade".
- **Article 17.º** — the data of **deceased persons** stay protected when they are special categories or concern the intimacy of private life, image or communications.
- **Article 16.º** — the age of digital consent is **13**.
- **Article 13.º, alínea b)** — speaks of data "relacionados com condenações penais e contraordenacionais": in Portugal, administrative offences count too.

Infringements are in articles 37.º and 38.º. Processing special categories outside article 9, or criminal data outside article 10, is a **very serious infringement** (art. 37.º, n.º 1, d) and e)), and breaching the security rules of article 32 of the Regulation a serious one (art. 38.º, n.º 1, i)). The CNPD decided, in **Deliberação 2019/494** of 3 September 2019, to disapply nine provisions of the law on grounds of the primacy of Union law — among them the fine ranges of articles 37.º, n.º 2 and 38.º, n.º 2 —, and so applies those of article 83 of the Regulation directly: up to 20 million euros or 4% of worldwide turnover. Alíneas d) and e) of article 37.º, n.º 1 still apply for the limitation periods.

And the law has **crimes**, which the Regulation does not. Article 46.º punishes using personal data in a way incompatible with the purpose of collection; article 47.º, undue access; and **article 48.º, "Desvio de dados"** (diversion of data), punishes with up to one year in prison or a fine "quem copiar, subtrair, ceder ou transferir, a título oneroso ou gratuito, dados pessoais sem previsão legal ou consentimento, independentemente da finalidade prosseguida" — whoever copies personal data without a legal basis or consent, whatever the purpose. In all three the penalty doubles for the data of articles 9 and 10 of the Regulation, and attempt is punishable (art. 53.º).

Pseudonymisation, anonymisation and copies outside production

The Regulation names the technique. Article 4.5 defines **pseudonymisation** as processing personal data so that they can no longer be attributed to a specific person without the use of additional information, "provided that such additional information is kept separately and is subject to technical and organisational measures". Recital 26 leaves anonymous information outside the Regulation altogether and measures identifiability by "all the means reasonably likely to be used". Article 25.1 names pseudonymisation as the first example of data protection by design, article 32.1 a) as the first example of a security measure, and article 6.4 e) as a safeguard that makes further processing compatible with the original purpose.

Masking with the engine is pseudonymisation in exactly that sense: the result is deterministic for the engine's key, and whoever has the key and the production data can reproduce the mapping. A masked copy is still personal data **for whoever can reach the key**, and the key must be kept apart from the copy. The Court of Justice drew the consequence on 4 September 2025 in **EDPS v SRB (C-413/23 P)**: pseudonymised data may not be personal data for a recipient with no reasonable means to re-identify them, while they remain so for whoever holds the additional information. The European Data Protection Board said the same in its Guidelines 01/2025 on pseudonymisation of 16 January 2025, and on 7 July 2026 adopted Guidelines on anonymisation, open for public consultation until 30 October 2026, under which removing direct identifiers is not enough while a risk of re-identification remains — the reason for layers L2 and L3 of this policy.

Portuguese law is more direct than the Regulation about the copy itself. A copy of production for a test environment is processing for a purpose other than the collection; article 48.º of Lei n.º 58/2019 makes **copying personal data without a legal basis or consent a crime**, "independentemente da finalidade prosseguida", and article 46.º does the same with incompatible use. A masked copy is no longer, for whoever works with it, the copy of personal data those articles speak of.

For the public administration there is a technical rule. **Resolução do Conselho de Ministros n.º 41/2018**, of 28 March, approved the minimum technical requirements for the State's networks and information systems that process personal data — binding on the direct and indirect administration and recommended to State-owned companies —, and among the requirements of the **database layer** is **"mascaramento, anonimização ou, sendo necessário, cifra dos dados pessoais transmitidos ou acedidos"** — masking, anonymisation or, where necessary, encryption of the personal data transmitted or accessed —, beside a log of every action on personal data. Article 58.º of Lei n.º 58/2019 refers to those technical guidelines.

In health, **Lei n.º 12/2005** (personal genetic information and health information) asks health units to keep "a separação entre a informação de saúde e genética e a restante informação pessoal" and admits access for research only to **anonymised** information (art. 4.º). A clinical database copied for testing without masking undoes that separation.

4

How sensitive data is discovered

A discovery job looks at every column of its rule set and asks each classifier of the discovery policy how confident it is that the column belongs to its data class. The policy uses the four classifier frameworks of Delphix:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the data class out. It never assigns a data class on its own.

- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per data class, and the column is assigned to the data class with the highest confidence when it reaches the assignment threshold of the discovery policy — **60%** here. Values that do not match a format or a list count against their data class by the classifier's reject strength.

These are the names Data Control Tower gives the objects: data classes, classifiers and a discovery policy, run by a discovery job. A Continuous Compliance Engine used on its own calls the same objects domains, classifiers and a profile set, run by a profiling job; everything in this document applies to both.

Databases pad values: a CHAR column fills them with spaces up to its length, and a numeric code kept as text often comes with zeros on the left. Discovery tests values as they come, so every format pattern first removes the spaces around the value, patterns of digits also accept zeros on the left, lists of single words are looked up word by word, and lists of names made of several words (places, categories) are held as a single value-format pattern. A column whose name says nothing — `CAMPO1`, `FLD_07`, the short names of packaged systems — is found by its values alone wherever their format is distinctive: documents with a check digit, e-mail addresses, telephone numbers, cards, places, names.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

> Discovery proposes; it does not decide. Review the data classes assigned in the rule set before running a masking job, and look for columns the policy left unassigned.

5

How data is masked

Each data class names one algorithm, which a masking job applies to every column the rule set assigns to the data class. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each data class shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine and compliance node uses the same keys.

Where an algorithm that comes with Delphix already does the job — CM Numeric for amounts, Credit Card, the blood group lookup — the policy names it instead of creating one of its own. Those algorithms appear in the trees by their `dlpx-core:` name, the one an engine uses; Data Control Tower lists them without the prefix (`CM Numeric`, `CreditCard`, `BloodType SL`). They are on every engine and in every Data Control Tower, and are not listed in Appendix A.

Padding stays where it is: the spaces around a value are kept, and zeros on the left of a number are not masked — `0012345678` becomes `00` followed by what `12345678` becomes. A value kept in a zero-filled CHAR column still joins the same value kept as a number.

> The masked examples in this document were produced with one particular key. With other keys the masked values differ; their shape does not.

6

Essential and extended packs

The policy can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create just its data classes, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the discovery policy.

PACK	DATA CLASSES	CLASSIFIERS	ALGORITHMS	FILES
Essential	14	31	72	9
Extended	87	155	299	67

The essential pack holds these data classes, marked **Essential** in the tables and chapters:

- Cartão de Cidadão and civil identification number — `PT_L1_CARTAO_CIDADAO`
- NIF of a natural person — `PT_L1_NIF`
- Social Security identification number (NISS) — `PT_L1_NISS`
- Passport — `PT_L1_PASSAPORTE`
- Residence permit — `PT_L1_TITULO_RESIDENCIA`
- Given name — `PT_L1_NOME`
- Surname — `PT_L1_APELIDO`
- Full name — `PT_L1_NOME_COMPLETO`
- Email address — `PT_L1_EMAIL`
- Telephone — `PT_L1_TELEFONE`
- Address — `PT_L1_MORADA`
- Address detail — `PT_L1_MORADA_COMPLEMENTO`
- Birth date — `PT_L2_DATA_NASCIMENTO`
- Número de utente of the SNS — `PT_SAUDE_NUMERO_UTENTE`

> With fewer data classes competing, a column that a data class of the extended pack would claim by its name can be proposed for an essential data class instead — a numeric code, for instance, can look like a telephone number. Review the discovery result.

7

Data classes at a glance

Every data class of the policy, how it is found and the algorithm that masks it.

DATA CLASS	FOUND BY	ALGORITHM
DIRECT IDENTIFIERS		
Cartão de Cidadão and civil identification number ESSENTIAL `PT_L1_CARTAO_CIDADAO`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PT_IDENTIFICACAO`
NIF of a natural person ESSENTIAL `PT_L1_NIF`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PT_NIF`
Social Security identification number (NISS) ESSENTIAL `PT_L1_NISS`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PT_NISS`
Passport ESSENTIAL `PT_L1_PASSAPORTE`	COLUMN NAME · VALUE FORMAT	`PT_CM_DIGITOS_LETRAS`
Residence permit ESSENTIAL `PT_L1_TITULO_RESIDENCIA`	COLUMN NAME	`PT_CM_ALFANUM`
Driving licence `PT_L1_CARTA_CONDUCAO`	COLUMN NAME	`PT_CM_DIGITOS_LETRAS`
Student number `PT_L1_NUMERO_ESTUDANTE`	COLUMN NAME	`PT_CM_ALFANUM`
Professional card `PT_L1_CEDULA_PROFISSIONAL`	COLUMN NAME	`PT_CM_ALFANUM`
Given name ESSENTIAL `PT_L1_NOME`	COLUMN NAME · KNOWN VALUES	`PT_NOMES`
Surname ESSENTIAL `PT_L1_APELIDO`	COLUMN NAME · KNOWN VALUES	`PT_APELIDOS`
Full name ESSENTIAL `PT_L1_NOME_COMPLETO`	COLUMN NAME · KNOWN VALUES	`PT_NOME_COMPLETO`
Email address ESSENTIAL `PT_L1_EMAIL`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PT_EMAIL`
Telephone ESSENTIAL `PT_L1_TELEFONE`	COLUMN NAME · VALUE FORMAT	`PT_TELEFONE`
Address ESSENTIAL `PT_L1_MORADA`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PT_MORADA`
Address detail ESSENTIAL `PT_L1_MORADA_COMPLEMENTO`	COLUMN NAME	`PT_CM_ALFANUM`
IBAN and NIB `PT_L1_CONTA_BANCARIA`	COLUMN NAME · VALUE FORMAT	`PT_CONTA`
Payment card `PT_L1_CARTAO_PAGAMENTO`	COLUMN NAME · VALUE FORMAT	`PT_CARTAO`
Digital wallet `PT_L1_CARTEIRA_DIGITAL`	COLUMN NAME · VALUE FORMAT	`PT_CM_ALFANUM`

DATA CLASS	FOUND BY	ALGORITHM
IP address `PT_L1_IP`	COLUMN NAME · VALUE FORMAT	`PT_IP`
Device identifier `PT_L1_DISPOSITIVO`	COLUMN NAME · VALUE FORMAT	`PT_CM_HEX`
Cookie and online identifier `PT_L1_COOKIE`	COLUMN NAME	`PT_CM_ALFANUM`
Vehicle plate `PT_L1_MATRICULA`	COLUMN NAME · VALUE FORMAT	`PT_MATRICULA`
Vehicle identification `PT_L1_VEICULO`	COLUMN NAME · VALUE FORMAT	`PT_CM_ALFANUM`
Property `PT_L1_IMOVEL`	COLUMN NAME · VALUE FORMAT	`PT_IMOVEL`
CPE and CUI `PT_L1_PONTO_ENTREGA`	COLUMN NAME · VALUE FORMAT	`PT_CPE`
Contract or customer number `PT_L1_CONTRATO`	COLUMN NAME	`PT_CM_ALFANUM`
User name `PT_L1_UTILIZADOR`	COLUMN NAME	`PT_CM_ALFANUM`
Credential `PT_L1_CREDENCIAL`	COLUMN NAME · VALUE FORMAT	`PT_REDIGIR`
Image and voice `PT_L1_IMAGEM`	COLUMN NAME	`PT_REDIGIR`
Geolocation `PT_L1_GEOLOCALIZACAO`	COLUMN NAME · VALUE FORMAT	`PT_COORDENADA`
Free text `PT_L1_TEXTO_LIVRE`	COLUMN NAME · DATA TYPE · VALUE FORMAT	`PT_TEXTO_LIVRE`
QUASI-IDENTIFIERS		
Birth date ESSENTIAL `PT_L2_DATA_NASCIMENTO`	COLUMN NAME · DATA TYPE	`PT_DATA_NASCIMENTO`
Birth year `PT_L2_ANO_NASCIMENTO`	COLUMN NAME · DATA TYPE	`PT_ANO`
Age `PT_L2_IDADE`	COLUMN NAME · DATA TYPE	`PT_IDADE`
Date of a personal event `PT_L2_DATA_EVENTO`	COLUMN NAME · DATA TYPE	`PT_DATA_EVENTO`
Sex `PT_L2_SEXO`	COLUMN NAME · KNOWN VALUES	`PT_SEXO`
Concelho `PT_L2_CONCELHO`	COLUMN NAME · VALUE FORMAT	`PT_CONCELHO`
Freguesia `PT_L2_FREGUESIA`	COLUMN NAME · VALUE FORMAT	`PT_FREGUESIA`
Concelho or freguesia code (DICO and DICOFRE) `PT_L2_CODIGO_AUTARQUICO`	COLUMN NAME · VALUE FORMAT	`PT_CODIGO_AUTARQUICO`
Postal code `PT_L2_CODIGO_POSTAL`	COLUMN NAME · VALUE FORMAT	`PT_CODIGO_POSTAL`

DATA CLASS	FOUND BY	ALGORITHM
Nationality `PT_L2_NACIONALIDADE`	COLUMN NAME VALUE FORMAT	`PT_NACIONALIDADE`
Residence status `PT_L2_SITUACAO_RESIDENCIA`	COLUMN NAME VALUE FORMAT	`PT_SITUACAO_RESIDENCIA`
Marital status `PT_L2_ESTADO_CIVIL`	COLUMN NAME VALUE FORMAT	`PT_ESTADO_CIVIL`
Occupation `PT_L2_PROFISSAO`	COLUMN NAME	`PT_PROFISSAO_OU_CODIGO`
Employer `PT_L2_ENTIDADE_EMPREGADORA`	COLUMN NAME	`PT_ENTIDADE_EMPREGADORA`
Education `PT_L2_ESCOLARIDADE`	COLUMN NAME VALUE FORMAT	`PT_ESCOLARIDADE`
School `PT_L2_ESTABELECIMENTO_ENSINO`	COLUMN NAME	`PT_ESTABELECIMENTO_ENSINO`
Dependants and household `PT_L2_AGREGADO`	COLUMN NAME DATA TYPE	`PT_CONTAGEM_LIMITADA`
SPECIAL CATEGORIES (ART. 9 GDPR AND ART. 35.º, N.º 3 OF THE CONSTITUTION)		
Ethnic origin `PT_L3_ORIGEM_ETNICA`	COLUMN NAME VALUE FORMAT	`PT_ORIGEM_ETNICA`
Religion `PT_L3_RELIGIAO`	COLUMN NAME VALUE FORMAT	`PT_RELIGIAO`
Philosophical belief `PT_L3_CONVICCAO_FILOSOFICA`	COLUMN NAME	`PT_CATEGORIA_SUPRIMIDA`
Political opinion `PT_L3_OPINIAO_POLITICA`	COLUMN NAME VALUE FORMAT	`PT_OPINIAO_POLITICA`
Party membership `PT_L3_FILIACAO_PARTIDARIA`	COLUMN NAME VALUE FORMAT	`PT_PARTIDO`
Trade union membership `PT_L3_FILIACAO_SINDICAL`	COLUMN NAME VALUE FORMAT	`PT_CATEGORIA_SUPRIMIDA`
Biometric data `PT_L3_BIOMETRICO`	COLUMN NAME DATA TYPE	`PT_REDIGIR`
Genetic data `PT_L3_GENETICO`	COLUMN NAME VALUE FORMAT	`PT_REDIGIR`
Sexual orientation `PT_L3_ORIENTACAO_SEXUAL`	COLUMN NAME VALUE FORMAT	`PT_ORIENTACAO_SEXUAL`
Sex life `PT_L3_VIDA_SEXUAL`	COLUMN NAME	`PT_CATEGORIA_SUPRIMIDA`
Gender identity `PT_L3_IDENTIDADE_GENERO`	COLUMN NAME VALUE FORMAT	`PT_IDENTIDADE_GENERO`
Victim of violence `PT_L3_VITIMA`	COLUMN NAME	`PT_CATEGORIA_SUPRIMIDA`
HEALTH DATA (ART. 9 GDPR, ART. 29.º OF LEI N.º 58/2019 AND LEI N.º 12/2005)		
Número de utente of the SNS ESSENTIAL `PT_SAUDE_NUMERO_UTENTE`	COLUMN NAME DATA TYPE	`PT_NUMERO_UTENTE`

DATA CLASS	FOUND BY	ALGORITHM
Prescription number `PT_SAUDE_RECEITA`	COLUMN NAME · VALUE FORMAT	`PT_NUMERO_RECEITA`
Clinical or subsystem identifier `PT_SAUDE_IDENTIFICADOR`	COLUMN NAME	`PT_CM_ALFANUM`
Health subsystem and insurance `PT_SAUDE_SUBSISTEMA`	COLUMN NAME · VALUE FORMAT	`PT_COBERTURA_SAUDE`
Diagnosis `PT_SAUDE_DIAGNOSTICO`	COLUMN NAME · VALUE FORMAT	`PT_DIAGNOSTICO`
Procedure `PT_SAUDE_PROCEDIMENTO`	COLUMN NAME	`PT_PROCEDIMENTO`
Medicine `PT_SAUDE_MEDICAMENTO`	COLUMN NAME · VALUE FORMAT	`PT_MEDICAMENTO`
Clinical text `PT_SAUDE_TEXTO_CLINICO`	COLUMN NAME · DATA TYPE	`PT_TEXTO_LIVRE`
Test result `PT_SAUDE_RESULTADO_EXAME`	COLUMN NAME	`PT_CM_ALFANUM`
HIV and sexually transmitted infections `PT_SAUDE_VIH`	COLUMN NAME	`PT_CATEGORIA_SUPRIMIDA`
Blood group `PT_SAUDE_GRUPO_SANGUINEO`	COLUMN NAME · VALUE FORMAT	`dlpx-core:BloodTypeSL`
Disability `PT_SAUDE_INCAPACIDADE`	COLUMN NAME · VALUE FORMAT	`PT_INCAPACIDADE`
Dependency `PT_SAUDE_DEPENDENCIA`	COLUMN NAME · VALUE FORMAT	`PT_DEPENDENCIA`
Occupational health `PT_SAUDE_TRABALHO`	COLUMN NAME · VALUE FORMAT	`PT_APTIDAO`
Reproductive health `PT_SAUDE_REPRODUTIVA`	COLUMN NAME	`PT_CATEGORIA_SUPRIMIDA`
Mental health `PT_SAUDE_MENTAL`	COLUMN NAME	`PT_CATEGORIA_SUPRIMIDA`
ECONOMIC AND TAX DATA (ART. 64.º LGT)		
Credit history `PT_FIN_CREDITO`	COLUMN NAME	`PT_HISTORICO_CREDITO`
Debt `PT_FIN_DIVIDA`	COLUMN NAME · DATA TYPE	`dlpx-core:CM Numeric`
Income `PT_FIN_RENDIMENTO`	COLUMN NAME · DATA TYPE	`dlpx-core:CM Numeric`
Assets `PT_FIN_PATRIMONIO`	COLUMN NAME · DATA TYPE	`dlpx-core:CM Numeric`
Pension `PT_FIN_PENSAO`	COLUMN NAME · DATA TYPE	`dlpx-core:CM Numeric`
Social benefit `PT_FIN_PRESTACAO_SOCIAL`	COLUMN NAME · VALUE FORMAT	`PT_PRESTACAO_SOCIAL`
Tax data `PT_FIN_FISCAL`	COLUMN NAME	`PT_FISCAL`

DATA CLASS	FOUND BY	ALGORITHM
CRIMINAL AND ADMINISTRATIVE OFFENCES (ART. 10 GDPR AND ART. 13.º, ALÍNEA B) OF LEI N.º 58/2019)		
Criminal record `PT_PENAL_REGISTO_CRIMINAL`	COLUMN NAME	`PT_REGISTO_CRIMINAL`
Certificate for work with minors `PT_PENAL_CERTIFICADO_MENORES`	COLUMN NAME VALUE FORMAT	`PT_CERTIFICADO_MENORES`
Case number `PT_PENAL_PROCESSO`	COLUMN NAME VALUE FORMAT	`PT_PROCESSO`
Administrative offence `PT_PENAL_CONTRAORDENACAO`	COLUMN NAME	`PT_CONTRAORDENACAO`

PART 8

Direct identifiers

Data that identify a person on their own. Portuguese identifiers carry check characters — the digit of the civil identification number and the last digit of the document number of the Cartão de Cidadão, the digit of the NIF and of the NISS, the two digits of the NIB, the two letters of the CPE — and every Portuguese system validates them, so the policy recomputes each one from the masked digits. The NIF of a company and the NISS of a legal person are no one's personal data and pass through untouched.

8.1 Cartão de Cidadão and civil identification number

PT_L1_CARTAO_CIDADAO

ESSENTIAL | COLUMN NAME | DATA TYPE | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The **número de identificação civil** — the old number of the bilhete de identidade — is eight digits and a **check digit** (Lei n.º 12/91): weights 9 down to 2, modulo 11, eleven minus the remainder, written 0 when that gives 10 or 11. The **document number** of the Cartão de Cidadão (Lei n.º 7/2007, art. 17.º) is that number, two characters of the card's version and a last check digit: `12345678 9 ZZ1`. The last digit is a Luhn digit computed over digits **and letters** (A = 10 … Z = 35).

The same data class takes what an identification column holds beside it: the civil number with or without its digit, an old bilhete de identidade of seven digits, a passport.

HOW IT IS FOUND

COLUMN NAME PT_L1_CARTAO_CIDADAO – Path

90%

`cc` `c_c` `cart[aã]o_?(de_?)?cidad[aã]o` `n(o|r|ro|um|umero)_?(cc|cart[aã]o_?cidad[aã]o|documento_?identifica[cç][aã]o|doc_?id|bi|identifica[cç][aã]o_?civil|id_?civil)` `bi` `b_i` `bilhete_?(de_?)?identidade` `nic` `n_i_c` `identifica[cç][aã]o_?civil` `doc_?identifica[cç][aã]o` `documento_?(de_?)?identifica[cç][aã]o` `num_?doc` `n_?doc` `identifica[cç][aã]o` *(except when preceded by* `(tipo|tp|cod|codigo|desc)_` *; except when followed by* `tipo` , `fiscal` , `seguran[cç]a` *)*

`(cliente|cli|utente|doente|paciente|utilizador|segurado|beneficiario|benef|titular|funcionario|trabalhador|colaborador|empregado|aluno|estudante|devedor|fiador|avalista|requerente|proprietario|arrendatario|inquilino|condutor|tomador|responsavel|representante|procurador|pessoa|cidadao|eleitor|contribuinte|fornecedor|socio|conjuge|pai|mae|filho|familiar|pensionista|reformado|interessado|declarante|herdeiro)_?(cc|bi|nic|doc|documento)` `(cc|bi)_?(cliente|cli|utente|doente|paciente|utilizador|segurado|beneficiario|benef|titular|funcionario|trabalhador|colaborador|empregado|aluno|estudante|devedor|fiador|avalista|requerente|proprietario|arrendatario|inquilino|condutor|tomador|responsavel|representante|procurador|pessoa|cidadao|eleitor|contribuinte|fornecedor|socio|conjuge|pai|mae|filho|familiar|pensionista|reformado|interessado|declarante|herdeiro)` `national_?id` `id_?number` `id_?card`

60%

`documento` `doc` `identificador`

DATA TYPE PT_L1_CARTAO_CIDADAO – Type

Accepts text (length 7 or more) or number (length 7 or more); any other type rules the data class out.

VALUE FORMAT PT_L1_CARTAO_CIDADAO — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{8}\s?\d\s?[A-Z0-9]{2}\d)`	95%	
`0*(?:\d{8}[\s\-]\d)`	60%	
`0*(?:\d{8})`	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The eight digits change; the **first check digit is recomputed** by Check Digit, whose rule is exactly the Portuguese one; the card's version stays; and the **last digit is recomputed** by a state — the sum so far and whether the next character doubles — that crosses the eleven characters one at a time, with a table of 1,300 lines, stepping over spaces and hyphens. The masked number is valid under both rules and belongs to no one. The civil number on its own and inside the document number use the same mapping, so the two still agree.

`PT_IDENTIFICACAO` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

> `PT_CC` STRING ALGORITHM CHAIN
>
> Applies `PT_CC_1` → `PT_CC_2` → `PT_CC_3`, in this order. It is made of 26 algorithms that repeat the same step position by position; each one is in Appendix A.
>
> `PT_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `PT_CM_DIGITOS_LETRAS` CHARACTER MAPPING
>
> Maps each character to another of its group (2 groups), keeping length and format.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`12345678 9 ZZ1`	→	**`46916122 1 ZZ8`**
`123456789ZY3`	→	**`469161221ZY0`**
`12345678-9`	→	**`46916122-1`**

8.2 NIF of a natural person

PT_L1_NIF

ESSENTIAL COLUMN NAME DATA TYPE VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The Número de Identificação Fiscal of the Autoridade Tributária: nine digits, the last a check digit by the same rule as the civil number. The first digit says what the taxpayer is: **1, 2 and 3** a natural person, **45** a non-resident natural person, **8** the old sole trader; **5** a company, **6** the public administration, **7** undivided inheritances, funds and other entities, **9** irregular companies and condominiums. Sometimes written with the VAT prefix `PT`.

HOW IT IS FOUND

COLUMN NAME PT_L1_NIF — Path

90% `nif` *(except when followed by list E1)* `n_i_f` `nifp?s` `n(o|r|ro|um|umero)_?(de_?)?(contribuinte|identifica[cç][aã]o_?fiscal|nif|fiscal)` `contribuinte` `num_?contrib` `n_?contrib` `identifica[cç][aã]o_?fiscal` `(cliente|cli|utente|doente|paciente|utilizador|segurado|beneficiario|benef|titular|funcionario|trabalhador|colaborador|empregado|aluno|estudante|devedor|fiador|avalista|requerente|proprietario|arrendatario|inquilino|condutor|tomador|responsavel|representante|procurador|pessoa|cidadao|eleitor|contribuinte|fornecedor|socio|conjuge|pai|mae|filho|familiar|pensionista|reformado|interessado|declarante|herdeiro)_?nif` `nif_?(cliente|cli|utente|doente|paciente|utilizador|segurado|beneficiario|benef|titular|funcionario|trabalhador|colaborador|empregado|aluno|estudante|devedor|fiador|avalista|requerente|proprietario|arrendatario|inquilino|condutor|tomador|responsavel|representante|procurador|pessoa|cidadao|eleitor|contribuinte|fornecedor|socio|conjuge|pai|mae|filho|familiar|pensionista|reformado|interessado|declarante|herdeiro)` `vat_?(no|number|id)?` `tax_?id` `tin`

50% `fiscal` `ident_?fiscal`

DATA TYPE PT_L1_NIF — Type

Accepts text (length 9 or more) or number (length 9 or more); any other type rules the data class out.

VALUE FORMAT PT_L1_NIF — Regex

PATTERN	STRENGTH	NOTES
`(PT\s?)?(?:[123]\d{2}|45\d)[\s\-.]?\d{3}[\s\-.]?\d{3}`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

A natural person's NIF keeps its first digit — still a person's —, the other seven change and the **check digit is recomputed** by Check Digit. The NIF of a company, a public body or an inheritance passes untouched: article 4.1 of the Regulation reaches natural persons only. The NIF is not the civil number: they share the rule, not the value, and each has its own mapping.

`PT_NIF` **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM` .

> `PT_NIF_CD` **CHECK DIGIT**
>
> Masks the digits with `PT_NIF_CORPO` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 8 9` from the right.
>
> > `PT_NIF_CORPO` **REGEX DECOMPOSE**
> >
> > Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.
> >
> > > `PT_CM_DIGITOS_LARGURA_FIXA` **CHARACTER MAPPING**
> > >
> > > Maps each character to another of its group (1 groups), keeping length and format.
>
> `PT_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
234567899	→	**291264611**
PT234567899	→	**PT291264611**
501964843	→	**501964843**

8.3 Social Security identification number (NISS)

PT_L1_NISS

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Eleven digits: **1** for a natural person, **2** for a legal person, nine digits and a check digit — nine minus the sum of the first ten with the weights 29, 23, 19, 17, 13, 11, 7, 5, 3 and 2, modulo 10.

HOW IT IS FOUND

COLUMN NAME PT_L1_NISS — Path

90% `niss` `n_i_s_s` `n(o|r|ro|um|umero)_?(de_?)?(identifica[cç][aã]o_?)?(da_?|na_?)?seguran[cç]a_?social` `n(o|r|ro|um|umero)_?(ss|benefici[aá]rio_?ss)` `seguran[cç]a_?social` `num_?ss` `nss` `n_?ss` `social_?security(_?number)?` `ssn`

DATA TYPE PT_L1_NISS — Type

Accepts text (length 11 or more) or number (length 11 or more); any other type rules the data class out.

VALUE FORMAT PT_L1_NISS — Regex

PATTERN	STRENGTH	NOTES
`0*(?:1\d{10})`	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

A person's NISS keeps its 1, the nine digits change and the **check digit is recomputed** by Check Digit: Check Digit writes ten minus the remainder, and giving the leading 1 the weight 0 instead of 29 adds exactly the unit that turns one rule into the other. A legal person's NISS passes untouched.

`PT_NISS` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM` .

- `PT_NISS_CD` CHECK DIGIT

  Masks the digits with `PT_NISS_CORPO` and recomputes a modulus 10 check digit with weights `2 3 5 7 11 13 17 19 23 0` from the right.

  - `PT_NISS_CORPO` REGEX DECOMPOSE

    Matches one pattern and gives each part of the value its own action; when none matches: keep.

    - `PT_CM_DIGITOS_LARGURA_FIXA` CHARACTER MAPPING

      Maps each character to another of its group (1 groups), keeping length and format.

- `PT_CM_ALFANUM` CHARACTER MAPPING

  Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
12345678902	→	**13218879830**
21234567890	→	**21234567890**

8.4 Passport

PT_L1_PASSAPORTE

ESSENTIAL · COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

The number of the Portuguese electronic passport: one or two letters and six digits.

HOW IT IS FOUND

COLUMN NAME PT_L1_PASSAPORTE — Path

90% `passaporte[a-z0-9_]*` `n(o|r|ro|um|umero)_?passaporte` `passport[a-z0-9_]*`

VALUE FORMAT PT_L1_PASSAPORTE — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{1,2}\d{6}`	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Letters become letters and digits digits, keeping the shape.

`PT_CM_DIGITOS_LETRAS` CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
CB123456	→	**NF254624**

8.5 Residence permit

PT_L1_TITULO_RESIDENCIA

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The number of the residence permit or card issued by the AIMA (Agência para a Integração, Migrações e Asilo, successor of the SEF), or of the registration certificate of a Union citizen. It has no public rule.

HOW IT IS FOUND

COLUMN NAME PT_L1_TITULO_RESIDENCIA — Path

90% `t[ií]tulo_?(de_?)?resid[eê]ncia` `autoriza[cç][aã]o_?(de_?)?resid[eê]ncia` `cart[aã]o_?(de_?)?resid[eê]ncia` `n(o|r|ro|um|umero)_?(t[ií]tulo|autoriza[cç][aã]o|cart[aã]o)_?(de_?)?resid[eê]ncia` `ar_?cplp` `certificado_?(de_?)?registo_?(de_?)?cidad[aã]o_?(da_?)?ue` `n(o|r|ro|um|umero)_?(sef|aima)` `residence_?permit`

HOW IT IS MASKED

Character by character: vowels for vowels, consonants for consonants, digits for digits; separators stay.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
A123456789	→	**0031407646**

8.6 Driving licence

PT_L1_CARTA_CONDUCAO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The number of the driving licence issued by the IMT. It has no public check-digit rule.

HOW IT IS FOUND

COLUMN NAME PT_L1_CARTA_CONDUCAO — Path

90% `carta_?(de_?)?condu[cç][aã]o` `n(o|r|ro|um|umero)_?carta(_?(de_?)?condu[cç][aã]o)?` `licen[cç]a_?(de_?)?condu[cç][aã]o` `driv(er|ing)_?licen[cs]e`

HOW IT IS MASKED

Letters become letters and digits digits, keeping the shape and the separators.

`PT_CM_DIGITOS_LETRAS` CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
L-123456 7	→	**D-795984 2**

8.7 Student number

PT_L1_NUMERO_ESTUDANTE

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

A pupil's or student's number at a school or university, or a staff number.

HOW IT IS FOUND

COLUMN NAME PT_L1_NUMERO_ESTUDANTE — Path

80% `n(o|r|ro|um|umero)_?(de_?)?(aluno|estudante|matr[ií]cula_?(aluno|estudante)|processo_?(do_?)?aluno|mecanogr[aá]fico)` `c[oó]digo_?(de_?)?(aluno|estudante)` `cod_?(aluno|estudante)` `id_?(aluno|estudante)` `processo_?(do_?)?aluno` `student_?(id|number)`

HOW IT IS MASKED

Character by character, keeping the shape.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
2012345	→	**0845072**

8.8 Professional card

PT_L1_CEDULA_PROFISSIONAL

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The registration number in a professional order — of physicians, nurses, lawyers, engineers — or the card of a certified accountant. In a record of medical acts it identifies the physician and, beside it, the patient.

HOW IT IS FOUND

COLUMN NAME PT_L1_CEDULA_PROFISSIONAL — Path

85% `c[eé]dula_?profissional` `n(o|r|ro|um|umero)_?(de_?)?(c[eé]dula|inscri[cç][aã]o_?(na_?)?ordem|ordem|ordem_?(dos_?)?(m[eé]dicos|enfermeiros|advogados|engenheiros|farmac[eê]uticos|psic[oó]logos))` `n(o|r|ro|um|umero)_?(om|oe|oa|occ)` `c[oó]digo_?(m[eé]dico|profissional)`

HOW IT IS MASKED

Character by character, keeping the shape.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
54321	→	**79669**

8.9 Given name

PT_L1_NOME

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

One or more given names — `Maria da Conceição`, `João Pedro`, `Inês`.

HOW IT IS FOUND

COLUMN NAME PT_L1_NOME — Path

85% `primeiro_?nome` `segundo_?nome` `nomes?_?pr[oó]prios?` `nome_?1` `nome_?2` `first_?names?` `given_?names?` `fname` `middle_?names?` `nomes` *(except when followed by `completos?`, `apelidos?`)*

50% `nome` *(except when followed by list E2)* `name` *(except when followed by list E3)*

KNOWN VALUES PT_L1_NOME — List

LIST	VALUES	STRENGTH	FIRST VALUES
`pt-detetar-nomes.txt`	362	70%	Maria, José, Jose, João, Joao, Ana

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Word by word from a list of 282 Portuguese given names, female and male, of several generations, with the case of the input. `de`, `da`, `do`, `dos`, `das` and `e` stay where they are.

`PT_NOMES` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

> `PT_PALAVRA_NOME` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `PT_NOME`.
>
> > `PT_NOME` NAME
> >
> > Replaces the name with one of the 282 names in `pt-nomes.txt`.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Maria da Conceição	→	**Leonardo da Sara**
JOÃO PEDRO	→	**MARCELO ALBERTINA**
Inês	→	**Tiago**

8.10 Surname

PT_L1_APELIDO

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

One or more surnames — `Ferreira dos Santos`, `Sousa e Silva`. In Portugal a person usually carries the mother's surname before the father's, up to four in all (Código do Registo Civil, art. 103.º).

HOW IT IS FOUND

COLUMN NAME PT_L1_APELIDO — Path

85% `apelidos?` `sobrenomes?` `[uú]ltimo_?nome` `apelido_?(1|2|materno|paterno)` `nome_?(de_?)?fam[ií]lia` `last_?names?` `surnames?` `family_?names?` `lname`

KNOWN VALUES PT_L1_APELIDO — List

LIST	VALUES	STRENGTH	FIRST VALUES
`pt-detetar-apelidos.txt`	498	70%	Silva, Santos, Ferreira, Pereira, Oliveira, Costa

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Word by word from a list of 425 Portuguese surnames, from the most frequent — Silva, Santos, Ferreira, Pereira — to less common ones; the particles stay.

`PT_APELIDOS` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

> `PT_PALAVRA_APELIDO` REGEX DECOMPOSE
>
> Matches one pattern and gives each part of the value its own action; when none matches: `PT_APELIDO`.
>
> > `PT_APELIDO` NAME
> >
> > Replaces the name with one of the 425 names in `pt-apelidos.txt`.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Ferreira dos Santos	→	**Coutinho dos Neves**
Sousa e Silva	→	**Saraiva e Ricardo**

8.11 Full name

PT_L1_NOME_COMPLETO

ESSENTIAL · COLUMN NAME · KNOWN VALUES · REGEX DECOMPOSE

WHAT IT IS

Given names and surnames in one column: `Maria da Conceição Ferreira dos Santos`, or `SILVA, JOÃO PEDRO` with the surnames first.

HOW IT IS FOUND

COLUMN NAME PT_L1_NOME_COMPLETO — Path

90% `nomes?_?(completos?|e_?apelidos?|apelidos?)` `apelidos?_?(e_?)?nomes?` `nome_?(do_?|da_?)?(cliente|cli|utente|doente|paciente|utilizador|segurado|beneficiario|benef|titular|funcionario|trabalhador|colaborador|empregado|aluno|estudante|devedor|fiador|avalista|requerente|proprietario|arrendatario|inquilino|condutor|tomador|responsavel|representante|procurador|pessoa|cidadao|contribuinte|mae|pai|conjuge|contacto|referencia|vitima|denunciante|arguido|testemunha|medico|docente|socio|herdeiro|dador|tutor|pensionista|reformado|interessado|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)` `(cliente|cli|utente|doente|paciente|utilizador|segurado|beneficiario|benef|titular|funcionario|trabalhador|colaborador|empregado|aluno|estudante|devedor|fiador|avalista|requerente|proprietario|arrendatario|inquilino|condutor|tomador|responsavel|representante|procurador|pessoa|cidadao|contribuinte|mae|pai|conjuge|contacto|referencia|vitima|denunciante|arguido|testemunha|medico|docente|socio|herdeiro|dador|tutor|pensionista|reformado|interessado|customer|patient|employee|member|holder|mother|father|spouse|contact|person|student|driver|owner)_?nome` `nome_?(m[aã]e|pai|tutor|c[oô]njuge|contacto_?(de_?)?emerg[eê]ncia|refer[eê]ncia)` `full_?name` `person_?name`

60% `filia[cç][aã]o_?(materna|paterna)` `m[aã]e` `pai` `tutor` `tutora` `c[oô]njuge` `representante_?legal` `procurador` `fiador` `avalista` `benefici[aá]rio` `herdeiro` `titular` `tomador` `refer[eê]ncia_?(pessoal|familiar)`

50% `nome` *(except when followed by list E2)* `name` *(except when followed by list E3)*

KNOWN VALUES PT_L1_NOME_COMPLETO — List

LIST	VALUES	STRENGTH	FIRST VALUES
pt-detetar-nomes.txt	362	65%	Maria, José, Jose, João, Joao, Ana
pt-detetar-apelidos.txt	498	65%	Silva, Santos, Ferreira, Pereira, Oliveira, Costa

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Two words are a given name and a surname; three, a given name and two surnames; four, two and two; more, two given names and the rest surnames. With a comma, what comes first are the surnames. Each word becomes another from its list, and the particles stay.

`PT_NOME_COMPLETO` REGEX DECOMPOSE

Tries 9 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

> `PT_APELIDOS` REGEX DECOMPOSE
>
> Tries 5 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.
>
> > `PT_PALAVRA_APELIDO` REGEX DECOMPOSE
> >
> > Matches one pattern and gives each part of the value its own action; when none matches: `PT_APELIDO`.

`PT_APELIDO` NAME

Replaces the name with one of the 425 names in `pt-apelidos.txt`.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_NOMES` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

`PT_PALAVRA_NOME` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_NOME`.

`PT_NOME` NAME

Replaces the name with one of the 282 names in `pt-nomes.txt`.

EXAMPLES

VALUE		MASKED
Maria da Conceição Ferreira dos Santos	→	**Leonardo da Sara Coutinho dos Neves**
Inês Gonçalves	→	**Tiago Santiago**
SILVA, JOÃO PEDRO	→	**RICARDO, MARCELO ALBERTINA**

8.12 Email address

PT_L1_EMAIL

ESSENTIAL COLUMN NAME DATA TYPE VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

An email address, accented letters included.

HOW IT IS FOUND

COLUMN NAME PT_L1_EMAIL – Path

85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `correio(_?eletr[oó]nico)?[a-z0-9_]*` `endere[cç]o_?(de_?)?(e_?mail|correio_?eletr[oó]nico)`

DATA TYPE PT_L1_EMAIL – Type

Accepts text (length 5 or more); any other type rules the data class out.

VALUE FORMAT PT_L1_EMAIL – Regex

PATTERN	STRENGTH	NOTES
`[\p{L}\p{N}._%+'\-]+@[\p{L}\p{N}.\-]+\.[A-Za-z]{2,24}`	100%	

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

The local part and the domain are masked character by character, and the top-level domain becomes `.test`, reserved for tests: a masked address can never deliver.

`PT_EMAIL` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
ines.goncalves@gmail.com	→	**ukut.piyxundit@pgoeb.test**

8.13 Telephone

PT_L1_TELEFONE

ESSENTIAL · COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

A Portuguese number of nine digits — **91, 92, 93 and 96** for a mobile, **2** and the area code for a landline, **30** for a nomadic one —, with or without `+351`. MB WAY makes a mobile number a payment address as well.

HOW IT IS FOUND

> **COLUMN NAME** PT_L1_TELEFONE — Path
>
> 85% `tel` `tlf` `tlm` `telef` `telefone[a-z0-9_]*` `tel_?(fixo|casa|resid[eê]ncia|escrit[oó]rio|trabalho|contacto|m[oó]vel)` `telem[oó]vel` `tlmv` `m[oó]vel` `movel[a-z0-9_]*` `n(o|r|ro|um|umero)_?(tel|telefone|telem[oó]vel|contacto)` `contacto_?telef[oó]nico` `whats_?app` `mb_?way` `fax` `phone[a-z0-9_]*` `mobile[a-z0-9_]*`

> **VALUE FORMAT** PT_L1_TELEFONE — Regex
>
PATTERN	STRENGTH	NOTES
`0*(?:((\+|00)351[\s\-]?)?9[1236]\d[\s\-]?\d{3}[\s\-]?\d{3})`	80%	
`0*(?:(\+|00)351[\s\-]?2\d{2}[\s\-]?\d{3}[\s\-]?\d{3})`	80%	
`0*(?:2\d[\s\-]\d{3}[\s\-]?\d{4}|2\d{2}[\s\-]\d{3}[\s\-]\d{3})`	60%	
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The country code and the first two digits stay — the operator or the area, no finer than a district —, so the masked number is still a mobile or a landline; the other seven change, and the separators stay.

`PT_TELEFONE` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_DIGITOS`.

> `PT_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
+351 912 345 678	→	**+351 914 951 769**
912345678	→	**914951769**
21 123 4567	→	**21 564 9285**

8.14 Address

PT_L1_MORADA

ESSENTIAL · COLUMN NAME · DATA TYPE · VALUE FORMAT · SECURE LOOKUP

WHAT IT IS

A Portuguese address: type of street, name, door number, floor and side — `Rua da Liberdade, 12, 3.º Esq.`.

HOW IT IS FOUND

COLUMN NAME PT_L1_MORADA — Path

80% `morada[a-z0-9_]*` `endere[cç]o[a-z0-9_]*` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`, `correio`; except when followed by list E4)* `domic[ií]lio[a-z0-9_]*` *(except when followed by `fiscal_?empresa`)* `resid[eê]ncia(_?habitual)?` *(except when preceded by list E5; except when followed by `fiscal`, `permit`, `status`, `permanente`, `tempor[aá]ria`, `cplp`)* `local_?(de_?)?resid[eê]ncia` `arruamento` `nome_?(da_?)?(rua|art[eé]ria)` `art[eé]ria` `rua` `address[a-z0-9_]*` *(except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`; except when followed by list E6)*

DATA TYPE PT_L1_MORADA — Type

Accepts text (length 6 or more); any other type rules the data class out.

VALUE FORMAT PT_L1_MORADA — Regex

PATTERN	STRENGTH	NOTES
`(?iu)(rua|r\.|avenida|av\.?|travessa|tv\.?|largo|lg\.?|pra[çc]a|p[çc]\.?|estrada|est\.?|cal[çc]ada|alameda|beco|rotunda|praceta|urbaniza[çc][ãa]o|urb\.?|bairro|lugar|quinta|caminho)\s+.{2,60}\d.*`	85%	
`(?iu).*\b\d{1,4}\s*,?\s*(\d{1,2}\s*\.?\s*º\s*(esq|dto|dt|frente|fte)|r/?c|r[ée]s[\s\-]do[\s\-]ch[ãa]o|cave)\b.*`	70%	

A value that matches none counts 20% against the data class.

HOW IT IS MASKED

The whole line becomes a fictitious address from a list of 4,000 — streets, avenues, lanes, squares and housing estates with names common in Portugal, numbers, floors and sides.

`PT_MORADA` SECURE LOOKUP

Replaces the value with one of the 4,000 values in `pt-moradas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Rua da Liberdade, 12, 3.º Esq.	→	**Praça da Liberdade, 62**
Avenida 25 de Abril 45, R/C	→	**Urbanização da Boavista, Lote 20, 86, R/C Esq.**

8.15 Address detail

PT_L1_MORADA_COMPLEMENTO

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Floor, side, door, plot, block, unit, post office box.

HOW IT IS FOUND

COLUMN NAME PT_L1_MORADA_COMPLEMENTO — Path

70% `andar` `piso` `porta` `lado` `fra[cç][aã]o` `lote` `bloco` `entrada` `n(o|r|ro|um|umero)_?(de_?)?(porta|pol[ií]cia|rua|casa|lote)` `num_?porta` `complemento_?(da_?)?(morada|endere[cç]o)` `complemento` *(except when followed by `[a-z_]*(depend|solid|salar|pens|reforma|abono|remunera)`)* `resto_?(da_?)?morada` `apartado` `p_?o_?box`

HOW IT IS MASKED

Character by character, keeping the shape.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`3.º Esq.`	→	**`4.º Unt.`**
`Lote 12`	→	**`Kora 36`**

8.16 IBAN and NIB

PT_L1_CONTA_BANCARIA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

A Portuguese account is a **NIB** of twenty-one digits — four for the bank, four for the branch, eleven for the account and two **check digits**, 98 minus the first nineteen times 100 modulo 97 — and the **IBAN** puts `PT50` in front. The NIB rule makes the whole NIB one more than a multiple of 97, which makes the IBAN check digits of every Portuguese account **50**.

HOW IT IS FOUND

> COLUMN NAME PT_L1_CONTA_BANCARIA — Path
>
> **90%** `conta_?(banc[aá]ria|banco|corrente|ordem|poupan[cç]a|cliente|ordenado|d[eé]bito|cr[eé]dito|iban|nib) n(o|r|ro|um|umero)_?(de_?)?(conta|cta) num_?conta cta_?(bancaria|ordem|debito) iban[a-z0-9_]* nib n_i_b account_?(no|num|number) bank_?account`

> VALUE FORMAT PT_L1_CONTA_BANCARIA — Regex
>
PATTERN	STRENGTH	NOTES
`PT50\d{21}`	95%	MOD97 check digit
`PT50( \d{4}){5} \d`	95%	MOD97 check digit; after removing `\s`
`0*(?:\d{4}[\s.\-]?\d{4}[\s.\-]?\d{11}[\s.\-]?\d{2})`	70%	
>
> A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The eleven digits of the account change and bank and branch stay. The two NIB check digits are **recomputed** by a state — the number so far modulo 97 — that crosses the nineteen digits with a table of 1,261 lines and becomes the two digits itself; with the NIB right again, the IBAN is valid again with the same `PT50`. In an IBAN printed in groups of four a space falls between the two check digits, and the last table writes it back in place. The plugin's IBAN algorithm would recompute the ISO digits and leave the NIB wrong; it is used only for the IBAN of another country found in the column.

`PT_CONTA` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_DIGITOS`.

> `PT_NIB` STRING ALGORITHM CHAIN
>
> Applies `PT_NIB_1` → `PT_NIB_2` → `PT_NIB_3` → `PT_NIB_4`, in this order. It is made of 36 algorithms that repeat the same step position by position; each one is in Appendix A.
>
> `PT_NIB_IMPRESSO` STRING ALGORITHM CHAIN

Applies `PT_NIB_IMPRESSO_1` → `PT_NIB_IMPRESSO_2` → `PT_NIB_IMPRESSO_3` → `PT_NIB_IMPRESSO_4`, in this order. It is made of 36 algorithms that repeat the same step position by position; each one is in Appendix A.

`PT_IBAN_ESTRANGEIRO` **IBAN**

Masks the last 8 characters of the IBAN and recomputes its two ISO 13616 check digits; the country code and the characters before stay.

`PT_CM_DIGITOS` **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
PT50003506510000002073145	→	**PT50003506515988566829272**
PT50 0035 0651 0000 0020 7314 5	→	**PT50 0035 0651 5988 5668 2927 2**
003506510000002073145	→	**003506515988566829272**

8.17 Payment card

`PT_L1_CARTAO_PAGAMENTO`

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

The number of a credit or debit (Multibanco) card.

HOW IT IS FOUND

COLUMN NAME `PT_L1_CARTAO_PAGAMENTO` – Path

85% `cart[aã]o_?(de_?)?(cr[eé]dito|d[eé]bito|pagamento|multibanco)` `n(o|r|ro|um|umero)_?` `cart[aã]o(_?(cr[eé]dito|d[eé]bito))?` `pan` `card_?(no|num|number)` `credit_?card`

VALUE FORMAT `PT_L1_CARTAO_PAGAMENTO` – Regex

PATTERN	STRENGTH	NOTES
`0*(?:3[47]\d{13}|[1–9]\d{12,13}|[1–9]\d{15,18})`	90%	LUHN check digit; after removing `[\s\-]`

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Masked by the Credit Card algorithm that comes with Delphix: another number that passes the Luhn check, keeping the first six digits (the issuer, not the holder).

`PT_CARTAO` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

`dlpx-core:Credit Card` **PAYMENT CARD**

Comes with Delphix and is used as it ships. Replaces the card number with another that passes the Luhn check, keeping the first six digits — the issuer, not the holder.

EXAMPLES

VALUE		MASKED
4532 0000 0000 0001	→	**4532 0086 1298 3134**

8.18 Digital wallet

PT_L1_CARTEIRA_DIGITAL

COLUMN NAME | VALUE FORMAT | CHARACTER MAPPING

WHAT IT IS

The address of a cryptocurrency wallet.

HOW IT IS FOUND

COLUMN NAME PT_L1_CARTEIRA_DIGITAL – Path

85% `carteira_?(digital|cripto|bitcoin)` `wallet(_?(id|address|endereco))?` `endere[cç]o_?(bitcoin|btc|wallet|cripto)` `btc_?(address|endereco)`

VALUE FORMAT PT_L1_CARTEIRA_DIGITAL – Regex

PATTERN	STRENGTH	NOTES
`(bc1|[13])[a-zA-HJ-NP-Z0-9]{25,59}`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping the shape.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
bc1qar0srrr7xfkvy5l643lydnw9re59gtzzwf5mdq	→	**mh2wis8tsdm0pdjdv8v511yqxqg4ze53qkjbvp7dgf**

8.19 IP address

PT_L1_IP

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

An IPv4 or IPv6 address. The Court of Justice has held that a dynamic IP is personal data for whoever has legal means to reach the subscriber (Breyer, C-582/14).

HOW IT IS FOUND

COLUMN NAME PT_L1_IP – Path

85% `ip` `ip_?(address|addr|origem|destino|cliente|utilizador|acesso|login|remoto|publico)` `endere[cç]o_?ip` `end_?ip` `ipv[46]` `remote_?addr(ess)?` `client_?ip` `host_?ip`

VALUE FORMAT PT_L1_IP – Regex

PATTERN	STRENGTH	NOTES
`0*(?:((25[0-5]|2[0-4]\d|1?\d?\d)\.){3}(25[0-5]|2[0-4]\d|1?\d?\d))`	100%	
`0*(?:[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7})`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Each octet of an IPv4 becomes a number from 1 to 254; an IPv6 is masked as hexadecimal.

`PT_IP` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_HEX`.

`PT_OCTET0` NUMERIC MAPPING

Maps the number to another between 1 and 254.

`PT_CM_HEX` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
85.243.120.12	→	**54.203.254.94**

8.20 Device identifier

PT_L1_DISPOSITIV0

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

IMEI, IMSI, ICCID, MAC address, advertising identifier, session identifier.

HOW IT IS FOUND

COLUMN NAME PT_L1_DISPOSITIV0 – Path

80% `imei` `imsi` `iccid` `mac` `mac_?address` `endere[cç]o_?mac` `device_?(id|uuid|serial)` `id_?(dispositivo|equipamento|terminal)` `serial_?(equipamento|terminal|dispositivo)` `advertising_?id` `idfa` `gaid` `session_?id` `id_?sess[aã]o`

VALUE FORMAT PT_L1_DISPOSITIV0 – Regex

PATTERN	STRENGTH	NOTES
`0*(?:([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2})`	100%	
`0*(?:\d{15})`	80%	LUHN check digit

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, with the hexadecimal letters in a group of their own, so that a MAC or UUID stays valid hexadecimal.

`PT_CM_HEX` CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3c:22:fb:9a:10:e4	→	**5e:83:bb:3c:31:f9**
356938035643809	→	**906695788992197**

8.21 Cookie and online identifier

PT_L1_COOKIE

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The value of a cookie, a visitor or tracking identifier.

HOW IT IS FOUND

COLUMN NAME PT_L1_COOKIE — Path

80% `cookie(_?(id|value|valor|nome))?` `cookies` `_?ga` `_?gid` `fbp` `fbclid` `utm_?(source|medium|campaign|term|content)` `id_?(navegador|browser|visitante)` `visitor_?id` `tracking_?id` `client_?id`

HOW IT IS MASKED

Character by character, keeping the shape.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
GA1.2.123456789.1700000000	→	**ZE0.5.891552838.7889916184**

8.22 Vehicle plate

PT_L1_MATRICULA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Four series of plates have run since 1937, each with two pairs of letters and digits in another order: `AA-00-00`, `00-00-AA` (1992), `00-AA-00` (2005) and `AA-00-AA` (2020).

HOW IT IS FOUND

COLUMN NAME PT_L1_MATRICULA — Path

85% `matr[ií]cula(_?(ve[ií]culo|viatura|carro|autom[oó]vel|mota))?` *(except when followed by list E7)* `n(o|r|ro|um|umero)_?matr[ií]cula` `chapa_?matr[ií]cula` `license_?plate` `plate(_?(no|number))?`

VALUE FORMAT PT_L1_MATRICULA — Regex

PATTERN	STRENGTH	NOTES
`[A-Z]{2}-\d{2}-[A-Z]{2}|\d{2}-[A-Z]{2}-\d{2}|\d{2}-\d{2}-[A-Z]{2}|[A-Z]{2}-\d{2}-\d{2}`	90%	
`[A-Z]{2}\d{2}[A-Z]{2}|\d{2}[A-Z]{2}\d{2}|\d{4}[A-Z]{2}|[A-Z]{2}\d{4}`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The letters change within the 23 letters the series use — no K, W or Y —, the digits among digits, and the order stays: a masked plate still dates the car by its series.

`PT_MATRICULA` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_DIGITOS_LETRAS`.

> `PT_CM_MATRICULA` CHARACTER MAPPING
>
> Maps each character to another of its group (2 groups), keeping length and format.
>
> `PT_CM_DIGITOS_LETRAS` CHARACTER MAPPING
>
> Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
AA–12–BC	→	**ZP–58–DR**
12–AB–34	→	**58–GU–28**
12–34–AB	→	**58–28–GU**

8.23 Vehicle identification

PT_L1_VEICULO

COLUMN NAME · VALUE FORMAT · CHARACTER MAPPING

WHAT IT IS

Chassis (VIN), engine, registration certificate or documento único automóvel number.

HOW IT IS FOUND

COLUMN NAME — PT_L1_VEICULO – Path

85% `vin` `chassis` `chassi` `n(o|r|ro|um|umero)_?(de_?)?(chassis|quadro|motor|vin|s[eé]rie)` `certificado_?(de_?)?matr[ií]cula` `dua` `documento_?[uú]nico_?autom[oó]vel` `livrete`

VALUE FORMAT — PT_L1_VEICULO – Regex

PATTERN	STRENGTH	NOTES
`[A–HJ–NPR–Z0–9]{17}`	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Character by character, keeping the shape.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
VF1RFB00X56123456	→	**TR2ZSD88Q90360794**

8.24 Property

PT_L1_IMOVEL

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

A property in the tax register is an **artigo matricial** — the freguesia, U for urban or R for rural, and a number: `110508–U–1234` — and in the land register a descrição. Beside a person's name, it says where that person owns a house.

HOW IT IS FOUND

COLUMN NAME — PT_L1_IMOVEL – Path

90% `artigo_?matricial` `art_?matricial` `matriz_?predial` `n(o|r|ro|um|umero)_?(de_?)?` `(artigo|matriz|descri[cç][aã]o_?predial|pr[eé]dio|im[oó]vel|fra[cç][aã]o)` `descri[cç][aã]o_?predial` `registo_?predial` `caderneta_?predial` `property_?(id|number)`

VALUE FORMAT PT_L1_IMOVEL — Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{6}[\s\-]?[UR][\s\-]?\d{1,6})`	80%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The number of the article changes; the freguesia and the kind stay.

`PT_IMOVEL` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

> `PT_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`110508-U-1234`	→	**`110508-U-9707`**
`R-123`	→	**`R-957`**

8.25 CPE and CUI

PT_L1_PONTO_ENTREGA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The **CPE** (Código de Ponto de Entrega) names every electricity supply point, and the **CUI** every gas one: `PT`, four digits for the network operator — `0002` for E-Redes on the mainland —, twelve for the point and two **control letters**. They follow the same rule as the Spanish CUPS: the sixteen digits modulo 529, divided by 23, read in the table `TRWAGMYFPDXBNJZSQVHLCKE` — checked on two CPE published in public tenders. A CPE names a home: the bill, the smart meter's consumption curve and the social tariff hang from it.

HOW IT IS FOUND

COLUMN NAME PT_L1_PONTO_ENTREGA — Path

95% `cpe` `c_p_e` `c[oó]digo_?(de_?)?ponto_?(de_?)?entrega` `ponto_?(de_?)?entrega` `cui` `c[oó]digo_?universal_?(de_?)?instala[cç][aã]o` `cpe_?(luz|gas|eletricidade)` `cups`

VALUE FORMAT PT_L1_PONTO_ENTREGA — Regex

PATTERN	STRENGTH	NOTES
`PT\d{16}[A-Z]{2}(\d[A-Z])?`	95%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The operator stays and the twelve digits change. The two letters are **recomputed** by a state of three digits that crosses the value with a table of 6,877 lines, and a last table of 529 lines turns it into the letters.

`PT_CPE` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

> `PT_CPE_CADEIA` STRING ALGORITHM CHAIN
>
> Applies `PT_CPE_CADEIA_1` → `PT_CPE_CADEIA_2` → `PT_CPE_CADEIA_3` → `PT_CPE_CADEIA_4`, in this order.
> It is made of 34 algorithms that repeat the same step position by position; each one is in Appendix A.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING

> Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
PT00020000664435112QY	→	**PT0002116863393487HY**

8.26 Contract or customer number

PT_L1_CONTRATO

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Contract, policy, loan, customer, member, employee, claim or complaint number.

HOW IT IS FOUND

COLUMN NAME PT_L1_CONTRATO — Path

70% `n(o|r|ro|um|umero)_?(contrato|ap[oó]lice|empr[eé]stimo|pedido|processo_?(administrativo|interno)|refer[eê]ncia|cliente|s[oó]cio|assinante|instala[cç][aã]o|servi[cç]o|caso|ticket|sinistro|reclama[cç][aã]o|ocorr[eê]ncia)` `contrato_?(n(o|r|ro|um|umero))` `c[oó]digo_?(cliente|s[oó]cio|funcion[aá]rio|assinante)` `id_?(cliente|s[oó]cio|funcion[aá]rio)` `n(o|r|ro)_?(funcion[aá]rio|mecanogr[aá]fico|colaborador)`

HOW IT IS MASKED

Character by character, keeping the shape.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
CT-123456	→	**NG-557411**

8.27 User name

PT_L1_UTILIZADOR

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Login, nickname or social media handle.

HOW IT IS FOUND

COLUMN NAME PT_L1_UTILIZADOR — Path

70% `utilizador` `user_?name` `username` `login` `alcunha` `nick(_?name)?` `perfil_?(instagram|facebook|twitter|tiktok|linkedin|x)` `instagram` `facebook` `twitter` `tiktok` `linkedin` `rede_?social` `handle`

HOW IT IS MASKED

Character by character, keeping the shape.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
ines_goncalves	→	**ukut_piyxundit**

8.28 Credential

PT_L1_CREDENCIAL

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Password, PIN, token, API key, security codes — and password hashes, recognised by their scheme (bcrypt, crypt, Argon2, PBKDF2, `{SSHA}`).

HOW IT IS FOUND

COLUMN NAME PT_L1_CREDENCIAL – Path

90% `palavra_?passe` `senha` `password` `passwd` `pwd` `pass` `hash_?(senha|password|palavra_?passe)` `pin` `c[oó]digo_?(seguran[cç]a|verifica[cç][aã]o|acesso|otp)` `cvv` `cvc` `token(_?(acesso|refresh|api))?` `access_?token` `refresh_?token` `api_?key` `chave_?(api|privada|m[oó]vel_?digital)` `segredo` `secret` `otp` `pergunta_?secreta` `resposta_?secreta` `seed_?phrase`

VALUE FORMAT PT_L1_CREDENCIAL – Regex

PATTERN	STRENGTH	NOTES
`\$2[abxy]?\$\d{2}\$[./A-Za-z0-9]{53}`	95%	
`\$(1|5|6)\$(rounds=\d+\$)?[./A-Za-z0-9]{1,16}\$[./A-Za-z0-9]{22,86}`	95%	
`\$argon2(id|i|d)\$v=\d+\$m=\d+,t=\d+,p=\d+\$\S+`	95%	
`pbkdf2_sha(1|256|512)\$\d+\$\S+\$\S+`	95%	
`\{(SSHA|SHA|SSHA256|SSHA512|SMD5|MD5|CRYPT)\}\S+`	95%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Redacted: every character becomes `X`. A credential has no use in a test copy.

`PT_REDIGIR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
Senha#2024	→	**XXXXXXXXXX**

8.29 Image and voice

PT_L1_IMAGEM

COLUMN NAME · REGEX DECOMPOSE

WHAT IT IS

Photograph, video, voice recording, or the path to them. Image is a right of its own (art. 26.º of the Constitution, art. 79.º of the Código Civil), Lei n.º 58/2019 protects that of the dead (art. 17.º) and limits video surveillance (art. 19.º).

HOW IT IS FOUND

COLUMN NAME PT_L1_IMAGEM – Path

85% `foto(grafia)?[a-z0-9_]*` `imagem_?(pessoa|rosto|perfil|cc|documento)` `avatar` `selfie` `retrato` `video_?(pessoa|entrevista|vigil[aâ]ncia)` `videovigil[aâ]ncia` `grava[cç][aã]o(_?(chamada|voz|c[aâ]mara))?` `audio_?(voz|chamada)` `url_?foto` `caminho_?(foto|imagem)` `photo[a-z0-9_]*` `picture` `image_?(url|path|person)`

HOW IT IS MASKED

Redacted: every character becomes `X`.

`PT_REDIGIR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
`/fotos/pessoa_12.jpg`	→	XXXXXXXXXXXXXXXXXXXX

8.30 Geolocation

PT_L1_GEOLOCALIZACAO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in separate columns.

HOW IT IS FOUND

COLUMN NAME PT_L1_GEOLOCALIZACAO – Path

85% `lat` `latitude` `lon` `lng` `longitude` `coordenadas?` `coord_?[xy]` `geo_?(lat|lon|lng|loc|localizacao|posicao)` `georreferencia[cç][aã]o` `geolocaliza[cç][aã]o` `gps(_?(localiza[cç][aã]o|posi[cç][aã]o|coordenadas))?` `localiza[cç][aã]o_?gps`

50% `long`

VALUE FORMAT PT_L1_GEOLOCALIZACAO – Regex

PATTERN	STRENGTH	NOTES
`0*(?:(3[2-9]|4[0-2])\.\d{3,}\s*,\s*-(\d|[12]\d|3[01])\.\d{3,})`	90%	
`0*(?:(3[7-9]|4[0-2])\.\d{4,})`	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The integer part and the first decimal stay — about 11 km — and the other decimals change: the place is generalized, not moved.

`PT_COORDENADA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `PT_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
38.722252,-9.139337	→	**38.715147,-9.197372**

8.31 Free text

PT_L1_TEXTO_LIVRE

COLUMN NAME · DATA TYPE · VALUE FORMAT · FREE TEXT REDACTION

WHAT IT IS

Remarks, comments, notes, complaint descriptions — where anything gets written, identifiers included.

HOW IT IS FOUND

COLUMN NAME PT_L1_TEXTO_LIVRE – Path

60% `observa[cç][aã]o(es|[oõ]es)?` `obs` `coment[aá]rios?` `notas?` `anota[cç][aã]o(es|[oõ]es)?` `descri[cç][aã]o_?(queixa|reclama[cç][aã]o|pedido|caso|factos|ocorr[eê]ncia|atendimento|den[uú]ncia)` `detalhe_?(reclama[cç][aã]o|pedido|caso|ocorr[eê]ncia)` `factos` `relato` `motivo_?(da_?)?(reclama[cç][aã]o|pedido|chamada)` `justifica[cç][aã]o` `mensagem` *(except when preceded by list E8; except when followed by list E9)* `texto(_?livre)?` `resumo_?(caso|atendimento)` `queixa` `reclama[cç][aã]o` `remarks?` `comments?` `notes?` `free_?text` `memo`

DATA TYPE PT_L1_TEXTO_LIVRE – Type

Accepts text (length 30 or more); any other type rules the data class out.

VALUE FORMAT PT_L1_TEXTO_LIVRE – Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{8}\s?\d\s?[A-Z0-9]{2}\d)`	80%	anywhere in the value
`[\w.+\-]+@[\w\-]+\.[A-Za-z]{2,}`	70%	anywhere in the value
`0*(?:9[1236]\d[\s\-]?\d{3}[\s\-]?\d{3})`	60%	anywhere in the value

A value that matches none does not count against the data class.

HOW IT IS MASKED

Free Text Redaction: document numbers, NIFs and nine-digit numbers, NISS, emails, phones, IBANs, NIBs, cards, IPs and plates become `[DADO]`, and any word that is a given name or surname of the list becomes `[NOME]`.

`PT_TEXTO_LIVRE` FREE TEXT REDACTION

Replaces the text matching 10 patterns with `[DADO]`, and the 1,618 terms of `pt-texto-nomes.txt` with `[NOME]`.

EXAMPLES

VALUE		MASKED
Cliente Gonçalves, NIF 234567899, email i.goncalves@gmail.com, telemóvel 912345678	→	**Cliente [NOME], NIF [DADO], email [DADO], telemóvel [DADO]**

PART 9

Quasi-identifiers

Data that identify no one on their own and almost everyone together. Recital 26 of the Regulation asks how identifiable a person is by "all the means reasonably likely to be used", singling out included — and a birth date, a sex and a small freguesia are such means. These columns are not emptied — a test needs ages and places that behave — but coarsened until a combination no longer points at one person.

9.1 Birth date

PT_L2_DATA_NASCIMENTO

ESSENTIAL · COLUMN NAME · DATA TYPE · DATE SHIFT

WHAT IT IS

The birth date, as a date, a timestamp or text.

HOW IT IS FOUND

COLUMN NAME PT_L2_DATA_NASCIMENTO — Path

90% `(data|dt)_?(de_?)?nasc(imento)?` `dtnasc` `datanasc(imento)?` `aniversario` `anivers[aá]rio` `dob` `date_?of_?birth` `birth_?date` `birthday`

DATA TYPE PT_L2_DATA_NASCIMENTO — Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Shifted up to 60 days forwards or backwards: enough to break the link to the person, little enough that ages and school years move for few people.

`PT_DATA_NASCIMENTO` DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	**1985-08-05T00:00**

9.2 Birth year

PT_L2_ANO_NASCIMENTO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The birth year on its own.

HOW IT IS FOUND

COLUMN NAME PT_L2_ANO_NASCIMENTO — Path

90% `ano_?(de_?)?nasc(imento)?` `year_?of_?birth` `birth_?year` `yob`

DATA TYPE PT_L2_ANO_NASCIMENTO — Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

The decade stays and the last digit changes.

`PT_ANO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

> `PT_CM_DIGITOS` CHARACTER MAPPING
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	**1980**

9.3 Age

PT_L2_IDADE

COLUMN NAME | DATA TYPE | REGEX DECOMPOSE

WHAT IT IS

Age, age group or bracket.

HOW IT IS FOUND

> COLUMN NAME PT_L2_IDADE — Path
>
> 85% `idade(_?(atual|anos|utente|doente|cliente|na_?(admiss[aã]o|data_?(do_?)?diagn[oó]stico|morte|[oó]bito)))?` `grupo_?et[aá]rio` `faixa_?et[aá]ria` `escal[aã]o_?et[aá]rio` `age(_?(years|group))?`

> DATA TYPE PT_L2_IDADE — Type
> Accepts number (length up to 6) or text (length up to 6); any other type rules the data class out.

HOW IT IS MASKED

The tens stay and the units change; from 100 on, the age becomes 90.

`PT_IDADE` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

> `PT_CM_DIGITOS` CHARACTER MAPPING
> Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	**35**
104	→	**90**

9.4 Date of a personal event

PT_L2_DATA_EVENTO

COLUMN NAME | DATA TYPE | DATE SHIFT

WHAT IT IS

Dates in a person's life: death, marriage, divorce, hiring and dismissal, admission and discharge, diagnosis, childbirth, arrest, issue and expiry of the document.

HOW IT IS FOUND

COLUMN NAME PT_L2_DATA_EVENTO — Path

80% `(data|dt)_?(de_?|do_?|da_?)?` `([oó]bito|falecimento|casamento|div[oó]rcio|admiss[aã]o|demiss[aã]o|cessa[cç]` `[aã]o|despedimento|reforma|aposenta[cç]` `[aã]o|internamento|alta|diagn[oó]stico|atendimento|consulta|parto|deten[cç]` `[aã]o|senten[cç]a|condena[cç][aã]o|emiss[aã]o_?(cc|bi|documento)|validade_?` `(cc|bi|documento|t[ií]tulo)|vacina[cç][aã]o|interven[cç][aã]o|acidente|incapacidade|baixa_?` `m[eé]dica)` `date_?of_?(death|marriage|hire|admission|discharge)`

DATA TYPE PT_L2_DATA_EVENTO — Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the data class out.

HOW IT IS MASKED

Shifted up to 30 days forwards or backwards.

`PT_DATA_EVENTO` DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	**2021-03-05T00:00**

9.5 Sex

PT_L2_SEXO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Sex — `F` / `M`, `Feminino` / `Masculino`, `Mulher` / `Homem`, `1` / `2`.

HOW IT IS FOUND

COLUMN NAME PT_L2_SEXO — Path

85% `sexo(_?(biol[oó]gico|registado|utente|doente|cliente))?` `(tp|tipo|cod|cd|id)_?sexo` `g[eé]nero` *(except when followed by* ***`identidade`****,* ***`sentido`****)* `sex` `gender` *(except when followed by* ***`identity`****)*

KNOWN VALUES PT_L2_SEXO — List

LIST	VALUES	STRENGTH	FIRST VALUES
`pt-detetar-sexo.txt`	6	80%	homem, mulher, feminino, masculino, female, male
`pt-detetar-sexo-letra.txt`	3	60%	f, m, h

Values are split into words, and each word is looked up.

A value that matches none counts 50% against the data class.

HOW IT IS MASKED

Each vocabulary is replaced within itself: an F/M column stays F/M. A single `M` is read as male, the convention of the Cartão de Cidadão and of every Portuguese register.

`PT_SEXO` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_SEXO_FEMININO_MASCULINO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-sexo-feminino-masculino.txt`, chosen by a keyed hash.

`PT_SEXO_MULHER_HOMEM` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `pt-sexo-mulher-homem.txt`, chosen by a keyed hash.

`PT_SEXO_FEMALE_MALE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `pt-sexo-female-male.txt`, chosen by a keyed hash.

`PT_SEXO_F_M` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `pt-sexo-f-m.txt`, chosen by a keyed hash.

`PT_SEXO_H_M` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `pt-sexo-h-m.txt`, chosen by a keyed hash.

`PT_SEXO_1_2` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `pt-sexo-1-2.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	**M**
Masculino	→	**Feminino**

9.6 Concelho

`PT_L2_CONCELHO`

COLUMN NAME **VALUE FORMAT** **DATA CLEANSING**

WHAT IT IS

The concelho (municipality) of residence or birth, or the naturalidade — `Mértola`, `Corvo`, `Lisboa` —, on its own or with the distrito beside it.

HOW IT IS FOUND

COLUMN NAME `PT_L2_CONCELHO – Path`

85% `concelho(_?(resid[eê]ncia|nascimento|naturalidade|morada))?` *(except when followed by `cod`, `codigo`, `id`, `dico`)* `munic[ií]pio(_?(resid[eê]ncia|nascimento))?` *(except when followed by `cod`, `codigo`, `id`)* `localidade(_?(resid[eê]ncia|nascimento|morada))?` `cidade(_?(resid[eê]ncia|nascimento|morada))?` `naturalidade` `(nome|desc)_?(concelho|munic[ií]pio|localidade|cidade)` `local_?(de_?)?nascimento` `city` `town` `municipality`

VALUE FORMAT `PT_L2_CONCELHO – Values`

PATTERN	STRENGTH	NOTES
One of 271 known values, ignoring case — Águeda, Albergaria-a-Velha, Anadia, Arouca, Castelo de Paiva, Espinho, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A concelho of fewer than 20,000 inhabitants becomes the **nearest concelho of at least 20,000 in the same distrito** — or, on the islands, in the same autonomous region; a larger one stays, and so do the distrito and the region. A name is generalized only when every concelho bearing it is small; written with the distrito, the same rule applies inside it and the distrito stays.

`PT_CONCELHO` **DATA CLEANSING**

Replaces each value found in `pt-concelhos-generalizados.txt` (1,612 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Mértola	→	**Beja**
Corvo	→	**Angra do Heroísmo**
Lisboa	→	**Lisboa**

9.7 Freguesia

PT_L2_FREGUESIA

COLUMN NAME | VALUE FORMAT | DATA CLEANSING

WHAT IT IS

The freguesia — the smallest Portuguese local authority —, by the name of the 2013 map (`União das freguesias de …`) or by that of the freguesias the 2025 reorganization brought back, on its own or with the concelho beside it.

HOW IT IS FOUND

COLUMN NAME PT_L2_FREGUESIA – Path

90% `freguesia(_?(resid[eê]ncia|nascimento|naturalidade|morada))?` *(except when followed by* `cod` , `codigo` , `id` , `dicofre` *)* `(nome|desc)_?freguesia` `junta_?(de_?)?freguesia` `parish`

VALUE FORMAT PT_L2_FREGUESIA – Values

PATTERN	STRENGTH	NOTES
One of 2,873 known values, ignoring case — Aguada de Cima, Fermentelos, Macinhata do Vouga, Valongo do Vouga, União das freguesias de Águeda e Borralha, União das freguesias de Barrô e Aguada de Baixo, …	60%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

A freguesia of fewer than 20,000 inhabitants — 2,973 of the 3,092 of the census — becomes the **most populous freguesia of the concelho its own concelho goes to**: as a rule, the seat of the concelho. Written with the concelho, the concelho written becomes the destination's. The 119 larger freguesias stay.

`PT_FREGUESIA` DATA CLEANSING

Replaces each value found in `pt-freguesias-generalizadas.txt` (29,506 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Alvarenga	→	**União das freguesias de Arouca e Burgo**
Ajuda (Lisboa)	→	**Lumiar (Lisboa)**
Amora	→	**Amora**

9.8 Concelho or freguesia code (DICO and DICOFRE)

PT_L2_CODIGO_AUTARQUICO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The INE code of a concelho — **DICO**, two digits for the distrito or island and two for the concelho, `0209` — or of a freguesia — **DICOFRE**, the DICO and two more, `020901` . Barcelos, which had more than 99 freguesias, has codes with letters: `0302FA` .

HOW IT IS FOUND

COLUMN NAME PT_L2_CODIGO_AUTARQUICO – Path

90% `dico` `dicofre` `(cod|codigo|cd|id)_?(ine_?)?(concelho|munic[ií]pio|freguesia|localidade)(_?(ine|resid[eê]ncia|nascimento|morada))?` `c[oó]digo_?ine` `cod_?ine` `ine_?(concelho|freguesia|code)` `municipality_?code` `parish_?code`

VALUE FORMAT PT_L2_CODIGO_AUTARQUICO – Regex

PATTERN	STRENGTH	NOTES
`0*(?:(0[1-9]|1[0-8]|3[12]|4[1-9])\d{2}([0-9A-Z]{2})?)`	40%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The codes follow the names: the DICO of a small concelho becomes that of the concelho it is generalized to, and the DICOFRE of a small freguesia that of the freguesia replacing it. Zeros on the left that were dropped — `209` for `0209` — are recognised and kept.

`PT_CODIGO_AUTARQUICO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `PT_CODIGO_AUTARQUICO_TABELA` DATA CLEANSING
>
> Replaces each value found in `pt-codigos-autarquicos-generalizados.txt` (5,039 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
0209	→	**0205**
020901	→	**020521**
1106	→	**1106**

9.9 Postal code

PT_L2_CODIGO_POSTAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The postal code of the CTT: four digits (CP4) and three (CP3), `7750-320`, sometimes with the postal designation beside it. There are 760 CP4, each with 13,600 people on average; the CP3 narrows it to a street.

HOW IT IS FOUND

COLUMN NAME PT_L2_CODIGO_POSTAL – Path

90% `c[oó]digo_?postal` `cod_?postal` `codpostal` `cp` `c_p` `cp_?(resid[eê]ncia|morada|cliente|envio)` `cp4` `cp7` `postal_?code` `zip(_?code)?`

VALUE FORMAT PT_L2_CODIGO_POSTAL – Regex

PATTERN	STRENGTH	NOTES
`0*(?:[1-9]\d{3}-\d{3})`	90%	
`0*(?:[1-9]\d{3})`	30%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The CP4 follows the concelho it mostly serves: a CP4 whose main concelho is small becomes the main CP4 of the concelho it is generalized to — 253 of the 760 —, so the masked code agrees with the masked concelho beside it. The **CP3 changes digit by digit**. The postal designation goes through the concelho table.

`PT_CODIGO_POSTAL` **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

> `PT_CP4` **DATA CLEANSING**
>
> Replaces each value found in `pt-cp4-generalizados.txt` (253 pairs) by its counterpart; values not in the file stay as they are.
>
> `PT_CM_DIGITOS` **CHARACTER MAPPING**
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `PT_CONCELHO` **DATA CLEANSING**
>
> Replaces each value found in `pt-concelhos-generalizados.txt` (1,612 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
7750-320	→	**7800-135**
1000-001	→	**1000-006**

9.10 Nationality

`PT_L2_NACIONALIDADE`

COLUMN NAME **VALUE FORMAT** **SECURE LOOKUP**

WHAT IT IS

Nationality or country of birth. Not a special category, but article 13.º of the Constitution forbids discrimination by "território de origem", and Portugal has more than a million foreign residents — in a small place, nationality points at few.

HOW IT IS FOUND

> **COLUMN NAME** `PT_L2_NACIONALIDADE – Path`
>
> 85% `nacionalidade(_?(origem|atual))?` `pa[ií]s_?(de_?)?` `(nascimento|origem|nacionalidade|proveni[eê]ncia)` `cidadania` `nationality` `citizenship` `country_?of_?birth`

> **VALUE FORMAT** `PT_L2_NACIONALIDADE – Values`
>
PATTERN	STRENGTH	NOTES
One of 47 known values, ignoring case — Portuguesa, Brasileira, Angolana, Cabo-verdiana, Britânica, Indiana, …	70%	
>
> A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within a list of the most numerous nationalities among residents of Portugal.

`PT_NACIONALIDADE` **SECURE LOOKUP**

Replaces the value with one of the 20 values in `pt-nacionalidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Timorense	→	**Brasileira**

9.11 Residence status

PT_L2_SITUACAO_RESIDENCIA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The kind of residence permit, visa or protection: temporary, permanent, CPLP, long-term, Union citizen, international or temporary protection, irregular.

HOW IT IS FOUND

COLUMN NAME PT_L2_SITUACAO_RESIDENCIA – Path

90% `situa[cç][aã]o_?(de_?)?(resid[eê]ncia|migrat[oó]ria|documental|legal)` `tipo_?(de_?)?(resid[eê]ncia|autoriza[cç][aã]o|visto|t[ií]tulo)` `estatuto_?(de_?)?(refugiado|ap[aá]trida|residente)` `prote[cç][aã]o_?(internacional|tempor[aá]ria|subsidi[aá]ria)` `requerente_?(de_?)?asilo` `asilo` `manifesta[cç][aã]o_?(de_?)?interesse` `migration_?status` `immigration_?status` `residence_?status`

VALUE FORMAT PT_L2_SITUACAO_RESIDENCIA – Values

PATTERN	STRENGTH	NOTES
One of 26 known values, ignoring case — Autorização de residência temporária, Autorização de residência permanente, Autorização de residência CPLP, Estatuto de residente de longa duração, Certificado de registo de cidadão da UE, Cartão de residência de familiar de cidadão da UE, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within a list of statuses; a yes/no flag stays a flag.

`PT_SITUACAO_RESIDENCIA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_SITUACAO_RESIDENCIA_LISTA`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_SITUACAO_RESIDENCIA_LISTA` SECURE LOOKUP

Replaces the value with one of the 15 values in `pt-situacao-residencia.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Autorização de residência CPLP	→	**Proteção temporária**

9.12 Marital status

PT_L2_ESTADO_CIVIL

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Single, married, de facto union, divorced, judicially separated, widowed — as text or code.

HOW IT IS FOUND

COLUMN NAME PT_L2_ESTADO_CIVIL – Path

85% `estado_?civil` `est_?civil` `(cod|tipo|id)_?estado_?civil` `uni[aã]o_?de_?facto` `regime_?(de_?)?bens` `marital_?status` `civil_?status`

VALUE FORMAT PT_L2_ESTADO_CIVIL – Values

PATTERN	STRENGTH	NOTES
One of 17 known values, ignoring case — Solteiro a, Casado a, União de facto, Divorciado a, Separado a de pessoas e bens, Viúvo a, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within the list; a code becomes another code.

`PT_ESTADO_CIVIL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_ESTADO_CIVIL_LISTA`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_ESTADO_CIVIL_CODIGO` SECURE LOOKUP

Replaces the value with one of the 6 values in `pt-estado-civil-codigos.txt`, chosen by a keyed hash.

`PT_ESTADO_CIVIL_LISTA` SECURE LOOKUP

Replaces the value with one of the 6 values in `pt-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
União de facto	→	**Separado(a) de pessoas e bens**
2	→	**4**

9.13 Occupation

PT_L2_PROFISSAO

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Occupation, professional category or position, as text or as a code of the Classificação Portuguesa das Profissões (CPP 2010).

HOW IT IS FOUND

COLUMN NAME PT_L2_PROFISSAO — Path

80% `profiss[aã]o` `ocupa[cç][aã]o` `of[ií]cio` `cpp(_?2010)?` `(cod|codigo)_?(profiss[aã]o|ocupa[cç][aã]o|cpp)` `categoria_?profissional` `posto_?(de_?)?trabalho` `fun[cç][aã]o_?(exercida|atual)` `occupation` `profession` `job_?title`

50% `cargo` `fun[cç][aã]o`

HOW IT IS MASKED

A code becomes another with the same number of digits; a text becomes another occupation from a list.

`PT_PROFISSAO_OU_CODIGO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_PROFISSAO`.

`PT_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`PT_PROFISSAO` SECURE LOOKUP

Replaces the value with one of the 38 values in `pt-profissoes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Diretor de operações	→	**Operador de armazém**
2221	→	**1980**

9.14 Employer

PT_L2_ENTIDADE_EMPREGADORA

COLUMN NAME | SECURE LOOKUP

WHAT IT IS

The name of the employer or workplace.

HOW IT IS FOUND

COLUMN NAME PT_L2_ENTIDADE_EMPREGADORA — Path

90% `entidade_?(empregadora|patronal)` `empregador(_?(nome|firma))?` `(nome|nom)_?(empregador|empresa_?onde_?trabalha)` `empresa_?(onde_?)?(trabalha|empregadora)` `local_?(de_?)?trabalho` `empresa_?atual` `employer(_?name)?` `workplace`

HOW IT IS MASKED

Replaced by a fictitious company from a list.

`PT_ENTIDADE_EMPREGADORA` SECURE LOOKUP

Replaces the value with one of the 24 values in `pt-empregadores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Corporação Industrial do Atlântico, S.A.	→	**Supermercados Bom Preço, S.A.**

9.15 Education

PT_L2_ESCOLARIDADE

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The level of education or qualifications, from the 1.º ciclo to a doctorate.

HOW IT IS FOUND

COLUMN NAME PT_L2_ESCOLARIDADE — Path

80% `escolaridade` `n[ií]vel_?(de_?)?(escolaridade|ensino|forma[cç][aã]o|instru[cç][aã]o|estudos)` `habilita[cç][oõ]es(_?(liter[aá]rias|acad[eé]micas))?` `grau_?acad[eé]mico` `forma[cç][aã]o_?acad[eé]mica` `education(_?level)?`

VALUE FORMAT PT_L2_ESCOLARIDADE — Values

PATTERN	STRENGTH	NOTES
One of 22 known values, ignoring case — Sem nível de escolaridade, Ensino básico - 1.º ciclo, Ensino básico - 2.º ciclo, Ensino básico - 3.º ciclo, Ensino secundário, Ensino pós-secundário não superior, …	60%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within the list; a code becomes another code.

`PT_ESCOLARIDADE` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_ESCOLARIDADE_LISTA`.

> `PT_INDICADOR` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PT_INDICADOR_SIM_NAO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.
>
> `PT_ESCOLARIDADE_CODIGO` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `pt-escolaridade-codigos.txt`, chosen by a keyed hash.

`PT_ESCOLARIDADE_LISTA` SECURE LOOKUP

Replaces the value with one of the 10 values in `pt-escolaridade.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Licenciatura	→	**Licenciatura**
7	→	**2**

9.16 School

PT_L2_ESTABELECIMENTO_ENSINO

COLUMN NAME SECURE LOOKUP

WHAT IT IS

School, school cluster, college or university.

HOW IT IS FOUND

COLUMN NAME PT_L2_ESTABELECIMENTO_ENSINO – Path

75% `estabelecimento_?(de_?)?ensino` `escola(_?(frequentada|atual))?` `agrupamento(_?(de_?)?escolas)?` `col[eé]gio` `liceu` `universidade` `faculdade` `instituto_?polit[eé]cnico` `(nome|nom)_?(escola|universidade|faculdade)` `c[oó]digo_?(de_?)?escola` `school(_?name)?` `university`

HOW IT IS MASKED

Replaced by another establishment from a list.

`PT_ESTABELECIMENTO_ENSINO` SECURE LOOKUP

Replaces the value with one of the 14 values in `pt-estabelecimentos-ensino.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Universidade de Évora	→	**Universidade de Lisboa**

9.17 Dependants and household

PT_L2_AGREGADO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

Number of children, dependants or household members.

HOW IT IS FOUND

COLUMN NAME PT_L2_AGREGADO – Path

80% `dependentes` `n(o|r|ro|um|umero)_?(de_?)?(filhos|dependentes|descendentes|membros)` `filhos` `descendentes` `membros_?(do_?)?agregado` `agregado_?familiar` `dimens[aã]o_?(do_?)?agregado` `pessoas_?(no_?)?agregado` `number_?of_?children` `dependents`

DATA TYPE PT_L2_AGREGADO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the data class out.

HOW IT IS MASKED

Capped at 5: large households are rare, and a rare count identifies.

`PT_CONTAGEM_LIMITADA` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	**5**

PART 10

Special categories (art. 9 GDPR and art. 35.º, n.º 3 of the Constitution)

Article 9.1 of the Regulation prohibits processing these data save under one of the exceptions of article 9.2, and the Portuguese Constitution has said so since 1976 for "convicções filosóficas ou políticas, filiação partidária ou sindical, fé religiosa, vida privada e origem étnica" (art. 35.º, n.º 3). A test copy is none of those exceptions: processing these data outside them is a very serious infringement (art. 37.º, n.º 1, d) of Lei n.º 58/2019), and copying them without a legal basis a crime with a doubled penalty (art. 48.º, n.º 2). Gender identity and victims of domestic violence join them because Portuguese law protects them on their own: Lei n.º 38/2018 guarantees self-determination of gender identity and expression, and Lei n.º 112/2009 gives victims a status of their own. Categorical columns are replaced within their own vocabulary, or suppressed.

10.1 Ethnic origin

PT_L3_ORIGEM_ETNICA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Ethnic or racial origin, or belonging to a community — the Roma community, for one. The Portuguese census does not ask for ethnicity; the INE's survey on living conditions, origins and trajectories (2023) asked for self-identification with these groups.

HOW IT IS FOUND

COLUMN NAME PT_L3_ORIGEM_ETNICA — Path

95% `etnia` `origem_?([eé]tnica|racial|[eé]tnico_?racial)` `grupo_?[eé]tnico` `perten[cç]a_?[eé]tnica` `autoidentifica[cç][aã]o_?([eé]tnica|racial)` `(cod|codigo|tipo|id)_?etnia` `ra[cç]a` `comunidade_?cigana` `ethnicity` `race`

VALUE FORMAT PT_L3_ORIGEM_ETNICA — Values

PATTERN	STRENGTH	NOTES
One of 21 known values, ignoring case — Branca, Negra, Asiática, Cigana, Mista, Outra, …	90%	
One of 13 known values, ignoring case — s, n, sim, não, 1, 2, …	30%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within a list; a code becomes another code; a yes/no flag stays a flag.

`PT_ORIGEM_ETNICA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_ORIGEM_ETNICA_LISTA`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_ORIGEM_ETNICA_CODIGO` SECURE LOOKUP

Replaces the value with one of the 7 values in `pt-origem-etnica-codigos.txt`, chosen by a keyed hash.

`PT_ORIGEM_ETNICA_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `pt-origem-etnica.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Cigana	→	**Cigana**
N	→	**N**

10.2 Religion

PT_L3_RELIGIAO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Religion or denomination — including enrolment in Catholic Moral and Religious Education and the allocation of income tax to a church.

HOW IT IS FOUND

COLUMN NAME PT_L3_RELIGIAO — Path

95% `religi[aã]o` `cren[cç]a_?(religiosa)?` `confiss[aã]o_?religiosa` `f[eé]_?religiosa` `culto` `igreja` `(cod|codigo|tipo)_?religi[aã]o` `educa[cç][aã]o_?moral_?(e_?)?religiosa` `emrc` `consigna[cç][aã]o_?(irs_?)?igreja` `religion` `church`

VALUE FORMAT PT_L3_RELIGIAO — Values

PATTERN	STRENGTH	NOTES
One of 32 known values, ignoring case — Católica, Ortodoxa, Protestante ou evangélica, Testemunha de Jeová, Outra cristã, Judaica, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within the list of religions of the Censos 2021 question; a yes/no flag stays a flag.

`PT_RELIGIAO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_RELIGIAO_LISTA`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_RELIGIAO_LISTA` SECURE LOOKUP

Replaces the value with one of the 11 values in `pt-religioes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Anglicana	→	**Sem religião**

10.3 Philosophical belief

PT_L3_CONVICCAO_FILOSOFICA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Philosophical, moral or ethical convictions, conscientious objection, freemasonry.

HOW IT IS FOUND

COLUMN NAME PT_L3_CONVICCAO_FILOSOFICA — Path

90% `convic[cç][aã]o(es|[oõ]es)?_?(filos[oó]ficas?|morais?|pessoais?|[eé]ticas?)` `cren[cç]as?_?(filos[oó]ficas?|morais?|pessoais?)` `ideologia` *(except when followed by* `pol[ií]tica` *)* `obje[cç][aã]o_?(de_?)?consci[eê]ncia` `objetor_?(de_?)?consci[eê]ncia` `ma[cç]onaria` `loja_?ma[cç][oó]nica` `veganismo` `philosophical_?beliefs?` `beliefs?`

HOW IT IS MASKED

Suppressed: becomes `Sem informação`; a yes/no flag stays a flag.

`PT_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_SUPRIMIR`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `pt-sem-informacao.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Objetor a transfusões`	→	**`Sem informação`**

10.4 Political opinion

PT_L3_OPINIAO_POLITICA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Ideological self-placement, voting intention or choice, political sympathy.

HOW IT IS FOUND

COLUMN NAME PT_L3_OPINIAO_POLITICA — Path

95% `opini[aã]o_?pol[ií]tica` `ideologia_?pol[ií]tica` `prefer[eê]ncia_?(pol[ií]tica|partid[aá]ria|eleitoral)` `autoposicionamento_?ideol[oó]gico` `escala_?ideol[oó]gica` `orienta[cç][aã]o_?pol[ií]tica` `tend[eê]ncia_?pol[ií]tica` `inten[cç][aã]o_?(de_?)?voto` `sentido_?(de_?)?voto` `simpatia_?pol[ií]tica` `political_?(opinion|orientation|view|preference)` `voting_?intention`

VALUE FORMAT PT_L3_OPINIAO_POLITICA — Values

PATTERN	STRENGTH	NOTES
One of 20 known values, ignoring case — Esquerda, Centro-esquerda, Centro, Centro-direita, Direita, Nenhuma, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within a list of positions; a number on a scale becomes another number.

`PT_OPINIAO_POLITICA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_OPINIAO_POLITICA_LISTA`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_OPINIAO_POLITICA_CODIGO` SECURE LOOKUP

Replaces the value with one of the 10 values in `pt-opinioes-politicas-codigos.txt`, chosen by a keyed hash.

`PT_OPINIAO_POLITICA_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `pt-opinioes-politicas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Progressista	→	**Nenhuma**
7	→	**2**

10.5 Party membership

PT_L3_FILIACAO_PARTIDARIA

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Party, membership, member's fee.

HOW IT IS FOUND

COLUMN NAME PT_L3_FILIACAO_PARTIDARIA — Path

95% `partido(_?pol[ií]tico)?(_?(filia[cç][aã]o|nome|militancia))?` `filia[cç][aã]o_?(pol[ií]tica|partid[aá]ria|partido)` `milit[aâ]ncia(_?pol[ií]tica)?` `militante` `quota_?(de_?)?(militante|filiado)` `(cod|codigo|nome)_?partido` `political_?party` `party_?membership`

VALUE FORMAT PT_L3_FILIACAO_PARTIDARIA — Values

PATTERN	STRENGTH	NOTES
One of 24 known values, ignoring case — PS, PSD, Chega, IL, Livre, PCP, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within a list of parties with seats in parliament; a yes/no flag stays a flag.

`PT_PARTIDO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_PARTIDO_LISTA`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_PARTIDO_LISTA` SECURE LOOKUP

Replaces the value with one of the 11 values in `pt-partidos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
PEV	→	**PAN**

10.6 Trade union membership

PT_L3_FILIACAO_SINDICAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Trade union, union fee deducted from the salary, union delegate.

HOW IT IS FOUND

COLUMN NAME PT_L3_FILIACAO_SINDICAL — Path

95% `sindicato(_?(nome|filiado|filia[cç][aã]o|c[oó]digo))?` `sindicalizad[oa]` `filiado_?sindicato` `filia[cç][aã]o_?sindical` `quota_?sindical` `desconto_?sindical` `delegado_?sindical` `dirigente_?sindical` `comiss[aã]o_?(de_?)?trabalhadores` `cr[eé]dito_?(de_?)?horas_?sindical` `trade_?union` `union_?member(ship)?`

VALUE FORMAT PT_L3_FILIACAO_SINDICAL — Values

PATTERN	STRENGTH	NOTES
One of 17 known values, ignoring case — CGTP, CGTP-IN, UGT, FENPROF, FNE, STAL, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Suppressed: becomes `Sem informação`; a yes/no flag stays a flag.

`PT_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_SUPRIMIR`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_SUPRIMIR` SECURE LOOKUP

> Replaces the value with one of the 1 values in `pt-sem-informacao.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
CGTP	→	**Sem informação**
S	→	**S**

10.7 Biometric data

PT_L3_BIOMETRICO

COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

Fingerprint, face template, iris, voice — "for the purpose of uniquely identifying a natural person" (art. 9.1 GDPR). Article 28.º, n.º 6 of Lei n.º 58/2019 lets an employer process them only for attendance and access control, as irreversible representations.

HOW IT IS FOUND

> COLUMN NAME PT_L3_BIOMETRICO — Path
>
> **90%** `biometria[a-z_]*` `biom[eé]trico[a-z_]*` `impress[aã]o_?digital(_?(template|modelo|imagem|hash))?` `impress[oõ]es_?digitais` `dactilar` `template_?(facial|digital|biometrico)` `modelo_?(facial|biom[eé]trico)` `rosto_?(hash|template)` `reconhecimento_?(facial|de_?voz)` `assinatura_?(biom[eé]trica|digitalizada)` `[ií]ris` `voz_?(biom[eé]trica|template)` `fingerprints?` `face_?(template|hash|encoding)` `biometric[a-z_]*`

> DATA TYPE PT_L3_BIOMETRICO — Type
>
> Accepts text; any other type rules the data class out.

HOW IT IS MASKED

Redacted: every character becomes `X`.

`PT_REDIGIR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	**XXXXXXXXXXXX**

10.8 Genetic data

PT_L3_GENETICO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Genetic test result, DNA profile, nucleotide sequence. Lei n.º 12/2005 makes genetic information the property of the person and forbids its use by employers and insurers.

HOW IT IS FOUND

COLUMN NAME PT_L3_GENETICO — Path

90% `adn` `dna` `gen[eé]tic[oa]s?` `dados?_?gen[eé]ticos?` `informa[cç][aã]o_?gen[eé]tica` `genoma` `gen[oó]tip[a-z_]*` `teste_?(gen[eé]tico|de_?adn|de_?paternidade)` `perfil_?gen[eé]tico` `muta[cç][aã]o` `brca[12]?` `cari[oó]tipo` `rastreio_?neonatal` `teste_?do_?pezinho` `genetic[a-z_]*`

VALUE FORMAT PT_L3_GENETICO — Regex

PATTERN	STRENGTH	NOTES
`[ACGTUN]{24,}`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Redacted: every character becomes `X`.

`PT_REDIGIR` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
BRCA1 positivo	→	XXXXXXXXXXXXXX

10.9 Sexual orientation

PT_L3_ORIENTACAO_SEXUAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The sexual orientation declared.

HOW IT IS FOUND

COLUMN NAME PT_L3_ORIENTACAO_SEXUAL — Path

95% `orienta[cç][aã]o_?sexual` `prefer[eê]ncias?_?sexua(l|is)` `(cod|codigo|tipo)_?orienta[cç][aã]o_?sexual` `sexual_?orientation`

VALUE FORMAT PT_L3_ORIENTACAO_SEXUAL — Values

PATTERN	STRENGTH	NOTES
One of 13 known values, ignoring case — Heterossexual, Gay, Lésbica, Bissexual, Pansexual, Assexual, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within a list of orientations.

`PT_ORIENTACAO_SEXUAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_ORIENTACAO_SEXUAL_LISTA`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_ORIENTACAO_SEXUAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 8 values in `pt-orientacoes-sexuais.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Homossexual	→	**Pansexual**

10.10 Sex life

PT_L3_VIDA_SEXUAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Sexual activity, behaviour or partners.

HOW IT IS FOUND

COLUMN NAME PT_L3_VIDA_SEXUAL — Path

90% `vida_?sexual` `atividade_?sexual` `comportamento_?sexual` `pr[aá]ticas?_?sexua(l|is)` `parceir[oa]s?_?sexua(l|is)` `n(o|r|ro|um|umero)_?parceiros` `sexualmente_?ativ[oa]` `rela[cç][oõ]es_?sexuais` `sex(ual)?_?life` `sexual_?(activity|behavio(u)?r|partners)`

HOW IT IS MASKED

Suppressed: becomes `Sem informação`.

`PT_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_SUPRIMIR`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `pt-sem-informacao.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Ativa	→	**Sem informação**

10.11 Gender identity

PT_L3_IDENTIDADE_GENERO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Gender identity and expression, chosen name, pronouns. Lei n.º 38/2018 guarantees self-determination of gender identity and lets a person change the sex in the civil register by declaration.

HOW IT IS FOUND

COLUMN NAME PT_L3_IDENTIDADE_GENERO — Path

95% `identidade_?(de_?)?g[eé]nero` `(cod|codigo|tipo)_?identidade_?g[eé]nero` `g[eé]nero_?(sentido|autodeterminado)` `express[aã]o_?(de_?)?g[eé]nero` `transg[eé]nero` `pessoa_?trans` `mudan[cç]a_?(de_?)?(sexo|men[cç][aã]o_?do_?sexo)_?(no_?)?registo` `nome_?social` `pronomes?` `gender_?identity`

VALUE FORMAT PT_L3_IDENTIDADE_GENERO — Values

PATTERN	STRENGTH	NOTES
One of 15 known values, ignoring case — Mulher cis, Homem cis, Mulher trans, Homem trans, Pessoa não binária, Outra, …	70%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within a list of identities.

`PT_IDENTIDADE_GENERO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_IDENTIDADE_GENERO_LISTA`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_IDENTIDADE_GENERO_LISTA` SECURE LOOKUP

Replaces the value with one of the 7 values in `pt-identidades-genero.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Transgénero	→	**Homem trans**

10.12 Victim of violence

PT_L3_VITIMA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Victim status, kind of violence, restraining or protection measures, shelter. Lei n.º 112/2009 protects the identity of the victim of domestic violence.

HOW IT IS FOUND

COLUMN NAME PT_L3_VITIMA – Path

90% `v[ií]tima(_?(de_?)?(viol[eê]ncia(_?(dom[eé]stica|de_?g[eé]nero|sexual|no_?namoro))?|crime|tr[aá]fico|agress[aã]o|ass[eé]dio))?` `estatuto_?(de_?)?v[ií]tima` `viol[eê]ncia_?(dom[eé]stica|de_?g[eé]nero|sexual|no_?namoro|intrafamiliar)` `tipo_?(de_?)?viol[eê]ncia` `medida_?(de_?)?(afastamento|prote[cç][aã]o)` `teleassist[eê]ncia_?v[ií]tima` `casa_?(de_?)?abrigo` `tr[aá]fico_?(de_?)?(seres_?humanos|pessoas)`

HOW IT IS MASKED

Suppressed: becomes `Sem informação`; a yes/no flag stays a flag.

`PT_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_SUPRIMIR`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `pt-sem-informacao.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Violência doméstica	→	**Sem informação**
S	→	**S**

PART 11

Health data (art. 9 GDPR, art. 29.º of Lei n.º 58/2019 and Lei n.º 12/2005)

Health is a special category of article 9, and article 29.º of Lei n.º 58/2019 adds rules of its own: access by the principle of **need to know**, only by people bound by secrecy, with an electronic log of each access and **notification to the data subject of any access** to their data. Lei n.º 12/2005 makes health information the property of the person, which "não pode ser utilizada para outros fins que não os da prestação de cuidados e a investigação em saúde" (art. 3.º), asks that it be kept apart from the rest of a person's data and opens it to research only anonymised (art. 4.º). The numbers of the SNS — the número de utente, the prescription number — carry check characters and are recomputed.

11.1 Número de utente of the SNS

PT_SAUDE_NUMERO_UTENTE

ESSENTIAL · COLUMN NAME · DATA TYPE · REGEX DECOMPOSE

WHAT IT IS

The national health service user number (Decreto-Lei n.º 198/95, Portaria n.º 981/95): nine digits — the health region of the first registration (**1** Norte, **2** Centro, **3** Lisboa e Vale do Tejo, **4** Alentejo, **5** Algarve, **6** Açores, **7** Madeira, **9** registered with the Cartão de Cidadão), seven for the person and a **check digit by ISO/IEC 7064 MOD 11,10**. The Portaria says MOD 11-2, a slip a mathematician of the Universidade dos Açores pointed out when he found the right system. It is one of the four numbers of the Cartão de Cidadão.

HOW IT IS FOUND

> **COLUMN NAME** PT_SAUDE_NUMERO_UTENTE — Path
>
> 95% `n(o|r|ro|um|umero)_?(de_?)?utente(_?(do_?)?(sns|sa[uú]de|servi[cç]os_?de_?sa[uú]de))?` `n(o|r|ro|um|umero)_?(nacional_?(de_?)?)?utente` `nnu` `n_n_u` `utente_?sns` `cart[aã]o_?(de_?)?utente` `rnu` `sns_?(id|number|numero)`

> **DATA TYPE** PT_SAUDE_NUMERO_UTENTE — Type
>
> Accepts text (length 9 or more) or number (length 9 or more); any other type rules the data class out.

HOW IT IS MASKED

The region stays, the seven digits change and the check digit is **recomputed** by a state — what MOD 11,10 carries from one digit to the next, 1 to 10 — that crosses the number with a table of 130 lines.

`PT_NUMERO_UTENTE` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM` .

> `PT_UTENTE` STRING ALGORITHM CHAIN
>
> Applies `PT_UTENTE_1` → `PT_UTENTE_2` → `PT_UTENTE_RESTAURAR` , in this order. It is made of 22 algorithms that repeat the same step position by position; each one is in Appendix A.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
629033874	→	**691412131**

11.2 Prescription number

PT_SAUDE_RECEITA

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

The number of the paperless prescription: nineteen characters, the health region first and a **check character by ISO/IEC 7064 MOD 11-2**, written X for ten. It is the code a patient gets by SMS to collect the medicines, and it links the patient to them.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_RECEITA — Path

90% `n(o|r|ro|um|umero)_?(da_?)?receita(_?(m[eé]dica|eletr[oó]nica))?` `receita_?(m[eé]dica|eletr[oó]nica|sem_?papel)` `c[oó]digo_?(de_?)?(acesso_?e_?)?dispensa` `c[oó]digo_?(da_?)?receita` `prescri[cç][aã]o_?(n(o|r|ro|um|umero)|id)` `prescription_?(id|number)`

VALUE FORMAT PT_SAUDE_RECEITA — Regex

PATTERN	STRENGTH	NOTES
`0*(?:[1-7]\d{17}[\dX])`	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The region stays, the seventeen digits in the middle change and the check character is **recomputed** by a state of 0 to 10 that crosses the number with a table of 143 lines.

`PT_NUMERO_RECEITA` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

> `PT_RECEITA` STRING ALGORITHM CHAIN
>
> Applies `PT_RECEITA_1` → `PT_RECEITA_2` → `PT_RECEITA_3`, in this order. It is made of 27 algorithms that repeat the same step position by position; each one is in Appendix A.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3010000123456789016	→	**3135624259991845399**

11.3 Clinical or subsystem identifier

PT_SAUDE_IDENTIFICADOR

COLUMN NAME | CHARACTER MAPPING

WHAT IT IS

Hospital record, episode, admission or appointment number, and a subsystem's beneficiary number — ADSE, SAD, ADM, SAMS.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_IDENTIFICADOR — Path

85% `n(o|r|ro|um|umero)_?(de_?)?(processo(_?cl[ií]nico)?|epis[oó]dio|internamento|atendimento|consulta|benefici[aá]rio_?(adse|sad|adm|sams)|adse|sams)` `processo_?cl[ií]nico` `n_?processo` `n(o|r|ro)_?benef` `adse_?(n(o|r|ro|um|umero)|id)` `id_?(utente|doente|paciente)` `c[oó]digo_?(utente|doente|epis[oó]dio)` `sclinico_?id` `patient_?id` `medical_?record_?(no|number)`

55% `processo` `epis[oó]dio` `internamento` `consulta`

HOW IT IS MASKED

Character by character, keeping the shape.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
12345678	→	**46916122**

11.4 Health subsystem and insurance

PT_SAUDE_SUBSISTEMA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The body responsible for paying for care: SNS, ADSE, the SAD of the GNR and the PSP, ADM, SAMS, a private insurer.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_SUBSISTEMA — Path

85% `subsistema(_?(de_?)?sa[uú]de)?` `entidade_?(financeira_?)?respons[aá]vel` `efr` `tipo_?(de_?)?(benefici[aá]rio|cobertura|seguro)` `seguro_?(de_?)?sa[uú]de` `seguradora_?(de_?)?sa[uú]de` `plano_?(de_?)?sa[uú]de` `cobertura(_?(de_?)?sa[uú]de)?` `adse` `sams` `insurance_?(type|plan)` `health_?insurance`

VALUE FORMAT PT_SAUDE_SUBSISTEMA — Values

PATTERN	STRENGTH	NOTES
One of 19 known values, ignoring case — SNS, ADSE - titular, ADSE - beneficiário familiar, SAD GNR, SAD PSP, ADM, …	80%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within a list; a number changes digit by digit; a flag stays a flag.

`PT_COBERTURA_SAUDE` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_COBERTURA` .

> `PT_INDICADOR` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PT_INDICADOR_SIM_NAO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt` , chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`PT_COBERTURA` SECURE LOOKUP

Replaces the value with one of the 9 values in `pt-cobertura-saude.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
ADSE – titular	→	**Sem subsistema**

11.5 Diagnosis

PT_SAUDE_DIAGNOSTICO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Diagnosis, disease, allergy or cause of death, as text or coded — in **ICD-10-CM** in hospitals since 2017, in **ICPC-2** in primary care: `F33.1`, `K86`.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_DIAGNOSTICO – Path

85% `diagn[oó]stico[a-z_]*` `dx(_?(principal|secund[aá]rio|admiss[aã]o|alta)[0-9]?)?` `cid_?10` `icd_?(10|11)?(_?cm)?` `icpc(_?2)?` `ciap(_?2)?` `(cod|codigo)_?(diagn[oó]stico|dx|cid|icd|icpc)` `doen[cç]a(s)?[a-z_]*` `patologia` `comorbilidade(s)?` `antecedentes?_?(m[eé]dicos|patol[oó]gicos|cl[ií]nicos|pessoais|familiares)` `causa_?(de_?)?(morte|[oó]bito|baixa|internamento)` `motivo_?(de_?|da_?)?(consulta|baixa|internamento)` `alergias?` `problema_?(de_?)?sa[uú]de` `diagnosis` `diagnos(is|es)`

VALUE FORMAT PT_SAUDE_DIAGNOSTICO – Regex

PATTERN	STRENGTH	NOTES
`[A-TV-Za-tv-z]\d{2}(\.[\dA-Za-z]{1,4}|\d|X)?`	50%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

A code becomes another code of the same shape, from a list of common diagnoses; a text becomes another diagnosis; a flag stays a flag.

`PT_DIAGNOSTICO` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PT_DIAGNOSTICO_TEXTO`.

`PT_CID10_DECIMAL` SECURE LOOKUP

Replaces the value with one of the 33 values in `pt-cid10-decimal.txt`, chosen by a keyed hash.

`PT_CID10` SECURE LOOKUP

Replaces the value with one of the 46 values in `pt-cid10.txt`, chosen by a keyed hash.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

> `PT_INDICADOR_SIM_NAO` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.
>
> `PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.
>
> `PT_INDICADOR_YES_NO` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.
>
> `PT_INDICADOR_S_N` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.
>
> `PT_INDICADOR_Y_N` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.
>
> `PT_INDICADOR_0_1` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_DIAGNOSTICO_TEXTO` SECURE LOOKUP

Replaces the value with one of the 30 values in `pt-diagnosticos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F33.1	→	**K21.9**
K86	→	**J32**
Depressão major	→	**Sinusite aguda**

11.6 Procedure

PT_SAUDE_PROCEDIMENTO

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Medical act, surgery, complementary exam (MCDT), as text or coded in ICD-10-PCS.

HOW IT IS FOUND

> COLUMN NAME PT_SAUDE_PROCEDIMENTO — Path
>
> 85% `procedimento(_?(m[eé]dico|cir[uú]rgico|realizado|autorizado))?` `(cod|codigo)_?(procedimento|ato_?m[eé]dico|interven[cç][aã]o|mcdt)` `ato_?m[eé]dico` `mcdt` `exame_?(complementar|realizado|requisitado)` `interven[cç][aã]o_?cir[uú]rgica` `cirurgia(_?realizada)?` `t[eé]cnica_?(diagn[oó]stica|cir[uú]rgica)` `medical_?procedure`

HOW IT IS MASKED

A seven-character code keeps its shape; a number changes digit by digit; a text becomes another procedure.

`PT_PROCEDIMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_PROCEDIMENTO_TEXTO`.

> `PT_CM_DIGITOS_LETRAS` CHARACTER MAPPING
>
> Maps each character to another of its group (2 groups), keeping length and format.
>
> `PT_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`PT_PROCEDIMENTO_TEXTO` SECURE LOOKUP

Replaces the value with one of the 10 values in `pt-procedimentos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`0DTJ4ZZ`	→	**`0PYM8QU`**
`Carga viral do VIH`	→	**`Eletrocardiograma`**

11.7 Medicine

PT_SAUDE_MEDICAMENTO

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Medicine, active substance, therapy, dosage. An antiretroviral, an antipsychotic or methadone tells the diagnosis.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_MEDICAMENTO — Path

85% `medicamentos?(_?(prescrito|dispensado|nome|ativo))?` `f[aá]rmacos?` `subst[aâ]ncia_?ativa` `dci` `cnpem` `c[oó]digo_?(do_?)?medicamento` `n(o|r|ro)_?registo_?medicamento` `posologia` `terap[eê]utica(_?(atual|cr[oó]nica|farmacol[oó]gica))?` `tratamento_?(farmacol[oó]gico|atual|cr[oó]nico)` `medication(s)?` `drugs?_?prescribed`

VALUE FORMAT PT_SAUDE_MEDICAMENTO — Values

PATTERN	STRENGTH	NOTES
One of 50 known values, ignoring case — Paracetamol, Ibuprofeno, Metamizol, Omeprazol, Pantoprazol, Metformina, …	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced within a list of common medicines.

`PT_MEDICAMENTO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_MEDICAMENTO_LISTA`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_MEDICAMENTO_LISTA` SECURE LOOKUP

Replaces the value with one of the 23 values in `pt-medicamentos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Sertralina 50 mg`	→	**`Metformina`**

11.8 Clinical text

PT_SAUDE_TEXTO_CLINICO

COLUMN NAME · DATA TYPE · FREE TEXT REDACTION

WHAT IT IS

Clinical diary, history, discharge notes, reports, triage.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_TEXTO_CLINICO — Path

85% `anamnese` `hist[oó]ria_?cl[ií]nica` `di[aá]rio_?cl[ií]nico` `evolu[cç][aã]o(_?(m[eé]dica|cl[ií]nica|de_?enfermagem))?` `exame_?objetivo` `plano_?(de_?)?(tratamento|cuidados)` `nota_?(de_?)?alta` `carta_?(de_?)?alta` `relat[oó]rio_?(m[eé]dico|cl[ií]nico|de_?alta|radiol[oó]gico|anatomopatol[oó]gico)` `notas?_?(m[eé]dicas|cl[ií]nicas|de_?enfermagem)` `triagem(_?texto)?` `soap` `clinical_?notes?` `discharge_?summary`

DATA TYPE PT_SAUDE_TEXTO_CLINICO — Type

Accepts text (length 30 or more); any other type rules the data class out.

HOW IT IS MASKED

Free Text Redaction, as for free text: identifiers become `[DADO]` and names `[NOME]`.

`PT_TEXTO_LIVRE` FREE TEXT REDACTION

Replaces the text matching 10 patterns with `[DADO]`, and the 1,618 terms of `pt-texto-nomes.txt` with `[NOME]`.

EXAMPLES

VALUE		MASKED
`Doente Gonçalves, utente 629033874, consulta por cefaleia.`	→	**`Doente [NOME], utente [DADO], consulta por cefaleia.`**

11.9 Test result

PT_SAUDE_RESULTADO_EXAME

COLUMN NAME · CHARACTER MAPPING

WHAT IT IS

Result of a lab analysis, a test or a clinical measurement.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_RESULTADO_EXAME — Path

80% `resultado_?(do_?)?(exame|an[aá]lise|teste|laborat[oó]rio|pcr|serologia|bi[oó]psia|citologia)` `(exame|an[aá]lise|teste)_?(resultado|laborat[oó]rio)` `glicemia` `glicose` `hemoglobina(_?glicada)?` `hba1c` `colesterol(_?(total|hdl|ldl))?` `imc` `tens[aã]o_?arterial` `teste_?(de_?)?gravidez` `espirometria` `taxa_?(de_?)?alcoolemia` `lab_?results?` `test_?results?`

50% `resultado` `exame` `analise`

HOW IT IS MASKED

Character by character, keeping the shape.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Positivo	→	**Qucuruhe**

11.10 HIV and sexually transmitted infections

PT_SAUDE_VIH

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Serological status, viral load, antiretroviral therapy, PrEP, other STIs, tuberculosis.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_VIH — Path

90% `vih(_?(estado|resultado|teste|diagn[oó]stico|positivo))?` `hiv` `sida` `aids` `serologia_?(vih|hiv)` `estado_?serol[oó]gico` `carga_?viral` `cd4` `tarv` `terap[eê]utica_?antirretroviral` `antirretrovira(l|is)` `prep` `profilaxia_?pr[eé]_?exposi[cç][aã]o` `ist` `ists` `infe[cç][aã]o(es|[oõ]es)?_?sexualmente_?transmiss[ií]ve(l|is)` `s[ií]filis` `hepatite_?[bc]` `tuberculose`

HOW IT IS MASKED

Suppressed: becomes `Sem informação` ; a yes/no flag stays a flag.

`PT_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_SUPRIMIR` .

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt` , chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt` , chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt` , chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt` , chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_SUPRIMIR` SECURE LOOKUP

Replaces the value with one of the 1 values in `pt-sem-informacao.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Positivo	→	**Sem informação**

11.11 Blood group

PT_SAUDE_GRUPO_SANGUINEO

COLUMN NAME | VALUE FORMAT | SECURE LOOKUP

WHAT IT IS

ABO group and Rh factor.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_GRUPO_SANGUINEO — Path

90% `grupo_?sangu[ií]neo` `tipo_?(de_?)?sangue` `rh` `fator_?rh` `grupo_?rh` `abo(_?rh)?` `blood_?(type|group)`

VALUE FORMAT PT_SAUDE_GRUPO_SANGUINEO — Values

PATTERN	STRENGTH	NOTES
One of 18 known values, ignoring case — A, A-, B, B-, AB, AB-, …	90%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Masked by the BloodType SL that comes with Delphix: one of the eight groups.

`dlpx-core:BloodType SL` SECURE LOOKUP

Comes with Delphix and is used as it ships. Replaces the blood group with one of the eight groups, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
0+	→	**0-**

11.12 Disability

PT_SAUDE_INCAPACIDADE

COLUMN NAME | VALUE FORMAT | REGEX DECOMPOSE

WHAT IT IS

Kind or degree of disability — the Atestado Médico de Incapacidade Multiuso, under the Tabela Nacional de Incapacidades, opens tax and social benefits from 60%.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_INCAPACIDADE — Path

90% `incapacidade(_?(grau|percentagem|tipo))?` `defici[eê]ncia[a-z_]*` `(tipo|cod|codigo|grau|percentagem)_?(de_?)?(incapacidade|defici[eê]ncia)` `atestado_?(m[eé]dico_?)?(de_?)?incapacidade(_?multiuso)?` `amim` `pessoa_?com_?defici[eê]ncia` `mobilidade_?reduzida` `necessidades_?(de_?sa[uú]de_?)?especiais` `nee` `disabilit(y|ies)`

VALUE FORMAT PT_SAUDE_INCAPACIDADE — Values

PATTERN	STRENGTH	NOTES
One of 22 known values, ignoring case — Motora, Orgânica, Visual, Auditiva, Intelectual, Psicossocial, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced within a list of kinds; a yes/no flag stays a flag.

`PT_INCAPACIDADE` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_INCAPACIDADE_LISTA`.

> `PT_INDICADOR` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PT_INDICADOR_SIM_NAO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.
>
> `PT_INCAPACIDADE_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 8 values in `pt-incapacidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Perturbação do espetro do autismo`	→	**`Sem incapacidade reconhecida`**

11.13 Dependency

PT_SAUDE_DEPENDENCIA

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

The degree of the complemento por dependência of the Segurança Social, the status of informal carer (Lei n.º 100/2019), long-term care.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_DEPENDENCIA — Path

90% `depend[eê]ncia(_?(grau|reconhecida|avalia[cç][aã]o))?` `grau_?(de_?)?depend[eê]ncia` `complemento_?(por_?)?depend[eê]ncia` `cuidador_?informal` `estatuto_?(do_?)?cuidador` `apoio_?domicili[aá]rio` `cuidados_?continuados` `rncci` `teleassist[eê]ncia`

VALUE FORMAT PT_SAUDE_DEPENDENCIA — Values

PATTERN	STRENGTH	NOTES
One of 9 known values, ignoring case — Dependência de 1.º grau, Dependência de 2.º grau, Sem dependência reconhecida, Em avaliação, 1.º grau, 2.º grau, …	70%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced within the list; a code becomes another code.

`PT_DEPENDENCIA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_DEPENDENCIA_LISTA`.

> `PT_INDICADOR` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PT_INDICADOR_SIM_NAO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.
>
> `PT_DEPENDENCIA_CODIGO` SECURE LOOKUP
>
> Replaces the value with one of the 2 values in `pt-dependencia-codigos.txt`, chosen by a keyed hash.
>
> `PT_DEPENDENCIA_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 4 values in `pt-dependencia.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Dependência de 2.º grau`	→	**`Em avaliação`**
`1`	→	**`1`**

11.14 Occupational health

PT_SAUDE_TRABALHO

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Fitness certificate, occupational medicine exams, work accidents, occupational diseases, sick leave. Lei n.º 102/2009 lets occupational medicine tell the employer only whether the worker is fit, and the Código do

Trabalho (arts. 17.º and 19.º) protects the worker's health from the employer.

HOW IT IS FOUND

COLUMN NAME PT_SAUDE_TRABALHO — Path

85% `aptid[aã]o_?(m[eé]dica|para_?o_?trabalho)?` `ficha_?(de_?)?aptid[aã]o` `medicina_?(do_?)?trabalho` `sa[uú]de_?(no_?|do_?)?trabalho` `exame_?(de_?)?(admiss[aã]o|peri[oó]dico|ocasional)` `acidente_?(de_?)?trabalho` `doen[cç]a_?profissional` `incapacidade_?(tempor[aá]ria|permanente)` `cit` `certificado_?(de_?)?incapacidade_?tempor[aá]ria` `baixa(_?(m[eé]dica|por_?doen[cç]a))?` `dias_?(de_?)?baixa` `absentismo`

VALUE FORMAT PT_SAUDE_TRABALHO — Values

PATTERN	STRENGTH	NOTES
One of 9 known values, ignoring case — apto, inapto, apto condicionalmente, inapto temporariamente, inapto definitivamente, baixa médica, …	60%	
One of 13 known values, ignoring case — s, n, sim, não, 1, 2, …	30%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced within a list of fitness results; a yes/no flag stays a flag.

`PT_APTIDAO` **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_APTIDAO_LISTA`.

> `PT_INDICADOR` **REGEX DECOMPOSE**
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PT_INDICADOR_SIM_NAO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_TRUE_FALSE` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_YES_NO` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_S_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_Y_N` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_0_1` **SECURE LOOKUP**
> >
> > Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.
>
> `PT_CM_ALFANUM` **CHARACTER MAPPING**
>
> Maps each character to another of its group (9 groups), keeping length and format.
>
> `PT_APTIDAO_LISTA` **SECURE LOOKUP**
>
> Replaces the value with one of the 4 values in `pt-aptidao.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Inapto temporariamente`	→	**`Inapto temporariamente`**

11.15 Reproductive health

PT_SAUDE_REPRODUTIVA

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Pregnancy, childbirth, voluntary termination of pregnancy (Lei n.º 16/2007), contraception, medically assisted procreation (Lei n.º 32/2006).

HOW IT IS FOUND

> COLUMN NAME — PT_SAUDE_REPRODUTIVA — Path
>
> 90% `gravidez` `gr[aá]vida` `gestante` `gesta[cç][aã]o` `idade_?gestacional` `semanas_?(de_?)?gesta[cç][aã]o` `dum` `data_?([uú]ltima_?)?menstrua[cç][aã]o` `vigil[aâ]ncia_?(da_?)?gravidez` `pr[eé]_?natal` `parto(_?tipo)?` `ces[aá]riana` `ivg` `interrup[cç][aã]o_?(volunt[aá]ria_?)?(da_?)?gravidez` `aborto` `m[eé]todo_?contracetivo` `contrace[cç][aã]o` `planeamento_?familiar` `pma` `procria[cç][aã]o_?medicamente_?assistida` `fertiliza[cç][aã]o_?in_?vitro` `fiv` `sa[uú]de_?(sexual|reprodutiva)` `pregnan(t|cy)` `contracepti(on|ve)`

HOW IT IS MASKED

Suppressed: becomes `Sem informação`; a yes/no flag stays a flag.

`PT_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_SUPRIMIR`.

> `PT_INDICADOR` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PT_INDICADOR_SIM_NAO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.
>
> `PT_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `pt-sem-informacao.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`12 semanas de gestação`	→	**`Sem informação`**

11.16 Mental health

PT_SAUDE_MENTAL

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Psychiatric disorders, suicidal behaviour, addictions, compulsory admission.

HOW IT IS FOUND

> COLUMN NAME — PT_SAUDE_MENTAL — Path
>
> 90% `sa[uú]de_?mental` `perturba[cç][aã]o[a-z_]*` `psiqui[aá]tri[a-z_]*` `psicol[oó]gi[a-z_]*` `depress[aã]o` `ansiedade` `suic[ií]d[a-z_]*` `tentativa_?(de_?)?suic[ií]dio` `autoles[aã]o` `comportamento_?suicida` `consumo_?(de_?)?(subst[aâ]ncias|[aá]lcool|drogas)` `adi[cç][oõ]es` `toxicodepend[eê]ncia` `alcoolismo` `tabagismo` `jogo_?patol[oó]gico` `cri` `dicad` `internamento_?compulsivo` `mental_?health`

HOW IT IS MASKED

Suppressed: becomes `Sem informação`.

`PT_CATEGORIA_SUPRIMIDA` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_SUPRIMIR`.

> `PT_INDICADOR` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PT_INDICADOR_SIM_NAO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.
>
> `PT_SUPRIMIR` SECURE LOOKUP
>
> Replaces the value with one of the 1 values in `pt-sem-informacao.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Perturbação bipolar`	→	**`Sem informação`**

PART 12

Economic and tax data (art. 64.º LGT)

Financial data are not a special category, but a test copy holding them does the most harm when it leaks, and a salary beside a concelho identifies. **Article 64.º of the Lei Geral Tributária** binds to secrecy everyone at the Autoridade Tributária who learns of a taxpayer's tax situation; the **Central de Responsabilidades de Crédito** of the Banco de Portugal holds every loan of every borrower; and the **PERSI** (Decreto-Lei n.º 227/2012) is the procedure a bank must follow before suing over a defaulted consumer loan. Amounts are masked keeping their order of magnitude; statuses, within their vocabulary.

12.1 Credit history

PT_FIN_CREDITO

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Responsibilities in the Banco de Portugal's Central, PERSI, default, insolvency, risk rating.

HOW IT IS FOUND

> COLUMN NAME PT_FIN_CREDITO — Path
>
> 90% `hist[oó]rico_?(de_?)?cr[eé]dito` `crc` `central_?(de_?)?responsabilidades_?(de_?)?cr[eé]dito` `mapa_?(de_?)?responsabilidades` `persi` `incumprimento` `cr[eé]dito_?(vencido|malparado)` `scoring(_?(de_?)?cr[eé]dito)?` `score(_?cr[eé]dito)?` `rating_?(de_?)?cr[eé]dito` `nota[cç][aã]o_?(de_?)?risco` `classe_?(de_?)?risco` `dias_?(de_?)?(atraso|incumprimento|mora)` `devedor_?(relapso|em_?mora)` `insolv[eê]ncia(_?pessoal)?` `per` `peap` `lista_?(negra|de_?devedores)` `credit_?score` `credit_?rating`

HOW IT IS MASKED

A status becomes another from a list; a score changes digit by digit; a flag stays a flag.

`PT_HISTORICO_CREDITO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_ESTADO_CREDITO`.

> `PT_CM_DIGITOS` CHARACTER MAPPING
>
> Maps each character to another of its group (1 groups), keeping length and format.
>
> `PT_INDICADOR` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PT_INDICADOR_SIM_NAO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.
>
> `PT_ESTADO_CREDITO` SECURE LOOKUP
>
> Replaces the value with one of the 10 values in `pt-estados-credito.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Em PERSI	→	**Regularizado**
745	→	**471**

12.2 Debt

PT_FIN_DIVIDA

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Outstanding balance, loan or instalment amount, credit limit, garnishment.

HOW IT IS FOUND

COLUMN NAME PT_FIN_DIVIDA – Path

85% `saldo_?(devedor|em_?d[ií]vida|em_?atraso|cr[eé]dito|empr[eé]stimo|hipoteca)` `montante_?(da_?)?(d[ií]vida|presta[cç][aã]o|empr[eé]stimo|cr[eé]dito|penhora|financiado)` `d[ií]vida(_?total)?` `capital_?(em_?d[ií]vida|em_?falta)` `plafond` `limite_?(de_?)?(cr[eé]dito|cart[aã]o)` `presta[cç][aã]o_?(mensal|cr[eé]dito|habita[cç][aã]o)` `penhora(_?(montante|valor))?` `loan_?(amount|balance)` `outstanding_?balance` `debt`

DATA TYPE PT_FIN_DIVIDA – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, which comes with Delphix: each digit becomes another, and the amount keeps its number of digits, its sign and its decimals — the same order of magnitude, unrelated to the real amount.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
18500	→	**10882**

12.3 Income

PT_FIN_RENDIMENTO

COLUMN NAME | DATA TYPE | NUMERIC MAPPING

WHAT IT IS

Salary, wage, pay, remuneration, household income.

HOW IT IS FOUND

COLUMN NAME PT_FIN_RENDIMENTO – Path

85% `vencimento(_?(base|bruto|l[ií]quido|mensal|anual))?` `sal[aá]rio(_?(base|bruto|l[ií]quido|mensal|anual))?` `ordenado(_?(base|bruto|l[ií]quido))?` `remunera[cç][aã]o(_?(base|bruta|l[ií]quida|anual|mensal))?` `rendimentos?(_?(mensal|anual|total|familiar|l[ií]quido|bruto|do_?agregado|per_?capita))?` `retribui[cç][aã]o` `salary` `income` `wages?`

DATA TYPE PT_FIN_RENDIMENTO – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, keeping the order of magnitude.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
1450	→	**7988**

12.4 Assets

PT_FIN_PATRIMONIO

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Taxable property value, valuation of a property, balances, deposits, investments, retirement savings plans (PPR).

HOW IT IS FOUND

COLUMN NAME PT_FIN_PATRIMONIO – Path

85% `patrim[oó]nio(_?(l[ií]quido|total))?` `valor_?patrimonial(_?tribut[aá]vel)?` `vpt` `valor_?(de_?)?(avalia[cç][aã]o|mercado|do_?im[oó]vel|da_?habita[cç][aã]o|do_?ve[ií]culo)` `saldo_?(conta|poupan[cç]a|dep[oó]sito|m[eé]dio)` `dep[oó]sitos?(_?a_?prazo)?` `aplica[cç][oõ]es_?financeiras` `carteira_?(de_?)?t[ií]tulos` `fundos?_?(de_?)?(investimento|pens[oõ]es)` `ppr` `net_?worth` `account_?balance`

DATA TYPE PT_FIN_PATRIMONIO – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, keeping the order of magnitude.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
185000	→	**477515**

12.5 Pension

PT_FIN_PENSAO

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Amount of an old-age, disability or survivor's pension, of maintenance, or of another benefit.

HOW IT IS FOUND

COLUMN NAME PT_FIN_PENSAO – Path

90% `pens[aã]o(_?` `(montante|valor|mensal|anual|velhice|invalidez|sobreviv[eê]ncia|alimentos|social))?` `reforma_?(montante|valor)` `montante_?(da_?)?(pens[aã]o|presta[cç][aã]o|subs[ií]dio)` `valor_?(da_?)?(pens[aã]o|presta[cç][aã]o|subs[ií]dio)` `pension_?amount`

DATA TYPE PT_FIN_PENSAO – Type

Accepts number; any other type rules the data class out.

HOW IT IS MASKED

Masked by CM Numeric, keeping the order of magnitude.

`dlpx-core:CM Numeric` NUMERIC MAPPING

Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
650	→	298

12.6 Social benefit

PT_FIN_PRESTACAO_SOCIAL

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Rendimento Social de Inserção, unemployment benefit, child benefit and its bracket, the Complemento Solidário para Idosos, the Prestação Social para a Inclusão, social tariff, school social support — a family's economic need.

HOW IT IS FOUND

COLUMN NAME PT_FIN_PRESTACAO_SOCIAL – Path

90% `presta[cç][aã]o(_?(social|de_?desemprego))?` `subs[ií]dio(_?(de_?desemprego|social|de_?doen[cç]a|parental))?` `rendimento_?social_?(de_?)?inser[cç][aã]o` `rsi` `abono(_?(de_?)?fam[ií]lia)?` `escal[aã]o_?(do_?)?(abono|ase|a[cç][aã]o_?social)` `complemento_?solid[aá]rio` `csi` `presta[cç][aã]o_?social_?(para_?a_?)?inclus[aã]o` `psi` `tarifa_?social` `a[cç][aã]o_?social_?escolar` `ase` `bolsa(_?(de_?)?estudo)?` `benefici[aá]rio_?(rsi|abono|subs[ií]dio|bolsa)` `apoio_?(social|[aà]_?renda|extraordin[aá]rio)` `vulnerabilidade` `car[eê]ncia_?econ[oó]mica` `social_?benefit`

VALUE FORMAT PT_FIN_PRESTACAO_SOCIAL – Values

PATTERN	STRENGTH	NOTES
One of 23 known values, ignoring case — Rendimento Social de Inserção, Subsídio de desemprego, Subsídio social de desemprego, Abono de família, Complemento Solidário para Idosos, Prestação Social para a Inclusão, …	80%	
One of 13 known values, ignoring case — s, n, sim, não, 1, 2, …	30%	

A value that matches none counts 40% against the data class.

HOW IT IS MASKED

Replaced within a list of benefits; a yes/no flag stays a flag.

`PT_PRESTACAO_SOCIAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_PRESTACAO_SOCIAL_LISTA`.

> `PT_INDICADOR` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PT_INDICADOR_SIM_NAO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.
>
> `PT_PRESTACAO_SOCIAL_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 12 values in `pt-prestacoes-sociais.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Rendimento Social de Inserção	→	**Subsídio de desemprego**

12.7 Tax data

PT_FIN_FISCAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Taxable income, tax due, refund or amount payable of the IRS, the IMI, withholdings — protected by the tax secrecy of article 64.º of the Lei Geral Tributária.

HOW IT IS FOUND

> COLUMN NAME PT_FIN_FISCAL – Path
>
> 90% `irs(_?(rendimento|coleta|reembolso|liquida[cç][aã]o|reten[cç][aã]o|montante|a_?pagar))?` `rendimento_?(coletável|colet[aá]vel|global|tribut[aá]vel)` `mat[eé]ria_?colet[aá]vel` `coleta(_?(l[ií]quida|total))?` `reembolso_?(de_?)?irs` `nota_?(de_?)?liquida[cç][aã]o` `modelo_?(3|10|22)` `imi(_?(valor|montante))?` `reten[cç][aã]o_?na_?fonte` `dedu[cç][oõ]es_?([aà]_?)?coleta` `escal[aã]o_?(de_?)?irs` `tax_?(base|return|amount)`

HOW IT IS MASKED

Each digit becomes another: the amount keeps its sign — a refund stays a refund — and its decimals.

`PT_FISCAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

> `dlpx-core:CM Numeric` **NUMERIC MAPPING**
>
> Comes with Delphix and is used as it ships. Maps each digit to another, keeping the number of digits, the sign, the decimal places and the zeros on the left — an amount keeps its order of magnitude.

EXAMPLES

VALUE		MASKED
−1240.55	→	**−7247.55**
24350	→	**15057**

PART 13

Criminal and administrative offences (art. 10 GDPR and art. 13.º, alínea b) of Lei n.º 58/2019)

Article 10 of the Regulation admits processing data on criminal convictions and offences only under the control of a public authority or a law that authorises it, and Portugal reads it for administrative offences too: article 13.º, alínea b) of Lei n.º 58/2019 speaks of data "relacionados com condenações penais e contraordenacionais". The criminal record is kept by the Direção-Geral da Administração da Justiça (Lei n.º 37/2015), which cancels decisions five to ten years after the sentence ends — a copy keeps them for as long as the copy lives.

13.1 Criminal record

PT_PENAL_REGISTO_CRIMINAL

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Criminal record, convictions, crimes, procedural and prison situation, coercive measures.

HOW IT IS FOUND

COLUMN NAME — PT_PENAL_REGISTO_CRIMINAL — Path

95%

`registo_?criminal` `certificado_?(de_?)?registo_?criminal` `crc_?(pessoa|individual)` `antecedentes(_?(criminais|penais|policiais))?` `cadastro(_?criminal)?` `reincid[eê]ncia` `condena[cç][aã]o(_?(penal|tipo))?` `crime(_?(tipo|cometido|praticado))?` `tipo_?(de_?)?crime` `situa[cç][aã]o_?(penal|processual|prisional)` `medida_?(de_?)?coa[cç][aã]o` `pris[aã]o_?preventiva` `recluso` `estabelecimento_?prisional` `liberdade_?condicional` `pulseira_?eletr[oó]nica` `criminal_?record`

55%

`estado_?(do_?)?processo` `senten[cç]a` `ac[oó]rd[aã]o` `decis[aã]o_?judicial`

HOW IT IS MASKED

Replaced within a list of situations; a yes/no flag stays a flag.

`PT_REGISTO_CRIMINAL` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_REGISTO_CRIMINAL_LISTA` .

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt` , chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt` , chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt` , chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt` , chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt` , chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt` , chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_REGISTO_CRIMINAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 8 values in `pt-registo-criminal.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Condenado por furto em 2019`	→	**`Sem informação`**

13.2 Certificate for work with minors

PT_PENAL_CERTIFICADO_MENORES

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

Lei n.º 113/2009 obliges whoever hires for work with regular contact with minors to ask for the candidate's criminal record certificate, and Lei n.º 103/2015 created the register of those convicted of crimes against the sexual self-determination of minors. Schools, clubs and companies keep the column — and its value is a criminal-record datum.

HOW IT IS FOUND

COLUMN NAME PT_PENAL_CERTIFICADO_MENORES – Path

95% `certificado_?(de_?)?registo_?criminal_?(para_?)?(fins_?de_?)?(contacto|trabalho)_?com_?menores` `crc_?menores` `lei_?113_?2009` `registo_?(de_?)?(identifica[cç][aã]o_?criminal_?de_?)?condenados_?(por_?crimes_?)?(contra_?a_?)?(autodetermina[cç][aã]o_?sexual)?` `crimes?_?sexua(l|is)(_?(contra_?)?menores)?` `abuso_?sexual_?(de_?)?menores`

VALUE FORMAT PT_PENAL_CERTIFICADO_MENORES – Values

PATTERN	STRENGTH	NOTES
One of 8 known values, ignoring case — certificado apresentado, apresentado, não apresentado, pendente, caducado, dispensado, …	60%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

Replaced within a list of certificate situations; a yes/no flag stays a flag.

`PT_CERTIFICADO_MENORES` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_CERTIFICADO_MENORES_LISTA`.

`PT_INDICADOR` REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`PT_INDICADOR_SIM_NAO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.

`PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

`PT_INDICADOR_YES_NO` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

`PT_INDICADOR_S_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_Y_N` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

`PT_INDICADOR_0_1` SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

`PT_CERTIFICADO_MENORES_LISTA` SECURE LOOKUP

Replaces the value with one of the 5 values in `pt-certificado-menores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
`Certificado apresentado`	→	**`Certificado caducado`**

13.3 Case number

PT_PENAL_PROCESSO

COLUMN NAME · VALUE FORMAT · REGEX DECOMPOSE

WHAT IT IS

The NUIPC of a criminal case — `123/24.5PBLSB`: the number, the year, a control digit and the code of the body and the place — or the number of a court case, written the same way: `1234/23.0T8LSB`.

HOW IT IS FOUND

COLUMN NAME PT_PENAL_PROCESSO – Path

90%	`nuipc` `n_u_i_p_c` `n(o|r|ro|um|umero)_?([uú]nico_?)?(de_?)?(identifica[cç][aã]o_?(do_?)?)?` `processo(_?(crime|judicial|penal|inqu[eé]rito))?` `processo_?(crime|judicial|penal|de_?inqu[eé]rito)` `inqu[eé]rito(_?(n(o|r|ro|um|umero)))?` `auto_?(de_?)?not[ií]cia` `n(o|r|ro)_?auto`
50%	`processo` `autos`

VALUE FORMAT PT_PENAL_PROCESSO – Regex

PATTERN	STRENGTH	NOTES
`0*(?:\d{1,7}/\d{2}\.\d[A-Z0-9]{2,8})`	90%	

A value that matches none counts 30% against the data class.

HOW IT IS MASKED

The number changes; the year, the digit and the code stay. The rule of the control digit is not public, so the masked number no longer passes it.

`PT_PROCESSO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

`PT_CM_DIGITOS` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

`PT_CM_ALFANUM` CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
`123/24.5PBLSB`	→	**`957/24.5PBLSB`**
`1234/23.0T8LSB`	→	**`9707/23.0T8LSB`**

13.4 Administrative offence

PT_PENAL_CONTRAORDENACAO

COLUMN NAME | REGEX DECOMPOSE

WHAT IT IS

Fines, records of contraordenações, traffic offences, the points of the driving licence (twelve, since 2016), driving bans.

HOW IT IS FOUND

COLUMN NAME — PT_PENAL_CONTRAORDENACAO — Path

90% `contraordena[cç][aã]o(es|[oõ]es)?(_?(tipo|grau|rodovi[aá]ria))?` `coima(s)?(_?(montante|valor|tipo))?` `auto_?(de_?)?contraordena[cç][aã]o` `infra[cç][aã]o(es|[oõ]es)?_?(rodovi[aá]ria|estradal|tr[aâ]nsito)` `multa(s)?(_?(tr[aâ]nsito|montante))?` `pontos_?(da_?)?carta` `saldo_?(de_?)?pontos` `perda_?(de_?)?pontos` `inibi[cç][aã]o_?(de_?)?conduzir` `cassa[cç][aã]o_?(da_?)?carta` `administrative_?(sanction|penalty)` `traffic_?fine`

HOW IT IS MASKED

Replaced within a list of situations; a number changes digit by digit; a flag stays a flag.

`PT_CONTRAORDENACAO` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_CONTRAORDENACAO_LISTA`.

> `PT_INDICADOR` REGEX DECOMPOSE
>
> Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
>
> > `PT_INDICADOR_SIM_NAO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-sim-nao.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_TRUE_FALSE` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_YES_NO` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_S_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-s-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_Y_N` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.
> >
> > `PT_INDICADOR_0_1` SECURE LOOKUP
> >
> > Replaces the value with one of the 2 values in `pt-indicador-0-1.txt`, chosen by a keyed hash.
>
> `PT_CM_ALFANUM` CHARACTER MAPPING
>
> Maps each character to another of its group (9 groups), keeping length and format.
>
> `PT_CONTRAORDENACAO_LISTA` SECURE LOOKUP
>
> Replaces the value with one of the 9 values in `pt-contraordenacoes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Perda de pontos	→	**Contraordenação leve**

14

Check characters

Almost every Portuguese identifier is checked by arithmetic, and a masked value whose check characters were not recomputed is refused by every form, bank or administration system that receives it — exactly what a test must avoid. The policy recomputes six rules.

Two fit the Check Digit framework as it is. The **civil identification number and the NIF** are eight digits and a ninth weighted 9 down to 2, modulo 11, eleven minus the remainder — and Portugal writes both 10 and 11 as 0, which is exactly what Check Digit writes. A mathematician of the Universidade de Coimbra showed that this lets many typing errors through in numbers ending in 0; for masking it is luck, since it needs no correction. The **NISS** is ten digits and an eleventh, nine minus the weighted sum modulo 10: Check Digit writes ten minus the remainder, and since only persons' NISS are masked — they start with 1 — giving that 1 the weight 0 instead of 29 adds the unit that turns one rule into the other.

The others are no weighted sum Check Digit writes: the last digit of the **document number** of the Cartão de Cidadão is a Luhn digit over digits and letters; that of the **número de utente**, an ISO/IEC 7064 MOD 11,10; that of the **prescription**, a MOD 11-2 that writes X; the two of the **NIB**, a remainder modulo 97; the two letters of the **CPE**, a remainder modulo 529. The policy computes them with tables. A **state** — what the rule has accumulated so far — is put in front of the value and crosses it one character at a time. Each step is a Regex Decompose that hands "state + next character" to a Data Cleansing whose table answers "next character + new state"; separators are stepped over by lines that carry the state unchanged, and a step that finds no line leaves the value as it is, so one chain serves every written form. At the end a last table turns the state into the check characters.

The tables are small — 130 lines for the número de utente, 143 for the prescription, 1,261 for the NIB, 1,300 for the Cartão de Cidadão, 6,877 for the CPE —, and each chain is run in the build itself with masking taken as the identity: it must hand a valid example back unchanged, or the build fails. The example of the número de utente is the one the Universidade dos Açores published, `629033874`; those of the CPE, two codes from public tenders.

15

Where people live: concelhos, freguesias and postal codes

Portugal divides into 18 distritos on the mainland and two autonomous regions, **308 concelhos** and, since the local elections of 2025, 3,259 freguesias. In the Censos 2021, **188 concelhos had fewer than 20,000 inhabitants** — 1.6 million people — and so did **2,973 of the 3,092 freguesias** of the time, home to 6.3 million, more than 60% of the country. A birth date, a sex and one of those freguesias point at a handful of neighbours.

A concelho below the threshold becomes the **nearest concelho of at least 20,000 in the same distrito**, measured between centres; every distrito has one — its capital at least —, so a generalized value never leaves its distrito. On the islands the reference is the autonomous region: in the Açores Ponta Delgada, Ribeira Grande and Angra do Heroísmo stay, and a small concelho of another island goes to the nearest large one, on another island; in Madeira Funchal, Santa Cruz and Câmara de Lobos stay, and Porto Santo goes to Madeira.

A freguesia below the threshold becomes the **most populous freguesia of the concelho its own concelho goes to** — the seat, as a rule —, chosen among those that still exist. **Lei n.º 25-A/2025** brought back 302 freguesias merged in 2013, effective when the bodies elected in 2025 took office; the table holds the names of both generations — the 3,092 of the 2013 map, unions included, and the 303 that came back, with the population GeoNames gives them —, so an old database and a new one are both recognised. Names shared

by several freguesias — `Santa Maria`, `São Pedro`, `Sé` — are generalized on their own only when all that bear them are small; written with the concelho beside them, the rule applies inside it.

The codes follow the names. The DICO of a small concelho becomes that of the destination concelho, the DICOFRE of a small freguesia that of its destination freguesia, always in the same distrito or region. The postal code follows the concelho the CP4 mostly serves, by the addresses of the CTT postal code database: a CP4 whose main concelho is small becomes the main CP4 of the destination concelho — 253 of the 760 —, so masked postal code and concelho agree.

16

Limits

- **Masking with a key is pseudonymisation, not anonymisation.** Whoever holds the key and the production data can reproduce the mapping, so the masked copy is still personal data for them and still needs the measures of article 32 of the Regulation. Keep the key apart from the copy and do not call the copy anonymous while the key exists.
- **Populations are those of the Censos 2021**, and those of the freguesias brought back in 2025 the ones GeoNames gives them. A freguesia or concelho near 20,000 may cross the line; rebuild the policy when the INE publishes populations for the new freguesias.
- **Names of freguesias older than 2013** that did not come back in 2025 are not in the table and pass unchanged, like any name the table does not know: a place, a village, a typo. A name that, without accents, coincides with a distrito or region — `Madeirã` is `Madeira` — is generalized only when written with its concelho.
- **A CP4 may cover more than one concelho.** The policy follows the concelho with most addresses; the CP4 of a large town that also serves villages of neighbouring concelhos stays, and with it the hint that the person lives in one of them. The postal code database used dates from 2020.
- **The masked CP3 may not exist.** The three digits change one by one; the code keeps the shape of a postal code and the right CP4, but not every CP4-CP3 so formed is assigned by the CTT.
- **Bank and branch are kept.** They are not personal data, and keeping them keeps a test account inside a real bank; but the branch may point at a town. Mask the branch with a rule of its own where that matters.
- **The control digit of the NUIPC is not recomputed**: its rule is not public. The masked number has the shape of a NUIPC but does not pass the check.
- **Driving licence, residence permit and ADSE beneficiary** have no public rule of formation — the ADSE number uses the NIF's rule, but its full format is not public — and are masked character by character, recomputing nothing.
- **A single M is read as male.** It is the convention of the Cartão de Cidadão (F/M); a column coding sex as H/M would get F in some rows and should have an algorithm of its own.
- **A nine-digit number is ambiguous.** NIF, civil number with its digit, número de utente and landline share the shape; without a column name that says which, discovery picks the NIF, and the NIF's masking keeps the first digit and recomputes the last — which, in a número de utente, would break its digit.
- **Free text** is suppressed word by word: Free Text Redaction splits on spaces, so a number written in groups is reached in pieces, and the policy's patterns cover the eight or nine digits of each piece.
- **Children**: a birth date moves at most 60 days, so few people cross 13 — the age of digital consent under article 16.º of Lei n.º 58/2019 — or 18; but some do. Split the rule by age group with Multi-Column Condition where that matters.
- **Binary columns and attachments are out of reach.** A scan of the Cartão de Cidadão — which article 5.º of Lei n.º 7/2007 allows only with consent —, a photograph, the PDF of a medical report keep everything the columns beside them no longer say. Inventory them and report them as residual risk.

- **Discovery is a proposal, not a verdict.** The classifiers read column names and values; a column with a name no one recognises may escape, and one with a person's name may be caught by mistake. Review the inventory before running a masking job.

17

Verification

The policy is checked on every build. Each chain that computes a check character is run first in the build itself with masking taken as the identity, and must hand back a valid example unchanged — the Cartão de Cidadão `12345678 9 ZZ1`, the NIB and the IBAN compact and printed, the número de utente `629033874`, a prescription number and the CPE `PT00020000664351120Y`. The rules are checked beforehand against published examples: the número de utente of the Universidade dos Açores, an ORCID for MOD 11-2, the document numbers of python-stdnum, two CPE from public tenders.

The 155 classifier configurations are reviewed one by one, and a battery of 153 columns — well named, badly named, named in English, with opaque names like those of a banking package, and 31 that are not personal data at all, the NIF of a company among them — is profiled with the whole policy at the threshold of 60 and again with the essential pack only: every column lands where it should, and none of the 31 is claimed. The same columns are profiled again with values padded with spaces and zeros, as a CHAR column hands them over.

The generalization is audited offline: the 308 concelhos, the 3,395 freguesias of both generations and the 760 CP4 are checked against the rule — each replacement names a place of at least 20,000, or the seat freguesia of the destination concelho, in the same distrito or region.

Masking is run for real, in the plugin, across every data class — samples, flags and each algorithm's sample input —, each value checked against what it must become, and again with spaces and zeros around it. Then in bulk: 200 document numbers of the Cartão de Cidadão, 100 civil numbers, 200 NIFs, 150 NISS, 150 números de utente, 100 prescriptions, 200 IBANs — a hundred compact and a hundred printed in groups of four —, 100 NIBs and 100 CPE give as many distinct outputs, **all valid under their own rule**, of the same shape, and keeping what they should keep: the card's version, the kind of taxpayer, the health region, bank and branch, the network operator.

18

Sources

- Regulation (EU) 2016/679, General Data Protection Regulation: articles 4, 6, 9, 10, 25, 32 and 83, and recitals 14 and 26.
- Lei n.º 58/2019, de 8 de agosto, ensuring the execution of the GDPR (unamended since publication): articles 13.º, 16.º, 17.º, 19.º, 21.º, 28.º to 31.º, 37.º, 38.º, 46.º to 48.º, 53.º and 58.º.
- Comissão Nacional de Proteção de Dados, Deliberação 2019/494, of 3 September 2019 (disapplication of provisions of Lei n.º 58/2019).
- Constitution of the Portuguese Republic, articles 13.º, 26.º and 35.º.
- Resolução do Conselho de Ministros n.º 41/2018, of 28 March, minimum technical requirements for the networks and information systems of the public administration.
- Court of Justice of the European Union, judgment of 4 September 2025, EDPS v SRB, C-413/23 P; judgment of 19 October 2016, Breyer, C-582/14. European Data Protection Board, Guidelines 01/2025 on pseudonymisation (16 January 2025) and Guidelines on anonymisation (adopted 7 July 2026, in public consultation).

- Lei n.º 7/2007 (Cartão de Cidadão), articles 2.º, 5.º, 16.º and 17.º; Lei n.º 12/91 (bilhete de identidade); Lei n.º 12/2005 (personal genetic and health information), articles 3.º and 4.º; Decreto-Lei n.º 198/95 and Portaria n.º 981/95 (health user card); Lei n.º 102/2009 (safety and health at work); Código do Trabalho, articles 17.º and 19.º; Lei n.º 38/2018; Lei n.º 112/2009; Lei n.º 100/2019; Lei n.º 16/2007; Lei n.º 32/2006.
- Lei Geral Tributária, article 64.º; Decreto-Lei n.º 227/2012 (PERSI); Lei n.º 37/2015 (criminal identification); Lei n.º 113/2009 and Lei n.º 103/2015 (protection of minors); Código da Estrada.
- Lei n.º 25-A/2025, of 13 March, bringing back freguesias merged by Lei n.º 11-A/2013.
- Instituto Nacional de Estatística, Censos 2021: resident population by concelho and freguesia (indicator 0011609). GeoNames: centres of the concelhos and the 2025 freguesias with their DICO and DICOFRE codes. CTT postal code database (2020).
- The rules of the check characters: R. C. Teixeira, Universidade dos Açores, on the civil identification number and the NIF and on the número de utente (MOD 11,10); ISO/IEC 7064 for MOD 11,10 and MOD 11-2; the Agência para a Modernização Administrativa, "Validação de Número de Documento do Cartão de Cidadão", and the independent implementations of python-stdnum and django-localflavor for the document number and the NISS; the Banco de Portugal and ISO 13616 for the NIB and the IBAN; the CPE checked against codes published in public tenders.

APPENDIX A

Algorithms

Every algorithm of the policy in alphabetical order, with its configuration. The one a data class names is the top of its tree; the others are building blocks.

PT_ANO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_L2_ANO_NASCIMENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{3})(\d))`	keep · keep · `PT_CM_DIGITOS`
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_APELIDO NAME

Replaces the name with one of the 425 names in `pt-apelidos.txt`.

Used by: `PT_PALAVRA_APELIDO`

CONFIGURATION

`lookupFile`	`pt-apelidos.txt`
`maskedValueCase`	`PRESERVE_INPUT`
`filterAccent`	yes
`inputCaseSensitive`	no

PT_APELIDOS REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_L1_APELIDO`, `PT_NOME_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`PT_PALAVRA_APELIDO`
`(\S+)\s+(\S+)`	`PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO`
`otherwise`	`PT_CM_ALFANUM`

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_APTIDAO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_APTIDAO_LISTA`.

Used by: `PT_SAUDE_TRABALHO`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_ALFANUM`
otherwise	`PT_APTIDAO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_APTIDAO_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in `pt-aptidao.txt`, chosen by a keyed hash.

Used by: `PT_APTIDAO`

CONFIGURATION

lookupFile	`pt-aptidao.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_CARTAO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_L1_CARTAO_PAGAMENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d[\d\s\-]{11,22}\d))`	keep · `dlpx-core:Credit Card`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_SUPRIMIR`.

Used by: `PT_L3_CONVICCAO_FILOSOFICA`, `PT_L3_FILIACAO_SINDICAL`, `PT_L3_VIDA_SEXUAL`, `PT_L3_VITIMA`, `PT_SAUDE_VIH`, `PT_SAUDE_REPRODUTIVA`, `PT_SAUDE_MENTAL`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(0*?)(?:(\d{1,6}))))))))`	keep · keep · keep · keep · keep · keep · keep · `PT_CM_ALFANUM`
otherwise	`PT_SUPRIMIR`

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC STRING ALGORITHM CHAIN

Applies `PT_CC_1` → `PT_CC_2` → `PT_CC_3`, in this order.

Used by: `PT_IDENTIFICACAO`

CONFIGURATION

`algorithmReferences[1]`	`PT_CC_1`
`algorithmReferences[2]`	`PT_CC_2`
`algorithmReferences[3]`	`PT_CC_3`

`PT_CC_1` STRING ALGORITHM CHAIN

Applies `PT_CC_NIC` → `PT_CC_MARCAR` → `PT_CC_PREPARAR` → `PT_CC_PASSO_00` → `PT_CC_PASSO_01` → `PT_CC_PASSO_02` → `PT_CC_PASSO_03` → `PT_CC_PASSO_04` , in this order.

Used by: `PT_CC`

CONFIGURATION

`algorithmReferences[1]`	`PT_CC_NIC`
`algorithmReferences[2]`	`PT_CC_MARCAR`
`algorithmReferences[3]`	`PT_CC_PREPARAR`
`algorithmReferences[4]`	`PT_CC_PASSO_00`
`algorithmReferences[5]`	`PT_CC_PASSO_01`
`algorithmReferences[6]`	`PT_CC_PASSO_02`
`algorithmReferences[7]`	`PT_CC_PASSO_03`
`algorithmReferences[8]`	`PT_CC_PASSO_04`

`PT_CC_2` STRING ALGORITHM CHAIN

Applies `PT_CC_PASSO_05` → `PT_CC_PASSO_06` → `PT_CC_PASSO_07` → `PT_CC_PASSO_08` → `PT_CC_PASSO_09` → `PT_CC_PASSO_10` → `PT_CC_PASSO_11` → `PT_CC_PASSO_12` , in this order.

Used by: `PT_CC`

CONFIGURATION

`algorithmReferences[1]`	`PT_CC_PASSO_05`
`algorithmReferences[2]`	`PT_CC_PASSO_06`
`algorithmReferences[3]`	`PT_CC_PASSO_07`
`algorithmReferences[4]`	`PT_CC_PASSO_08`
`algorithmReferences[5]`	`PT_CC_PASSO_09`
`algorithmReferences[6]`	`PT_CC_PASSO_10`
`algorithmReferences[7]`	`PT_CC_PASSO_11`
`algorithmReferences[8]`	`PT_CC_PASSO_12`

`PT_CC_3` STRING ALGORITHM CHAIN

Applies `PT_CC_PASSO_13` → `PT_CC_CONTROLO` → `PT_CC_RESTAURAR` , in this order.

Used by: `PT_CC`

CONFIGURATION

`algorithmReferences[1]`	`PT_CC_PASSO_13`
`algorithmReferences[2]`	`PT_CC_CONTROLO`
`algorithmReferences[3]`	`PT_CC_RESTAURAR`

`PT_CC_CONTROLO` REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_3`

PATTERNS, TRIED IN ORDER

`(.*)(\d[12]~)`	keep · `PT_CC_CONTROLO_TABELA`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_CONTROLO_TABELA DATA CLEANSING

Replaces each value found in `pt-cc-controlo.txt` (20 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PT_CC_CONTROLO`

CONFIGURATION

lookupFile	`pt-cc-controlo.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PT_CC_MARCAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_1`

PATTERNS, TRIED IN ORDER

`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_NIC REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_1`

PATTERNS, TRIED IN ORDER

`(\d{8}[\s\-]?\d)(.*)`	`PT_NIC` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PASSO DATA CLEANSING

Replaces each value found in `pt-cc-passo.txt` (1,300 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PT_CC_PASSO_00`, `PT_CC_PASSO_01`, `PT_CC_PASSO_02`, `PT_CC_PASSO_03`, `PT_CC_PASSO_04`, `PT_CC_PASSO_05`, `PT_CC_PASSO_06`, `PT_CC_PASSO_07`, `PT_CC_PASSO_08`, `PT_CC_PASSO_09`, `PT_CC_PASSO_10`, `PT_CC_PASSO_11`, `PT_CC_PASSO_12`, `PT_CC_PASSO_13`

CONFIGURATION

lookupFile	`pt-cc-passo.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PT_CC_PASSO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_1`

PATTERNS, TRIED IN ORDER

`(.{0})(.{3})(.*)`	keep · `PT_CC_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PASSO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_1`

PATTERNS, TRIED IN ORDER

`(.{1})(.{3})(.*)`	keep · `PT_CC_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PASSO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_1`

PATTERNS, TRIED IN ORDER

`(.{2})(.{3})(.*)`	keep · `PT_CC_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PASSO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_CC_1

PATTERNS, TRIED IN ORDER

(.{3})(.{3})(.*)	keep · PT_CC_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PASSO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_CC_1

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · PT_CC_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PASSO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_CC_2

PATTERNS, TRIED IN ORDER

(.{5})(.{3})(.*)	keep · PT_CC_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PASSO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_CC_2

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · PT_CC_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PASSO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_2`

PATTERNS, TRIED IN ORDER

`(.{7})(.{3})(.*)`	keep · `PT_CC_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CC_PASSO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_2`

PATTERNS, TRIED IN ORDER

`(.{8})(.{3})(.*)`	keep · `PT_CC_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CC_PASSO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_2`

PATTERNS, TRIED IN ORDER

`(.{9})(.{3})(.*)`	keep · `PT_CC_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CC_PASSO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_2`

PATTERNS, TRIED IN ORDER

`(.{10})(.{3})(.*)`	keep · `PT_CC_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CC_PASSO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_2`

PATTERNS, TRIED IN ORDER

`(.{11})(.{3})(.*)`	keep · `PT_CC_PASS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PASS0_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_2`

PATTERNS, TRIED IN ORDER

`(.{12})(.{3})(.*)`	keep · `PT_CC_PASS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PASS0_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_3`

PATTERNS, TRIED IN ORDER

`(.{13})(.{3})(.*)`	keep · `PT_CC_PASS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_PREPARAR REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CC_1`

PATTERNS, TRIED IN ORDER

`(0)(.*)([0-9])`	replace with `020` · keep · replace with `~`
`(1)(.*)([0-9])`	replace with `021` · keep · replace with `~`
`(2)(.*)([0-9])`	replace with `022` · keep · replace with `~`
`(3)(.*)([0-9])`	replace with `023` · keep · replace with `~`
`(4)(.*)([0-9])`	replace with `024` · keep · replace with `~`
`(5)(.*)([0-9])`	replace with `025` · keep · replace with `~`
`(6)(.*)([0-9])`	replace with `026` · keep · replace with `~`
`(7)(.*)([0-9])`	replace with `027` · keep · replace with `~`
`(8)(.*)([0-9])`	replace with `028` · keep · replace with `~`
`(9)(.*)([0-9])`	replace with `029` · keep · replace with `~`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CC_RESTAURAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_CC_3

PATTERNS, TRIED IN ORDER

([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep
([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep
([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep
([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)	keep · replace with · keep · replace with · keep · replace with · keep
([^_]*)(_)([^_]*)(_)([^_]*)	keep · replace with · keep · replace with · keep
([^_]*)(_)([^_]*)	keep · replace with · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CERTIFICADO_MENORES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: PT_CERTIFICADO_MENORES_LISTA.

Used by: PT_PENAL_CERTIFICADO_MENORES

PATTERNS, TRIED IN ORDER

(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])	PT_INDICADOR
(0*?)(?:(\d{1,6}))	keep · PT_CM_ALFANUM
otherwise	PT_CERTIFICADO_MENORES_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

PT_CERTIFICADO_MENORES_LISTA SECURE LOOKUP

Replaces the value with one of the 5 values in pt-certificado-menores.txt, chosen by a keyed hash.

Used by: PT_CERTIFICADO_MENORES

CONFIGURATION

lookupFile	pt-certificado-menores.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_CID10 SECURE LOOKUP

Replaces the value with one of the 46 values in `pt-cid10.txt`, chosen by a keyed hash.

Used by: `PT_DIAGNOSTICO`

CONFIGURATION

lookupFile	`pt-cid10.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_CID10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `pt-cid10-decimal.txt`, chosen by a keyed hash.

Used by: `PT_DIAGNOSTICO`

CONFIGURATION

lookupFile	`pt-cid10-decimal.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (9 groups), keeping length and format.

Used by: `PT_L1_TITULO_RESIDENCIA`, `PT_L1_NUMERO_ESTUDANTE`, `PT_L1_CEDULA_PROFISSIONAL`, `PT_L1_MORADA_COMPLEMENTO`, `PT_L1_CARTEIRA_DIGITAL`, `PT_L1_COOKIE`, `PT_L1_VEICULO`, `PT_L1_CONTRATO`, `PT_L1_UTILIZADOR`, `PT_SAUDE_IDENTIFICADOR`, `PT_SAUDE_RESULTADO_EXAME`, `PT_CATEGORIA_SUPRIMIDA`, `PT_IDENTIFICACAO`, `PT_NIF`, `PT_NISS`, `PT_NOMES`, `PT_APELIDOS`, `PT_NOME_COMPLETO`, `PT_EMAIL`, `PT_IMOVEL`, `PT_CPE`, `PT_SITUACAO_RESIDENCIA`, `PT_RELIGIAO`, `PT_PARTIDO`, `PT_ORIENTACAO_SEXUAL`, `PT_IDENTIDADE_GENERO`, `PT_NUMERO_UTENTE`, `PT_NUMERO_RECEITA`, `PT_MEDICAMENTO`, `PT_INCAPACIDADE`, `PT_APTIDAO`, `PT_PRESTACAO_SOCIAL`, `PT_REGISTO_CRIMINAL`, `PT_CERTIFICADO_MENORES`, `PT_PROCESSO`, `PT_CONTRAORDENACAO`

CONFIGURATION

characterGroups	`0123456789` `AEIOU` `BCDFGHJKLMNPQRSTVWXYZ` `aeiou` `bcdfghjklmnpqrstvwxyz` `ÁÉÍÓÚ` `áéíóú` `ÂÊÔÃÕ` `âêôãõ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

PT_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: `PT_IDENTIFICACAO`, `PT_TELEFONE`, `PT_CONTA`, `PT_IMOVEL`, `PT_COORDENADA`, `PT_ANO`, `PT_IDADE`, `PT_CODIGO_POSTAL`, `PT_PROFISSAO_OU_CODIGO`, `PT_COBERTURA_SAUDE`, `PT_PROCEDIMENTO`, `PT_HISTORICO_CREDITO`, `PT_PROCESSO`

CONFIGURATION

characterGroups	`0123456789`
caseSensitive	yes
minMaskedPositions	`0`

preserveLeadingZeros	yes

PT_CM_DIGITOS_LARGURA_FIXA CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: `PT_NIF_CORPO`, `PT_NISS_CORPO`, `PT_NIB_CONTA`, `PT_NIB_IMPRESSO_CONTA`, `PT_CPE_PONTO`, `PT_UTENTE_CORPO`, `PT_RECEITA_CORPO`

CONFIGURATION

characterGroups	`0123456789`
caseSensitive	yes
minMaskedPositions	`0`

PT_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: `PT_L1_PASSAPORTE`, `PT_L1_CARTA_CONDUCAO`, `PT_IDENTIFICACAO`, `PT_MATRICULA`, `PT_PROCEDIMENTO`

CONFIGURATION

characterGroups	`0123456789` `ABCDEFGHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

PT_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `PT_L1_DISPOSITIVO`, `PT_IP`

CONFIGURATION

characterGroups	`0123456789` `abcdef` `ABCDEF` `ghijklmnopqrstuvwxyz` `GHIJKLMNOPQRSTUVWXYZ`
caseSensitive	yes
minMaskedPositions	`0`
preserveLeadingZeros	yes

PT_CM_MATRICULA CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: `PT_MATRICULA`

CONFIGURATION

characterGroups	`0123456789` `ABCDEFGHIJLMNOPQRSTUVXZ`
caseSensitive	yes
minMaskedPositions	`0`

PT_COBERTURA SECURE LOOKUP

Replaces the value with one of the 9 values in `pt-cobertura-saude.txt`, chosen by a keyed hash.

Used by: `PT_COBERTURA_SAUDE`

CONFIGURATION

lookupFile	`pt-cobertura-saude.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_COBERTURA_SAUDE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_COBERTURA`.

Used by: `PT_SAUDE_SUBSISTEMA`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,8}))`	keep · `PT_CM_DIGITOS`
otherwise	`PT_COBERTURA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_CODIGO_AUTARQUICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_L2_CODIGO_AUTARQUICO`

PATTERNS, TRIED IN ORDER

`(0*)([1-9]\d{2,3}[A-Za-z]{2})`	keep · `PT_CODIGO_AUTARQUICO_TABELA`
`(0*)([1-9]\d*)`	keep · `PT_CODIGO_AUTARQUICO_TABELA`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CODIGO_AUTARQUICO_TABELA DATA CLEANSING

Replaces each value found in `pt-codigos-autarquicos-generalizados.txt` (5,039 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PT_CODIGO_AUTARQUICO`

CONFIGURATION

lookupFile	`pt-codigos-autarquicos-generalizados.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PT_CODIGO_POSTAL REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_L2_CODIGO_POSTAL`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{4})(-)(\d{3})(\s+)(.+))`	keep · `PT_CP4` · keep · `PT_CM_DIGITOS` · keep · `PT_CONCELHO`
`(0*?)(?:(\d{4})([\s\-]?)(\d{3}))`	keep · `PT_CP4` · keep · `PT_CM_DIGITOS`
`(0*?)(?:(\d{4}))`	keep · `PT_CP4`

otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CONCELHO DATA CLEANSING

Replaces each value found in `pt-concelhos-generalizados.txt` (1,612 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PT_L2_CONCELHO`, `PT_CODIGO_POSTAL`

CONFIGURATION

lookupFile	`pt-concelhos-generalizados.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PT_CONTA REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_DIGITOS`.

Used by: `PT_L1_CONTA_BANCARIA`

PATTERNS, TRIED IN ORDER

`(PT50)(\d{21})`	keep · `PT_NIB`
`(PT50 )(\d{4} \d{4} \d{4} \d{4} \d{4} \d)`	keep · `PT_NIB_IMPRESSO`
`(0*?)(?:(\d{4}[\s.\-]?\d{4}[\s.\-]?\d{11}[\s.\-]?\d{2}))`	keep · `PT_NIB`
`((?!PT)[A-Z]{2}\d{2}[A-Z0-9]{10,30})`	`PT_IBAN_ESTRANGEIRO`
otherwise	`PT_CM_DIGITOS`

CONFIGURATION

trimInput	yes
requireMask	no

PT_CONTAGEM_LIMITADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_L2_AGREGADO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([0-5]))`	keep · keep
`(0*?)(?:(\d+))`	keep · replace with `5`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CONTRAORDENACAO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_CONTRAORDENACAO_LISTA`.

Used by: `PT_PENAL_CONTRAORDENACAO`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_ALFANUM`
otherwise	`PT_CONTRAORDENACAO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_CONTRAORDENACAO_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in `pt-contraordenacoes.txt`, chosen by a keyed hash.

Used by: `PT_CONTRAORDENACAO`

CONFIGURATION

lookupFile	`pt-contraordenacoes.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_L1_GEOLOCALIZACAO`

PATTERNS, TRIED IN ORDER

`(-?\d{1,3}[.,]\d)(\d+)\s*([,;])\s*(-?\d{1,3}[.,]\d)(\d+)`	keep · `PT_CM_DIGITOS` · keep · keep · `PT_CM_DIGITOS`
`(-?\d{1,3}[.,]\d)(\d+)`	keep · `PT_CM_DIGITOS`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CP4 DATA CLEANSING

Replaces each value found in `pt-cp4-generalizados.txt` (253 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PT_CODIGO_POSTAL`

CONFIGURATION

lookupFile	`pt-cp4-generalizados.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PT_CPE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_L1_PONTO_ENTREGA`

PATTERNS, TRIED IN ORDER

`(PT\s?\d{4}\s?\d{4}\s?\d{4}\s?\d{4}\s?[A-Za-z]{2}(?:\d[A-Za-z])?)`	`PT_CPE_CADEIA`
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

`PT_CPE_CADEIA` STRING ALGORITHM CHAIN

Applies `PT_CPE_CADEIA_1` → `PT_CPE_CADEIA_2` → `PT_CPE_CADEIA_3` → `PT_CPE_CADEIA_4`, in this order.

Used by: `PT_CPE`

CONFIGURATION

algorithmReferences[1]	`PT_CPE_CADEIA_1`
algorithmReferences[2]	`PT_CPE_CADEIA_2`
algorithmReferences[3]	`PT_CPE_CADEIA_3`
algorithmReferences[4]	`PT_CPE_CADEIA_4`

`PT_CPE_CADEIA_1` STRING ALGORITHM CHAIN

Applies `PT_CPE_PONTO` → `PT_CPE_MARCAR` → `PT_CPE_PREPARAR` → `PT_CPE_PASSO_00` → `PT_CPE_PASSO_01` → `PT_CPE_PASSO_02` → `PT_CPE_PASSO_03` → `PT_CPE_PASSO_04`, in this order.

Used by: `PT_CPE_CADEIA`

CONFIGURATION

algorithmReferences[1]	`PT_CPE_PONTO`
algorithmReferences[2]	`PT_CPE_MARCAR`
algorithmReferences[3]	`PT_CPE_PREPARAR`
algorithmReferences[4]	`PT_CPE_PASSO_00`
algorithmReferences[5]	`PT_CPE_PASSO_01`
algorithmReferences[6]	`PT_CPE_PASSO_02`
algorithmReferences[7]	`PT_CPE_PASSO_03`
algorithmReferences[8]	`PT_CPE_PASSO_04`

`PT_CPE_CADEIA_2` STRING ALGORITHM CHAIN

Applies `PT_CPE_PASSO_05` → `PT_CPE_PASSO_06` → `PT_CPE_PASSO_07` → `PT_CPE_PASSO_08` → `PT_CPE_PASSO_09` → `PT_CPE_PASSO_10` → `PT_CPE_PASSO_11` → `PT_CPE_PASSO_12`, in this order.

Used by: `PT_CPE_CADEIA`

CONFIGURATION

algorithmReferences[1]	`PT_CPE_PASSO_05`
algorithmReferences[2]	`PT_CPE_PASSO_06`
algorithmReferences[3]	`PT_CPE_PASSO_07`
algorithmReferences[4]	`PT_CPE_PASSO_08`
algorithmReferences[5]	`PT_CPE_PASSO_09`
algorithmReferences[6]	`PT_CPE_PASSO_10`
algorithmReferences[7]	`PT_CPE_PASSO_11`
algorithmReferences[8]	`PT_CPE_PASSO_12`

PT_CPE_CADEIA_3 STRING ALGORITHM CHAIN

Applies `PT_CPE_PASSO_13` → `PT_CPE_PASSO_14` → `PT_CPE_PASSO_15` → `PT_CPE_PASSO_16` → `PT_CPE_PASSO_17` → `PT_CPE_PASSO_18` → `PT_CPE_PASSO_19` → `PT_CPE_PASSO_20`, in this order.

Used by: `PT_CPE_CADEIA`

CONFIGURATION

algorithmReferences[1]	`PT_CPE_PASSO_13`
algorithmReferences[2]	`PT_CPE_PASSO_14`
algorithmReferences[3]	`PT_CPE_PASSO_15`
algorithmReferences[4]	`PT_CPE_PASSO_16`
algorithmReferences[5]	`PT_CPE_PASSO_17`
algorithmReferences[6]	`PT_CPE_PASSO_18`
algorithmReferences[7]	`PT_CPE_PASSO_19`
algorithmReferences[8]	`PT_CPE_PASSO_20`

PT_CPE_CADEIA_4 STRING ALGORITHM CHAIN

Applies `PT_CPE_PASSO_21` → `PT_CPE_LETRAS` → `PT_CPE_RESTAURAR`, in this order.

Used by: `PT_CPE_CADEIA`

CONFIGURATION

algorithmReferences[1]	`PT_CPE_PASSO_21`
algorithmReferences[2]	`PT_CPE_LETRAS`
algorithmReferences[3]	`PT_CPE_RESTAURAR`

PT_CPE_LETRAS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_4`

PATTERNS, TRIED IN ORDER

`(.*)(\d{3}~)(.*)`	keep · `PT_CPE_LETRAS_TABELA` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_LETRAS_TABELA DATA CLEANSING

Replaces each value found in `pt-cpe-letras.txt` (529 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PT_CPE_LETRAS`

CONFIGURATION

lookupFile	`pt-cpe-letras.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PT_CPE_MARCAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_1`

PATTERNS, TRIED IN ORDER

`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO DATA CLEANSING

Replaces each value found in `pt-cpe-passo.txt` (6,877 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PT_CPE_PASSO_00`, `PT_CPE_PASSO_01`, `PT_CPE_PASSO_02`, `PT_CPE_PASSO_03`, `PT_CPE_PASSO_04`, `PT_CPE_PASSO_05`, `PT_CPE_PASSO_06`, `PT_CPE_PASSO_07`, `PT_CPE_PASSO_08`, `PT_CPE_PASSO_09`, `PT_CPE_PASSO_10`, `PT_CPE_PASSO_11`, `PT_CPE_PASSO_12`, `PT_CPE_PASSO_13`, `PT_CPE_PASSO_14`, `PT_CPE_PASSO_15`, `PT_CPE_PASSO_16`, `PT_CPE_PASSO_17`, `PT_CPE_PASSO_18`, `PT_CPE_PASSO_19`, `PT_CPE_PASSO_20`, `PT_CPE_PASSO_21`

CONFIGURATION

lookupFile	`pt-cpe-passo.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PT_CPE_PASSO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_1`

PATTERNS, TRIED IN ORDER

`(.{0})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_1`

PATTERNS, TRIED IN ORDER

`(.{1})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
otherwise	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CPE_PASSO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_1`

PATTERNS, TRIED IN ORDER

`(.{2})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CPE_PASSO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_1`

PATTERNS, TRIED IN ORDER

`(.{3})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CPE_PASSO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_1`

PATTERNS, TRIED IN ORDER

`(.{4})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CPE_PASSO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_2`

PATTERNS, TRIED IN ORDER

`(.{5})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes

requireMask	no

PT_CPE_PASSO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_CPE_CADEIA_2

PATTERNS, TRIED IN ORDER

(.{6})(.{4})(.*)	keep · PT_CPE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_CPE_CADEIA_2

PATTERNS, TRIED IN ORDER

(.{7})(.{4})(.*)	keep · PT_CPE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_CPE_CADEIA_2

PATTERNS, TRIED IN ORDER

(.{8})(.{4})(.*)	keep · PT_CPE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_CPE_CADEIA_2

PATTERNS, TRIED IN ORDER

(.{9})(.{4})(.*)	keep · PT_CPE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_2`

PATTERNS, TRIED IN ORDER

`(.{10})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CPE_PASSO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_2`

PATTERNS, TRIED IN ORDER

`(.{11})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CPE_PASSO_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_2`

PATTERNS, TRIED IN ORDER

`(.{12})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CPE_PASSO_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_3`

PATTERNS, TRIED IN ORDER

`(.{13})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_CPE_PASSO_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_3`

PATTERNS, TRIED IN ORDER

`(.{14})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_3`

PATTERNS, TRIED IN ORDER

`(.{15})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_3`

PATTERNS, TRIED IN ORDER

`(.{16})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_17 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_3`

PATTERNS, TRIED IN ORDER

`(.{17})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_18 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_3`

PATTERNS, TRIED IN ORDER

`(.{18})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_19 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_3`

PATTERNS, TRIED IN ORDER

`(.{19})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_20 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_3`

PATTERNS, TRIED IN ORDER

`(.{20})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PASSO_21 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_4`

PATTERNS, TRIED IN ORDER

`(.{21})(.{4})(.*)`	keep · `PT_CPE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PONTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_CPE_CADEIA_1`

PATTERNS, TRIED IN ORDER

`(PT\s?\d{4}\s?)(\d{4}\s?\d{4}\s?\d{4}|\d{12})(.*)`	keep · `PT_CM_DIGITOS_LARGURA_FIXA` · keep

otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_PREPARAR REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_CPE_CADEIA_1

PATTERNS, TRIED IN ORDER

(P)(.*[\d_])([A-Za-z]{2})(\d[A-Za-z])	replace with 000P · keep · replace with ~ · keep
(P)(.*[\d_])([A-Za-z]{2})	replace with 000P · keep · replace with ~
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_CPE_RESTAURAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_CPE_CADEIA_4

PATTERNS, TRIED IN ORDER

([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep
([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep
([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)	keep · replace with · keep · replace with · keep · replace with · keep · replace with · keep
([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)	keep · replace with · keep · replace with · keep · replace with · keep
([^_]*)(_)([^_]*)(_)([^_]*)	keep · replace with · keep · replace with · keep
([^_]*)(_)([^_]*)	keep · replace with · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_DATA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: PT_L2_DATA_EVENTO

CONFIGURATION

minRange	-30
maxRange	30
unit	DAYS
roll	no

PT_DATA_NASCIMENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `PT_L2_DATA_NASCIMENTO`

CONFIGURATION

minRange	`-60`
maxRange	`60`
unit	`DAYS`
roll	no

PT_DEPENDENCIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_DEPENDENCIA_LISTA`.

Used by: `PT_SAUDE_DEPENDENCIA`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*)([1-9]\d{0,5}|0)`	keep · `PT_DEPENDENCIA_CODIGO`
otherwise	`PT_DEPENDENCIA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_DEPENDENCIA_CODIGO SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-dependencia-codigos.txt`, chosen by a keyed hash.

Used by: `PT_DEPENDENCIA`

CONFIGURATION

lookupFile	`pt-dependencia-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_DEPENDENCIA_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in `pt-dependencia.txt`, chosen by a keyed hash.

Used by: `PT_DEPENDENCIA`

CONFIGURATION

lookupFile	`pt-dependencia.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PT_DIAGNOSTICO_TEXTO`.

Used by: `PT_SAUDE_DIAGNOSTICO`

PATTERNS, TRIED IN ORDER

`([A-Za-z]\d{2}\.[\dA-Za-z]{1,4})`	`PT_CID10_DECIMAL`
`([A-Za-z]\d{2,3}X?)`	`PT_CID10`
`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
otherwise	`PT_DIAGNOSTICO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

PT_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in `pt-diagnosticos.txt`, chosen by a keyed hash.

Used by: `PT_DIAGNOSTICO`

CONFIGURATION

lookupFile	`pt-diagnosticos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_L1_EMAIL`

PATTERNS, TRIED IN ORDER

`([^@\s]+)@([^@\s]+)\.([A-Za-z]{2,24}(?:\.[A-Za-z]{2})?)`	`PT_CM_ALFANUM` · `PT_CM_ALFANUM` · replace with `test`
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PT_ENTIDADE_EMPREGADORA SECURE LOOKUP

Replaces the value with one of the 24 values in `pt-empregadores.txt`, chosen by a keyed hash.

Used by: `PT_L2_ENTIDADE_EMPREGADORA`

CONFIGURATION

lookupFile	`pt-empregadores.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_ESCOLARIDADE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_ESCOLARIDADE_LISTA`.

Used by: `PT_L2_ESCOLARIDADE`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*)([1-9]\d{0,5}|0)`	keep · `PT_ESCOLARIDADE_CODIGO`
otherwise	`PT_ESCOLARIDADE_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_ESCOLARIDADE_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in `pt-escolaridade-codigos.txt`, chosen by a keyed hash.

Used by: `PT_ESCOLARIDADE`

CONFIGURATION

lookupFile	`pt-escolaridade-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_ESCOLARIDADE_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `pt-escolaridade.txt`, chosen by a keyed hash.

Used by: `PT_ESCOLARIDADE`

CONFIGURATION

lookupFile	`pt-escolaridade.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_ESTABELECIMENTO_ENSINO SECURE LOOKUP

Replaces the value with one of the 14 values in `pt-estabelecimentos-ensino.txt`, chosen by a keyed hash.

Used by: `PT_L2_ESTABELECIMENTO_ENSINO`

CONFIGURATION

lookupFile	`pt-estabelecimentos-ensino.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_ESTADO_CIVIL_LISTA`.

Used by: `PT_L2_ESTADO_CIVIL`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*)([1-9]\d{0,5}|0)`	keep · `PT_ESTADO_CIVIL_CODIGO`
otherwise	`PT_ESTADO_CIVIL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in `pt-estado-civil-codigos.txt`, chosen by a keyed hash.

Used by: `PT_ESTADO_CIVIL`

CONFIGURATION

lookupFile	`pt-estado-civil-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `pt-estado-civil.txt`, chosen by a keyed hash.

Used by: `PT_ESTADO_CIVIL`

CONFIGURATION

lookupFile	`pt-estado-civil.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 10 values in `pt-estados-credito.txt`, chosen by a keyed hash.

Used by: `PT_HISTORICO_CREDITO`

CONFIGURATION

lookupFile	`pt-estados-credito.txt`
hashMethod	`SHA256`

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_FISCAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_FIN_FISCAL

PATTERNS, TRIED IN ORDER

(-?)(\d+)([.,]\d{1,2})	keep · dlpx-core:CM Numeric · keep
(-?)(\d+)	keep · dlpx-core:CM Numeric
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_FREGUESIA DATA CLEANSING

Replaces each value found in pt-freguesias-generalizadas.txt (29,506 pairs) by its counterpart; values not in the file stay as they are.

Used by: PT_L2_FREGUESIA

CONFIGURATION

lookupFile	pt-freguesias-generalizadas.txt
delimiter	|
caseSensitive	yes
trimWhitespace	yes

PT_HISTORICO_CREDITO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: PT_ESTADO_CREDITO.

Used by: PT_FIN_CREDITO

PATTERNS, TRIED IN ORDER

(0*?)(?:(\d{1,4}))	keep · PT_CM_DIGITOS
(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])	PT_INDICADOR
otherwise	PT_ESTADO_CREDITO

CONFIGURATION

trimInput	yes
requireMask	no

PT_IBAN_ESTRANGEIRO IBAN

Masks the last 8 characters of the IBAN and recomputes its two ISO 13616 check digits; the country code and the characters before stay.

Used by: PT_CONTA

CONFIGURATION

validateInput	no

numCharsToMask	8

PT_IDADE REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_L2_IDADE

PATTERNS, TRIED IN ORDER

(0*?)(?:([1-9]\d{2,}))	keep · replace with 90
(0*?)(?:([1-9])(\d)([.,]\d+))	keep · keep · PT_CM_DIGITOS · keep
(0*?)(?:([1-9])(\d))	keep · keep · PT_CM_DIGITOS
(0*?)(?:(\d))	keep · PT_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_IDENTIDADE_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: PT_IDENTIDADE_GENERO_LISTA.

Used by: PT_L3_IDENTIDADE_GENERO

PATTERNS, TRIED IN ORDER

(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])	PT_INDICADOR
(0*?)(?:(\d{1,6}))	keep · PT_CM_ALFANUM
otherwise	PT_IDENTIDADE_GENERO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

PT_IDENTIDADE_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in pt-identidades-genero.txt, chosen by a keyed hash.

Used by: PT_IDENTIDADE_GENERO

CONFIGURATION

lookupFile	pt-identidades-genero.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_IDENTIFICACAO REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: PT_CM_ALFANUM.

Used by: PT_L1_CARTAO_CIDADAO

PATTERNS, TRIED IN ORDER

(0*?)(?:(\d{8}[\s\-]?\d[\s\-]?[A-Za-z0-9]{2}\d))	keep · PT_CC

`(0*?)(?:(\d{8}[\s\-]?\d))`	keep · `PT_NIC`
`(0*?)(?:(\d{8}))`	keep · `PT_NIC_CORPO`
`(0*?)(?:(\d{5,7}))`	keep · `PT_CM_DIGITOS`
`([A-Za-z]{1,2}\d{6})`	`PT_CM_DIGITOS_LETRAS`
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PT_IMOVEL REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_L1_IMOVEL`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{6}[\s\-]?)([URO])([\s\-]?)(\d{1,6})(.*))`	keep · keep · keep · keep · `PT_CM_DIGITOS` · keep
`([URO])([\s\-]?)(\d{1,6})(.*)`	keep · keep · `PT_CM_DIGITOS` · keep
`(0*?)(?:(\d{1,6})(/)(\d{8}))`	keep · `PT_CM_DIGITOS` · keep · keep
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PT_INCAPACIDADE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_INCAPACIDADE_LISTA`.

Used by: `PT_SAUDE_INCAPACIDADE`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_ALFANUM`
otherwise	`PT_INCAPACIDADE_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_INCAPACIDADE_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `pt-incapacidades.txt`, chosen by a keyed hash.

Used by: `PT_INCAPACIDADE`

CONFIGURATION

lookupFile	`pt-incapacidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes

PT_INDICADOR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_CATEGORIA_SUPRIMIDA, PT_SITUACAO_RESIDENCIA, PT_ESTADO_CIVIL, PT_ESCOLARIDADE, PT_ORIGEM_ETNICA, PT_RELIGIAO, PT_OPINIAO_POLITICA, PT_PARTIDO, PT_ORIENTACAO_SEXUAL, PT_IDENTIDADE_GENERO, PT_COBERTURA_SAUDE, PT_DIAGNOSTICO, PT_MEDICAMENTO, PT_INCAPACIDADE, PT_DEPENDENCIA, PT_APTIDAO, PT_HISTORICO_CREDITO, PT_PRESTACAO_SOCIAL, PT_REGISTO_CRIMINAL, PT_CERTIFICADO_MENORES, PT_CONTRAORDENACAO

PATTERNS, TRIED IN ORDER

(?i)(sim|n[aã]o)	PT_INDICADOR_SIM_NAO
(?i)(true|false)	PT_INDICADOR_TRUE_FALSE
(?i)(yes|no)	PT_INDICADOR_YES_NO
(?i)([sn])	PT_INDICADOR_S_N
(?i)([yx])	PT_INDICADOR_Y_N
([01])	PT_INDICADOR_0_1
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_INDICADOR_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in pt-indicador-0-1.txt, chosen by a keyed hash.

Used by: PT_INDICADOR

CONFIGURATION

lookupFile	pt-indicador-0-1.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_INDICADOR_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in pt-indicador-s-n.txt, chosen by a keyed hash.

Used by: PT_INDICADOR

CONFIGURATION

lookupFile	pt-indicador-s-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_INDICADOR_SIM_NAO SECURE LOOKUP

Replaces the value with one of the 2 values in pt-indicador-sim-nao.txt, chosen by a keyed hash.

Used by: PT_INDICADOR

CONFIGURATION

lookupFile	`pt-indicador-sim-nao.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_INDICADOR_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-true-false.txt`, chosen by a keyed hash.

Used by: `PT_INDICADOR`

CONFIGURATION

lookupFile	`pt-indicador-true-false.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_INDICADOR_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-y-n.txt`, chosen by a keyed hash.

Used by: `PT_INDICADOR`

CONFIGURATION

lookupFile	`pt-indicador-y-n.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_INDICADOR_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-indicador-yes-no.txt`, chosen by a keyed hash.

Used by: `PT_INDICADOR`

CONFIGURATION

lookupFile	`pt-indicador-yes-no.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_HEX`.

Used by: `PT_L1_IP`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3}))`	keep · `PT_OCTETO` · `PT_OCTETO` · `PT_OCTETO` · `PT_OCTETO`
otherwise	`PT_CM_HEX`

CONFIGURATION

trimInput	yes
requireMask	no

PT_MATRICULA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_DIGITOS_LETRAS`.

Used by: `PT_L1_MATRICULA`

PATTERNS, TRIED IN ORDER

`([A-Z]{2}|\d{2})([\s\-]?)([A-Z]{2}|\d{2})([\s\-]?)([A-Z]{2}|\d{2})`	`PT_CM_MATRICULA` · keep · `PT_CM_MATRICULA` · keep · `PT_CM_MATRICULA`
otherwise	`PT_CM_DIGITOS_LETRAS`

CONFIGURATION

trimInput	yes
requireMask	no

PT_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_MEDICAMENTO_LISTA`.

Used by: `PT_SAUDE_MEDICAMENTO`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_ALFANUM`
otherwise	`PT_MEDICAMENTO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 23 values in `pt-medicamentos.txt`, chosen by a keyed hash.

Used by: `PT_MEDICAMENTO`

CONFIGURATION

lookupFile	`pt-medicamentos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_MORADA SECURE LOOKUP

Replaces the value with one of the 4,000 values in `pt-moradas.txt`, chosen by a keyed hash.

Used by: `PT_L1_MORADA`

CONFIGURATION

lookupFile	`pt-moradas.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_NACIONALIDADE SECURE LOOKUP

Replaces the value with one of the 20 values in `pt-nacionalidades.txt`, chosen by a keyed hash.

Used by: `PT_L2_NACIONALIDADE`

CONFIGURATION

lookupFile	`pt-nacionalidades.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_NIB STRING ALGORITHM CHAIN

Applies `PT_NIB_1` → `PT_NIB_2` → `PT_NIB_3` → `PT_NIB_4`, in this order.

Used by: `PT_CONTA`

CONFIGURATION

algorithmReferences[1]	`PT_NIB_1`
algorithmReferences[2]	`PT_NIB_2`
algorithmReferences[3]	`PT_NIB_3`
algorithmReferences[4]	`PT_NIB_4`

PT_NIB_1 STRING ALGORITHM CHAIN

Applies `PT_NIB_CONTA` → `PT_NIB_MARCAR` → `PT_NIB_PREPARAR` → `PT_NIB_PASSO_00` → `PT_NIB_PASSO_01` → `PT_NIB_PASSO_02` → `PT_NIB_PASSO_03` → `PT_NIB_PASSO_04`, in this order.

Used by: `PT_NIB`

CONFIGURATION

algorithmReferences[1]	`PT_NIB_CONTA`
algorithmReferences[2]	`PT_NIB_MARCAR`
algorithmReferences[3]	`PT_NIB_PREPARAR`
algorithmReferences[4]	`PT_NIB_PASSO_00`
algorithmReferences[5]	`PT_NIB_PASSO_01`
algorithmReferences[6]	`PT_NIB_PASSO_02`
algorithmReferences[7]	`PT_NIB_PASSO_03`

algorithmReferences[8]	PT_NIB_PASSO_04

PT_NIB_2 STRING ALGORITHM CHAIN

Applies PT_NIB_PASSO_05 → PT_NIB_PASSO_06 → PT_NIB_PASSO_07 → PT_NIB_PASSO_08 → PT_NIB_PASSO_09 → PT_NIB_PASSO_10 → PT_NIB_PASSO_11 → PT_NIB_PASSO_12 , in this order.

Used by: PT_NIB

CONFIGURATION

algorithmReferences[1]	PT_NIB_PASSO_05
algorithmReferences[2]	PT_NIB_PASSO_06
algorithmReferences[3]	PT_NIB_PASSO_07
algorithmReferences[4]	PT_NIB_PASSO_08
algorithmReferences[5]	PT_NIB_PASSO_09
algorithmReferences[6]	PT_NIB_PASSO_10
algorithmReferences[7]	PT_NIB_PASSO_11
algorithmReferences[8]	PT_NIB_PASSO_12

PT_NIB_3 STRING ALGORITHM CHAIN

Applies PT_NIB_PASSO_13 → PT_NIB_PASSO_14 → PT_NIB_PASSO_15 → PT_NIB_PASSO_16 → PT_NIB_PASSO_17 → PT_NIB_PASSO_18 → PT_NIB_PASSO_19 → PT_NIB_PASSO_20 , in this order.

Used by: PT_NIB

CONFIGURATION

algorithmReferences[1]	PT_NIB_PASSO_13
algorithmReferences[2]	PT_NIB_PASSO_14
algorithmReferences[3]	PT_NIB_PASSO_15
algorithmReferences[4]	PT_NIB_PASSO_16
algorithmReferences[5]	PT_NIB_PASSO_17
algorithmReferences[6]	PT_NIB_PASSO_18
algorithmReferences[7]	PT_NIB_PASSO_19
algorithmReferences[8]	PT_NIB_PASSO_20

PT_NIB_4 STRING ALGORITHM CHAIN

Applies PT_NIB_PASSO_21 → PT_NIB_PASSO_22 → PT_NIB_PASSO_23 → PT_NIB_CONTROLO → PT_NIB_RESTAURAR , in this order.

Used by: PT_NIB

CONFIGURATION

algorithmReferences[1]	PT_NIB_PASSO_21
algorithmReferences[2]	PT_NIB_PASSO_22
algorithmReferences[3]	PT_NIB_PASSO_23
algorithmReferences[4]	PT_NIB_CONTROLO
algorithmReferences[5]	PT_NIB_RESTAURAR

PT_NIB_CONTA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_1

PATTERNS, TRIED IN ORDER

`(\d{8})(\d{11})(\d{2})`	keep · `PT_CM_DIGITOS_LARGURA_FIXA` · keep
`(\d{4} \d{4} )(\d{4} \d{4} \d{3})(\d \d)`	keep · `PT_CM_DIGITOS_LARGURA_FIXA` · keep
`(\d{4}[\s.\-]\d{4}[\s.\-])(\d{11})([\s.\-]\d{2})`	keep · `PT_CM_DIGITOS_LARGURA_FIXA` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_CONTROLO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_4`

PATTERNS, TRIED IN ORDER

`(.*)(\d{2}~_?\^)`	keep · `PT_NIB_CONTROLO_TABELA`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_CONTROLO_TABELA DATA CLEANSING

Replaces each value found in `pt-nib-controlo.txt` (194 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PT_NIB_CONTROLO`, `PT_NIB_IMPRESSO_CONTROLO`

CONFIGURATION

lookupFile	`pt-nib-controlo.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PT_NIB_IMPRESSO STRING ALGORITHM CHAIN

Applies `PT_NIB_IMPRESSO_1` → `PT_NIB_IMPRESSO_2` → `PT_NIB_IMPRESSO_3` → `PT_NIB_IMPRESSO_4`, in this order.

Used by: `PT_CONTA`

CONFIGURATION

algorithmReferences[1]	`PT_NIB_IMPRESSO_1`
algorithmReferences[2]	`PT_NIB_IMPRESSO_2`
algorithmReferences[3]	`PT_NIB_IMPRESSO_3`
algorithmReferences[4]	`PT_NIB_IMPRESSO_4`

PT_NIB_IMPRESSO_1 STRING ALGORITHM CHAIN

Applies `PT_NIB_IMPRESSO_CONTA` → `PT_NIB_IMPRESSO_MARCAR` → `PT_NIB_IMPRESSO_PREPARAR` → `PT_NIB_IMPRESSO_PASSO_00` → `PT_NIB_IMPRESSO_PASSO_01` → `PT_NIB_IMPRESSO_PASSO_02` → `PT_NIB_IMPRESSO_PASSO_03` → `PT_NIB_IMPRESSO_PASSO_04`, in this order.

Used by: `PT_NIB_IMPRESSO`

CONFIGURATION

algorithmReferences[1]	PT_NIB_IMPRESSO_CONTA
algorithmReferences[2]	PT_NIB_IMPRESSO_MARCAR
algorithmReferences[3]	PT_NIB_IMPRESSO_PREPARAR
algorithmReferences[4]	PT_NIB_IMPRESSO_PASSO_00
algorithmReferences[5]	PT_NIB_IMPRESSO_PASSO_01
algorithmReferences[6]	PT_NIB_IMPRESSO_PASSO_02
algorithmReferences[7]	PT_NIB_IMPRESSO_PASSO_03
algorithmReferences[8]	PT_NIB_IMPRESSO_PASSO_04

PT_NIB_IMPRESSO_2 STRING ALGORITHM CHAIN

Applies PT_NIB_IMPRESSO_PASSO_05 → PT_NIB_IMPRESSO_PASSO_06 → PT_NIB_IMPRESSO_PASSO_07 → PT_NIB_IMPRESSO_PASSO_08 → PT_NIB_IMPRESSO_PASSO_09 → PT_NIB_IMPRESSO_PASSO_10 → PT_NIB_IMPRESSO_PASSO_11 → PT_NIB_IMPRESSO_PASSO_12 , in this order.

Used by: PT_NIB_IMPRESSO

CONFIGURATION

algorithmReferences[1]	PT_NIB_IMPRESSO_PASSO_05
algorithmReferences[2]	PT_NIB_IMPRESSO_PASSO_06
algorithmReferences[3]	PT_NIB_IMPRESSO_PASSO_07
algorithmReferences[4]	PT_NIB_IMPRESSO_PASSO_08
algorithmReferences[5]	PT_NIB_IMPRESSO_PASSO_09
algorithmReferences[6]	PT_NIB_IMPRESSO_PASSO_10
algorithmReferences[7]	PT_NIB_IMPRESSO_PASSO_11
algorithmReferences[8]	PT_NIB_IMPRESSO_PASSO_12

PT_NIB_IMPRESSO_3 STRING ALGORITHM CHAIN

Applies PT_NIB_IMPRESSO_PASSO_13 → PT_NIB_IMPRESSO_PASSO_14 → PT_NIB_IMPRESSO_PASSO_15 → PT_NIB_IMPRESSO_PASSO_16 → PT_NIB_IMPRESSO_PASSO_17 → PT_NIB_IMPRESSO_PASSO_18 → PT_NIB_IMPRESSO_PASSO_19 → PT_NIB_IMPRESSO_PASSO_20 , in this order.

Used by: PT_NIB_IMPRESSO

CONFIGURATION

algorithmReferences[1]	PT_NIB_IMPRESSO_PASSO_13
algorithmReferences[2]	PT_NIB_IMPRESSO_PASSO_14
algorithmReferences[3]	PT_NIB_IMPRESSO_PASSO_15
algorithmReferences[4]	PT_NIB_IMPRESSO_PASSO_16
algorithmReferences[5]	PT_NIB_IMPRESSO_PASSO_17
algorithmReferences[6]	PT_NIB_IMPRESSO_PASSO_18
algorithmReferences[7]	PT_NIB_IMPRESSO_PASSO_19
algorithmReferences[8]	PT_NIB_IMPRESSO_PASSO_20

PT_NIB_IMPRESSO_4 STRING ALGORITHM CHAIN

Applies PT_NIB_IMPRESSO_PASSO_21 → PT_NIB_IMPRESSO_PASSO_22 → PT_NIB_IMPRESSO_PASSO_23 → PT_NIB_IMPRESSO_CONTROLO → PT_NIB_IMPRESSO_RESTAURAR , in this order.

Used by: PT_NIB_IMPRESSO

CONFIGURATION

algorithmReferences[1]	PT_NIB_IMPRESSO_PASSO_21

algorithmReferences[2]	PT_NIB_IMPRESSO_PASSO_22
algorithmReferences[3]	PT_NIB_IMPRESSO_PASSO_23
algorithmReferences[4]	PT_NIB_IMPRESSO_CONTROLO
algorithmReferences[5]	PT_NIB_IMPRESSO_RESTAURAR

PT_NIB_IMPRESSO_CONTA REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_1

PATTERNS, TRIED IN ORDER

(\d{8})(\d{11})(\d{2})	keep · PT_CM_DIGITOS_LARGURA_FIXA · keep
(\d{4} \d{4})(\d{4} \d{4} \d{3})(\d \d)	keep · PT_CM_DIGITOS_LARGURA_FIXA · keep
(\d{4}[\s.\-]\d{4}[\s.\-])(\d{11})([\s.\-]\d{2})	keep · PT_CM_DIGITOS_LARGURA_FIXA · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_CONTROLO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_4

PATTERNS, TRIED IN ORDER

(.*)(\d{2}~_?\^)	keep · PT_NIB_CONTROLO_TABELA
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_MARCAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_1

PATTERNS, TRIED IN ORDER

([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
([^\s]*)(\s)([^\s]*)(\s)([^\s]*)	keep · replace with _ · keep · replace with _ · keep
([^\s]*)(\s)([^\s]*)	keep · replace with _ · keep
otherwise	keep

CONFIGURATION

trimInput	yes

requireMask	no

PT_NIB_IMPRESSO_PASSO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_1`

PATTERNS, TRIED IN ORDER

`(.{0})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_1`

PATTERNS, TRIED IN ORDER

`(.{1})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_1`

PATTERNS, TRIED IN ORDER

`(.{2})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_1`

PATTERNS, TRIED IN ORDER

`(.{3})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_1`

PATTERNS, TRIED IN ORDER

`(.{4})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_2`

PATTERNS, TRIED IN ORDER

`(.{5})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_2`

PATTERNS, TRIED IN ORDER

`(.{6})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_2`

PATTERNS, TRIED IN ORDER

`(.{7})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_2`

PATTERNS, TRIED IN ORDER

`(.{8})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_2`

PATTERNS, TRIED IN ORDER

`(.{9})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_2`

PATTERNS, TRIED IN ORDER

`(.{10})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_2`

PATTERNS, TRIED IN ORDER

`(.{11})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_2`

PATTERNS, TRIED IN ORDER

`(.{12})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_3`

PATTERNS, TRIED IN ORDER

`(.{13})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_3`

PATTERNS, TRIED IN ORDER

`(.{14})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_3`

PATTERNS, TRIED IN ORDER

`(.{15})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_3`

PATTERNS, TRIED IN ORDER

`(.{16})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep

otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_17 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_3

PATTERNS, TRIED IN ORDER

(.{17})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_18 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_3

PATTERNS, TRIED IN ORDER

(.{18})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_19 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_3

PATTERNS, TRIED IN ORDER

(.{19})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_20 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_3

PATTERNS, TRIED IN ORDER

(.{20})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_21 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_4

PATTERNS, TRIED IN ORDER

(.{21})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_22 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_4

PATTERNS, TRIED IN ORDER

(.{22})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PASSO_23 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_4

PATTERNS, TRIED IN ORDER

(.{23})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_IMPRESSO_PREPARAR REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_IMPRESSO_1

PATTERNS, TRIED IN ORDER

(0)(.*)(\d)(_?)(\d)	replace with 000 · keep · replace with ~ · keep · replace with ^
(1)(.*)(\d)(_?)(\d)	replace with 001 · keep · replace with ~ · keep · replace with ^
(2)(.*)(\d)(_?)(\d)	replace with 002 · keep · replace with ~ · keep · replace with ^
(3)(.*)(\d)(_?)(\d)	replace with 003 · keep · replace with ~ · keep · replace with ^
(4)(.*)(\d)(_?)(\d)	replace with 004 · keep · replace with ~ · keep · replace with ^

`(5)(.*)(\d)(_?)(\d)`	replace with `005` · keep · replace with `~` · keep · replace with `^`
`(6)(.*)(\d)(_?)(\d)`	replace with `006` · keep · replace with `~` · keep · replace with `^`
`(7)(.*)(\d)(_?)(\d)`	replace with `007` · keep · replace with `~` · keep · replace with `^`
`(8)(.*)(\d)(_?)(\d)`	replace with `008` · keep · replace with `~` · keep · replace with `^`
`(9)(.*)(\d)(_?)(\d)`	replace with `009` · keep · replace with `~` · keep · replace with `^`
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_NIB_IMPRESSO_RESTAURAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_IMPRESSO_4`

PATTERNS, TRIED IN ORDER

`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with `` · keep · replace with `` · keep · replace with `` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with `` · keep · replace with `` · keep
`([^_]*)(_)([^_]*)`	keep · replace with `` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_NIB_MARCAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_1`

PATTERNS, TRIED IN ORDER

`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep · replace with `_` · keep
`([^\s]*)(\s)([^\s]*)`	keep · replace with `_` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes

requireMask	no

PT_NIB_PASSO DATA CLEANSING

Replaces each value found in `pt-nib-passo.txt` (1,261 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PT_NIB_PASSO_00`, `PT_NIB_PASSO_01`, `PT_NIB_PASSO_02`, `PT_NIB_PASSO_03`, `PT_NIB_PASSO_04`, `PT_NIB_PASSO_05`, `PT_NIB_PASSO_06`, `PT_NIB_PASSO_07`, `PT_NIB_PASSO_08`, `PT_NIB_PASSO_09`, `PT_NIB_PASSO_10`, `PT_NIB_PASSO_11`, `PT_NIB_PASSO_12`, `PT_NIB_PASSO_13`, `PT_NIB_PASSO_14`, `PT_NIB_PASSO_15`, `PT_NIB_PASSO_16`, `PT_NIB_PASSO_17`, `PT_NIB_PASSO_18`, `PT_NIB_PASSO_19`, `PT_NIB_PASSO_20`, `PT_NIB_PASSO_21`, `PT_NIB_PASSO_22`, `PT_NIB_PASSO_23`, `PT_NIB_IMPRESSO_PASSO_00`, `PT_NIB_IMPRESSO_PASSO_01`, `PT_NIB_IMPRESSO_PASSO_02`, `PT_NIB_IMPRESSO_PASSO_03`, `PT_NIB_IMPRESSO_PASSO_04`, `PT_NIB_IMPRESSO_PASSO_05`, `PT_NIB_IMPRESSO_PASSO_06`, `PT_NIB_IMPRESSO_PASSO_07`, `PT_NIB_IMPRESSO_PASSO_08`, `PT_NIB_IMPRESSO_PASSO_09`, `PT_NIB_IMPRESSO_PASSO_10`, `PT_NIB_IMPRESSO_PASSO_11`, `PT_NIB_IMPRESSO_PASSO_12`, `PT_NIB_IMPRESSO_PASSO_13`, `PT_NIB_IMPRESSO_PASSO_14`, `PT_NIB_IMPRESSO_PASSO_15`, `PT_NIB_IMPRESSO_PASSO_16`, `PT_NIB_IMPRESSO_PASSO_17`, `PT_NIB_IMPRESSO_PASSO_18`, `PT_NIB_IMPRESSO_PASSO_19`, `PT_NIB_IMPRESSO_PASSO_20`, `PT_NIB_IMPRESSO_PASSO_21`, `PT_NIB_IMPRESSO_PASSO_22`, `PT_NIB_IMPRESSO_PASSO_23`

CONFIGURATION

lookupFile	`pt-nib-passo.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PT_NIB_PASSO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_1`

PATTERNS, TRIED IN ORDER

`(.{0})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_1`

PATTERNS, TRIED IN ORDER

`(.{1})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_1`

PATTERNS, TRIED IN ORDER

`(.{2})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep

otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_1

PATTERNS, TRIED IN ORDER

(.{3})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_1

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_2

PATTERNS, TRIED IN ORDER

(.{5})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_2

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_2

PATTERNS, TRIED IN ORDER

(.{7})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_2

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_2

PATTERNS, TRIED IN ORDER

(.{9})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_2

PATTERNS, TRIED IN ORDER

(.{10})(.{3})(.*)	keep · PT_NIB_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes

requireMask	no

PT_NIB_PASS0_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_2

PATTERNS, TRIED IN ORDER

(.{11})(.{3})(.*)	keep · PT_NIB_PASS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASS0_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_2

PATTERNS, TRIED IN ORDER

(.{12})(.{3})(.*)	keep · PT_NIB_PASS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASS0_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_3

PATTERNS, TRIED IN ORDER

(.{13})(.{3})(.*)	keep · PT_NIB_PASS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASS0_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_NIB_3

PATTERNS, TRIED IN ORDER

(.{14})(.{3})(.*)	keep · PT_NIB_PASS0 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_3`

PATTERNS, TRIED IN ORDER

`(.{15})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_3`

PATTERNS, TRIED IN ORDER

`(.{16})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_17 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_3`

PATTERNS, TRIED IN ORDER

`(.{17})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_18 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_3`

PATTERNS, TRIED IN ORDER

`(.{18})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PASSO_19 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_3`

PATTERNS, TRIED IN ORDER

`(.{19})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_NIB_PASSO_20 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_3`

PATTERNS, TRIED IN ORDER

`(.{20})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_NIB_PASSO_21 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_4`

PATTERNS, TRIED IN ORDER

`(.{21})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_NIB_PASSO_22 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_4`

PATTERNS, TRIED IN ORDER

`(.{22})(.{3})(.*)`	keep · `PT_NIB_PASSO` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_NIB_PASSO_23 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_4`

PATTERNS, TRIED IN ORDER

`(.{23})(.{3})(.*)`	keep · `PT_NIB_PASS0` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_PREPARAR REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_1`

PATTERNS, TRIED IN ORDER

`(0)(.*)(\d)(_?)(\d)`	replace with `000` · keep · replace with `~` · keep · replace with `^`
`(1)(.*)(\d)(_?)(\d)`	replace with `001` · keep · replace with `~` · keep · replace with `^`
`(2)(.*)(\d)(_?)(\d)`	replace with `002` · keep · replace with `~` · keep · replace with `^`
`(3)(.*)(\d)(_?)(\d)`	replace with `003` · keep · replace with `~` · keep · replace with `^`
`(4)(.*)(\d)(_?)(\d)`	replace with `004` · keep · replace with `~` · keep · replace with `^`
`(5)(.*)(\d)(_?)(\d)`	replace with `005` · keep · replace with `~` · keep · replace with `^`
`(6)(.*)(\d)(_?)(\d)`	replace with `006` · keep · replace with `~` · keep · replace with `^`
`(7)(.*)(\d)(_?)(\d)`	replace with `007` · keep · replace with `~` · keep · replace with `^`
`(8)(.*)(\d)(_?)(\d)`	replace with `008` · keep · replace with `~` · keep · replace with `^`
`(9)(.*)(\d)(_?)(\d)`	replace with `009` · keep · replace with `~` · keep · replace with `^`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NIB_RESTAURAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIB_4`

PATTERNS, TRIED IN ORDER

`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with `` · keep · replace with `` · keep · replace with `` · keep · replace with `` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with `` · keep · replace with `` · keep · replace with `` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with `` · keep · replace with `` · keep
`([^_]*)(_)([^_]*)`	keep · replace with `` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

`PT_NIC` CHECK DIGIT

Masks the digits with `PT_NIC_CORPO` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 8 9` from the right.

Used by: `PT_CC_NIC`, `PT_IDENTIFICACAO`

CONFIGURATION

`weightList`	`2 3 4 5 6 7 8 9`
`modulusNumber`	`11`
`checkDigitIndex`	`8`
`numDigitsForCheckdigitCalculation`	`8`
`calculateChecksumRightToLeft`	yes
`numericAlgorithm`	`PT_NIC_CORPO`
`alphaNumericAlgorithm`	`PT_NIC_CORPO`
`preserveRegex`	`[.\-\s]`
`inputHandlingConfig.characterHandling`	`STANDARD`
`inputHandlingConfig.invalidInputHandling`	`ERROR`
`inputHandlingConfig.shortInputHandling`	`FALLBACK`
`inputHandlingConfig.padCharacter`	`0`
`inputHandlingConfig.trimWhitespace`	yes

`PT_NIC_CORPO` CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: `PT_NIC`, `PT_IDENTIFICACAO`

CONFIGURATION

`characterGroups`	`0123456789`
`caseSensitive`	yes
`minMaskedPositions`	`0`

`PT_NIF` REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_L1_NIF`

PATTERNS, TRIED IN ORDER

`(PT\s?)((?:[1-38]\d{2}|45\d)[\s\-.]?\d{3}[\s\-.]?\d{3})`	keep · `PT_NIF_CD`
`(0*?)(?:((?:[1-38]\d{2}|45\d)[\s\-.]?\d{3}[\s\-.]?\d{3}))`	keep · `PT_NIF_CD`
`(PT\s?)((?:[5-79]|4[0-46-9])\d{2}[\s\-.]?\d{3}[\s\-.]?\d{3})`	keep · keep
`(0*?)(?:((?:[5-79]|4[0-46-9])\d{2}[\s\-.]?\d{3}[\s\-.]?\d{3}))`	keep · keep
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_NIF_CD CHECK DIGIT

Masks the digits with `PT_NIF_CORPO` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 8 9` from the right.

Used by: `PT_NIF`

CONFIGURATION

weightList	`2 3 4 5 6 7 8 9`
modulusNumber	`11`
checkDigitIndex	`8`
numDigitsForCheckdigitCalculation	`8`
calculateChecksumRightToLeft	yes
numericAlgorithm	`PT_NIF_CORPO`
alphaNumericAlgorithm	`PT_NIF_CORPO`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

PT_NIF_CORPO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NIF_CD`

PATTERNS, TRIED IN ORDER

`(45)(\d{6})`	keep · `PT_CM_DIGITOS_LARGURA_FIXA`
`([1-38])(\d{7})`	keep · `PT_CM_DIGITOS_LARGURA_FIXA`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NISS REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_L1_NISS`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(1(?:[\s\-.]?\d){10}))`	keep · `PT_NISS_CD`
`(0*?)(?:(2(?:[\s\-.]?\d){10}))`	keep · keep
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PT_NISS_CD CHECK DIGIT

Masks the digits with `PT_NISS_CORPO` and recomputes a modulus 10 check digit with weights `2 3 5 7 11 13 17 19 23 0` from the right.

Used by: `PT_NISS`

CONFIGURATION

weightList	`2` `3` `5` `7` `11` `13` `17` `19` `23` `0`
modulusNumber	`10`
checkDigitIndex	`10`
numDigitsForCheckdigitCalculation	`10`
calculateChecksumRightToLeft	yes
numericAlgorithm	`PT_NISS_CORPO`
alphaNumericAlgorithm	`PT_NISS_CORPO`
preserveRegex	`[.\-\s]`
inputHandlingConfig.characterHandling	`STANDARD`
inputHandlingConfig.invalidInputHandling	`ERROR`
inputHandlingConfig.shortInputHandling	`FALLBACK`
inputHandlingConfig.padCharacter	`0`
inputHandlingConfig.trimWhitespace	yes

PT_NISS_CORPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_NISS_CD`

PATTERNS, TRIED IN ORDER

`(1)(\d{9})`	keep · `PT_CM_DIGITOS_LARGURA_FIXA`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_NOME NAME

Replaces the name with one of the 282 names in `pt-nomes.txt`.

Used by: `PT_PALAVRA_NOME`

CONFIGURATION

lookupFile	`pt-nomes.txt`
maskedValueCase	`PRESERVE_INPUT`
filterAccent	yes
inputCaseSensitive	no

PT_NOME_COMPLETO REGEX DECOMPOSE

Tries 9 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_L1_NOME_COMPLETO`

PATTERNS, TRIED IN ORDER

`([^,]+),\s*(.+)`	`PT_APELIDOS` · `PT_NOMES`
`(?iu)(maria)\s+(d[aeo]s?)\s+(\S+)\s+(.+)`	`PT_PALAVRA_NOME` · keep · `PT_PALAVRA_NOME` · `PT_APELIDOS`
`(\S+)`	`PT_PALAVRA_NOME`
`(\S+)\s+(\S+)`	`PT_PALAVRA_NOME` · `PT_PALAVRA_APELIDO`
`(\S+)\s+(\S+)\s+(\S+)`	`PT_PALAVRA_NOME` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO`

`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`PT_PALAVRA_NOME` · `PT_PALAVRA_NOME` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`PT_PALAVRA_NOME` · `PT_PALAVRA_NOME` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`PT_PALAVRA_NOME` · `PT_PALAVRA_NOME` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`PT_PALAVRA_NOME` · `PT_PALAVRA_NOME` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO` · `PT_PALAVRA_APELIDO`
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PT_NOMES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_L1_NOME`, `PT_NOME_COMPLETO`

PATTERNS, TRIED IN ORDER

`(\S+)`	`PT_PALAVRA_NOME`
`(\S+)\s+(\S+)`	`PT_PALAVRA_NOME` · `PT_PALAVRA_NOME`
`(\S+)\s+(\S+)\s+(\S+)`	`PT_PALAVRA_NOME` · `PT_PALAVRA_NOME` · `PT_PALAVRA_NOME`
`(\S+)\s+(\S+)\s+(\S+)\s+(\S+)`	`PT_PALAVRA_NOME` · `PT_PALAVRA_NOME` · `PT_PALAVRA_NOME` · `PT_PALAVRA_NOME`
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PT_NUMERO_RECEITA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_SAUDE_RECEITA`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-7]\d{17}[\dXx]))`	keep · `PT_RECEITA`
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PT_NUMERO_UTENTE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_SAUDE_NUMERO_UTENTE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([1-79](?:[\s\-.]?\d){8}))`	keep · `PT_UTENTE`
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PT_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: PT_IP

CONFIGURATION

minValue	1
maxValue	254

PT_OPINIAO_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: PT_OPINIAO_POLITICA_LISTA .

Used by: PT_L3_OPINIAO_POLITICA

PATTERNS, TRIED IN ORDER

(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])	PT_INDICADOR
(0*)([1-9]\d{0,5}|0)	keep · PT_OPINIAO_POLITICA_CODIGO
otherwise	PT_OPINIAO_POLITICA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

PT_OPINIAO_POLITICA_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in pt-opinioes-politicas-codigos.txt , chosen by a keyed hash.

Used by: PT_OPINIAO_POLITICA

CONFIGURATION

lookupFile	pt-opinioes-politicas-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_OPINIAO_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in pt-opinioes-politicas.txt , chosen by a keyed hash.

Used by: PT_OPINIAO_POLITICA

CONFIGURATION

lookupFile	pt-opinioes-politicas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_ORIENTACAO_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_ORIENTACAO_SEXUAL_LISTA`.

Used by: `PT_L3_ORIENTACAO_SEXUAL`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_ALFANUM`
otherwise	`PT_ORIENTACAO_SEXUAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_ORIENTACAO_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `pt-orientacoes-sexuais.txt`, chosen by a keyed hash.

Used by: `PT_ORIENTACAO_SEXUAL`

CONFIGURATION

lookupFile	`pt-orientacoes-sexuais.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_ORIGEM_ETNICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_ORIGEM_ETNICA_LISTA`.

Used by: `PT_L3_ORIGEM_ETNICA`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*)([1-9]\d{0,5}|0)`	keep · `PT_ORIGEM_ETNICA_CODIGO`
otherwise	`PT_ORIGEM_ETNICA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_ORIGEM_ETNICA_CODIGO SECURE LOOKUP

Replaces the value with one of the 7 values in `pt-origem-etnica-codigos.txt`, chosen by a keyed hash.

Used by: `PT_ORIGEM_ETNICA`

CONFIGURATION

lookupFile	`pt-origem-etnica-codigos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_ORIGEM_ETNICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `pt-origem-etnica.txt`, chosen by a keyed hash.

Used by: `PT_ORIGEM_ETNICA`

CONFIGURATION

lookupFile	`pt-origem-etnica.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_PALAVRA_APELIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_APELIDO`.

Used by: `PT_APELIDOS`, `PT_NOME_COMPLETO`

PATTERNS, TRIED IN ORDER

`(?i)(de|da|do|das|dos|e|d')`	keep
otherwise	`PT_APELIDO`

CONFIGURATION

trimInput	yes
requireMask	no

PT_PALAVRA_NOME REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_NOME`.

Used by: `PT_NOMES`, `PT_NOME_COMPLETO`

PATTERNS, TRIED IN ORDER

`(?i)(de|da|do|das|dos|e|d')`	keep
otherwise	`PT_NOME`

CONFIGURATION

trimInput	yes
requireMask	no

PT_PARTIDO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_PARTIDO_LISTA`.

Used by: `PT_L3_FILIACAO_PARTIDARIA`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_ALFANUM`
otherwise	`PT_PARTIDO_LISTA`

CONFIGURATION

trimInput	yes

requireMask	no

PT_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `pt-partidos.txt`, chosen by a keyed hash.

Used by: `PT_PARTIDO`

CONFIGURATION

lookupFile	`pt-partidos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_PRESTACAO_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_PRESTACAO_SOCIAL_LISTA`.

Used by: `PT_FIN_PRESTACAO_SOCIAL`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_ALFANUM`
otherwise	`PT_PRESTACAO_SOCIAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_PRESTACAO_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in `pt-prestacoes-sociais.txt`, chosen by a keyed hash.

Used by: `PT_PRESTACAO_SOCIAL`

CONFIGURATION

lookupFile	`pt-prestacoes-sociais.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_PROCEDIMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_PROCEDIMENTO_TEXTO`.

Used by: `PT_SAUDE_PROCEDIMENTO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:([0-9A-HJ-NP-Z]{7}))`	keep · `PT_CM_DIGITOS_LETRAS`
`(0*?)(?:(\d{4,6}))`	keep · `PT_CM_DIGITOS`
otherwise	`PT_PROCEDIMENTO_TEXTO`

CONFIGURATION

trimInput	yes
requireMask	no

PT_PROCEDIMENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in `pt-procedimentos.txt`, chosen by a keyed hash.

Used by: `PT_PROCEDIMENTO`

CONFIGURATION

lookupFile	`pt-procedimentos.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_PROCESSO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_ALFANUM`.

Used by: `PT_PENAL_PROCESSO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,7})(/\d{2}\.\d[A-Z0-9]{2,8}))`	keep · `PT_CM_DIGITOS` · keep
`(0*?)(?:(\d{1,7})(/\d{2,4}))`	keep · `PT_CM_DIGITOS` · keep
otherwise	`PT_CM_ALFANUM`

CONFIGURATION

trimInput	yes
requireMask	no

PT_PROFISSAO SECURE LOOKUP

Replaces the value with one of the 38 values in `pt-profissoes.txt`, chosen by a keyed hash.

Used by: `PT_PROFISSAO_OU_CODIGO`

CONFIGURATION

lookupFile	`pt-profissoes.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_PROFISSAO_OU_CODIGO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `PT_PROFISSAO`.

Used by: `PT_L2_PROFISSAO`

PATTERNS, TRIED IN ORDER

`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_DIGITOS`
otherwise	`PT_PROFISSAO`

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA STRING ALGORITHM CHAIN

Applies `PT_RECEITA_1` → `PT_RECEITA_2` → `PT_RECEITA_3`, in this order.

Used by: `PT_NUMERO_RECEITA`

CONFIGURATION

algorithmReferences[1]	`PT_RECEITA_1`
algorithmReferences[2]	`PT_RECEITA_2`
algorithmReferences[3]	`PT_RECEITA_3`

PT_RECEITA_1 STRING ALGORITHM CHAIN

Applies `PT_RECEITA_CORPO` → `PT_RECEITA_PREPARAR` → `PT_RECEITA_PASSO_00` → `PT_RECEITA_PASSO_01` → `PT_RECEITA_PASSO_02` → `PT_RECEITA_PASSO_03` → `PT_RECEITA_PASSO_04` → `PT_RECEITA_PASSO_05`, in this order.

Used by: `PT_RECEITA`

CONFIGURATION

algorithmReferences[1]	`PT_RECEITA_CORPO`
algorithmReferences[2]	`PT_RECEITA_PREPARAR`
algorithmReferences[3]	`PT_RECEITA_PASSO_00`
algorithmReferences[4]	`PT_RECEITA_PASSO_01`
algorithmReferences[5]	`PT_RECEITA_PASSO_02`
algorithmReferences[6]	`PT_RECEITA_PASSO_03`
algorithmReferences[7]	`PT_RECEITA_PASSO_04`
algorithmReferences[8]	`PT_RECEITA_PASSO_05`

PT_RECEITA_2 STRING ALGORITHM CHAIN

Applies `PT_RECEITA_PASSO_06` → `PT_RECEITA_PASSO_07` → `PT_RECEITA_PASSO_08` → `PT_RECEITA_PASSO_09` → `PT_RECEITA_PASSO_10` → `PT_RECEITA_PASSO_11` → `PT_RECEITA_PASSO_12` → `PT_RECEITA_PASSO_13`, in this order.

Used by: `PT_RECEITA`

CONFIGURATION

algorithmReferences[1]	`PT_RECEITA_PASSO_06`
algorithmReferences[2]	`PT_RECEITA_PASSO_07`
algorithmReferences[3]	`PT_RECEITA_PASSO_08`
algorithmReferences[4]	`PT_RECEITA_PASSO_09`
algorithmReferences[5]	`PT_RECEITA_PASSO_10`
algorithmReferences[6]	`PT_RECEITA_PASSO_11`
algorithmReferences[7]	`PT_RECEITA_PASSO_12`
algorithmReferences[8]	`PT_RECEITA_PASSO_13`

PT_RECEITA_3 STRING ALGORITHM CHAIN

Applies `PT_RECEITA_PASSO_14` → `PT_RECEITA_PASSO_15` → `PT_RECEITA_PASSO_16` → `PT_RECEITA_PASSO_17` → `PT_RECEITA_CONTROLO`, in this order.

Used by: `PT_RECEITA`

CONFIGURATION

algorithmReferences[1]	PT_RECEITA_PASSO_14
algorithmReferences[2]	PT_RECEITA_PASSO_15
algorithmReferences[3]	PT_RECEITA_PASSO_16
algorithmReferences[4]	PT_RECEITA_PASSO_17
algorithmReferences[5]	PT_RECEITA_CONTROLO

PT_RECEITA_CONTROLO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_RECEITA_3

PATTERNS, TRIED IN ORDER

(.*)(\d{2}~)	keep · PT_RECEITA_CONTROLO_TABELA
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_CONTROLO_TABELA DATA CLEANSING

Replaces each value found in pt-receita-controlo.txt (11 pairs) by its counterpart; values not in the file stay as they are.

Used by: PT_RECEITA_CONTROLO

CONFIGURATION

lookupFile	pt-receita-controlo.txt
delimiter	|
caseSensitive	yes
trimWhitespace	yes

PT_RECEITA_CORPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_RECEITA_1

PATTERNS, TRIED IN ORDER

([1-7])(\d{17})([\dXx])	keep · PT_CM_DIGITOS_LARGURA_FIXA · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO DATA CLEANSING

Replaces each value found in pt-receita-passo.txt (143 pairs) by its counterpart; values not in the file stay as they are.

Used by: PT_RECEITA_PASSO_00, PT_RECEITA_PASSO_01, PT_RECEITA_PASSO_02, PT_RECEITA_PASSO_03, PT_RECEITA_PASSO_04, PT_RECEITA_PASSO_05, PT_RECEITA_PASSO_06, PT_RECEITA_PASSO_07, PT_RECEITA_PASSO_08, PT_RECEITA_PASSO_09, PT_RECEITA_PASSO_10, PT_RECEITA_PASSO_11, PT_RECEITA_PASSO_12, PT_RECEITA_PASSO_13, PT_RECEITA_PASSO_14, PT_RECEITA_PASSO_15, PT_RECEITA_PASSO_16, PT_RECEITA_PASSO_17

CONFIGURATION

lookupFile	`pt-receita-passo.txt`
delimiter	`|`
caseSensitive	yes
trimWhitespace	yes

PT_RECEITA_PASSO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_1`

PATTERNS, TRIED IN ORDER

`(.{0})(.{3})(.*)`	keep · `PT_RECEITA_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_1`

PATTERNS, TRIED IN ORDER

`(.{1})(.{3})(.*)`	keep · `PT_RECEITA_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_1`

PATTERNS, TRIED IN ORDER

`(.{2})(.{3})(.*)`	keep · `PT_RECEITA_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_1`

PATTERNS, TRIED IN ORDER

`(.{3})(.{3})(.*)`	keep · `PT_RECEITA_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_RECEITA_1

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · PT_RECEITA_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_RECEITA_1

PATTERNS, TRIED IN ORDER

(.{5})(.{3})(.*)	keep · PT_RECEITA_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_RECEITA_2

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · PT_RECEITA_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_RECEITA_2

PATTERNS, TRIED IN ORDER

(.{7})(.{3})(.*)	keep · PT_RECEITA_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes

requireMask	no

PT_RECEITA_PASSO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_RECEITA_2

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · PT_RECEITA_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_RECEITA_2

PATTERNS, TRIED IN ORDER

(.{9})(.{3})(.*)	keep · PT_RECEITA_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_RECEITA_2

PATTERNS, TRIED IN ORDER

(.{10})(.{3})(.*)	keep · PT_RECEITA_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_RECEITA_2

PATTERNS, TRIED IN ORDER

(.{11})(.{3})(.*)	keep · PT_RECEITA_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_12 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_2`

PATTERNS, TRIED IN ORDER

`(.{12})(.{3})(.*)`	keep · `PT_RECEITA_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_13 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_2`

PATTERNS, TRIED IN ORDER

`(.{13})(.{3})(.*)`	keep · `PT_RECEITA_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_14 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_3`

PATTERNS, TRIED IN ORDER

`(.{14})(.{3})(.*)`	keep · `PT_RECEITA_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_15 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_3`

PATTERNS, TRIED IN ORDER

`(.{15})(.{3})(.*)`	keep · `PT_RECEITA_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_16 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_3`

PATTERNS, TRIED IN ORDER

`(.{16})(.{3})(.*)`	keep · `PT_RECEITA_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PASSO_17 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_3`

PATTERNS, TRIED IN ORDER

`(.{17})(.{3})(.*)`	keep · `PT_RECEITA_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_RECEITA_PREPARAR REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `PT_RECEITA_1`

PATTERNS, TRIED IN ORDER

`(0)(.*)([\dXx])`	replace with `000` · keep · replace with `~`
`(1)(.*)([\dXx])`	replace with `001` · keep · replace with `~`
`(2)(.*)([\dXx])`	replace with `002` · keep · replace with `~`
`(3)(.*)([\dXx])`	replace with `003` · keep · replace with `~`
`(4)(.*)([\dXx])`	replace with `004` · keep · replace with `~`
`(5)(.*)([\dXx])`	replace with `005` · keep · replace with `~`
`(6)(.*)([\dXx])`	replace with `006` · keep · replace with `~`
`(7)(.*)([\dXx])`	replace with `007` · keep · replace with `~`
`(8)(.*)([\dXx])`	replace with `008` · keep · replace with `~`
`(9)(.*)([\dXx])`	replace with `009` · keep · replace with `~`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_REDIGIR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_L1_CREDENCIAL`, `PT_L1_IMAGEM`, `PT_L3_BIOMETRICO`, `PT_L3_GENETICO`

PATTERNS, TRIED IN ORDER

`(.+)`	each character → `X`
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_REGISTO_CRIMINAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_REGISTO_CRIMINAL_LISTA`.

Used by: `PT_PENAL_REGISTO_CRIMINAL`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_ALFANUM`
otherwise	`PT_REGISTO_CRIMINAL_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_REGISTO_CRIMINAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `pt-registo-criminal.txt`, chosen by a keyed hash.

Used by: `PT_REGISTO_CRIMINAL`

CONFIGURATION

lookupFile	`pt-registo-criminal.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_RELIGIAO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_RELIGIAO_LISTA`.

Used by: `PT_L3_RELIGIAO`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_ALFANUM`
otherwise	`PT_RELIGIAO_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_RELIGIAO_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in `pt-religioes.txt`, chosen by a keyed hash.

Used by: `PT_RELIGIAO`

CONFIGURATION

lookupFile	`pt-religioes.txt`
hashMethod	`SHA256`

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_SEXO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_L2_SEXO

PATTERNS, TRIED IN ORDER

(?iu)(feminino|masculino)	PT_SEXO_FEMININO_MASCULINO
(?iu)(mulher|homem)	PT_SEXO_MULHER_HOMEM
(?i)(female|male)	PT_SEXO_FEMALE_MALE
(?i)([fm])	PT_SEXO_F_M
(?i)(h)	PT_SEXO_H_M
(0*?)(?:([12]))	keep · PT_SEXO_1_2
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_SEXO_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in pt-sexo-1-2.txt, chosen by a keyed hash.

Used by: PT_SEXO

CONFIGURATION

lookupFile	pt-sexo-1-2.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_SEXO_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in pt-sexo-f-m.txt, chosen by a keyed hash.

Used by: PT_SEXO

CONFIGURATION

lookupFile	pt-sexo-f-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_SEXO_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in pt-sexo-female-male.txt, chosen by a keyed hash.

Used by: `PT_SEXO`

CONFIGURATION

lookupFile	`pt-sexo-female-male.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_SEXO_FEMININO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-sexo-feminino-masculino.txt`, chosen by a keyed hash.

Used by: `PT_SEXO`

CONFIGURATION

lookupFile	`pt-sexo-feminino-masculino.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-sexo-h-m.txt`, chosen by a keyed hash.

Used by: `PT_SEXO`

CONFIGURATION

lookupFile	`pt-sexo-h-m.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_SEXO_MULHER_HOMEM SECURE LOOKUP

Replaces the value with one of the 2 values in `pt-sexo-mulher-homem.txt`, chosen by a keyed hash.

Used by: `PT_SEXO`

CONFIGURATION

lookupFile	`pt-sexo-mulher-homem.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_SITUACAO_RESIDENCIA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `PT_SITUACAO_RESIDENCIA_LISTA`.

Used by: `PT_L2_SITUACAO_RESIDENCIA`

PATTERNS, TRIED IN ORDER

`(?i)(sim|n[aã]o|true|false|yes|no|[snyx01])`	`PT_INDICADOR`
`(0*?)(?:(\d{1,6}))`	keep · `PT_CM_ALFANUM`
otherwise	`PT_SITUACAO_RESIDENCIA_LISTA`

CONFIGURATION

trimInput	yes
requireMask	no

PT_SITUACAO_RESIDENCIA_LISTA SECURE LOOKUP

Replaces the value with one of the 15 values in `pt-situacao-residencia.txt`, chosen by a keyed hash.

Used by: `PT_SITUACAO_RESIDENCIA`

CONFIGURATION

lookupFile	`pt-situacao-residencia.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_INPUT`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `pt-sem-informacao.txt`, chosen by a keyed hash.

Used by: `PT_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	`pt-sem-informacao.txt`
hashMethod	`SHA256`
maskedValueCase	`PRESERVE_LOOKUP_FILE`
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

PT_TELEFONE REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `PT_CM_DIGITOS`.

Used by: `PT_L1_TELEFONE`

PATTERNS, TRIED IN ORDER

`(0*?)(?:((?:\+|00)351[\s\-]?)(9[1236]|2\d|30)([\d\s\-]{7,10}))`	keep · keep · keep · `PT_CM_DIGITOS`
`(\(?(?:\+|00)351\)?[\s\-]?)(9[1236]|2\d|30)([\d\s\-]{7,10})`	keep · keep · `PT_CM_DIGITOS`
`(0*?)(?:(9[1236]|2\d|30)([\d\s\-]{7,10}))`	keep · keep · `PT_CM_DIGITOS`
otherwise	`PT_CM_DIGITOS`

CONFIGURATION

trimInput	yes

requireMask	no

PT_TEXTO_LIVRE FREE TEXT REDACTION

Replaces the text matching 10 patterns with `[DADO]`, and the 1,618 terms of `pt-texto-nomes.txt` with `[NOME]`.

Used by: `PT_L1_TEXTO_LIVRE`, `PT_SAUDE_TEXTO_CLINICO`

PATTERNS, TRIED IN ORDER

`(?<![\dA-Za-z])\d{8}-?\d-?[A-Za-z0-9]{2}\d(?![A-Za-z\d])`
`(?<![\d\-])\d{8,9}(?![\d\-])`
`(?<!\d)[12]\d{10}(?!\d)`
`[\w.+\-]+@[\w\-]+(\.[\w\-]+)+`
`(?<![\d\-])(\+|00)351\d{9}(?![\d\-])`
`(?<!\d)\d{13,19}(?!\d)`
`PT50\d{21}`
`(?<!\d)\d{21}(?!\d)`
`(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\d)`
`[A-Z]{2}-\d{2}-[A-Z]{2}|\d{2}-[A-Z]{2}-\d{2}`

CONFIGURATION

regExRedactValue	`[DADO]`
lookupFile	`pt-texto-nomes.txt`
lookupFileRedactValue	`[NOME]`
isDenyList	yes

PT_UTENTE STRING ALGORITHM CHAIN

Applies `PT_UTENTE_1` → `PT_UTENTE_2` → `PT_UTENTE_RESTAURAR`, in this order.

Used by: `PT_NUMERO_UTENTE`

CONFIGURATION

algorithmReferences[1]	`PT_UTENTE_1`
algorithmReferences[2]	`PT_UTENTE_2`
algorithmReferences[3]	`PT_UTENTE_RESTAURAR`

PT_UTENTE_1 STRING ALGORITHM CHAIN

Applies `PT_UTENTE_CORPO` → `PT_UTENTE_MARCAR` → `PT_UTENTE_PREPARAR` → `PT_UTENTE_PASSO_00` → `PT_UTENTE_PASSO_01` → `PT_UTENTE_PASSO_02` → `PT_UTENTE_PASSO_03` → `PT_UTENTE_PASSO_04`, in this order.

Used by: `PT_UTENTE`

CONFIGURATION

algorithmReferences[1]	`PT_UTENTE_CORPO`
algorithmReferences[2]	`PT_UTENTE_MARCAR`
algorithmReferences[3]	`PT_UTENTE_PREPARAR`
algorithmReferences[4]	`PT_UTENTE_PASSO_00`
algorithmReferences[5]	`PT_UTENTE_PASSO_01`
algorithmReferences[6]	`PT_UTENTE_PASSO_02`
algorithmReferences[7]	`PT_UTENTE_PASSO_03`
algorithmReferences[8]	`PT_UTENTE_PASSO_04`

PT_UTENTE_2 STRING ALGORITHM CHAIN

Applies `PT_UTENTE_PASSO_05` → `PT_UTENTE_PASSO_06` → `PT_UTENTE_PASSO_07` → `PT_UTENTE_PASSO_08` → `PT_UTENTE_PASSO_09` → `PT_UTENTE_PASSO_10` → `PT_UTENTE_PASSO_11` → `PT_UTENTE_CONTROLO`, in this order.

Used by: `PT_UTENTE`

CONFIGURATION

`algorithmReferences[1]`	`PT_UTENTE_PASSO_05`
`algorithmReferences[2]`	`PT_UTENTE_PASSO_06`
`algorithmReferences[3]`	`PT_UTENTE_PASSO_07`
`algorithmReferences[4]`	`PT_UTENTE_PASSO_08`
`algorithmReferences[5]`	`PT_UTENTE_PASSO_09`
`algorithmReferences[6]`	`PT_UTENTE_PASSO_10`
`algorithmReferences[7]`	`PT_UTENTE_PASSO_11`
`algorithmReferences[8]`	`PT_UTENTE_CONTROLO`

PT_UTENTE_CONTROLO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_UTENTE_2`

PATTERNS, TRIED IN ORDER

`(.*)(\d{2}~)`	keep · `PT_UTENTE_CONTROLO_TABELA`
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

PT_UTENTE_CONTROLO_TABELA DATA CLEANSING

Replaces each value found in `pt-utente-controlo.txt` (10 pairs) by its counterpart; values not in the file stay as they are.

Used by: `PT_UTENTE_CONTROLO`

CONFIGURATION

`lookupFile`	`pt-utente-controlo.txt`
`delimiter`	`|`
`caseSensitive`	yes
`trimWhitespace`	yes

PT_UTENTE_CORPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_UTENTE_1`

PATTERNS, TRIED IN ORDER

`([1-79])([\s\-.]?\d{3}[\s\-.]?\d{3}[\s\-.]?\d)(\d)`	keep · `PT_CM_DIGITOS_LARGURA_FIXA` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes

requireMask	no

PT_UTENTE_MARCAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE_1

PATTERNS, TRIED IN ORDER

`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with _ · keep · replace with _ · keep · replace with _ · keep · replace with _ · keep
`([^\s]*)(\s)([^\s]*)(\s)([^\s]*)`	keep · replace with _ · keep · replace with _ · keep
`([^\s]*)(\s)([^\s]*)`	keep · replace with _ · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO DATA CLEANSING

Replaces each value found in `pt-utente-passo.txt` (130 pairs) by its counterpart; values not in the file stay as they are.

Used by: PT_UTENTE_PASSO_00, PT_UTENTE_PASSO_01, PT_UTENTE_PASSO_02, PT_UTENTE_PASSO_03, PT_UTENTE_PASSO_04, PT_UTENTE_PASSO_05, PT_UTENTE_PASSO_06, PT_UTENTE_PASSO_07, PT_UTENTE_PASSO_08, PT_UTENTE_PASSO_09, PT_UTENTE_PASSO_10, PT_UTENTE_PASSO_11

CONFIGURATION

lookupFile	pt-utente-passo.txt
delimiter	|
caseSensitive	yes
trimWhitespace	yes

PT_UTENTE_PASSO_00 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE_1

PATTERNS, TRIED IN ORDER

`(.{0})(.{3})(.*)`	keep · PT_UTENTE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_01 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE_1

PATTERNS, TRIED IN ORDER

`(.{1})(.{3})(.*)`	keep · `PT_UTENTE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_02 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_UTENTE_1`

PATTERNS, TRIED IN ORDER

`(.{2})(.{3})(.*)`	keep · `PT_UTENTE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_03 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_UTENTE_1`

PATTERNS, TRIED IN ORDER

`(.{3})(.{3})(.*)`	keep · `PT_UTENTE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_04 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_UTENTE_1`

PATTERNS, TRIED IN ORDER

`(.{4})(.{3})(.*)`	keep · `PT_UTENTE_PASSO` · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_05 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `PT_UTENTE_2`

PATTERNS, TRIED IN ORDER

`(.{5})(.{3})(.*)`	keep · `PT_UTENTE_PASSO` · keep

otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_06 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE_2

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · PT_UTENTE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_07 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE_2

PATTERNS, TRIED IN ORDER

(.{7})(.{3})(.*)	keep · PT_UTENTE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_08 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE_2

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · PT_UTENTE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_09 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE_2

PATTERNS, TRIED IN ORDER

(.{9})(.{3})(.*)	keep · PT_UTENTE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_10 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE_2

PATTERNS, TRIED IN ORDER

(.{10})(.{3})(.*)	keep · PT_UTENTE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PASSO_11 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE_2

PATTERNS, TRIED IN ORDER

(.{11})(.{3})(.*)	keep · PT_UTENTE_PASSO · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_PREPARAR REGEX DECOMPOSE

Tries 10 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE_1

PATTERNS, TRIED IN ORDER

(0)(.*)(\d)	replace with 100 · keep · replace with ~
(1)(.*)(\d)	replace with 101 · keep · replace with ~
(2)(.*)(\d)	replace with 102 · keep · replace with ~
(3)(.*)(\d)	replace with 103 · keep · replace with ~
(4)(.*)(\d)	replace with 104 · keep · replace with ~
(5)(.*)(\d)	replace with 105 · keep · replace with ~
(6)(.*)(\d)	replace with 106 · keep · replace with ~
(7)(.*)(\d)	replace with 107 · keep · replace with ~
(8)(.*)(\d)	replace with 108 · keep · replace with ~
(9)(.*)(\d)	replace with 109 · keep · replace with ~
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

PT_UTENTE_RESTAURAR REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: PT_UTENTE

PATTERNS, TRIED IN ORDER

`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with ` ` · keep · replace with ` ` · keep · replace with ` ` · keep · replace with ` ` · keep · replace with ` ` · keep · replace with ` ` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with ` ` · keep · replace with ` ` · keep · replace with ` ` · keep · replace with ` ` · keep · replace with ` ` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with ` ` · keep · replace with ` ` · keep · replace with ` ` · keep · replace with ` ` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with ` ` · keep · replace with ` ` · keep · replace with ` ` · keep
`([^_]*)(_)([^_]*)(_)([^_]*)`	keep · replace with ` ` · keep · replace with ` ` · keep
`([^_]*)(_)([^_]*)`	keep · replace with ` ` · keep
`otherwise`	keep

CONFIGURATION

`trimInput`	yes
`requireMask`	no

APPENDIX B

Files

The lookup and detection files the policy reads. In Delphix each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
`pt-apelidos.txt`	425	`PT_APELIDO`	Silva · Santos · Ferreira · Pereira
`pt-aptidao.txt`	4	`PT_APTIDAO_LISTA`	Apto · Apto condicionalmente · Inapto temporariamente · Inapto definitivamente
`pt-cc-controlo.txt`	20	`PT_CC_CONTROLO_TABELA`	02~|0 · 01~|0 · 12~|9 · 11~|9
`pt-cc-passo.txt`	1,300	`PT_CC_PASSO`	020|001 · 021|121 · 022|241 · 023|361
`pt-certificado-menores.txt`	5	`PT_CERTIFICADO_MENORES_LISTA`	Certificado apresentado · Certificado pendente · Certificado caducado · Não apresentado
`pt-cid10-decimal.txt`	33	`PT_CID10_DECIMAL`	E11.9 · E78.5 · J45.909 · J06.9
`pt-cid10.txt`	46	`PT_CID10`	I10 · E11 · E78 · J45
`pt-cobertura-saude.txt`	9	`PT_COBERTURA`	SNS · ADSE - titular · ADSE - beneficiário familiar · SAD/GNR
`pt-codigos-autarquicos-generalizados.txt`	5,039	`PT_CODIGO_AUTARQUICO_TABELA`	0106|0104 · 0111|0103 · 0112|0108 · 0117|0119
`pt-concelhos-generalizados.txt`	1,612	`PT_CONCELHO`	Castelo de Paiva|Arouca · Castelo de Paiva (Aveiro)|Arouca (Aveiro) · Castelo de Paiva, Aveiro|Arouca, Aveiro · Mealhada|Anadia
`pt-contraordenacoes.txt`	9	`PT_CONTRAORDENACAO_LISTA`	Sem contraordenações · Contraordenação leve · Contraordenação grave · Contraordenação muito grave
`pt-cp4-generalizados.txt`	253	`PT_CP4`	2090|2080 · 2100|2125 · 2140|2330 · 2150|2330
`pt-cpe-letras.txt`	529	`PT_CPE_LETRAS_TABELA`	000~|TT · 001~|TR · 002~|TW · 003~|TA
`pt-cpe-passo.txt`	6,877	`PT_CPE_PASSO`	0000|0000 · 0001|1001 · 0002|2002 · 0003|3003
`pt-dependencia-codigos.txt`	2	`PT_DEPENDENCIA_CODIGO`	1 · 2
`pt-dependencia.txt`	4	`PT_DEPENDENCIA_LISTA`	Dependência de 1.º grau · Dependência de 2.º grau · Sem dependência reconhecida · Em avaliação
`pt-detetar-apelidos.txt`	498	`PT_L1_APELIDO – List` `PT_L1_NOME_COMPLETO – List`	Silva · Santos · Ferreira · Pereira
`pt-detetar-nomes.txt`	362	`PT_L1_NOME – List` `PT_L1_NOME_COMPLETO – List`	Maria · José · Jose · João
`pt-detetar-sexo-letra.txt`	3	`PT_L2_SEXO – List`	f · m · h
`pt-detetar-sexo.txt`	6	`PT_L2_SEXO – List`	homem · mulher · feminino · masculino

FILE	LINES	USED BY	FIRST LINES
pt-diagnosticos.txt	30	PT_DIAGNOSTICO_TEXTO	Hipertensão arterial · Diabetes mellitus tipo 2 · Asma · Lombalgia
pt-empregadores.txt	24	PT_ENTIDADE_EMPREGADORA	Distribuição Atlântica, Lda. · Construções do Norte, S.A. · Transportes da Planície, Lda. · Supermercados Bom Preço, S.A.
pt-escolaridade-codigos.txt	10	PT_ESCOLARIDADE_CODIGO	1 · 2 · 3 · 4
pt-escolaridade.txt	10	PT_ESCOLARIDADE_LISTA	Sem nível de escolaridade · Ensino básico - 1.º ciclo · Ensino básico - 2.º ciclo · Ensino básico - 3.º ciclo
pt-estabelecimentos-ensino.txt	14	PT_ESTABELECIMENTO_ENSINO	Escola Básica de Santo António · Escola Básica e Secundária D. Dinis · Escola Secundária Camões · Escola Secundária Alexandre Herculano
pt-estado-civil-codigos.txt	6	PT_ESTADO_CIVIL_CODIGO	1 · 2 · 3 · 4
pt-estado-civil.txt	6	PT_ESTADO_CIVIL_LISTA	Solteiro(a) · Casado(a) · União de facto · Divorciado(a)
pt-estados-credito.txt	10	PT_ESTADO_CREDITO	Sem incidentes · Crédito vencido · Em incumprimento · Em PERSI
pt-freguesias-generalizadas.txt	29,506	PT_FREGUESIA	Aguada de Cima|Águeda · Aguada de Cima (Águeda)|Águeda (Águeda) · Aguada de Cima, Águeda|Águeda, Águeda · Fermentelos|Águeda
pt-identidades-genero.txt	7	PT_IDENTIDADE_GENERO_LISTA	Mulher cis · Homem cis · Mulher trans · Homem trans
pt-incapacidades.txt	8	PT_INCAPACIDADE_LISTA	Motora · Orgânica · Visual · Auditiva
pt-indicador-0-1.txt	2	PT_INDICADOR_0_1	0 · 1
pt-indicador-s-n.txt	2	PT_INDICADOR_S_N	S · N
pt-indicador-sim-nao.txt	2	PT_INDICADOR_SIM_NAO	Sim · Não
pt-indicador-true-false.txt	2	PT_INDICADOR_TRUE_FALSE	true · false
pt-indicador-y-n.txt	2	PT_INDICADOR_Y_N	Y · N
pt-indicador-yes-no.txt	2	PT_INDICADOR_YES_NO	Yes · No
pt-medicamentos.txt	23	PT_MEDICAMENTO_LISTA	Paracetamol · Ibuprofeno · Metamizol · Omeprazol
pt-moradas.txt	4,000	PT_MORADA	Rua do Mercado, 113 · Rua da Fonte, 241, 5.º B · Rua D. João II, 127, 3.º C · Rua Sá da Bandeira, 148, Cave
pt-nacionalidades.txt	20	PT_NACIONALIDADE	Portuguesa · Brasileira · Angolana · Cabo-verdiana
pt-nib-controlo.txt	194	PT_NIB_CONTROLO_TABELA	00~^|98 · 00~_^|9_8 · 01~^|95 · 01~_^|9_5
pt-nib-passo.txt	1,261	PT_NIB_PASSO	000|000 · 001|101 · 002|202 · 003|303
pt-nomes.txt	282	PT_NOME	Maria · José · João · Ana

FILE	LINES	USED BY	FIRST LINES
pt-opinioes-politicas-codigos.txt	10	PT_OPINIAO_POLITICA_CODIGO	1 · 2 · 3 · 4
pt-opinioes-politicas.txt	7	PT_OPINIAO_POLITICA_LISTA	Esquerda · Centro-esquerda · Centro · Centro-direita
pt-orientacoes-sexuais.txt	8	PT_ORIENTACAO_SEXUAL_LISTA	Heterossexual · Gay · Lésbica · Bissexual
pt-origem-etnica-codigos.txt	7	PT_ORIGEM_ETNICA_CODIGO	1 · 2 · 3 · 4
pt-origem-etnica.txt	7	PT_ORIGEM_ETNICA_LISTA	Branca · Negra · Asiática · Cigana
pt-partidos.txt	11	PT_PARTIDO_LISTA	PS · PSD · Chega · IL
pt-prestacoes-sociais.txt	12	PT_PRESTACAO_SOCIAL_LISTA	Rendimento Social de Inserção · Subsídio de desemprego · Subsídio social de desemprego · Abono de família
pt-procedimentos.txt	10	PT_PROCEDIMENTO_TEXTO	Consulta de medicina geral e familiar · Consulta de urgência · Hemograma completo · Glicemia em jejum
pt-profissoes.txt	38	PT_PROFISSAO	Empregado administrativo · Empregado de balcão · Operador de caixa · Motorista de pesados
pt-receita-controlo.txt	11	PT_RECEITA_CONTROLO_TABELA	00~|1 · 01~|0 · 02~|X · 03~|9
pt-receita-passo.txt	143	PT_RECEITA_PASSO	000|000 · 001|102 · 002|204 · 003|306
pt-registo-criminal.txt	8	PT_REGISTO_CRIMINAL_LISTA	Sem registo criminal · Com registo criminal · Registo cancelado · Processo pendente
pt-religioes.txt	11	PT_RELIGIAO_LISTA	Católica · Ortodoxa · Protestante ou evangélica · Testemunha de Jeová
pt-sem-informacao.txt	1	PT_SUPRIMIR	Sem informação
pt-sexo-1-2.txt	2	PT_SEXO_1_2	1 · 2
pt-sexo-f-m.txt	2	PT_SEXO_F_M	F · M
pt-sexo-female-male.txt	2	PT_SEXO_FEMALE_MALE	Female · Male
pt-sexo-feminino-masculino.txt	2	PT_SEXO_FEMININO_MASCULINO	Feminino · Masculino
pt-sexo-h-m.txt	2	PT_SEXO_H_M	H · M
pt-sexo-mulher-homem.txt	2	PT_SEXO_MULHER_HOMEM	Mulher · Homem
pt-situacao-residencia.txt	15	PT_SITUACAO_RESIDENCIA_LISTA	Autorização de residência temporária · Autorização de residência permanente · Autorização de residência CPLP · Estatuto de residente de longa duração
pt-texto-nomes.txt	1,618	PT_TEXTO_LIVRE	Maria · MARIA · José · JOSÉ
pt-utente-controlo.txt	10	PT_UTENTE_CONTROLO_TABELA	01~|0 · 02~|9 · 03~|8 · 04~|7
pt-utente-passo.txt	130	PT_UTENTE_PASSO	010|002 · 011|104 · 012|206 · 013|308

APPENDIX C

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 `empresa` `entidade` `sociedade` `fornecedor` `pagador` `emitente` `fiscal_?empresa` `coletiv[oa]`

E2 `produto` `prod` `item` `artigo` `empresa` `emp` `firma` `razao` `social` `comercial` `ficheiro` `arquivo` `rua` `via` `avenida` `estrada` `bairro` `concelho` `municipio` `freguesia` `localidade` `distrito` `regiao` `pais` `banco` `entidade` `balcao` `agencia` `plano` `campanha` `projeto` `servico` `tabela` `coluna` `campo` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `centro` `escola` `instituto` `universidade` `curso` `disciplina` `documento` `doc` `unidade` `clinica` `hospital` `seguro` `area` `departamento` `cargo` `sistema` `app` `aplicacao` `grupo` `lista` `relatorio` `processo` `evento` `tarefa` `perfil` `papel` `classe` `objeto` `conta` `medicamento` `diagnostico` `estudo` `programa` `prestacao` `partido` `sindicato` `religiao` `lingua` `idioma` `lugar` `sede` `loja` `armazem` `fornecedor` `contrato` `apolice` `seguradora` `organismo` `organizacao` `parametro` `variavel` `metodo` `funcao` `indice` `job` `script` `fila` `recurso` `rede` `dispositivo` `modelo` `imagem` `foto` `pagina` `sitio` `modulo` `menu` `opcao` `acao` `permissao` `conceito` `imposto` `moeda` `emissor` `fatura` `pagamento` `forma` `zona` `linha` `atividade` `setor` `predio` `edificio` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `utente` `doente` `paciente` `utilizador` `segurado` `beneficiario` `benef` `titular` `funcionario` `trabalhador` `colaborador` `empregado` `aluno` `estudante` `devedor` `fiador` `avalista` `requerente` `proprietario` `arrendatario` `inquilino` `condutor` `tomador` `responsavel` `representante` `procurador` `pessoa` `cidadao` `contribuinte` `mae` `pai` `conjuge` `contacto` `referencia` `vitima` `denunciante` `arguido` `testemunha` `medico` `docente` `socio` `herdeiro` `dador` `tutor` `pensionista` `reformado` `interessado` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner` `completo` `apelidos?` `utilizador` `curto` `abreviado`

E3 `produto` `prod` `item` `artigo` `empresa` `emp` `firma` `razao` `social` `comercial` `ficheiro` `arquivo` `rua` `via` `avenida` `estrada` `bairro` `concelho` `municipio` `freguesia` `localidade` `distrito` `regiao` `pais` `banco` `entidade` `balcao` `agencia` `plano` `campanha` `projeto` `servico` `tabela` `coluna` `campo` `host` `servidor` `dominio` `marca` `modelo` `categoria` `tipo` `centro` `escola` `instituto` `universidade` `curso` `disciplina` `documento` `doc` `unidade` `clinica` `hospital` `seguro` `area` `departamento` `cargo` `sistema` `app` `aplicacao` `grupo` `lista` `relatorio` `processo` `evento` `tarefa` `perfil` `papel` `classe` `objeto` `conta` `medicamento` `diagnostico` `estudo` `programa` `prestacao` `partido` `sindicato` `religiao` `lingua` `idioma` `lugar` `sede` `loja` `armazem` `fornecedor` `contrato` `apolice` `seguradora` `organismo` `organizacao` `parametro` `variavel` `metodo` `funcao` `indice` `job` `script` `fila` `recurso` `rede` `dispositivo` `modelo` `imagem` `foto` `pagina` `sitio` `modulo` `menu` `opcao` `acao` `permissao` `conceito` `imposto` `moeda` `emissor` `fatura` `pagamento` `forma` `zona` `linha` `atividade` `setor` `predio` `edificio` `file` `table` `column` `field` `user` `server` `product` `company` `category` `type` `school` `document` `department` `system` `group` `report` `role` `account` `place` `store` `supplier` `contract` `device` `image` `page` `module` `action` `key` `label` `code` `project` `city` `country` `street` `bank` `cliente` `cli` `utente` `doente` `paciente` `utilizador` `segurado` `beneficiario` `benef` `titular` `funcionario` `trabalhador` `colaborador` `empregado` `aluno` `estudante` `devedor` `fiador` `avalista` `requerente` `proprietario` `arrendatario` `inquilino` `condutor` `tomador` `responsavel` `representante` `procurador` `pessoa` `cidadao` `contribuinte` `mae` `pai` `conjuge` `contacto` `referencia` `vitima` `denunciante` `arguido` `testemunha` `medico` `docente` `socio` `herdeiro` `dador` `tutor` `pensionista` `reformado` `interessado` `customer` `patient` `employee` `member` `holder` `mother` `father` `spouse` `contact` `person` `student` `driver` `owner` `full` `complete` `last` `first`

E4 `ip` `mac` `email` `e_?mail` `eletr[oó]nico` `web` `url` `tipo` `id`

E5 `situa[cç][aã]o` `tipo` `t[ií]tulo` `autoriza[cç][aã]o` `cart[aã]o` `estatuto` `pa[ií]s` `concelho` `freguesia` `distrito`

E6	`ip` `mac` `email` `e_?mail` `web` `url` `type` `id`
E7	`aluno` `estudante` `acad[eé]mica` `curso` `escolar` `profissional` `predial`
E8	`id` `cd` `cod` `codigo` `tipo` `data` `estado` `num` `nr`
E9	`id` `tipo` `codigo` `data` `estado` `fila` `log`

APPENDIX D

Discovery policy and classifiers

The discovery policy `PT – Lei 58 de 2019 – v1` runs these 155 classifiers, with an assignment threshold of 60%.

RGPD e Lei 58 de 2019 - dados pessoais

CLASSIFIER	KIND	DATA CLASS
`PT_L1_CARTAO_CIDADAO – Path`	COLUMN NAME	`PT_L1_CARTAO_CIDADAO`
`PT_L1_CARTAO_CIDADAO – Type`	DATA TYPE	`PT_L1_CARTAO_CIDADAO`
`PT_L1_CARTAO_CIDADAO – Regex`	VALUE FORMAT	`PT_L1_CARTAO_CIDADAO`
`PT_L1_NIF – Path`	COLUMN NAME	`PT_L1_NIF`
`PT_L1_NIF – Type`	DATA TYPE	`PT_L1_NIF`
`PT_L1_NIF – Regex`	VALUE FORMAT	`PT_L1_NIF`
`PT_L1_NISS – Path`	COLUMN NAME	`PT_L1_NISS`
`PT_L1_NISS – Type`	DATA TYPE	`PT_L1_NISS`
`PT_L1_NISS – Regex`	VALUE FORMAT	`PT_L1_NISS`
`PT_L1_PASSAPORTE – Path`	COLUMN NAME	`PT_L1_PASSAPORTE`
`PT_L1_PASSAPORTE – Regex`	VALUE FORMAT	`PT_L1_PASSAPORTE`
`PT_L1_TITULO_RESIDENCIA – Path`	COLUMN NAME	`PT_L1_TITULO_RESIDENCIA`
`PT_L1_CARTA_CONDUCAO – Path`	COLUMN NAME	`PT_L1_CARTA_CONDUCAO`
`PT_L1_NUMERO_ESTUDANTE – Path`	COLUMN NAME	`PT_L1_NUMERO_ESTUDANTE`
`PT_L1_CEDULA_PROFISSIONAL – Path`	COLUMN NAME	`PT_L1_CEDULA_PROFISSIONAL`
`PT_L1_NOME – Path`	COLUMN NAME	`PT_L1_NOME`
`PT_L1_NOME – List`	KNOWN VALUES	`PT_L1_NOME`
`PT_L1_APELIDO – Path`	COLUMN NAME	`PT_L1_APELIDO`
`PT_L1_APELIDO – List`	KNOWN VALUES	`PT_L1_APELIDO`
`PT_L1_NOME_COMPLETO – Path`	COLUMN NAME	`PT_L1_NOME_COMPLETO`
`PT_L1_NOME_COMPLETO – List`	KNOWN VALUES	`PT_L1_NOME_COMPLETO`
`PT_L1_EMAIL – Path`	COLUMN NAME	`PT_L1_EMAIL`
`PT_L1_EMAIL – Type`	DATA TYPE	`PT_L1_EMAIL`
`PT_L1_EMAIL – Regex`	VALUE FORMAT	`PT_L1_EMAIL`
`PT_L1_TELEFONE – Path`	COLUMN NAME	`PT_L1_TELEFONE`
`PT_L1_TELEFONE – Regex`	VALUE FORMAT	`PT_L1_TELEFONE`
`PT_L1_MORADA – Path`	COLUMN NAME	`PT_L1_MORADA`
`PT_L1_MORADA – Type`	DATA TYPE	`PT_L1_MORADA`
`PT_L1_MORADA – Regex`	VALUE FORMAT	`PT_L1_MORADA`
`PT_L1_MORADA_COMPLEMENTO – Path`	COLUMN NAME	`PT_L1_MORADA_COMPLEMENTO`
`PT_L1_CONTA_BANCARIA – Path`	COLUMN NAME	`PT_L1_CONTA_BANCARIA`

CLASSIFIER	KIND	DATA CLASS
PT_L1_CONTA_BANCARIA – Regex	VALUE FORMAT	PT_L1_CONTA_BANCARIA
PT_L1_CARTAO_PAGAMENTO – Path	COLUMN NAME	PT_L1_CARTAO_PAGAMENTO
PT_L1_CARTAO_PAGAMENTO – Regex	VALUE FORMAT	PT_L1_CARTAO_PAGAMENTO
PT_L1_CARTEIRA_DIGITAL – Path	COLUMN NAME	PT_L1_CARTEIRA_DIGITAL
PT_L1_CARTEIRA_DIGITAL – Regex	VALUE FORMAT	PT_L1_CARTEIRA_DIGITAL
PT_L1_IP – Path	COLUMN NAME	PT_L1_IP
PT_L1_IP – Regex	VALUE FORMAT	PT_L1_IP
PT_L1_DISPOSITIVO – Path	COLUMN NAME	PT_L1_DISPOSITIVO
PT_L1_DISPOSITIVO – Regex	VALUE FORMAT	PT_L1_DISPOSITIVO
PT_L1_COOKIE – Path	COLUMN NAME	PT_L1_COOKIE
PT_L1_MATRICULA – Path	COLUMN NAME	PT_L1_MATRICULA
PT_L1_MATRICULA – Regex	VALUE FORMAT	PT_L1_MATRICULA
PT_L1_VEICULO – Path	COLUMN NAME	PT_L1_VEICULO
PT_L1_VEICULO – Regex	VALUE FORMAT	PT_L1_VEICULO
PT_L1_IMOVEL – Path	COLUMN NAME	PT_L1_IMOVEL
PT_L1_IMOVEL – Regex	VALUE FORMAT	PT_L1_IMOVEL
PT_L1_PONTO_ENTREGA – Path	COLUMN NAME	PT_L1_PONTO_ENTREGA
PT_L1_PONTO_ENTREGA – Regex	VALUE FORMAT	PT_L1_PONTO_ENTREGA
PT_L1_CONTRATO – Path	COLUMN NAME	PT_L1_CONTRATO
PT_L1_UTILIZADOR – Path	COLUMN NAME	PT_L1_UTILIZADOR
PT_L1_CREDENCIAL – Path	COLUMN NAME	PT_L1_CREDENCIAL
PT_L1_CREDENCIAL – Regex	VALUE FORMAT	PT_L1_CREDENCIAL
PT_L1_IMAGEM – Path	COLUMN NAME	PT_L1_IMAGEM
PT_L1_GEOLOCALIZACAO – Path	COLUMN NAME	PT_L1_GEOLOCALIZACAO
PT_L1_GEOLOCALIZACAO – Regex	VALUE FORMAT	PT_L1_GEOLOCALIZACAO
PT_L1_TEXTO_LIVRE – Path	COLUMN NAME	PT_L1_TEXTO_LIVRE
PT_L1_TEXTO_LIVRE – Type	DATA TYPE	PT_L1_TEXTO_LIVRE
PT_L1_TEXTO_LIVRE – Regex	VALUE FORMAT	PT_L1_TEXTO_LIVRE
PT_L2_DATA_NASCIMENTO – Path	COLUMN NAME	PT_L2_DATA_NASCIMENTO
PT_L2_DATA_NASCIMENTO – Type	DATA TYPE	PT_L2_DATA_NASCIMENTO
PT_L2_ANO_NASCIMENTO – Path	COLUMN NAME	PT_L2_ANO_NASCIMENTO
PT_L2_ANO_NASCIMENTO – Type	DATA TYPE	PT_L2_ANO_NASCIMENTO
PT_L2_IDADE – Path	COLUMN NAME	PT_L2_IDADE
PT_L2_IDADE – Type	DATA TYPE	PT_L2_IDADE
PT_L2_DATA_EVENTO – Path	COLUMN NAME	PT_L2_DATA_EVENTO
PT_L2_DATA_EVENTO – Type	DATA TYPE	PT_L2_DATA_EVENTO
PT_L2_SEXO – Path	COLUMN NAME	PT_L2_SEXO

CLASSIFIER	KIND	DATA CLASS
PT_L2_SEXO – List	KNOWN VALUES	PT_L2_SEXO
PT_L2_CONCELHO – Path	COLUMN NAME	PT_L2_CONCELHO
PT_L2_CONCELHO – Values	VALUE FORMAT	PT_L2_CONCELHO
PT_L2_FREGUESIA – Path	COLUMN NAME	PT_L2_FREGUESIA
PT_L2_FREGUESIA – Values	VALUE FORMAT	PT_L2_FREGUESIA
PT_L2_CODIGO_AUTARQUICO – Path	COLUMN NAME	PT_L2_CODIGO_AUTARQUICO
PT_L2_CODIGO_AUTARQUICO – Regex	VALUE FORMAT	PT_L2_CODIGO_AUTARQUICO
PT_L2_CODIGO_POSTAL – Path	COLUMN NAME	PT_L2_CODIGO_POSTAL
PT_L2_CODIGO_POSTAL – Regex	VALUE FORMAT	PT_L2_CODIGO_POSTAL
PT_L2_NACIONALIDADE – Path	COLUMN NAME	PT_L2_NACIONALIDADE
PT_L2_NACIONALIDADE – Values	VALUE FORMAT	PT_L2_NACIONALIDADE
PT_L2_SITUACAO_RESIDENCIA – Path	COLUMN NAME	PT_L2_SITUACAO_RESIDENCIA
PT_L2_SITUACAO_RESIDENCIA – Values	VALUE FORMAT	PT_L2_SITUACAO_RESIDENCIA
PT_L2_ESTADO_CIVIL – Path	COLUMN NAME	PT_L2_ESTADO_CIVIL
PT_L2_ESTADO_CIVIL – Values	VALUE FORMAT	PT_L2_ESTADO_CIVIL
PT_L2_PROFISSAO – Path	COLUMN NAME	PT_L2_PROFISSAO
PT_L2_ENTIDADE_EMPREGADORA – Path	COLUMN NAME	PT_L2_ENTIDADE_EMPREGADORA
PT_L2_ESCOLARIDADE – Path	COLUMN NAME	PT_L2_ESCOLARIDADE
PT_L2_ESCOLARIDADE – Values	VALUE FORMAT	PT_L2_ESCOLARIDADE
PT_L2_ESTABELECIMENTO_ENSINO – Path	COLUMN NAME	PT_L2_ESTABELECIMENTO_ENSINO
PT_L2_AGREGADO – Path	COLUMN NAME	PT_L2_AGREGADO
PT_L2_AGREGADO – Type	DATA TYPE	PT_L2_AGREGADO
PT_L3_ORIGEM_ETNICA – Path	COLUMN NAME	PT_L3_ORIGEM_ETNICA
PT_L3_ORIGEM_ETNICA – Values	VALUE FORMAT	PT_L3_ORIGEM_ETNICA
PT_L3_RELIGIAO – Path	COLUMN NAME	PT_L3_RELIGIAO
PT_L3_RELIGIAO – Values	VALUE FORMAT	PT_L3_RELIGIAO
PT_L3_CONVICCAO_FILOSOFICA – Path	COLUMN NAME	PT_L3_CONVICCAO_FILOSOFICA
PT_L3_OPINIAO_POLITICA – Path	COLUMN NAME	PT_L3_OPINIAO_POLITICA
PT_L3_OPINIAO_POLITICA – Values	VALUE FORMAT	PT_L3_OPINIAO_POLITICA
PT_L3_FILIACAO_PARTIDARIA – Path	COLUMN NAME	PT_L3_FILIACAO_PARTIDARIA
PT_L3_FILIACAO_PARTIDARIA – Values	VALUE FORMAT	PT_L3_FILIACAO_PARTIDARIA
PT_L3_FILIACAO_SINDICAL – Path	COLUMN NAME	PT_L3_FILIACAO_SINDICAL
PT_L3_FILIACAO_SINDICAL – Values	VALUE FORMAT	PT_L3_FILIACAO_SINDICAL
PT_L3_BIOMETRICO – Path	COLUMN NAME	PT_L3_BIOMETRICO
PT_L3_BIOMETRICO – Type	DATA TYPE	PT_L3_BIOMETRICO
PT_L3_GENETICO – Path	COLUMN NAME	PT_L3_GENETICO
PT_L3_GENETICO – Regex	VALUE FORMAT	PT_L3_GENETICO

CLASSIFIER	KIND	DATA CLASS
PT_L3_ORIENTACAO_SEXUAL – Path	COLUMN NAME	PT_L3_ORIENTACAO_SEXUAL
PT_L3_ORIENTACAO_SEXUAL – Values	VALUE FORMAT	PT_L3_ORIENTACAO_SEXUAL
PT_L3_VIDA_SEXUAL – Path	COLUMN NAME	PT_L3_VIDA_SEXUAL
PT_L3_IDENTIDADE_GENERO – Path	COLUMN NAME	PT_L3_IDENTIDADE_GENERO
PT_L3_IDENTIDADE_GENERO – Values	VALUE FORMAT	PT_L3_IDENTIDADE_GENERO
PT_L3_VITIMA – Path	COLUMN NAME	PT_L3_VITIMA
PT_SAUDE_NUMERO_UTENTE – Path	COLUMN NAME	PT_SAUDE_NUMERO_UTENTE
PT_SAUDE_NUMERO_UTENTE – Type	DATA TYPE	PT_SAUDE_NUMERO_UTENTE
PT_SAUDE_RECEITA – Path	COLUMN NAME	PT_SAUDE_RECEITA
PT_SAUDE_RECEITA – Regex	VALUE FORMAT	PT_SAUDE_RECEITA
PT_SAUDE_IDENTIFICADOR – Path	COLUMN NAME	PT_SAUDE_IDENTIFICADOR
PT_SAUDE_SUBSISTEMA – Path	COLUMN NAME	PT_SAUDE_SUBSISTEMA
PT_SAUDE_SUBSISTEMA – Values	VALUE FORMAT	PT_SAUDE_SUBSISTEMA
PT_SAUDE_DIAGNOSTICO – Path	COLUMN NAME	PT_SAUDE_DIAGNOSTICO
PT_SAUDE_DIAGNOSTICO – Regex	VALUE FORMAT	PT_SAUDE_DIAGNOSTICO
PT_SAUDE_PROCEDIMENTO – Path	COLUMN NAME	PT_SAUDE_PROCEDIMENTO
PT_SAUDE_MEDICAMENTO – Path	COLUMN NAME	PT_SAUDE_MEDICAMENTO
PT_SAUDE_MEDICAMENTO – Values	VALUE FORMAT	PT_SAUDE_MEDICAMENTO
PT_SAUDE_TEXTO_CLINICO – Path	COLUMN NAME	PT_SAUDE_TEXTO_CLINICO
PT_SAUDE_TEXTO_CLINICO – Type	DATA TYPE	PT_SAUDE_TEXTO_CLINICO
PT_SAUDE_RESULTADO_EXAME – Path	COLUMN NAME	PT_SAUDE_RESULTADO_EXAME
PT_SAUDE_VIH – Path	COLUMN NAME	PT_SAUDE_VIH
PT_SAUDE_GRUPO_SANGUINEO – Path	COLUMN NAME	PT_SAUDE_GRUPO_SANGUINEO
PT_SAUDE_GRUPO_SANGUINEO – Values	VALUE FORMAT	PT_SAUDE_GRUPO_SANGUINEO
PT_SAUDE_INCAPACIDADE – Path	COLUMN NAME	PT_SAUDE_INCAPACIDADE
PT_SAUDE_INCAPACIDADE – Values	VALUE FORMAT	PT_SAUDE_INCAPACIDADE
PT_SAUDE_DEPENDENCIA – Path	COLUMN NAME	PT_SAUDE_DEPENDENCIA
PT_SAUDE_DEPENDENCIA – Values	VALUE FORMAT	PT_SAUDE_DEPENDENCIA
PT_SAUDE_TRABALHO – Path	COLUMN NAME	PT_SAUDE_TRABALHO
PT_SAUDE_TRABALHO – Values	VALUE FORMAT	PT_SAUDE_TRABALHO
PT_SAUDE_REPRODUTIVA – Path	COLUMN NAME	PT_SAUDE_REPRODUTIVA
PT_SAUDE_MENTAL – Path	COLUMN NAME	PT_SAUDE_MENTAL
PT_FIN_CREDITO – Path	COLUMN NAME	PT_FIN_CREDITO
PT_FIN_DIVIDA – Path	COLUMN NAME	PT_FIN_DIVIDA
PT_FIN_DIVIDA – Type	DATA TYPE	PT_FIN_DIVIDA
PT_FIN_RENDIMENTO – Path	COLUMN NAME	PT_FIN_RENDIMENTO
PT_FIN_RENDIMENTO – Type	DATA TYPE	PT_FIN_RENDIMENTO

CLASSIFIER	KIND	DATA CLASS
PT_FIN_PATRIMONIO – Path	COLUMN NAME	PT_FIN_PATRIMONIO
PT_FIN_PATRIMONIO – Type	DATA TYPE	PT_FIN_PATRIMONIO
PT_FIN_PENSAO – Path	COLUMN NAME	PT_FIN_PENSAO
PT_FIN_PENSAO – Type	DATA TYPE	PT_FIN_PENSAO
PT_FIN_PRESTACAO_SOCIAL – Path	COLUMN NAME	PT_FIN_PRESTACAO_SOCIAL
PT_FIN_PRESTACAO_SOCIAL – Values	VALUE FORMAT	PT_FIN_PRESTACAO_SOCIAL
PT_FIN_FISCAL – Path	COLUMN NAME	PT_FIN_FISCAL
PT_PENAL_REGISTO_CRIMINAL – Path	COLUMN NAME	PT_PENAL_REGISTO_CRIMINAL
PT_PENAL_CERTIFICADO_MENORES – Path	COLUMN NAME	PT_PENAL_CERTIFICADO_MENORES
PT_PENAL_CERTIFICADO_MENORES – Values	VALUE FORMAT	PT_PENAL_CERTIFICADO_MENORES
PT_PENAL_PROCESSO – Path	COLUMN NAME	PT_PENAL_PROCESSO
PT_PENAL_PROCESSO – Regex	VALUE FORMAT	PT_PENAL_PROCESSO
PT_PENAL_CONTRAORDENACAO – Path	COLUMN NAME	PT_PENAL_CONTRAORDENACAO