

Argentina — Ley 25.326

Discovery and masking of Argentine personal data: DNI, CUIT and CUIL with a valid check digit, CBU and CVU, quasi-identifiers, the sensitive data of articles 2 and 7, genetic and biometric data, gender identity, health data, financial data and criminal records.

83

DOMAINS

148

CLASSIFIERS

119

ALGORITHMS

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	About this profile set
2	Ley 25.326 in brief
3	Dissociation, pseudonymization and non-production copies
4	How sensitive data is discovered
5	How data is masked
6	Essential and extended packs
7	Domains at a glance

PART 8 · DIRECT IDENTIFIERS

8.1	DNI and libretas	AR_L1_DNI
8.2	CUIT, CUIL and CDI	AR_L1_CUIT
8.3	DNI tramit number	AR_L1_TRAMITE_DNI
8.4	Foreigner documents	AR_L1_DOCUMENTO_EXTRANJERO
8.5	Passport	AR_L1_PASAPORTE
8.6	Civil registry	AR_L1_REGISTRO_CIVIL
8.7	Professional registration	AR_L1_MATRICULA_PROFESIONAL
8.8	Given name	AR_L1_NOMBRE
8.9	Surname	AR_L1_APELLIDO
8.10	Full name	AR_L1_NOMBRE_COMPLETO
8.11	Company name	AR_L1_RAZON_SOCIAL
8.12	E-mail	AR_L1_EMAIL
8.13	Phone	AR_L1_TELEFONO
8.14	Address	AR_L1_DIRECCION
8.15	Address complement	AR_L1_DIRECCION_COMPLEMENTO
8.16	CBU and CVU	AR_L1_CBU
8.17	CBU alias	AR_L1_ALIAS_CBU
8.18	Bank account	AR_L1_CUENTA_BANCARIA
8.19	Payment card	AR_L1_TARJETA
8.20	IP address	AR_L1_IP
8.21	Device identifier	AR_L1_DISPOSITIVO
8.22	Vehicle plate	AR_L1_DOMINIO
8.23	Vehicle and licence	AR_L1_VEICULO
8.24	Property	AR_L1_INMUEBLE

8.25	Customer, employee and contract numbers	AR_L1_CONTRATO
8.26	User and social media	AR_L1_USUARIO
8.27	Credentials	AR_L1_CREDENCIAL
8.28	Geolocation	AR_L1_GEOLOCALIZACION
8.29	Free text	AR_L1_TEXTO_LIBRE

PART 9 · QUASI-IDENTIFIERS

9.1	Birth date	AR_L2_FECHA_NACIMIENTO
9.2	Birth year and clase	AR_L2_ANIO_NACIMIENTO
9.3	Age	AR_L2_EDAD
9.4	Personal event dates	AR_L2_FECHA_EVENTO
9.5	Sex	AR_L2_SEXO
9.6	Localidad and municipality	AR_L2_LOCALIDAD
9.7	Partido and departamento	AR_L2_DEPARTAMENTO
9.8	INDEC geographic codes	AR_L2_CODIGO_GEOGRAFICO
9.9	Postal code	AR_L2_CODIGO_POSTAL
9.10	Neighbourhood	AR_L2_BARRIO
9.11	Nationality	AR_L2_NACIONALIDAD
9.12	Marital status	AR_L2_ESTADO_CIVIL
9.13	Occupation	AR_L2_OCUPACION
9.14	Employer	AR_L2_EMPLEADOR
9.15	Education	AR_L2_NIVEL_EDUCATIVO
9.16	School	AR_L2_ESTABLECIMIENTO_EDUCATIVO
9.17	Children and dependants	AR_L2_PERSONAS_A_CARGO

PART 10 · SENSITIVE DATA

10.1	Ethnic origin	AR_L3_ORIGEN_ETNICO
10.2	Indigenous people	AR_L3_PUEBLO_INDIGENA
10.3	Indigenous language	AR_L3 LENGUA_INDIGENA
10.4	Religion	AR_L3_RELIGION
10.5	Philosophical or moral convictions	AR_L3_CONVICCION_FILOSOFICA
10.6	Political opinions	AR_L3_OPINION_POLITICA
10.7	Party membership	AR_L3_AFILIACION_PARTIDARIA
10.8	Trade union membership	AR_L3_AFILIACION_SINDICAL
10.9	Biometric data	AR_L3_BIOMETRICO
10.10	Genetic data	AR_L3_GENETICO
10.11	Sexual orientation	AR_L3_ORIENTACION_SEXUAL
10.12	Sexual life	AR_L3_VIDA_SEXUAL

10.13	Gender identity	AR_L3_IDENTIDAD_GENERO
10.14	Victims of violence	AR_L3_VICTIMA

PART 11 · HEALTH DATA

11.1	Health identifiers	AR_SALUD_IDENTIFICADOR
11.2	Obra social and prepaid plan	AR_SALUD_COBERTURA
11.3	Diagnosis and ICD-10	AR_SALUD_DIAGNOSTICO
11.4	Procedures and services	AR_SALUD_PROCEDIMIENTO
11.5	Medicines	AR_SALUD_MEDICAMENTO
11.6	Clinical text	AR_SALUD_TEXTO_CLINICO
11.7	Test results	AR_SALUD_RESULTADO_ESTUDIO
11.8	HIV, hepatitis, tuberculosis and STIs	AR_SALUD_VIH
11.9	Blood group	AR_SALUD_GRUPO_SANGUINEO
11.10	Disability and CUD	AR_SALUD_DISCAPACIDAD
11.11	Occupational health	AR_SALUD_OCUPACIONAL
11.12	Sexual and reproductive health	AR_SALUD_REPRODUCTIVA
11.13	Mental health	AR_SALUD_MENTAL

PART 12 · FINANCIAL AND SOCIOECONOMIC DATA

12.1	Debtor situation	AR_FIN_SITUACION_CREDITICIA
12.2	Debt	AR_FIN_DEUDA
12.3	Income and pay	AR_FIN_INGRESOS
12.4	Assets	AR_FIN_PATRIMONIO
12.5	Pensions and benefits	AR_FIN_JUBILACION
12.6	Social benefits and programmes	AR_FIN_PROGRAMA_SOCIAL
12.7	Monotributo category	AR_FIN_MONOTRIBUTO
12.8	Housing tenure	AR_FIN_VIVIENDA

PART 13 · CRIMINAL RECORDS AND COURT FILES

13.1	Records	AR_PENAL_ANTECEDENTES
13.2	Court file	AR_PENAL_EXPEDIENTE
14	The CUIT check digit	
15	Where people live: localidades, partidos and postal code	
16	Limits	
17	Verification	
18	Sources	
A	Algorithms	
B	Files	

C	Exclusion lists
D	Profile set and classifiers

About this profile set

This profile set finds the personal data in an Argentine database and masks it, so that a non-production copy — for testing, development, training or analysis — no longer identifies anyone.

Masking names and DNIs alone is not enough: a birth date, a sex and a small town already point at one person. The set works in the layers where the risk is:

- **Direct identifiers** — DNI and the older libretas, CUIT, CUIL and CDI, the DNI tramit number, foreigner documents, passport, civil registry certificates, professional registration, names, company names, contact, address, CBU, CVU and alias, accounts and cards, devices, vehicle plates, property, free text.
- **Quasi-identifiers** — birth date, age, sex, localidad, partido or departamento and their INDEC codes, postal code, neighbourhood, nationality, marital status, occupation, employer, education.
- **Sensitive data** — those of article 2: racial and ethnic origin, political opinions, religious, philosophical or moral convictions, trade union membership and sexual life; the genetic and biometric data of Convention 108+; gender identity (Law 26.743) and being a victim of gender violence or trafficking.
- **Health data** — sensitive under article 2 and governed by article 8, in a group of their own: medical record and affiliation, obra social or prepaid plan, ICD-10, procedures, medicines, test results, HIV, blood group, disability, occupational, sexual and reproductive and mental health.
- **Financial data** — those of the credit information services of article 26: debtor situation in the BCRA Central de Deudores, debt, income, assets, pensions; and those that reveal a person's socioeconomic situation: ANSES benefits and social programmes, monotributo category, housing tenure.
- **Criminal records** — those that article 7.4 reserves to public authorities, and court file numbers.

In a Masking Engine, the set is a profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those rely on — and the lookup files they read. The appendices list each of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it on its own; an ambiguous one — `NOMBRE` , `DOCUMENTO` , `PARTIDO` , `DEPARTAMENTO` — needs the values to agree. A column with a meaningless name (`CAMP01` , `OBS`) is still found when its values have a recognizable shape or vocabulary: a DNI with dots, a CUIT, a CBU, an address with floor and flat, a plate, a localidad.

Column names are recognized in Spanish, in the abbreviations of Argentine systems (`NRO_DOC` , `APYNOM` , `FEC_NAC` , `COD_LOCALIDAD` , `OBRA_SOCIAL` , `SITUACION_BCRA`) and in English.

Before masking, inventory the binary columns (BLOB, images, PDF). Onboarding processes often keep photos of the front and back of the DNI and a selfie validated against RENAPER. Report those columns as residual risk.

Ley 25.326 in brief

Law 25.326 on the Protection of Personal Data — passed on 4 October 2000 and partially promulgated on 30 October — develops the habeas data of article 43 of the National Constitution, and Decree 1558/2001 implements it. The enforcement authority is the **Agencia de Acceso a la Información Pública (AAIP)**, which absorbed the former National Directorate for Personal Data Protection in 2017. The European Union has recognized Argentina as providing an adequate level of protection since 2003, and confirmed it in its 2024 review.

What matters for a copy of production data:

- **Personal data** is information of any kind about identified or identifiable natural persons **or legal persons** (art. 2). The law protects legal persons too: that is why the set masks company names and companies' CUITs.
- **Sensitive data** is data revealing racial and ethnic origin, political opinions, religious, philosophical or moral convictions, trade union membership, and information about health or sexual life (art. 2). Nobody can be forced to provide it, and **forming files that store information directly or indirectly revealing it is prohibited**, save for exceptions (art. 7). Health data also has the regime of article 8 and professional secrecy.
- **Criminal or misdemeanour records** may only be processed by the competent public authorities (art. 7.4).
- **Dissociation.** The law defines *disociación de datos* as any processing of personal data such that the information obtained cannot be associated with an identified or identifiable person (art. 2). With dissociated data, disclosure needs no consent (art. 11.3.e), and surveys and statistics must use it (art. 28).
- **Security and confidentiality.** The controller must adopt the technical and organizational measures that ensure the security and confidentiality of the data (art. 9), and everyone involved in processing is bound by professional secrecy, even after their relationship with the controller ends (art. 10). The security measures recommended by the AAIP (Resolution 47/2018, Annex I) say, in item H.1.1: *use masking or dissociation techniques for the information in development, test and QA environments*; whoever uses personal data in those environments must apply every other measure of the annex to them.
- **Credit information.** Only data relevant to assess solvency over the last five years may be kept, or two if the debtor paid off the debt (art. 26).
- **Sanctions.** Warning, suspension, fine, and closure or cancellation of the file (art. 31); AAIP Resolution 126/2024 classifies infringements as minor, serious and very serious and grades the sanctions from 1 June 2024. The law also added articles 117 bis and 157 bis to the Criminal Code: inserting false data into a personal data file and illegitimately accessing a data bank or disclosing information recorded in it are crimes (art. 32).

Convention 108. Argentina approved Council of Europe Convention 108 and its additional protocol (Law 27.483) and the protocol that modernizes it, Convention 108+ (Law 27.699, 2022). 108+ adds genetic data, biometric data that uniquely identify a person, and data on offences, criminal proceedings and convictions to the special categories, and requires serious data breaches to be notified to the authority. The protocol enters into force once 38 Parties ratify it: in May 2026 there were 34. This set treats those categories as sensitive regardless.

Reform under way. Congress has several bills to replace Law 25.326 — among them files 644-S-2025 and 1948-D-2025, and 3397-D-2026, introduced on 16 July 2026, which takes up the bill the Executive sent in 2023 and sets 16 as the age to consent to the processing of one's own data. None has been passed. This set follows the law in force.

Dissociation, pseudonymization and non-production copies

The consequence of dissociation follows from the definitions: data that can no longer be associated with an identified or identifiable person is not personal data. The law does not speak of pseudonymization, but the question is the same as under any regime: **can anyone associate the data with the person again?**

The algorithms of this set are deterministic for the Masking Engine's key: the same DNI masks the same way in every table, which keeps joins working. So, for whoever holds the key **and** production, the masked copy can be linked back — it is not dissociated in the sense of article 2 and is still personal data. For whoever holds only the copy, direct identifiers have been replaced and quasi-identifiers generalized.

- Keep the engine key out of reach of the users of the masked copy.

- Do not hand the copy to people who also access production without need.
- Review the quasi-identifiers the set does not know, and measure the re-identification risk before publishing or disclosing the copy as dissociated.

4

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters:

`rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z]*` any continuation.

Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

5

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

6

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	12	25	21	5
Extended	83	148	119	82

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- DNI and libretas — AR_L1_DNI
- CUIT, CUIL and CDI — AR_L1_CUIT
- Foreigner documents — AR_L1_DOCUMENTO_EXTRANJERO
- Passport — AR_L1_PASAPORTE
- Given name — AR_L1_NOMBRE
- Surname — AR_L1_APELLIDO
- Full name — AR_L1_NOMBRE_COMPLETO
- E-mail — AR_L1_EMAIL
- Phone — AR_L1_TELEFONO
- Address — AR_L1_DIRECCION
- Address complement — AR_L1_DIRECCION_COMPLEMENTO
- Birth date — AR_L2_FECHA_NACIMIENTO

With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY			ALGORITHM
DIRECT IDENTIFIERS				
DNI and libretas ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	AR_DOCUMENTO
AR_L1_DNI				
CUIT, CUIL and CDI ESSENTIAL	COLUMN NAME	VALUE FORMAT		AR_CUIT
AR_L1_CUIT				
DNI tramit number	COLUMN NAME	VALUE FORMAT		AR_CM_ALFANUM
AR_L1_TRAMITE_DNI				
Foreigner documents ESSENTIAL	COLUMN NAME			AR_CM_ALFANUM
AR_L1_DOCUMENTO_EXTRANJERO				
Passport ESSENTIAL	COLUMN NAME	VALUE FORMAT		AR_CM_ALFANUM
AR_L1_PASAPORTE				
Civil registry	COLUMN NAME			AR_CM_ALFANUM
AR_L1_REGISTRO_CIVIL				
Professional registration	COLUMN NAME			AR_CM_ALFANUM
AR_L1_MATRICULA_PROFESIONAL				
Given name ESSENTIAL	COLUMN NAME	KNOWN VALUES		AR_NOMBRES
AR_L1_NOMBRE				
Surname ESSENTIAL	COLUMN NAME	KNOWN VALUES		AR_APELLIDOS
AR_L1_APELLIDO				
Full name ESSENTIAL	COLUMN NAME	KNOWN VALUES		AR_NOMBRE_COMPLETO
AR_L1_NOMBRE_COMPLETO				
Company name	COLUMN NAME	VALUE FORMAT		AR_EMPRESA
AR_L1_RAZON_SOCIAL				
E-mail ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	AR_EMAIL
AR_L1_EMAIL				
Phone ESSENTIAL	COLUMN NAME	VALUE FORMAT		AR_TELEFONO
AR_L1_TELEFONO				
Address ESSENTIAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	AR_DIRECCION
AR_L1_DIRECCION				
Address complement ESSENTIAL	COLUMN NAME			AR_CM_ALFANUM
AR_L1_DIRECCION_COMPLEMENTO				
CBU and CVU	COLUMN NAME	VALUE FORMAT		AR_CBU
AR_L1_CBU				
CBU alias	COLUMN NAME	VALUE FORMAT		AR_CM_ALFANUM
AR_L1_ALIAS_CBU				
Bank account	COLUMN NAME			AR_CM_DIGITOS
AR_L1_CUENTA_BANCARIA				
Payment card	COLUMN NAME	VALUE FORMAT		AR_TARJETA
AR_L1_TARJETA				

DOMAIN	FOUND BY			ALGORITHM
IP address AR_L1_IP	COLUMN NAME	VALUE FORMAT		AR_IP
Device identifier AR_L1_DISPOSITIVO	COLUMN NAME	VALUE FORMAT		AR_CM_HEX
Vehicle plate AR_L1_DOMINIO	COLUMN NAME	VALUE FORMAT		AR_CM_DIGITOS_LETRAS
Vehicle and licence AR_L1_VEHICULO	COLUMN NAME	VALUE FORMAT		AR_CM_ALFANUM
Property AR_L1_INMUEBLE	COLUMN NAME			AR_CM_ALFANUM
Customer, employee and contract numbers AR_L1_CONTRATO	COLUMN NAME			AR_CM_ALFANUM
User and social media AR_L1_USUARIO	COLUMN NAME			AR_CM_ALFANUM
Credentials AR_L1_CREDENCIAL	COLUMN NAME			AR_REDACTAR
Geolocation AR_L1_GEOLOCALIZACION	COLUMN NAME	VALUE FORMAT		AR_COORDENADA
Free text AR_L1_TEXTO_LIBRE	COLUMN NAME	DATA TYPE	VALUE FORMAT	AR_TEXTO_LIBRE
QUASI-IDENTIFIERS				
Birth date ESSENTIAL AR_L2_FECHA_NACIMIENTO	COLUMN NAME	DATA TYPE		AR_FECHA_NACIMIENTO
Birth year and clase AR_L2_ANIO_NACIMIENTO	COLUMN NAME	DATA TYPE		AR_ANIO
Age AR_L2_EDAD	COLUMN NAME	DATA TYPE		AR_EDAD
Personal event dates AR_L2_FECHA_EVENTO	COLUMN NAME	DATA TYPE		AR_FECHA_EVENTO
Sex AR_L2_SEXO	COLUMN NAME	KNOWN VALUES		AR_SEXO
Localidad and municipality AR_L2_LOCALIDAD	COLUMN NAME	KNOWN VALUES		AR_LOCALIDAD
Partido and departamento AR_L2_DEPARTAMENTO	COLUMN NAME	KNOWN VALUES		AR_DEPARTAMENTO
INDEC geographic codes AR_L2_CODIGO_GEOGRAFICO	COLUMN NAME	VALUE FORMAT		AR_CODIGO_GEOGRAFICO
Postal code AR_L2_CODIGO_POSTAL	COLUMN NAME	DATA TYPE	VALUE FORMAT	AR_CODIGO_POSTAL
Neighbourhood AR_L2_BARRIO	COLUMN NAME			AR_BARRIO
Nationality AR_L2_NACIONALIDAD	COLUMN NAME	KNOWN VALUES		AR_NACIONALIDAD

DOMAIN	FOUND BY		ALGORITHM
Marital status AR_L2_ESTADO_CIVIL	COLUMN NAME	KNOWN VALUES	AR_ESTADO_CIVIL
Occupation AR_L2_OCUPACION	COLUMN NAME		AR_OCUPACION_O_CODIGO
Employer AR_L2_EMPLEADOR	COLUMN NAME		AR_EMPLEADOR
Education AR_L2_NIVEL_EDUCATIVO	COLUMN NAME	KNOWN VALUES	AR_NIVEL_EDUCATIVO
School AR_L2_ESTABLECIMIENTO_EDUCATIVO	COLUMN NAME		AR_ESTABLECIMIENTO_EDUCATIVO
Children and dependants AR_L2_PERSONAS_A_CARGO	COLUMN NAME	DATA TYPE	AR_CONTEO_LIMITADO
SENSITIVE DATA			
Ethnic origin AR_L3_ORIGEN_ETNICO	COLUMN NAME	KNOWN VALUES	AR_ORIGEN_ETNICO
Indigenous people AR_L3_PUEBLO_INDIGENA	COLUMN NAME	KNOWN VALUES	AR_PUEBLO_INDIGENA
Indigenous language AR_L3_LENGUA_INDIGENA	COLUMN NAME	KNOWN VALUES	AR_LENGUA
Religion AR_L3_RELIGION	COLUMN NAME	KNOWN VALUES	AR_RELIGION
Philosophical or moral convictions AR_L3_CONVICCION_FILOSOFICA	COLUMN NAME		AR_CATEGORIA_SUPRIMIDA
Political opinions AR_L3_OPINION_POLITICA	COLUMN NAME	KNOWN VALUES	AR_OPINION_POLITICA
Party membership AR_L3_AFILIACION_PARTIDARIA	COLUMN NAME	KNOWN VALUES	AR_PARTIDO_POLITICO
Trade union membership AR_L3_AFILIACION_SINDICAL	COLUMN NAME	KNOWN VALUES	AR_CATEGORIA_SUPRIMIDA
Biometric data AR_L3_BIOMETRICO	COLUMN NAME	DATA TYPE	AR_REDACTAR
Genetic data AR_L3_GENETICO	COLUMN NAME		AR_REDACTAR
Sexual orientation AR_L3_ORIENTACION_SEXUAL	COLUMN NAME	KNOWN VALUES	AR_ORIENTACION_SEXUAL
Sexual life AR_L3_VIDA_SEXUAL	COLUMN NAME		AR_CATEGORIA_SUPRIMIDA
Gender identity AR_L3_IDENTIDAD_GENERO	COLUMN NAME	KNOWN VALUES	AR_IDENTIDAD_GENERO
Victims of violence AR_L3_VICTIMA	COLUMN NAME		AR_CATEGORIA_SUPRIMIDA
HEALTH DATA			
Health identifiers AR_SALUD_IDENTIFICADOR	COLUMN NAME		AR_CM_ALFANUM

DOMAIN	FOUND BY			ALGORITHM
Obra social and prepaid plan AR_SALUD_COBERTURA	COLUMN NAME	VALUE FORMAT	KNOWN VALUES	AR_COBERTURA_SALUD
Diagnosis and ICD-10 AR_SALUD_DIAGNOSTICO	COLUMN NAME	VALUE FORMAT		AR_DIAGNOSTICO
Procedures and services AR_SALUD_PROCEDIMIENTO	COLUMN NAME			AR_PROCEDIMIENTO
Medicines AR_SALUD_MEDICAMENTO	COLUMN NAME	KNOWN VALUES		AR_MEDICAMENTO
Clinical text AR_SALUD_TEXTO_CLINICO	COLUMN NAME	DATA TYPE		AR_TEXTO_LIBRE
Test results AR_SALUD_RESULTADO_ESTUDIO	COLUMN NAME			AR_CM_ALFANUM
HIV, hepatitis, tuberculosis and STIs AR_SALUD_VIH	COLUMN NAME			AR_CATEGORIA_SUPRIMIDA
Blood group AR_SALUD_GRUPO_SANGUINEO	COLUMN NAME	KNOWN VALUES		AR_GRUPO_SANGUINEO
Disability and CUD AR_SALUD_DISCAPACIDAD	COLUMN NAME	KNOWN VALUES		AR_DISCAPACIDAD
Occupational health AR_SALUD_OCUPACIONAL	COLUMN NAME	KNOWN VALUES		AR_SALUD_LABORAL
Sexual and reproductive health AR_SALUD_REPRODUCTIVA	COLUMN NAME			AR_CATEGORIA_SUPRIMIDA
Mental health AR_SALUD_MENTAL	COLUMN NAME			AR_CATEGORIA_SUPRIMIDA
FINANCIAL AND SOCIOECONOMIC DATA				
Debtor situation AR_FIN_SITUACION_CREDITICIA	COLUMN NAME	KNOWN VALUES		AR_SITUACION_CREDITICIA
Debt AR_FIN_DEUDA	COLUMN NAME	DATA TYPE		AR_VALOR_DEUDA
Income and pay AR_FIN_INGRESOS	COLUMN NAME	DATA TYPE		AR_INGRESOS
Assets AR_FIN_PATRIMONIO	COLUMN NAME	DATA TYPE		AR_PATRIMONIO
Pensions and benefits AR_FIN_JUBILACION	COLUMN NAME	DATA TYPE		AR_VALOR_JUBILACION
Social benefits and programmes AR_FIN_PROGRAMA_SOCIAL	COLUMN NAME	KNOWN VALUES		AR_PROGRAMA_SOCIAL
Monotributo category AR_FIN_MONOTRIBUTO	COLUMN NAME	DATA TYPE		AR_MONOTRIBUTO
Housing tenure AR_FIN_VIVIENDA	COLUMN NAME	KNOWN VALUES		AR_TENENCIA_VIVIENDA
CRIMINAL RECORDS AND COURT FILES				
Records AR_PENAL_ANTECEDENTES	COLUMN NAME			AR_ANTECEDENTES

DOMAIN	FOUND BY		ALGORITHM
Court file	COLUMN NAME	VALUE FORMAT	AR_EXPEDIENTE
AR_PENAL_EXPEDIENTE			

Direct identifiers

Data that identifies a person on its own. The DNI is the key of almost every Argentine record, and the same number sits inside every worker's CUIL and every taxpayer's CUIT. It masks the same way everywhere, and CUIT, CUIL, CBU and CVU come out with a valid check digit, because applications validate it.

8.1 DNI and libretas

AR_L1_DNI

ESSENTIAL COLUMN NAME DATA TYPE VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The number of the National Identity Document issued by RENAPER — seven or eight digits, written with thousands dots, 28.456.789 —, the same for life, and that of the Libreta de Enrolamiento and Libreta Cívica that preceded it. The DNIs of foreign residents start at 90 million.

NRO_DOCUMENTO columns often mix DNIs, CUITs or CUILs and passports: each value is masked by its shape.

HOW IT IS FOUND

COLUMN NAME AR_L1_DNI - Path

90% dni d_n_i n(o|ro|um|umero)?(de_?)(doc|documento|dni|le|lc) documento?(nacional|de_? identidad|identidad) doc?(identidad|nro|num|numero) nro?doc numdoc nrodoc libreta?(de_?)(enrolamiento|c[íí]vica) (cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp| agente|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietario|inquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciudadano|votante|elector|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|jubilado|pensionado)?(dni|doc|documento|nro?doc) dni? (cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|a gente|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietar io|inquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciu dadano|votante|elector|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|jubilad o|pensionado) c[eé]dula(_?(de_?)?identidad)?

60% documento doc tipo_y_?n(ro|umero)?(de_?)?doc

DATA TYPE AR_L1_DNI - Type

Accepts text (length 6 or more) or number (length 6 or more); any other type rules the domain out.

VALUE FORMAT AR_L1_DNI - Regex

PATTERN	STRENGTH	NOTES
\d{1,2}\.\d{3}\.\d{3}		80%
[1-9]\d{6,7}		40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Digit by digit, keeping the length and the dots. The mapping is one-to-one: a DNI used as a key does not collide. A CUIT-shaped value is masked as a CUIT; one with letters, character by character.

AR_DOCUMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM` .

`AR_CUIT_CADENA` **STRING ALGORITHM CHAIN**

Applies `AR_CUIT_AUX` → `AR_CUIT_AJUSTE` , in this order.

`AR_CUIT_AUX` **CHECK DIGIT**

Masks the digits with `AR_CUIT_CUERPO` and recomputes a modulus 11 check digit with weights `4 6 8 10 12 14 4 6 8 10` from the right.

`AR_CUIT_CUERPO` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches:

`AR_CM_DIGITOS` .

`AR_CM_DIGITOS` **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

`AR_CUIT_AJUSTE` **REGEX DECOMPOSE**

Tries 7 patterns in order and gives each part of the value its own action; when none matches: `AR_CUIT_DV` .

`AR_CUIT_DV` **CHECK DIGIT**

Masks the digits with `AR_IDENTIDAD` and recomputes a modulus 11 check digit with weights `2 3 4 5 6 7 2 3 4 5` from the right.

`AR_IDENTIDAD` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

`AR_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
28.456.789	→	82.036.250
5123456	→	9064408
20-28456789-1	→	20-82036250-1

8.2 CUIT, CUIL and CDI

AR_L1_CUIT

ESSENTIAL

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The tax identification key of ARCA (formerly AFIP), the labour identification key of ANSES and the identification key: eleven digits, `20-28456789-1` . The first two give the type — 20 man, 27 woman, 23 and 24 either, 30, 33 and 34 legal persons —; the eight in the middle are a natural person's DNI; the last is the check digit.

The digit uses weights 5, 4, 3, 2, 7, 6, 5, 4, 3 and 2 from the left, modulus 11: eleven minus the remainder, and 0 when the remainder is 0. When the remainder is 1 no digit is possible and the type changes: 20 and 27 become 23, 30 becomes 33, 23 becomes 24 and 33 becomes 34.

HOW IT IS FOUND

COLUMN NAME AR_L1_CUIT - Path

90% cuit[a-z0-9_]* cuil[a-z0-9_]* cdi n(o|ro|um|umero)?(de_)?(cuit|cuil|cdi) clave_?
[uú]nica?(de_)?(identificaci[oó]n_)?(tributaria|laboral)
(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|
agente|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propieta
rio|inquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ci
udadano|votante|elector|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|jubila
do|pensionado)?(cuit|cuil) id_?(tributario|fiscal) identificaci[oó]n_?(tributaria|fiscal)
nro_?afip tax_?id

VALUE FORMAT AR_L1_CUIT - Regex

PATTERN	STRENGTH	NOTES
(20 2[347] 3[034])-\d{8}-\d		95%
(20 2[347] 3[034])\d{9}		60%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The type stays, the eight digits are mapped with the same algorithm as the DNI — a person's CUIL still holds their masked DNI — and the digit is recomputed; when the remainder comes out as 1, the type changes as ARCA would change it. Every masked CUIT is valid and the mapping is one-to-one. See *The CUIT check digit*.

AR_CUIT REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_CM_DIGITOS .

AR_CUIT_CADENA STRING ALGORITHM CHAIN

Applies AR_CUIT_AUX → AR_CUIT_AJUSTE , in this order.

AR_CUIT_AUX CHECK DIGIT

Masks the digits with AR_CUIT_CUERPO and recomputes a modulus 11 check digit with weights 4 6 8 10 12 14 4 6 8 10 from the right.

AR_CUIT_CUERPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_CM_DIGITOS .

AR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

AR_CUIT_AJUSTE REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: AR_CUIT_DV .

AR_CUIT_DV CHECK DIGIT

Masks the digits with AR_IDENTIDAD and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 3 4 5 from the right.

AR_IDENTIDAD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
20-28456789-1	→	20-82036250-1
30500010912	→	30518024651

8.3 DNI tramit number

AR_L1_TRAMITE_DNI

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The eleven-digit tramit number and the copy letter printed on the DNI. Online services ask for them to check that whoever signs up holds the card.

HOW IT IS FOUND

COLUMN NAME	AR_L1_TRAMITE_DNI - Path		
85%	n(o ro um umero)?(de_)?tr[aá]mite(_?dni)? tramite_?dni id_?tr[aá]mite ejemplar(_?dni)? n(ro umero)?ejemplar		
VALUE FORMAT	AR_L1_TRAMITE_DNI - Regex		
PATTERN	STRENGTH	NOTES	
00\d{9}		50%	
A value that matches none counts 30% against the domain.			

HOW IT IS MASKED

Character by character, keeping length and format.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
00123456789	→ 34348564564

8.4 Foreigner documents

AR_L1_DOCUMENTO_EXTRANJERO

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The precarious residence and the residence certificate of the National Directorate of Migration, the residence file number, the foreign identity card and the visa number.

HOW IT IS FOUND

COLUMN NAME	AR_L1_DOCUMENTO_EXTRANJERO - Path		
85%	residencia_?precaria certificado_(de_)?residencia radicaci[oó]n(_? (n(o ro um umero) expediente))? expediente_?migratorio documento_?extranjero doc_? extranjero c[eé]dula_?extranjera n(o ro um umero)?(visa residencia) visa(_? (n(o ro um umero)))? dnm_(expediente n(ro umero))		

HOW IT IS MASKED

Character by character, keeping length and format.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

123456/2021

→

773455/6889

8.5 Passport

AR_L1_PASAPORTE

ESSENTIAL

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

Argentine passport numbers — three letters and six digits, AAA123456 — and foreign ones.

HOW IT IS FOUND

COLUMN NAME

AR_L1_PASAPORTE – Path

90%

pasaporte[a-z0-9]* n(o|ro|um|umero)?pasaporte passport[a-z0-9]*

VALUE FORMAT

AR_L1_PASAPORTE – Regex

PATTERN

STRENGTH

NOTES

[A-Z]{3}\d{6}

40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

AR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

AAA123456

→

IE0166988

8.6 Civil registry

AR_L1_REGISTRO_CIVIL

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The number, volume and folio of birth, marriage, civil union and death certificates, and certificates of vital events.

HOW IT IS FOUND

COLUMN NAME

AR_L1_REGISTRO_CIVIL – Path

85%

acta?(de_)?(nacimiento|matrimonio|defunci[oó]n|uni[oó]n?convivencial)(_?
 (n(o|ro|um|umero)|tomo|folio))? n(o|ro|um|umero)?acta partida?(de_)?
 (nacimiento|defunci[oó]n|matrimonio) certificado?(de_)?(nacimiento|defunci[oó]n|hecho?
 vital) tomo?(acta|partida) folio?(acta|partida)

HOW IT IS MASKED

Character by character, keeping length and format.

AR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

1234 Tomo 2A

→

3049 Jova 3U

8.7 Professional registration

AR_L1_MATRICULA_PROFESIONAL

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The national (MN) or provincial (MP) registration of doctors, lawyers, accountants and other chartered professions, and the REFEPS register of health professionals. Professional associations publish their rolls with names.

HOW IT IS FOUND

COLUMN NAME

AR_L1_MATRICULA_PROFESIONAL - Path

80%

matr[ií]cula(_?(profesional|nacional|provincial|m[eédica|colegio))?

mat_?(prof|nac|prov)

m_?n m_?p n(o|ro|um|umero)?matr[ií]cula refeps registro_profesional

HOW IT IS MASKED

Character by character, keeping length and format.

AR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

MN 123456

→

KW 614053

8.8 Given name

AR_L1_NOMBRE

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The given name, one or more: Soledad , Juan Carlos , María del Carmen . Also the self-perceived name of Law 26.743.

HOW IT IS FOUND

COLUMN NAME

AR_L1_NOMBRE - Path

85%

primer_?nombre segundo_?nombre nombres?_(de_?)?pila pri(mer)?_?nom seg(undo)?_?nom

nombre_?1 nombre_?2 first_?names? given_?names? fname middle_?names? nombres (except

when followed by completos? , y_apellidos? , apellidos?)

50%

nombre (except when followed by list E1) nom (except when followed by list E2) name (except when followed by list E3)

KNOWN VALUES

AR_L1_NOMBRE - List

LIST

VALUES

STRENGTH

FIRST VALUES

ar-detectar-nombres.txt

876

70%

María, Maria, Juan, José, Jose, Carlos

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, replacing each name with one from the list — the most frequent of RENAPER's historical register of names. `de`, `del` and `la` stay in place. More than four words are masked character by character.

AR_NOMBRES **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

AR_PALABRA_NOMBRE **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `AR_NOMBRE`.

AR_NOMBRE **NAME**

Replaces the name with one of the 756 names in `ar-nombres.txt`.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
María del Carmen	→	Lucía del Reinaldo
JUAN CARLOS	→	VERÓNICA GISEL

8.9 Surname

AR_L1_APELLIDO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The surname — one, or the father's and the mother's —, and the married name: `López de Rossi`.

HOW IT IS FOUND

COLUMN NAME `AR_L1_APELLIDO` - Path

85% `apellidos?` `primer_?apellido` `segundo_?apellido` `apellido_?(1|2|paterno|materno|casada)`
`ape_?(1|2)` `last_?names?` `surnames?` `family_?names?` `lname`

KNOWN VALUES `AR_L1_APELLIDO` - List

LIST	VALUES	STRENGTH	FIRST VALUES
<code>ar-detectar-apellidos.txt</code>	477	70%	González, Gonzalez, Rodríguez, Rodriguez, Gómez, Gomez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, replacing each surname with one from the list — of Spanish, Italian, Guaraní, Andean and other origins —; particles stay in place.

AR_APELLIDOS **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM`.

AR_PALABRA_APELLIDO **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `AR_APELLIDO`.

AR_APELLIDO **NAME**

Replaces the name with one of the 408 names in `ar-apellidos.txt`.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

López de Rossi

→ Guevara de Morelli

8.10 Full name

AR_L1_NOMBRE_COMPLETO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Given names and surnames in one column: Juan Carlos Fernández, FERNÁNDEZ, JUAN CARLOS. Also those of the father, mother, guardian, spouse or partner, guarantor and personal reference.

A column named just NOMBRE may hold given names or full names: the values decide between the two domains.

HOW IT IS FOUND

COLUMN NAME

AR_L1_NOMBRE_COMPLETO - Path

90%

nombres?_?(completos?|y_?apellidos?|apellidos?) apellidos?_?(y_?)?nombres? ape_?nom
apeynom apynom apenom ayn nombre_?(del_?|de_?la_?)?

(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|agent
e|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietario|i
nquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciudada
no|contribuyente|madre|padre|conyuge|concubino|conviviente|contacto|referencia|victima|denunci
ante|denunciado|imputado|procesado|testigo|medico|docente|socio|heredero|causante|donante|cura
dor|jubilado|pensionado|customer|patient|employee|member|holder|mother|father|spouse|contact|p
erson|student|driver|owner)

(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|agen
te|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietario|i
nquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciudad
ano|contribuyente|madre|padre|conyuge|concubino|conviviente|contacto|referencia|victima|denunc
iante|denunciado|imputado|procesado|testigo|medico|docente|socio|heredero|causante|donante|cur
ador|jubilado|pensionado|customer|patient|employee|member|holder|mother|father|spouse|contact|
person|student|driver|owner)?(nombre|nom|apynom) nom_?

(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|agent
e|trabajador|contratado|alumno|estudiante|deudor|codeudor|garante|fiador|tomador|propietario|i
nquilino|locatario|locador|conductor|tutor|responsable|representante|apoderado|persona|ciudada
no|contribuyente|madre|padre|conyuge|concubino|conviviente|contacto|referencia|victima|denunci
ante|denunciado|imputado|procesado|testigo|medico|docente|socio|heredero|causante|donante|cura
dor|jubilado|pensionado|customer|patient|employee|member|holder|mother|father|spouse|contact|p
erson|student|driver|owner) nombre_?(madre|padre|tutor|conyuge|contacto_?
emergencia|referencia) full_?name person_?name

60%

madre padre tutor conyuge conviviente concubin[oa] representante_?legal apoderado
garante fiador beneficiario heredero titular referencia_?(personal|familiar)

50%

nombre (except when followed by list E1) nom (except when followed by list E2) name (except when followed by list E3)

KNOWN VALUES AR_L1_NOMBRE_COMPLETO – List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-nombres.txt	876	60%	María, Maria, Juan, José, Jose, Carlos
ar-detectar-apellidos.txt	477	60%	González, Gonzalez, Rodríguez, Rodriguez, Gómez, Gomez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

In Argentine order, with a single surname as the most common: two words are a given name and a surname; three, two given names and a surname; four, two and two; five, three and two. APELLIDO, NOMBRES with a comma, as in lists and electoral rolls, is recognized too. The result is a plausible name, never the original.

AR_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: AR_CM_ALFANUM .

AR_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: AR_CM_ALFANUM .

AR_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_APELLIDO .

AR_APELLIDO NAME

Replaces the name with one of the 408 names in ar-apellidos.txt .

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_NOMBRES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: AR_CM_ALFANUM .

AR_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_NOMBRE .

AR_NOMBRE NAME

Replaces the name with one of the 756 names in ar-nombres.txt .

EXAMPLES

VALUE		MASKED
Juan Carlos Fernández	→	Verónica Gisel Moyano
Soledad Gómez	→	Catalino Fontana
FERNÁNDEZ, JUAN CARLOS	→	MOYANO, VERÓNICA GISEL

8.11 Company name

AR_L1_RAZON_SOCIAL

COLUMN NAME

VALUE FORMAT

SECURE LOOKUP

WHAT IT IS

The registered name or trade name of a company, supplier or shop. Law 25.326 also protects the data of legal persons, and in a one-person company or an SAS the company name is often the owner's name.

HOW IT IS FOUND

COLUMN NAME AR_L1_RAZON_SOCIAL – Path

85%

raz[oó]n_?social denominaci[oó]n_?social nombre_?(de_?)?fantas[ií]a nombre_?

(empresa|comercio|proveedor|sociedad|persona_?jur[ií]dica|comercial)

(empresa|proveedor|sociedad)_?(nombre|razon_?social) legal_?name company_?name business_?

name trade_?name

VALUE FORMAT AR_L1_RAZON_SOCIAL – Regex

PATTERN	STRENGTH	NOTES
<code>.*\b(S\.\.?s?A\.\.?(\s?S\.\.?)? S\.\.?s?R\.\.?s?L\.\.? S\.\.?s?C\.\.?s?S\.\.? S\.\.?s?A\.\.?s?U\.\.? Ltda\.\.? Coop(erativa)?\.\.?)\s*\$</code>	80%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a fictitious company from the list.

AR_EMPRESA **SECURE LOOKUP**

Replaces the value with one of the 24 values in `ar-empresas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Arcos Dorados Argentina S.A.	→ Construcciones Andinas S.R.L.

8.12 E-mail

AR_L1_EMAIL

ESSENTIAL **COLUMN NAME** **DATA TYPE** **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

Personal and corporate e-mail addresses.

HOW IT IS FOUND

COLUMN NAME AR_L1_EMAIL – Path

85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `correo(_?electr[oó]nico)?[a-z0-9_]*` `dir_?correo`
`direcci[oó]n_?(de_)?correo` `direcci[oó]n_?electr[oó]nica`

DATA TYPE AR_L1_EMAIL – Type

Accepts text (length 5 or more); any other type rules the domain out.

VALUE FORMAT AR_L1_EMAIL – Regex

PATTERN	STRENGTH	NOTES
<code>[A-Za-z0-9._%+'-]+@[A-Za-z0-9.\-]+\.[A-Za-z]{2,24}</code>	100%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

User and domain are mapped character by character, and the top-level domain — `.com`, `.com.ar` — becomes `.test`, reserved for testing: a masked address never delivers a message.

AR_EMAIL **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: **AR_CM_ALFANUM**.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
soledad.fernandez@hotmail.com.ar	→ femuhus.wunfilmac@zugyaiy.zen.test

8.13 Phone

AR_L1_TELEFONO

- ESSENTIAL
- COLUMN NAME
- VALUE FORMAT
- REGEX DECOMPOSE

WHAT IT IS

Ten-digit national numbers: an area code of two to four digits — 11 Buenos Aires, 351 Córdoba, 2966 Río Gallegos — and the subscriber number. Mobiles add 9 after +54 , or 15 after the area code when dialled within the country: +54 9 11 4567-8901 , (0351) 15-456-7890 . Also local numbers without an area code, 4567-8901 .

HOW IT IS FOUND

COLUMN NAME

AR_L1_TELEFONO - Path

85%

tel tel[eé]fono[a-z0-9_]* tel_?
(fijo|particular|laboral|m[ó]vil|celular|casa|oficina|contacto|alternativo) celular[a-z0-9_]* cel m[ó]vil whats_app n(o|ro|um|umero)_?
(tel|tel[eé]fono|celular|cel|contacto|movil) caracter[ii]stica_tel fax phone[a-z0-9_]*
mobile[a-z0-9_]*

VALUE FORMAT

AR_L1_TELEFONO - Regex

PATTERN	STRENGTH	NOTES
(\+?54[\s\~]?9?[\s\~]?)?(?0?(11 [23]\d{2,3})\)?[\s\~]?(15[\s\~]?)?\d{3,4}[\s\~]?\d{4}	90%	
(15[\s\~]?)?\d{4}-\d{4}	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

+54 , 9, the area code, 15 and the separators stay; the subscriber number — at least six digits — is mapped.

AR_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: AR_CM_DIGITOS .

AR_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
+54 9 11 4567-8901	→	+54 9 11 9910-5048
(0351) 15-456-7890	→	(0351) 15-047-9607

8.14 Address

AR_L1_DIRECCION

- ESSENTIAL
- COLUMN NAME
- DATA TYPE
- VALUE FORMAT
- SECURE LOOKUP

WHAT IT IS

The address with street and height — Av. Corrientes 1234 Piso 5 Dto. B —, with a numbered street as in La Plata (Calle 7 N° 1234), or with block and lot in neighbourhoods and housing plans (Mz. 12 Lote 5), and routes with a kilometre.

HOW IT IS FOUND

COLUMN NAME AR_L1_DIRECCION - Path

80% direcci[oó]n[a-z0-9]* (except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`, `correo`; except when followed by list E4) domicilio[a-z0-9]* (except when followed by `fiscal_?electr[oó]nico`, `electr[oó]nico`) dom_?(real|legal|fiscal|particular|laboral|postal|cliente|paciente) calle(_?y?(n(ro|umero)|altura))? residencia lugar_?(de_?)?residencia address[a-z0-9]* (except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`; except when followed by list E5)

DATA TYPE AR_L1_DIRECCION - Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT AR_L1_DIRECCION - Regex

PATTERN	STRENGTH	NOTES
(?i)(av avda avenida bv bvard boulevard diag diagonal pje pasaje calle)\.?\s+[a-záéíóúñü0-9.']{1,40}\s+(n[°º]\s*)?\d{1,5}.*	80%	
(?i)[a-záéíóúñü0-9.']{3,40}\s+(n[°º]\s*)?\d{1,5}\s*,?\s*(piso p\. pb dto depto dpto departamento)\b.*	80%	
(?i)[a-záéíóúñü.']{3,40}\s+\d{2,5}	40%	
(?i).*\b(mz mza manzana)\.?\s*\d+.*\b(lote casa lt)\.?\s*\d+.*	70%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The whole line is replaced by a fictitious Argentine address of the same forms. Neighbourhood, localidad, partido and postal code in columns of their own are handled by their domains.

AR_DIRECCION **SECURE LOOKUP**

Replaces the value with one of the 4,000 values in `ar-direcciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Av. Corrientes 1234 Piso 5 Dto. B	→ 25 de Mayo 2808

8.15 Address complement

AR_L1_DIRECCION_COMPLEMENTO

ESSENTIAL **COLUMN NAME** **CHARACTER MAPPING**

WHAT IT IS

Floor, flat, functional unit, tower, block, lot, house, height and cross streets in columns of their own.

HOW IT IS FOUND

COLUMN NAME AR_L1_DIRECCION_COMPLEMENTO - Path

70% piso dto depto dpto departamento_?(dom|domicilio|n(ro|umero)) unidad_?funcional uf torre manzana mz mza lote casa_?(n(o|ro|um|umero))? altura n(ro|umero)? (puerta|calle|domicilio) puerta entre_?calles? monoblock block oficina local

HOW IT IS MASKED

Character by character, keeping length and format.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

Piso 3 Dto. B

→

Vara 0 Pqi. M

8.16 CBU and CVU

AR_L1_CBU

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The Clave Bancaria Uniforme of a bank account and the Clave Virtual Uniforme of a payment account: 22 digits in two blocks. The first — bank and branch, or 000 and the payment service provider — carries a check digit with weights 7, 1, 3, 9, 7, 1, 3; the second, the account number, one with weights 3, 9, 7, 1 repeated.

HOW IT IS FOUND

COLUMN NAME

AR_L1_CBU - Path

90%

`cbu[a-z0-9]*` `cvu[a-z0-9]*` `clave_?bancaria?uniforme` `clave_?virtual?uniforme`
`n(o|ro|um|umero)?(cbu|cvu)` `(cbu|cvu)?(destino|origen|acreditaci[ó]n|cliente|proveedor)`

VALUE FORMAT

AR_L1_CBU - Regex

PATTERN

STRENGTH

NOTES

`\d{8}[\s\~]? \d{14}`

90%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The first block stays — the bank identifies nobody —; the thirteen account digits are mapped and their check digit recomputed with Check Digit. Every masked CBU and CVU is valid and the mapping is one-to-one.

AR_CBU REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_CM_DIGITOS .

AR_CBU_CUENTA CHECK DIGIT

Masks the digits with AR_CM_DIGITOS and recomputes a modulus 10 check digit with weights 3 1 7 9 3 1 7 9 3 1 7 9 3 from the right.

AR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

2850590940090418135201

→

2850590917727168338551

8.17 CBU alias

AR_L1_ALIAS_CBU

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

An account's alias, 6 to 20 characters with dots: gato.mesa.lluvia . Many holders build it from their name.

HOW IT IS FOUND

COLUMN NAME

AR_L1_ALIAS_CBU - Path

90%

`alias_?(cbu|cvu|bancario|cuenta|transferencia)` `(cbu|cvu)?alias`

VALUE FORMAT AR_L1_ALIAS_CBU - Regex

PATTERN

STRENGTH

NOTES

[a-z0-9-]{2,12}\.[a-z0-9-]{2,12}\.[a-z0-9-]{2,12}

50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the dots and the length.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

gato.mesa.lluvia

→ xupa.vutu.jxajue

8.18 Bank account

AR_L1_CUENTA_BANCARIA

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Savings, current and salary account numbers, and digital wallets. The bank code is not personal data and has no domain.

HOW IT IS FOUND

COLUMN NAME AR_L1_CUENTA_BANCARIA - Path

85%

cuenta?(bancaria|banco|corriente|sueldo|haberes|acreditaci[ó]n|destino|origen) caja?
(de_)?ahorros? n(o|ro|um|umero)?(de_)?(cuenta|cta) nro?cta num?cta cta?
(cte|corriente|ahorro|bancaria|sueldo) tipo?y?n(o|ro|um|umero)?cuenta iban account?
(no|num|number) bank?account billetera(_?virtual)?

HOW IT IS MASKED

Digits are mapped; separators stay.

AR_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

123-456789/0

→ 171-367811/5

8.19 Payment card

AR_L1_TARJETA

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers, recognized by the Luhn algorithm.

HOW IT IS FOUND

COLUMN NAMEAR_L1_TARJETA – Path

85%tarjeta(_?(cr[eé]dito|d[eé]bito|n(o|ro|um|umero)))?n(o|ro|um|umero)?tarjetapancard?(no|num|number)credit_?cardtc_?(numero|num|nro)td_?(numero|num|nro)

VALUE FORMATAR_L1_TARJETA – Regex

PATTERN	STRENGTH	NOTES
\d{13,19}	90%	LUHN check digit; after removing [\s\-]

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Payment Card: another number that passes the Luhn algorithm. Only card-shaped values reach it.

AR_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

AR_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

EXAMPLES

VALUE	MASKED
4509 9535 6623 3704	→ 1988 7321 0351 1038

8.20 IP address

AR_L1_IP

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses from access logs and transactions.

HOW IT IS FOUND

COLUMN NAMEAR_L1_IP – Path

85%ipip_?(address|addr|origen|destino|cliente|usuario|acceso|login|remota|publica)direcci[oó]n?ipdir?ipip[46]remote?addr(ess)?client?iphost?ip

VALUE FORMATAR_L1_IP – Regex

PATTERN	STRENGTH	NOTES
((25[0-5] 2[0-4]\d 1?\d?\d)\.){3}(25[0-5] 2[0-4]\d 1?\d?\d)	100%	
[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7}	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet is mapped to 1-254; an IPv6 address is mapped keeping its hex characters.

AR_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_CM_HEX .

AR_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

AR_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

181.47.132.21

→

250.89.176.95

8.21 Device identifier

AR_L1_DISPOSITIVO

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

IMEI, IMSI, ICCID, MAC address, advertising identifiers, cookies and sessions.

HOW IT IS FOUND

COLUMN NAME

AR_L1_DISPOSITIVO - Path

80%

imei imsi iccid mac mac_?address direcci[oó]n_?mac device_?(id|uuid|serial) id_?
(dispositivo|equipo|celular) serial_?(equipo|celular|dispositivo) advertising_?id idfa
gaid cookie(_?id)? session_?id id_?sesi[oó]n

VALUE FORMAT

AR_L1_DISPOSITIVO - Regex

PATTERN

STRENGTH

NOTES

([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2}

100%

\d{15}

80% LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, with hex digits kept hex: a MAC stays a MAC.

AR_CM_HEX

CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

3c:22:fb:9a:10:e4

→

5e:83:bb:3c:31:f9

8.22 Vehicle plate

AR_L1_DOMINIO

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

The plate (dominio): the Mercosur one, two letters, three digits and two letters for cars (AE 123 KD) and one letter, three digits and three letters for motorcycles (A123BCD); the one before 2016, three letters and three digits (ABC 123) or three digits and three letters for motorcycles. The Motor Vehicle Registry leads from the plate to the owner.

HOW IT IS FOUND

COLUMN NAME

AR_L1_DOMINIO - Path

85%

dominio(_?(veh[ii]culo|automotor|auto|moto|rodado))? patente(_?(veh[ii]culo|auto|moto))?
n(o|ro|um|umero)_?(dominio|patente) placa license_?plate plate(_?(no|number))?

VALUE FORMAT AR_L1_DOMINIO - Regex

PATTERN	STRENGTH	NOTES
[A-Z]{2}\s?\d{3}\s?[A-Z]{2}		80%
[A-Z]{3}\s?\d{3}		70%
[A-Z]\d{3}[A-Z]{3}		70%
\d{3}\s?[A-Z]{3}		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Letters to letters and digits to digits, position by position, with the spaces: the plate format stays.

AR_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
AE 123 KD	→	YQ 812 TI
ABC123	→	AFJ775

8.23 Vehicle and licence

AR_L1_VEHICULO

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The VIN or chassis number, the engine number, the vehicle identification card and the driving licence number.

HOW IT IS FOUND

COLUMN NAME AR_L1_VEHICULO - Path

85% vin chasis n(o|ro|um|umero)?(chasis|motor|cuadro|serie|vin) motor_n(o|ro|um|umero) c[eé]dula?(verde|azul|(de_)?identificaci[oó]n?(de_l_)?automotor) t[ií]tulo?(de_l_)? automotor dnrpa registro?automotor licencia?(de_)?conducir(_?(n(o|ro|um|umero)))? carnet?(de_)?conducir

VALUE FORMAT AR_L1_VEHICULO - Regex

PATTERN	STRENGTH	NOTES
[A-HJ-NPR-Z0-9]{17}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
8AJFB8CD1K1234567	→	9IBKD9YL8Y3173278

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The property tax number (partida inmobiliaria), the cadastral nomenclature, the Real Estate Registry number and the municipal or revenue account. They lead to the home and the owner.

HOW IT IS FOUND

COLUMN NAME

AR_L1_INMUEBLE - Path

80%

```
partida_?(inmobiliaria|municipal|arba|abl|catastral)? n(o|ro|um|umero)?partida
nomenclatura_?catastral nomenclatura catastro circunscripci[ó]n parcela
matr[ií]cula_?(registral|inmueble|folio_?real) folio_?real n(o|ro|um|umero)?
(abl|inmobiliario|arba|rentas) cuenta_?(rentas|municipal|abl|inmobiliaria) padr[oó]n_?
(inmobiliario|municipal)
```

HOW IT IS MASKED

Character by character, keeping length and format.

AR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

123-456789

→

110-858568

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Contract, policy, operation, loan, member, subscriber and meter numbers, employee and student file numbers (legajo), and customer or affiliate codes.

HOW IT IS FOUND

COLUMN NAME

AR_L1_CONTRATO - Path

70%

```
n(o|ro|um|umero)?
(contrato|p[ó]liza|operaci[ó]n|cr[eé]dito|pr[eé]stamo|solicitud|afiliado|afiliaci[ó]n|socio
|suscriptor|cliente|medidor|servicio|suministro|legajo|expediente_?
(administrativo|interno)|beneficio|carnet) contrato_?(n(o|ro|um|umero)) legajo(_?
(personal|empleado|agente|alumno))? c[ó]digo_?(cliente|socio|afiliado|empleado|alumno)
id_?(cliente|socio|afiliado|empleado|agente|alumno) n(o|ro)?socio n(ro|umero)?libreta_?
universitaria
```

HOW IT IS MASKED

Character by character, keeping length and format. The mapping is deterministic, so joins keep working.

AR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

LEG-12345

MASKED

→ FIW-25839

8.26 User and social media

AR_L1_USUARIO

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Login, nickname and social media profiles.

HOW IT IS FOUND

COLUMN NAME

AR_L1_USUARIO - Path

70%

usuario user_?name username login apodo nick(_?name)? perfil_
(instagram|facebook|twitter|tiktok|linkedin|x) instagram facebook twitter tiktok
linkedin red_?social handle

HOW IT IS MASKED

Character by character, keeping length and format.

AR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

@sole_fernandez

MASKED

→ @tixi_zilwatfaj

8.27 Credentials

AR_L1_CREDENCIAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Passwords and their hashes, the tax password (clave fiscal), PIN, security and OTP codes, CVV, tokens, API keys and secret answers.

HOW IT IS FOUND

COLUMN NAME

AR_L1_CREDENCIAL - Path

90%

contrase[nñ]a clave *(except when followed by list E6)* clave_?fiscal password passwd pwd pass
hash_?(clave|contrasena|password) pin c[oó]digo_?(seguridad|verificaci[oó]n|acceso|otp)
cvv cvc token(_?(acceso|refresh|api))? access_?token refresh_?token api_?key secreto
secret otp pregunta_?secreta respuesta_?secreta

HOW IT IS MASKED

Every character becomes X. A credential has no use in a test copy, and a hash masked character by character could still be attacked.

AR_REDACTAR

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

Clave#2024

→ XXXXXXXXXX

8.28 Geolocation

AR_L1_GEOLOCALIZACION

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in separate columns, from apps, visits, addresses and deliveries.

HOW IT IS FOUND

COLUMN NAME

AR_L1_GEOLOCALIZACION - Path

85%

lat latitud lon lng longitud coordenadas? coord_{xy} geo_
(lat|lon|lng|loc|localizacion|posicion) georreferenciaci{oó}n geolocalizaci{oó}n gps(_?
(ubicaci{oó}n|posici{oó}n|coordenadas))? ubicaci{oó}n_?gps

50%

long

VALUE FORMAT

AR_L1_GEOLOCALIZACION - Regex

PATTERN

STRENGTH

NOTES

-(2[1-9]| [34]\d|5[0-5])\.\d{3,}\s*,\s*-(5[3-9]|6\d|7[0-3])\.\d{3,}

90%

-(2[1-9]| [34]\d|5[0-5]|6\d|7[0-3])\.\d{4,}

40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the other decimals are mapped: the place is generalized, not moved far.

AR_COORDENADA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

-34.603722,-58.381592

→ -34.681151,-58.386711

8.29 Free text

AR_L1_TEXT0_LIBRE

COLUMN NAME

DATA TYPE

VALUE FORMAT

FREE TEXT REDACTION

WHAT IT IS

Remarks, complaint descriptions, accounts of events and messages where anything gets written — DNI, CUIL, mobile and name included.

HOW IT IS FOUND

COLUMN NAME AR_L1_TEXT0_LIBRE – Path

60% observaci[oó]n(es)? obs comentarios? notas? anotaci[oó]n(es)? descripci[oó]n?
(reclamo|queja|solicitud|caso|hechos|novedad|atenci[oó]n|incidente) detalle_
(reclamo|solicitud|caso|atenci[oó]n) hechos relato justificaci[oó]n mensaje *(except when
preceded by list E7; except when followed by list E8)* texto(_?libre)? resumen?(caso|atenci[oó]n) queja
reclamo motivo?(reclamo|contacto|llamado) remarks? comments? notes? free_?text memo

DATA TYPE AR_L1_TEXT0_LIBRE – Type

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT AR_L1_TEXT0_LIBRE – Regex

PATTERN	STRENGTH	NOTES
\d{1,2}\.\d{3}\.\d{3}	60%	anywhere in the value
[\w.+\\-]+@[\\w\\-]+\\. [A-Za-z]{2,}	70%	anywhere in the value
(20 2[347] 3[034])-\d{8}-\d	70%	anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

Free Text Redaction: DNIs with dots, CUITs and CUILs, 7- or 8-digit numbers, CBU's, e-mail, mobiles, cards, plates and IPs become [DAT0] ; given names and surnames from the list become [NOMBRE] . The rest of the text stays.

AR_TEXT0_LIBRE **FREE TEXT REDACTION**

Replaces the text matching 10 patterns with [DAT0] , and the 2,670 terms of ar-texto-nombres.txt with [NOMBRE] .

EXAMPLES

VALUE	MASKED
Cliente Fernández, DNI 28.456.789, correo s.fernandez@hotmail.com, cel 1145678901.	→ Cliente [NOMBRE], DNI [DAT0], correo [DAT0], cel [DAT0].

Quasi-identifiers

Data that identifies nobody on its own, but does in combination. The 2022 census counts 2,280 gobiernos locales — municipios, comunas, comisiones de fomento and municipales —; 1,952 have fewer than 20,000 inhabitants and more than a thousand fewer than 2,000. A birth date, a sex and one of those towns point at a handful of people. These attributes are generalized or shifted rather than replaced, and the data keeps its analytical value.

9.1 Birth date

AR_L2_FECHA_NACIMIENTO

ESSENTIAL COLUMN NAME DATA TYPE DATE SHIFT

WHAT IT IS

The birth date, as a date, timestamp or text.

HOW IT IS FOUND

COLUMN NAME AR_L2_FECHA_NACIMIENTO – Path

90% (fecha|fec|fch|f)?(de_?)?nac(imiento)? fnac fechanac(imiento)? cumplea[nños]os dob
date_of_birth birth_date birthday

DATA TYPE AR_L2_FECHA_NACIMIENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 60 days either way. Ages and school years change for few people; the date stays plausible and the same birth shifts the same way in every table.

AR_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	1985-08-05T00:00

9.2 Birth year and clase

AR_L2_ANIO_NACIMIENTO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The birth year in a column of its own, also called *clase*.

HOW IT IS FOUND

COLUMN NAME AR_L2_ANIO_NACIMIENTO – Path

90% a[nñ]o?(de_?)?nac(imiento)? anio?nac(imiento)? year_of_birth birth_year yob
clase

DATA TYPE AR_L2_ANIO_NACIMIENTO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit is mapped: 1985 becomes a year from 1980 to 1989.

AR_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

AR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	1980

9.3

Age

AR_L2_EDAD

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Age in years, also age group or five-year band.

HOW IT IS FOUND

COLUMN NAME

AR_L2_EDAD – Path

85%

```
edad(_?(actual|a[ñ]os|anios|paciente|afiliado|cliente|al_?
(ingreso|diagn[ó]stico|fallecimiento)))? grupo_?etario rango_?(de_?)?edad quinquenio
age(_?(years|group))?
```

DATA TYPE

AR_L2_EDAD – Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The tens digit stays and the unit is mapped (37 becomes 30–39). A hundred or more becomes 90: rare ages identify.

AR_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	35
104	→	90

9.4

Personal event dates

AR_L2_FECHA_EVENTO

COLUMN NAME

DATA TYPE

DATE SHIFT

WHAT IT IS

Dates that say something about the person: death, marriage and civil union, hiring, leaving and dismissal, retirement, admission and discharge, diagnosis, childbirth, arrest, conviction, DNI issue, residence filing, leave.

HOW IT IS FOUND

COLUMN NAME AR_L2_FECHA_EVENTO – Path

80% (fecha|fec|fch|f)?(de_?)(defunci[oó]n|fallecimiento|muerte|matrimonio|uni[oó]n?
convivencial|divorcio|ingreso|egreso|alta|baja|retiro|contrataci[oó]n|desvinculaci[oó]n|despid
o|jubilaci[oó]n|internaci[oó]n|diagn[oó]stico|atenci[oó]n|consulta|parto|detenci[oó]n|condena|
emisi[oó]n(_?(dni|documento))?)|vencimiento_
dni|radicaci[oó]n|vacunaci[oó]n|cirug[ií]a|accidente|licencia) fec_
(emision|defuncion|ingreso|egreso|baja) date_of_(death|marriage|hire|admission|discharge)

DATA TYPE AR_L2_FECHA_EVENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 30 days either way.

AR_FECHA_EVENTO **DATE SHIFT**

Moves the date by -30 to 30 days.

EXAMPLES

VALUE

MASKED

2021-03-15

→ 2021-03-05T00:00

9.5

Sex

AR_L2_SEX0

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Sex as the system records it: F / M , Femenino / Masculino , Mujer / Varón or the codes 1 and 2. Since Decree 476/2021 the DNI also admits X .

HOW IT IS FOUND

COLUMN NAME AR_L2_SEX0 – Path

85% sexo(_?(biol[oó]gico|al_?nacer|registral|dni|paciente|afiliado|cliente))?
(tp|tipo|cod|cd|id)?sexo g[eé]nero (except when followed by *identidad* , *autopercibido*) sex gender
(except when followed by *identity*)

KNOWN VALUES AR_L2_SEX0 – List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-sexo.txt	12	50%	f, m, x, femenino, masculino, mujer

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary: F stays F or M , 1 stays 1 or 2 . An X becomes F or M : a few thousand people hold it, and the mark would identify them.

AR_SEX0 **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_SEX0_FEMENINO_MASCULINO **SECURE LOOKUP**

Replaces the value with one of the 2 values in ar-sexo-femenino-masculino.txt , chosen by a keyed hash.

AR_SEX0_MUJER_VARON **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-sexo-mujer-varon.txt` , chosen by a keyed hash.

AR_SEX0_FEMALE_MALE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-sexo-female-male.txt` , chosen by a keyed hash.

AR_SEX0_F_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-sexo-f-m.txt` , chosen by a keyed hash.

AR_SEX0_1_2 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-sexo-1-2.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	M
X	→	F
Varón	→	Mujer

9.6 Localidad and municipality

AR_L2_LOCALIDAD

COLUMN NAME

KNOWN VALUES

DATA CLEANSING

WHAT IT IS

The localidad, city or municipality of residence, birth or document issue, by name — alone or with the province, Tres Lagos – Santa Cruz , Tres Lagos (Santa Cruz) .

HOW IT IS FOUND

COLUMN NAME AR_L2_LOCALIDAD – Path

85% `localidad(_?(residencia|nacimiento|domicilio|paciente|cliente|origen|emisi[oón])?)` *(except when followed by `cod` , `codigo` , `id` , `indec`)* `loc(_?(res|nac|dom)?)` `municipio(_?(residencia|domicilio)?)` *(except when followed by `cod` , `codigo` , `id` , `indec`)* `ciudad(_?(residencia|nacimiento|domicilio|cliente|origen)?)` `(nom|nombre|desc)_?` `(localidad|municipio|ciudad)` `lugar_?(de_?)?nacimiento` `pueblo_?(residencia|natal)` `city` `town`

KNOWN VALUES AR_L2_LOCALIDAD – List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-localidades.txt	4,816	80%	Adolfo Alsina, Adolfo Gonzales Chaves, Alberti, Almirante Brown, Avellaneda, Ayacucho

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A localidad of a gobierno local with fewer than 20,000 inhabitants — or outside any gobierno local — becomes the nearest gobierno local of the same province with at least 20,000; the others stay. See *Where people live*.

AR_LOCALIDAD **DATA CLEANSING**

Replaces each value found in `ar-localidades-generalizadas.txt` (55,794 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
El Chaltén	→	El Calafate
Tres Lagos – Santa Cruz	→	El Calafate – Santa Cruz
Rosario	→	Rosario

9.7 Partido and departamento

AR_L2_DEPARTAMENTO

COLUMN NAME

KNOWN VALUES

DATA CLEANSING

WHAT IT IS

The partido of Buenos Aires province, the departamento of the other provinces or the comuna of the City of Buenos Aires, by name.

HOW IT IS FOUND

COLUMN NAME

AR_L2_DEPARTAMENTO – Path

85%

partido(_?(residencia|domicilio))? (except when followed by pol[ií]tico, afiliaci[oó]n, cod, codigo, id) departamento_(geogr[aá]fico|residencia|provincial|indec) (nom|nombre|desc)? (partido|departamento|depto|dpto)

50%

departamento (except when followed by n(o|ro|umero), piso, cod, codigo, id) depto dpto

KNOWN VALUES

AR_L2_DEPARTAMENTO – List

LIST

VALUES STRENGTH FIRST VALUES

ar-detectar-departamentos.txt	532	80%	Adolfo Alsina, Adolfo Gonzales Chaves, Alberti, Almirante Brown, Avellaneda, Ayacucho
-------------------------------	-----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A partido or departamento with fewer than 20,000 inhabitants becomes the nearest one of the same province with at least 20,000: Iruya becomes Orán. The larger ones stay.

AR_DEPARTAMENTO DATA CLEANSING

Replaces each value found in ar-departamentos-generalizados.txt (3,254 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Iruya	→	Orán
La Matanza	→	La Matanza

9.8 INDEC geographic codes

AR_L2_CODIGO_GEOGRAFICO

COLUMN NAME

VALUE FORMAT

DATA CLEANSING

WHAT IT IS

INDEC codes: five digits for a partido or departamento, six for a gobierno local and eight for a localidad censal. The first two are the province.

HOW IT IS FOUND

COLUMN NAME AR_L2_CODIGO_GEOGRAFICO - Path

85% (cod|codigo|cd|id)?(localidad|loc|municipio|gobierno?local|departamento|depto|dpto|partido)
(?(indec|censal|res|residencia|nac|nacimiento))? (cod|codigo)?indec indec?
(cod|codigo|localidad|departamento) codloc coddepto cod?gl localidad?censal?(id|cod)

VALUE FORMAT AR_L2_CODIGO_GEOGRAFICO - Regex

PATTERN	STRENGTH	NOTES
(0[26] 1[0480] 2[26] 3[0484] 4[26] 5[048] 6[26] 7[048] 8[26] 9[04])\d{3} (\d \d{3})?	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The same generalization as the names: a small place's code becomes the code of the place that replaces its name; a localidad's, the code of the main localidad of that gobierno local.

AR_CODIGO_GEOGRAFICO **DATA CLEANSING**

Replaces each value found in ar-codigos-geograficos-generalizados.txt (5,070 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE	MASKED
10014	→ 10112
785035	→ 780070

9.9 Postal code

AR_L2_CODIGO_POSTAL

COLUMN NAME **DATA TYPE** **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

The Código Postal Argentino — a letter for the province, four digits and three letters that narrow it to a block face, C1043AAZ — and the older four-digit code, which names a town.

HOW IT IS FOUND

COLUMN NAME AR_L2_CODIGO_POSTAL - Path

85% c[oó]digo?postal cod?postal codpostal cpa zip(_?code)? postal?code cp

DATA TYPE AR_L2_CODIGO_POSTAL - Type

Accepts text (length 4 to 8) or number (length up to 4); any other type rules the domain out.

VALUE FORMAT AR_L2_CODIGO_POSTAL - Regex

PATTERN	STRENGTH	NOTES
[A-HJ-NP-Z]\d{4}[A-Z]{3}	80%	
[A-HJ-NP-Z]?[1-9]\d{3}	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The letter and the first two digits stay, the other two become zeros and the final letters AAA : C1043AAZ becomes C1000AAA and 1636 becomes 1600 .

AR_CODIGO_POSTAL **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
C1043AAZ	→	C1000AAA
1636	→	1600

9.10 Neighbourhood

AR_L2_BARRIO

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The neighbourhood, the gated community or country club, the informal settlement registered in RENABAP and the rural paraje.

HOW IT IS FOUND

COLUMN NAME

AR_L2_BARRIO – Path

80%

barrio(_?(residencia|domicilio|cliente|cerrado|privado))? (nom|nombre)?barrio country
club_de_campo villa_(de_)?emergencia asentamiento(_?informal)? renabap neighbou?
rhood paraje

HOW IT IS MASKED

Replaced by a common Argentine neighbourhood name, unrelated to the original.

AR_BARRIO

SECURE LOOKUP

Replaces the value with one of the 124 values in `ar-barrios.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Barrio Parque Los Andes	→	Barracas

9.11 Nationality

AR_L2_NACIONALIDAD

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Nationality or country of birth. Paraguayans and Bolivians are the largest foreign communities.

HOW IT IS FOUND

COLUMN NAME

AR_L2_NACIONALIDAD – Path

80%

nacionalidad pa[ií]s_(de_)?(nacimiento|origen|nacionalidad) ciudadan[ií]a nationality
citizenship country_of_birth

KNOWN VALUES

AR_L2_NACIONALIDAD – List

LIST

VALUES

STRENGTH

FIRST VALUES

ar-detectar-nacionalidades.txt	45	70%	Argentina, Paraguaya, Boliviana, Venezolana, Peruana, Chilena
--------------------------------	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a nationality from the list: Argentine and the largest foreign communities.

AR_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 14 values in `ar-nacionalidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

Senegalesa

→

MASKED

China

9.12 Marital status

AR_L2_ESTADO_CIVIL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Single, married, civil union — from the 2015 Civil and Commercial Code —, separated, divorced or widowed, in words or as a code.

HOW IT IS FOUND

COLUMN NAME

AR_L2_ESTADO_CIVIL - Path

85%

`estado_?civil` `est_?civil` `(cod|tipo|id)_?estado_?civil` `situaci[06]n_?conyugal` `marital_?`
`status` `civil_?status`

KNOWN VALUES

AR_L2_ESTADO_CIVIL - List

LIST

VALUES

STRENGTH

FIRST VALUES

<code>ar-detectar-estado-</code> <code>civil.txt</code>	21	70%	Soltero/a, Casado/a, Unión convivencial, Union convivencial, Separado/a de hecho, Divorciado/a
--	----	-----	--

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another status from the list; a code stays a code.

AR_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`AR_ESTADO_CIVIL_LISTA`.

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

AR_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in `ar-estado-civil-codigos.txt`, chosen by a keyed hash.

AR_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `ar-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Concubinato

→

Unión convivencial

9.13 Occupation

AR_L2_OCUPACION

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Occupation, profession, trade or position, in words or by the code of INDEC's National Classification of Occupations. A rare occupation in a small town identifies.

HOW IT IS FOUND

COLUMN NAME

AR_L2_OCUPACION - Path

80%

ocupaci[oó]n profesi[oó]n oficio cno (cod|codigo)?(ocupacion|cno|profesion) puesto_?
(de_)?trabajo categor[ií]a?laboral cargo?(actual|empleado|agente) occupation
profession job_title

50%

cargo puesto

HOW IT IS MASKED

Text is replaced by a common occupation; a code is mapped digit by digit.

AR_OCUPACION_0_CODIGO

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_OCUPACION .

AR_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

AR_OCUPACION

SECURE LOOKUP

Replaces the value with one of the 35 values in ar-ocupaciones.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Gerente regional de operaciones

→

Electricista

9.14 Employer

AR_L2_EMPLEADOR

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The name of the company or public body where the person works.

HOW IT IS FOUND

COLUMN NAME

AR_L2_EMPLEADOR - Path

90%

empleador(_?(nombre|raz[oó]n?social|cuit))? (nombre|nom)?(empleador|empresa?donde_?
trabaja) empresa?(donde_)?(trabaja|labora) lugar?(de_)?trabajo patr[oó]n employer(_?
name)? workplace

HOW IT IS MASKED

Replaced by a fictitious company.

AR_EMPLEADOR

SECURE LOOKUP

Replaces the value with one of the 24 values in `ar-empleadores.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Mercado Libre S.R.L.	→ Autopartes del Oeste S.R.L.

9.15 Education

AR_L2_NIVEL_EDUCATIVO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The highest level attained — from no schooling to postgraduate, complete or incomplete —, in words or as a code.

HOW IT IS FOUND

COLUMN NAME

AR_L2_NIVEL_EDUCATIVO - Path

80%

nivel_?(educativo|de_?instrucci[oó]n|de_?estudios|acad[eé]mico|alcanzado) m[aá]ximo_?nivel(_?educativo)? estudios_?(alcanzados|cursados) instrucci[oó]n escolaridadeducation(_?level)?

KNOWN VALUES

AR_L2_NIVEL_EDUCATIVO - List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-nivel-educativo.txt	21	60%	Sin instrucción, Sin instruccion, Primario incompleto, Primario completo, Secundario incompleto, Secundario completo

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another level from the list; a code stays a code.

AR_NIVEL_EDUCATIVO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_NIVEL_EDUCATIVO_LISTA .

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt` , chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.

AR_NIVEL_EDUCATIVO_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in `ar-nivel-educativo-codigos.txt` , chosen by a keyed hash.

AR_NIVEL_EDUCATIVO_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `ar-nivel-educativo.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Doctorado

→

Universitario completo

9.16 School

AR_L2_ESTABLECIMIENTO_EDUCATIVO

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The school, college, institute or university, by name or by its Clave Única de Establecimiento (CUE).

HOW IT IS FOUND

COLUMN NAME

AR_L2_ESTABLECIMIENTO_EDUCATIVO - Path

75%

escuela(_?(nombre|egreso))? colegio(_?(nombre|egreso))? (nombre|nom)?
(escuela|colegio|establecimiento_?educativo|universidad|instituto) establecimiento_?
educativo instituci[oó]n_?educativa universidad cue(_?anexo)? school(_?name)?
university

HOW IT IS MASKED

Replaced by a fictitious school.

AR_ESTABLECIMIENTO_EDUCATIVO **SECURE LOOKUP**

Replaces the value with one of the 12 values in `ar-establecimientos-educativos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Colegio Nacional de Buenos Aires

→

Instituto Superior de Formación Docente N° 21

9.17 Children and dependants

AR_L2_PERSONAS_A_CARGO

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Number of children, dependants or household members.

HOW IT IS FOUND

COLUMN NAME

AR_L2_PERSONAS_A_CARGO - Path

80%

personas_?a_?cargo familiares_?a_?cargo n(o|ro|um|umero)?(de_)?
(hijos|dependientes|personas_?a_?cargo) cant(idad)?(hijos|dependientes|personas_?
hogar|convivientes) hijos cargas_?de_?familia dependientes personas?(en_?el_)?hogar
tama[nñ]o_?hogar number_?of_?children dependents

DATA TYPE

AR_L2_PERSONAS_A_CARGO - Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Values from 0 to 5 stay; above 5 they become 5. Very large families are rare, and a rare count identifies.

AR_CONTEO_LIMITADO **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	5

Sensitive data

The categories of article 2 other than health — which has its own group: racial and ethnic origin, political opinions, religious, philosophical or moral convictions, trade union membership and sexual life. The set adds the special categories of Convention 108+ — genetic and biometric data —, sexual orientation, **gender identity**, whose registry correction is confidential (Law 26.743, art. 9), and being a **victim** of gender violence (Law 26.485), trafficking (Law 26.364) or sexual crimes, whose identity the law orders protected. Categorical columns keep their shape: a Y/N flag stays a flag, a code is replaced by another code and any other value by one from the list of its category. Where the values share no vocabulary, they are suppressed to Sin información.

10.1 Ethnic origin

AR_L3_ORIGEN_ETNICO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Self-recognition as indigenous or descendant of indigenous peoples and as Afro-descendant, the two questions of the 2022 census, in words, as a code or as a flag.

HOW IT IS FOUND

COLUMN NAME

AR_L3_ORIGEN_ETNICO - Path

95%

etnia origen_?([eé]tnico|racial) grupo_?[eé]tnico pertenencia_?[eé]tnica
autorreconocimiento(_?[eé]tnico)? auto_?reconocimiento (cod|codigo|tipo|id)_?
(etnia|origen_?etnico) raza afrodescendiente afroargentin[oa] ind[ií]gena originario
ethnicity race

KNOWN VALUES

AR_L3_ORIGEN_ETNICO - List

LIST

VALUES

STRENGTH

FIRST VALUES

ar-detectar-
origen-
etnico.txt

18

90%

Indígena o descendiente de pueblos indígenas u originarios, Indígena o descendiente de pueblos indígenas u originarios, Afrodescendiente, Ninguno, Prefiere no responder, indígena

ar-detectar-
codigos-
banderas.txt

11

30%

s, n, sí, si, no, 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a category from the list.

AR_ORIGEN_ETNICO

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_ORIGEN_ETNICO_LISTA.

AR_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-si-no.txt, chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-true-false.txt, chosen by a keyed hash.

AR_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt, chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

AR_ORIGEN_ETNICO_LISTA **SECURE LOOKUP**

Replaces the value with one of the 4 values in `ar-origen-etnico.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Afroargentino	→	Ninguno
S	→	S

10.2 Indigenous people

AR_L3_PUEBLO_INDIGENA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The indigenous people — Mapuche, Guaraní, Diaguita, Kolla, Qom, Wichí, among the dozens recorded by the 2022 census — and the community with legal personality registered in RENACI.

HOW IT IS FOUND

COLUMN NAME AR_L3_PUEBLO_INDIGENA - Path

90% `pueblo(_?(ind[ií]gena|originario))?` `(cod|codigo|nombre|nom)?pueblo` `comunidad_?`
`(ind[ií]gena|originaria|aborigen)` `personer[ií]a_?jur[ií]dica_?(comunidad|ind[ií]gena)`
`renaci` `inai` `aborigen` `indigenous_?people`

KNOWN VALUES AR_L3_PUEBLO_INDIGENA - List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-pueblos-indigenas.txt	93	90%	Mapuche, Guaraní, Guarani, Diaguita, Kolla, Qom

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by one of the most numerous peoples; a code stays a code.

AR_PUEBLO_INDIGENA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_PUEBLO_INDIGENA_LISTA

AR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

AR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

AR_PUEBLO_INDIGENA_LISTA **SECURE LOOKUP**

Replaces the value with one of the 20 values in `ar-pueblos-indigenas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Selk'nam

→

Tonokoté

10.3 Indigenous language

AR_L3 LENGUA_INDIGENA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The indigenous language the person speaks or understands — Guaraní, Quechua, Mapuzungun, Qom, Wichí. It reveals the people of origin.

HOW IT IS FOUND

COLUMN NAME

AR_L3 LENGUA_INDIGENA - Path

90%

`lengua_?(ind[ií]gena|originaria|materna|nativa)` `idioma_?`

`(ind[ií]gena|originario|materno|nativo)` `habla_?(lengua|idioma)_?(ind[ií]gena|originari[oa])`

`mother_?tongue` `native_?language`

KNOWN VALUES

AR_L3 LENGUA_INDIGENA - List

LIST

VALUES

STRENGTH

FIRST VALUES

`ar-detectar-lenguas.txt`

37

80%

Español, Espanol, Guaraní, Guarani, Quechua, Mapuzungun

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a language from the list; a flag stays a flag.

AR_LENGUA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_LENGUA_LISTA`.

AR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

AR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

AR LENGUA_LISTA **SECURE LOOKUP**

Replaces the value with one of the 12 values in `ar-lenguas.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Tapiete

→ **Pilagá**

10.4 Religion

AR_L3_RELIGION

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The religion, church or faith the person belongs to.

HOW IT IS FOUND

COLUMN NAME

AR_L3_RELIGION - Path

95%

religi[oó]n creencia_?religiosa convicci[oó]n_?religiosa credo confesi[oó]n_?religiosa
culto iglesia(_?(a_?la_?que_?pertenece|nombre))? denominaci[oó]n_?religiosa
(cod|codigo|tipo)_?religion religion church

KNOWN VALUES

AR_L3_RELIGION - List

LIST

VALUES

STRENGTH

FIRST VALUES

ar-detectar-
religiones.txt

41

90%

Católica, Catolica, Evangélica, Evangelica, Pentecostal, Testigo de
Jehová

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a religion from the list.

AR_RELIGION **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_RELIGION_LISTA .

AR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.

AR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt` , chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

AR_RELIGION_LISTA **SECURE LOOKUP**

Replaces the value with one of the 11 values in `ar-religiones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

Ortodoxa

MASKED

→ **Pentecostal**

10.5 Philosophical or moral convictions

AR_L3_CONVICCION_FILOSOFICA

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

The philosophical or moral convictions that article 2 names apart from religious ones: conscientious objection — invoked, for instance, against terminating a pregnancy or a transfusion — and membership of lodges.

HOW IT IS FOUND

COLUMN NAME

AR_L3_CONVICCION_FILOSOFICA - Path

90%

```
convicci[oó]n(es)?_?(filos[oó]ficas?|morales?|personales?)  creencias?_?(filos[oó]ficas?
|morales?|personales?)  objeci[oó]n?(de_)?conciencia  objetor?(de_)?conciencia
masoner[ií]a  logia  beliefs?  philosophical?beliefs?
```

HOW IT IS MASKED

The values share no vocabulary: they are suppressed to `Sin información`. Flags and codes keep their shape.

AR_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR`.

AR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

AR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

AR_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `ar-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Se niega a transfusiones

→ Sin información

10.6 Political opinions

AR_L3_OPINION_POLITICA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Political orientation and ideology, sympathy and voting intention, from surveys and records.

HOW IT IS FOUND

COLUMN NAME

AR_L3_OPINION_POLITICA - Path

90%

opini[oó]n_?pol[ií]tica orientaci[oó]n_?pol[ií]tica tendencia_?pol[ií]tica
ideolog[ií]a(_?pol[ií]tica)? preferencia_?(pol[ií]tica|partidaria|electoral)
intenci[oó]n_?(de_)?voto simpat[ií]a_?pol[ií]tica political_?(opinion|orientation|view)
voting_?intention

KNOWN VALUES

AR_L3_OPINION_POLITICA - List

LIST

VALUES

STRENGTH

FIRST VALUES

ar-detectar-opiniones-politicas.txt	22	70%	Izquierda, Centroizquierda, Centro, Centroderecha, Derecha, Independiente
-------------------------------------	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a position from the list — left to right, independent.

AR_OPINION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_OPINION_POLITICA_LISTA .

AR_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-si-no.txt , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-true-false.txt , chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt , chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-s-n.txt , chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-y-n.txt , chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.

AR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_OPINION_POLITICA_LISTA

SECURE LOOKUP

Replaces the value with one of the 7 values in ar-opiniones-politicas.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Libertario

→ Centro

10.7 Party membership

AR_L3_AFILIACION_PARTIDARIA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The political party the person is a member or activist of. A column named just `PARTIDO` may also be the partido of a Buenos Aires address: the values decide.

HOW IT IS FOUND

COLUMN NAME

AR_L3_AFILIACION_PARTIDARIA - Path

95%

partido_?pol[ií]tico(_?(afiliaci[oó]n|nombre))? afiliaci[oó]n_
(pol[ií]tica|partidaria|partido) afiliado_?partido militancia(_?pol[ií]tica)? militante
(cod|codigo|nombre|nom)_?partido_?pol agrupaci[oó]n_?pol[ií]tica fuerza_?pol[ií]tica
political_?party party_?membership

50%

partido

KNOWN VALUES

AR_L3_AFILIACION_PARTIDARIA - List

LIST

VALUES

STRENGTH

FIRST VALUES

ar-detectar-
partidos-
politicos.txt

54

80%

Partido Justicialista, Unión Cívica Radical, Union Civica Radical, Propuesta
Republicana (PRO), La Libertad Avanza, Coalición Cívica ARI

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another party from the list of national parties; a flag stays a flag.

AR_PARTIDO_POLITICO

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_PARTIDO_POLITICO_LISTA .

AR_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.

AR_BANDERA_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt` , chosen by a keyed hash.

AR_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.

AR_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

AR_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.

AR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_PARTIDO_POLITICO_LISTA **SECURE LOOKUP**

Replaces the value with one of the 29 values in `ar-partidos-politicos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

Movimiento Popular Neuquino

→

MASKED

Izquierda Socialista

10.8 Trade union membership

AR_L3_AFILIACION_SINDICAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The union, membership, the union dues deducted on the payslip, the union delegate and union protection — UOM, Comercio, UOCRA, Camioneros, ATE, UPCN.

HOW IT IS FOUND

COLUMN NAME AR_L3_AFILIACION_SINDICAL - Path

95%

```
sindicato(_?(nombre|afiliado|afiliaci[oó]n|codigo))? gremio(_?(nombre|afiliado|codigo))?
sindicalizado afiliado_?(sindicato|gremio) afiliaci[oó]n_?(sindical|gremial) cuota_?
(sindical|gremial) aporte_?(sindical|gremial) descuento_?(sindical|gremial)
asociaci[oó]n_?sindical delegado_?(gremial|sindical) comisi[oó]n_?interna tutela_?
sindical convenio_?colectivo_?(de_?trabajo)? cct trade_?union union_?member(ship)?
```

KNOWN VALUES AR_L3_AFILIACION_SINDICAL - List

LIST

VALUES

STRENGTH

FIRST VALUES

ar-detectar-sindicatos.txt

37

60%

CGT, CTA, CTA-T, CTA-A, UOM, UOCRA

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información.

AR_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_SUPRIMIR.

AR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

AR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

AR_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `ar-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
UOM	→	Sin información
S	→	S

10.9 Biometric data

AR_L3_BIOMETRICO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

Fingerprint and face templates — validation against RENAPER is routine in banks and digital wallets —, iris, voice and digitized signature.

HOW IT IS FOUND

COLUMN NAME AR_L3_BIOMETRICO - Path

90% `biometr[ií]a[a-z]* biom[eé]trico[a-z]* huella(?:dactilar)?(?:
(template|plantilla|imagen|hash))? huellas dactilar template?(facial|huella|biometrico)
plantilla?(facial|biom[eé]trica) rostro?(hash|template) reconocimiento?facial
validaci[oó]n?(facial|biom[eé]trica|renaper) firma?
(biom[eé]trica|digitalizada|ol[oó]grafa) iris voz?(biom[eé]trica|template)
fingerprints? face?(template|hash|encoding) biometric[a-z]*`

DATA TYPE AR_L3_BIOMETRICO - Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character becomes `X`. A masked template authenticates nobody.

AR_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	XXXXXXXXXXXX

10.10 Genetic data

AR_L3_GENETICO

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Results of genetic, DNA and parentage tests, genetic profiles, mutations, karyotype and newborn screening. Convention 108+ counts them among the special categories.

HOW IT IS FOUND

COLUMN NAME

AR_L3_GENETICO – Path

90%

adn dna gen[eé]tic[oa]s? datos?_?gen[eé]ticos? genoma genotip[a-z]* prueba_?
(gen[eé]tica|de_?adn|de_?filiaci[oó]n|de_?paternidad) perfil_?gen[eé]tico mutaci[oó]n
brca[12]? cariotipo pesquisa_?neonatal bndg genetic[a-z]*

HOW IT IS MASKED

Every character becomes X .

AR_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE	MASKED
BRCA1 positivo	→ XXXXXXXXXXXXX

10.11 Sexual orientation

AR_L3_ORIENTACION_SEXUAL

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Self-declared sexual orientation, in health and diversity records. It is information about sexual life.

HOW IT IS FOUND

COLUMN NAME

AR_L3_ORIENTACION_SEXUAL – Path

95%

orientaci[oó]n_?sexual orient_?sexual (cod|codigo|tipo)_?orientacion_?sexual
preferencia_?sexual sexual_?orientation

KNOWN VALUES

AR_L3_ORIENTACION_SEXUAL – List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-orientaciones-sexuales.txt	14	80%	Heterosexual, Gay, Lesbiana, Bisexual, Pansexual, Asexual

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a category from the list.

AR_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_ORIENTACION_SEXUAL_LISTA .

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-si-no.txt , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-true-false.txt , chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt , chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-s-n.txt , chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

AR_ORIENTACION_SEXUAL_LISTA **SECURE LOOKUP**

Replaces the value with one of the 8 values in `ar-orientaciones-sexuales.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Homosexual

→

Pansexual

10.12 Sexual life

AR_L3_VIDA_SEXUAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Sexual activity and behaviour, number of partners, age at first intercourse.

HOW IT IS FOUND

COLUMN NAME

AR_L3_VIDA_SEXUAL - Path

90%

vida_?sexual actividad_?sexual conducta_?sexual pr[aá]cticas_?sexuales? parejas_?sexuales? n(o|ro|um|umero)_?parejas sexualmente_?activ[oa] inicio_?(de_)?(las_)? relaciones_?sexuales relaciones_?sexuales sex(ual)?_?life sexual_?(activity|behavio(u)?r|partners)

HOW IT IS MASKED

A flag stays a flag; any other value becomes `Sin información` .

AR_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR` .

AR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.

AR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt` , chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

AR_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `ar-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

Activa

MASKED

→ Sin información

10.13 Gender identity

AR_L3_IDENTIDAD_GENERO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Self-perceived gender identity, the registry correction and the change of registered sex under Law 26.743, which forbids publicizing the correction and the original birth record without the person's authorization (art. 9). The self-perceived name falls under the given name domain.

HOW IT IS FOUND

COLUMN NAME

AR_L3_IDENTIDAD_GENERO - Path

95%

```
identidad_(de_)?g[eé]nero (cod|codigo|tipo)_?identidad_genero g[eé]nero_?
(autopercibido|identitario) rectificaci[ó]n_registral cambio_(de_)?(g[eé]nero|sexo_?
registral) ley_26743 transg[eé]nero persona_trans travesti pronombres? gender_?
identity
```

KNOWN VALUES

AR_L3_IDENTIDAD_GENERO - List

LIST

VALUES STRENGTH FIRST VALUES

ar-detectar- identidades- genero.txt	24	70%	Mujer cis, Varón cis, Varon cis, Mujer trans / travesti, Varón trans / masculinidad trans, Varon trans / masculinidad trans
--	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a category from the list.

AR_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_IDENTIDAD_GENERO_LISTA .

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt` , chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_IDENTIDAD_GENERO_LISTA **SECURE LOOKUP**

Replaces the value with one of the 7 values in `ar-identidades-genero.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Transgénero	→ Varón trans / masculinidad trans

10.14

Victims of violence

AR_L3_VICTIMA

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

Being a victim of gender, family or sexual violence, of trafficking or exploitation, the type of violence, protection and restraining orders, the panic button, and the identity restitution of children of the disappeared. Revealing it exposes the person to their aggressor.

HOW IT IS FOUND

COLUMN NAME AR_L3_VICTIMA – Path

90% `v[ií]ctima(_?(de_)?(violencia(_?(de_)?g[eé]nero|_?familiar|_?dom[eé]stica)?|trata|abuso(_?sexual)?|delito(_?sexual)?|explotaci[oó]n))? violencia_?(de_)?g[eé]nero violencia_(familiar|dom[eé]stica|sexual) tipo_?(de_)?violencia medida_?(de_)?(protecci[oó]n|restricci[oó]n|exclusi[oó]n) perimetral restricci[oó]n_?(de_)?acercamiento bot[oó]n_?antip[aá]nico linea_?144 trata(_?(de_)?personas)? restituci[oó]n_?(de_)?identidad conadi hij[oa]_?(de_)?desaparecid[oa]s?`

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información .

AR_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: **AR_SUPRIMIR** .

AR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.

AR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt` , chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

AR_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `ar-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Violencia física y psicológica

→

Sin información

S

→

S

Health data

Information about health is sensitive (art. 2), and the medical record is confidential (Law 26.529 on Patients' Rights). Several laws add their own secrecy: the law on HIV, viral hepatitis, tuberculosis and STIs (Law 27.675), the law on voluntary termination of pregnancy (Law 27.610) and the mental health law (Law 26.657). The group covers what clinics, obras sociales, prepaid plans, laboratories, occupational risk insurers (ART) and occupational medicine keep.

11.1 Health identifiers

AR_SALUD_IDENTIFICADOR

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Medical record numbers, affiliate numbers of the obra social, prepaid plan or PAMI, membership card, admission, authorization, order and prescription numbers.

HOW IT IS FOUND

COLUMN NAME	AR_SALUD_IDENTIFICADOR – Path
85%	<code>n(o ro um umero)?(historia?(cl[ií]nica)? hc afiliado?(obra?social os pami prepaga)? beneficio? pami credencial internaci[oó]n autorizaci[oó]n orden receta prescripci[oó]n) historia?cl[ií]nica hc?(n(o ro um umero))? afiliado?(obra?social os pami prepaga) n(ro umero)?(os pami) credencial?(obra?social prepaga pami) c[oó]digo? (paciente afiliado) id?paciente hce</code>
55%	<code>afiliado internaci[oó]n autorizaci[oó]n episodio</code>

HOW IT IS MASKED

Character by character, keeping length and format.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
15012345678/00	→ 11560473467/18

11.2 Obra social and prepaid plan

AR_SALUD_COBERTURA

COLUMN NAME VALUE FORMAT KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The obra social, the prepaid plan, PAMI or Incluir Salud, by name or by the code of the National Register of Obras Sociales (RNOS). Most obras sociales are run by unions: the code tells the trade and the union. Incluir Salud covers people who receive a non-contributory pension.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_COBERTURA - Path

85% obra_?social(_?(nombre|codigo|afiliado))? os (cod|codigo|nombre|nom)?(obra_?social|os|prepaga|rnos) rnos prepaga medicina_?prepaga cobertura(_?(m[eé]dica|de_?salud|social))? financiador plan_(de_)?salud pami incluir_?salud profe

VALUE FORMAT AR_SALUD_COBERTURA - Regex

PATTERN	STRENGTH	NOTES
\d-\d{4}-\d		70%

A value that matches none does not count against the domain.

KNOWN VALUES AR_SALUD_COBERTURA - List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-cobertura.txt	42	80%	PAMI, IOMA, OSDE, Swiss Medical, Galeno, Medifé

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A name is replaced by another coverage from the list; an RNOS code is mapped digit by digit; a flag stays a flag.

AR_COBERTURA_SALUD **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_OBRA_SOCIAL .

AR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in ar-bandera-si-no.txt , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in ar-bandera-true-false.txt , chosen by a keyed hash.

AR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt , chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in ar-bandera-s-n.txt , chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in ar-bandera-y-n.txt , chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.

AR_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

AR_OBRA_SOCIAL **SECURE LOOKUP**

Replaces the value with one of the 19 values in ar-obras-sociales.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
OSUOMRA	→	I0SFA
1-0020-4	→	7-9242-5

11.3 Diagnosis and ICD-10

AR_SALUD_DIAGNOSTICO

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

Diagnoses in words or by ICD-10 code, with a dot (F33.1) or without (F331); causes of death, of leave and of admission, history and allergies.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_DIAGNOSTICO - Path

85% `diagn[oó]stico[a-z_]* dx(?:principal|secundario|ingreso|egreso)[0-9]? cie_?10 cie(?:10|11|principal)? (cod|codigo)?(diagnostico|dx|cie) impresi[oó]n?diagn[oó]stica enfermedad(es)?[a-z_]* patolog[ií]a comorbilidad(es)? antecedentes?_? (m[eé]dicos|patol[oó]gicos|familiares|personales|cl[ií]nicos) causa?(de_)? (muerte|defunci[oó]n|licencia|internaci[oó]n|consulta) motivo?(de_)? (consulta|licencia|internaci[oó]n) alergias? diagnos(is|es) icd_?(10|11)?`

VALUE FORMAT AR_SALUD_DIAGNOSTICO - Regex

PATTERN	STRENGTH	NOTES
<code>[A-TV-Za-tv-z]\d{2}(\.\d{1,2} \d X)?</code>		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code becomes another common code in the same format, and text a common diagnosis: an HIV or mental disorder diagnosis does not survive as a category.

AR_DIAGNOSTICO **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

AR_DIAGNOSTICO_TEXTO .

AR_CIE10_DECIMAL **SECURE LOOKUP**

Replaces the value with one of the 33 values in `ar-cie10-decimal.txt` , chosen by a keyed hash.

AR_CIE10 **SECURE LOOKUP**

Replaces the value with one of the 37 values in `ar-cie10.txt` , chosen by a keyed hash.

AR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.

AR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt` , chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt` , chosen by a keyed hash.

AR_DIAGNOSTICO_TEXTO **SECURE LOOKUP**

Replaces the value with one of the 30 values in `ar-diagnosticos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F33.1	→	K21.9
B24X	→	R51

11.4 Procedures and services

AR_SALUD_PROCEDIMIENTO

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Procedures, tests and surgeries, in words or by the code of the National or a provincial nomenclator. A viral load or a pregnancy termination reveals the diagnosis.

HOW IT IS FOUND

COLUMN NAME

AR_SALUD_PROCEDIMIENTO - Path

85%

```

nomenclador (cod|codigo)?(nomenclador|prestaci[oó]n|pr[aá]ctica|procedimiento)
procedimiento(_?(m[eé]dico|quir[uú]rgico|realizado|autorizado))? pr[aá]ctica(_?
(m[eé]dica|realizada|autorizada))? prestaci[oó]n?(m[eé]dica|realizada|autorizada)
estudio?(solicitado|realizado) cirug[ií]a(_?realizada)? intervenci[oó]n?quir[uú]rgica
medical?procedure

```

HOW IT IS MASKED

A code is mapped digit by digit; text is replaced by a common procedure.

AR_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches:

AR_PROCEDIMIENTO_TEXTO .

AR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

AR_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in ar-procedimientos.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
420101	→	349877

11.5 Medicines

AR_SALUD_MEDICAMENTO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Prescribed or dispensed medicines, by brand, active ingredient or pack code (troquel). An antiretroviral, an antipsychotic or misoprostol reveals a diagnosis.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_MEDICAMENTO - Path

85% medicamentos?(_(recetado|prescrito|dispensado|nombre|uso))? f[aá]rmas? droga(_?(gen[eé]rica|principal))? monodroga principio_?activo troquel gtin (cod|codigo)? (medicamento|troquel|alfabeta|kairos) receta(_?(m[eé]dica|electr[oó]nica|archivada))? prescripci[oó]n?(medicamento)? posolog[ií]a tratamiento_?farmacol[oó]gico medications? drugs?_?prescribed

KNOWN VALUES AR_SALUD_MEDICAMENTO - List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-medicamentos.txt	55	70%	Paracetamol, Ibuprofeno, Diclofenac, Dipirona, Metformina, Glibenclamida

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a common medicine from the list; a flag stays a flag.

AR_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_MEDICAMENTO_LISTA .

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-si-no.txt , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-true-false.txt , chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt , chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-s-n.txt , chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-y-n.txt , chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 24 values in ar-medicamentos.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Sertralina 50 mg	→ Ibuprofeno

11.6 Clinical text

AR_SALUD_TEXTO_CLINICO

COLUMN NAME DATA TYPE FREE TEXT REDACTION

WHAT IT IS

History, present illness, progress notes, physical examination, orders, discharge summaries and reports.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_TEXTO_CLINICO – Path

85% anamnesis evoluci[oó]n(_?(m[eé]dica|cl[ií]nica|enfermer[ií]a))? enfermedad_?actual
examen_?f[ií]sico plan_?(de_)?(tratamiento|manejo) indicaciones_?m[eé]dicas conducta(_?
m[eé]dica)? epicrisis resumen_?(de_)?(alta|internaci[oó]n|atenci[oó]n) nota_?
(m[eé]dica|de_?enfermer[ií]a|cl[ií]nica) notas_?(m[eé]dicas|cl[ií]nicas) triage(_?texto)?
informe_?(anatomopatol[oó]gico|patolog[ií]a|radiol[oó]gico|m[eé]dico) clinical_?notes?
discharge_?summary

DATA TYPE AR_SALUD_TEXTO_CLINICO – Type

Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

The same Free Text Redaction as free text: documents, contacts and names from the list are redacted. The clinical content stays — if it must not be in the copy, suppress the column.

AR_TEXTO_LIBRE **FREE TEXT REDACTION**

Replaces the text matching 10 patterns with [DATO] , and the 2,670 terms of ar-texto-nombres.txt with [NOMBRE] .

EXAMPLES

VALUE

Paciente Fernández, DNI 28.456.789, consulta por cefalea.

MASKED

→ Paciente [NOMBRE], DNI [DATO], consulta por cefalea.

11.7 Test results

AR_SALUD_RESULTADO_ESTUDIO

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Laboratory and test results — glucose, Pap smear, pregnancy, toxicology, blood alcohol —, also as numeric values.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_RESULTADO_ESTUDIO – Path

80% resultado_?(del_)?
(estudio|an[aá]lisis|laboratorio|pcr|serolog[ií]a|biopsia|glucemia|papanicolaou|pap|hisopado|c
ovid) (estudio|an[aá]lisis)_?(resultado|laboratorio) glucemia hemoglobina_?glicosilada
hba1c colesterol imc presi[oó]n_?arterial tensi[oó]n_?arterial test_?(de_)?embarazo
toxicol[oó]gico alcoholemia test_?(de_)?drogas lab_?results? test_?results?
50% resultado

HOW IT IS MASKED

Character by character, keeping the format: a number stays a number.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

Alterado

→

Urjecipi

11.8 HIV, hepatitis, tuberculosis and STIs

AR_SALUD_VIH

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Serological status, viral load and antiretroviral treatment, viral hepatitis, tuberculosis and sexually transmitted infections. Law 27.675 guarantees confidentiality and forbids discrimination on these grounds.

HOW IT IS FOUND

COLUMN NAME

AR_SALUD_VIH - Path

90%

```
vih(?:estado|resultado|test|diagn[ó]stico|positivo))? hiv sida aids serolog[ií]a_?
(vih|hiv) estado?serol[ó]gico carga?viral cd4 tarv antirretroviral(es)? hepatitis_?
(b|c|viral) hbsag tuberculosis tbc its ets infecci[ó]n(es)?_(de_)?transmisi[ó]n_?
sexual s[ií]filis vdrl
```

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información .

AR_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_SUPRIMIR .

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-si-no.txt , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-true-false.txt , chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt , chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-s-n.txt , chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-y-n.txt , chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in ar-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Reactivo

→

Sin información

S

→

S

11.9 Blood group

AR_SALUD_GRUPO_SANGUINEO

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Blood group and Rh factor.

HOW IT IS FOUND

COLUMN NAME

AR_SALUD_GRUPO_SANGUINEO - Path

90%

grupo_?sangu[ií]neo grupo_?y_?factor tipo_?(de_)?sangre rh factor_?rh gs_?rh grupo_?rh abo(_?rh)? blood_?(type|group)

KNOWN VALUES

AR_SALUD_GRUPO_SANGUINEO - List

LIST

VALUES

STRENGTH

FIRST VALUES

ar-detectar-grupos-sanguineos.txt

20

90%

A+, A-, B+, B-, AB+, AB-

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another group from the list.

AR_GRUPO_SANGUINEO

SECURE LOOKUP

Replaces the value with one of the 8 values in `ar-grupos-sanguineos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

0+

→

A-

11.10 Disability and CUD

AR_SALUD_DISCAPACIDAD

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Disability status, its type — motor, hearing, visual, visceral, intellectual, mental — and the number of the Certificado Único de Discapacidad (Law 22.431), and the non-contributory disability pension.

HOW IT IS FOUND

COLUMN NAME

AR_SALUD_DISCAPACIDAD - Path

90%

discapacidad[a-z]* (tipo|cod|codigo|categoria)_?discapacidad persona_?con_?discapacidad pcd cud certificado_?([uú]nico_)?(de_)?discapacidad n(o|ro|um|umero)_?cud condici[oó]n_?(de_)?discapacidad pensi[oó]n_?(no_?contributiva_)?(por_)?invalidiez movilidad_?reducida disabilit(y|ies)

KNOWN VALUES

AR_SALUD_DISCAPACIDAD - List

LIST

VALUES

STRENGTH

FIRST VALUES

ar-detectar-discapacidades.txt

23

60%

Motora, Auditiva, Visual, Visceral, Intellectual, Mental

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag, a CUD number is mapped character by character and any other value is replaced by a type from the list.

AR_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_DISCAPACIDAD_TIPO

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_DISCAPACIDAD_TIPO SECURE LOOKUP

Replaces the value with one of the 8 values in `ar-discapacidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno del espectro autista

→

Ninguna

11.11 Occupational health

AR_SALUD_OCUPACIONAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The result of the pre-employment and periodic exams, pre-existing conditions, work and commuting accidents and occupational diseases reported to the ART (Law 24.557), sick leave and absenteeism, and the incapacity set by the medical boards.

HOW IT IS FOUND

COLUMN NAME

AR_SALUD_OCUPACIONAL - Path

85%

```
aptitud_?(laboral|m[eé]dica|psicof[íi]sica) examen_?(preocupacional|peri[oó]dico|de_?
egreso|psicot[eé]cnico) preocupacional accidente_?(de_?)?trabajo accidente_?in_?itinere
enfermedad_?profesional siniestro_?art denuncia_?art art_?(siniestro|denuncia)
licencia_?(m[eé]dica|por_?enfermedad|psiqui[aá]trica|por_?maternidad) d[ií]as_?(de_?)?
licencia ausentismo carpeta_?m[eé]dica incapacidad(_?(laboral|laborativa|porcentaje))?
comisi[oó]n_?m[eé]dica preexistencias?
```

KNOWN VALUES AR_SALUD_OCUPACIONAL - List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-aptitud-laboral.txt	5	60%	apto, no apto, apto con preexistencias, pendiente, apto condicional

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A result is replaced by another from the list — fit, unfit —; a flag stays a flag; the diagnosis falls under its domain.

AR_SALUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_SALUD_LABORAL_LISTA .

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-si-no.txt , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-true-false.txt , chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt , chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-s-n.txt , chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-y-n.txt , chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_SALUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in ar-aptitud-laboral.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
No apto temporariamente	→ Pendiente

11.12 Sexual and reproductive health

AR_SALUD_REPRODUCTIVA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy, last menstrual period, prenatal care, childbirth, voluntary or legal termination of pregnancy (Law 27.610), contraceptive method, fertility and assisted reproduction.

HOW IT IS FOUND

COLUMN NAME AR_SALUD_REPRODUCTIVA – Path

90% embarazo embarazada gestante gestaci[oó]n edad_?gestacional semanas_?(de_)? gestaci[oó]n fum fecha_?[uú]ltima_?menstruaci[oó]n control_?prenatal prenatal parto(_? tipo)? ces[aá]rea aborto ive ile interrupci[oó]n_?(voluntaria|legal)(_?del_?embarazo)? m[eé]todo_?anticonceptivo anticoncepci[oó]n anticonceptivo salud_?(sexual|reproductiva) fertilidad fertilizaci[oó]n_?asistida reproducci[oó]n_?asistida pregnan(t|cy) contracepti(on|ve)

HOW IT IS MASKED

Flags keep their shape; any other value becomes Sin información .

AR_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_SUPRIMIR .

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-si-no.txt , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-true-false.txt , chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt , chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-s-n.txt , chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-y-n.txt , chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in ar-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
12 semanas de gestación	→	Sin información
S	→	S

11.13 Mental health

AR_SALUD_MENTAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Mental disorders, psychiatric or psychological care, involuntary admission, suicide attempts and problematic substance use (Law 26.657).

HOW IT IS FOUND

COLUMN NAME	AR_SALUD_MENTAL - Path
90%	salud_?mental trastorno[a-z]* psiqui[aá]tri[a-z]* psicol[oó]gi[a-z]* depresi[oó]n ansiedad suicid[a-z]* intento_?(de_)?suicidio autolesi[oó]n internaci[oó]n_ involuntaria consumo_?(problem[aá]tico de_?(sustancias alcohol drogas)) adicci[oó]n(es)? sedronar alcoholismo tabaquismo mental_?health

HOW IT IS MASKED

Flags keep their shape; any other value becomes Sin información .

AR_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_SUPRIMIR .

AR_BANDERA REGEX DECOMPOSE
Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
AR_BANDERA_SI_NO SECURE LOOKUP
Replaces the value with one of the 2 values in ar-bandera-si-no.txt , chosen by a keyed hash.
AR_BANDERA_TRUE_FALSE SECURE LOOKUP
Replaces the value with one of the 2 values in ar-bandera-true-false.txt , chosen by a keyed hash.
AR_BANDERA_YES_NO SECURE LOOKUP
Replaces the value with one of the 2 values in ar-bandera-yes-no.txt , chosen by a keyed hash.
AR_BANDERA_S_N SECURE LOOKUP
Replaces the value with one of the 2 values in ar-bandera-s-n.txt , chosen by a keyed hash.
AR_BANDERA_Y_N SECURE LOOKUP
Replaces the value with one of the 2 values in ar-bandera-y-n.txt , chosen by a keyed hash.
AR_BANDERA_0_1 SECURE LOOKUP
Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.
AR_CM_ALFANUM CHARACTER MAPPING
Maps each character to another of its group (7 groups), keeping length and format.
AR_SUPRIMIR SECURE LOOKUP
Replaces the value with one of the 1 values in ar-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Trastorno bipolar	→	Sin información

Financial and socioeconomic data

Credit information has its own rules in article 26, and a person's situation in the **BCRA Central de Deudores** — from 1, normal, to 6, unrecoverable by technical disposition — is among the data with the heaviest consequences. ANSES benefits and the monotributo category tell how much someone earns, whether they have children or a disability. Categories are replaced within their own notation and band; amounts are mapped to a plausible range with no relation to the real value.

12.1 Debtor situation

AR_FIN_SITUACION_CREDITICIA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The debtor's situation in the BCRA Central de Deudores — 1 normal, 2 low risk or special monitoring, 3 medium risk or with problems, 4 high risk, 5 unrecoverable, 6 unrecoverable by technical disposition —, bounced cheques, days in arrears, legal collection and credit bureau scores.

HOW IT IS FOUND

COLUMN NAME AR_FIN_SITUACION_CREDITICIA - Path

90% situaci[oó]n_?(crediticia|bcra|deudor|central_?deudores) sit_?(bcra|deudor|cred) central_?(de_?)?deudores cendeu clasificaci[oó]n_?(de_l_?)?deudor score(_?(crediticio|veraz|nosis|equifax|interno))? puntaje_?crediticio veraz nosis equifax informe_?comercial cheques_?rechazados d[ií]as_?(de_?)?(atraso|mora) morosidad moroso en_?mora gesti[oó]n_?judicial credit_?score credit_?rating

KNOWN VALUES	AR_FIN_SITUACION_CREDITICIA - List		
LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-situacion-crediticia.txt	22	70%	normal, riesgo bajo, riesgo medio, riesgo alto, irrecuperable, con seguimiento especial

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The situation is replaced within its band — 1-2, 3-4, 5-6 —, so the analysis by band keeps its shape; Situación 4 stays written the same way. A score gets other digits of the same length; a status in words, another from the list; a flag stays a flag.

AR_SITUACION_CREDITICIA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches:

AR_ESTADO_CREDITO .

AR_SITUACION_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-situacion-1-2.txt , chosen by a keyed hash.

AR_SITUACION_3_4 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-situacion-3-4.txt , chosen by a keyed hash.

AR_SITUACION_5_6 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-situacion-5-6.txt , chosen by a keyed hash.

AR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt`, chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt`, chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-yes-no.txt`, chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt`, chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt`, chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-0-1.txt`, chosen by a keyed hash.

AR_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 10 values in `ar-estados-credito.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
4	→	3
Situación 6	→	Situación 5
Irrecuperable	→	Con problemas

12.2 Debt

AR_FIN_DEUDA

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Outstanding balances, loan and instalment amounts, amounts in arrears and spending limits.

HOW IT IS FOUND

COLUMN NAME AR_FIN_DEUDA - Path

85% `saldo_?(deudor|deuda|cr[eé]dito|capital|pr[eé]stamo|adeudado|tarjeta) monto_?(de_?la_?)?`
`(deuda|cuota|cr[eé]dito|pr[eé]stamo|adeudado|en_?mora|financiado) importe_?`
`(deuda|cuota|adeudado|mora) deuda(_?total)? l[ií]mite_?(de_?)?(cr[eé]dito|compra|tarjeta)`
`cuota_?mensual loan_?(amount|balance) outstanding_?balance debt`

DATA TYPE AR_FIN_DEUDA - Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 10,000 and 500,000,000 pesos, unrelated to the real one.

AR_VALOR_DEUDA NUMERIC MAPPING

Maps the number to another between 10,000 and 500,000,000.

EXAMPLES

VALUE		MASKED
1850000	→	4398071

12.3 Income and pay

AR_FIN_INGRESOS

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

Basic, gross or net salary, taxable pay, earnings, household income and annual turnover.

HOW IT IS FOUND

COLUMN NAME AR_FIN_INGRESOS – Path

85% `salario(_?(b[aá]sico|mensual|bruto|neto))?` `sueldo(_?(b[aá]sico|bruto|neto|mensual))?`
`remuneraci[oó]n(_?(bruta|neta|total|imponible))?` `haberes?` `ingresos?(_?(mensuales?|totales?`
`|familiares?|declarados?|netos?|brutos?))?` `neto_?a_?cobrar` `bruto_?mensual` `facturaci[oó]n_?`
`anual` `salary` `income` `wages?`

DATA TYPE AR_FIN_INGRESOS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 300,000 and 30,000,000 pesos.

AR_INGRESOS **NUMERIC MAPPING**

Maps the number to another between 300,000 and 30,000,000.

EXAMPLES

VALUE	MASKED
1450000	→ 4140719

12.4 Assets

AR_FIN_PATRIMONIO

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

Net worth, personal assets, tax and market valuations, account and fixed-term deposit balances, foreign currency holdings.

HOW IT IS FOUND

COLUMN NAME AR_FIN_PATRIMONIO – Path

85% `patrimonio(_?(neto|total))?` `bienes_?personales` `activos?(_?(totales?))?` `valuaci[oó]n_?`
`(fiscal|inmueble|veh[ií]culo)` `valor_?(del_?)?`
`(inmueble|veh[ií]culo|bienes|tasaci[oó]n|mercado)` `tasaci[oó]n` `saldo_?(cuenta|caja_?`
`ahorro|plazo_?fijo|inversi[oó]n)` `plazo_?fijo(_?monto)?` `tenencia_?(d[oó]lares|moneda_?`
`extranjera|cripto)` `net_?worth` `account_?balance`

DATA TYPE AR_FIN_PATRIMONIO – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 1,000,000 and 3,000,000,000 pesos.

AR_PATRIMONIO **NUMERIC MAPPING**

Maps the number to another between 1,000,000 and 3,000,000,000.

EXAMPLES

VALUE

MASKED

85000000

→

51593117

12.5 Pensions and benefits

AR_FIN_JUBILACION

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

The retirement or survivor pension, the amount of an allowance or benefit, and child support.

HOW IT IS FOUND

COLUMN NAME

AR_FIN_JUBILACION – Path

90%

haber_?(jubilatorio|previsional|mensual) jubilaci[oó]n_?(monto|haber|importe) pensi[oó]n_?
(monto|haber|importe) monto_
(jubilaci[oó]n|pensi[oó]n|asignaci[oó]n|prestaci[oó]n|beneficio) importe_
(asignaci[oó]n|beneficio|prestaci[oó]n) cuota_?alimentaria pension_?amount

DATA TYPE

AR_FIN_JUBILACION – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 250,000 and 12,000,000 pesos.

AR_VALOR_JUBILACION NUMERIC MAPPING

Maps the number to another between 250,000 and 12,000,000.

EXAMPLES

VALUE

MASKED

420000

→

646464

12.6 Social benefits and programmes

AR_FIN_PROGRAMA_SOCIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

ANSES benefits and national programmes — Universal Child and Pregnancy Allowance, Prestación Alimentar, Progresar, non-contributory pensions, PUAM, family allowances — and the income level of the energy subsidy segmentation, often as a flag. Receiving the AUH says the person has children and works informally; a non-contributory pension, that they have a disability.

HOW IT IS FOUND

COLUMN NAME

AR_FIN_PROGRAMA_SOCIAL – Path

90%

programa_?social plan_?social beneficiario_?(programa|plan|asignaci[oó]n|auh|anses)
prestaci[oó]n_?(social|anses|alimentar) asignaci[oó]n_?(universal|por_?hijo|por_
embarazo|familiar) auh aue tarjeta_?alimentar progresar potenciar_?trabajo volver_
al_?trabajo puam pnc pensi[oó]n_?no_?contributiva beneficio_?anses tipo_?(de_)?
beneficio segmentaci[oó]n_?(energ[eé]tica|subsidi[os]?) nivel_?(de_)?(subsidio|ingresos_
rase) rase social_?programme

KNOWN VALUES AR_FIN_PROGRAMA_SOCIAL - List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-programas-sociales.txt	36	80%	Asignación Universal por Hijo, Asignacion Universal por Hijo, Asignación por Embarazo, Asignacion por Embarazo, Prestación Alimentar, Prestacion Alimentar
ar-detectar-codigos-banderas.txt	11	30%	s, n, sí, si, no, 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a benefit from the list.

AR_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_PROGRAMA_SOCIAL_LISTA

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-si-no.txt , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-true-false.txt , chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt , chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-s-n.txt , chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-y-n.txt , chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in ar-programas-sociales.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Potenciar Trabajo	→	Acompañamiento Social
S	→	S

12.7 Monotributo category

AR_FIN_MONOTRIBUTO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The category of the Simplified Regime, A to K, which ARCA assigns by gross annual income.

HOW IT IS FOUND

COLUMN NAME AR_FIN_MONOTRIBUTO – Path

90% `categoria[ií]a_?(de_)?monotributo` `monotributo(_?categoria[ií]a)?` `cat_?monotributo`
`categoria[ií]a_?(afip|arca)` `r[eé]gimen_?simplificado`

DATA TYPE AR_FIN_MONOTRIBUTO – Type

Accepts text (length 1 to 12); any other type rules the domain out.

HOW IT IS MASKED

The category is replaced within its tier — A–D, E–H, I–K —; `Categoría C` stays written the same way.

AR_MONOTRIBUTO **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_MONOTRIBUTO_A_D **SECURE LOOKUP**

Replaces the value with one of the 4 values in `ar-monotributo-a-d.txt`, chosen by a keyed hash.

AR_MONOTRIBUTO_E_H **SECURE LOOKUP**

Replaces the value with one of the 4 values in `ar-monotributo-e-h.txt`, chosen by a keyed hash.

AR_MONOTRIBUTO_I_K **SECURE LOOKUP**

Replaces the value with one of the 3 values in `ar-monotributo-i-k.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
C	→	D
Categoría H	→	Categoría E

12.8 Housing tenure

AR_FIN_VIVIENDA

COLUMN NAME **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

Housing tenure as the 2022 census asks it: owner of the dwelling and the land or of the dwelling only, tenant, occupant on loan or through work.

HOW IT IS FOUND

COLUMN NAME AR_FIN_VIVIENDA – Path

90% `tenencia_?(de_)?(la_)?vivienda` `r[eé]gimen_?(de_)?tenencia` `tipo_?(de_)?tenencia`
`vivienda_?(propia|alquilada|tipo_?tenencia)` `condici[oó]n_?(de_)?ocupaci[oó]n` `housing_?`
`tenure`

KNOWN VALUES AR_FIN_VIVIENDA – List

LIST	VALUES	STRENGTH	FIRST VALUES
ar-detectar-tenencia-vivienda.txt	18	60%	Propietario de la vivienda y el terreno, Propietario solo de la vivienda, Inquilino, Ocupante por préstamo, Ocupante por prestamo, Ocupante por trabajo

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another tenure from the list.

AR_TENENCIA_VIVIENDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_TENENCIA_VIVIENDA_LISTA .

AR_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in **ar-bandera-si-no.txt** , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in **ar-bandera-true-false.txt** , chosen by a keyed hash.

AR_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in **ar-bandera-yes-no.txt** , chosen by a keyed hash.

AR_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in **ar-bandera-s-n.txt** , chosen by a keyed hash.

AR_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in **ar-bandera-y-n.txt** , chosen by a keyed hash.

AR_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in **ar-bandera-0-1.txt** , chosen by a keyed hash.

AR_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

AR_TENENCIA_VIVIENDA_LISTA **SECURE LOOKUP**

Replaces the value with one of the 6 values in **ar-tenencia-vivienda.txt** , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Ocupante de hecho	→	Otra situación

Criminal records and court files

Data on criminal or misdemeanour records may only be processed by the competent public authorities (art. 7.4), and Convention 108+ counts it among the special categories. A company that keeps it — a criminal record certificate requested in recruitment — must protect it with the care of sensitive data.

13.1 Records

AR_PENAL_ANTECEDENTES

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

The criminal record certificate of the National Recidivism Registry, misdemeanours, type of offence, procedural situation, pre-trial detention, detainee status and arrest warrants.

HOW IT IS FOUND

COLUMN NAME

AR_PENAL_ANTECEDENTES – Path

95% antecedentes?(?{penales|judiciales|policiales|contravencionales})? certificado?(de_)?
(antecedentes|reincidencia|buena_?conducta) reincidencia registro_?nacional_?(de_)?
reincidencia rnr condena_(?(penal|tipo))? delito_(?(tipo|imputado))? tipo_(de_)?
delito contravenci[oó]n(es)? situaci[oó]n_?procesal prisi[oó]n_?preventiva detenido
privad[oa]_(de_)?(la_)?libertad interno_(spf|penitenciario) reincidente pedido_?
(de_)?captura rebeld[ií]a criminal_?record

55% estado_(del_)?proceso sentencia fallo

HOW IT IS MASKED

Replaced by a generic status from the list — no record, convicted, dismissed —, whatever the outcome; a flag stays a flag.

AR_ANTECEDENTES

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_ANTECEDENTES_LISTA .

AR_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-si-no.txt , chosen by a keyed hash.

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-true-false.txt , chosen by a keyed hash.

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-yes-no.txt , chosen by a keyed hash.

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-s-n.txt , chosen by a keyed hash.

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-y-n.txt , chosen by a keyed hash.

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.

AR_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

AR_ANTECEDENTES_LISTA

SECURE LOOKUP

Replaces the value with one of the 8 values in `ar-antecedentes.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Condenado por robo en 2019	→ Absuelto

13.2 Court file

AR_PENAL_EXPEDIENTE

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The file number of the national and federal courts — the chamber's code, the number and the year, CCC 12345/2023 —, the criminal investigation number (IPP) of Buenos Aires province (PP-07-00-012345-23/00) and case, police report and complaint numbers. Cases can be looked up online and lead to the parties.

HOW IT IS FOUND

COLUMN NAME

AR_PENAL_EXPEDIENTE - Path

90%

`n(o|ro|um|umero)?(de_)?(expediente|causa|legajo_?penal|ipp|sumario|denuncia|carpeta_|judicial)(_(judicial|penal))? expediente?(judicial|penal) causa?(penal|judicial|n(o|ro|um|umero)) ipp cuuj sumario_?policial denuncia?(penal|policial)`

50%

`expediente causa`

VALUE FORMAT

AR_PENAL_EXPEDIENTE - Regex

PATTERN

STRENGTH

NOTES

`[A-Z]{2,4}\s?\d{1,6}\.\d{4}`

70%

`PP-\d{2}-\d{2}-\d{6}-\d{2}(\.\d{2})?`

80%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The number is mapped digit by digit; code, judicial district, prosecutor's office and year stay. Other numbers are masked character by character.

AR_EXPEDIENTE REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: AR_CM_ALFANUM .

AR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
CCC 12345/2023	→ CCC 31564/2023
PP-07-00-012345-23/00	→ PP-07-00-958068-23/00

The CUIT check digit

The Masking Engine's Check Digit algorithm computes a modulus-11 digit as *eleven minus the remainder* and writes 10 as 0. For the CUIT that is right for ten of the eleven possible remainders: when the remainder is 1, ARCA uses no digit but changes the type — 20 and 27 become 23, 30 becomes 33, 23 becomes 24, 33 becomes 34 —, and Check Digit would write 0. One masked CUIT in eleven would be invalid.

The set solves it in two steps, with no tables:

- A Check Digit with **doubled weights** keeps the type, maps the eight DNI digits and writes an auxiliary digit in place of the check digit. Since $2 \times 1 = 2$ modulo 11, the auxiliary digit is 9 exactly when the remainder of the masked body under the true weights is 1.
- A Regex Decompose, when the auxiliary digit is 9, rewrites type and digit: changing the type adds a known multiple of the weights, and the new digit follows — 23 and 9 for a 20, 23 and 4 for a 27, 33 and 9 for a 30, 24 and 6 for a 23, 34 and 6 for a 33. In any other case it applies a Check Digit with the true weights over the body, which it leaves as it is, and recomputes the digit.

The body is mapped with the same Character Mapping as the DNI: a natural person's CUIL still holds their masked DNI. CBU and CVU do not have the problem — their modulus is 10 — and are solved with a single Check Digit over the account.

Where people live: localidades, partidos and postal code

With the 2022 census population by gobierno local and by departamento, and the location of each from the Georef service, the set knows the size, province and position of 528 partidos, departamentos and comunas, of 2,280 gobiernos locales and of the 4,027 INDEC localidades censales.

- A **gobierno local** with fewer than 20,000 inhabitants becomes the nearest gobierno local of the same province with at least 20,000. There are 1,952 of them, with 7 million inhabitants — 15% of the population. El Chaltén (Santa Cruz) becomes El Calafate; Tilcara (Jujuy), Libertador General San Martín; Ancasti (Catamarca), Valle Viejo.
- A **localidad** follows its gobierno local. Those outside any gobierno local — rural areas of Santiago del Estero, Córdoba or Patagonia — are generalized too, to the nearest large gobierno local.
- A **partido or departamento** with fewer than 20,000 inhabitants becomes the nearest one of the same province with at least 20,000. There are 203, with 2 million inhabitants.
- The **province** stays. Every province has at least one gobierno local of 20,000 inhabitants.
- Distance is measured between the Georef centroids, in a straight line.
- Names repeat — San José, San Martín, Villa Nueva, 25 de Mayo — and some differ only by an accent. A name is generalized only when every place bearing it is small, and then follows the largest of them. With the province (San José – Entre Ríos , San José (Entre Ríos) , San José, Entre Ríos) the same rule applies within the province.
- The **INDEC codes** follow the same table, and a person's name and code still agree.
- In Buenos Aires province the gobierno local is the partido: a small localidad becomes the name of the nearest partido, which is not always the name of its main town — Carhué becomes Saavedra , whose main town is Pigüé.
- The **postal code** keeps the province and the first two digits.

Place names that are also given names or surnames, and province names, are left out of the detection list, so that a surname column is not taken for localidades.

16

Limits

- **Binary columns** — DNI photos, biometric validation selfies, fingerprints, clinical PDFs in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **A small localidad inside a large gobierno local** stays: the census publishes population by gobierno local, not by localidad. A rural paraje of a large partido keeps its name.
- **A seven-digit DNI** is masked with seven digits; inside the CUIL it has a leading zero and is masked with eight. That person's DNI and CUIL no longer agree.
- **A check digit in a column of its own** is not recomputed: it is masked and no longer matches the masked CUIT.
- **Province, the CBU's bank and the phone area code stay.**
- **Data Cleansing leaves unknown values as they are:** a localidad written in a way the table does not have — abbreviated, misspelled — passes unchanged.
- **Free text** is redacted word by word: a mobile written with spaces is not found, and a name that is also a common word (Luz , Rosa , Paz) is redacted wherever it appears.
- **Children and adolescents** — a birth date moves at most 60 days, so few people cross their 13th, 16th or 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, height, neighbourhood, localidad and postal code in separate columns are masked independently and no longer form a coherent address.
- **The engine key** links masked values back to production for whoever holds both: in that case the result is not dissociated and is still personal data. Keep the key away from the users of the copy.

17

Verification

Before publication, the set was checked outside a Masking Engine:

- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 160 columns with the whole set at its assignment threshold — well named, badly named and 31 columns that are not personal data — and again with only the classifiers of the essential pack.
- The tables that generalize places were audited for the 528 partidos and departamentos and for the 2,280 gobiernos locales and 4,027 localidades: by name, by name with the province and by code.
- The algorithms, run with the Delphix algorithm plugin, masked each domain's sample values and placeholders such as N/A , checking every output against its vocabulary; 240 CUITs of every type — including those that change type — and 150 CBUs for validity and collisions; 150 DNIs for collisions; and 20 people whose DNI and CUIL must still agree. Every algorithm also masked its own sample value.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

Sources

- Law 25.326 on the Protection of Personal Data and Decree 1558/2001 (InfoLEG). National Constitution, art. 43. Law 27.483 (Convention 108) and Law 27.699 (Convention 108+). Criminal Code, arts. 117 bis and 157 bis.
- Agencia de Acceso a la Información Pública: Resolution 47/2018, recommended security measures (Annex I, item H); Resolution 126/2024, classification of infringements and grading of sanctions. Bills 644-S-2025, 1948-D-2025 and 3397-D-2026. European Commission, Decision 2003/490/EC and 2024 review report.
- Laws 26.529 (patients' rights), 26.657 (mental health), 27.675 (HIV, hepatitis, tuberculosis and STIs), 27.610 (voluntary termination of pregnancy), 26.743 (gender identity), 26.485 (violence against women), 26.364 (human trafficking), 22.431 (disability), 24.557 (occupational risks). Decree 476/2021 (DNI with X).
- INDEC: 2022 National Census of Population, Households and Dwellings, final results by departamento and by gobierno local; localidades censales. Georef geographic data normalization service (datos.gob.ar). RENAPER: names of natural persons (datos.gob.ar).
- ARCA (formerly AFIP): CUIT, CUIL and simplified regime. BCRA: Central de Deudores and debtor classification; Clave Bancaria Uniforme and Clave Virtual Uniforme. ANSES: benefits. Correo Argentino: Código Postal Argentino. Superintendencia de Servicios de Salud: National Register of Obras Sociales.

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

AR_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: AR_L2_ANIO_NACIMIENTO

PATTERNS, TRIED IN ORDER

(\d{3})(\d)	keep · AR_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_ANTECEDENTES_LISTA .

Used by: AR_PENAL_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_ANTECEDENTES_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in ar-antecedentes.txt , chosen by a keyed hash.

Used by: AR_ANTECEDENTES

CONFIGURATION

lookupFile	ar-antecedentes.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_APELLIDO NAME

Replaces the name with one of the 408 names in ar-apellidos.txt .

Used by: AR_PALABRA_APELLIDO

CONFIGURATION

lookupFile	ar-apellidos.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

AR_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: AR_CM_ALFANUM .

Used by: AR_L1_APELLIDO , AR_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(\S+)	AR_PALABRA_APELLIDO
(\S+)\s+(\S+)	AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO
otherwise	AR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

AR_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: AR_CATEGORIA_SUPRIMIDA , AR_ESTADO_CIVIL , AR_NIVEL_EDUCATIVO , AR_ORIGEN_ETNICO , AR_PUEBLO_INDIGENA , AR_LENGUA , AR_RELIGION , AR_OPINION_POLITICA , AR_PARTIDO_POLITICO , AR_ORIENTACION_SEXUAL , AR_IDENTIDAD_GENERO , AR_COBERTURA_SALUD , AR_DIAGNOSTICO , AR_MEDICAMENTO , AR_DISCAPACIDAD , AR_SALUD_LABORAL , AR_SITUACION_CREDITICIA , AR_PROGRAMA_SOCIAL , AR_TENENCIA_VIVIENDA , AR_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no)	AR_BANDERA_SI_NO
(?i)(true false)	AR_BANDERA_TRUE_FALSE
(?i)(yes)	AR_BANDERA_YES_NO
(?i)([sn])	AR_BANDERA_S_N
(?i)([yx])	AR_BANDERA_Y_N
([01])	AR_BANDERA_0_1
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-bandera-0-1.txt , chosen by a keyed hash.

Used by: AR_BANDERA

CONFIGURATION

lookupFile	ar-bandera-0-1.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-s-n.txt` , chosen by a keyed hash.

Used by: `AR_BANDERA`

CONFIGURATION

lookupFile	<code>ar-bandera-s-n.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-si-no.txt` , chosen by a keyed hash.

Used by: `AR_BANDERA`

CONFIGURATION

lookupFile	<code>ar-bandera-si-no.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-true-false.txt` , chosen by a keyed hash.

Used by: `AR_BANDERA`

CONFIGURATION

lookupFile	<code>ar-bandera-true-false.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera-y-n.txt` , chosen by a keyed hash.

Used by: `AR_BANDERA`

CONFIGURATION

lookupFile	<code>ar-bandera-y-n.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-bandera=yes-no.txt`, chosen by a keyed hash.

Used by: `AR_BANDERA`

CONFIGURATION

lookupFile	ar-bandera=yes-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_BARRIO SECURE LOOKUP

Replaces the value with one of the 124 values in `ar-barrios.txt`, chosen by a keyed hash.

Used by: `AR_L2_BARRIO`

CONFIGURATION

lookupFile	ar-barrios.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `AR_SUPRIMIR`.

Used by: `AR_L3_CONVICCION_FILOSOFICA`, `AR_L3_AFILIACION_SINDICAL`, `AR_L3_VIDA_SEXUAL`, `AR_L3_VICTIMA`, `AR_SALUD_VIH`, `AR_SALUD_REPRODUCTIVA`, `AR_SALUD_MENTAL`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>AR_BANDERA</code>
<code>(\d{1,6})</code>	<code>AR_CM_ALFANUM</code>
otherwise	<code>AR_SUPRIMIR</code>

CONFIGURATION

trimInput	yes
requireMask	no

AR_CBU REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_DIGITOS`.

Used by: `AR_L1_CBU`

PATTERNS, TRIED IN ORDER

<code>(\d{8})([s\-\])?(\d{14})</code>	<code>keep · keep · AR_CBU_CUENTA</code>
otherwise	<code>AR_CM_DIGITOS</code>

CONFIGURATION

trimInput	yes
requireMask	no

AR_CBU_CUENTA CHECK DIGIT

Masks the digits with AR_CM_DIGITOS and recomputes a modulus 10 check digit with weights 3 1 7 9 3 1 7 9 3 1 7 9 3 from the right.

Used by: AR_CBU

CONFIGURATION

weightList	3 1 7 9 3 1 7 9 3 1 7 9 3
modulusNumber	10
checkDigitIndex	13
numDigitsForCheckdigitCalculation	13
calculateChecksumRightToLeft	yes
numericAlgorithm	AR_CM_DIGITOS
alphaNumericAlgorithm	AR_CM_DIGITOS
preserveRegex	
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

AR_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in ar-cie10.txt , chosen by a keyed hash.

Used by: AR_DIAGNOSTICO

CONFIGURATION

lookupFile	ar-cie10.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in ar-cie10-decimal.txt , chosen by a keyed hash.

Used by: AR_DIAGNOSTICO

CONFIGURATION

lookupFile	ar-cie10-decimal.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: AR_L1_TRAMITE_DNI , AR_L1_DOCUMENTO_EXTRANJERO , AR_L1_PASAPORTE , AR_L1_REGISTRO_CIVIL , AR_L1_MATRICULA_PROFESIONAL , AR_L1_DIRECCION_COMPLEMENTO , AR_L1_ALIAS_CBU , AR_L1_VEHICULO , AR_L1_INMUEBLE , AR_L1_CONTRATO , AR_L1_USUARIO , AR_SALUD_IDENTIFICADOR , AR_SALUD_RESULTADO_ESTUDIO , AR_CATEGORIA_SUPRIMIDA , AR_DOCUMENTO , AR_NOMBRES , AR_APELLIDOS , AR_NOMBRE_COMPLETO , AR_EMAIL , AR_ORIGEN_ETNICO , AR_PUEBLO_INDIGENA , AR LENGUA , AR_RELIGION , AR_OPINION_POLITICA , AR_PARTIDO_POLITICO , AR_ORIENTACION_SEXUAL , AR_IDENTIDAD_GENERO , AR_MEDICAMENTO , AR_DISCAPACIDAD , AR_SALUD_LABORAL , AR_PROGRAMA_SOCIAL , AR_TENENCIA_VIVIENDA , AR_ANTECEDENTES , AR_EXPEDIENTE

CONFIGURATION

characterGroups	0123456789 AEIOU BCDFGHJKLMNPQRSTUVWXYZ aeiou bcdfghjklmnpqrstvwxyz ÁÉÍÓÚú áéíóúú
caseSensitive	yes
minMaskedPositions	0

AR_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: AR_L1_CUENTA_BANCARIA , AR_CUIT_CUERPO , AR_CUIT , AR_DOCUMENTO , AR_TELEFONO , AR_CBU_CUENTA , AR_CBU , AR_COORDENADA , AR_ANIO , AR_EDAD , AR_OCUPACION_O_CODIGO , AR_COBERTURA_SALUD , AR_PROCEDIMIENTO , AR_SITUACION_CREDITICIA , AR_EXPEDIENTE

CONFIGURATION

characterGroups	0123456789
caseSensitive	yes
minMaskedPositions	0

AR_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: AR_L1_DOMINIO

CONFIGURATION

characterGroups	0123456789 ABCDEFGHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

AR_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: AR_L1_DISPOSITIVO , AR_IP

CONFIGURATION

characterGroups	0123456789 abcdef ABCDEF ghijklmnopqrstuvwxyz GHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

AR_COBERTURA_SALUD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_OBRA_SOCIAL .

Used by: AR_SALUD_COBERTURA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
--	------------

(\d[\d\-]{3,8}\d)	AR_CM_DIGITOS
otherwise	AR_OBRA_SOCIAL
CONFIGURATION	
trimInput	yes
requireMask	no

AR_CODIGO_GEOGRAFICO DATA CLEANSING

Replaces each value found in `ar-codigos-geograficos-generalizados.txt` (5,070 pairs) by its counterpart; values not in the file stay as they are.
Used by: `AR_L2_CODIGO_GEOGRAFICO`

CONFIGURATION	
lookupFile	<code>ar-codigos-geograficos-generalizados.txt</code>
delimiter	
caseSensitive	yes
trimWhitespace	yes

AR_CODIGO_POSTAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.
Used by: `AR_L2_CODIGO_POSTAL`

PATTERNS, TRIED IN ORDER	
([A-Za-z])(\d{2})(\d{2})([A-Za-z]{3})	keep · keep · replace with <code>00</code> · replace with <code>AAA</code>
([A-Za-z]?)(\d{2})(\d{2})	keep · keep · replace with <code>00</code>
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

AR_CONTEO_LIMITADO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.
Used by: `AR_L2_PERSONAS_A_CARGO`

PATTERNS, TRIED IN ORDER	
([0-5])	keep
(\d+)	replace with <code>5</code>
otherwise	keep
CONFIGURATION	
trimInput	yes
requireMask	no

AR_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.
Used by: `AR_L1_GEOLOCALIZACION`

PATTERNS, TRIED IN ORDER

(-?\d{1,3}[.,]\d)(\d+)\s*([,;])\s*(-?\d{1,3}[.,]\d)(\d+)	keep · AR_CM_DIGITOS · keep · keep · AR_CM_DIGITOS
(-?\d{1,3}[.,]\d)(\d+)	keep · AR_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_CUIT REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_CM_DIGITOS .

Used by: AR_L1_CUIT

PATTERNS, TRIED IN ORDER

(\d{2}[\s\-.\/]? \d{8}[\s\-.\/]? \d)	AR_CUIT_CADENA
otherwise	AR_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

AR_CUIT_AJUSTE REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: AR_CUIT_DV .

Used by: AR_CUIT_CADENA

PATTERNS, TRIED IN ORDER

(20)([\s\-.\/]? \d{8}[\s\-.\/]?)(9)	replace with 23 · keep · replace with 9
(27)([\s\-.\/]? \d{8}[\s\-.\/]?)(9)	replace with 23 · keep · replace with 4
(23)([\s\-.\/]? \d{8}[\s\-.\/]?)(9)	replace with 24 · keep · replace with 6
(24)([\s\-.\/]? \d{8}[\s\-.\/]?)(9)	replace with 23 · keep · replace with 3
(30)([\s\-.\/]? \d{8}[\s\-.\/]?)(9)	replace with 33 · keep · replace with 9
(33)([\s\-.\/]? \d{8}[\s\-.\/]?)(9)	replace with 34 · keep · replace with 6
(34)([\s\-.\/]? \d{8}[\s\-.\/]?)(9)	replace with 33 · keep · replace with 3
otherwise	AR_CUIT_DV

CONFIGURATION

trimInput	yes
requireMask	no

AR_CUIT_AUX CHECK DIGIT

Masks the digits with AR_CUIT_CUERPO and recomputes a modulus 11 check digit with weights 4 6 8 10 12 14 4 6 8 10 6 8 10 from the right.

Used by: AR_CUIT_CADENA

CONFIGURATION

weightList	4 6 8 10 12 14 4 6 8 10
modulusNumber	11
checkDigitIndex	10
numDigitsForCheckdigitCalculation	10

calculateChecksumRightToLeft	yes
numericAlgorithm	AR_CUIT_CUERPO
alphaNumericAlgorithm	AR_CUIT_CUERPO
preserveRegex	[.\-\\s/]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

AR_CUIT_CADENA STRING ALGORITHM CHAIN

Applies AR_CUIT_AUX → AR_CUIT_AJUSTE , in this order.

Used by: AR_CUIT , AR_DOCUMENTO

CONFIGURATION

algorithmReferences[1]	AR_CUIT_AUX
algorithmReferences[2]	AR_CUIT_AJUSTE

AR_CUIT_CUERPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_CM_DIGITOS .

Used by: AR_CUIT_AUX

PATTERNS, TRIED IN ORDER

(\d{2})(\d{8})	keep · AR_CM_DIGITOS
otherwise	AR_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

AR_CUIT_DV CHECK DIGIT

Masks the digits with AR_IDENTIDAD and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 3 4 5 from the right.

Used by: AR_CUIT_AJUSTE

CONFIGURATION

weightList	2 3 4 5 6 7 2 3 4 5
modulusNumber	11
checkDigitIndex	10
numDigitsForCheckdigitCalculation	10
calculateChecksumRightToLeft	yes
numericAlgorithm	AR_IDENTIDAD
alphaNumericAlgorithm	AR_IDENTIDAD
preserveRegex	[.\-\\s/]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0

inputHandlingConfig.trimWhitespace	yes
------------------------------------	-----

AR_DEPARTAMENTO DATA CLEANSING

Replaces each value found in `ar-departamentos-generalizados.txt` (3,254 pairs) by its counterpart; values not in the file stay as they are.

Used by: `AR_L2_DEPARTAMENTO`

CONFIGURATION

lookupFile	<code>ar-departamentos-generalizados.txt</code>
delimiter	
caseSensitive	yes
trimWhitespace	yes

AR_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

`AR_DIAGNOSTICO_TEXTO`.

Used by: `AR_SALUD_DIAGNOSTICO`

PATTERNS, TRIED IN ORDER

<code>([A-TV-Za-tv-z]\d{2}\.\d{1,2})</code>	<code>AR_CIE10_DECIMAL</code>
<code>([A-TV-Za-tv-z]\d{2,3}X?)</code>	<code>AR_CIE10</code>
<code>(?i)(s[ií] no true false yes [sn]yx01))</code>	<code>AR_BANDERA</code>
otherwise	<code>AR_DIAGNOSTICO_TEXTO</code>

CONFIGURATION

trimInput	yes
requireMask	no

AR_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in `ar-diagnosticos.txt`, chosen by a keyed hash.

Used by: `AR_DIAGNOSTICO`

CONFIGURATION

lookupFile	<code>ar-diagnosticos.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in `ar-direcciones.txt`, chosen by a keyed hash.

Used by: `AR_L1_DIRECCION`

CONFIGURATION

lookupFile	<code>ar-direcciones.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_DISCAPACIDAD_TIPO .

Used by: AR_SALUD_DISCAPACIDAD

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
([A-Za-z0-9\-\-]*\d{4,}[A-Za-z0-9\-\-]*)	AR_CM_ALFANUM
otherwise	AR_DISCAPACIDAD_TIPO

CONFIGURATION

trimInput	yes
requireMask	no

AR_DISCAPACIDAD_TIPO SECURE LOOKUP

Replaces the value with one of the 8 values in ar-discapacidades.txt , chosen by a keyed hash.

Used by: AR_DISCAPACIDAD

CONFIGURATION

lookupFile	ar-discapacidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_DOCUMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_CM_ALFANUM .

Used by: AR_L1_DNI

PATTERNS, TRIED IN ORDER

(\d{2}[\s\-\-./]?[d{8}[\s\-\-./]?[d])	AR_CUIT_CADENA
(\d{1,3}(?:\.\d{3}){1,2} \d{6,8})	AR_CM_DIGITOS
otherwise	AR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

AR_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: AR_L2_EDAD

PATTERNS, TRIED IN ORDER

(\d{3,})	replace with 90
([1-9])(\d)([.,]\d+)	keep · AR_CM_DIGITOS · keep

<code>([1-9])(\d)</code>	<code>keep · AR_CM_DIGITOS</code>
<code>(\d)</code>	<code>AR_CM_DIGITOS</code>
otherwise	<code>keep</code>

CONFIGURATION

<code>trimInput</code>	<code>yes</code>
<code>requireMask</code>	<code>no</code>

AR_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_CM_ALFANUM` .

Used by: `AR_L1_EMAIL`

PATTERNS, TRIED IN ORDER

<code>(^[^\s]+)@([^\s]+)\.([A-Za-z]{2,24})(?:\.[A-Za-z]{2})?)</code>	<code>AR_CM_ALFANUM · AR_CM_ALFANUM · replace with test</code>
otherwise	<code>AR_CM_ALFANUM</code>

CONFIGURATION

<code>trimInput</code>	<code>yes</code>
<code>requireMask</code>	<code>no</code>

AR_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 24 values in `ar-empleadores.txt` , chosen by a keyed hash.

Used by: `AR_L2_EMPLEADOR`

CONFIGURATION

<code>lookupFile</code>	<code>ar-empleadores.txt</code>
<code>hashMethod</code>	<code>SHA256</code>
<code>maskedValueCase</code>	<code>PRESERVE_LOOKUP_FILE</code>
<code>inputCaseSensitive</code>	<code>no</code>
<code>trimWhitespaceFromInput</code>	<code>yes</code>
<code>trimWhitespaceInLookupFile</code>	<code>yes</code>

AR_EMPRESA SECURE LOOKUP

Replaces the value with one of the 24 values in `ar-empresas.txt` , chosen by a keyed hash.

Used by: `AR_L1_RAZON_SOCIAL`

CONFIGURATION

<code>lookupFile</code>	<code>ar-empresas.txt</code>
<code>hashMethod</code>	<code>SHA256</code>
<code>maskedValueCase</code>	<code>PRESERVE_LOOKUP_FILE</code>
<code>inputCaseSensitive</code>	<code>no</code>
<code>trimWhitespaceFromInput</code>	<code>yes</code>
<code>trimWhitespaceInLookupFile</code>	<code>yes</code>

AR_ESTABLECIMIENTO_EDUCATIVO SECURE LOOKUP

Replaces the value with one of the 12 values in `ar-establecimientos-educativos.txt` , chosen by a keyed hash.

Used by: `AR_L2_ESTABLECIMIENTO_EDUCATIVO`

CONFIGURATION

lookupFile	ar-establecimientos-educativos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_ESTADO_CIVIL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_ESTADO_CIVIL_LISTA .

Used by: AR_L2_ESTADO_CIVIL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_ESTADO_CIVIL_CODIGO
otherwise	AR_ESTADO_CIVIL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_ESTADO_CIVIL_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in ar-estado-civil-codigos.txt , chosen by a keyed hash.

Used by: AR_ESTADO_CIVIL

CONFIGURATION

lookupFile	ar-estado-civil-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_ESTADO_CIVIL_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in ar-estado-civil.txt , chosen by a keyed hash.

Used by: AR_ESTADO_CIVIL

CONFIGURATION

lookupFile	ar-estado-civil.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 10 values in ar-estados-credito.txt , chosen by a keyed hash.

Used by: AR_SITUACION_CREDITICIA

CONFIGURATION

lookupFile	ar-estados-credito.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_EXPEDIENTE REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: AR_CM_ALFANUM .

Used by: AR_PENAL_EXPEDIENTE

PATTERNS, TRIED IN ORDER

([A-Za-z]{2,4}[\s\-\]?) (\d{1,6}) (\/\d{2,4} (?:\/[A-Za-z0-9]{1,6})*)	keep · AR_CM_DIGITOS · keep
((?:PP IPP) [\s\-\]? \d{2} [\s\-\] \d{2} [\s\-\] (\d{6}) ([\s\-\] \d{2} (?:\/\d{2})?))	keep · AR_CM_DIGITOS · keep
(\d{1,6}) (\/\d{2,4})	AR_CM_DIGITOS · keep
otherwise	AR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

AR_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: AR_L2_FECHA_EVENTO

CONFIGURATION

minRange	-30
maxRange	30
unit	DAYS
roll	no

AR_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: AR_L2_FECHA_NACIMIENTO

CONFIGURATION

minRange	-60
maxRange	60
unit	DAYS
roll	no

AR_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in ar-grupos-sanguineos.txt , chosen by a keyed hash.

Used by: AR_SALUD_GRUPO_SANGUINEO

CONFIGURATION

lookupFile	ar-grupos-sanguineos.txt
------------	--------------------------

hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_IDENTIDAD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: AR_CUIT_DV

PATTERNS, TRIED IN ORDER

(.*)	keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_IDENTIDAD_GENERO_LISTA .

Used by: AR_L3_IDENTIDAD_GENERO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_IDENTIDAD_GENERO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in ar-identidades-genero.txt , chosen by a keyed hash.

Used by: AR_IDENTIDAD_GENERO

CONFIGURATION

lookupFile	ar-identidades-genero.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_INGRESOS NUMERIC MAPPING

Maps the number to another between 300,000 and 30,000,000.

Used by: AR_FIN_INGRESOS

CONFIGURATION

minValue	300000
maxValue	30000000

AR_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_CM_HEX .

Used by: AR_L1_IP

PATTERNS, TRIED IN ORDER

(\d{1,3})\.\(\d{1,3})\.\(\d{1,3})\.\(\d{1,3})	AR_OCTETO · AR_OCTETO · AR_OCTETO · AR_OCTETO
otherwise	AR_CM_HEX

CONFIGURATION

trimInput	yes
requireMask	no

AR LENGUA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_LENGUA_LISTA .

Used by: AR_L3_LENGUA_INDIGENA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_LENGUA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_LENGUA_LISTA SECURE LOOKUP

Replaces the value with one of the 12 values in ar-lenguas.txt , chosen by a keyed hash.

Used by: AR_LENGUA

CONFIGURATION

lookupFile	ar-lenguas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_LOCALIDAD DATA CLEANSING

Replaces each value found in ar-localidades-generalizadas.txt (55,794 pairs) by its counterpart; values not in the file stay as they are.

Used by: AR_L2_LOCALIDAD

CONFIGURATION

lookupFile	ar-localidades-generalizadas.txt
delimiter	
caseSensitive	yes

trimWhitespace	yes
----------------	-----

AR_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_MEDICAMENTO_LISTA .

Used by: AR_SALUD_MEDICAMENTO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_MEDICAMENTO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 24 values in ar-medicamentos.txt , chosen by a keyed hash.

Used by: AR_MEDICAMENTO

CONFIGURATION

lookupFile	ar-medicamentos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_MONOTRIBUTO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: AR_FIN_MONOTRIBUTO

PATTERNS, TRIED IN ORDER

(?i)(categor[ií]a\s*)([A-D])	keep · AR_MONOTRIBUTO_A_D
(?i)(categor[ií]a\s*)([E-H])	keep · AR_MONOTRIBUTO_E_H
(?i)(categor[ií]a\s*)([I-K])	keep · AR_MONOTRIBUTO_I_K
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_MONOTRIBUTO_A_D SECURE LOOKUP

Replaces the value with one of the 4 values in ar-monotributo-a-d.txt , chosen by a keyed hash.

Used by: AR_MONOTRIBUTO

CONFIGURATION

lookupFile	ar-monotributo-a-d.txt
hashMethod	SHA256

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_MONOTRIBUTO_E_H SECURE LOOKUP

Replaces the value with one of the 4 values in `ar-monotributo-e-h.txt` , chosen by a keyed hash.

Used by: `AR_MONOTRIBUTO`

CONFIGURATION

lookupFile	ar-monotributo-e-h.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_MONOTRIBUTO_I_K SECURE LOOKUP

Replaces the value with one of the 3 values in `ar-monotributo-i-k.txt` , chosen by a keyed hash.

Used by: `AR_MONOTRIBUTO`

CONFIGURATION

lookupFile	ar-monotributo-i-k.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 14 values in `ar-nacionalidades.txt` , chosen by a keyed hash.

Used by: `AR_L2_NACIONALIDAD`

CONFIGURATION

lookupFile	ar-nacionalidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_NIVEL_EDUCATIVO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`AR_NIVEL_EDUCATIVO_LISTA` .

Used by: `AR_L2_NIVEL_EDUCATIVO`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>AR_BANDERA</code>
---	-------------------------

(\d{1,6})	AR_NIVEL_EDUCATIVO_CODIGO
otherwise	AR_NIVEL_EDUCATIVO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_NIVEL_EDUCATIVO_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in ar-nivel-educativo-codigos.txt , chosen by a keyed hash.

Used by: AR_NIVEL_EDUCATIVO

CONFIGURATION

lookupFile	ar-nivel-educativo-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_NIVEL_EDUCATIVO_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in ar-nivel-educativo.txt , chosen by a keyed hash.

Used by: AR_NIVEL_EDUCATIVO

CONFIGURATION

lookupFile	ar-nivel-educativo.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_NOMBRE NAME

Replaces the name with one of the 756 names in ar-nombres.txt .

Used by: AR_PALABRA_NOMBRE

CONFIGURATION

lookupFile	ar-nombres.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

AR_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: AR_CM_ALFANUM .

Used by: AR_L1_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

([^,]+), \s*(.+)	AR_APELLIDOS · AR_NOMBRES
(\S+)	AR_PALABRA_NOMBRE
(\S+)\s+(\S+)	AR_PALABRA_NOMBRE · AR_PALABRA_APELLIDO

(\S+)\s+(\S+)\s+(\S+)	AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE · AR_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE · AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE · AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE · AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO · AR_PALABRA_APELLIDO
otherwise	AR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

AR_NOMBRES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: AR_CM_ALFANUM .

Used by: AR_L1_NOMBRE , AR_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(\S+)	AR_PALABRA_NOMBRE
(\S+)\s+(\S+)	AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE
(\S+)\s+(\S+)\s+(\S+)	AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE · AR_PALABRA_NOMBRE
otherwise	AR_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

AR_OBRA_SOCIAL SECURE LOOKUP

Replaces the value with one of the 19 values in ar-obras-sociales.txt , chosen by a keyed hash.

Used by: AR_COBERTURA_SALUD

CONFIGURATION

lookupFile	ar-obras-sociales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: AR_IP

CONFIGURATION

minValue	1
maxValue	254

AR_OCUPACION SECURE LOOKUP

Replaces the value with one of the 35 values in `ar-ocupaciones.txt` , chosen by a keyed hash.

Used by: `AR_OCUPACION_O_CODIGO`

CONFIGURATION

lookupFile	ar-ocupaciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_OCUPACION_O_CODIGO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `AR_OCUPACION` .

Used by: `AR_L2_OCUPACION`

PATTERNS, TRIED IN ORDER

<code>(\d{2,5})</code>	<code>AR_CM_DIGITOS</code>
otherwise	<code>AR_OCUPACION</code>

CONFIGURATION

trimInput	yes
requireMask	no

AR_OPINION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`AR_OPINION_POLITICA_LISTA` .

Used by: `AR_L3_OPINION_POLITICA`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[íí] no true false yes [snyx01])</code>	<code>AR_BANDERA</code>
<code>(\d{1,6})</code>	<code>AR_CM_ALFANUM</code>
otherwise	<code>AR_OPINION_POLITICA_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

AR_OPINION_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `ar-opiniones-politicas.txt` , chosen by a keyed hash.

Used by: `AR_OPINION_POLITICA`

CONFIGURATION

lookupFile	ar-opiniones-politicas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

AR_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_ORIENTACION_SEXUAL_LISTA .

Used by: AR_L3_ORIENTACION_SEXUAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_ORIENTACION_SEXUAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in ar-orientaciones-sexuales.txt , chosen by a keyed hash.

Used by: AR_ORIENTACION_SEXUAL

CONFIGURATION

lookupFile	ar-orientaciones-sexuales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_ORIGEN_ETNICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_ORIGEN_ETNICO_LISTA .

Used by: AR_L3_ORIGEN_ETNICO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_ORIGEN_ETNICO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_ORIGEN_ETNICO_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in ar-origen-etnico.txt , chosen by a keyed hash.

Used by: AR_ORIGEN_ETNICO

CONFIGURATION

lookupFile	ar-origen-etnico.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_APELLIDO .

Used by: AR_APELLIDOS , AR_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(?i) (de del la las los y e san santa van von di da dos)	keep
otherwise	AR_APELLIDO

CONFIGURATION

trimInput	yes
requireMask	no

AR_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: AR_NOMBRE .

Used by: AR_NOMBRES , AR_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(?i) (de del la las los y e san santa van von di da dos)	keep
otherwise	AR_NOMBRE

CONFIGURATION

trimInput	yes
requireMask	no

AR_PARTIDO_POLITICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_PARTIDO_POLITICO_LISTA .

Used by: AR_L3_AFILIACION_PARTIDARIA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_PARTIDO_POLITICO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_PARTIDO_POLITICO_LISTA SECURE LOOKUP

Replaces the value with one of the 29 values in ar-partidos-politicos.txt , chosen by a keyed hash.

Used by: AR_PARTIDO_POLITICO

CONFIGURATION

lookupFile	ar-partidos-politicos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_PATRIMONIO NUMERIC MAPPING

Maps the number to another between 1,000,000 and 3,000,000,000.

Used by: AR_FIN_PATRIMONIO

CONFIGURATION

minValue	1000000
maxValue	3000000000

AR_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches:

AR_PROCEDIMIENTO_TEXTO .

Used by: AR_SALUD_PROCEDIMIENTO

PATTERNS, TRIED IN ORDER

(\d{2}\.?\d{2}\.?\d{2})	AR_CM_DIGITOS
otherwise	AR_PROCEDIMIENTO_TEXTO

CONFIGURATION

trimInput	yes
requireMask	no

AR_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in ar-procedimientos.txt , chosen by a keyed hash.

Used by: AR_PROCEDIMIENTO

CONFIGURATION

lookupFile	ar-procedimientos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_PROGRAMA_SOCIAL_LISTA .

Used by: AR_FIN_PROGRAMA_SOCIAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM

otherwise	AR_PROGRAMA_SOCIAL_LISTA
-----------	--------------------------

CONFIGURATION

trimInput	yes
requireMask	no

AR_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in ar-programas-sociales.txt , chosen by a keyed hash.

Used by: AR_PROGRAMA_SOCIAL

CONFIGURATION

lookupFile	ar-programas-sociales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_PUEBLO_INDIGENA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_PUEBLO_INDIGENA_LISTA .

Used by: AR_L3_PUEBLO_INDIGENA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_PUEBLO_INDIGENA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_PUEBLO_INDIGENA_LISTA SECURE LOOKUP

Replaces the value with one of the 20 values in ar-pueblos-indigenas.txt , chosen by a keyed hash.

Used by: AR_PUEBLO_INDIGENA

CONFIGURATION

lookupFile	ar-pueblos-indigenas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: AR_L1_CREDENCIAL , AR_L3_BIOMETRICO , AR_L3_GENETICO

PATTERNS, TRIED IN ORDER

(.+)	each character → X
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: AR_RELIGION_LISTA .

Used by: AR_L3_RELIGION

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_RELIGION_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in ar-religiones.txt , chosen by a keyed hash.

Used by: AR_RELIGION

CONFIGURATION

lookupFile	ar-religiones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SALUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_SALUD_LABORAL_LISTA .

Used by: AR_SALUD_OCUPACIONAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_SALUD_LABORAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_SALUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in ar-aptitud-laboral.txt , chosen by a keyed hash.

Used by: AR_SALUD_LABORAL

CONFIGURATION

lookupFile	ar-aptitud-laboral.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SEX0 REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: AR_L2_SEX0

PATTERNS, TRIED IN ORDER

(?i)(femenino masculino no\s+binario)	AR_SEX0_FEMENINO_MASCULINO
(?i)(mujer var[ó]n hombre)	AR_SEX0_MUJER_VARON
(?i)(female male)	AR_SEX0_FEMALE_MALE
(?i)([fmx])	AR_SEX0_F_M
([12])	AR_SEX0_1_2
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_SEX0_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in ar-sexo-1-2.txt , chosen by a keyed hash.

Used by: AR_SEX0

CONFIGURATION

lookupFile	ar-sexo-1-2.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SEX0_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in ar-sexo-f-m.txt , chosen by a keyed hash.

Used by: AR_SEX0

CONFIGURATION

lookupFile	ar-sexo-f-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SEXO_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-sexo-female-male.txt` , chosen by a keyed hash.

Used by: `AR_SEX0`

CONFIGURATION

lookupFile	ar-sexo-female-male.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SEXO_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-sexo-femenino-masculino.txt` , chosen by a keyed hash.

Used by: `AR_SEX0`

CONFIGURATION

lookupFile	ar-sexo-femenino-masculino.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SEXO_MUJER_VARON SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-sexo-mujer-varon.txt` , chosen by a keyed hash.

Used by: `AR_SEX0`

CONFIGURATION

lookupFile	ar-sexo-mujer-varon.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SITUACION_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-situacion-1-2.txt` , chosen by a keyed hash.

Used by: `AR_SITUACION_CREDITICIA`

CONFIGURATION

lookupFile	ar-situacion-1-2.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SITUACION_3_4 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-situacion-3-4.txt` , chosen by a keyed hash.

Used by: `AR_SITUACION_CREDITICIA`

CONFIGURATION

lookupFile	ar-situacion-3-4.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SITUACION_5_6 SECURE LOOKUP

Replaces the value with one of the 2 values in `ar-situacion-5-6.txt` , chosen by a keyed hash.

Used by: `AR_SITUACION_CREDITICIA`

CONFIGURATION

lookupFile	ar-situacion-5-6.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_SITUACION_CREDITICIA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: `AR_ESTADO_CREDITO` .

Used by: `AR_FIN_SITUACION_CREDITICIA`

PATTERNS, TRIED IN ORDER

<code>(?i)(situaci[oó]n\s*)?([12])</code>	keep · <code>AR_SITUACION_1_2</code>
<code>(?i)(situaci[oó]n\s*)?([34])</code>	keep · <code>AR_SITUACION_3_4</code>
<code>(?i)(situaci[oó]n\s*)?([56])</code>	keep · <code>AR_SITUACION_5_6</code>
<code>(\d{2,4})</code>	<code>AR_CM_DIGITOS</code>
<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>AR_BANDERA</code>
otherwise	<code>AR_ESTADO_CREDITO</code>

CONFIGURATION

trimInput	yes
requireMask	no

AR_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `ar-sin-informacion.txt` , chosen by a keyed hash.

Used by: `AR_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	ar-sin-informacion.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: AR_L1_TARJETA

PATTERNS, TRIED IN ORDER

(\d[\d\s\-\-]{11,22}\d)	AR_TARJETA_LUHN
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

AR_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: AR_TARJETA

CONFIGURATION

minMaskedPositions	6
preserve	0

AR_TELEFONO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: AR_CM_DIGITOS .

Used by: AR_L1_TELEFONO

PATTERNS, TRIED IN ORDER

(\+?54[\s\-\-]?(?:9[\s\-\-])?)?(\\(?:0?(?:11 [23]\d{1,3}))\)?[\s\-\-]+)(15[\s\-\-])?(\d{2,4})([\s\-\-])?(\d{4})	keep · keep · keep · AR_CM_DIGITOS · keep · AR_CM_DIGITOS
(\+?54[\s\-\-]?(?:9[\s\-\-])?)? 0?(11 [23]\d{2,3})(\d{6,8})	keep · keep · AR_CM_DIGITOS
(15[\s\-\-])?(\d{3,4})([\s\-\-])?(\d{4})	keep · AR_CM_DIGITOS · keep · AR_CM_DIGITOS
otherwise	AR_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

AR_TENENCIA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

AR_TENENCIA_VIVIENDA_LISTA .

Used by: AR_FIN_VIVIENDA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	AR_BANDERA
(\d{1,6})	AR_CM_ALFANUM
otherwise	AR_TENENCIA_VIVIENDA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

AR_TENENCIA_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `ar-tenencia-vivienda.txt` , chosen by a keyed hash.

Used by: `AR_TENENCIA_VIVIENDA`

CONFIGURATION

lookupFile	<code>ar-tenencia-vivienda.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

AR_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 10 patterns with `[DATO]` , and the 2,670 terms of `ar-texto-nombres.txt` with `[NOMBRE]` .

Used by: `AR_L1_TEXTO_LIBRE` , `AR_SALUD_TEXTO_CLINICO`

PATTERNS, TRIED IN ORDER

<code>(?<![\d.])\d{1,2}\.\d{3}\.\d{3}(?![\d.])</code>
<code>(?<!\d)(20 2[347] 3[034])-\d{8}-\d(?!\\d)</code>
<code>(?<!\d)\d{7,8}(?!\\d)</code>
<code>(?<!\d)\d{22}(?!\\d)</code>
<code>[\w.+\\-]+@[\\w\\-]+(\\. [\\w\\-]+)+</code>
<code>(?<![\\d\\-])(\\+?549?)?(11 [23]\\d{2,3})(15)?\\d{6,8}(?![\\d\\-])</code>
<code>(?<![\\d\\-])(15-)?\\d{4}-\\d{4}(?![\\d\\-])</code>
<code>(?<!\d)\d{13,19}(?!\\d)</code>
<code>(?<![A-Za-z])([A-Z]{2}\\d{3}[A-Z]{2} [A-Z]{3}\\d{3} [A-Z]\\d{3}[A-Z]{3})(?![A-Za-z\\d])</code>
<code>(?<!\d)(\\d{1,3}\\.){3}\\d{1,3}(?!\\d)</code>

CONFIGURATION

regexRedactValue	<code>[DATO]</code>
lookupFile	<code>ar-texto-nombres.txt</code>
lookupFileRedactValue	<code>[NOMBRE]</code>
isDenyList	yes

AR_VALOR_DEUDA NUMERIC MAPPING

Maps the number to another between 10,000 and 500,000,000.

Used by: `AR_FIN_DEUDA`

CONFIGURATION

minValue	<code>10000</code>
maxValue	<code>500000000</code>

AR_VALOR_JUBILACION NUMERIC MAPPING

Maps the number to another between 250,000 and 12,000,000.

Used by: AR_FIN_JUBILACION

CONFIGURATION

minValue	250000
maxValue	12000000

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
ar- antecedentes.txt	8	AR_ANTECEDENTES_LISTA	No registra antecedentes · Registra antecedentes · Imputado · Procesado
ar-apellidos.txt	408	AR_APELLIDO	González · Rodríguez · Gómez · Fernández
ar-aptitud- laboral.txt	4	AR_SALUD_LABORAL_LISTA	Apto · Apto con preexistencias · No apto · Pendiente
ar-bandera-0- 1.txt	2	AR_BANDERA_0_1	0 · 1
ar-bandera-s- n.txt	2	AR_BANDERA_S_N	S · N
ar-bandera-si- no.txt	2	AR_BANDERA_SI_NO	Sí · No
ar-bandera-true- false.txt	2	AR_BANDERA_TRUE_FALSE	true · false
ar-bandera-y- n.txt	2	AR_BANDERA_Y_N	Y · N
ar-bandera-yes- no.txt	2	AR_BANDERA_YES_NO	Yes · No
ar-barrios.txt	124	AR_BARRIO	Agronomía · Almagro · Balvanera · Barracas
ar-cie10- decimal.txt	33	AR_CIE10_DECIMAL	E11.9 · E78.5 · J45.9 · J06.9
ar-cie10.txt	37	AR_CIE10	I10 · E11 · E78 · J45
ar-codigos- geograficos- generalizados.txt	5,070	AR_CODIGO_GEOGRAFICO	06007 06700 · 06014 06084 · 06021 06112 · 06140 06077
ar-departamentos- generalizados.txt	3,254	AR_DEPARTAMENTO	Adolfo Gonzales Chaves Benito Juárez · Alberti Bragado · Capitán Sarmiento Arrecifes · Carlos Tejedor Pehuajó
ar-detectar- apellidos.txt	477	AR_L1_APELLIDO – List AR_L1_NOMBRE_COMPLETO – List	González · Gonzalez · Rodríguez · Rodriguez
ar-detectar- aptitud- laboral.txt	5	AR_SALUD_OCUPACIONAL – List	apto · no apto · apto con preexistencias · pendiente
ar-detectar- cobertura.txt	42	AR_SALUD_COBERTURA – List	PAMI · IOMA · OSDE · Swiss Medical
ar-detectar- codigos- banderas.txt	11	AR_L3_ORIGEN_ETNICO – List AR_FIN_PROGRAMA_SOCIAL – List	s · n · sí · si

FILE	LINES	USED BY	FIRST LINES
ar-detectar-departamentos.txt	532	AR_L2_DEPARTAMENTO – List	Adolfo Alsina · Adolfo Gonzales Chaves · Alberti · Almirante Brown
ar-detectar-discapacidades.txt	23	AR_SALUD_DISCAPACIDAD – List	Motora · Auditiva · Visual · Visceral
ar-detectar-estado-civil.txt	21	AR_L2_ESTADO_CIVIL – List	Soltero/a · Casado/a · Unión convivencial · Union convivencial
ar-detectar-grupos-sanguineos.txt	20	AR_SALUD_GRUPO_SANGUINEO – List	A+ · A- · B+ · B-
ar-detectar-identidades-genero.txt	24	AR_L3_IDENTIDAD_GENERO – List	Mujer cis · Varón cis · Varon cis · Mujer trans / travesti
ar-detectar-lenguas.txt	37	AR_L3 LENGUA_INDIGENA – List	Español · Espanol · Guaraní · Guarani
ar-detectar-localidades.txt	4,816	AR_L2_LOCALIDAD – List	Adolfo Alsina · Adolfo Gonzales Chaves · Alberti · Almirante Brown
ar-detectar-medicamentos.txt	55	AR_SALUD_MEDICAMENTO – List	Paracetamol · Ibuprofeno · Diclofenac · Dipirona
ar-detectar-nacionalidades.txt	45	AR_L2_NACIONALIDAD – List	Argentina · Paraguay · Boliviana · Venezolana
ar-detectar-nivel-educativo.txt	21	AR_L2_NIVEL_EDUCATIVO – List	Sin instrucción · Sin instruccion · Primario incompleto · Primario completo
ar-detectar-nombres.txt	876	AR_L1_NOMBRE – List AR_L1_NOMBRE_COMPLETO – List	María · Maria · Juan · José
ar-detectar-opiniones-politicas.txt	22	AR_L3_OPINION_POLITICA – List	Izquierda · Centroizquierda · Centro · Centroderecha
ar-detectar-orientaciones-sexuales.txt	14	AR_L3_ORIENTACION_SEXUAL – List	Heterosexual · Gay · Lesbiana · Bisexual
ar-detectar-origen-etnico.txt	18	AR_L3_ORIGEN_ETNICO – List	Indígena o descendiente de pueblos indígenas u originarios · Indigena o descendiente de pueblos indigenas u originarios · Afrodescendiente · Ninguno
ar-detectar-partidos-politicos.txt	54	AR_L3_AFILIACION_PARTIDARIA – List	Partido Justicialista · Unión Cívica Radical · Union Civica Radical · Propuesta Republicana (PRO)
ar-detectar-programas-sociales.txt	36	AR_FIN_PROGRAMA_SOCIAL – List	Asignación Universal por Hijo · Asignacion Universal por Hijo · Asignación por Embarazo · Asignacion por Embarazo
ar-detectar-pueblos-indigenas.txt	93	AR_L3_PUEBLO_INDIGENA – List	Mapuche · Guaraní · Guarani · Diaguita
ar-detectar-religiones.txt	41	AR_L3_RELIGION – List	Católica · Catolica · Evangélica · Evangelica
ar-detectar-sexo.txt	12	AR_L2_SEX0 – List	f · m · x · femenino

FILE	LINES	USED BY	FIRST LINES
ar-detectar-sindicatos.txt	37	AR_L3_AFILIACION_SINDICAL - List	CGT · CTA · CTA-T · CTA-A
ar-detectar-situacion-crediticia.txt	22	AR_FIN_SITUACION_CREDITICIA - List	normal · riesgo bajo · riesgo medio · riesgo alto
ar-detectar-tenencia-vivienda.txt	18	AR_FIN_VIVIENDA - List	Propietario de la vivienda y el terreno · Propietario solo de la vivienda · Inquilino · Ocupante por préstamo
ar-diagnosticos.txt	30	AR_DIAGNOSTICO_TEXTO	Hipertensión arterial · Diabetes mellitus tipo 2 · Asma · Lumbalgia
ar-direcciones.txt	4,000	AR_DIRECCION	Calle 130 N° 1082 · Estrada 335 PB 1 · Calle 23 N° 2702 · Estrada 765
ar-discapacidades.txt	8	AR_DISCAPACIDAD_TIPO	Motora · Auditiva · Visual · Visceral
ar-empleadores.txt	24	AR_EMPLEADOR	Comercializadora del Plata S.A. · Construcciones Andinas S.R.L. · Transportes La Pampa S.A. · Supermercados El Hornero S.A.
ar-empresas.txt	24	AR_EMPRESA	Comercializadora del Plata S.A. · Construcciones Andinas S.R.L. · Transportes La Pampa S.A. · Supermercados El Hornero S.A.
ar-establecimientos-educativos.txt	12	AR_ESTABLECIMIENTO_EDUCATIVO	Escuela N° 12 Domingo F. Sarmiento · Escuela Primaria N° 45 · Escuela de Educación Secundaria N° 3 · Escuela Técnica N° 8
ar-estado-civil-codigos.txt	6	AR_ESTADO_CIVIL_CODIGO	1 · 2 · 3 · 4
ar-estado-civil.txt	6	AR_ESTADO_CIVIL_LISTA	Soltero/a · Casado/a · Unión convivencial · Separado/a de hecho
ar-estados-credito.txt	10	AR_ESTADO_CREDITO	Normal · Riesgo bajo · Riesgo medio · Riesgo alto
ar-grupos-sanguineos.txt	8	AR_GRUPO_SANGUINEO	A+ · A- · B+ · B-
ar-identidades-genero.txt	7	AR_IDENTIDAD_GENERO_LISTA	Mujer cis · Varón cis · Mujer trans / travesti · Varón trans / masculinidad trans
ar-lenguas.txt	12	AR LENGUA LISTA	Español · Guaraní · Quechua · Mapuzungun
ar-localidades-generalizadas.txt	55,794	AR_LOCALIDAD	Adolfo Alsina Saavedra · Adolfo Gonzales Chaves Benito Juárez · Alberti Bragado · Capitán Sarmiento Arrecifes
ar-medicamentos.txt	24	AR_MEDICAMENTO_LISTA	Paracetamol · Ibuprofeno · Diclofenac · Dipirona
ar-monotributo-a-d.txt	4	AR_MONOTRIBUTO_A_D	A · B · C · D
ar-monotributo-e-h.txt	4	AR_MONOTRIBUTO_E_H	E · F · G · H
ar-monotributo-i-k.txt	3	AR_MONOTRIBUTO_I_K	I · J · K
ar-nacionalidades.txt	14	AR_NACIONALIDAD	Argentina · Paraguay · Boliviana · Venezolana

FILE	LINES	USED BY	FIRST LINES
ar-nivel-educativo-codigos.txt	10	AR_NIVEL_EDUCATIVO_CODIGO	1 · 2 · 3 · 4
ar-nivel-educativo.txt	10	AR_NIVEL_EDUCATIVO_LISTA	Sin instrucción · Primario incompleto · Primario completo · Secundario incompleto
ar-nombres.txt	756	AR_NOMBRE	María · Juan · José · Carlos
ar-obras-sociales.txt	19	AR_OBRA_SOCIAL	PAMI · IOMA · OSDE · Swiss Medical
ar-ocupaciones.txt	35	AR_OCUPACION	Empleado administrativo · Vendedor · Cajero · Chofer
ar-opiniones-politicas.txt	7	AR_OPINION_POLITICA_LISTA	Izquierda · Centroizquierda · Centro · Centroderecha
ar-orientaciones-sexuales.txt	8	AR_ORIENTACION_SEXUAL_LISTA	Heterosexual · Gay · Lesbiana · Bisexual
ar-origen-etnico.txt	4	AR_ORIGEN_ETNICO_LISTA	Indígena o descendiente de pueblos indígenas u originarios · Afrodescendiente · Ninguno · Prefiere no responder
ar-partidos-politicos.txt	29	AR_PARTIDO_POLITICO_LISTA	Partido Justicialista · Unión Cívica Radical · Propuesta Republicana (PRO) · La Libertad Avanza
ar-procedimientos.txt	10	AR_PROCEDIMIENTO_TEXTO	Consulta médica en consultorio · Consulta de guardia · Hemograma completo · Glucemia
ar-programas-sociales.txt	13	AR_PROGRAMA_SOCIAL_LISTA	Asignación Universal por Hijo · Asignación por Embarazo · Prestación Alimentar · Progresar
ar-pueblos-indigenas.txt	20	AR_PUEBLO_INDIGENA_LISTA	Mapuche · Guaraní · Diaguita · Kolla
ar-religiones.txt	11	AR_RELIGION_LISTA	Católica · Evangélica · Pentecostal · Testigo de Jehová
ar-sexo-1-2.txt	2	AR_SEXO_1_2	1 · 2
ar-sexo-f-m.txt	2	AR_SEXO_F_M	F · M
ar-sexo-female-male.txt	2	AR_SEXO_FEMALE_MALE	Female · Male
ar-sexo-femenino-masculino.txt	2	AR_SEXO_FEMENINO_MASCULINO	Femenino · Masculino
ar-sexo-mujer-varon.txt	2	AR_SEXO_MUJER_VARON	Mujer · Varón
ar-sin-informacion.txt	1	AR_SUPRIMIR	Sin información
ar-situacion-1-2.txt	2	AR_SITUACION_1_2	1 · 2
ar-situacion-3-4.txt	2	AR_SITUACION_3_4	3 · 4
ar-situacion-5-6.txt	2	AR_SITUACION_5_6	5 · 6
ar-tenencia-vivienda.txt	6	AR_TENENCIA_VIVIENDA_LISTA	Propietario de la vivienda y el terreno · Propietario solo de la vivienda · Inquilino · Ocupante por préstamo
ar-texto-nombres.txt	2,670	AR_TEXTO_LIBRE	María · MARÍA · Maria · MARIA

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 producto prod item articulo empresa emp razon social fantasia comercial archivo calle via barrio localidad municipio ciudad partido departamento depto dpto provincia pais banco sucursal plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo colegio escuela establecimiento institucion curso materia documento doc centro unidad clinica hospital sanatorio obra prepaga area dependencia reparticion cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa beneficio sindicato gremio religion pueblo lengua lugar sede local tienda deposito proveedor convenio contrato poliza seguro aseguradora entidad organismo organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura comprobante pago forma zona ruta linea actividad rubro sector file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado agente trabajador contratado alumno estudiante deudor codeudor garante fiador tomador propietario inquilino locatario locador conductor tutor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge concubino conviviente contacto referencia victima denunciante denunciado imputado procesado testigo medico docente socio heredero causante donante curador jubilado pensionado customer patient employee member holder mother father spouse contact person student driver owner completo apellidos? usuario corto largo

E2 producto prod item articulo empresa emp razon social fantasia comercial archivo calle via barrio localidad municipio ciudad partido departamento depto dpto provincia pais banco sucursal plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo colegio escuela establecimiento institucion curso materia documento doc centro unidad clinica hospital sanatorio obra prepaga area dependencia reparticion cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa beneficio sindicato gremio religion pueblo lengua lugar sede local tienda deposito proveedor convenio contrato poliza seguro aseguradora entidad organismo organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura comprobante pago forma zona ruta linea actividad rubro sector file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado agente trabajador contratado alumno estudiante deudor codeudor garante fiador tomador propietario inquilino locatario locador conductor tutor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge concubino conviviente contacto referencia victima denunciante denunciado imputado procesado testigo medico docente socio heredero causante donante curador jubilado pensionado customer patient employee member holder mother father spouse contact person student driver owner

E3 producto prod item articulo empresa emp razon social fantasia comercial archivo calle via barrio localidad municipio ciudad partido departamento depto dpto provincia pais banco sucursal plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo colegio escuela establecimiento institucion curso materia documento doc centro unidad clinica hospital sanatorio obra prepaga area dependencia reparticion cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa beneficio sindicato gremio religion pueblo lengua lugar sede local tienda deposito proveedor convenio contrato poliza seguro aseguradora entidad organismo organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura comprobante pago forma zona ruta linea actividad rubro sector file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado agente trabajador contratado alumno estudiante deudor codeudor garante fiador tomador propietario inquilino locatario locador conductor tutor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge concubino conviviente contacto referencia victima denunciante denunciado imputado procesado testigo medico docente socio heredero causante donante curador jubilado pensionado customer patient employee member holder mother father spouse contact person student driver owner full complete last first

E4 ip mac email e_?mail correo electr[ó]nica web url tipo id general nacional provincial t[eé]cnica regional

E5 ip mac email e_?mail web url type id

E6 producto catastral primaria for[aá]nea valor bancaria virtual [uú]nica

E7 id cd cod codigo tipo fecha estado num nro

E8 id tipo codigo fecha estado cola log

APPENDIX D

Profile set and classifiers

The profile set `AR - Ley 25.326 - v1` runs these 148 classifiers, with an assignment threshold of 60%.

Identificadores directos, cuasi-identificadores, datos sensibles (arts. 2 y 7), datos genéticos y biométricos, identidad de género, datos de salud, datos financieros (art. 26) y antecedentes penales, conforme a la Ley 25.326 de Protección de los Datos Personales.

CLASSIFIER	KIND	DOMAIN
AR_L1_DNI - Path	COLUMN NAME	AR_L1_DNI
AR_L1_DNI - Type	DATA TYPE	AR_L1_DNI
AR_L1_DNI - Regex	VALUE FORMAT	AR_L1_DNI
AR_L1_CUIT - Path	COLUMN NAME	AR_L1_CUIT
AR_L1_CUIT - Regex	VALUE FORMAT	AR_L1_CUIT
AR_L1_TRAMITE_DNI - Path	COLUMN NAME	AR_L1_TRAMITE_DNI
AR_L1_TRAMITE_DNI - Regex	VALUE FORMAT	AR_L1_TRAMITE_DNI
AR_L1_DOCUMENTO_EXTRANJERO - Path	COLUMN NAME	AR_L1_DOCUMENTO_EXTRANJERO
AR_L1_PASAPORTE - Path	COLUMN NAME	AR_L1_PASAPORTE
AR_L1_PASAPORTE - Regex	VALUE FORMAT	AR_L1_PASAPORTE
AR_L1_REGISTRO_CIVIL - Path	COLUMN NAME	AR_L1_REGISTRO_CIVIL
AR_L1_MATRICULA_PROFESIONAL - Path	COLUMN NAME	AR_L1_MATRICULA_PROFESIONAL
AR_L1_NOMBRE - Path	COLUMN NAME	AR_L1_NOMBRE
AR_L1_NOMBRE - List	KNOWN VALUES	AR_L1_NOMBRE
AR_L1_APELLIDO - Path	COLUMN NAME	AR_L1_APELLIDO
AR_L1_APELLIDO - List	KNOWN VALUES	AR_L1_APELLIDO
AR_L1_NOMBRE_COMPLETO - Path	COLUMN NAME	AR_L1_NOMBRE_COMPLETO
AR_L1_NOMBRE_COMPLETO - List	KNOWN VALUES	AR_L1_NOMBRE_COMPLETO
AR_L1_RAZON_SOCIAL - Path	COLUMN NAME	AR_L1_RAZON_SOCIAL
AR_L1_RAZON_SOCIAL - Regex	VALUE FORMAT	AR_L1_RAZON_SOCIAL
AR_L1_EMAIL - Path	COLUMN NAME	AR_L1_EMAIL
AR_L1_EMAIL - Type	DATA TYPE	AR_L1_EMAIL
AR_L1_EMAIL - Regex	VALUE FORMAT	AR_L1_EMAIL
AR_L1_TELEFONO - Path	COLUMN NAME	AR_L1_TELEFONO
AR_L1_TELEFONO - Regex	VALUE FORMAT	AR_L1_TELEFONO
AR_L1_DIRECCION - Path	COLUMN NAME	AR_L1_DIRECCION
AR_L1_DIRECCION - Type	DATA TYPE	AR_L1_DIRECCION
AR_L1_DIRECCION - Regex	VALUE FORMAT	AR_L1_DIRECCION
AR_L1_DIRECCION_COMPLEMENTO - Path	COLUMN NAME	AR_L1_DIRECCION_COMPLEMENTO
AR_L1_CBU - Path	COLUMN NAME	AR_L1_CBU

CLASSIFIER	KIND	DOMAIN
AR_L1_CBU – Regex	VALUE FORMAT	AR_L1_CBU
AR_L1_ALIAS_CBU – Path	COLUMN NAME	AR_L1_ALIAS_CBU
AR_L1_ALIAS_CBU – Regex	VALUE FORMAT	AR_L1_ALIAS_CBU
AR_L1_CUENTA_BANCARIA – Path	COLUMN NAME	AR_L1_CUENTA_BANCARIA
AR_L1_TARJETA – Path	COLUMN NAME	AR_L1_TARJETA
AR_L1_TARJETA – Regex	VALUE FORMAT	AR_L1_TARJETA
AR_L1_IP – Path	COLUMN NAME	AR_L1_IP
AR_L1_IP – Regex	VALUE FORMAT	AR_L1_IP
AR_L1_DISPOSITIVO – Path	COLUMN NAME	AR_L1_DISPOSITIVO
AR_L1_DISPOSITIVO – Regex	VALUE FORMAT	AR_L1_DISPOSITIVO
AR_L1_DOMINIO – Path	COLUMN NAME	AR_L1_DOMINIO
AR_L1_DOMINIO – Regex	VALUE FORMAT	AR_L1_DOMINIO
AR_L1_VEHICULO – Path	COLUMN NAME	AR_L1_VEHICULO
AR_L1_VEHICULO – Regex	VALUE FORMAT	AR_L1_VEHICULO
AR_L1_INMUEBLE – Path	COLUMN NAME	AR_L1_INMUEBLE
AR_L1_CONTRATO – Path	COLUMN NAME	AR_L1_CONTRATO
AR_L1_USUARIO – Path	COLUMN NAME	AR_L1_USUARIO
AR_L1_CREDENCIAL – Path	COLUMN NAME	AR_L1_CREDENCIAL
AR_L1_GEOLOCALIZACION – Path	COLUMN NAME	AR_L1_GEOLOCALIZACION
AR_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	AR_L1_GEOLOCALIZACION
AR_L1_TEXTO_LIBRE – Path	COLUMN NAME	AR_L1_TEXTO_LIBRE
AR_L1_TEXTO_LIBRE – Type	DATA TYPE	AR_L1_TEXTO_LIBRE
AR_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	AR_L1_TEXTO_LIBRE
AR_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	AR_L2_FECHA_NACIMIENTO
AR_L2_FECHA_NACIMIENTO – Type	DATA TYPE	AR_L2_FECHA_NACIMIENTO
AR_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	AR_L2_ANIO_NACIMIENTO
AR_L2_ANIO_NACIMIENTO – Type	DATA TYPE	AR_L2_ANIO_NACIMIENTO
AR_L2_EDAD – Path	COLUMN NAME	AR_L2_EDAD
AR_L2_EDAD – Type	DATA TYPE	AR_L2_EDAD
AR_L2_FECHA_EVENTO – Path	COLUMN NAME	AR_L2_FECHA_EVENTO
AR_L2_FECHA_EVENTO – Type	DATA TYPE	AR_L2_FECHA_EVENTO
AR_L2_SEX0 – Path	COLUMN NAME	AR_L2_SEX0
AR_L2_SEX0 – List	KNOWN VALUES	AR_L2_SEX0
AR_L2_LOCALIDAD – Path	COLUMN NAME	AR_L2_LOCALIDAD
AR_L2_LOCALIDAD – List	KNOWN VALUES	AR_L2_LOCALIDAD
AR_L2_DEPARTAMENTO – Path	COLUMN NAME	AR_L2_DEPARTAMENTO
AR_L2_DEPARTAMENTO – List	KNOWN VALUES	AR_L2_DEPARTAMENTO

CLASSIFIER	KIND	DOMAIN
AR_L2_CODIGO_GEOGRAFICO - Path	COLUMN NAME	AR_L2_CODIGO_GEOGRAFICO
AR_L2_CODIGO_GEOGRAFICO - Regex	VALUE FORMAT	AR_L2_CODIGO_GEOGRAFICO
AR_L2_CODIGO_POSTAL - Path	COLUMN NAME	AR_L2_CODIGO_POSTAL
AR_L2_CODIGO_POSTAL - Type	DATA TYPE	AR_L2_CODIGO_POSTAL
AR_L2_CODIGO_POSTAL - Regex	VALUE FORMAT	AR_L2_CODIGO_POSTAL
AR_L2_BARRIO - Path	COLUMN NAME	AR_L2_BARRIO
AR_L2_NACIONALIDAD - Path	COLUMN NAME	AR_L2_NACIONALIDAD
AR_L2_NACIONALIDAD - List	KNOWN VALUES	AR_L2_NACIONALIDAD
AR_L2_ESTADO_CIVIL - Path	COLUMN NAME	AR_L2_ESTADO_CIVIL
AR_L2_ESTADO_CIVIL - List	KNOWN VALUES	AR_L2_ESTADO_CIVIL
AR_L2_OCUPACION - Path	COLUMN NAME	AR_L2_OCUPACION
AR_L2_EMPLEADOR - Path	COLUMN NAME	AR_L2_EMPLEADOR
AR_L2_NIVEL_EDUCATIVO - Path	COLUMN NAME	AR_L2_NIVEL_EDUCATIVO
AR_L2_NIVEL_EDUCATIVO - List	KNOWN VALUES	AR_L2_NIVEL_EDUCATIVO
AR_L2_ESTABLECIMIENTO_EDUCATIVO - Path	COLUMN NAME	AR_L2_ESTABLECIMIENTO_EDUCATIVO
AR_L2_PERSONAS_A_CARGO - Path	COLUMN NAME	AR_L2_PERSONAS_A_CARGO
AR_L2_PERSONAS_A_CARGO - Type	DATA TYPE	AR_L2_PERSONAS_A_CARGO
AR_L3_ORIGEN_ETNICO - Path	COLUMN NAME	AR_L3_ORIGEN_ETNICO
AR_L3_ORIGEN_ETNICO - List	KNOWN VALUES	AR_L3_ORIGEN_ETNICO
AR_L3_PUEBLO_INDIGENA - Path	COLUMN NAME	AR_L3_PUEBLO_INDIGENA
AR_L3_PUEBLO_INDIGENA - List	KNOWN VALUES	AR_L3_PUEBLO_INDIGENA
AR_L3 LENGUA_INDIGENA - Path	COLUMN NAME	AR_L3 LENGUA_INDIGENA
AR_L3 LENGUA_INDIGENA - List	KNOWN VALUES	AR_L3 LENGUA_INDIGENA
AR_L3_RELIGION - Path	COLUMN NAME	AR_L3_RELIGION
AR_L3_RELIGION - List	KNOWN VALUES	AR_L3_RELIGION
AR_L3_CONVICCION_FILOSOFICA - Path	COLUMN NAME	AR_L3_CONVICCION_FILOSOFICA
AR_L3_OPINION_POLITICA - Path	COLUMN NAME	AR_L3_OPINION_POLITICA
AR_L3_OPINION_POLITICA - List	KNOWN VALUES	AR_L3_OPINION_POLITICA
AR_L3_AFILIACION_PARTIDARIA - Path	COLUMN NAME	AR_L3_AFILIACION_PARTIDARIA
AR_L3_AFILIACION_PARTIDARIA - List	KNOWN VALUES	AR_L3_AFILIACION_PARTIDARIA
AR_L3_AFILIACION_SINDICAL - Path	COLUMN NAME	AR_L3_AFILIACION_SINDICAL
AR_L3_AFILIACION_SINDICAL - List	KNOWN VALUES	AR_L3_AFILIACION_SINDICAL
AR_L3_BIOMETRICO - Path	COLUMN NAME	AR_L3_BIOMETRICO
AR_L3_BIOMETRICO - Type	DATA TYPE	AR_L3_BIOMETRICO
AR_L3_GENETICO - Path	COLUMN NAME	AR_L3_GENETICO
AR_L3_ORIENTACION_SEXUAL - Path	COLUMN NAME	AR_L3_ORIENTACION_SEXUAL
AR_L3_ORIENTACION_SEXUAL - List	KNOWN VALUES	AR_L3_ORIENTACION_SEXUAL

CLASSIFIER	KIND	DOMAIN
AR_L3_VIDA_SEXUAL - Path	COLUMN NAME	AR_L3_VIDA_SEXUAL
AR_L3_IDENTIDAD_GENERO - Path	COLUMN NAME	AR_L3_IDENTIDAD_GENERO
AR_L3_IDENTIDAD_GENERO - List	KNOWN VALUES	AR_L3_IDENTIDAD_GENERO
AR_L3_VICTIMA - Path	COLUMN NAME	AR_L3_VICTIMA
AR_SALUD_IDENTIFICADOR - Path	COLUMN NAME	AR_SALUD_IDENTIFICADOR
AR_SALUD_COBERTURA - Path	COLUMN NAME	AR_SALUD_COBERTURA
AR_SALUD_COBERTURA - List	KNOWN VALUES	AR_SALUD_COBERTURA
AR_SALUD_COBERTURA - Regex	VALUE FORMAT	AR_SALUD_COBERTURA
AR_SALUD_DIAGNOSTICO - Path	COLUMN NAME	AR_SALUD_DIAGNOSTICO
AR_SALUD_DIAGNOSTICO - Regex	VALUE FORMAT	AR_SALUD_DIAGNOSTICO
AR_SALUD_PROCEDIMIENTO - Path	COLUMN NAME	AR_SALUD_PROCEDIMIENTO
AR_SALUD_MEDICAMENTO - Path	COLUMN NAME	AR_SALUD_MEDICAMENTO
AR_SALUD_MEDICAMENTO - List	KNOWN VALUES	AR_SALUD_MEDICAMENTO
AR_SALUD_TEXTO_CLINICO - Path	COLUMN NAME	AR_SALUD_TEXTO_CLINICO
AR_SALUD_TEXTO_CLINICO - Type	DATA TYPE	AR_SALUD_TEXTO_CLINICO
AR_SALUD_RESULTADO_ESTUDIO - Path	COLUMN NAME	AR_SALUD_RESULTADO_ESTUDIO
AR_SALUD_VIH - Path	COLUMN NAME	AR_SALUD_VIH
AR_SALUD_GRUPO_SANGUINEO - Path	COLUMN NAME	AR_SALUD_GRUPO_SANGUINEO
AR_SALUD_GRUPO_SANGUINEO - List	KNOWN VALUES	AR_SALUD_GRUPO_SANGUINEO
AR_SALUD_DISCAPACIDAD - Path	COLUMN NAME	AR_SALUD_DISCAPACIDAD
AR_SALUD_DISCAPACIDAD - List	KNOWN VALUES	AR_SALUD_DISCAPACIDAD
AR_SALUD_OCUPACIONAL - Path	COLUMN NAME	AR_SALUD_OCUPACIONAL
AR_SALUD_OCUPACIONAL - List	KNOWN VALUES	AR_SALUD_OCUPACIONAL
AR_SALUD_REPRODUCTIVA - Path	COLUMN NAME	AR_SALUD_REPRODUCTIVA
AR_SALUD_MENTAL - Path	COLUMN NAME	AR_SALUD_MENTAL
AR_FIN_SITUACION_CREDITICIA - Path	COLUMN NAME	AR_FIN_SITUACION_CREDITICIA
AR_FIN_SITUACION_CREDITICIA - List	KNOWN VALUES	AR_FIN_SITUACION_CREDITICIA
AR_FIN_DEUDA - Path	COLUMN NAME	AR_FIN_DEUDA
AR_FIN_DEUDA - Type	DATA TYPE	AR_FIN_DEUDA
AR_FIN_INGRESOS - Path	COLUMN NAME	AR_FIN_INGRESOS
AR_FIN_INGRESOS - Type	DATA TYPE	AR_FIN_INGRESOS
AR_FIN_PATRIMONIO - Path	COLUMN NAME	AR_FIN_PATRIMONIO
AR_FIN_PATRIMONIO - Type	DATA TYPE	AR_FIN_PATRIMONIO
AR_FIN_JUBILACION - Path	COLUMN NAME	AR_FIN_JUBILACION
AR_FIN_JUBILACION - Type	DATA TYPE	AR_FIN_JUBILACION
AR_FIN_PROGRAMA_SOCIAL - Path	COLUMN NAME	AR_FIN_PROGRAMA_SOCIAL
AR_FIN_PROGRAMA_SOCIAL - List	KNOWN VALUES	AR_FIN_PROGRAMA_SOCIAL

CLASSIFIER	KIND	DOMAIN
AR_FIN_MONOTRIBUTO – Path	COLUMN NAME	AR_FIN_MONOTRIBUTO
AR_FIN_MONOTRIBUTO – Type	DATA TYPE	AR_FIN_MONOTRIBUTO
AR_FIN_VIVIENDA – Path	COLUMN NAME	AR_FIN_VIVIENDA
AR_FIN_VIVIENDA – List	KNOWN VALUES	AR_FIN_VIVIENDA
AR_PENAL_ANTECEDENTES – Path	COLUMN NAME	AR_PENAL_ANTECEDENTES
AR_PENAL_EXPEDIENTE – Path	COLUMN NAME	AR_PENAL_EXPEDIENTE
AR_PENAL_EXPEDIENTE – Regex	VALUE FORMAT	AR_PENAL_EXPEDIENTE