

El Salvador — Ley para la Protección de Datos Personales

Discovery and masking of Salvadoran personal data: DUI and NIT with a valid check digit, quasi-identifiers, the sensitive data of article 4 g), the nationality of article 59 b), health data, financial data and criminal records.

85

DOMAINS

143

CLASSIFIERS

110

ALGORITHMS

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	About this profile set
2	Decreto 144 in brief
3	Dissociation, pseudonymization and non-production copies
4	How sensitive data is discovered
5	How data is masked
6	Essential and extended packs
7	Domains at a glance

PART 8 · DIRECT IDENTIFIERS

8.1	DUI	SV_L1_DUI
8.2	NIT	SV_L1_NIT
8.3	NRC	SV_L1_NRC
8.4	Foreigner documents	SV_L1_DOCUMENTO_EXTRANJERO
8.5	Passport	SV_L1_PASAPORTE
8.6	Civil registry records	SV_L1_PARTIDA
8.7	ISSS, AFP and pensions	SV_L1_SEGURO_SOCIAL
8.8	Student number	SV_L1_NIE
8.9	Professional registration	SV_L1_MATRICULA_PROFESIONAL
8.10	Given name	SV_L1_NOMBRE
8.11	Surname	SV_L1_APELLIDO
8.12	Full name	SV_L1_NOMBRE_COMPLETO
8.13	E-mail	SV_L1_EMAIL
8.14	Phone	SV_L1_TELEFONO
8.15	Address	SV_L1_DIRECCION
8.16	Address complement	SV_L1_DIRECCION_COMPLEMENTO
8.17	Bank account	SV_L1_CUENTA_BANCARIA
8.18	Payment card	SV_L1_TARJETA
8.19	Digital wallet and bitcoin	SV_L1_BILLETERA
8.20	IP address	SV_L1_IP
8.21	Device identifier	SV_L1_DISPOSITIVO
8.22	Cookies and tracking identifiers	SV_L1_COOKIE
8.23	Vehicle plate	SV_L1_PLACA
8.24	Vehicle and licence	SV_L1_VEHICULO

8.25	Property	SV_L1_INMUEBLE
8.26	Customer and contract numbers	SV_L1_CONTRATO
8.27	User and social media	SV_L1_USUARIO
8.28	Credentials	SV_L1_CREDENCIAL
8.29	Geolocation	SV_L1_GEOLOCALIZACION
8.30	Free text	SV_L1_TEXTO_LIBRE

PART 9 · QUASI-IDENTIFIERS

9.1	Birth date	SV_L2_FECHA_NACIMIENTO
9.2	Birth year	SV_L2_ANIO_NACIMIENTO
9.3	Age	SV_L2_EDAD
9.4	Personal event dates	SV_L2_FECHA_EVENTO
9.5	Sex	SV_L2_SEXO
9.6	Distrito and municipio	SV_L2_DISTRITO
9.7	Distrito and municipio codes	SV_L2_CODIGO_GEOGRAFICO
9.8	Cantón and caserío	SV_L2_CANTON
9.9	Colonia, residencial and barrio	SV_L2_COLONIA
9.10	Postal code	SV_L2_CODIGO_POSTAL
9.11	Family status	SV_L2_ESTADO_FAMILIAR
9.12	Occupation	SV_L2_OCUPACION
9.13	Employer	SV_L2_EMPLEADOR
9.14	Education	SV_L2_ESCOLARIDAD
9.15	School	SV_L2_CENTRO_EDUCATIVO
9.16	Dependants and children	SV_L2_PERSONAS_A_CARGO

PART 10 · SENSITIVE DATA

10.1	Ethnic origin	SV_L3_ORIGEN_ETNICO
10.2	Language	SV_L3 LENGUA_INDIGENA
10.3	Nationality	SV_L3_NACIONALIDAD
10.4	Religion	SV_L3_RELIGION
10.5	Spiritual or philosophical convictions	SV_L3_CONVICCION_FILOSOFICA
10.6	Political ideology	SV_L3_IDEOLOGIA_POLITICA
10.7	Party membership	SV_L3_AFILIACION_PARTIDARIA
10.8	Trade union membership	SV_L3_AFILIACION_SINDICAL
10.9	Biometric data	SV_L3_BIOMETRICO
10.10	Genetic data	SV_L3_GENETICO
10.11	Sexual preferences	SV_L3_ORIENTACION_SEXUAL
10.12	Sexual life	SV_L3_VIDA_SEXUAL

10.13	Gender identity	SV_L3_IDENTIDAD_GENERO
10.14	Moral and family situation	SV_L3_SITUACION_FAMILIAR
10.15	Personal habits	SV_L3_HABITOS
10.16	Victims of violence	SV_L3_VICTIMA

PART 11 · HEALTH DATA

11.1	Health identifiers	SV_SALUD_IDENTIFICADOR
11.2	Health coverage	SV_SALUD_COBERTURA
11.3	Diagnosis and ICD-10	SV_SALUD_DIAGNOSTICO
11.4	Procedures	SV_SALUD_PROCEDIMIENTO
11.5	Medicines	SV_SALUD_MEDICAMENTO
11.6	Clinical text	SV_SALUD_TEXTO_CLINICO
11.7	Test results	SV_SALUD_RESULTADO_EXAMEN
11.8	HIV and sexually transmitted infections	SV_SALUD_VIH
11.9	Blood group and Rh	SV_SALUD_GRUPO_SANGUINEO
11.10	Disability	SV_SALUD_DISCAPACIDAD
11.11	Occupational health	SV_SALUD_OCUPACIONAL
11.12	Sexual and reproductive health	SV_SALUD_REPRODUCTIVA
11.13	Mental health	SV_SALUD_MENTAL

PART 12 · FINANCIAL AND SOCIOECONOMIC DATA

12.1	Credit history	SV_FIN_HISTORIAL_CREDITICIO
12.2	Debt	SV_FIN_DEUDA
12.3	Income and pay	SV_FIN_INGRESOS
12.4	Assets	SV_FIN_PATRIMONIO
12.5	Pension and benefits	SV_FIN_PENSION
12.6	Remittances	SV_FIN_REMESAS
12.7	Subsidies and social programmes	SV_FIN_PROGRAMA_SOCIAL
12.8	Housing tenure	SV_FIN_VIVIENDA

PART 13 · CRIMINAL RECORDS AND COURT FILES

13.1	Criminal records	SV_PENAL_ANTECEDENTES
13.2	Court or prosecution file	SV_PENAL_EXPEDIENTE
14	The DUI and NIT check digits	
15	Where people live: distritos, cantones and postal code	
16	Limits	
17	Verification	
18	Sources	

A	Algorithms
B	Files
C	Exclusion lists
D	Profile set and classifiers

About this profile set

This profile set finds the personal data in a Salvadoran database and masks it, so that a non-production copy — for testing, development, training or analysis — no longer identifies anyone.

Masking names and DUIs alone is not enough: a birth date, a sex and a small distrito already point at one person. The set works in the layers where the risk is:

- **Direct identifiers** — DUI, NIT and NRC, foreigner documents, passport, civil registry records, ISSS and pension numbers, student number, names, contact, address, accounts, cards, digital wallets, devices, cookies, plates, property, free text.
- **Quasi-identifiers** — birth date, age, sex, distrito and municipio with their codes, postal code, colonia, cantón, family status, occupation, employer, education.
- **Sensitive data** — those of article 4 g): ethnic origin, religious convictions, political affiliation or ideology, trade union membership, sexual preferences, physical and mental health, biometric and genetic data, **moral and family situation** and **personal habits**; plus nationality, which article 59 b) names beside racial or ethnic origin, and being a victim of violence.
- **Health data** — sensitive under article 4 g) and with rules of its own in article 39, in a group of its own: clinical record, coverage, ICD-10, procedures, medicines, HIV, blood group, disability, occupational, reproductive and mental health.
- **Financial data** — the credit history that article 3 a) leaves to its own law, debt, income, assets, pensions, **remittances**, subsidies and housing tenure.
- **Criminal records** — record certificates, procedural situation and court or prosecution file numbers.

In a Masking Engine, the set is a profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those rely on — and the lookup files they read. The appendices list each of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it on its own; an ambiguous one — `NOMBRE` , `DOCUMENTO` , `EXPEDIENTE` , `CARGO` — needs the values to agree. A column with a meaningless name (`CAMP01` , `OBS`) is still found when its values have a recognizable shape or vocabulary: a DUI, a NIT, an eight-digit phone, an address with colonia and polígono, a plate, a distrito.

Column names are recognized in Spanish, in the abbreviations of Salvadoran systems (`NUM_DOC` , `FEC_NAC` , `COD_MUNICIPIO` , `NRC` , `ISSS` , `CENTRO_ESCOLAR`) and in English.

Before masking, inventory the binary columns (BLOB, images, PDF). Onboarding processes often keep a photo of the DUI — with the fingerprint and the signature — and a validation selfie. Report those columns as residual risk.

Decreto 144 in brief

The **Law for the Protection of Personal Data** was passed as Legislative Decree 144 on 12 November 2024, published in Official Gazette 219, Volume 445, of 15 November, and entered into force eight days later (art. 64). It is El Salvador's first general data protection law, and applying and supervising it falls to the **Agencia de Ciberseguridad del Estado (ACE)**, created by the Cybersecurity and Information Security Law passed the same day.

What matters for a copy of production data:

- **Personal data** is information about an identified or identifiable natural person; data that does not allow a person to be identified or located is not personal data (art. 4 f). The data subject is always a **natural person** (art. 4 s): unlike other countries of the region, the law does not protect legal persons.
- **Sensitive data** is data about the physical or moral characteristics, or the facts and circumstances of the private life, whose improper use may give rise to discrimination. The list in article 4 g) is open-ended and goes further than its neighbours': religious beliefs and convictions, ethnic origin, political affiliation or ideologies, trade union membership, sexual preferences, physical and mental health, biometric and genetic information, **moral and family situation, personal habits** and other intimate information of a similar nature.
- **Dissociation or anonymization** is the **irreversible** procedure by which data stops being associated with its subject or allowing their identification (art. 4 h). **Pseudonymization** is processing after which the data can no longer be associated with the subject *without using additional information*, provided that this additional information is kept separate, hidden, classified and safeguarded (art. 4 q).
- **Where they appear.** Sensitive data may be processed for statistical or scientific purposes when dissociated from its subjects (art. 38); public bodies may transfer or disclose data for statistical, scientific or general-interest reasons provided it is dissociated or pseudonymized (art. 49 a); and the ACE publishes its sanction decisions only with the personal data dissociated or anonymized (art. 55).
- **Security.** The controller must implement security measures and comply with those the ACE issues, ensuring integrity, availability and confidentiality (arts. 34 and 36). Any security breach is notified to the ACE, to the Attorney General's Office and to the affected subjects within a maximum of **72 hours** (art. 25).
- **Sanctions.** Fines of one to ten minimum wages of the commerce sector for minor infringements, eleven to twenty-five for serious ones and twenty-six to forty for very serious ones (art. 57) — with the 2026 commerce and services minimum wage of 408.80 dollars, up to some 16,350 dollars. **Reversing the pseudonymization of personal data without the subject's consent is a very serious infringement** (art. 56 c, 8).

What the law leaves out. The credit history processed by those covered by the Law regulating credit history information services is excluded (art. 3 a), although that law has its own duty of secrecy; so are domestic processing, public security and defence, and the public registries and the civil registry (art. 3 b, c and d).

What came after. Article 60 gave the ACE three months to issue the policies, measures and guidelines. In the Official Gazette of 11 August 2026 the Agency published the **Guidelines for the Data Protection Delegate** and the **Rules for the Administrative Sanctioning Procedure**, in force eight days later. The security-measure policies of article 36 are the thing to watch: when they are published, this set should be reviewed against them.

Dissociation, pseudonymization and non-production copies

Few laws in the region separate the two concepts as clearly as Decreto 144. **Dissociation or anonymization** is irreversible (art. 4 h): the data no longer allows identification. **Pseudonymization** (art. 4 q) accepts that the data can be associated with its subject again *with additional information*, and for that reason requires that information to be separate, hidden, classified and safeguarded under technical and organizational measures.

The algorithms of this set are deterministic for the Masking Engine's key: the same DUI masks the same way in every table, which keeps joins working. That key is exactly the *additional information* of article 4 q). The masked copy is **pseudonymized**, not anonymized, and remains personal data for whoever holds the key and production.

- Keep the engine key separate, hidden and safeguarded — that is what the law asks for pseudonymization to count.
- Do not hand the copy to people who also access production without need: reversing pseudonymization without the subject's consent is a very serious infringement (art. 56 c, 8).
- If what you need is to treat the data as dissociated — statistics or science, art. 38 —, measure the re-identification risk of the quasi-identifiers that remain; the irreversibility of article 4 h) is a higher standard than this set meets.

4

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters:

`rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

5

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

6

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	12	25	21	5
Extended	85	143	110	73

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- DUI — SV_L1_DUI
- NIT — SV_L1_NIT
- Foreigner documents — SV_L1_DOCUMENTO_EXTRANJERO
- Passport — SV_L1_PASAPORTE
- Given name — SV_L1_NOMBRE
- Surname — SV_L1_APELLIDO
- Full name — SV_L1_NOMBRE_COMPLETO
- E-mail — SV_L1_EMAIL
- Phone — SV_L1_TELEFONO
- Address — SV_L1_DIRECCION
- Address complement — SV_L1_DIRECCION_COMPLEMENTO
- Birth date — SV_L2_FECHA_NACIMIENTO

With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY			ALGORITHM
DIRECT IDENTIFIERS				
DUI ESSENTIAL SV_L1_DUI	COLUMN NAME	DATA TYPE	VALUE FORMAT	SV_DOCUMENTO
NIT ESSENTIAL SV_L1_NIT	COLUMN NAME	VALUE FORMAT		SV_NIT
NRC SV_L1_NRC	COLUMN NAME	VALUE FORMAT		SV_CM_DIGITOS
Foreigner documents ESSENTIAL SV_L1_DOCUMENTO_EXTRANJERO	COLUMN NAME			SV_CM_ALFANUM
Passport ESSENTIAL SV_L1_PASAPORTE	COLUMN NAME	VALUE FORMAT		SV_CM_ALFANUM
Civil registry records SV_L1_PARTIDA	COLUMN NAME			SV_CM_ALFANUM
ISSS, AFP and pensions SV_L1_SEGURO_SOCIAL	COLUMN NAME			SV_CM_DIGITOS
Student number SV_L1_NIE	COLUMN NAME			SV_CM_DIGITOS
Professional registration SV_L1_MATRICULA_PROFESIONAL	COLUMN NAME			SV_CM_ALFANUM
Given name ESSENTIAL SV_L1_NOMBRE	COLUMN NAME	KNOWN VALUES		SV_NOMBRES
Surname ESSENTIAL SV_L1_APELLIDO	COLUMN NAME	KNOWN VALUES		SV_APELLIDOS
Full name ESSENTIAL SV_L1_NOMBRE_COMPLETO	COLUMN NAME	KNOWN VALUES		SV_NOMBRE_COMPLETO
E-mail ESSENTIAL SV_L1_EMAIL	COLUMN NAME	DATA TYPE	VALUE FORMAT	SV_EMAIL
Phone ESSENTIAL SV_L1_TELEFONO	COLUMN NAME	VALUE FORMAT		SV_TELEFONO
Address ESSENTIAL SV_L1_DIRECCION	COLUMN NAME	DATA TYPE	VALUE FORMAT	SV_DIRECCION
Address complement ESSENTIAL SV_L1_DIRECCION_COMPLEMENTO	COLUMN NAME			SV_CM_ALFANUM
Bank account SV_L1_CUENTA_BANCARIA	COLUMN NAME			SV_CM_DIGITOS
Payment card SV_L1_TARJETA	COLUMN NAME	VALUE FORMAT		SV_TARJETA
Digital wallet and bitcoin SV_L1_BILLETERA	COLUMN NAME	VALUE FORMAT		SV_CM_ALFANUM

DOMAIN	FOUND BY		ALGORITHM
IP address SV_L1_IP	COLUMN NAME	VALUE FORMAT	SV_IP
Device identifier SV_L1_DISPOSITIVO	COLUMN NAME	VALUE FORMAT	SV_CM_HEX
Cookies and tracking identifiers SV_L1_COOKIE	COLUMN NAME		SV_CM_ALFANUM
Vehicle plate SV_L1_PLACA	COLUMN NAME	VALUE FORMAT	SV_CM_DIGITOS_LETRAS
Vehicle and licence SV_L1_VEHICULO	COLUMN NAME	VALUE FORMAT	SV_CM_ALFANUM
Property SV_L1_INMUEBLE	COLUMN NAME		SV_CM_ALFANUM
Customer and contract numbers SV_L1_CONTRATO	COLUMN NAME		SV_CM_ALFANUM
User and social media SV_L1_USUARIO	COLUMN NAME		SV_CM_ALFANUM
Credentials SV_L1_CREDENCIAL	COLUMN NAME		SV_REDACTAR
Geolocation SV_L1_GEOLOCALIZACION	COLUMN NAME	VALUE FORMAT	SV_COORDENADA
Free text SV_L1_TEXTO_LIBRE	COLUMN NAME	DATA TYPE	VALUE FORMAT
QUASI-IDENTIFIERS			
Birth date ESSENTIAL SV_L2_FECHA_NACIMIENTO	COLUMN NAME	DATA TYPE	SV_FECHA_NACIMIENTO
Birth year SV_L2_ANIO_NACIMIENTO	COLUMN NAME	DATA TYPE	SV_ANIO
Age SV_L2_EDAD	COLUMN NAME	DATA TYPE	SV_EDAD
Personal event dates SV_L2_FECHA_EVENTO	COLUMN NAME	DATA TYPE	SV_FECHA_EVENTO
Sex SV_L2_SEXO	COLUMN NAME	KNOWN VALUES	SV_SEXO
Distrito and municipio SV_L2_DISTRITO	COLUMN NAME	KNOWN VALUES	SV_DISTRITO
Distrito and municipio codes SV_L2_CODIGO_GEOGRAFICO	COLUMN NAME	VALUE FORMAT	SV_CODIGO_GEOGRAFICO
Cantón and caserío SV_L2_CANTON	COLUMN NAME		SV_ZONA_RURAL
Colonia, residencial and barrio SV_L2_COLONIA	COLUMN NAME		SV_COLONIA
Postal code SV_L2_CODIGO_POSTAL	COLUMN NAME	DATA TYPE	SV_CODIGO_POSTAL
Family status SV_L2_ESTADO_FAMILIAR	COLUMN NAME	KNOWN VALUES	SV_ESTADO_FAMILIAR

DOMAIN	FOUND BY	ALGORITHM
Occupation SV_L2_OCUPACION	COLUMN NAME	SV_OCUPACION_O_CODIGO
Employer SV_L2_EMPLEADOR	COLUMN NAME	SV_EMPLEADOR
Education SV_L2_ESCOLARIDAD	COLUMN NAME KNOWN VALUES	SV_ESCOLARIDAD
School SV_L2_CENTRO_EDUCATIVO	COLUMN NAME	SV_CENTRO_EDUCATIVO
Dependants and children SV_L2_PERSONAS_A_CARGO	COLUMN NAME DATA TYPE	SV_CONTEO_LIMITADO
SENSITIVE DATA		
Ethnic origin SV_L3_ORIGEN_ETNICO	COLUMN NAME KNOWN VALUES	SV_ORIGEN_ETNICO
Language SV_L3_LENGUA_INDIGENA	COLUMN NAME KNOWN VALUES	SV_LENGUA
Nationality SV_L3_NACIONALIDAD	COLUMN NAME KNOWN VALUES	SV_NACIONALIDAD
Religion SV_L3_RELIGION	COLUMN NAME KNOWN VALUES	SV_RELIGION
Spiritual or philosophical convictions SV_L3_CONVICCION_FILOSOFICA	COLUMN NAME	SV_CATEGORIA_SUPRIMIDA
Political ideology SV_L3_IDEOLOGIA_POLITICA	COLUMN NAME KNOWN VALUES	SV_IDEOLOGIA_POLITICA
Party membership SV_L3_AFILIACION_PARTIDARIA	COLUMN NAME KNOWN VALUES	SV_PARTIDO
Trade union membership SV_L3_AFILIACION_SINDICAL	COLUMN NAME KNOWN VALUES	SV_CATEGORIA_SUPRIMIDA
Biometric data SV_L3_BIOMETRICO	COLUMN NAME DATA TYPE	SV_REDACTAR
Genetic data SV_L3_GENETICO	COLUMN NAME	SV_REDACTAR
Sexual preferences SV_L3_ORIENTACION_SEXUAL	COLUMN NAME KNOWN VALUES	SV_ORIENTACION_SEXUAL
Sexual life SV_L3_VIDA_SEXUAL	COLUMN NAME	SV_CATEGORIA_SUPRIMIDA
Gender identity SV_L3_IDENTIDAD_GENERO	COLUMN NAME KNOWN VALUES	SV_IDENTIDAD_GENERO
Moral and family situation SV_L3_SITUACION_FAMILIAR	COLUMN NAME	SV_CATEGORIA_SUPRIMIDA
Personal habits SV_L3_HABITOS	COLUMN NAME	SV_CATEGORIA_SUPRIMIDA
Victims of violence SV_L3_VICTIMA	COLUMN NAME	SV_CATEGORIA_SUPRIMIDA
HEALTH DATA		

DOMAIN	FOUND BY	ALGORITHM
Health identifiers SV_SALUD_IDENTIFICADOR	COLUMN NAME	SV_CM_ALFANUM
Health coverage SV_SALUD_COBERTURA	COLUMN NAME KNOWN VALUES	SV_COBERTURA_SALUD
Diagnosis and ICD-10 SV_SALUD_DIAGNOSTICO	COLUMN NAME VALUE FORMAT	SV_DIAGNOSTICO
Procedures SV_SALUD_PROCEDIMIENTO	COLUMN NAME	SV_PROCEDIMIENTO
Medicines SV_SALUD_MEDICAMENTO	COLUMN NAME KNOWN VALUES	SV_MEDICAMENTO
Clinical text SV_SALUD_TEXTO_CLINICO	COLUMN NAME DATA TYPE	SV_TEXTO_LIBRE
Test results SV_SALUD_RESULTADO_EXAMEN	COLUMN NAME	SV_CM_ALFANUM
HIV and sexually transmitted infections SV_SALUD_VIH	COLUMN NAME	SV_CATEGORIA_SUPRIMIDA
Blood group and Rh SV_SALUD_GRUPO_SANGUINEO	COLUMN NAME KNOWN VALUES	SV_GRUPO_SANGUINEO
Disability SV_SALUD_DISCAPACIDAD	COLUMN NAME KNOWN VALUES	SV_DISCAPACIDAD
Occupational health SV_SALUD_OCUPACIONAL	COLUMN NAME KNOWN VALUES	SV_APTITUD_LABORAL
Sexual and reproductive health SV_SALUD_REPRODUCTIVA	COLUMN NAME	SV_CATEGORIA_SUPRIMIDA
Mental health SV_SALUD_MENTAL	COLUMN NAME	SV_CATEGORIA_SUPRIMIDA
FINANCIAL AND SOCIOECONOMIC DATA		
Credit history SV_FIN_HISTORIAL_CREDITICIO	COLUMN NAME	SV_HISTORIAL_CREDITICIO
Debt SV_FIN_DEUDA	COLUMN NAME DATA TYPE	SV_VALOR_DEUDA
Income and pay SV_FIN_INGRESOS	COLUMN NAME DATA TYPE	SV_INGRESOS
Assets SV_FIN_PATRIMONIO	COLUMN NAME DATA TYPE	SV_PATRIMONIO
Pension and benefits SV_FIN_PENSION	COLUMN NAME DATA TYPE	SV_VALOR_PENSION
Remittances SV_FIN_REMESAS	COLUMN NAME DATA TYPE	SV_REMESAS
Subsidies and social programmes SV_FIN_PROGRAMA_SOCIAL	COLUMN NAME KNOWN VALUES	SV_PROGRAMA_SOCIAL
Housing tenure SV_FIN_VIVIENDA	COLUMN NAME KNOWN VALUES	SV_TENENCIA_VIVIENDA
CRIMINAL RECORDS AND COURT FILES		

DOMAIN	FOUND BY		ALGORITHM
Criminal records	COLUMN NAME		SV_ANTECEDENTES
SV_PENAL_ANTECEDENTES			
Court or prosecution file	COLUMN NAME	VALUE FORMAT	SV_EXPEDIENTE_JUDICIAL
SV_PENAL_EXPEDIENTE			

Direct identifiers

Data that identifies a person on its own. The DUI is the key of almost every Salvadoran record, and since Legislative Decree 203 of 2021 the DUI number **is** the NIT of an adult natural person. It masks the same way everywhere, and DUI and NIT come out with a valid check digit, because applications validate it.

8.1 DUI

SV_L1_DUI

ESSENTIAL COLUMN NAME DATA TYPE VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The number of the Documento Único de Identidad issued by the Registro Nacional de las Personas Naturales: eight digits and a check digit, 04567890-1. It follows the person through life and, since 2021, is also their NIT.

NUMERO_DOCUMENTO columns often mix DUIs, fourteen-digit NITs and passports: each value is masked by its shape.

HOW IT IS FOUND

COLUMN NAME SV_L1_DUI - Path

90% dui d_u_i documento_?[uú]nico(_?de_?identidad)? n(o|ro|um|umero)_?
(dui|documento|doc|identificaci[oó]n|id(ent)?) doc_?identidad numdoc nrodoc
(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|
trabajador|colaborador|alumno|estudiante|deudor|codeudor|fiador|solicitante|propietario|arrend
atario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|votante|contr
ibuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|jubilado|pensionado|cotizante)?
(dui|doc|documento) dui_
(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|t
rabajador|colaborador|alumno|estudiante|deudor|codeudor|fiador|solicitante|propietario|arrenda
tario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|votante|contri
buyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|jubilado|pensionado|cotizante)
carn[eé]_?(de_)?minoridad

60% documento doc identificaci[oó]n

DATA TYPE SV_L1_DUI - Type

Accepts text (length 8 or more) or number (length 8 or more); any other type rules the domain out.

VALUE FORMAT SV_L1_DUI - Regex

PATTERN	STRENGTH	NOTES
\d{8}-\d		90%
0\d{8}		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Digit by digit, with the check digit recomputed: weights 9, 8, 7, 6, 5, 4, 3 and 2, modulus 10, ten minus the remainder. Every masked DUI is valid and the mapping is one-to-one, so a DUI used as a key does not collide.

SV_DOCUMENTO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: SV_CM_ALFANUM.

SV_NIT_ANTIGUO CHECK DIGIT

Masks the digits with SV_NIT_CUERPO_ANTIGUO and recomputes a modulus 11 check digit with weights 9 8 7 6 5 4 3 2 1 0 10 9 8 from the right.

SV_NIT_CUERPO_ANTIGUO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_DIGITOS .

SV_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

SV_NIT_NUEVO CHECK DIGIT

Masks the digits with SV_NIT_CUERPO_NUEVO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 3 4 5 6 7 2 from the right.

SV_NIT_CUERPO_NUEVO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_DIGITOS .

SV_NIT_CORRELATIVO NUMERIC MAPPING

Maps the number to another between 101 and 999.

SV_DUI CHECK DIGIT

Masks the digits with SV_CM_DIGITOS and recomputes a modulus 10 check digit with weights 2 3 4 5 6 7 8 9 from the right.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
04567890-1	→	51433978-3
0513-010180-238-7	→	0309-178218-233-8

8.2

NIT

SV_L1_NIT

ESSENTIAL

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The fourteen-digit tax identification number, 0513-010180-238-7 : four digits for the municipality, six for the **date of birth** (ddmmyy) or of incorporation, three for a correlative and one check digit. Since Legislative Decree 203 of 2021 adult natural persons use their DUI as their NIT; the fourteen-digit one lives on for minors, foreigners and legal persons.

The digit is modulus 11 over the thirteen digits, with two rules: when the correlative is 100 or less the digit is the remainder (ten written as 0); above that, it is eleven minus the remainder (0 when the remainder is 0 or 1).

HOW IT IS FOUND

COLUMN NAME SV_L1_NIT - Path

90% nit[a-z0-9]* n(o|ro|um|umero)?nit n[uú]mero?(de_)?identificaci[oó]n?tributaria (cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|trabajador|colaborador|alumno|estudiante|deudor|codeudor|fiador|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|votante|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|jubilado|pensionado|cotizante)? nit nit_? (cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|emp|trabajador|colaborador|alumno|estudiante|deudor|codeudor|fiador|solicitante|propietario|arrendatario|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|votante|contribuyente|proveedor|socio|conyuge|padre|madre|hijo|familiar|jubilado|pensionado|cotizante) id_?tributario tax_?id

VALUE FORMAT SV_L1_NIT - Regex

PATTERN	STRENGTH	NOTES
\d{4}-\d{6}-\d{3}-\d		95%
\d{14}		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The whole body is mapped – **the birth date included** – and the digit recomputed with the matching rule, keeping the correlative in its class. A NIT column holding a DUI is masked as a DUI. See *The DUI and NIT check digits*.

SV_NIT REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: SV_CM_DIGITOS .

SV_NIT_ANTIGUO CHECK DIGIT

Masks the digits with SV_NIT_CUERPO_ANTIGUO and recomputes a modulus 11 check digit with weights 9 8 7 6 5 4 3 2 1 0 10 9 8 from the right.

SV_NIT_CUERPO_ANTIGUO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_DIGITOS .

SV_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

SV_NIT_NUEVO CHECK DIGIT

Masks the digits with SV_NIT_CUERPO_NUEVO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 3 4 5 6 7 2 from the right.

SV_NIT_CUERPO_NUEVO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_DIGITOS .

SV_NIT_CORRELATIVO NUMERIC MAPPING

Maps the number to another between 101 and 999.

SV_DUI CHECK DIGIT

Masks the digits with SV_CM_DIGITOS and recomputes a modulus 10 check digit with weights 2 3 4 5 6 7 8 9 from the right.

EXAMPLES

VALUE		MASKED
0513-010180-238-7	→	0309-178218-233-8
0614-050589-018-3	→	9125-830418-020-9
04567890-1	→	51433978-3

8.3

NRC

SV_L1_NRC

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The VAT taxpayer registration number, 123456-7.

HOW IT IS FOUND

COLUMN NAME SV_L1_NRC - Path

90% nrc[a-z0-9]* n(o|ro|um|umero)?(de_)?registro?(de_)?contribuyente registro? contribuyente n(o|ro|um|umero)?nrc

VALUE FORMAT SV_L1_NRC - Regex

PATTERN	STRENGTH	NOTES
\d{1,7}-\d		40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Digits are mapped and separators stay. Its check-digit rule is not public, so it is not recomputed.

SV_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456-7	→	564928-5

8.4

Foreigner documents

SV_L1_DOCUMENTO_EXTRANJERO

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The residence card, the temporary or permanent residence number, the work permit and the visa number.

HOW IT IS FOUND

COLUMN NAME SV_L1_DOCUMENTO_EXTRANJERO - Path

85% carn[eé]?(de_)?residente carn[eé]?(de_)?extranjer[oa] documento?(de_)?extranjer[oa] doc?extranjero residencia?(n(o|ro|um|umero)|definitiva|temporal) n(o|ro|um|umero)? (residencia|extranjer[ii]a) permiso?(de_)?(residencia|trabajo) visa(_? (n(o|ro|um|umero)))? gr[uú]a?_migratoria

HOW IT IS MASKED

Character by character, keeping length and format.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

R123456

→

MASKED

Q801473

8.5 Passport

SV_L1_PASAPORTE

ESSENTIAL

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

Salvadoran passport numbers — a letter and six or seven digits — and foreign ones.

HOW IT IS FOUND

COLUMN NAME

SV_L1_PASAPORTE – Path

90%

pasaporte[a-z0-9]* n(o|ro|um|umero)?pasaporte passport[a-z0-9]*

VALUE FORMAT

SV_L1_PASAPORTE – Regex

PATTERN

[A-Z]\d{6,8}

STRENGTH

NOTES

40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

A1234567

→

MASKED

U2438404

8.6 Civil registry records

SV_L1_PARTIDA

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The number, folio and book of the birth, marriage and death records kept by the alcaldías. Article 3 d) excludes the processing done by the registry itself, not the copy a private system keeps.

HOW IT IS FOUND

COLUMN NAME

SV_L1_PARTIDA – Path

85%

partida?(de_)?(nacimiento|matrimonio|defunci[oó]n)(_?(n(o|ro|um|umero)|folio|libro))?
n(o|ro|um|umero)?partida folio?(partida|libro) libro?(partida|registro) asiento?
(registrar|partida) certificaci[oó]n?(de_)?partida registro?(del_)?estado?familiar

HOW IT IS MASKED

Character by character, keeping length and format.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123/1985	→	091/7273

8.7 ISSS, AFP and pensions

SV_L1_SEGURO_SOCIAL

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The ISSS affiliation number, the employer number, the NUP of the pension system and the AFP individual account number.

HOW IT IS FOUND

COLUMN NAME

SV_L1_SEGURO_SOCIAL - Path

85%

```
iss[0-9]* n(o|ro|um|umero)_(iss|afiliaci[oó]n|patronal|asegurado) afiliaci[oó]n?  
iss n(o|ro|um|umero)?patronal nup n(o|ro|um|umero)?[uú]nico?previsional afp[a-z0-  
9]* n(o|ro|um|umero)?(afp|cuenta?individual|ciap) inep ipsfa bienestar?magisterial
```

HOW IT IS MASKED

Digits are mapped; separators stay.

SV_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456789	→	110858568

8.8 Student number

SV_L1_NIE

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The student identification number of the Ministry of Education and the codes and cards schools use.

HOW IT IS FOUND

COLUMN NAME

SV_L1_NIE - Path

80%

```
nie n(o|ro|um|umero)_(de_)?identificaci[oó]n?(de_)?estudiante c[oó]digo?(de_)?  
estudiante carn[eé]?(de_)?estudiante c[oó]digo?(de_)?alumno n(o|ro|um|umero)_(de_)?  
carn[eé]
```

HOW IT IS MASKED

Digits are mapped.

SV_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

1234567

→

5649285

8.9 Professional registration

SV_L1_MATRICULA_PROFESIONAL

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The number of the Junta de Vigilancia de la Profesión Médica (JVPM) and the professional registrations, published together with the person's name.

HOW IT IS FOUND

COLUMN NAME

SV_L1_MATRICULA_PROFESIONAL - Path

85%

jvpm junta_?de_?vigilancia n(o|ro|um|umero)_?(de_)?(junta|jvpm) matr[ií]cula_?
(profesional|m[eé]dica) registro_?(m[eé]dico|profesional) n(o|ro|um|umero)_?colegiado
colegiatura

HOW IT IS MASKED

Character by character, keeping length and format.

SV_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

JVPM-12345

→

NYDT-53410

8.10 Given name

SV_L1_NOMBRE

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The given name, one or two: Morena , José Alberto , María de los Ángeles .

HOW IT IS FOUND

COLUMN NAME

SV_L1_NOMBRE - Path

85%

primer_?nombre segundo_?nombre nombres_?(de_)?pila pri(mer)?_?nom seg(undo)?_?nom
nombre_?1 nombre_?2 first_?names? given_?names? fname middle_?names? nombres (except
when followed by completos? , y_?apellidos? , apellidos?)

50%

nombre (except when followed by list E1) nom (except when followed by list E2) name (except when followed by list E3)

KNOWN VALUES

SV_L1_NOMBRE - List

LIST

VALUES

STRENGTH

FIRST VALUES

sv-detectar-nombres.txt

466

70%

José, Jose, María, Maria, Juan, Carlos

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, replacing each name with one from the list. `de`, `del` and `la` stay in place. More than four words are masked character by character.

SV_NOMBRES **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `SV_CM_ALFANUM`.

SV_PALABRA_NOMBRE **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `SV_NOMBRE`.

SV_NOMBRE **NAME**

Replaces the name with one of the 405 names in `sv-nombres.txt`.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
María de los Ángeles	→	Cándido de los Johana
JOSÉ ALBERTO	→	FELICITA GRACIELA

8.11 Surname

SV_L1_APELLIDO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The surnames — the father's and the mother's —, in separate columns or together, and the married name with `de`: Menjívar de Portillo.

HOW IT IS FOUND

COLUMN NAME `SV_L1_APELLIDO` - Path

85% `apellidos?` `primer_apellido` `segundo_apellido` `apellido_?(1|2|paterno|materno|casada)`
`ape_?(1|2)` `apellido_?(de_)?casada` `last_names?` `surnames?` `family_names?` `lname`

KNOWN VALUES `SV_L1_APELLIDO` - List

LIST	VALUES	STRENGTH	FIRST VALUES
<code>sv-detectar-apellidos.txt</code>	436	70%	Hernández, Hernandez, Rodríguez, Rodriguez, Martínez, Martinez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Word by word, replacing each surname with one from the list; particles stay in place.

SV_APELLIDOS **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `SV_CM_ALFANUM`.

SV_PALABRA_APELLIDO **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `SV_APELLIDO`.

SV_APELLIDO **NAME**

Replaces the name with one of the 347 names in `sv-apellidos.txt`.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

Menjívar de Portillo

→ Centeno de Estrada

8.12 Full name

SV_L1_NOMBRE_COMPLETO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Given names and surnames in one column: José Alberto Menjívar Portillo . Also those of the mother, father, guardian, spouse, guarantor or personal reference.

A column named just NOMBRE may hold given names or full names: the values decide between the two domains.

HOW IT IS FOUND

COLUMN NAME

SV_L1_NOMBRE_COMPLETO - Path

90%

```
nombres?_?(completos?|y_?apellidos?|apellidos?)  apellidos?_?(y_?)?nombres?  nombre_?(del_?
|de_?la_?)?

(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|traba
jador|colaborador|alumno|estudiante|deudor|codeudor|fiador|solicitante|propietario|arrendatari
o|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madr
e|padre|conyuge|companero|contacto|referencia|victima|denunciante|imputado|procesado|testigo|m
edico|docente|socio|heredero|donante|tutor|jubilado|pensionado|cotizante|customer|patient|empl
oyee|member|holder|mother|father|spouse|contact|person|student|driver|owner)

(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|trab
ajador|colaborador|alumno|estudiante|deudor|codeudor|fiador|solicitante|propietario|arrendatar
io|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|contribuyente|mad
re|padre|conyuge|companero|contacto|referencia|victima|denunciante|imputado|procesado|testigo|
medico|docente|socio|heredero|donante|tutor|jubilado|pensionado|cotizante|customer|patient|emp
loyee|member|holder|mother|father|spouse|contact|person|student|driver|owner)_?(nombre|nom)
nom_?

(cliente|cli|paciente|pac|usuario|afiliado|asegurado|beneficiario|benef|titular|empleado|traba
jador|colaborador|alumno|estudiante|deudor|codeudor|fiador|solicitante|propietario|arrendatari
o|inquilino|conductor|responsable|representante|apoderado|persona|ciudadano|contribuyente|madr
e|padre|conyuge|companero|contacto|referencia|victima|denunciante|imputado|procesado|testigo|m
edico|docente|socio|heredero|donante|tutor|jubilado|pensionado|cotizante|customer|patient|empl
oyee|member|holder|mother|father|spouse|contact|person|student|driver|owner)  nombre_?

(madre|padre|tutor|conyuge|contacto_?emergencia|referencia)  full_?name  person_?name
```

60%

```
madre  padre  tutor  conyuge  companero_?(de_?)?vida  representante_?legal  apoderado
fiador  beneficiario  heredero  titular  referencia_?(personal|familiar)
```

50%

```
nombre (except when followed by list E1)  nom (except when followed by list E2)  name (except when followed by list E3)
```

KNOWN VALUES SV_L1_NOMBRE_COMPLETO – List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-nombres.txt	466	60%	José, Jose, María, Maria, Juan, Carlos
sv-detectar-apellidos.txt	436	60%	Hernández, Hernandez, Rodríguez, Rodriguez, Martínez, Martinez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

In Salvadoran order: two words are a given name and a surname; three, a given name and two surnames; four, two and two. **APELLIDOS**, **NOMBRES** with a comma, as in lists, is recognized too. The result is a plausible name, never the original.

SV_NOMBRE_COMPLETO **REGEX DECOMPOSE**

Tries 7 patterns in order and gives each part of the value its own action; when none matches: **SV_CM_ALFANUM** .

SV_APELLIDOS **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: **SV_CM_ALFANUM** .

SV_PALABRA_APELLIDO **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: **SV_APELLIDO** .

SV_APELLIDO **NAME**

Replaces the name with one of the 347 names in **sv-apellidos.txt** .

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

SV_NOMBRES **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: **SV_CM_ALFANUM** .

SV_PALABRA_NOMBRE **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: **SV_NOMBRE** .

SV_NOMBRE **NAME**

Replaces the name with one of the 405 names in **sv-nombres.txt** .

EXAMPLES

VALUE		MASKED
José Alberto Menjívar Portillo	→	Felicita Graciela Centeno Estrada
Morena Menjívar	→	Ofelia Centeno
MENJÍVAR PORTILLO, JOSÉ ALBERTO	→	CENTENO ESTRADA, FELICITA GRACIELA

8.13 E-mail

SV_L1_EMAIL

ESSENTIAL**COLUMN NAME****DATA TYPE****VALUE FORMAT****REGEX DECOMPOSE****WHAT IT IS**

Personal and corporate e-mail addresses.

HOW IT IS FOUND**COLUMN NAME** SV_L1_EMAIL – Path

85% e_?mail[a-z0-9_]* mail[a-z0-9_]* correo(?:electr[oó]nico)?[a-z0-9_]* dir_?correo
direcci[oó]n_?(de_)?correo direcci[oó]n_electr[oó]nica

DATA TYPE SV_L1_EMAIL – Type

Accepts text (length 5 or more); any other type rules the domain out.

VALUE FORMAT SV_L1_EMAIL - Regex

PATTERN	STRENGTH	NOTES
[A-Za-z0-9._%+\-]+\@[A-Za-z0-9.\-]+\.[A-Za-z]{2,24}	100%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

User and domain are mapped character by character, and the top-level domain — .com , .com.sv — becomes .test , reserved for testing: a masked address never delivers a message.

SV_EMAIL **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_ALFANUM .

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
morena.menjivar@gmail.com	→ vehefe.savrazac@pgoeb.test

8.14 Phone

SV_L1_TELEFONO

ESSENTIAL **COLUMN NAME** **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

Eight-digit numbers from the 2005 plan: landlines start with 2 and mobiles with 6 or 7, written 2222-3333 or 7123-4567 , with or without +503 .

HOW IT IS FOUND

COLUMN NAME SV_L1_TELEFONO - Path

85% tel tel[eé]fono[a-z0-9]* tel_?(fijo|casa|oficina|trabajo|contacto|celular|m[ó]vil)
celular[a-z0-9]* cel m[ó]vil whats_app n(o|ro|um|umero)?
(tel|tel[eé]fono|celular|cel|contacto) fax phone[a-z0-9]* mobile[a-z0-9]*

VALUE FORMAT SV_L1_TELEFONO - Regex

PATTERN	STRENGTH	NOTES
(\+?503[\s\-\])?[267]\d{3}[\s\-\]?[267]\d{4}	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

+503 and the first digit — which says landline or mobile — stay; the other seven digits are mapped.

SV_TELEFONO **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_DIGITOS .

SV_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
+503 7123-4567	→ +503 7957-9910
2222-3333	→ 2738-1457

8.15 Address

SV_L1_DIRECCION

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

SECURE LOOKUP

WHAT IT IS

The address with the street or avenue and the number — Calle Arce #123, Colonia Escalón —, with polígono and pasaje in the colonias and housing plans, or with the kilometre of a road.

HOW IT IS FOUND

COLUMN NAME SV_L1_DIRECCION – Path

80% `direcci[oó]n[a-z0-9_]*` (except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`, `correo`; except when followed by list E4) `domicilio[a-z0-9_]*` `dom_?(residencia|particular|laboral|cliente)` `residencia` `lugar_?(de_)?residencia` `calle(_?y_?n[uú]mero)?` `address[a-z0-9_]*` (except when preceded by `mac`, `ip`, `e_?mail`, `web`, `url`; except when followed by list E5)

DATA TYPE SV_L1_DIRECCION – Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT SV_L1_DIRECCION – Regex

PATTERN	STRENGTH	NOTES
<code>(?i)(calle avenida av avda pasaje pje boulevard blvd bulevar diagonal alameda final prolongaci[oó]n)\.?\s+[a-zAÉÍÓÚÑ0-9.']{2,40}\s*#\s*\d{1,5}.*</code>	80%	
<code>(?i).*\b(colonia col residencial res reparto urbanizaci[oó]n lotificaci[oó]n barrio pol[ií]gono pol)\.?\s+[a-zAÉÍÓÚÑ0-9.']{2,40}.*</code>	70%	
<code>(?i)k(m il[oó]metro)\.?\s*\d{1,3}\s+(carretera autopista).*</code>	70%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The whole line is replaced by a fictitious Salvadoran address of the same form. Colonia, cantón, distrito and postal code in columns of their own are handled by their domains.

SV_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in `sv-direcciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Calle Arce #123, Colonia Escalón	→ Blvd. Sur #371, Pol. 21, Comunidad El Coro

8.16 Address complement

SV_L1_DIRECCION_COMPLEMENTO

ESSENTIAL

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Polígono, pasaje, block, house, flat, lot or level in columns of their own.

HOW IT IS FOUND

COLUMN NAME SV_L1_DIRECCION_COMPLEMENTO – Path

70% pol[ií]gono pol block bloque pasaje_?(n(o|ro|um|umero))? casa_?(n(o|ro|um|umero))?
apartamento apto local nivel *(except when followed by educativo, acad[eé]mico, de_estudios, escolaridad)* piso lote manzana mz n(o|ro|um|umero)_(casa|puerta|apartamento)
complemento(_?direcci[oó]n)? referencia_?(de_)?(direcci[oó]n|domicilio)

HOW IT IS MASKED

Character by character, keeping length and format.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

Pol. 12 #5

→

Pun. 48 #7

8.17 Bank account

SV_L1_CUENTA_BANCARIA

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Savings, current and payroll account numbers. The bank code is not personal data and has no domain.

HOW IT IS FOUND

COLUMN NAME SV_L1_CUENTA_BANCARIA – Path

85% cuenta_?(bancaria|banco|corriente|ahorro|sueldo|planilla|abono|dep[oó]sito|destino|origen)
n(o|ro|um|umero)_(de_)?(cuenta|cta) nro_?cta num_?cta cta_
(cte|corriente|ahorro|bancaria) iban account_?(no|num|number) bank_?account

HOW IT IS MASKED

Digits are mapped; separators stay.

SV_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

0123-456789-012

→

5399-877380-764

8.18 Payment card

SV_L1_TARJETA

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers, recognized by the Luhn algorithm.

HOW IT IS FOUND

COLUMN NAME SV_L1_TARJETA – Path

85% tarjeta(_?(cr[eé]dito|d[eé]bito|n(o|ro|um|umero)))? n(o|ro|um|umero)?tarjeta pan card_?
(no|num|number) credit_?card tc_?(numero|num|nro)

VALUE FORMAT SV_L1_TARJETA – Regex

PATTERN	STRENGTH	NOTES
---------	----------	-------

\d{13,19}	90%	LUHN check digit; after removing [\s-]
-----------	-----	--

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Payment Card: another number that passes the Luhn algorithm. Only card-shaped values reach it.

SV_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

SV_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

EXAMPLES

VALUE	MASKED
4162 0935 0038 1234	→ 1521 1864 6750 7155

8.19 Digital wallet and bitcoin

SV_L1_BILLETERA

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The Chivo wallet identifier and the bitcoin and Lightning addresses that stayed in Salvadoran systems after the 2021 Bitcoin Law.

HOW IT IS FOUND

COLUMN NAME SV_L1_BILLETERA – Path

85% billetera(_?(digital|virtual|chivo))? wallet(_?(id|address|direccion))? chivo(_?
(id|wallet|usuario))? direcci[oó]n_?(bitcoin|btc|wallet|lightning) btc_?
(address|direccion) lightning_?(address|invoice) llave_?p[uú]blica

VALUE FORMAT SV_L1_BILLETERA – Regex

PATTERN	STRENGTH	NOTES
(bc1 [13])[a-zA-HJ-NP-Z0-9]{25,59}	70%	
[a-z0-9._\-\+](chivowallet walletofsatoshi strike)\.[a-z]{2,10}	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the shape. The masked address no longer passes its own checksum, which is what a test copy wants: nobody can send funds to it.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

bc1qar0srrr7xfkvy5l643lydnw9re59gtzzwf5mdq

→

mh2wis8tsdm0pdjdv8v51lyqxqg4ze53qkjbp7dgf

8.20 IP address

SV_L1_IP

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses from access logs and transactions.

HOW IT IS FOUND

COLUMN NAME

SV_L1_IP - Path

85%

ip ip?(address|addr|origen|destino|cliente|usuario|acceso|login|remota|publica)
direcci[oó]n?ip dir?ip ipv[46] remote?addr(ess)? client?ip host?ip

VALUE FORMAT

SV_L1_IP - Regex

PATTERN

STRENGTH

NOTES

((25[0-5]|2[0-4]\d|1?\d?\d)\.){3}(25[0-5]|2[0-4]\d|1?\d?\d)

100%

[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7}

90%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet is mapped to 1-254; an IPv6 address is mapped keeping its hex characters.

SV_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_HEX .

SV_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

SV_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

190.86.45.12

→

164.79.51.94

8.21 Device identifier

SV_L1_DISPOSITIVO

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

IMEI, IMSI, ICCID, MAC address, advertising and session identifiers.

HOW IT IS FOUND

COLUMN NAME

SV_L1_DISPOSITIVO - Path

80%

imei imsi iccid mac mac?address direcci[oó]n?mac device?(id|uuid|serial) id?
(dispositivo|equipo|celular) serial?(equipo|celular|dispositivo) advertising?id idfa
gaid session?id id?sesi[oó]n

VALUE FORMAT SV_L1_DISPOSITIVO – Regex

PATTERN	STRENGTH	NOTES
<code>([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2}</code>	100%	
<code>\d{15}</code>	80%	LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, with hex digits kept hex: a MAC stays a MAC.

SV_CM_HEX **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
3c:22:fb:9a:10:e4	→ 5e:83:bb:3c:31:f9

8.22 Cookies and tracking identifiers

SV_L1_COOKIE

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Article 4 e) defines the cookie as what a site stores in the browser to know the browsing habits of the person behind it: cookie, visitor and campaign identifiers.

HOW IT IS FOUND

COLUMN NAME SV_L1_COOKIE – Path

80% `cookie(_?(id|value|valor|nombre))?` `cookies` `_?ga` `_?gid` `fbp` `fbclid` `utm_?`
`(source|medium|campaign|term|content)` `id_?(navegador|browser|visitante)` `visitor_?id`
`tracking_?id` `client_?id`

HOW IT IS MASKED

Character by character, keeping length and format.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
GA1.2.123456789.1700000000	→ ZE0.5.891552838.7889916184

8.23 Vehicle plate

SV_L1_PLACA

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The plate with the class letter — P private, A rental, C freight, M motorcycle, AB bus, N national, O official, CD diplomatic — and six characters, P123–456 ; the newest ones mix digits and letters.

HOW IT IS FOUND

COLUMN NAME

SV_L1_PLACA – Path

85%

placa(_?(veh[ii]culo|carro|moto|automotor))?

n(o|ro|um|umero)_?placa

matr[ii]cula_

(veh[ii]culo|automotor)

license_?plate

plate(_?(no|number))?

VALUE FORMAT

SV_L1_PLACA – Regex

HOW IT IS MASKED

Letters to letters and digits to digits, position by position: the plate format stays.

SV_CM_DIGITOS_LETRAS

CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
P123-456	→	M829-400
M12345A	→	Q19997S

8.24

Vehicle and licence

SV_L1_VEHICULO

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

The VIN or chassis number, the engine number, the registration card and the driving licence number.

HOW IT IS FOUND

COLUMN NAME

SV_L1_VEHICULO – Path

85%

vin

chasis

n(o|ro|um|umero)_?(chasis|motor|serie|vin)

motor_?n(o|ro|um|umero)

tarjeta_?

(de_)?circulaci[oó]n

licencia_?(de_)?conducir(_?(n(o|ro|um|umero)))?

n(o|ro|um|umero)_?

licencia

VALUE FORMAT

SV_L1_VEHICULO – Regex

HOW IT IS MASKED

Character by character, keeping length and format.

SV_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
9FBHS41A1YM123456	→	0PQRZ7700SS723598

8.25 Property

SV_L1_INMUEBLE

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The registry number of the Centro Nacional de Registros, the registral entry and the cadastral number: they lead to the home and its owner.

HOW IT IS FOUND

COLUMN NAME

SV_L1_INMUEBLE - Path

80%

matr[ií]cula_?(inmueble|registral|cnr) n(o|ro|um|umero)_?

(matr[ií]cula|inmueble|catastral|partida_?catastral) c[oó]digo_?catastral catastro

inscripci[oó]n_?registral asiento_?registral folio_?real n(o|ro|um|umero)_?(de_?)?predio

HOW IT IS MASKED

Character by character, keeping length and format.

SV_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

12345678-00000

→

69087987-17079

8.26 Customer and contract numbers

SV_L1_CONTRATO

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Contract, policy, loan, application, member, subscriber, meter, case or administrative file numbers, and customer or employee codes.

HOW IT IS FOUND

COLUMN NAME

SV_L1_CONTRATO - Path

70%

n(o|ro|um|umero)_?(contrato|p[oó]liza|cr[eé]dito|pr[eé]stamo|solicitud|expediente_?

(administrativo|interno)|referencia|cliente|socio|suscriptor|medidor|servicio|caso|ticket|bene

ficio) contrato_?(n(o|ro|um|umero)) c[oó]digo_?(cliente|socio|empleado|afiliado) id_?

(cliente|socio|empleado|afiliado) n(o|ro)_?empleado c[oó]digo_?(de_?)?empleado

HOW IT IS MASKED

Character by character, keeping length and format. The mapping is deterministic, so joins keep working.

SV_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

CT-123456

→

NG-557411

8.27 User and social media

SV_L1_USUARIO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Login, alias and social media profiles.

HOW IT IS FOUND

COLUMN NAME SV_L1_USUARIO - Path

70% usuario user_?name username login alias apodo nick(_?name)? perfil_?
(instagram|facebook|twitter|tiktok|linkedin|x) instagram facebook twitter tiktok
linkedin red_?social handle

HOW IT IS MASKED

Character by character, keeping length and format.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

@morena_menjivar

→

@vehefe_savrazac

8.28 Credentials

SV_L1_CREDENCIAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Passwords and their hashes, PIN, security and OTP codes, CVV, tokens, API keys, private keys and seed phrases.

HOW IT IS FOUND

COLUMN NAME SV_L1_CREDENCIAL - Path

90% contrase[nñ]a clave (except when followed by catastral, primaria, for[aá]nea, valor, producto)
password passwd pwd pass hash_?(clave|contrasena|password) pin c[oó]digo_
(seguridad|verificaci[oó]n|acceso|otp) cvv cvc token(_?(acceso|refresh|api))? access_
token refresh_?token api_?key llave_?(api|privada) secreto secret otp pregunta_
secreta respuesta_?secreta frase_?semilla seed_?phrase

HOW IT IS MASKED

Every character becomes X. A credential has no use in a test copy, and a hash masked character by character could still be attacked.

SV_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

Clave#2024

→

XXXXXXXXXX

8.29 Geolocation

SV_L1_GEOLOCALIZACION

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in separate columns, from apps, visits, addresses and deliveries.

HOW IT IS FOUND

COLUMN NAME

SV_L1_GEOLOCALIZACION – Path

85%

lat latitud lon lng longitud coordenadas? coord_?[xy] geo_?
(lat|lon|lng|loc|localizacion|posicion) georreferenciaci[oó]n geolocalizaci[oó]n gps(_?
(ubicaci[oó]n|posici[oó]n|coordenadas))? ubicaci[oó]n_?gps

50%

long

VALUE FORMAT

SV_L1_GEOLOCALIZACION – Regex

PATTERN

STRENGTH

NOTES

1[34]\.\d{3,}\s*,\s*-(8[89]|90)\.\d{3,}

90%

-(8[89]|90)\.\d{4,}

50%

1[34]\.\d{4,}

40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the other decimals are mapped: the place is generalized, not moved far.

SV_COORDENADA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

13.698935,-89.191439

→

13.679136,-89.103595

8.30 Free text

SV_L1_TEXTO_LIBRE

COLUMN NAME

DATA TYPE

VALUE FORMAT

FREE TEXT REDACTION

WHAT IT IS

Remarks, complaint descriptions, accounts of events and messages where anything gets written — DUI, NIT, phone and name included.

HOW IT IS FOUND

COLUMN NAME

SV_L1_TEXTO_LIBRE – Path

60%

observaci[oó]n(es)? obs comentarios? notas? anotaci[oó]n(es)? descripci[oó]n_
(queja|reclamo|solicitud|caso|hechos|novedad|atenci[oó]n|denuncia) detalle_
(reclamo|solicitud|caso|atenci[oó]n) hechos relato justificaci[oó]n mensaje *(except when*
preceded by list E6; except when followed by list E7) texto(_?libre)? resumen_?(caso|atenci[oó]n) queja
reclamo denuncia_?texto remarks? comments? notes? free_?text memo

DATA TYPE SV_L1_TEXT0_LIBRE – Type

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT SV_L1_TEXT0_LIBRE – Regex

PATTERN	STRENGTH	NOTES
<code>\d{8}-\d</code>	70%	anywhere in the value
<code>[\w.+\\-]+@[\\w\\-]+\\. [A-Za-z]{2,}</code>	70%	anywhere in the value
<code>[267]\d{3}-\d{4}</code>	60%	anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

Free Text Redaction: DUIs, NITs, nine- and fourteen-digit numbers, e-mail, phones, cards, plates and IPs become `[DAT0]` ; given names and surnames from the list become `[NOMBRE]` . The rest of the text stays.

SV_TEXT0_LIBRE FREE TEXT REDACTION

Replaces the text matching 9 patterns with `[DAT0]` , and the 1,770 terms of `sv-texto-nombres.txt` with `[NOMBRE]` .

EXAMPLES

VALUE	MASKED
Cliente Menjívar, DUI 04567890-1, correo m.menjivar@gmail.com, cel 7123-4567.	→ Cliente <code>[NOMBRE]</code> , DUI <code>[DAT0]</code> , correo <code>[DAT0]</code> , cel <code>[DAT0]</code> .

Quasi-identifiers

Data that identifies nobody on its own, but does in combination. The 2023 municipal restructuring turned the 262 municipalities into distritos of 44 municipios, and the 2024 census counts both: 190 of the 262 distritos have fewer than 20,000 inhabitants — a quarter of the country lives in them — and the smallest has under 600. A birth date, a sex and one of those distritos point at a handful of people. These attributes are generalized or shifted rather than replaced, and the data keeps its analytical value.

9.1 Birth date

SV_L2_FECHA_NACIMIENTO

ESSENTIAL COLUMN NAME DATA TYPE DATE SHIFT

WHAT IT IS

The birth date, as a date, timestamp or text. In a fourteen-digit NIT it also sits inside the number.

HOW IT IS FOUND

COLUMN NAME SV_L2_FECHA_NACIMIENTO – Path

90% (fecha|fec|fch|f)?(de_?)?nac(imiento)? fnac fechanac(imiento)? cumplea[nños] dob
date_of_birth birth_date birthday

DATA TYPE SV_L2_FECHA_NACIMIENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 60 days either way. Ages and school years change for few people; the date stays plausible and the same birth shifts the same way in every table.

SV_FECHA_NACIMIENTO DATE SHIFT
Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	1985-08-05T00:00

9.2 Birth year

SV_L2_ANIO_NACIMIENTO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The birth year in a column of its own.

HOW IT IS FOUND

COLUMN NAME SV_L2_ANIO_NACIMIENTO – Path

90% a[nño]o?(de_?)?nac(imiento)? anio?nac(imiento)? year_of_birth birth_year yob

DATA TYPE SV_L2_ANIO_NACIMIENTO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit is mapped: 1985 becomes a year from 1980 to 1989.

SV_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

SV_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	1980

9.3

Age

SV_L2_EDAD

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Age in years, also age group or five-year band.

HOW IT IS FOUND

COLUMN NAME

SV_L2_EDAD – Path

85%

```
edad(_?(actual|a[nños|anios|paciente|afiliado|cliente|al_?
(ingreso|diagn[ó]stico|fallecimiento)))? grupo_?etario rango_?(de_)?edad quinquenio
age(_?(years|group)))?
```

DATA TYPE

SV_L2_EDAD – Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The tens digit stays and the unit is mapped (37 becomes 30–39). A hundred or more becomes 90: rare ages identify.

SV_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	35
104	→	90

9.4

Personal event dates

SV_L2_FECHA_EVENTO

COLUMN NAME

DATA TYPE

DATE SHIFT

WHAT IT IS

Dates that say something about the person: death, marriage, hiring and leaving, retirement, admission, diagnosis, childbirth, arrest, conviction, DUI issue, sick leave.

HOW IT IS FOUND

COLUMN NAME SV_L2_FECHA_EVENTO – Path

80% (fecha|fec|fch|f)?(de_?)?
(defunci[oó]n|fallecimiento|muerte|matrimonio|divorcio|ingreso|egreso|alta|baja|retiro|contrat
aci[oó]n|despido|jubilaci[oó]n|hospitalizaci[oó]n|internamiento|diagn[oó]stico|atenci[oó]n|con
sulta|parto|captura|detenci[oó]n|condena|expedici[oó]n(_?(dui|documento))?)|vencimiento_
dui|vacunaci[oó]n|cirug[ií]a|accidente|incapacidad) fec_?
(exp|expedicion|defuncion|ingreso|egreso|baja) date_?of_
(death|marriage|hire|admission|discharge)

DATA TYPE SV_L2_FECHA_EVENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 30 days either way.

SV_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE		MASKED
2021-03-15	→	2021-03-05T00:00

9.5

Sex

SV_L2_SEX0

COLUMN NAME **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

Sex as the system records it: F / M , Femenino / Masculino , Mujer / Hombre or the codes 1 and 2.

HOW IT IS FOUND

COLUMN NAME SV_L2_SEX0 – Path

85% sexo(_?(biol[oó]gico|al_?nacer|paciente|afiliado|cliente))? (tp|tipo|cod|cd|id)?sexo
g[eé]nero (except when followed by *identidad* , *autopercebido*) sex gender (except when followed by
identity)

KNOWN VALUES SV_L2_SEX0 – List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-sexo.txt	9	50%	f, m, h, femenino, masculino, mujer

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary: F stays F or M , 1 stays 1 or 2 .

SV_SEX0 REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_SEX0_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-sexo-femenino-masculino.txt , chosen by a keyed hash.

SV_SEX0_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-sexo-mujer-hombre.txt , chosen by a keyed hash.

SV_SEX0_FEMALE_MALE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-sexo-female-male.txt` , chosen by a keyed hash.

SV_SEX0_F_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-sexo-f-m.txt` , chosen by a keyed hash.

SV_SEX0_H_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-sexo-h-m.txt` , chosen by a keyed hash.

SV_SEX0_1_2 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-sexo-1-2.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	M
Femenino	→	Femenino

9.6

Distrito and municipio

SV_L2_DISTRITO

COLUMN NAME **KNOWN VALUES** **DATA CLEANSING**

WHAT IT IS

The distrito or municipio of residence, birth or care, by name — alone or with the departamento, El Rosario – La Paz . Since 2024 the 262 former municipalities are distritos of 44 municipios, and systems keep one or the other.

HOW IT IS FOUND

COLUMN NAME SV_L2_DISTRITO – Path

85% `distrito(_?(residencia|nacimiento|domicilio))?` *(except when followed by `cod` , `codigo` , `id` , `escolar` , `judicial`)* `municipio(_?(residencia|nacimiento|domicilio))?` *(except when followed by `cod` , `codigo` , `id`)* `ciudad(_?(residencia|nacimiento|domicilio|cliente))?` `(nom|nombre|desc)_?` `(distrito|municipio|ciudad)` `lugar_?(de_)?nacimiento` `city` `town`

KNOWN VALUES SV_L2_DISTRITO – List

LIST	VALUES	STRENGTH	FIRST VALUES
<code>sv-detectar-distritos.txt</code>	363	80%	Apaneca, Concepción de Ataco, Concepcion de Ataco, Tacuba, Atiquizaya, El Refugio

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A distrito with fewer than 20,000 inhabitants becomes the nearest distrito of its municipio with at least 20,000 — or of its departamento, when its municipio has none. The larger ones and the 44 municipios stay. See *Where people live*.

SV_DISTRITO **DATA CLEANSING**

Replaces each value found in `sv-distritos-generalizados.txt` (3,484 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Apaneca	→	Ahuachapán
San Salvador	→	San Salvador
El Rosario – La Paz	→	Santiago Nonualco – La Paz

9.7 Distrito and municipio codes

SV_L2_CODIGO_GEOGRAFICO

COLUMN NAME VALUE FORMAT DATA CLEANSING

WHAT IT IS

The codes of the Dirección General de Estadística y Censos: two digits for the departamento, four for the municipio and six for the distrito.

HOW IT IS FOUND

COLUMN NAME SV_L2_CODIGO_GEOGRAFICO – Path

85% (cod|codigo|cd|id)?(distrito|municipio|mun|ciudad|lugar)(? (digestyc|censo|res|residencia|nac|nacimiento))? (cod|codigo)?(digestyc|geogr[aá]fico) coddis codmun

VALUE FORMAT SV_L2_CODIGO_GEOGRAFICO – Regex

PATTERN	STRENGTH	NOTES
(0[1-9] 1[0-4])\d{2}(\d{2})?		40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The same generalization as the name: a small distrito's code becomes the code of the distrito that replaces its name. The two still agree.

SV_CODIGO_GEOGRAFICO DATA CLEANSING

Replaces each value found in sv-codigos-geograficos-generalizados.txt (190 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
010102	→	010101
010101	→	010101

9.8 Cantón and caserío

SV_L2_CANTON

COLUMN NAME SECURE LOOKUP

WHAT IT IS

The cantón, caserío or hamlet of a rural address: communities of a few dozen families, and the address of much of the country.

HOW IT IS FOUND

COLUMN NAME SV_L2_CANTON – Path

85% cant[oó]n(_?(residencia|nombre))? caser[ii]o aldea paraje zona_?rural comunidad(_?rural)? hacienda finca parcelaci[oó]n

HOW IT IS MASKED

Replaced by Zona rural.

SV_ZONA_RURAL **SECURE LOOKUP**

Replaces the value with one of the 1 values in sv-zona-rural.txt, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Cantón El Espino

→ **Zona rural**

9.9 Colonia, residencial and barrio

SV_L2_COLONIA

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The colonia, residencial, reparto, lotificación or barrio of residence.

HOW IT IS FOUND

COLUMN NAME SV_L2_COLONIA – Path

80% colonia col (except when followed by umna, or) residencial reparto urbanizaci[oó]n lotificaci[oó]n barrio(_?(residencia|domicilio))? (nom|nombre)? (colonia|barrio|residencial) comunidad(_?urbana)? neighbou?rhood

HOW IT IS MASKED

Replaced by a common Salvadoran colonia name, unrelated to the original.

SV_COLONIA **SECURE LOOKUP**

Replaces the value with one of the 106 values in sv-colonias.txt, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Colonia San Benito

→ **Colonia Sonsonate**

9.10 Postal code

SV_L2_CODIGO_POSTAL

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

The four-digit postal code: the first two are the departamento and the postal zone.

HOW IT IS FOUND

COLUMN NAME SV_L2_CODIGO_POSTAL – Path

85% c[oó]digo_?postal cod_?postal codpostal zip(_?code)? postal_?code cp

DATA TYPE SV_L2_CODIGO_POSTAL – Type

Accepts text (length 4 to 4) or number (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The first two digits stay and the others become zeros: 1101 becomes 1100.

SV_CODIGO_POSTAL **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

1101

→

1100

9.11 Family status

SV_L2_ESTADO_FAMILIAR

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Single, married, acompañado — the non-marital union the Family Code recognizes —, separated, divorced or widowed, in words or as a code.

HOW IT IS FOUND

COLUMN NAME SV_L2_ESTADO_FAMILIAR – Path

85%

estado_?(familiar|civil) est_?(familiar|civil) (cod|tipo|id)?estado_?(familiar|civil)
situaci[ó]n?conyugal marital?status civil?status

KNOWN VALUES SV_L2_ESTADO_FAMILIAR – List

LIST

VALUES

STRENGTH

FIRST VALUES

sv-detectar-estado-familiar.txt	23	70%	Soltero/a, Casado/a, Acompañado/a, Acompanado/a, Separado/a, Divorciado/a
---------------------------------	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another status from the list; a code stays a code. The *family situation* itself has its own domain among the sensitive data.

SV_ESTADO_FAMILIAR **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_ESTADO_FAMILIAR_LISTA .

SV_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_ESTADO_FAMILIAR_CODIGO **SECURE LOOKUP**

Replaces the value with one of the 6 values in `sv-estado-familiar-codigos.txt` , chosen by a keyed hash.

`SV_ESTADO_FAMILIAR_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 6 values in `sv-estado-familiar.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Unión no matrimonial

→

Viudo/a

9.12 Occupation

SV_L2_OCUPACION

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Occupation, profession or trade, in words or by the national occupation classification code. A rare occupation in a small distrito identifies.

HOW IT IS FOUND

COLUMN NAME

SV_L2_OCUPACION - Path

80%

`ocupaci[oó]n profes[ió]n oficio cno (cod|codigo)?(ocupacion|profesion|cno) puesto_?(de_)?trabajo categor[ií]a?ocupacional cargo?(actual|empleado) occupation profession job?title`

50%

`cargo puesto`

HOW IT IS MASKED

Text is replaced by a common occupation; a code is mapped digit by digit.

`SV_OCUPACION_0_CODIGO` **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `SV_OCUPACION` .

`SV_CM_DIGITOS` **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

`SV_OCUPACION` **SECURE LOOKUP**

Replaces the value with one of the 35 values in `sv-ocupaciones.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Gerente de operaciones

→

Contador

9.13 Employer

SV_L2_EMPLEADOR

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The name of the company or institution where the person works.

HOW IT IS FOUND

COLUMN NAME

SV_L2_EMPLEADOR - Path

90%

`empleador(_?(nombre|raz[oó]n?social|nit))? (nombre|nom)?(empleador|empresa?donde?trabaja|patrono) empresa?(donde_)?(trabaja|labora) lugar?(de_)?trabajo patrono(_?nombre)? employer(_?name)? workplace`

HOW IT IS MASKED

Replaced by a fictitious company.

SV_EMPLEADOR **SECURE LOOKUP**

Replaces the value with one of the 24 values in `sv-empleadores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

Grupo Agrisal S.A. de C.V.

→

MASKED

Constructora Salvadoreña S.A. de C.V.

9.14 Education

SV_L2_ESCOLARIDAD

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The education level attained — from none to doctorate —, in words or as a code.

HOW IT IS FOUND

COLUMN NAME

SV_L2_ESCOLARIDAD - Path

80%

`escolaridad nivel?(educativo|de?estudios|acad[eé]mico|alcanzado) grado?(de_)?`
`(estudio|escolaridad) m[aá]ximo?nivel a[nñ]os?(de_)?estudio education(_?level)?`

KNOWN VALUES

SV_L2_ESCOLARIDAD - List

LIST

VALUES

STRENGTH

FIRST VALUES

`sv-detectar-escolaridad.txt`

27

60%

Ninguno, Parvularia, Básica (1.º a 6.º), Basica (1.º a 6.º), Básica (7.º a 9.º), Basica (7.º a 9.º)

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another level from the list; a code stays a code.

SV_ESCOLARIDAD **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_ESCOLARIDAD_LISTA

SV_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-si-no.txt`, chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-true-false.txt`, chosen by a keyed hash.

SV_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-yes-no.txt`, chosen by a keyed hash.

SV_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-s-n.txt`, chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-y-n.txt`, chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-0-1.txt`, chosen by a keyed hash.

SV_ESCOLARIDAD_CODIGO **SECURE LOOKUP**

Replaces the value with one of the 10 values in `sv-escolaridad-codigos.txt`, chosen by a keyed hash.

SV_ESCOLARIDAD_LISTA **SECURE LOOKUP**

Replaces the value with one of the 10 values in `sv-escolaridad.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

Educación media incompleta

→

MASKED

Básica (7.º a 9.º)

9.15 School

SV_L2_CENTRO_EDUCATIVO

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

The centro escolar, complejo educativo, institute or university, by name or by the Ministry of Education's infrastructure code.

HOW IT IS FOUND

COLUMN NAME

SV_L2_CENTRO_EDUCATIVO – Path

75%

centro?(escolar|educativo) complejo?educativo (nombre|nom)?(centro?
escolar|escuela|colegio|instituci[oó]n?educativa|universidad) instituci[oó]n?educativa
escuela colegio instituto universidad c[oó]digo?(de_)?(infraestructura|centro?
escolar) school(_?name)? university

HOW IT IS MASKED

Replaced by a fictitious school.

SV_CENTRO_EDUCATIVO **SECURE LOOKUP**

Replaces the value with one of the 12 values in `sv-centros-educativos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

Universidad de El Salvador

→

MASKED

Complejo Educativo Walter Thilo Deininger

9.16 Dependants and children

SV_L2_PERSONAS_A_CARGO

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Number of dependants, children or household members.

HOW IT IS FOUND

COLUMN NAME

SV_L2_PERSONAS_A_CARGO – Path

80%

personas?a?cargo n(o|ro|um|umero)?(de_)?(hijos|dependientes|personas?a?cargo)
cant(idad)?(hijos|dependientes|personas?hogar|miembros) hijos dependientes personas?
(en?el_)?hogar tama[ñ]o?(de_l_)?hogar miembros?(de_l_)?hogar number?of?children
dependents

DATA TYPE

SV_L2_PERSONAS_A_CARGO – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Values from 0 to 5 stay; above 5 they become 5. Very large households are rare, and a rare count identifies.

SV_CONTEO_LIMITADO **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	5

Sensitive data

The categories of article 4 g) other than health — which has its own group —, plus what article 59 b) forbids processing without following the sensitive-data chapter: racial or ethnic origin, **nationality**, party affiliation, religious, spiritual or philosophical convictions, health, sexual life and orientation. The set adds two categories the law names and no other in the region spells out — **moral and family situation** and **personal habits** — and being a victim of violence, which other Salvadoran laws order protected. Categorical columns keep their shape: a Y/N flag stays a flag, a code is replaced by another code and any other value by one from the list of its category. Where the values share no vocabulary, they are suppressed to Sin información .

10.1 Ethnic origin

SV_L3_ORIGEN_ETNICO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Self-identification with an indigenous people — náhuat pipil, lenca, kakawira — or as mestizo, white or afro-descendant, as the 2024 census asks it; in words, as a code or as a flag.

HOW IT IS FOUND

COLUMN NAME SV_L3_ORIGEN_ETNICO - Path

95%
etnia origen_?([eé]tnico|racial) grupo_?[eé]tnico pertenencia_?[eé]tnica
autoidentificaci[oó]n(_?[eé]tnica)? autorreconocimiento (cod|codigo|tipo|id)?
(etnia|origen_etnico) raza ind[ií]lgena pueblo_?(ind[ií]lgena|originario)
afrodescendiente ethnicity race

KNOWN VALUES SV_L3_ORIGEN_ETNICO - List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-origen-etnico.txt	22	90%	Náhuat Pipil, Nahuat Pipil, Lenca, Kakawira (Cacaopera), Mestizo, Blanco
sv-detectar-codigos-banderas.txt	11	30%	s, n, sí, si, no, 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag, a code is replaced by another code and any other value by a category from the list.

SV_ORIGEN_ETNICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_ORIGEN_ETNICO_LISTA .

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-s-n.txt` , chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-y-n.txt` , chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-0-1.txt` , chosen by a keyed hash.

SV_ORIGEN_ETNICO_CODIGO **SECURE LOOKUP**

Replaces the value with one of the 6 values in `sv-origen-etnico-codigos.txt` , chosen by a keyed hash.

SV_ORIGEN_ETNICO_LISTA **SECURE LOOKUP**

Replaces the value with one of the 8 values in `sv-origen-etnico.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Indígena	→	Ninguno
S	→	S

10.2 Language

SV_L3 LENGUA_INDIGENA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The mother or indigenous language: náhuat, the language of the Pipil, is spoken by a few dozen elderly people, so declaring it identifies almost on its own.

HOW IT IS FOUND

COLUMN NAME

SV_L3 LENGUA_INDIGENA - Path

90%

`lengu(?:([ií]gena|materna|nativa|originaria|de_?se[ñ]as))?` `idioma(?:`
`(ind[ií]gena|materno|nativo))?` `habla_?(lengu|idioma)` `mother_?tongue` `native_?language`

KNOWN VALUES

SV_L3 LENGUA_INDIGENA - List

LIST

VALUES

STRENGTH

FIRST VALUES

`sv-detectar-lenguas.txt`

25

80%

Español, Espanol, Náhuat, Nahuat, Lenca (potón), Lenca (poton)

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a language from the list; a flag stays a flag.

SV LENGUA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `SV LENGUA LISTA` .

SV_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-si-no.txt` , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-true-false.txt` , chosen by a keyed hash.

SV_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-yes-no.txt` , chosen by a keyed hash.

SV_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-s-n.txt` , chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-y-n.txt`, chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-0-1.txt`, chosen by a keyed hash.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

SV LENGUA_LISTA **SECURE LOOKUP**

Replaces the value with one of the 8 values in `sv-lenguas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Náhuat pipil

→ Náhuat

10.3 Nationality

SV_L3_NACIONALIDAD

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Nationality, country of origin and the condition of a returnee. Article 59 b) names it beside racial or ethnic origin among what cannot be processed without following the sensitive-data chapter.

HOW IT IS FOUND

COLUMN NAME

SV_L3_NACIONALIDAD - Path

85%

nacionalidad pa[ií]s_?(de_?)(nacimiento|origen|nacionalidad|procedencia) ciudadan[ií]a
nationality citizenship country_of_birth condici[oó]n_migratoria persona_retornada
deportad[oa]

KNOWN VALUES

SV_L3_NACIONALIDAD - List

LIST

VALUES

STRENGTH

FIRST VALUES

sv-detectar-nacionalidades.txt	40	70%	Salvadoreña, Salvadorená, Hondureña, Hondurena, Guatemalteca, Nicaragüense
--------------------------------	----	-----	--

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a nationality from the list: the Salvadoran one and the largest foreign communities.

SV_NACIONALIDAD **SECURE LOOKUP**

Replaces the value with one of the 12 values in `sv-nacionalidades.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Panameña

→ Italiana

10.4 Religion

SV_L3_RELIGION

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The religion, church or congregation the person belongs to.

HOW IT IS FOUND

COLUMN NAME SV_L3_RELIGION – Path

95% religi[oó]n creencia_?(religiosa|espiritual) convicci[oó]n_?(religiosa|espiritual) credo
confesi[oó]n_?religiosa culto iglesia(_?(a_?la_?que_?pertenece|nombre))?
denominaci[oó]n_?religiosa (cod|codigo|tipo)_?religion religion church

KNOWN VALUES SV_L3_RELIGION – List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-religiones.txt	37	90%	Católica, Catolica, Evangélica, Evangelica, Protestante histórica, Protestante historica

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a religion from the list.

SV_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_RELIGION_LISTA .

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in sv-religiones.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Ortodoxa	→ Otra

10.5 Spiritual or philosophical convictions

SV_L3_CONVICCION_FILOSOFICA

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The spiritual, philosophical or moral convictions article 59 b) names apart from religious ones, conscientious objection and membership of lodges.

HOW IT IS FOUND

COLUMN NAME	SV_L3_CONVICCION_FILOSOFICA - Path
90%	convicci[oó]n(es)?_?(filos[oó]ficas? morales? espirituales? personales?) creencias?_?(filos[oó]ficas? morales? personales?) objeci[oó]n?(de_)?conciencia objetor?(de_)?conciencia logia masoner[ií]a beliefs? philosophical_beliefs?

HOW IT IS MASKED

The values share no vocabulary: they are suppressed to Sin información . Flags and codes keep their shape.

SV_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_SUPRIMIR .

SV_BANDERA REGEX DECOMPOSE
Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
SV_BANDERA_SI_NO SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.
SV_BANDERA_TRUE_FALSE SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.
SV_BANDERA_YES_NO SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.
SV_BANDERA_S_N SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.
SV_BANDERA_Y_N SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.
SV_BANDERA_0_1 SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.
SV_CM_ALFANUM CHARACTER MAPPING
Maps each character to another of its group (7 groups), keeping length and format.
SV_SUPRIMIR SECURE LOOKUP
Replaces the value with one of the 1 values in sv-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Se niega a transfusiones	→ Sin información

10.6 Political ideology

SV_L3_IDEOLOGIA_POLITICA

COLUMN NAME	KNOWN VALUES	REGEX DECOMPOSE
-------------	--------------	-----------------

WHAT IT IS

Ideology, leaning, sympathy and voting intention, from surveys and records.

HOW IT IS FOUND

COLUMN NAME	SV_L3_IDEOLOGIA_POLITICA - Path
90%	ideolog[ií]a(_?pol[ií]tica)? opini[oó]n?pol[ií]tica orientaci[oó]n?pol[ií]tica tendencia?pol[ií]tica preferencia?(pol[ií]tica partidaria electoral) intenci[oó]n?(de_)?voto simpat[ií]a?pol[ií]tica political?(opinion orientation view) voting?intention

KNOWN VALUES SV_L3_IDEOLOGIA_POLITICA - List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-ideologias-politicas.txt	16	70%	Izquierda, Centroizquierda, Centro, Centroderecha, Derecha, Independiente

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a position from the list — left to right, independent.

SV_IDEOLOGIA_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_IDEOLOGIA_POLITICA_LISTA .

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_IDEOLOGIA_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in sv-ideologias-politicas.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Oficialista	→ Centro

10.7 Party membership

SV_L3_AFILIACION_PARTIDARIA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The political party the person belongs to. Article 4 g) names *political affiliation or ideologies* and article 59 b) forbids processing it without following the sensitive-data chapter.

HOW IT IS FOUND

COLUMN NAME SV_L3_AFILIACION_PARTIDARIA - Path

95% partido(?:pol[í]tico)?(?:afiliaci[oó]n|nombre)? afiliaci[oó]n?
 (pol[í]tica|partidaria|partido) afiliado_?partido militancia(?:pol[í]tica)? militante
 (cod|codigo|nombre|nom)_?partido bandera_?pol[í]tica political_?party party_?membership

KNOWN VALUES SV_L3_AFILIACION_PARTIDARIA - List

LIST	VALUES	STRENGTH	FIRST VALUES
sv- detectar- partidos.t xt	24	80%	Nuevas Ideas, Alianza Republicana Nacionalista (ARENA), Frente Farabundo Martí para la Liberación Nacional (FMLN), Frente Farabundo Marti para la Liberacion Nacional (FMLN), Gran Alianza por la Unidad Nacional (GANA), Partido de Concertación Nacional (PCN)

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another party from the list of those registered with the Supreme Electoral Tribunal; a flag stays a flag.

SV_PARTIDO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_PARTIDO_LISTA .

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in sv-partidos.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Cambio Democrático	→ Vamos

10.8 Trade union membership

SV_L3_AFILIACION_SINDICAL

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

The union, membership, the union dues deducted on the payroll and union protection.

HOW IT IS FOUND

COLUMN NAME SV_L3_AFILIACION_SINDICAL - Path

95% sindicato(_?(nombre|afiliado|afiliaci[oó]n|codigo))? sindicalizado afiliado?sindicato
afiliaci[oó]n?sindical cuota?sindical descuento?sindical aporte?sindical
asociaci[oó]n?sindical contrato?colectivo fuero?sindical directivo?sindical trade?
union union?member(ship)?

KNOWN VALUES SV_L3_AFILIACION_SINDICAL - List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-sindicatos.txt	14	60%	CATS, CSTS, CTS, SIMETRISSS, ANDES, SITRASAL

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información .

SV_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_SUPRIMIR .

SV_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

SV_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in sv-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
SIMETRISSS	→	Sin información
S	→	S

10.9 Biometric data

SV_L3_BIOMETRICO

COLUMN NAME **DATA TYPE** **REGEX DECOMPOSE**

WHAT IT IS

Fingerprint templates — the DUI's fingerprint is the country's identification pattern —, face, iris, voice and digitized signature.

HOW IT IS FOUND

COLUMN NAME SV_L3_BIOMETRICO - Path

90% biometr[ií]a[a-z]* biom[eé]trico[a-z]* huella(_?dactilar)?(_?
(template|plantilla|imagen|hash))? huellas dactilar template?(facial|huella|biometrico)
plantilla?(facial|biom[eé]trica) rostro?(hash|template) reconocimiento?facial firma?
(biom[eé]trica|digitalizada|electr[oó]nica) iris voz?(biom[eé]trica|template)
fingerprints? face?(template|hash|encoding) biometric[a-z]*

DATA TYPE SV_L3_BIOMETRICO - Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character becomes `x` . A masked template authenticates nobody.

SV_REDACTAR **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	XXXXXXXXXX

10.10 Genetic data

SV_L3_GENETICO

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

Results of genetic and DNA tests, paternity tests, genetic profiles, mutations, karyotype and newborn screening.

HOW IT IS FOUND

COLUMN NAME SV_L3_GENETICO - Path

90% adn dna gen[eé]tic[oa]s? datos?_?gen[eé]ticos? genoma genotip[a-z]* prueba?
(gen[eé]tica|de?adn|de?paternidad|de?filiaci[oó]n) perfil?gen[eé]tico mutaci[oó]n
brca[12]? cariotipo tamizaje?neonatal genetic[a-z]*

HOW IT IS MASKED

Every character becomes `x` .

SV_REDACTAR **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
BRCA1 positivo	→	XXXXXXXXXXXX

10.11 Sexual preferences

SV_L3_ORIENTACION_SEXUAL

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Self-declared sexual orientation or preference, in health and diversity records.

HOW IT IS FOUND

COLUMN NAME	SV_L3_ORIENTACION_SEXUAL - Path		
95%	orientaci[oó]n_?sexual	preferencias?_?sexuales?	(cod codigo tipo)_?orientacion_?sexual sexual_?orientation
KNOWN VALUES	SV_L3_ORIENTACION_SEXUAL - List		
LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-orientaciones-sexuales.txt	13	80%	Heterosexual, Gay, Lesbiana, Bisexual, Pansexual, Asexual

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a category from the list.

SV_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_ORIENTACION_SEXUAL_LISTA .

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in sv-orientaciones-sexuales.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Homosexual	→ Pansexual

10.12 Sexual life

SV_L3_VIDA_SEXUAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Sexual activity and behaviour, number of partners, age at first intercourse.

HOW IT IS FOUND

COLUMN NAME

SV_L3_VIDA_SEXUAL - Path

90%

vida_?sexual actividad_?sexual conducta_?sexual pr[aá]cticas?_?sexuales? parejas?_? sexuales? n(o|ro|um|umero)_?parejas sexualmente_?activ[oa] inicio_?(de_?)(la_?)?vida_? sexual relaciones_?sexuales sex(ual)?_?life sexual?(activity|behavio(u)?r|partners)

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información .

SV_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_SUPRIMIR .

SV_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in sv-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Activa

→

Sin información

10.13 Gender identity

SV_L3_IDENTIDAD_GENERO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Self-declared gender identity. The law does not name it, but it falls squarely within the *physical or moral characteristics* whose improper use discriminates.

HOW IT IS FOUND

COLUMN NAMESV_L3_IDENTIDAD_GENERO – Path

95%

identidad_?(de_)?g[eé]nero (cod|codigo|tipo)_?identidad_?genero g[eé]nero_?
(autopercebido|identitario) expresi[oó]n_?de_?g[eé]nero transg[eé]nero persona_?trans
nombre_?identitario pronombres? gender_?identity

KNOWN VALUESSV_L3_IDENTIDAD_GENERO – List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-identidades- genero.txt	19	70%	Mujer cisgénero, Mujer cisgenero, Hombre cisgénero, Hombre cisgenero, Mujer trans, Hombre trans

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a category from the list.

SV_IDENTIDAD_GENERO **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_IDENTIDAD_GENERO_LISTA .

SV_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

SV_IDENTIDAD_GENERO_LISTA **SECURE LOOKUP**

Replaces the value with one of the 7 values in sv-identidades-genero.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Transgénero	→ Hombre trans

10.14 Moral and family situation

SV_L3_SITUACION_FAMILIAR

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

The *moral and family situation* that article 4 g) lists among sensitive data: family composition and ties, who the person lives with, moral and conduct references.

HOW IT IS FOUND

COLUMN NAME SV_L3_SITUACION_FAMILIAR – Path

85% situaci[oó]n?(moral|familiar) composici[oó]n?familiar v[íi]nculo?familiar convivencia vive?con estructura?familiar antecedentes?familiares (except when followed by m[eé]dicos, patol[oó]gicos) referencias?_?morales conducta?(moral|personal) reputaci[oó]n

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información. Family status — single, married — has its own domain among the quasi-identifiers.

SV_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_SUPRIMIR.

SV_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-si-no.txt, chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-true-false.txt, chosen by a keyed hash.

SV_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt, chosen by a keyed hash.

SV_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-s-n.txt, chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-y-n.txt, chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-0-1.txt, chosen by a keyed hash.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

SV_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in sv-sin-informacion.txt, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Vive con su madre y dos hermanos

→ Sin información

10.15 Personal habits

SV_L3_HABITOS

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

The *personal habits* of article 4 g): consumption, lifestyle and browsing habits, preferences, interests and purchase or search history — the profile built by the cookies of article 4 e).

HOW IT IS FOUND

COLUMN NAME SV_L3_HABITOS – Path

85% h[aá]bitos?(? (personales|de_?consumo|de_?navegaci[oó]n|alimenticios|de_?vida))? estilo_?
de_?vida preferencias?(? (de_?consumo|personales|de_?navegaci[oó]n)) perfil(_?(de_?)?
(consumo|navegaci[oó]n|comportamiento)) comportamiento_?(de_?)?
(compra|navegaci[oó]n|usuario) intereses gustos historial_?(de_?)?
(navegaci[oó]n|b[uú]squeda|compras) browsing_?history habits?

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información .

SV_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_SUPRIMIR .

SV_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

SV_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in sv-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Compra en línea cada semana

→ Sin información

10.16 Victims of violence

SV_L3_VICTIMA

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

Being a victim of gender, domestic or sexual violence, of trafficking or of forced displacement, the type of violence and the protection measures. The Special Comprehensive Law for a Life Free of Violence for Women and the law on internal forced displacement order the victim's identity protected.

HOW IT IS FOUND

COLUMN NAME SV_L3_VICTIMA – Path

```
90% v[í]ctima(_?(de_)?(violencia(_?(de_?g[eé]nero|intrafamiliar|sexual|patrimonial)))?
|delito|trata|desplazamiento|abuso))? violencia_?(de_)?g[eé]nero violencia_?
(intrafamiliar|dom[eé]stica|sexual|patrimonial) tipo_?(de_)?violencia medida_?(de_)?
protecci[oó]n orden_?(de_)?restricci[oó]n desplazamiento_?forzado persona_?desplazada
trata_?(de_)?personas denunciante_?violencia
```

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información .

SV_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_SUPRIMIR .

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in sv-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Violencia intrafamiliar	→	Sin información
S	→	S

Health data

Physical and mental health is sensitive data (art. 4 g), and article 39 lets health establishments and professionals process it while respecting professional secrecy and the Law on the Duties and Rights of Patients and Health Service Providers. The law on the prevention and control of HIV adds its own confidentiality. The group covers what the ISSS, the Ministry of Health, private clinics, laboratories and occupational health keep.

11.1 Health identifiers

SV_SALUD_IDENTIFICADOR

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Clinical record, admission, care, consultation and prescription numbers.

HOW IT IS FOUND

COLUMN NAME

SV_SALUD_IDENTIFICADOR - Path

85%

n(o|ro|um|umero)?(expediente(_?cl[ií]nico)?|hc|historia(_?cl[ií]nica)?
|ingreso|atenci[oó]n|consulta|referencia_?m[eé]dica|receta) expediente_
(cl[ií]nico|m[eé]dico) historia_?cl[ií]nica hc_?(n(o|ro|um|umero))? n(o|ro|um|umero)?
(asegurado|afiliado_?iss) c[ó]digo_?(paciente|expediente) id_?paciente

55%

expediente atenci[oó]n ingreso consulta

HOW IT IS MASKED

Character by character, keeping length and format.

SV_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

EXP-2024-00123

→ IRH-7843-85225

11.2 Health coverage

SV_SALUD_COBERTURA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The ISSS, the public system, Bienestar Magisterial, military health, the ISBM or a private insurer, by name or code. Who pays for care says a lot about employment and income.

HOW IT IS FOUND

COLUMN NAME

SV_SALUD_COBERTURA - Path

85%

cobertura(_?(m[eé]dica|de_?salud|social))? seguro_?(m[eé]dico|salud) r[eé]gimen(_?(de_?)?
salud)? proveedor_?(de_?)?salud iss(_?(afiliado|cobertura))? minal fosalud
bienestar_?magisterial cosam isbm aseguradora_?(m[eé]dica|salud) plan_?m[eé]dico

KNOWN VALUES SV_SALUD_COBERTURA – List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-cobertura.txt	20	80%	ISSS, MINSAL (sistema público), MINSAL (sistema publico), Bienestar Magisterial, Sanidad Militar (COSAM), ISBM

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A name is replaced by another coverage from the list; a code is mapped digit by digit; a flag stays a flag.

SV_COBERTURA_SALUD **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_COBERTURA .

SV_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_DIGITOS **CHARACTER MAPPING**

Maps each character to another of its group (1 groups), keeping length and format.

SV_COBERTURA **SECURE LOOKUP**

Replaces the value with one of the 8 values in sv-cobertura-salud.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
ISSS	→	ISBM
12345	→	31564

11.3 Diagnosis and ICD-10

SV_SALUD_DIAGNOSTICO

COLUMN NAME**VALUE FORMAT****REGEX DECOMPOSE****WHAT IT IS**

Diagnoses in words or by ICD-10 code, with a dot (F33.1) or without (F331); causes of death, of sick leave and of admission, history and allergies.

HOW IT IS FOUND

COLUMN NAME SV_SALUD_DIAGNOSTICO – Path

85% `diagn[oó]stico[a-z]*   dx(?:principal|secundario|ingreso|egreso)[0-9]?   cie_?10   cie(?:`
`(10|11|principal))?)?   (cod|codigo)_?(diagnostico|dx|cie)   impresi[oó]n_?diagn[oó]stica`
`enfermedad(es)?[a-z]*   patolog[ií]a   comorbilidad(es)?   antecedentes?_?`
`(m[eé]dicos|patol[oó]gicos|cl[ií]nicos|personales)   causa_?(de_)?`
`(muerte|defunci[oó]n|incapacidad|hospitalizaci[oó]n|consulta)   motivo_?(de_)?`
`(consulta|incapacidad|hospitalizaci[oó]n)   alergias?   diagnos(is|es)   icd_?(10|11)?`

VALUE FORMAT SV_SALUD_DIAGNOSTICO – Regex

PATTERN	STRENGTH	NOTES
<code>[A-TV-Za-tv-z]\d{2}(\.\d{1,2} \d X)?</code>		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code becomes another common code in the same format, and text a common diagnosis: an HIV or mental disorder diagnosis does not survive as a category.

SV_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

SV_DIAGNOSTICO_TEXT0 .

SV_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `sv-cie10-decimal.txt` , chosen by a keyed hash.

SV_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in `sv-cie10.txt` , chosen by a keyed hash.

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-si-no.txt` , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-true-false.txt` , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-yes-no.txt` , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-s-n.txt` , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-y-n.txt` , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-0-1.txt` , chosen by a keyed hash.

SV_DIAGNOSTICO_TEXT0 SECURE LOOKUP

Replaces the value with one of the 30 values in `sv-diagnostics.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F33.1	→	K21.9
B24X	→	R51

11.4 Procedures

SV_SALUD_PROCEDIMIENTO

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Procedures, tests and surgeries, in words or by code. A viral load or a pregnancy test reveals the diagnosis.

HOW IT IS FOUND

COLUMN NAME SV_SALUD_PROCEDIMIENTO - Path

85% procedimiento(?:([m[eé]dico|quir[uú]rgico|realizado|autorizado))?) (cod|codigo)?
(procedimiento|prestaci[ó]n|servicio_?salud) prestaci[ó]n?(m[eé]dica|de_?salud) examen?
(ordenado|realizado) cirug[ií]a(?:realizada)? intervenci[ó]n_?quir[uú]rgica medical_
procedure

HOW IT IS MASKED

A code is mapped digit by digit; text is replaced by a common procedure.

SV_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches:

SV_PROCEDIMIENTO_TEXTO .

SV_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

SV_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in sv-procedimientos.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
901234	→	928120

11.5 Medicines

SV_SALUD_MEDICAMENTO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Prescribed or dispensed medicines, by name or active ingredient. An antiretroviral, an antipsychotic or a contraceptive reveals a diagnosis.

HOW IT IS FOUND

COLUMN NAME SV_SALUD_MEDICAMENTO - Path

85% medicamentos(?:([recetado|prescrito|entregado|despachado|nombre|uso])?) f[aá]rmacos?
principio_?activo receta(?:m[eé]dica)? prescripci[ó]n(?:_?medicamento)? posolog[ií]a
tratamiento_?farmacol[ó]gico (cod|codigo)?medicamento medications? drugs?_?prescribed

KNOWN VALUES SV_SALUD_MEDICAMENTO - List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar- medicamentos.txt	51	70%	Acetaminofén, Acetaminofen, Ibuprofeno, Diclofenaco, Metformina, Glibenclamida

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a common medicine from the list; a flag stays a flag.

SV_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_MEDICAMENTO_LISTA

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-si-no.txt`, chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-true-false.txt`, chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-yes-no.txt`, chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-s-n.txt`, chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-y-n.txt`, chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-bandera-0-1.txt`, chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 22 values in `sv-medicamentos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Sertralina 50 mg

→

Complejo B

11.6 Clinical text

SV_SALUD_TEXTO_CLINICO

COLUMN NAME

DATA TYPE

FREE TEXT REDACTION

WHAT IT IS

History, present illness, progress notes, physical examination, treatment plan, discharge summaries and nursing notes.

HOW IT IS FOUND

COLUMN NAME

SV_SALUD_TEXTO_CLINICO - Path

85%

anamnesis evolucion(?:m[eé]dica|cl[ií]nica|enfermer[ií]a)? enfermedad?actual
examen?f[ií]sico plan?(de_)?(manejo|tratamiento) indicaciones?m[eé]dicas conducta(?:
m[eé]dica)? epicrisis resumen?(de_)?(alta|egreso|atenci[oó]n) nota?(m[eé]dica|de_
enfermer[ií]a|cl[ií]nica) notas?(m[eé]dicas|cl[ií]nicas) triage(?:texto)? informe?
(patolog[ií]a|radiolog[ií]a|m[eé]dico) clinical?notes? discharge?summary

DATA TYPE

SV_SALUD_TEXTO_CLINICO - Type

Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

The same Free Text Redaction as free text: documents, contacts and names from the list are redacted. The clinical content stays — if it must not be in the copy, suppress the column.

SV_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 9 patterns with [DATO] , and the 1,770 terms of sv-texto-nombres.txt with [NOMBRE] .

EXAMPLES

VALUE

Paciente Menjívar, DUI 04567890-1, consulta por cefalea.

MASKED

Paciente [NOMBRE], DUI [DATO], consulta por cefalea.

11.7 Test results

SV_SALUD_RESULTADO_EXAMEN

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Laboratory and test results — glucose, pregnancy, toxicology, blood alcohol —, also as numeric values.

HOW IT IS FOUND

COLUMN NAME

SV_SALUD_RESULTADO_EXAMEN - Path

80%

resultado?(del_)?

(examen|prueba|laboratorio|pcr|serolog[ií]a|biopsia|glucosa|citolog[ií]a|papanicolaou)

(examen|prueba)?(resultado|laboratorio) glucemia hemoglobina?glicosilada hba1c

colesterol imc presi[oó]n?arterial prueba?(de_)?embarazo toxicol[oó]gico

alcoholemia lab_results? test_results?

50%

resultado prueba

HOW IT IS MASKED

Character by character, keeping the format: a number stays a number.

SV_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

Reactivo

MASKED

Quilqaju

11.8 HIV and sexually transmitted infections

SV_SALUD_VIH

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Serological status, viral load and antiretroviral treatment, hepatitis, tuberculosis and sexually transmitted infections. The HIV prevention and control law guarantees confidentiality and forbids requiring a test to get or keep a job.

HOW IT IS FOUND

COLUMN NAME

SV_SALUD_VIH - Path

90%

vih(_?(estado|resultado|prueba|diagn[oó]stico|positivo))? hiv sida aids serolog[ií]a?

(vih|hiv) estado?serol[oó]gico carga?viral cd4 tar antirretroviral(es)? its ets

infecci[oó]n(es)??(de_)?transmisi[oó]n?sexual s[ií]filis hepatitis?[bc] tuberculosis

tb

HOW IT IS MASKED

A flag stays a flag; any other value becomes Sin información .

SV_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_SUPRIMIR .

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in sv-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Reactivo	→	Sin información
S	→	S

11.9 Blood group and Rh

SV_SALUD_GRUPO_SANGUINEO

COLUMN NAME KNOWN VALUES SECURE LOOKUP

WHAT IT IS

Blood group and Rh factor.

HOW IT IS FOUND

COLUMN NAME SV_SALUD_GRUPO_SANGUINEO - Path

90% grupo_?sangu[ií]neo tipo_?(de_)?sangre rh factor_?rh gs_?rh grupo_?rh abo(_?rh)?
blood_?(type|group)

KNOWN VALUES SV_SALUD_GRUPO_SANGUINEO - List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-grupos-sanguineos.txt	18	90%	A+, A-, B+, B-, AB+, AB-

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another group from the list.

SV_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in `sv-grupos-sanguineos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
0+	→	A-

11.10 Disability

SV_SALUD_DISCAPACIDAD

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Disability status and type and the CONAIPD card, under the Special Law for the Inclusion of Persons with Disabilities.

HOW IT IS FOUND

COLUMN NAME

SV_SALUD_DISCAPACIDAD - Path

90%

```
discapacidad[a-z]* (tipo|cod|codigo|categoria)?discapacidad persona?con?discapacidad  
pcd conaipd carn[eé]??(de_)?discapacidad condi[ó]n?(de_)?discapacidad  
necesidades?(educativas?)?especiales movilidad?reducida disabilit(y|ies)
```

KNOWN VALUES

SV_SALUD_DISCAPACIDAD - List

LIST

VALUES

STRENGTH

FIRST VALUES

sv-detectar-
discapacidades.txt

26

60%

Física o motora, Fisica o motora, Auditiva, Visual, Sordoceguera,
Intellectual

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a category from the list.

SV_DISCAPACIDAD **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_DISCAPACIDAD_LISTA .

SV_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-si-no.txt` , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-true-false.txt` , chosen by a keyed hash.

SV_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-yes-no.txt` , chosen by a keyed hash.

SV_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-s-n.txt` , chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-y-n.txt` , chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-0-1.txt` , chosen by a keyed hash.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

SV_DISCAPACIDAD_LISTA **SECURE LOOKUP**

Replaces the value with one of the 8 values in `sv-discapacidades.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno del espectro autista

→

Ninguna

11.11 Occupational health

SV_SALUD_OCUPACIONAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The fitness opinion of occupational medical exams, work accidents and occupational diseases, sick leave and absenteeism.

HOW IT IS FOUND

COLUMN NAME

SV_SALUD_OCUPACIONAL – Path

85%

```
aptitud_?(laboral|m[eé]dica) concepto_?(de_)?aptitud examen_?(m[eé]dico_)?
(ocupacional|preempleo|de_ingreso|de_retiro|peri[oó]dico) accidente_?(de_)?trabajo
enfermedad_?(laboral|profesional) riesgo_profesional incapacidad(_?
(m[eé]dica|laboral|d[ií]as))? d[ií]as_?(de_)?incapacidad licencia_?(m[eé]dica|por_?
enfermedad|de_maternidad) ausentismo comit[eé]_?(de_)?seguridad
```

KNOWN VALUES

SV_SALUD_OCUPACIONAL – List

LIST

VALUES STRENGTH FIRST VALUES

VALUES	STRENGTH	FIRST VALUES
sv-detectar-aptitud-laboral.txt	5	60%

apto, no apto, apto con restricciones, pendiente, apto con recomendaciones

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An opinion is replaced by another from the list — fit, unfit —; a flag stays a flag; the diagnosis falls under its domain.

SV_APTITUD_LABORAL

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_APTITUD_LABORAL_LISTA .

SV_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_APTITUD_LABORAL_LISTA **SECURE LOOKUP**

Replaces the value with one of the 4 values in `sv-aptitud-laboral.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

No apto temporalmente

→

Pendiente

11.12 Sexual and reproductive health

SV_SALUD_REPRODUCTIVA

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Pregnancy, last menstrual period, prenatal care, childbirth, family planning, fertility.

HOW IT IS FOUND

COLUMN NAME

SV_SALUD_REPRODUCTIVA - Path

90%

embarazo embarazada gestante gestaci[oón]n edad_?gestacional semanas_?(de_)?
gestaci[oón]n fum fecha_?[uú]ltima_?(regla|menstruaci[oón]n) control_?prenatal prenatal
parto(_?tipo)? ces[aá]rea aborto m[eé]todo_?(de_)?planificaci[oón]n planificaci[oón]n_
familiar anticoncepci[oón]n anticonceptivo fertilidad salud_?(sexual|reproductiva)
pregnan(t|cy) contracepti(on|ve)

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Sin información` .

SV_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `SV_SUPRIMIR` .

SV_BANDERA **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-si-no.txt` , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-true-false.txt` , chosen by a keyed hash.

SV_BANDERA_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-yes-no.txt` , chosen by a keyed hash.

SV_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-s-n.txt` , chosen by a keyed hash.

SV_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-y-n.txt` , chosen by a keyed hash.

SV_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `sv-bandera-0-1.txt` , chosen by a keyed hash.

SV_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

SV_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `sv-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

12 semanas de gestación

→

Sin información

S

→

S

11.13 Mental health

SV_SALUD_MENTAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Mental disorders, psychiatric or psychological care, suicide attempts and substance use. Article 4 g) names **physical and mental** health.

HOW IT IS FOUND

COLUMN NAME

SV_SALUD_MENTAL - Path

90%

salud_?mental trastorno[a-z]* psiqui[aá]tri[a-z]* psicol[oó]gi[a-z]* depresi[oó]n
ansiedad suicid[a-z]* intento_?(de_)?suicidio autolesi[oó]n consumo_?(de_)?
(sustancias|alcohol|drogas) adicci[oó]n(es)? alcoholismo tabaquismo mental_?health

HOW IT IS MASKED

Flags keep their shape; any other value becomes Sin información .

SV_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_SUPRIMIR .

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in sv-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno bipolar

→

Sin información

Financial and socioeconomic data

Credit history falls outside the law (art. 3 a), but not outside a test copy: its own law imposes secrecy, and a negative report follows a person for years. To that add the amounts that say how much someone has and the **remittances** that support one in four Salvadoran households and reveal who emigrated. Categories are replaced within their own notation; amounts are mapped to a plausible range in dollars, with no relation to the real value.

12.1 Credit history

SV_FIN_HISTORIAL_CREDITICIO

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

The credit bureau report, the score, days in arrears, the state of the obligation and legal collection. Article 3 a) leaves this processing to the Law regulating credit history information services, which imposes its own duty of secrecy.

HOW IT IS FOUND

COLUMN NAME

SV_FIN_HISTORIAL_CREDITICIO - Path

90%

```
historial_?(crediticio|de_?cr[eé]dito) bur[oó]_?(de_)?cr[eé]dito infored dicom
equifax transunion score(_?(crediticio|interno))? puntaje_?(de_)?cr[eé]dito
calificaci[oó]n_?(de_)?(riesgo|cr[eé]dito|cartera) categor[ií]a_?(de_)?riesgo d[ií]as_?
(de_)?mora altura_?(de_)?mora estado_?(de_)?(cr[eé]dito|cartera|obligaci[oó]n)
morosidad moroso cobro_?judicial credit_?score credit_?rating
```

HOW IT IS MASKED

A score gets other digits of the same length; a flag stays a flag; a status is replaced by another from the list.

SV_HISTORIAL_CREDITICIO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_ESTADO_CREDITO .

SV_CM_DIGITOS

CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

SV_BANDERA

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 10 values in sv-estados-credito.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Reportado en el buró de crédito

→

Refinanciado

745

→

471

12.2 Debt

SV_FIN_DEUDA

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

Credit and portfolio balances, amounts in arrears, instalments, disbursed amounts and limits.

HOW IT IS FOUND

COLUMN NAME

SV_FIN_DEUDA – Path

85%

saldo_?(deuda|cr[eé]dito|capital|obligaci[oó]n|cartera|en_?mora|adeudado) monto_?(de_?la_?)?
(deuda|cuota|obligaci[oó]n|cr[eé]dito|pr[eé]stamo|mora|desembolsado) deuda(_?total)?
l[ií]mite_?(de_?)?(cr[eé]dito|tarjeta) cupo_?(de_?)?cr[eé]dito cuota_?mensual loan_?
(amount|balance) outstanding_?balance debt

DATA TYPE

SV_FIN_DEUDA – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 100 and 250,000 dollars, unrelated to the real one.

SV_VALOR_DEUDA NUMERIC MAPPING

Maps the number to another between 100 and 250,000.

EXAMPLES

VALUE

MASKED

5400

→

7882

12.3 Income and pay

SV_FIN_INGRESOS

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

Salary, monthly or household income, fees and contributory pay. The commerce and services minimum wage was 408.80 dollars in 2026.

HOW IT IS FOUND

COLUMN NAME

SV_FIN_INGRESOS – Path

85%

salario(_?(b[aá]sico|mensual|bruto|neto|nominal))? sueldo(_?
(b[aá]sico|mensual|bruto|neto))? ingresos?(_?(mensuales?|totales?|familiares?|declarados?
|netos?))? remuneraci[oó]n devengado honorarios salario_?cotizable ingreso_?
(base|familiar) salary income wages?

DATA TYPE

SV_FIN_INGRESOS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 365 and 6,000 dollars.

SV_INGRESOS NUMERIC MAPPING

Maps the number to another between 365 and 6,000.

EXAMPLES

VALUE		MASKED
612	→	463

12.4 Assets

SV_FIN_PATRIMONIO

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Net worth, assets, valuations, account balances and term deposits.

HOW IT IS FOUND

COLUMN NAME SV_FIN_PATRIMONIO - Path

85% patrimonio(_?(neto|l[ií]quido))? activos?_(totales)? valor_?(del_)?
(inmueble|veh[ií]culo|bienes|aval[uú]o|cat[aa]stro|comercial) aval[uú]o saldo_
(cuenta|ahorro|dep[oó]sito|inversi[oón]|cuenta_?individual) dep[oó]sito_?a_?plazo
inversiones net_?worth account_?balance

DATA TYPE SV_FIN_PATRIMONIO - Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 1,000 and 500,000 dollars.

SV_PATRIMONIO NUMERIC MAPPING

Maps the number to another between 1,000 and 500,000.

EXAMPLES

VALUE		MASKED
48000	→	78077

12.5 Pension and benefits

SV_FIN_PENSION

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

The amount of the pension, subsidy or benefit, and child support.

HOW IT IS FOUND

COLUMN NAME SV_FIN_PENSION - Path

90% pensi[oó]n(_?(monto|mensual|valor))? monto?(pensi[oó]n|jubilaci[oó]n|beneficio|subsidio)
valor_?(pensi[oó]n|subsidio|beneficio) haber?(pensional|jubilatorio) cuota_?alimenticia
pension_?amount

DATA TYPE SV_FIN_PENSION – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 304 and 3,000 dollars.

SV_VALOR_PENSION **NUMERIC MAPPING**

Maps the number to another between 304 and 3,000.

EXAMPLES

VALUE		MASKED
425	→	577

12.6 Remittances

SV_FIN_REMESAS

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

The amount and frequency of family remittances and the condition of receiving them. One in four Salvadoran households does, and the data says who emigrated and what the household lives on.

HOW IT IS FOUND

COLUMN NAME SV_FIN_REMESAS – Path

90% remesa[a-z0-9]* monto_?remesa env[ií]o?(de_)?(dinero|remesa) receptor?(de_)?remesas
recibe_?remesas remittance[a-z]* money_?transfer

DATA TYPE SV_FIN_REMESAS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to a value between 20 and 2,000 dollars.

SV_REMESAS **NUMERIC MAPPING**

Maps the number to another between 20 and 2,000.

EXAMPLES

VALUE		MASKED
250	→	385

12.7 Subsidies and social programmes

SV_FIN_PROGRAMA_SOCIAL

COLUMN NAME **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

The gas and electricity subsidies, the agricultural and school packages, the universal basic pension and other programmes, often as a flag.

HOW IT IS FOUND

COLUMN NAME SV_FIN_PROGRAMA_SOCIAL - Path

90% programa_?social beneficiario_?(programa|subsidio|bono|pensi[oó]n_?b[aá]sica) subsidio(_?(gas|energ[ií]a|transporte|tipo))? paquete_?(agr[ií]cola|escolar) pensi[oó]n_?b[aá]sica_? universal bono(_?(salud|educaci[oó]n))? transferencia_?monetaria ayuda_?(social|estatal) social_?programme

KNOWN VALUES SV_FIN_PROGRAMA_SOCIAL - List

LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-programas-sociales.txt	20	80%	Subsidio al gas licuado, Subsidio a la energía eléctrica, Subsidio a la energia electrica, Paquete agrícola, Paquete agrícola, Paquete escolar
sv-detectar-codigos-banderas.txt	11	30%	s, n, sí, si, no, 1

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag and any other value is replaced by a programme from the list.

SV_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_PROGRAMA_SOCIAL_LISTA .

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in sv-programas-sociales.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Comunidades Solidarias	→ Subsidio al gas licuado

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Housing tenure: owned outright or being paid for, rented, lent, in caretaking.

HOW IT IS FOUND

COLUMN NAME	SV_FIN_VIVIENDA – Path		
90%	tenencia_(de_)?(la_)?vivienda	tipo_(de_)?tenencia	vivienda_(propia alquilada tipo_?tenencia)
	condici[oó]n_(de_)?(la_)?vivienda	ocupaci[oó]n_vivienda	housing_tenure
KNOWN VALUES	SV_FIN_VIVIENDA – List		
LIST	VALUES	STRENGTH	FIRST VALUES
sv-detectar-tenencia-vivienda.txt	16	60%	Propia totalmente pagada, Propia pagándose, Propia pagandose, Alquilada, Cedida o prestada, Guardianía

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another tenure from the list.

SV_TENENCIA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_TENENCIA_VIVIENDA_LISTA .

SV_BANDERA	REGEX DECOMPOSE
Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.	
SV_BANDERA_SI_NO	SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.	
SV_BANDERA_TRUE_FALSE	SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.	
SV_BANDERA_YES_NO	SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.	
SV_BANDERA_S_N	SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.	
SV_BANDERA_Y_N	SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.	
SV_BANDERA_0_1	SECURE LOOKUP
Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.	
SV_CM_ALFANUM	CHARACTER MAPPING
Maps each character to another of its group (7 groups), keeping length and format.	
SV_TENENCIA_VIVIENDA_LISTA	SECURE LOOKUP
Replaces the value with one of the 6 values in sv-tenencia-vivienda.txt , chosen by a keyed hash.	

EXAMPLES

VALUE	MASKED
Ocupación de hecho	→ Guardianía

Criminal records and court files

The law does not name them apart, but a criminal record certificate and a procedural situation are among the data with the heaviest consequences for a person, and their misuse discriminates — the test of article 4 g). They get the same care as sensitive data.

13.1 Criminal records

SV_PENAL_ANTECEDENTES

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The criminal and police record certificate, the type of offence, the procedural situation, being deprived of liberty and arrest warrants.

HOW IT IS FOUND

COLUMN NAME SV_PENAL_ANTECEDENTES – Path

95% antecedentes?(_(?penales|policiales|judiciales))? solvencia?(de_)?
(antecedentes|penal|policial) certificado?(de_)?antecedentes record?policial condena(_?
(penal|tipo))? delito(_?(tipo|cometido))? tipo?(de_)?delito situaci[oó]n?jur[ií]dica
detenci[oó]n?administrativa privad[oa]?(de_)?libertad interno?(penal|centro?penal)
reo orden?(de_)?captura r[eé]gimen?de?excepci[oó]n criminal?record

55% estado?(del_)?proceso sentencia fallo

HOW IT IS MASKED

Replaced by a generic status from the list — no record, convicted, acquitted —, whatever the outcome; a flag stays a flag.

SV_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_ANTECEDENTES_LISTA .

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

SV_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in sv-antecedentes.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Condenado por hurto en 2019	→	Absuelto

13.2 Court or prosecution file

SV_PENAL_EXPEDIENTE

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The file, case or reference number the prosecution service and the courts use: correlative, unit and year, 123-UDVM-2024 . Files are looked up and lead to the parties.

HOW IT IS FOUND

COLUMN NAME	SV_PENAL_EXPEDIENTE – Path		
90%	n(o ro um umero)?(de_)?(expediente?(judicial penal fiscal) causa proceso?(judicial penal) denuncia referencia?(judicial fiscal) aviso) expediente?(judicial penal fiscal) referencia?(judicial fiscal) causa?penal n(o ro um umero)?[uú]nico?(de_)?expediente nue		
50%	expediente	causa	proceso
VALUE FORMAT	SV_PENAL_EXPEDIENTE – Regex		
PATTERN	STRENGTH		NOTES
\d{1,6}-[A-Z]{2,10}-\d{4}			70%
[A-Z]{1,6}-?\d{1,6}-\d{4}			50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The correlative is mapped digit by digit; unit and year stay. Other numbers are masked character by character.

SV_EXPEDIENTE_JUDICIAL REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: SV_CM_ALFANUM .

SV_CM_DIGITOS	CHARACTER MAPPING
Maps each character to another of its group (1 groups), keeping length and format.	
SV_CM_ALFANUM	CHARACTER MAPPING
Maps each character to another of its group (7 groups), keeping length and format.	

EXAMPLES

VALUE		MASKED
123-UDVM-2024	→	957-UDVM-2024
1234/2023	→	9707/2023

The DUI and NIT check digits

The **DUI** is the simple case: eight digits with weights 9, 8, 7, 6, 5, 4, 3 and 2 from the left, modulus 10, and the digit is ten minus the remainder, written 0 when it is ten. That is exactly what the Masking Engine's Check Digit algorithm does, so one step is enough: it maps the eight digits and writes the ninth.

The fourteen-digit **NIT** has two rules, and which applies depends on the correlative — the third block:

- Correlative **above 100**: weights 2, 7, 6, 5, 4, 3, 2, 7, 6, 5, 4, 3 and 2, modulus 11, and the digit is eleven minus the remainder, or 0 when the remainder is 0 or 1. Check Digit writes eleven minus the remainder and ten as 0: it matches with no adjustment.
- Correlative **of 100 or less**: weights 14, 13, 12 ... 2, modulus 11, and the digit **is the remainder** (ten written as 0). Check Digit cannot write the remainder, but it can write eleven minus it — so the set uses the **complementary weights** (eleven minus each weight, modulo 11). With them the remainder is inverted, and what Check Digit writes is the true remainder.

Since the rule depends on the correlative and the whole body is masked, each branch keeps its class: the old branch leaves the correlative with a leading zero, and the new one maps it with Numeric Mapping into 101–999. A Regex Decompose picks the branch by the shape of the input value, with or without hyphens. The two blocks that say most about the person — the municipality and the **date of birth** — are mapped digit by digit, so a masked NIT no longer reveals when or where anyone was born.

Where people live: distritos, cantones and postal code

With the population of the 2024 census and the location published by the Banco Central de Reserva, the set knows the size, municipio, departamento and position of the 262 distritos and the 44 municipios.

- A **distrito** with fewer than 20,000 inhabitants becomes the nearest distrito of its **municipio** with at least 20,000; when its municipio has none, the nearest of its departamento. There are 190 of 262, with 1.5 million inhabitants — a quarter of the country. Apaneca becomes Ahuachapán; Perquín, San Francisco Gotera.
- The **44 municipios** and the 14 departamentos stay: the smallest municipio is far above the threshold.
- Distance is measured between the census centroids, in a straight line.
- Names repeat — El Rosario, San José, San Isidro, San Fernando, El Carmen, San Lorenzo. A name is generalized only when every distrito bearing it is small, and then follows the largest of them. With the departamento (El Rosario – La Paz , El Rosario (La Paz)) the same rule applies within the departamento.
- The **DIGESTYC codes** follow the same table, and a person's name and code still agree.
- The **cantón** and the **caserío** become **Zona rural**, the **colonia** is replaced by another and the **postal code** keeps only the departamento and the zone.

Distrito names that are also given names or surnames, and departamento names, are left out of the detection list, so that a surname column is not taken for distritos.

Limits

- **Binary columns** — DUI photos, fingerprints, validation selfies, clinical PDFs in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **The NRC does not get its check digit back**: its rule is not public, so it is mapped digit by digit.
- **A check digit in a column of its own** is not recomputed: it is masked and no longer matches the masked DUI or NIT.
- **Departamento, municipio, the bank code and the phone prefix stay**.
- **Data Cleansing leaves unknown values as they are**: a distrito spelled in a way that is not in the table — abbreviated, misspelled — passes unchanged.
- **Free text** is redacted word by word: a phone written with spaces is not found, and a name that is also a common word (Rosa , Cruz , Flores) is redacted wherever it appears.
- **Children and adolescents** — a birth date moves at most 60 days, so few people cross their 12th or 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, colonia, distrito and postal code in separate columns are masked independently and no longer form a coherent address.
- **Masked bitcoin addresses** no longer pass their checksum: they serve to test the system, not to transact with it.
- **The engine key** links masked values back to production for whoever holds both: the result is **pseudonymized** data (art. 4 q), not dissociated, and still personal data. Keep the key separate and safeguarded.

17

Verification

Before publication, the set was checked outside a Masking Engine:

- The DUI check-digit rule was checked against numbers published as valid, and the NIT rule against two independent implementations of the routine Salvadoran systems use.
- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 146 columns with the whole set at its assignment threshold — well named, badly named and 30 columns that are not personal data — and again with only the classifiers of the essential pack.
- The table that generalizes distritos was audited for all 262: by name, by name with the departamento and by code.
- The algorithms, run with the Delphix algorithm plugin, masked each domain's sample values and placeholders such as N/A , checking every output against its vocabulary; 150 DUIs and 200 NITs of both rules for validity and collisions, and 20 NITs to confirm that the birth date inside them does not survive. Every algorithm also masked its own sample value.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

18

Sources

- Ley para la Protección de Datos Personales, Legislative Decree 144 of 12 November 2024 (Official Gazette 219, Volume 445, of 15 November 2024). Cybersecurity and Information Security Law. Agencia de Ciberseguridad del Estado: Guidelines for the Data Protection Delegate and Rules for the Administrative Sanctioning Procedure (Official Gazette of 11 August 2026).
- Law regulating credit history information services. Law on the Duties and Rights of Patients and Health Service Providers. Law on the prevention and control of HIV. Special Comprehensive Law for a Life Free of Violence for Women. Special Law for the Inclusion of Persons with Disabilities.
- Legislative Decree 203 of December 2021 (NIT and DUI harmonization). Special Law for Municipal Restructuring, Legislative Decree 762 of 2023 (44 municipios and 262 distritos, in force since 1 May 2024).
- Banco Central de Reserva, Oficina Nacional de Estadística y Censos: VII Population and VI Housing Census 2024, population and location by municipio and distrito (BCR geoportal).
- Ministry of Labour: minimum wage in force since June 2025. Vice-ministry of Transport: plate classes. The 2005 telephone numbering plan.

APPENDIX A

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

SV_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: SV_L2_ANIO_NACIMIENTO

PATTERNS, TRIED IN ORDER

(\d{3})(\d)	keep · SV_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

SV_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_ANTECEDENTES_LISTA .

Used by: SV_PENAL_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_CM_ALFANUM
otherwise	SV_ANTECEDENTES_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

SV_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in sv-antecedentes.txt , chosen by a keyed hash.

Used by: SV_ANTECEDENTES

CONFIGURATION

lookupFile	sv-antecedentes.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_APELLIDO NAME

Replaces the name with one of the 347 names in sv-apellidos.txt .

Used by: SV_PALABRA_APELLIDO

CONFIGURATION

lookupFile	sv-apellidos.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

SV_APELLIDOS REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: SV_CM_ALFANUM .

Used by: SV_L1_APELLIDO , SV_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(\S+)	SV_PALABRA_APELLIDO
(\S+)\s+(\S+)	SV_PALABRA_APELLIDO · SV_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	SV_PALABRA_APELLIDO · SV_PALABRA_APELLIDO · SV_PALABRA_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	SV_PALABRA_APELLIDO · SV_PALABRA_APELLIDO · SV_PALABRA_APELLIDO · SV_PALABRA_APELLIDO
otherwise	SV_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

SV_APTITUD_LABORAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_APTITUD_LABORAL_LISTA .

Used by: SV_SALUD_OCUPACIONAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_CM_ALFANUM
otherwise	SV_APTITUD_LABORAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

SV_APTITUD_LABORAL_LISTA SECURE LOOKUP

Replaces the value with one of the 4 values in sv-aptitud-laboral.txt , chosen by a keyed hash.

Used by: SV_APTITUD_LABORAL

CONFIGURATION

lookupFile	sv-aptitud-laboral.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_BANDERA REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: SV_CATEGORIA_SUPRIMIDA , SV_ESTADO_FAMILIAR , SV_ESCOLARIDAD , SV_ORIGEN_ETNICO , SV_LENGUA , SV_RELIGION , SV_IDEOLOGIA_POLITICA , SV_PARTIDO , SV_ORIENTACION_SEXUAL , SV_IDENTIDAD_GENERO , SV_COBERTURA_SALUD , SV_DIAGNOSTICO , SV_MEDICAMENTO , SV_DISCAPACIDAD , SV_APTITUD_LABORAL , SV_HISTORIAL_CREDITICIO , SV_PROGRAMA_SOCIAL , SV_TENENCIA_VIVIENDA , SV_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no)	SV_BANDERA_SI_NO
(?i)(true false)	SV_BANDERA_TRUE_FALSE
(?i)(yes)	SV_BANDERA_YES_NO
(?i)([sn])	SV_BANDERA_S_N
(?i)([yx])	SV_BANDERA_Y_N
([01])	SV_BANDERA_0_1
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

SV_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-0-1.txt , chosen by a keyed hash.

Used by: SV_BANDERA

CONFIGURATION

lookupFile	sv-bandera-0-1.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-s-n.txt , chosen by a keyed hash.

Used by: SV_BANDERA

CONFIGURATION

lookupFile	sv-bandera-s-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-si-no.txt , chosen by a keyed hash.

Used by: SV_BANDERA

CONFIGURATION

lookupFile	sv-bandera-si-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-true-false.txt , chosen by a keyed hash.

Used by: SV_BANDERA

CONFIGURATION

lookupFile	sv-bandera-true-false.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-y-n.txt , chosen by a keyed hash.

Used by: SV_BANDERA

CONFIGURATION

lookupFile	sv-bandera-y-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_BANDERA_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in sv-bandera-yes-no.txt , chosen by a keyed hash.

Used by: SV_BANDERA

CONFIGURATION

lookupFile	sv-bandera-yes-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_SUPRIMIR .

Used by: SV_L3_CONVICCION_FILOSOFICA , SV_L3_AFILIACION_SINDICAL , SV_L3_VIDA_SEXUAL , SV_L3_SITUACION_FAMILIAR , SV_L3_HABITOS , SV_L3_VICTIMA , SV_SALUD_VIH , SV_SALUD_REPRODUCTIVA , SV_SALUD_MENTAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_CM_ALFANUM
otherwise	SV_SUPRIMIR

CONFIGURATION

trimInput	yes
requireMask	no

SV_CENTRO_EDUCATIVO SECURE LOOKUP

Replaces the value with one of the 12 values in `sv-centros-educativos.txt`, chosen by a keyed hash.

Used by: `SV_L2_CENTRO_EDUCATIVO`

CONFIGURATION

lookupFile	sv-centros-educativos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in `sv-cie10.txt`, chosen by a keyed hash.

Used by: `SV_DIAGNOSTICO`

CONFIGURATION

lookupFile	sv-cie10.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `sv-cie10-decimal.txt`, chosen by a keyed hash.

Used by: `SV_DIAGNOSTICO`

CONFIGURATION

lookupFile	sv-cie10-decimal.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: `SV_L1_DOCUMENTO_EXTRANJERO`, `SV_L1_PASAPORTE`, `SV_L1_PARTIDA`, `SV_L1_MATRICULA_PROFESIONAL`, `SV_L1_DIRECCION_COMPLEMENTO`, `SV_L1_BILETERA`, `SV_L1_COOKIE`, `SV_L1_VEHICULO`, `SV_L1_INMUEBLE`, `SV_L1_CONTRATO`,

SV_L1_USUARIO , SV_SALUD_IDENTIFICADOR , SV_SALUD_RESULTADO_EXAMEN , SV_CATEGORIA_SUPRIMIDA , SV_DOCUMENTO , SV_NOMBRES , SV_APELLIDOS , SV_NOMBRE_COMPLETO , SV_EMAIL , SV LENGUA , SV_RELIGION , SV_IDEOLOGIA_POLITICA , SV_PARTIDO , SV_ORIENTACION_SEXUAL , SV_IDENTIDAD_GENERO , SV_MEDICAMENTO , SV_DISCAPACIDAD , SV_APTITUD_LABORAL , SV_PROGRAMA_SOCIAL , SV_TENENCIA_VIVIENDA , SV_ANTECEDENTES , SV_EXPEDIENTE_JUDICIAL

CONFIGURATION

characterGroups	0123456789 AEIOU BCFGHJKLMNPQRSTUVWXYZ aeiou bcdfghjklmnpqrstvwxyz ÁÉÍÓÚÚ áéíóúú
caseSensitive	yes
minMaskedPositions	0

SV_CM_DIGITOS CHARACTER MAPPING

Maps each character to another of its group (1 groups), keeping length and format.

Used by: SV_L1_NRC , SV_L1_SEGURO_SOCIAL , SV_L1_NIE , SV_L1_CUENTA_BANCARIA , SV_DUI , SV_NIT_CUERPO_ANTIGUO , SV_NIT_CUERPO_NUEVO , SV_NIT , SV_TELEFONO , SV_COORDENADA , SV_ANIO , SV_EDAD , SV_OCUPACION_O_CODIGO , SV_COBERTURA_SALUD , SV_PROCEDIMIENTO , SV_HISTORIAL_CREDITICIO , SV_EXPEDIENTE_JUDICIAL

CONFIGURATION

characterGroups	0123456789
caseSensitive	yes
minMaskedPositions	0

SV_CM_DIGITOS_LETRAS CHARACTER MAPPING

Maps each character to another of its group (2 groups), keeping length and format.

Used by: SV_L1_PLACA

CONFIGURATION

characterGroups	0123456789 ABCDEFGHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

SV_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: SV_L1_DISPOSITIVO , SV_IP

CONFIGURATION

characterGroups	0123456789 abcdef ABCDEF ghijklmnopqrstuvwxyz GHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

SV_COBERTURA SECURE LOOKUP

Replaces the value with one of the 8 values in sv-cobertura-salud.txt , chosen by a keyed hash.

Used by: SV_COBERTURA_SALUD

CONFIGURATION

lookupFile	sv-cobertura-salud.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

SV_COBERTURA_SALUD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_COBERTURA .

Used by: SV_SALUD_COBERTURA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [sn]yx01))	SV_BANDERA
(\d{1,8})	SV_CM_DIGITOS
otherwise	SV_COBERTURA

CONFIGURATION

trimInput	yes
requireMask	no

SV_CODIGO_GEOGRAFICO DATA CLEANSING

Replaces each value found in sv-codigos-geograficos-generalizados.txt (190 pairs) by its counterpart; values not in the file stay as they are.

Used by: SV_L2_CODIGO_GEOGRAFICO

CONFIGURATION

lookupFile	sv-codigos-geograficos-generalizados.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

SV_CODIGO_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: SV_L2_CODIGO_POSTAL

PATTERNS, TRIED IN ORDER

(\d{2})(\d{2})	keep · replace with 00
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

SV_COLONIA SECURE LOOKUP

Replaces the value with one of the 106 values in sv-colonias.txt , chosen by a keyed hash.

Used by: SV_L2_COLONIA

CONFIGURATION

lookupFile	sv-colonias.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_CONTEO_LIMITADO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: SV_L2_PERSONAS_A_CARGO

PATTERNS, TRIED IN ORDER

([0-5])	keep
(\d+)	replace with 5
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

SV_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: SV_L1_GEOLOCALIZACION

PATTERNS, TRIED IN ORDER

(-?\d{1,3}[.,]\d)(\d+)\s*([,;])\s*(-?\d{1,3}[.,]\d)(\d+)	keep · SV_CM_DIGITOS · keep · keep · SV_CM_DIGITOS
(-?\d{1,3}[.,]\d)(\d+)	keep · SV_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

SV_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

SV_DIAGNOSTICO_TEXTO .

Used by: SV_SALUD_DIAGNOSTICO

PATTERNS, TRIED IN ORDER

([A-TV-Za-tv-z]\d{2}\.\d{1,2})	SV_CIE10_DECIMAL
([A-TV-Za-tv-z]\d{2,3}X?)	SV_CIE10
(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
otherwise	SV_DIAGNOSTICO_TEXTO

CONFIGURATION

trimInput	yes
requireMask	no

SV_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in sv-diagnostics.txt , chosen by a keyed hash.

Used by: SV_DIAGNOSTICO

CONFIGURATION

lookupFile	sv-diagnostics.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_DIRECCION SECURE LOOKUP

Replaces the value with one of the 4,000 values in `sv-direcciones.txt` , chosen by a keyed hash.

Used by: `SV_L1_DIRECCION`

CONFIGURATION

lookupFile	sv-direcciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`SV_DISCAPACIDAD_LISTA` .

Used by: `SV_SALUD_DISCAPACIDAD`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	SV_BANDERA
<code>(\d{1,6})</code>	SV_CM_ALFANUM
otherwise	SV_DISCAPACIDAD_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

SV_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `sv-discapacidades.txt` , chosen by a keyed hash.

Used by: `SV_DISCAPACIDAD`

CONFIGURATION

lookupFile	sv-discapacidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_DISTRITO DATA CLEANSING

Replaces each value found in `sv-distritos-generalizados.txt` (3,484 pairs) by its counterpart; values not in the file stay as they are.

Used by: `SV_L2_DISTRITO`

CONFIGURATION

lookupFile	sv-distritos-generalizados.txt
------------	--------------------------------

delimiter	
caseSensitive	yes
trimWhitespace	yes

SV_DOCUMENTO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: SV_CM_ALFANUM .

Used by: SV_L1_DUI

PATTERNS, TRIED IN ORDER

(\d{4}-?\d{6}-?(?:0\d{2} 100)-?\d)	SV_NIT_ANTIGUO
(\d{4}-?\d{6}-?[1-9]\d{2}-?\d)	SV_NIT_NUEVO
(\d{8}-?\d)	SV_DUI
otherwise	SV_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

SV_DUI CHECK DIGIT

Masks the digits with SV_CM_DIGITOS and recomputes a modulus 10 check digit with weights 2 3 4 5 6 7 8 9 from the right.

Used by: SV_NIT , SV_DOCUMENTO

CONFIGURATION

weightList	2 3 4 5 6 7 8 9
modulusNumber	10
checkDigitIndex	8
numDigitsForCheckdigitCalculation	8
calculateChecksumRightToLeft	yes
numericAlgorithm	SV_CM_DIGITOS
alphaNumericAlgorithm	SV_CM_DIGITOS
preserveRegex	[.\-\\s]
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

SV_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: SV_L2_EDAD

PATTERNS, TRIED IN ORDER

(\d{3,})	replace with 90
([1-9])(\d)([.,]\d+)	keep · SV_CM_DIGITOS · keep
([1-9])(\d)	keep · SV_CM_DIGITOS
(\d)	SV_CM_DIGITOS
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

SV_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_ALFANUM .

Used by: SV_L1_EMAIL

PATTERNS, TRIED IN ORDER

(([^@\\s]+)@([^\s]+\.)\.[A-Za-z]{2,24}(?:\.[A-Za-z]{2})?)	SV_CM_ALFANUM · SV_CM_ALFANUM · replace with test
otherwise	SV_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

SV_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 24 values in sv-empleadores.txt , chosen by a keyed hash.

Used by: SV_L2_EMPLEADOR

CONFIGURATION

lookupFile	sv-empleadores.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_ESCOLARIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_ESCOLARIDAD_LISTA .

Used by: SV_L2_ESCOLARIDAD

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_ESCOLARIDAD_CODIGO
otherwise	SV_ESCOLARIDAD_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

SV_ESCOLARIDAD_CODIGO SECURE LOOKUP

Replaces the value with one of the 10 values in sv-escolaridad-codigos.txt , chosen by a keyed hash.

Used by: SV_ESCOLARIDAD

CONFIGURATION

lookupFile	sv-escolaridad-codigos.txt
hashMethod	SHA256

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_ESCOLARIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `sv-escolaridad.txt` , chosen by a keyed hash.

Used by: `SV_ESCOLARIDAD`

CONFIGURATION

lookupFile	sv-escolaridad.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_ESTADO_CREDITO SECURE LOOKUP

Replaces the value with one of the 10 values in `sv-estados-credito.txt` , chosen by a keyed hash.

Used by: `SV_HISTORIAL_CREDITICIO`

CONFIGURATION

lookupFile	sv-estados-credito.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_ESTADO_FAMILIAR REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`SV_ESTADO_FAMILIAR_LISTA` .

Used by: `SV_L2_ESTADO_FAMILIAR`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snx01])</code>	<code>SV_BANDERA</code>
<code>(\d{1,6})</code>	<code>SV_ESTADO_FAMILIAR_CODIGO</code>
otherwise	<code>SV_ESTADO_FAMILIAR_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

SV_ESTADO_FAMILIAR_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in `sv-estado-familiar-codigos.txt` , chosen by a keyed hash.

Used by: `SV_ESTADO_FAMILIAR`

CONFIGURATION

lookupFile	sv-estado-familiar-codigos.txt
------------	--------------------------------

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_ESTADO_FAMILIAR_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in sv-estado-familiar.txt , chosen by a keyed hash.

Used by: SV_ESTADO_FAMILIAR

CONFIGURATION

lookupFile	sv-estado-familiar.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_EXPEDIENTE_JUDICIAL REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: SV_CM_ALFANUM .

Used by: SV_PENAL_EXPEDIENTE

PATTERNS, TRIED IN ORDER

(\d{1,6})([\\s\\-\\/])([A-Za-z]{2,10})([\\s\\-\\/])(\\d{4})	SV_CM_DIGITOS · keep · keep · keep · keep
([A-Za-z]{1,6}[\\s\\-]?)(\\d{1,6})([\\s\\-\\/])(\\d{4})	keep · SV_CM_DIGITOS · keep · keep
(\\d{1,6})([\\s\\-\\/])(\\d{4})	SV_CM_DIGITOS · keep · keep
otherwise	SV_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

SV_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: SV_L2_FECHA_EVENTO

CONFIGURATION

minRange	-30
maxRange	30
unit	DAYS
roll	no

SV_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: SV_L2_FECHA_NACIMIENTO

CONFIGURATION

minRange	-60
maxRange	60
unit	DAYS
roll	no

SV_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in sv-grupos-sanguineos.txt , chosen by a keyed hash.

Used by: SV_SALUD_GRUPO_SANGUINEO

CONFIGURATION

lookupFile	sv-grupos-sanguineos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_HISTORIAL_CREDITICIO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_ESTADO_CREDITO .

Used by: SV_FIN_HISTORIAL_CREDITICIO

PATTERNS, TRIED IN ORDER

(\d{1,4})	SV_CM_DIGITOS
(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
otherwise	SV_ESTADO_CREDITO

CONFIGURATION

trimInput	yes
requireMask	no

SV_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_IDENTIDAD_GENERO_LISTA .

Used by: SV_L3_IDENTIDAD_GENERO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_CM_ALFANUM
otherwise	SV_IDENTIDAD_GENERO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

SV_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in sv-identidades-genero.txt , chosen by a keyed hash.

Used by: SV_IDENTIDAD_GENERO

CONFIGURATION

lookupFile	sv-identidades-genero.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_IDEOLOGIA_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_IDEOLOGIA_POLITICA_LISTA .

Used by: SV_L3_IDEOLOGIA_POLITICA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_CM_ALFANUM
otherwise	SV_IDEOLOGIA_POLITICA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

SV_IDEOLOGIA_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in sv-ideologias-politicas.txt , chosen by a keyed hash.

Used by: SV_IDEOLOGIA_POLITICA

CONFIGURATION

lookupFile	sv-ideologias-politicas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_INGRESOS NUMERIC MAPPING

Maps the number to another between 365 and 6,000.

Used by: SV_FIN_INGRESOS

CONFIGURATION

minValue	365
maxValue	6000

SV_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_HEX .

Used by: SV_L1_IP

PATTERNS, TRIED IN ORDER

(\d{1,3})\.\(\d{1,3}\)\.\(\d{1,3}\)\.\(\d{1,3}\)	SV_OCTETO · SV_OCTETO · SV_OCTETO · SV_OCTETO
otherwise	SV_CM_HEX

CONFIGURATION

trimInput	yes
requireMask	no

SV_LENGUA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_LENGUA_LISTA .

Used by: SV_L3_LENGUA_INDIGENA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_CM_ALFANUM
otherwise	SV_LENGUA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

SV_LENGUA_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in sv-lenguas.txt , chosen by a keyed hash.

Used by: SV_LENGUA

CONFIGURATION

lookupFile	sv-lenguas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_MEDICAMENTO_LISTA .

Used by: SV_SALUD_MEDICAMENTO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_CM_ALFANUM
otherwise	SV_MEDICAMENTO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

SV_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 22 values in sv-medicamentos.txt , chosen by a keyed hash.

Used by: SV_MEDICAMENTO

CONFIGURATION

lookupFile	sv-medicamentos.txt
hashMethod	SHA256

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 12 values in `sv-nacionalidades.txt` , chosen by a keyed hash.

Used by: `SV_L3_NACIONALIDAD`

CONFIGURATION

lookupFile	sv-nacionalidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_NIT REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `SV_CM_DIGITOS` .

Used by: `SV_L1_NIT`

PATTERNS, TRIED IN ORDER

<code>(\d{4}-?\d{6}-?(?:0\d{2} 100)-?\d)</code>	SV_NIT_ANTIGUO
<code>(\d{4}-?\d{6}-?[1-9]\d{2}-?\d)</code>	SV_NIT_NUEVO
<code>(\d{8}-?\d)</code>	SV_DUI
otherwise	SV_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

SV_NIT_ANTIGUO CHECK DIGIT

Masks the digits with `SV_NIT_CUERPO_ANTIGUO` and recomputes a modulus 11 check digit with weights `9 8 7 6 5 4 3 2 1 0 10 9 8 4 3 2 1 0 10 9 8` from the right.

Used by: `SV_NIT` , `SV_DOCUMENTO`

CONFIGURATION

weightList	9 8 7 6 5 4 3 2 1 0 10 9 8
modulusNumber	11
checkDigitIndex	13
numDigitsForCheckdigitCalculation	13
calculateChecksumRightToLeft	yes
numericAlgorithm	SV_NIT_CUERPO_ANTIGUO
alphaNumericAlgorithm	SV_NIT_CUERPO_ANTIGUO
preserveRegex	<code>[.\-\\s]</code>
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK

inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

SV_NIT_CORRELATIVO NUMERIC MAPPING

Maps the number to another between 101 and 999.

Used by: SV_NIT_CUERPO_NUEVO

CONFIGURATION

minValue	101
maxValue	999

SV_NIT_CUERPO_ANTIGUO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_DIGITOS .

Used by: SV_NIT_ANTIGUO

PATTERNS, TRIED IN ORDER

(\d{10})(\d)(\d{2})	SV_CM_DIGITOS · replace with 0 · SV_CM_DIGITOS
otherwise	SV_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

SV_NIT_CUERPO_NUEVO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_CM_DIGITOS .

Used by: SV_NIT_NUEVO

PATTERNS, TRIED IN ORDER

(\d{10})(\d{3})	SV_CM_DIGITOS · SV_NIT_CORRELATIVO
otherwise	SV_CM_DIGITOS

CONFIGURATION

trimInput	yes
requireMask	no

SV_NIT_NUEVO CHECK DIGIT

Masks the digits with SV_NIT_CUERPO_NUEVO and recomputes a modulus 11 check digit with weights 2 3 4 5 6 7 2 3 4 5 6 7 2 from the right.

Used by: SV_NIT , SV_DOCUMENTO

CONFIGURATION

weightList	2 3 4 5 6 7 2 3 4 5 6 7 2
modulusNumber	11
checkDigitIndex	13
numDigitsForCheckdigitCalculation	13
calculateChecksumRightToLeft	yes
numericAlgorithm	SV_NIT_CUERPO_NUEVO
alphaNumericAlgorithm	SV_NIT_CUERPO_NUEVO
preserveRegex	[.\-\\s]

CONFIGURATION

trimInput	yes
requireMask	no

SV_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: SV_IP

CONFIGURATION

minValue	1
maxValue	254

SV_OCUPACION SECURE LOOKUP

Replaces the value with one of the 35 values in sv-ocupaciones.txt , chosen by a keyed hash.

Used by: SV_OCUPACION_O_CODIGO

CONFIGURATION

lookupFile	sv-ocupaciones.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_OCUPACION_O_CODIGO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_OCUPACION .

Used by: SV_L2_OCUPACION

PATTERNS, TRIED IN ORDER

(\d{2,5})	SV_CM_DIGITOS
otherwise	SV_OCUPACION

CONFIGURATION

trimInput	yes
requireMask	no

SV_ORIENTACION_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_ORIENTACION_SEXUAL_LISTA .

Used by: SV_L3_ORIENTACION_SEXUAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_CM_ALFANUM
otherwise	SV_ORIENTACION_SEXUAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

SV_ORIENTACION_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `sv-orientaciones-sexuales.txt` , chosen by a keyed hash.

Used by: `SV_ORIENTACION_SEXUAL`

CONFIGURATION

lookupFile	sv-orientaciones-sexuales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_ORIGEN_ETNICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`SV_ORIGEN_ETNICO_LISTA` .

Used by: `SV_L3_ORIGEN_ETNICO`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>SV_BANDERA</code>
<code>(\d{1,6})</code>	<code>SV_ORIGEN_ETNICO_CODIGO</code>
otherwise	<code>SV_ORIGEN_ETNICO_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

SV_ORIGEN_ETNICO_CODIGO SECURE LOOKUP

Replaces the value with one of the 6 values in `sv-origen-etnico-codigos.txt` , chosen by a keyed hash.

Used by: `SV_ORIGEN_ETNICO`

CONFIGURATION

lookupFile	sv-origen-etnico-codigos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_ORIGEN_ETNICO_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `sv-origen-etnico.txt` , chosen by a keyed hash.

Used by: `SV_ORIGEN_ETNICO`

CONFIGURATION

lookupFile	sv-origen-etnico.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

SV_PALABRA_APELLIDO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_APELLIDO .

Used by: SV_APELLIDOS , SV_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(?i)	keep
(de del la las los y e san santa van von di da)	
otherwise	SV_APELLIDO

CONFIGURATION

trimInput	yes
requireMask	no

SV_PALABRA_NOMBRE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: SV_NOMBRE .

Used by: SV_NOMBRES , SV_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(?i)	keep
(de del la las los y e san santa van von di da)	
otherwise	SV_NOMBRE

CONFIGURATION

trimInput	yes
requireMask	no

SV_PARTIDO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: SV_PARTIDO_LISTA .

Used by: SV_L3_AFILIACION_PARTIDARIA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_CM_ALFANUM
otherwise	SV_PARTIDO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

SV_PARTIDO_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in sv-partidos.txt , chosen by a keyed hash.

Used by: SV_PARTIDO

CONFIGURATION

lookupFile	sv-partidos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT

inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_PATRIMONIO NUMERIC MAPPING

Maps the number to another between 1,000 and 500,000.

Used by: SV_FIN_PATRIMONIO

CONFIGURATION

minValue	1000
maxValue	500000

SV_PROCEDIMIENTO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches:

SV_PROCEDIMIENTO_TEXTO .

Used by: SV_SALUD_PROCEDIMIENTO

PATTERNS, TRIED IN ORDER

(\d{4,6})	SV_CM_DIGITOS
otherwise	SV_PROCEDIMIENTO_TEXTO

CONFIGURATION

trimInput	yes
requireMask	no

SV_PROCEDIMIENTO_TEXTO SECURE LOOKUP

Replaces the value with one of the 10 values in sv-procedimientos.txt , chosen by a keyed hash.

Used by: SV_PROCEDIMIENTO

CONFIGURATION

lookupFile	sv-procedimientos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

SV_PROGRAMA_SOCIAL_LISTA .

Used by: SV_FIN_PROGRAMA_SOCIAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false yes [snyx01])	SV_BANDERA
(\d{1,6})	SV_CM_ALFANUM
otherwise	SV_PROGRAMA_SOCIAL_LISTA

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

SV_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in `sv-programas-sociales.txt` , chosen by a keyed hash.

Used by: `SV_PROGRAMA_SOCIAL`

CONFIGURATION

lookupFile	<code>sv-programas-sociales.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `SV_L1_CREDENCIAL` , `SV_L3_BIOMETRICO` , `SV_L3_GENETICO`

PATTERNS, TRIED IN ORDER

<code>(.+) </code>	each character → X
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

SV_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `SV_RELIGION_LISTA` .

Used by: `SV_L3_RELIGION`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01]) </code>	<code>SV_BANDERA</code>
<code>(\d{1,6}) </code>	<code>SV_CM_ALFANUM</code>
otherwise	<code>SV_RELIGION_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

SV_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `sv-religiones.txt` , chosen by a keyed hash.

Used by: `SV_RELIGION`

CONFIGURATION

lookupFile	<code>sv-religiones.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

SV_REMESAS NUMERIC MAPPING

Maps the number to another between 20 and 2,000.

Used by: SV_FIN_REMESAS

CONFIGURATION

minValue	20
maxValue	2000

SV_SEX0 REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: SV_L2_SEX0

PATTERNS, TRIED IN ORDER

(?i)(femenino masculino)	SV_SEX0_FEMENINO_MASCULINO
(?i)(mujer hombre)	SV_SEX0_MUJER_HOMBRE
(?i)(female male)	SV_SEX0_FEMALE_MALE
(?i)([fm])	SV_SEX0_F_M
(?i)([hm])	SV_SEX0_H_M
([12])	SV_SEX0_1_2
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

SV_SEX0_1_2 SECURE LOOKUP

Replaces the value with one of the 2 values in sv-sexo-1-2.txt , chosen by a keyed hash.

Used by: SV_SEX0

CONFIGURATION

lookupFile	sv-sexo-1-2.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_SEX0_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in sv-sexo-f-m.txt , chosen by a keyed hash.

Used by: SV_SEX0

CONFIGURATION

lookupFile	sv-sexo-f-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

SV_SEXO_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-sexo-female-male.txt` , chosen by a keyed hash.

Used by: `SV_SEX0`

CONFIGURATION

lookupFile	<code>sv-sexo-female-male.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_SEXO_FEMENINO_MASCULINO SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-sexo-femenino-masculino.txt` , chosen by a keyed hash.

Used by: `SV_SEX0`

CONFIGURATION

lookupFile	<code>sv-sexo-femenino-masculino.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-sexo-h-m.txt` , chosen by a keyed hash.

Used by: `SV_SEX0`

CONFIGURATION

lookupFile	<code>sv-sexo-h-m.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_SEXO_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `sv-sexo-mujer-hombre.txt` , chosen by a keyed hash.

Used by: `SV_SEX0`

CONFIGURATION

lookupFile	<code>sv-sexo-mujer-hombre.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

SV_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `sv-sin-informacion.txt`, chosen by a keyed hash.

Used by: `SV_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	<code>sv-sin-informacion.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `SV_L1_TARJETA`

PATTERNS, TRIED IN ORDER

<code>(\d[\d\s\-\-]{11,22}\d)</code>	<code>SV_TARJETA_LUHN</code>
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

SV_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: `SV_TARJETA`

CONFIGURATION

minMaskedPositions	6
preserve	0

SV_TELEFONO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `SV_CM_DIGITOS`.

Used by: `SV_L1_TELEFONO`

PATTERNS, TRIED IN ORDER

<code>(\+?503[\s\-\-]?)([267])(\d{3})([\s\-\-]?)(\d{4})</code>	keep · keep · <code>SV_CM_DIGITOS</code> · keep · <code>SV_CM_DIGITOS</code>
otherwise	<code>SV_CM_DIGITOS</code>

CONFIGURATION

trimInput	yes
requireMask	no

SV_TENENCIA_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`SV_TENENCIA_VIVIENDA_LISTA`.

Used by: `SV_FIN_VIVIENDA`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false yes [snyx01])</code>	<code>SV_BANDERA</code>
<code>(\d{1,6})</code>	<code>SV_CM_ALFANUM</code>
otherwise	<code>SV_TENENCIA_VIVIENDA_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

SV_TENENCIA_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `sv-tenencia-vivienda.txt` , chosen by a keyed hash.

Used by: `SV_TENENCIA_VIVIENDA`

CONFIGURATION

lookupFile	<code>sv-tenencia-vivienda.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

SV_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 9 patterns with `[DATO]` , and the 1,770 terms of `sv-texto-nombres.txt` with `[NOMBRE]` .

Used by: `SV_L1_TEXTO_LIBRE` , `SV_SALUD_TEXTO_CLINICO`

PATTERNS, TRIED IN ORDER

<code>(?<!\d)\d{8}-\d(?:\d)</code>
<code>(?<!\d)\d{4}-\d{6}-\d{3}-\d(?:\d)</code>
<code>(?<!\d)\d{9}(?:\d)</code>
<code>(?<!\d)\d{14}(?:\d)</code>
<code>[\w.+\\-]+@[\\w\\-]+(\\. [\\w\\-]+)+</code>
<code>(?<![\\d\\-])(\\+?503[\\s\\-]?)?[267]\\d{3}[\\s\\-]?\\d{4}(?![\\d\\-])</code>
<code>(?<!\d)\d{13,19}(?:\d)</code>
<code>(?<![A-Za-z])(P A C M N O AB CD)[\\s\\-]?\\d{3}[\\s\\-]?\\d{3}(?![A-Za-z\\d])</code>
<code>(?<!\d)(\\d{1,3}\\.){3}\\d{1,3}(?:\d)</code>

CONFIGURATION

regExRedactValue	<code>[DATO]</code>
lookupFile	<code>sv-texto-nombres.txt</code>
lookupFileRedactValue	<code>[NOMBRE]</code>
isDenyList	yes

SV_VALOR_DEUDA NUMERIC MAPPING

Maps the number to another between 100 and 250,000.

Used by: `SV_FIN_DEUDA`

CONFIGURATION

minValue	100
maxValue	250000

SV_VALOR_PENSION NUMERIC MAPPING

Maps the number to another between 304 and 3,000.

Used by: SV_FIN_PENSION

CONFIGURATION

minValue	304
maxValue	3000

SV_ZONA_RURAL SECURE LOOKUP

Replaces the value with one of the 1 values in sv-zona-rural.txt , chosen by a keyed hash.

Used by: SV_L2_CANTON

CONFIGURATION

lookupFile	sv-zona-rural.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
sv- antecedentes.txt	7	SV_ANTECEDENTES_LISTA	No registra antecedentes penales · Registra antecedentes · Procesado · Condenado
sv- apellidos.txt	347	SV_APELLIDO	Hernández · Rodríguez · Martínez · López
sv-aptitud- laboral.txt	4	SV_APTITUD_LABORAL_LISTA	Apto · Apto con restricciones · No apto · Pendiente
sv-bandera-0- 1.txt	2	SV_BANDERA_0_1	0 · 1
sv-bandera-s- n.txt	2	SV_BANDERA_S_N	S · N
sv-bandera-si- no.txt	2	SV_BANDERA_SI_NO	Sí · No
sv-bandera-true- false.txt	2	SV_BANDERA_TRUE_FALSE	true · false
sv-bandera-y- n.txt	2	SV_BANDERA_Y_N	Y · N
sv-bandera-yes- no.txt	2	SV_BANDERA_YES_NO	Yes · No
sv-centros- educativos.txt	12	SV_CENTRO_EDUCATIVO	Centro Escolar Cantón El Espino · Centro Escolar República de Panamá · Complejo Educativo Tomás Medina · Instituto Nacional General Francisco Menéndez
sv-cie10- decimal.txt	33	SV_CIE10_DECIMAL	E11.9 · E78.5 · J45.9 · J06.9
sv-cie10.txt	37	SV_CIE10	I10 · E11 · E78 · J45
sv-cobertura- salud.txt	8	SV_COBERTURA	ISSS · MINSAL (sistema público) · Bienestar Magisterial · Sanidad Militar (COSAM)
sv-codigos- geograficos- generalizados.tx t	190	SV_CODIGO_GEOGRAFICO	010102 010101 · 010104 010111 · 010205 010203 · 010209 010203
sv-colonias.txt	106	SV_COLONIA	Colonia Escalón · Colonia San Benito · Colonia Miramonte · Colonia Layco
sv-detectar- apellidos.txt	436	SV_L1_APELLIDO – List SV_L1_NOMBRE_COMPLETO – List	Hernández · Hernandez · Rodríguez · Rodriguez
sv-detectar- aptitud- laboral.txt	5	SV_SALUD_OCUPACIONAL – List	apto · no apto · apto con restricciones · pendiente
sv-detectar- cobertura.txt	20	SV_SALUD_COBERTURA – List	ISSS · MINSAL (sistema público) · MINSAL (sistema publico) · Bienestar Magisterial

FILE	LINES	USED BY	FIRST LINES
sv-detectar-codigos-banderas.txt	11	SV_L3_ORIGEN_ETNICO – List SV_FIN_PROGRAMA_SOCIAL – List	s · n · sí · si
sv-detectar-discapacidades.txt	26	SV_SALUD_DISCAPACIDAD – List	Física o motora · Fisica o motora · Auditiva · Visual
sv-detectar-distritos.txt	363	SV_L2_DISTRITO – List	Apaneca · Concepción de Ataco · Concepcion de Ataco · Tacuba
sv-detectar-escolaridad.txt	27	SV_L2_ESCOLARIDAD – List	Ninguno · Parvularia · Básica (1.º a 6.º) · Basica (1.º a 6.º)
sv-detectar-estado-familiar.txt	23	SV_L2_ESTADO_FAMILIAR – List	Soltero/a · Casado/a · Acompañado/a · Acompanado/a
sv-detectar-grupos-sanguineos.txt	18	SV_SALUD_GRUPO_SANGUIN E0 – List	A+ · A- · B+ · B-
sv-detectar-identidades-genero.txt	19	SV_L3_IDENTIDAD_GENERO – List	Mujer cisgénero · Mujer cisgenero · Hombre cisgénero · Hombre cisgenero
sv-detectar-ideologias-politicas.txt	16	SV_L3_IDEOLOGIA_POLITICA – List	Izquierda · Centroizquierda · Centro · Centroderecha
sv-detectar-lenguas.txt	25	SV_L3 LENGUA_INDIGENA – List	Español · Espanol · Náhuat · Nahuat
sv-detectar-medicamentos.txt	51	SV_SALUD_MEDICAMENTO – List	Acetaminofén · Acetaminofen · Ibuprofeno · Diclofenaco
sv-detectar-nacionalidades.txt	40	SV_L3_NACIONALIDAD – List	Salvadoreña · Salvadorena · Hondureña · Hondurena
sv-detectar-nombres.txt	466	SV_L1_NOMBRE – List SV_L1_NOMBRE_COMPLETO – List	José · Jose · María · Maria
sv-detectar-orientaciones-sexuales.txt	13	SV_L3_ORIENTACION_SEXUAL – List	Heterosexual · Gay · Lesbiana · Bisexual
sv-detectar-origen-etnico.txt	22	SV_L3_ORIGEN_ETNICO – List	Náhuat Pipil · Nahuat Pipil · Lenca · Kakawira (Cacaopera)
sv-detectar-partidos.txt	24	SV_L3_AFILIACION_PARTIDARIA – List	Nuevas Ideas · Alianza Republicana Nacionalista (ARENA) · Frente Farabundo Martí para la Liberación Nacional (FMLN) · Frente Farabundo Marti para la Liberacion Nacional (FMLN)
sv-detectar-programas-sociales.txt	20	SV_FIN_PROGRAMA_SOCIAL – List	Subsidio al gas licuado · Subsidio a la energía eléctrica · Subsidio a la energia electrica · Paquete agrícola
sv-detectar-religiones.txt	37	SV_L3_RELIGION – List	Católica · Catolica · Evangélica · Evangelica

FILE	LINES	USED BY	FIRST LINES
sv-detectar-sexo.txt	9	SV_L2_SEX0 – List	f · m · h · femenino
sv-detectar-sindicatos.txt	14	SV_L3_AFILIACION_SINDICAL – List	CATS · CSTS · CTS · SIMETRISSS
sv-detectar-tenencia-vivienda.txt	16	SV_FIN_VIVIENDA – List	Propia totalmente pagada · Propia pagándose · Propia pagandose · Alquilada
sv-diagnosticos.txt	30	SV_DIAGNOSTICO_TEXTO	Hipertensión arterial · Diabetes mellitus tipo 2 · Asma · Lumbalgia
sv-direcciones.txt	4,000	SV_DIRECCION	Calle Sur #147, Pol. 38, Colonia Las Brisas · Avenida Constitución #162 · Alameda Norte #662, Colonia Guadalupe · Calle Bernal #87
sv-discapacidades.txt	8	SV_DISCAPACIDAD_LISTA	Física o motora · Auditiva · Visual · Sordoceguera
sv-distritos-generalizados.txt	3,484	SV_DISTRITO	Apaneca Ahuachapán · Concepción de Ataco Tacuba · El Refugio Atiquizaya · San Lorenzo Atiquizaya
sv-empleadores.txt	24	SV_EMPLEADOR	Distribuidora Cuscatlán S.A. de C.V. · Constructora Salvadoreña S.A. de C.V. · Transportes El Trébol S.A. de C.V. · Supermercados La Despensa S.A. de C.V.
sv-escolaridad-codigos.txt	10	SV_ESCOLARIDAD_CODIGO	1 · 2 · 3 · 4
sv-escolaridad.txt	10	SV_ESCOLARIDAD_LISTA	Ninguno · Parvularia · Básica (1.º a 6.º) · Básica (7.º a 9.º)
sv-estado-familiar-codigos.txt	6	SV_ESTADO_FAMILIAR_CODIGO	1 · 2 · 3 · 4
sv-estado-familiar.txt	6	SV_ESTADO_FAMILIAR_LISTA	Soltero/a · Casado/a · Acompañado/a · Separado/a
sv-estados-credito.txt	10	SV_ESTADO_CREDITO	Al día · Mora de 30 días · Mora de 60 días · Mora de 90 días
sv-grupos-sanguineos.txt	8	SV_GRUPO_SANGUINEO	A+ · A- · B+ · B-
sv-identidades-genero.txt	7	SV_IDENTIDAD_GENERO_LISTA	Mujer cisgénero · Hombre cisgénero · Mujer trans · Hombre trans
sv-ideologias-politicas.txt	7	SV_IDEOLOGIA_POLITICA_LISTA	Izquierda · Centroizquierda · Centro · Centroderecha
sv-lenguas.txt	8	SV LENGUA_LISTA	Español · Náhuat · Lenca (potón) · Kakawira
sv-medicamentos.txt	22	SV_MEDICAMENTO_LISTA	Acetaminofén · Ibuprofeno · Diclofenaco · Metformina
sv-nacionalidades.txt	12	SV_NACIONALIDAD	Salvadoreña · Hondureña · Guatemalteca · Nicaragüense
sv-nombres.txt	405	SV_NOMBRE	José · María · Juan · Carlos
sv-ocupaciones.txt	35	SV_OCUPACION	Empleado administrativo · Vendedor · Cajero · Motorista

FILE	LINES	USED BY	FIRST LINES
sv-orientaciones-sexuales.txt	8	SV_ORIENTACION_SEXUAL_LISTA	Heterosexual · Gay · Lesbiana · Bisexual
sv-origen-etnico-codigos.txt	6	SV_ORIGEN_ETNICO_CODIGO	1 · 2 · 3 · 4
sv-origen-etnico.txt	8	SV_ORIGEN_ETNICO_LISTA	Náhuat Pipil · Lenca · Kakawira (Cacaoopera) · Mestizo
sv-partidos.txt	11	SV_PARTIDO_LISTA	Nuevas Ideas · Alianza Republicana Nacionalista (ARENA) · Frente Farabundo Martí para la Liberación Nacional (FMLN) · Gran Alianza por la Unidad Nacional (GANA)
sv-procedimientos.txt	10	SV_PROCEDIMIENTO_TEXTO	Consulta médica general · Consulta de emergencia · Hemograma completo · Glucosa en sangre
sv-programas-sociales.txt	7	SV_PROGRAMA_SOCIAL_LISTA	Subsidio al gas licuado · Subsidio a la energía eléctrica · Paquete agrícola · Paquete escolar
sv-religiones.txt	10	SV_RELIGION_LISTA	Católica · Evangélica · Protestante histórica · Testigo de Jehová
sv-sexo-1-2.txt	2	SV_SEXO_1_2	1 · 2
sv-sexo-f-m.txt	2	SV_SEXO_F_M	F · M
sv-sexo-female-male.txt	2	SV_SEXO_FEMALE_MALE	Female · Male
sv-sexo-femenino-masculino.txt	2	SV_SEXO_FEMENINO_MASCULINO	Femenino · Masculino
sv-sexo-h-m.txt	2	SV_SEXO_H_M	H · M
sv-sexo-mujer-hombre.txt	2	SV_SEXO_MUJER_HOMBRE	Mujer · Hombre
sv-sin-informacion.txt	1	SV_SUPRIMIR	Sin información
sv-tenencia-vivienda.txt	6	SV_TENENCIA_VIVIENDA_LISTA	Propia totalmente pagada · Propia pagándose · Alquilada · Cedida o prestada
sv-texto-nombres.txt	1,770	SV_TEXTO_LIBRE	José · JOSÉ · Jose · JOSE
sv-zona-rural.txt	1	SV_ZONA_RURAL	Zona rural

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 producto prod item articulo empresa emp razon social comercial archivo calle avenida pasaje colonia canton caserio barrio distrito municipio departamento depto dpto pais banco sucursal agencia plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo centro escuela colegio institucion universidad curso materia documento doc unidad clinica hospital issa seguro area dependencia cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa beneficio partido sindicato religion pueblo lengua lugar sede local tienda bodega proveedor convenio contrato poliza aseguradora entidad organismo organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura comprobante pago forma zona ruta linea actividad rubro sector file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador colaborador alumno estudiante deudor codeudor fiador solicitante propietario arrendatario inquilino conductor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge companero contacto referencia victima denunciante imputado procesado testigo medico docente socio heredero donante tutor jubilado pensionado cotizante customer patient employee member holder mother father spouse contact person student driver owner completo apellidos? usuario corto largo

E2 producto prod item articulo empresa emp razon social comercial archivo calle avenida pasaje colonia canton caserio barrio distrito municipio departamento depto dpto pais banco sucursal agencia plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo centro escuela colegio institucion universidad curso materia documento doc unidad clinica hospital issa seguro area dependencia cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa beneficio partido sindicato religion pueblo lengua lugar sede local tienda bodega proveedor convenio contrato poliza aseguradora entidad organismo organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura comprobante pago forma zona ruta linea actividad rubro sector file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador colaborador alumno estudiante deudor codeudor fiador solicitante propietario arrendatario inquilino conductor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge companero contacto referencia victima denunciante imputado procesado testigo medico docente socio heredero donante tutor jubilado pensionado cotizante customer patient employee member holder mother father spouse contact person student driver owner

E3 producto prod item articulo empresa emp razon social comercial archivo calle avenida pasaje colonia canton caserio barrio distrito municipio departamento depto dpto pais banco sucursal agencia plan campana proyecto servicio tabla columna campo usuario host servidor dominio marca modelo categoria tipo centro escuela colegio institucion universidad curso materia documento doc unidad clinica hospital issa seguro area dependencia cargo sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento diagnostico estudio programa beneficio partido sindicato religion pueblo lengua lugar sede local tienda bodega proveedor convenio contrato poliza aseguradora entidad organismo organizacion parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla imagen foto pagina sitio modulo menu opcion accion permiso concepto impuesto moneda emisor factura comprobante pago forma zona ruta linea actividad rubro sector file table column field user server product company category type school document department system group report role account place store supplier contract device image page module action key label code project city country street bank cliente cli paciente pac usuario afiliado asegurado beneficiario benef titular empleado trabajador colaborador alumno estudiante deudor codeudor fiador solicitante propietario arrendatario inquilino conductor responsable representante apoderado persona ciudadano contribuyente madre padre conyuge companero contacto referencia victima denunciante imputado procesado testigo medico docente socio heredero donante tutor jubilado pensionado cotizante customer patient employee member holder mother father spouse contact person student driver owner full complete last first

E4 ip mac email e_?mail correo electr[ó]nica web url tipo id general regional

E5 ip mac email e_?mail web url type id

E6 id cd cod codigo tipo fecha estado num nro

E7 id tipo codigo fecha estado cola log

Profile set and classifiers

The profile set `SV - Decreto 144 - v1` runs these 143 classifiers, with an assignment threshold of 60%.

Identificadores directos, cuasi-identificadores, datos sensibles (art. 4 g y art. 59 b), datos de salud, datos financieros y antecedentes penales, conforme a la Ley para la Protección de Datos Personales de El Salvador (Decreto Legislativo 144 de 2024).

CLASSIFIER	KIND	DOMAIN
SV_L1_DUI - Path	COLUMN NAME	SV_L1_DUI
SV_L1_DUI - Type	DATA TYPE	SV_L1_DUI
SV_L1_DUI - Regex	VALUE FORMAT	SV_L1_DUI
SV_L1_NIT - Path	COLUMN NAME	SV_L1_NIT
SV_L1_NIT - Regex	VALUE FORMAT	SV_L1_NIT
SV_L1_NRC - Path	COLUMN NAME	SV_L1_NRC
SV_L1_NRC - Regex	VALUE FORMAT	SV_L1_NRC
SV_L1_DOCUMENTO_EXTRANJERO - Path	COLUMN NAME	SV_L1_DOCUMENTO_EXTRANJERO
SV_L1_PASAPORTE - Path	COLUMN NAME	SV_L1_PASAPORTE
SV_L1_PASAPORTE - Regex	VALUE FORMAT	SV_L1_PASAPORTE
SV_L1_PARTIDA - Path	COLUMN NAME	SV_L1_PARTIDA
SV_L1_SEGURO_SOCIAL - Path	COLUMN NAME	SV_L1_SEGURO_SOCIAL
SV_L1_NIE - Path	COLUMN NAME	SV_L1_NIE
SV_L1_MATRICULA_PROFESIONAL - Path	COLUMN NAME	SV_L1_MATRICULA_PROFESIONAL
SV_L1_NOMBRE - Path	COLUMN NAME	SV_L1_NOMBRE
SV_L1_NOMBRE - List	KNOWN VALUES	SV_L1_NOMBRE
SV_L1_APELLIDO - Path	COLUMN NAME	SV_L1_APELLIDO
SV_L1_APELLIDO - List	KNOWN VALUES	SV_L1_APELLIDO
SV_L1_NOMBRE_COMPLETO - Path	COLUMN NAME	SV_L1_NOMBRE_COMPLETO
SV_L1_NOMBRE_COMPLETO - List	KNOWN VALUES	SV_L1_NOMBRE_COMPLETO
SV_L1_EMAIL - Path	COLUMN NAME	SV_L1_EMAIL
SV_L1_EMAIL - Type	DATA TYPE	SV_L1_EMAIL
SV_L1_EMAIL - Regex	VALUE FORMAT	SV_L1_EMAIL
SV_L1_TELEFONO - Path	COLUMN NAME	SV_L1_TELEFONO
SV_L1_TELEFONO - Regex	VALUE FORMAT	SV_L1_TELEFONO
SV_L1_DIRECCION - Path	COLUMN NAME	SV_L1_DIRECCION
SV_L1_DIRECCION - Type	DATA TYPE	SV_L1_DIRECCION
SV_L1_DIRECCION - Regex	VALUE FORMAT	SV_L1_DIRECCION
SV_L1_DIRECCION_COMPLEMENTO - Path	COLUMN NAME	SV_L1_DIRECCION_COMPLEMENTO
SV_L1_CUENTA_BANCARIA - Path	COLUMN NAME	SV_L1_CUENTA_BANCARIA

CLASSIFIER	KIND	DOMAIN
SV_L1_TARJETA – Path	COLUMN NAME	SV_L1_TARJETA
SV_L1_TARJETA – Regex	VALUE FORMAT	SV_L1_TARJETA
SV_L1_BILLETERA – Path	COLUMN NAME	SV_L1_BILLETERA
SV_L1_BILLETERA – Regex	VALUE FORMAT	SV_L1_BILLETERA
SV_L1_IP – Path	COLUMN NAME	SV_L1_IP
SV_L1_IP – Regex	VALUE FORMAT	SV_L1_IP
SV_L1_DISPOSITIVO – Path	COLUMN NAME	SV_L1_DISPOSITIVO
SV_L1_DISPOSITIVO – Regex	VALUE FORMAT	SV_L1_DISPOSITIVO
SV_L1_COOKIE – Path	COLUMN NAME	SV_L1_COOKIE
SV_L1_PLACA – Path	COLUMN NAME	SV_L1_PLACA
SV_L1_PLACA – Regex	VALUE FORMAT	SV_L1_PLACA
SV_L1_VEHICULO – Path	COLUMN NAME	SV_L1_VEHICULO
SV_L1_VEHICULO – Regex	VALUE FORMAT	SV_L1_VEHICULO
SV_L1_INMUEBLE – Path	COLUMN NAME	SV_L1_INMUEBLE
SV_L1_CONTRATO – Path	COLUMN NAME	SV_L1_CONTRATO
SV_L1_USUARIO – Path	COLUMN NAME	SV_L1_USUARIO
SV_L1_CREDENCIAL – Path	COLUMN NAME	SV_L1_CREDENCIAL
SV_L1_GEOLOCALIZACION – Path	COLUMN NAME	SV_L1_GEOLOCALIZACION
SV_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	SV_L1_GEOLOCALIZACION
SV_L1_TEXTO_LIBRE – Path	COLUMN NAME	SV_L1_TEXTO_LIBRE
SV_L1_TEXTO_LIBRE – Type	DATA TYPE	SV_L1_TEXTO_LIBRE
SV_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	SV_L1_TEXTO_LIBRE
SV_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	SV_L2_FECHA_NACIMIENTO
SV_L2_FECHA_NACIMIENTO – Type	DATA TYPE	SV_L2_FECHA_NACIMIENTO
SV_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	SV_L2_ANIO_NACIMIENTO
SV_L2_ANIO_NACIMIENTO – Type	DATA TYPE	SV_L2_ANIO_NACIMIENTO
SV_L2_EDAD – Path	COLUMN NAME	SV_L2_EDAD
SV_L2_EDAD – Type	DATA TYPE	SV_L2_EDAD
SV_L2_FECHA_EVENTO – Path	COLUMN NAME	SV_L2_FECHA_EVENTO
SV_L2_FECHA_EVENTO – Type	DATA TYPE	SV_L2_FECHA_EVENTO
SV_L2_SEX0 – Path	COLUMN NAME	SV_L2_SEX0
SV_L2_SEX0 – List	KNOWN VALUES	SV_L2_SEX0
SV_L2_DISTRITO – Path	COLUMN NAME	SV_L2_DISTRITO
SV_L2_DISTRITO – List	KNOWN VALUES	SV_L2_DISTRITO
SV_L2_CODIGO_GEOGRAFICO – Path	COLUMN NAME	SV_L2_CODIGO_GEOGRAFICO
SV_L2_CODIGO_GEOGRAFICO – Regex	VALUE FORMAT	SV_L2_CODIGO_GEOGRAFICO
SV_L2_CANTON – Path	COLUMN NAME	SV_L2_CANTON

CLASSIFIER	KIND	DOMAIN
SV_L2_COLONIA – Path	COLUMN NAME	SV_L2_COLONIA
SV_L2_CODIGO_POSTAL – Path	COLUMN NAME	SV_L2_CODIGO_POSTAL
SV_L2_CODIGO_POSTAL – Type	DATA TYPE	SV_L2_CODIGO_POSTAL
SV_L2_ESTADO_FAMILIAR – Path	COLUMN NAME	SV_L2_ESTADO_FAMILIAR
SV_L2_ESTADO_FAMILIAR – List	KNOWN VALUES	SV_L2_ESTADO_FAMILIAR
SV_L2_OCUPACION – Path	COLUMN NAME	SV_L2_OCUPACION
SV_L2_EMPLEADOR – Path	COLUMN NAME	SV_L2_EMPLEADOR
SV_L2_ESCOLARIDAD – Path	COLUMN NAME	SV_L2_ESCOLARIDAD
SV_L2_ESCOLARIDAD – List	KNOWN VALUES	SV_L2_ESCOLARIDAD
SV_L2_CENTRO_EDUCATIVO – Path	COLUMN NAME	SV_L2_CENTRO_EDUCATIVO
SV_L2_PERSONAS_A_CARGO – Path	COLUMN NAME	SV_L2_PERSONAS_A_CARGO
SV_L2_PERSONAS_A_CARGO – Type	DATA TYPE	SV_L2_PERSONAS_A_CARGO
SV_L3_ORIGEN_ETNICO – Path	COLUMN NAME	SV_L3_ORIGEN_ETNICO
SV_L3_ORIGEN_ETNICO – List	KNOWN VALUES	SV_L3_ORIGEN_ETNICO
SV_L3 LENGUA_INDIGENA – Path	COLUMN NAME	SV_L3 LENGUA_INDIGENA
SV_L3 LENGUA_INDIGENA – List	KNOWN VALUES	SV_L3 LENGUA_INDIGENA
SV_L3_NACIONALIDAD – Path	COLUMN NAME	SV_L3_NACIONALIDAD
SV_L3_NACIONALIDAD – List	KNOWN VALUES	SV_L3_NACIONALIDAD
SV_L3_RELIGION – Path	COLUMN NAME	SV_L3_RELIGION
SV_L3_RELIGION – List	KNOWN VALUES	SV_L3_RELIGION
SV_L3_CONVICCION_FILOSOFICA – Path	COLUMN NAME	SV_L3_CONVICCION_FILOSOFICA
SV_L3_IDEOLOGIA_POLITICA – Path	COLUMN NAME	SV_L3_IDEOLOGIA_POLITICA
SV_L3_IDEOLOGIA_POLITICA – List	KNOWN VALUES	SV_L3_IDEOLOGIA_POLITICA
SV_L3_AFILIACION_PARTIDARIA – Path	COLUMN NAME	SV_L3_AFILIACION_PARTIDARIA
SV_L3_AFILIACION_PARTIDARIA – List	KNOWN VALUES	SV_L3_AFILIACION_PARTIDARIA
SV_L3_AFILIACION_SINDICAL – Path	COLUMN NAME	SV_L3_AFILIACION_SINDICAL
SV_L3_AFILIACION_SINDICAL – List	KNOWN VALUES	SV_L3_AFILIACION_SINDICAL
SV_L3_BIOMETRICO – Path	COLUMN NAME	SV_L3_BIOMETRICO
SV_L3_BIOMETRICO – Type	DATA TYPE	SV_L3_BIOMETRICO
SV_L3_GENETICO – Path	COLUMN NAME	SV_L3_GENETICO
SV_L3_ORIENTACION_SEXUAL – Path	COLUMN NAME	SV_L3_ORIENTACION_SEXUAL
SV_L3_ORIENTACION_SEXUAL – List	KNOWN VALUES	SV_L3_ORIENTACION_SEXUAL
SV_L3_VIDA_SEXUAL – Path	COLUMN NAME	SV_L3_VIDA_SEXUAL
SV_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	SV_L3_IDENTIDAD_GENERO
SV_L3_IDENTIDAD_GENERO – List	KNOWN VALUES	SV_L3_IDENTIDAD_GENERO
SV_L3_SITUACION_FAMILIAR – Path	COLUMN NAME	SV_L3_SITUACION_FAMILIAR
SV_L3_HABITOS – Path	COLUMN NAME	SV_L3_HABITOS

CLASSIFIER	KIND	DOMAIN
SV_L3_VICTIMA – Path	COLUMN NAME	SV_L3_VICTIMA
SV_SALUD_IDENTIFICADOR – Path	COLUMN NAME	SV_SALUD_IDENTIFICADOR
SV_SALUD_COBERTURA – Path	COLUMN NAME	SV_SALUD_COBERTURA
SV_SALUD_COBERTURA – List	KNOWN VALUES	SV_SALUD_COBERTURA
SV_SALUD_DIAGNOSTICO – Path	COLUMN NAME	SV_SALUD_DIAGNOSTICO
SV_SALUD_DIAGNOSTICO – Regex	VALUE FORMAT	SV_SALUD_DIAGNOSTICO
SV_SALUD_PROCEDIMIENTO – Path	COLUMN NAME	SV_SALUD_PROCEDIMIENTO
SV_SALUD_MEDICAMENTO – Path	COLUMN NAME	SV_SALUD_MEDICAMENTO
SV_SALUD_MEDICAMENTO – List	KNOWN VALUES	SV_SALUD_MEDICAMENTO
SV_SALUD_TEXTO_CLINICO – Path	COLUMN NAME	SV_SALUD_TEXTO_CLINICO
SV_SALUD_TEXTO_CLINICO – Type	DATA TYPE	SV_SALUD_TEXTO_CLINICO
SV_SALUD_RESULTADO_EXAMEN – Path	COLUMN NAME	SV_SALUD_RESULTADO_EXAMEN
SV_SALUD_VIH – Path	COLUMN NAME	SV_SALUD_VIH
SV_SALUD_GRUPO_SANGUINEO – Path	COLUMN NAME	SV_SALUD_GRUPO_SANGUINEO
SV_SALUD_GRUPO_SANGUINEO – List	KNOWN VALUES	SV_SALUD_GRUPO_SANGUINEO
SV_SALUD_DISCAPACIDAD – Path	COLUMN NAME	SV_SALUD_DISCAPACIDAD
SV_SALUD_DISCAPACIDAD – List	KNOWN VALUES	SV_SALUD_DISCAPACIDAD
SV_SALUD_OCUPACIONAL – Path	COLUMN NAME	SV_SALUD_OCUPACIONAL
SV_SALUD_OCUPACIONAL – List	KNOWN VALUES	SV_SALUD_OCUPACIONAL
SV_SALUD_REPRODUCTIVA – Path	COLUMN NAME	SV_SALUD_REPRODUCTIVA
SV_SALUD_MENTAL – Path	COLUMN NAME	SV_SALUD_MENTAL
SV_FIN_HISTORIAL_CREDITICIO – Path	COLUMN NAME	SV_FIN_HISTORIAL_CREDITICIO
SV_FIN_DEUDA – Path	COLUMN NAME	SV_FIN_DEUDA
SV_FIN_DEUDA – Type	DATA TYPE	SV_FIN_DEUDA
SV_FIN_INGRESOS – Path	COLUMN NAME	SV_FIN_INGRESOS
SV_FIN_INGRESOS – Type	DATA TYPE	SV_FIN_INGRESOS
SV_FIN_PATRIMONIO – Path	COLUMN NAME	SV_FIN_PATRIMONIO
SV_FIN_PATRIMONIO – Type	DATA TYPE	SV_FIN_PATRIMONIO
SV_FIN_PENSION – Path	COLUMN NAME	SV_FIN_PENSION
SV_FIN_PENSION – Type	DATA TYPE	SV_FIN_PENSION
SV_FIN_REMESAS – Path	COLUMN NAME	SV_FIN_REMESAS
SV_FIN_REMESAS – Type	DATA TYPE	SV_FIN_REMESAS
SV_FIN_PROGRAMA_SOCIAL – Path	COLUMN NAME	SV_FIN_PROGRAMA_SOCIAL
SV_FIN_PROGRAMA_SOCIAL – List	KNOWN VALUES	SV_FIN_PROGRAMA_SOCIAL
SV_FIN_VIVIENDA – Path	COLUMN NAME	SV_FIN_VIVIENDA
SV_FIN_VIVIENDA – List	KNOWN VALUES	SV_FIN_VIVIENDA
SV_PENAL_ANTECEDENTES – Path	COLUMN NAME	SV_PENAL_ANTECEDENTES

CLASSIFIER	KIND	DOMAIN
SV_PENAL_EXPEDIENTE – Path	COLUMN NAME	SV_PENAL_EXPEDIENTE
SV_PENAL_EXPEDIENTE – Regex	VALUE FORMAT	SV_PENAL_EXPEDIENTE