

Belize — Data Protection Act, 2021

Discovery and masking of Belizean personal data: identity numbers and names, quasi-identifiers, the sensitive personal data of section 2 — including financial record or position and criminal proceedings — and health records.

72

DOMAINS

124

CLASSIFIERS

90

ALGORITHMS

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	About this profile set
2	The Data Protection Act, 2021 at a glance
3	How sensitive data is discovered
4	How data is masked
5	Essential and extended packs
6	Domains at a glance

PART 7 · DIRECT IDENTIFIERS

7.1	Social security number	BZ_L1_SOCIAL_SECURITY_NUMBER
7.2	Taxpayer identification number	BZ_L1_TIN
7.3	Passport	BZ_L1_PASSPORT
7.4	Voter ID	BZ_L1_VOTER_ID
7.5	Driver's licence	BZ_L1_DRIVERS_LICENCE
7.6	Immigration document	BZ_L1_IMMIGRATION_DOCUMENT
7.7	Civil registry entry	BZ_L1_VITAL_RECORD
7.8	Given names	BZ_L1_GIVEN_NAME
7.9	Surnames	BZ_L1_SURNAME
7.10	Full name	BZ_L1_FULL_NAME
7.11	E-mail	BZ_L1_EMAIL
7.12	Phone	BZ_L1_PHONE
7.13	Address	BZ_L1_ADDRESS
7.14	Address detail	BZ_L1_ADDRESS_DETAIL
7.15	Bank account	BZ_L1_BANK_ACCOUNT
7.16	Payment card	BZ_L1_PAYMENT_CARD
7.17	IP address	BZ_L1_IP_ADDRESS
7.18	Device identifier	BZ_L1_DEVICE_ID
7.19	Licence plate	BZ_L1_LICENCE_PLATE
7.20	Vehicle identification number	BZ_L1_VIN
7.21	Land parcel	BZ_L1_LAND_PARCEL
7.22	Contract or customer number	BZ_L1_CONTRACT_NUMBER
7.23	User name or social media	BZ_L1_USERNAME
7.24	Credential	BZ_L1_CREDENTIAL
7.25	Geolocation	BZ_L1_GEOLOCATION

7.26	Free text	BZ_L1_FREE_TEXT
------	-----------	-----------------

PART 8 · QUASI-IDENTIFIERS

8.1	Birth date	BZ_L2_BIRTH_DATE
8.2	Birth year	BZ_L2_BIRTH_YEAR
8.3	Age	BZ_L2_AGE
8.4	Life event dates	BZ_L2_EVENT_DATE
8.5	Sex	BZ_L2_SEX
8.6	Town or village	BZ_L2_TOWN_VILLAGE
8.7	Neighbourhood	BZ_L2_NEIGHBOURHOOD
8.8	Nationality	BZ_L2_NATIONALITY
8.9	Marital status	BZ_L2_MARITAL_STATUS
8.10	Occupation	BZ_L2_OCCUPATION
8.11	Employer	BZ_L2_EMPLOYER
8.12	Education	BZ_L2_EDUCATION
8.13	School	BZ_L2_SCHOOL
8.14	Children and dependants	BZ_L2_DEPENDANTS

PART 9 · SENSITIVE PERSONAL DATA

9.1	Ethnic origin	BZ_L3_ETHNICITY
9.2	Language	BZ_L3_LANGUAGE
9.3	Religion	BZ_L3_RELIGION
9.4	Beliefs of a similar nature	BZ_L3_BELIEF
9.5	Political opinion	BZ_L3_POLITICAL_OPINION
9.6	Membership of a political body	BZ_L3_POLITICAL_MEMBERSHIP
9.7	Trade union membership	BZ_L3_TRADE_UNION
9.8	Genetic data	BZ_L3_GENETIC
9.9	Biometric data	BZ_L3_BIOMETRIC
9.10	Sexual orientation	BZ_L3_SEXUAL_ORIENTATION
9.11	Sexual life	BZ_L3_SEXUAL_LIFE
9.12	Gender identity	BZ_L3_GENDER_IDENTITY

PART 10 · HEALTH RECORDS

10.1	Health identifier	BZ_HEALTH_ID
10.2	Diagnosis	BZ_HEALTH_DIAGNOSIS
10.3	Medication	BZ_HEALTH_MEDICATION
10.4	Clinical text	BZ_HEALTH_CLINICAL_TEXT
10.5	Test result	BZ_HEALTH_TEST_RESULT

10.6	Blood group	BZ_HEALTH_BLOOD_GROUP
10.7	Disability	BZ_HEALTH_DISABILITY
10.8	Sexual and reproductive health	BZ_HEALTH_REPRODUCTIVE
10.9	Mental health and addiction	BZ_HEALTH_MENTAL

PART 11 · FINANCIAL RECORD OR POSITION

11.1	Credit reference	BZ_FIN_CREDIT_REFERENCE
11.2	Debt amount	BZ_FIN_DEBT
11.3	Salary and income	BZ_FIN_INCOME
11.4	Assets	BZ_FIN_ASSETS
11.5	Pension	BZ_FIN_PENSION
11.6	Social security benefit	BZ_FIN_SSB_BENEFIT
11.7	Social programme	BZ_FIN_SOCIAL_PROGRAMME
11.8	Poverty and socioeconomic status	BZ_FIN_POVERTY
11.9	Housing tenure	BZ_FIN_HOUSING

PART 12 · CRIMINAL RECORD AND PROCEEDINGS

12.1	Criminal record and proceedings	BZ_PENAL_CRIMINAL_RECORD
12.2	Case number	BZ_PENAL_CASE_NUMBER
13	Where people live: towns and villages	
14	Limits	
15	Verification	
16	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	
D	Profile set and classifiers	

About this profile set

This profile set finds the personal data in a Belizean database and masks it, so that a non-production copy — for testing, development, training or analytics — no longer identifies anyone.

Masking only names and social security numbers does not get there: a birth date, a sex and a village of a few hundred people are enough to point at one person. The set works on the layers where the risk is:

- **Direct identifiers** — social security number, TIN, passport, voter ID, driver's licence, immigration permits, civil registry entries, names, contact, accounts and cards, land parcels, devices, vehicles, free text.
- **Quasi-identifiers** — birth date, age, sex, town or village, neighbourhood, nationality, marital status, occupation, employer, education.
- **Sensitive personal data** — the categories of section 2: racial or ethnic origin, political opinions, religious and similar beliefs, membership of a political body, trade union membership, genetic and biometric data, sexual orientation and sexual life — and, beyond the list, gender identity.
- **Health records** — health identifiers, diagnoses, medications, clinical notes, test results, disability, reproductive and mental health.
- **Financial record or position** — credit references, debt, income, assets, pensions, social security benefits, social programmes, poverty and housing tenure. Section 2 makes them sensitive.
- **Criminal record and proceedings** — records, charges, outcomes and case numbers, also sensitive under section 2.

On a Masking Engine the set is one profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those build on — and the lookup files they read. The appendices list every one of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it alone; an ambiguous one — `NAME`, `RESULT`, `CITY` — needs the values to agree. A column with a meaningless name (`FIELD1`, `REMARKS`) is still found when its values have a recognizable shape or vocabulary: a social security number, a Belizean phone number, a plate, a village.

Column names are recognized in English, in the abbreviations of Belizean systems (`SSN`, `SSB_NO`, `TIN`, `BHIS_NO`, `NHI_NO`, `DOB`) and in Spanish, which a large part of the country speaks.

Before masking, inventory the binary columns (BLOBs, images, PDFs). Onboarding processes often store a scan of the social security card or passport: the number is still readable in the image. Report those columns as residual risk.

The Data Protection Act, 2021 at a glance

The Data Protection Act, 2021 — Act No. 45 of 2021 — was assented to on 29 November 2021 and gazetted on 30 November 2021. It regulates the collection, keeping, use and dissemination of personal data and protects the privacy of individuals in relation to it.

Commencement. The Act comes into force on a day appointed by the Minister by Order published in the Gazette, and different days may be appointed for different provisions (s. 97). In the public sources consulted in September 2026 no commencement Order was found, and secondary sources disagree on whether and when the Act took effect. Confirm the status with the Ministry before relying on a date; the design of the set does not depend on it.

What matters for a copy of production data:

- **Personal data** is data which relates to an individual who can be identified from that data, or from that data together with other information which is in the possession of, or is likely to come into the possession of, the data controller (s. 2). Data from which no individual can be identified, even with that other information, is not personal data.
- **Sensitive personal data** is information on a data subject's racial or ethnic origin; political opinions; religious beliefs or other beliefs of a similar nature; membership of a political body; membership of a trade union; genetic data; biometric data; sexual orientation or sexual life; **financial record or position**; criminal record; and proceedings for any offence committed or alleged to have been committed, their disposal or sentence (s. 2). Health is not on the list; genetic and biometric data are, and the Act defines both.
- **Processing of sensitive personal data is prohibited** unless one of the conditions of section 10 applies — consent, employment obligations, vital interests, legal proceedings, public functions, medical purposes under a duty of confidentiality, among others. Data relating to criminal convictions and offences is processed only under the control of an official authority or as an enactment authorises (s. 10(2)).
- **Principles.** Personal data is collected for specified, explicit and legitimate purposes and not further processed in a manner incompatible with them; it is adequate, relevant and limited to what is necessary; kept in identifiable form no longer than necessary; and processed with appropriate security (s. 4). A controller who fails to comply commits an offence punishable by a fine of five hundred thousand dollars, imprisonment for three years, or both (s. 5(7)).
- **Security.** Technical and organisational measures appropriate to the risk, including pseudonymisation and encryption (s. 60), and data protection by design and by default (s. 55).
- **Breaches.** The Commissioner is notified without undue delay and, where feasible, within seventy-two hours (s. 61). Data subjects are told when the breach is likely to result in a high risk — unless the data affected had been rendered unintelligible to anyone not authorised to access it (s. 62).
- **Children.** A child is a person under 16. Processing a child's data is lawful only with the consent of a parent or guardian, or of the child when over thirteen (s. 9).
- **Scope.** Small businesses, with an annual turnover of \$3,000,000 or less, are exempt — except those providing health services, credit reporting bodies, reporting entities under the anti-money-laundering law and others listed in section 3(3).
- **Research and statistics.** Processing only for research, statistical or historical purposes is compatible with the original purpose when results are not made available in a form which identifies data subjects (s. 36).
- **Supervision.** The Data Protection Commissioner, a public officer in the Ministry responsible for digital transformation and e-governance who acts independently, administers the Act (s. 68); appeals go to the Data Protection Tribunal (s. 88).

A test environment with production data is processing for purposes the data was not collected for, and it holds sensitive data — financial and criminal data among them — outside the controls built for it. A copy from which individuals can no longer be identified is not personal data: that is what the set is for.

The list of sensitive data in section 2 is closed, but the set goes further where the risk is the same: it treats health records, gender identity and the language a person speaks — which reveals Maya, Garifuna or Mennonite origin — with the same care.

The definition of personal data counts what the controller holds or is likely to hold. Masking is deterministic for the engine key, so whoever has both the production data and the key can link a masked row back to its source. Keep the key, and access to production, away from the people who use the masked copy. Whether a copy counts as anonymised is a legal assessment of the whole environment, not of the profile set alone.

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters: `rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

4

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

5

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	11	22	10	5

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Extended	72	124	90	70

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- Social security number — BZ_L1_SOCIAL_SECURITY_NUMBER
- Taxpayer identification number — BZ_L1_TIN
- Passport — BZ_L1_PASSPORT
- Given names — BZ_L1_GIVEN_NAME
- Surnames — BZ_L1_SURNAME
- Full name — BZ_L1_FULL_NAME
- E-mail — BZ_L1_EMAIL
- Phone — BZ_L1_PHONE
- Address — BZ_L1_ADDRESS
- Address detail — BZ_L1_ADDRESS_DETAIL
- Birth date — BZ_L2_BIRTH_DATE

With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY			ALGORITHM
DIRECT IDENTIFIERS				
Social security number ESSENTIAL BZ_L1_SOCIAL_SECURITY_NUMBER	COLUMN NAME	VALUE FORMAT	BZ_CM_ALNUM	
Taxpayer identification number ESSENTIAL BZ_L1_TIN	COLUMN NAME		BZ_CM_ALNUM	
Passport ESSENTIAL BZ_L1_PASSPORT	COLUMN NAME	VALUE FORMAT	BZ_CM_ALNUM	
Voter ID BZ_L1_VOTER_ID	COLUMN NAME		BZ_CM_ALNUM	
Driver's licence BZ_L1_DRIVERS_LICENCE	COLUMN NAME		BZ_CM_ALNUM	
Immigration document BZ_L1_IMMIGRATION_DOCUMENT	COLUMN NAME		BZ_CM_ALNUM	
Civil registry entry BZ_L1_VITAL_RECORD	COLUMN NAME		BZ_CM_ALNUM	
Given names ESSENTIAL BZ_L1_GIVEN_NAME	COLUMN NAME	KNOWN VALUES	BZ_GIVEN_NAMES	
Surnames ESSENTIAL BZ_L1_SURNAME	COLUMN NAME	KNOWN VALUES	BZ_SURNAMES	
Full name ESSENTIAL BZ_L1_FULL_NAME	COLUMN NAME	KNOWN VALUES	BZ_FULL_NAME	
E-mail ESSENTIAL BZ_L1_EMAIL	COLUMN NAME	DATA TYPE	VALUE FORMAT	BZ_EMAIL
Phone ESSENTIAL BZ_L1_PHONE	COLUMN NAME	VALUE FORMAT	BZ_PHONE	
Address ESSENTIAL BZ_L1_ADDRESS	COLUMN NAME	DATA TYPE	VALUE FORMAT	BZ_ADDRESS
Address detail ESSENTIAL BZ_L1_ADDRESS_DETAIL	COLUMN NAME		BZ_CM_ALNUM	
Bank account BZ_L1_BANK_ACCOUNT	COLUMN NAME		BZ_CM_ALNUM	
Payment card BZ_L1_PAYMENT_CARD	COLUMN NAME	VALUE FORMAT	BZ_CARD	
IP address BZ_L1_IP_ADDRESS	COLUMN NAME	VALUE FORMAT	BZ_IP	
Device identifier BZ_L1_DEVICE_ID	COLUMN NAME	VALUE FORMAT	BZ_CM_HEX	
Licence plate BZ_L1_LICENCE_PLATE	COLUMN NAME	VALUE FORMAT	BZ_PLATE	

DOMAIN	FOUND BY			ALGORITHM
Vehicle identification number BZ_L1_VIN	COLUMN NAME	VALUE FORMAT		BZ_CM_ALNUM
Land parcel BZ_L1_LAND_PARCEL	COLUMN NAME	VALUE FORMAT		BZ_PARCEL
Contract or customer number BZ_L1_CONTRACT_NUMBER	COLUMN NAME			BZ_CM_ALNUM
User name or social media BZ_L1_USERNAME	COLUMN NAME			BZ_CM_ALNUM
Credential BZ_L1_CREDENTIAL	COLUMN NAME			BZ_REDACT
Geolocation BZ_L1_GEOLOCATION	COLUMN NAME	VALUE FORMAT		BZ_COORDINATE
Free text BZ_L1_FREE_TEXT	COLUMN NAME	DATA TYPE	VALUE FORMAT	BZ_FREE_TEXT
QUASI-IDENTIFIERS				
Birth date ESSENTIAL BZ_L2_BIRTH_DATE	COLUMN NAME	DATA TYPE		BZ_BIRTH_DATE
Birth year BZ_L2_BIRTH_YEAR	COLUMN NAME	DATA TYPE		BZ_YEAR
Age BZ_L2_AGE	COLUMN NAME	DATA TYPE		BZ_AGE
Life event dates BZ_L2_EVENT_DATE	COLUMN NAME	DATA TYPE		BZ_EVENT_DATE
Sex BZ_L2_SEX	COLUMN NAME	KNOWN VALUES		BZ_SEX
Town or village BZ_L2_TOWN_VILLAGE	COLUMN NAME	KNOWN VALUES		BZ_TOWN_VILLAGE
Neighbourhood BZ_L2_NEIGHBOURHOOD	COLUMN NAME			BZ_NEIGHBOURHOOD
Nationality BZ_L2_NATIONALITY	COLUMN NAME	KNOWN VALUES		BZ_NATIONALITY
Marital status BZ_L2_MARITAL_STATUS	COLUMN NAME	KNOWN VALUES		BZ_MARITAL_STATUS
Occupation BZ_L2_OCCUPATION	COLUMN NAME			BZ_OCCUPATION
Employer BZ_L2_EMPLOYER	COLUMN NAME			BZ_EMPLOYER
Education BZ_L2_EDUCATION	COLUMN NAME	KNOWN VALUES		BZ_EDUCATION
School BZ_L2_SCHOOL	COLUMN NAME			BZ_SCHOOL
Children and dependants BZ_L2_DEPENDANTS	COLUMN NAME	DATA TYPE		BZ_CAPPED_COUNT
SENSITIVE PERSONAL DATA				

DOMAIN	FOUND BY		ALGORITHM
Ethnic origin BZ_L3_ETHNICITY	COLUMN NAME	KNOWN VALUES	BZ_ETHNICITY
Language BZ_L3_LANGUAGE	COLUMN NAME	KNOWN VALUES	BZ_LANGUAGE
Religion BZ_L3_RELIGION	COLUMN NAME	KNOWN VALUES	BZ_RELIGION
Beliefs of a similar nature BZ_L3_BELIEF	COLUMN NAME		BZ_SUPPRESSED_CATEGORY
Political opinion BZ_L3_POLITICAL_OPINION	COLUMN NAME	KNOWN VALUES	BZ_POLITICAL_OPINION
Membership of a political body BZ_L3_POLITICAL_MEMBERSHIP	COLUMN NAME	KNOWN VALUES	BZ_POLITICAL_PARTY
Trade union membership BZ_L3_TRADE_UNION	COLUMN NAME	KNOWN VALUES	BZ_SUPPRESSED_CATEGORY
Genetic data BZ_L3_GENETIC	COLUMN NAME		BZ_REDACT
Biometric data BZ_L3_BIOMETRIC	COLUMN NAME	DATA TYPE	BZ_REDACT
Sexual orientation BZ_L3_SEXUAL_ORIENTATION	COLUMN NAME	KNOWN VALUES	BZ_SEXUAL_ORIENTATION
Sexual life BZ_L3_SEXUAL_LIFE	COLUMN NAME		BZ_SUPPRESSED_CATEGORY
Gender identity BZ_L3_GENDER_IDENTITY	COLUMN NAME	KNOWN VALUES	BZ_GENDER_IDENTITY
HEALTH RECORDS			
Health identifier BZ_HEALTH_ID	COLUMN NAME		BZ_CM_ALNUM
Diagnosis BZ_HEALTH_DIAGNOSIS	COLUMN NAME	VALUE FORMAT	BZ_DIAGNOSIS
Medication BZ_HEALTH_MEDICATION	COLUMN NAME	KNOWN VALUES	BZ_MEDICATION
Clinical text BZ_HEALTH_CLINICAL_TEXT	COLUMN NAME	DATA TYPE	BZ_FREE_TEXT
Test result BZ_HEALTH_TEST_RESULT	COLUMN NAME		BZ_CM_ALNUM
Blood group BZ_HEALTH_BLOOD_GROUP	COLUMN NAME	KNOWN VALUES	BZ_BLOOD_GROUP
Disability BZ_HEALTH_DISABILITY	COLUMN NAME	KNOWN VALUES	BZ_DISABILITY
Sexual and reproductive health BZ_HEALTH_REPRODUCTIVE	COLUMN NAME		BZ_SUPPRESSED_CATEGORY
Mental health and addiction BZ_HEALTH_MENTAL	COLUMN NAME		BZ_SUPPRESSED_CATEGORY
FINANCIAL RECORD OR POSITION			

DOMAIN	FOUND BY		ALGORITHM
Credit reference BZ_FIN_CREDIT_REFERENCE	COLUMN NAME		BZ_CREDIT
Debt amount BZ_FIN_DEBT	COLUMN NAME	DATA TYPE	BZ_DEBT_AMOUNT
Salary and income BZ_FIN_INCOME	COLUMN NAME	DATA TYPE	BZ_INCOME
Assets BZ_FIN_ASSETS	COLUMN NAME	DATA TYPE	BZ_ASSETS
Pension BZ_FIN_PENSION	COLUMN NAME	DATA TYPE	BZ_PENSION_AMOUNT
Social security benefit BZ_FIN_SSB_BENEFIT	COLUMN NAME	KNOWN VALUES	BZ_SSB_BENEFIT
Social programme BZ_FIN_SOCIAL_PROGRAMME	COLUMN NAME	KNOWN VALUES	BZ_SOCIAL_PROGRAMME
Poverty and socioeconomic status BZ_FIN_POVERTY	COLUMN NAME	KNOWN VALUES	BZ_POVERTY
Housing tenure BZ_FIN_HOUSING	COLUMN NAME	KNOWN VALUES	BZ_HOUSING
CRIMINAL RECORD AND PROCEEDINGS			
Criminal record and proceedings BZ_PENAL_CRIMINAL_RECORD	COLUMN NAME		BZ_CRIMINAL_RECORD
Case number BZ_PENAL_CASE_NUMBER	COLUMN NAME	VALUE FORMAT	BZ_CM_ALNUM

Direct identifiers

Data that identifies a person on its own. Belize has no national identity card for its citizens: the Social Security Board card is the everyday identification, asked for by employers, banks, the credit bureau and public hospitals, so its number is the key of most records. It is masked the same way everywhere, keeping its nine digits.

7.1 Social security number

BZ_L1_SOCIAL_SECURITY_NUMBER

ESSENTIAL COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The nine-digit number of the Social Security Board, printed on the card every worker must have from age 14. It is issued in sequence and has no public check digit. Without a national identity card, it is the identifier employers, banks, credit unions, the credit bureau and public hospitals ask for.

HOW IT IS FOUND

COLUMN NAME	BZ_L1_SOCIAL_SECURITY_NUMBER – Path		
90%	ssn ss_?(no num number nbr) social_?security(_?(no num number nbr card id))? soc_?sec(_?(no num number))?)? ssb_?(no num number id card) social_?sec_?card insured_?(person_)?(no num number) n(o um ro umero)_?(de_)?seguro_?social seguro_?social		
VALUE FORMAT	BZ_L1_SOCIAL_SECURITY_NUMBER – Regex		
PATTERN	STRENGTH	NOTES	
\d{3}[\s\–]\d{3}[\s\–]\d{3}		70%	
\d{9}		50%	
A value that matches none counts 30% against the domain.			

HOW IT IS MASKED

Each digit is mapped to another digit, keeping the length and any separators (123–456–789). The mapping is one-to-one: a social security number used as a key does not collide, and the same number masks the same way in every table.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
000123456	→ 522757585
123–456–789	→ 110–858–568

7.2 Taxpayer identification number

BZ_L1_TIN

ESSENTIAL COLUMN NAME CHARACTER MAPPING

WHAT IT IS

The TIN of the Belize Tax Service, used for income tax, GST, customs and excise: six digits and a check digit that is not shown to the taxpayer. Individuals, sole proprietors, partnerships and companies all have one.

HOW IT IS FOUND

COLUMN NAME	BZ_L1_TIN - Path
90%	tin tin?(no num number) tax?(id identification)(?(no num number))? tax_payer?(id no num number) taxpayer?(id no num number) bts?(no id tin number) gst?(no number reg registration)(?no)? n(o um ro)?contribuyente nit

HOW IT IS MASKED

Digit by digit, keeping the length. A company's TIN cannot be told apart from a person's and is masked too; the mapping is deterministic, so joins with supplier tables still work.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
123456	→ 904292

7.3 Passport

BZ_L1_PASSPORT

ESSENTIAL	COLUMN NAME	VALUE FORMAT	CHARACTER MAPPING
-----------	-------------	--------------	-------------------

WHAT IT IS

Belizean and foreign passport numbers.

HOW IT IS FOUND

COLUMN NAME	BZ_L1_PASSPORT - Path
85%	passport[a-z]* pass_port?(no num number) pp?(no num number) travel_document?(no num number)? pasaporte[a-z]*

VALUE FORMAT		BZ_L1_PASSPORT - Regex	
PATTERN		STRENGTH	NOTES
[A-Z]{1,2}\d{6,8}			30%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
P0123456	→ M1295864

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The ID number and the registration number of the voter identification card of the Elections and Boundaries Department — one of the photo IDs accepted across public services.

HOW IT IS FOUND

COLUMN NAME

BZ_L1_VOTER_ID - Path

85%

voter_?(id|card|reg|registration)(_?(no|num|number|card))? voters_?
(id|card|reg|registration)(_?(no|num|number))? elector(al)?_
(id|no|num|number|card|reg|registration)(_?(no|num|number))? ebd_?(no|id|reg|number)
registration_?(no|num|number)_?(voter|elector) elector_?reg?no

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
123456	→	904292

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

The number of the driver's licence issued by the Department of Transport or a town council.

HOW IT IS FOUND

COLUMN NAME

BZ_L1_DRIVERS_LICENCE - Path

85%

drivers?_?licen[cs]e(_?(no|num|number))? driving_?licen[cs]e(_?(no|num|number))? dl_
(no|num|number) licen[cs]e_(no|num|number) (except when followed by plate , vehicle , business ,
trade , liquor , professional) licencia_?(de_)?conducir

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
BZ-012345	→	CT-763680

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Permanent residence cards, temporary employment (work) permits, visas, nationality and naturalization certificates, refugee and asylum identification, Qualified Retired Persons cards. In a country where 11.5% of the population was born abroad, they are common in employment and banking records.

HOW IT IS FOUND

COLUMN NAME	BZ_L1_IMMIGRATION_DOCUMENT - Path
85%	<code>permanent_?residen(ce cy t)(_(?(permit card no num number id)))? pr_?(card permit)(_(?(no number)))? work_?permit(_(?(no num number)))? temporary_?employment_?permit tep_?(no num number) immigration_?(permit document card file status_?no no num number) visa_?(no num number) residen(ce cy)_?permit(_(?(no number)))? nationality_?certificate(_(?(no number)))? naturali[sz]ation_?(certificate cert no number) refugee_?(id card no number) asylum_?(id no number) qrp_?(id no number card) carne_?migratorio permiso_?(de_?)?(residencia trabajo)</code>

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
PR 12345	→ XY 20897

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Birth, death and marriage certificate or registry entry numbers of the Vital Statistics Unit.

HOW IT IS FOUND

COLUMN NAME	BZ_L1_VITAL_RECORD - Path
85%	<code>birth_?cert(ificate)?(_(?(no num number entry)))? death_?cert(ificate)?(_(?(no num number)))? marriage_?cert(ificate)?(_(?(no num number)))? registry_?entry(_(?(no number)))? vital_?(record statistics)_?(no num number) certificado_?(de_?)?(nacimiento defuncion matrimonio) acta_?(de_?)?(nacimiento defuncion matrimonio)</code>
55%	<code>entry_?(no number)</code>

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

1234/1985

→

1092/4201

7.8 Given names

BZ_L1_GIVEN_NAME

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

First and middle names (FIRST_NAME , MIDDLE_NAME), including two given names in one column such as Maria Isabel .

HOW IT IS FOUND

COLUMN NAME BZ_L1_GIVEN_NAME – Path

85% first_?names? given_?names? fore_?names? christian_?name fname name_?first middle_?names? mname name_?middle nombres?_?(de_?)?pila primer_?nombre segundo_?nombre nombres (except when followed by list E1)

50% name (except when followed by list E2) nombre (except when followed by list E3)

KNOWN VALUES BZ_L1_GIVEN_NAME – List

LIST	VALUES	STRENGTH	FIRST VALUES
bz-detect-given-names.txt	208	70%	Maria, Jose, Juan, Carlos, Luis, Francisco

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each word is replaced by a name from a list of 208 names used in Belize, keeping the number of words and the case. More than three words are masked character by character.

BZ_GIVEN_NAMES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

BZ_GIVEN_NAME NAME

Replaces the name with one of the 208 names in bz-given-names.txt .

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

Kenrick

→

Yvette

MARIA ISABEL

→

NELSON CANDELARIA

7.9 Surnames

BZ_L1_SURNAME

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Surnames and maiden names, one or two per column, and hyphenated surnames: Gillett , Gomez Cal , Young-Flowers .

COLUMN NAME BZ_L1_SURNAME - Path

85% last_?names? surnames? family_?names? lname name_?last maiden_?name mothers_?
maiden_?name maiden second_?surname married_?name apellidos? apellido_
(paterno|materno) primer_?apellido segundo_?apellido

KNOWN VALUES BZ_L1_SURNAME - List

LIST	VALUES	STRENGTH	FIRST VALUES
bz-detect-surnames.txt	225	70%	Martinez, Garcia, Castillo, Lopez, Williams, Perez

Values are split into words, and each word is looked up.
A value that matches none counts 30% against the domain.

Each surname is replaced by one from a list of 225 surnames frequent in Belize – Mestizo, Creole, Maya, Garifuna and Mennonite, led by Martinez, Garcia, Castillo, Lopez and Williams –, keeping the number of words, the hyphen and the case.

Tries 4 patterns in order and gives each part of the value its own action; when none matches: BZ CM ALNUM .

Replaces the name with one of the 225 names in `bz-surnames.txt`.

Maps each character to another of its group (7 groups), keeping length and format.

VALUE		MASKED
Gillett	→	Munoz
Young-Flowers	→	McKenzie-Ramirez

BZ L1 FULL NAME

REGEX DECOMPOSE

Given names and surnames in one column, in the English order used by the civil registry – given name, middle name, surname – with a middle initial or a second surname in Hispanic families, or written as SURNAME, GIVEN NAMES . Also the name of an account holder, beneficiary, guardian or next of kin.

HOW IT IS FOUND

COLUMN NAME BZ_L1_FULL_NAME - Path

90%	full_?name (customer cust client patient employee emp staff worker member student pupil insured beneficiary holder account_?holder policy_?holder mother father parent guardian spouse partner next_?of_?kin doctor physician nurse contact emergency_?contact guarantor debtor borrower applicant signatory witness representative owner tenant landlord victim complainant accused defendant donor heir person driver agent citizen elector voter taxpayer child dependant dependent relative officer teacher cliente paciente empleado beneficiario titular madre padre conyuge persona) (customer cust client patient employee emp staff worker member student pupil insured beneficiary holder account_?holder policy_?holder mother father parent guardian spouse partner next_?of_?kin doctor physician nurse contact emergency_?contact guarantor debtor borrower applicant signatory witness representative owner tenant landlord victim complainant accused defendant donor heir person driver agent citizen elector voter taxpayer child dependant dependent relative officer teacher cliente paciente empleado beneficiario titular madre padre conyuge persona)_?name nombre_?(completo compl) nombres?_?y_?apellidos?
60%	beneficiary guardian next_?of_?kin spouse emergency_?contact guarantor account_?holder policy_?holder legal_?representative attorney patient victim complainant accused defendant insured_?person titular beneficiario conyuge
50%	name (except when followed by list E2) nombre (except when followed by list E3)

KNOWN VALUES BZ_L1_FULL_NAME - List

LIST	VALUES	STRENGTH	FIRST VALUES
bz-detect-given-names.txt	208	60%	Maria, Jose, Juan, Carlos, Luis, Francisco
bz-detect-surnames.txt	225	60%	Martinez, Garcia, Castillo, Lopez, Williams, Perez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Given names become given names and surnames become surnames, by position: one word is a given name; two, a given name and a surname; three, two given names and a surname; four, two of each. A middle initial stays an initial (Kenrick A. Gillett), and a comma separates surnames from given names.

BZ_FULL_NAME REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

BZ_SURNAMES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

BZ_SURNAME NAME

Replaces the name with one of the 225 names in bz-surnames.txt .

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_GIVEN_NAMES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

BZ_GIVEN_NAME NAME

Replaces the name with one of the 208 names in `bz-given-names.txt`.

EXAMPLES

VALUE		MASKED
Kenrick A. Gillett	→	Yvette A. Munoz
Jose Luis Martinez Cal	→	Sylvia Cesar Contreras Requena
CAYETANO, SHANICE	→	ZETINA, OSCAR

7.11 E-mail

BZ_L1_EMAIL

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Personal and work e-mail addresses.

HOW IT IS FOUND

COLUMN NAME BZ_L1_EMAIL - Path

85% `e_?mail[a-z0-9_]*` `mail[a-z0-9_]*` `email_?address` `correo(_?electronico)?[a-z0-9_]*`

DATA TYPE BZ_L1_EMAIL - Type

Accepts text (length 5 or more); any other type rules the domain out.

VALUE FORMAT BZ_L1_EMAIL - Regex

PATTERN	STRENGTH	NOTES
<code>[A-Za-z0-9._%+\-]+\@[A-Za-z0-9.\-]+\.[A-Za-z]{2,24}</code>	100%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The name and domain are mapped character by character and the top-level domain becomes `.test`, reserved for testing; a masked address never receives mail.

BZ_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: BZ_CM_ALNUM.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
kenrick.gillett@gmail.com	→	hasyinl.gajzek@pgoeb.test

7.12 Phone

BZ_L1_PHONE

ESSENTIAL

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Seven-digit numbers, with or without `+501`: mobiles start with 6 (`622-4567`) and landlines with the digit of their district — 2 Belize, 3 Orange Walk, 4 Corozal, 5 Stann Creek, 7 Toledo, 8 Cayo.

HOW IT IS FOUND

COLUMN NAME BZ_L1_PHONE – Path

85% tel telephone[a-z0-9_]* tel_?(no|num|number|home|work|mobile|cell) phone[a-z0-9_]* ph_?
(no|num|number) mobile[a-z0-9_]* cell cell_?(phone|no|number) cellphone cellular
contact_?(no|num|number) fax whatsapp telefono[a-z0-9_]* celular movil n(o|um|ro)?
tel(efono)?

VALUE FORMAT BZ_L1_PHONE – Regex

PATTERN	STRENGTH	NOTES
(\+?(?501\)?[\s-]?)6\d{2}[\s-]?\d{4}	100%	
6\d{2}[\s-]?\d{4}	80%	
(\+?(?501\)?[\s-]?)?[2-578]\d{2}[\s-]?\d{4}	70%	
\+?\d[\d\s()\-]{6,15}	30%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

+501 , the separators and the first digit — mobile, or the district of a landline — stay; the other six digits are masked. A number not shaped like a Belizean number is masked whole.

BZ_PHONE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
+501 622-4567	→ +501 690-9910
822-1234	→ 890-9707

7.13 Address

BZ_L1_ADDRESS

ESSENTIAL COLUMN NAME DATA TYPE VALUE FORMAT SECURE LOOKUP

WHAT IT IS

The address line as written in Belize, where there are no postal codes: a house number and street, a mile marker on a highway, or a lot in a neighbourhood, followed by the town.

HOW IT IS FOUND

COLUMN NAME BZ_L1_ADDRESS – Path

80% address[a-z0-9_]* (except when preceded by mac , ip , e_?mail , web , url ; except when followed by list E4)
addr(ess)?_?(line|1|2)?[a-z0-9_]* (except when preceded by mac , ip , e_?mail , web , url) street(_?
(address|name))? residential_?address home_?address mailing_?address postal_?address
physical_?address residence place_?of_?residence domicile direccion[a-z_]* (except when
followed by ip , mac , correo , electronica) domicilio[a-z_]*

DATA TYPE BZ_L1_ADDRESS – Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT BZ_L1_ADDRESS – Regex

PATTERN	STRENGTH	NOTES
(?i)#[s\d+[A-Z]?[s+.*\b(street st\. avenue ave\. road rd\. drive dr\. lane boulevard blvd\. highway hwy)\b.*	80%	
(?i).*\bmile\s+\d+.*\b(highway road hwy)\b.*	90%	
(?i).*\b[lot\s*(no\. #\s*)?\d+\s*,.+	60%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

It is replaced by one of 3,000 fictitious Belizean addresses — streets of Belize City and the towns, mile markers on the Philip Goldson, George Price, Hummingbird and Southern highways, lots in real neighbourhoods.

BZ_ADDRESS **SECURE LOOKUP**

Replaces the value with one of the 3,000 values in `bz-addresses.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
#24 Cleghorn Street, Belize City	→ Mile 60 Philip Goldson Highway, Corozal Town

7.14 Address detail

BZ_L1_ADDRESS_DETAIL

ESSENTIAL **COLUMN NAME** **CHARACTER MAPPING**

WHAT IT IS

House, apartment, unit, floor or lot numbers in columns of their own.

HOW IT IS FOUND

COLUMN NAME BZ_L1_ADDRESS_DETAIL – Path

70% house_?(no|num|number) apt_?(no|number)? apartment_?(no|number)? unit_?
 (no|num|number) flat_?(no|number) lot_?(no|num|number) floor_?(no|number)? suite_?(no)?
 building_?(no|number) num_casa n(o|um|ro)_casa apto

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
Apt. 4B	→ Adv. 9W

7.15 Bank account

BZ_L1_BANK_ACCOUNT

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Savings, chequing and share account numbers of banks and credit unions.

HOW IT IS FOUND

COLUMN NAME

BZ_L1_BANK_ACCOUNT - Path

85%

account_?(no|num|number|nbr) acct_?(no|num|number|nbr)? acc_?(no|num|number) bank_?
(account|acct)(_?(no|num|number))? savings_(account|acct)(_?(no|number))? checking_?
(account|acct)(_?(no|number))? chequing_(account|acct)(_?(no|number))? share_account(_?
no)? iban cuenta_?(bancaria|ahorros?|corriente) n(o|um|ro)_?(de_?)?cuenta

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
010-123456-7	→	099-011707-8

7.16 Payment card

BZ_L1_PAYMENT_CARD

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Credit, debit and prepaid card numbers.

HOW IT IS FOUND

COLUMN NAME

BZ_L1_PAYMENT_CARD - Path

85%

card_?(no|num|number) credit_card(_?(no|num|number))? debit_card(_?(no|num|number))?
cc_?(no|num|number) pan card_pan masked_pan tarjeta(_?(credito|debito))?
n(o|um|ro)_?tarjeta

VALUE FORMAT

BZ_L1_PAYMENT_CARD - Regex

PATTERN	STRENGTH	NOTES
\d{13,19}	90%	LUHN check digit; after removing [\s-]

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another card number that still passes the Luhn check. Values not shaped like a card pass unchanged instead of failing the row.

BZ_CARD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

BZ_CARD_LUHN

PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

EXAMPLES

VALUE		MASKED
4916 3131 2345 6780	→	1374 9602 1069 5000

7.17 IP address

BZ_L1_IP_ADDRESS

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

IPv4 and IPv6 addresses of users and devices.

HOW IT IS FOUND

COLUMN NAME BZ_L1_IP_ADDRESS - Path

85% ip ip?(address|addr|origin|source|destination|client|user|remote|public|private|login)
ipv[46] remote?addr(ess)? client?ip host?ip source?ip direccion?ip

VALUE FORMAT BZ_L1_IP_ADDRESS - Regex

PATTERN	STRENGTH	NOTES
((25[0-5] 2[0-4]\d 1?\d?\d)\.){3}(25[0-5] 2[0-4]\d 1?\d?\d)	100%	
[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7}	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet is mapped to a number from 1 to 254; an IPv6 address is mapped as hexadecimal.

BZ_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: BZ_CM_HEX .

BZ_OCTET NUMERIC MAPPING

Maps the number to another between 1 and 254.

BZ_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
200.32.211.10	→ 146.25.143.16

7.18 Device identifier

BZ_L1_DEVICE_ID

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

IMEI, MAC address, advertising and session identifiers, handset serial numbers.

HOW IT IS FOUND

COLUMN NAME BZ_L1_DEVICE_ID - Path

80% imei imsi iccid mac mac?address device?(id|uuid|serial) advertising?id idfa
gaid cookie(?id)? session?id serial?(no|number)?(device|phone|handset) handset?
serial

VALUE FORMAT BZ_L1_DEVICE_ID - Regex

PATTERN	STRENGTH	NOTES
([0-9A-Fa-f]{2}[:\-\-]){5}[0-9A-Fa-f]{2}	100%	
\d{15}	80%	LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Hex stays hex and digits stay digits, so the value keeps its format.

BZ_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
3c:22:fb:9a:10:e4	→ 5e:83:bb:3c:31:f9

7.19 Licence plate

BZ_L1_LICENCE_PLATE

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Plates with a district or town code — BZ , CY , CZL , OW , SC , TOL , BMP , SP — a category letter for motorcycles, taxis and other public service vehicles, and a serial number: CY C-12345 , BZ 12345 .

HOW IT IS FOUND

COLUMN NAME BZ_L1_LICENCE_PLATE - Path

85% `licen[cs]e_?plates?(_(no|num|number))?` `plates?(_(no|num|number))?` `vehicle_?`
`(reg|registration|plate|licen[cs]e)_(no|num|number)?` `registration_?plate` `number_?plate`
`tag_(no|number)` `placas?` `matricula`

VALUE FORMAT BZ_L1_LICENCE_PLATE - Regex

PATTERN	STRENGTH	NOTES
<code>(BMP CZL TOL BZ BC CY OW SC SP SI SE PG DG) [\s\-\]? ([A-Z] [\s\-\]?)? \d{3,5}</code>	80%	
<code>[A-Z] [\s\-\] \d{4,5}</code>	40%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The code and the category letter stay, so a Cayo taxi is still a Cayo taxi; the serial digits are masked.

BZ_PLATE REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
CY C-12345	→ CY C-31564
BZ 12345	→ BZ 31564

7.20 Vehicle identification number

BZ_L1_VIN

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

The VIN, and engine and chassis numbers.

HOW IT IS FOUND

COLUMN NAME BZ_L1_VIN – Path

80% vin vin_?(no|number) vehicle_?identification_?(no|number) chassis(_?(no|number))?
engine_?(no|number|serial) motor_?(no|number) serial_?(no|number)?vehicle n(o|um|ro)?
(de_?)?(serie|chasis|motor)

VALUE FORMAT BZ_L1_VIN – Regex

PATTERN	STRENGTH	NOTES
[A-HJ-NPR-Z0-9]{17}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
1HGCM82633A004352	→ 1JTRL73362E132318

7.21 Land parcel

BZ_L1_LAND_PARCEL

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

Registered land is identified by registration section, block and parcel (Caribbean Shores, Block 16, Parcel 1234); national land by lease, Minister's Fiat grant or title numbers. The Land Registry leads from a parcel to its proprietor.

HOW IT IS FOUND

COLUMN NAME BZ_L1_LAND_PARCEL – Path

85% parcel(_?(no|num|number|id))? block_?(and_)?parcel land_
(title|parcel|registry|register|certificate|lease)(_?(no|num|number))? title_?(deed_)?
(no|number) land_?certificate lease_?(no|number) minister_?s_?fiat(_?no)? fiat_?grant(_?
no)? deed_?(no|number) cadastr[a-z]* finca folio_?real

VALUE FORMAT BZ_L1_LAND_PARCEL – Regex

PATTERN	STRENGTH	NOTES
(?i).*block\s*(no\.\?s*)?\d+.*parcel\s*(no\.\?s*)?\d+.*		90%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The block and parcel numbers are masked digit by digit; the words and the registration section stay. Other formats are masked character by character.

BZ_PARCEL **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

Caribbean Shores, Block 16, Parcel 1234

→

Caribbean Shores, Block 62, Parcel 9707

7.22 Contract or customer number

BZ_L1_CONTRACT_NUMBER

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Contract, policy, loan, mortgage, membership, customer, employee, student or claim numbers, and electricity and water account numbers.

HOW IT IS FOUND

COLUMN NAME

BZ_L1_CONTRACT_NUMBER – Path

70%

```
contract_?(no|num|number)  policy_?(no|num|number)  loan_?(no|num|number|id)  mortgage_?
(no|number)  member(ship)?_?(no|num|number|id)  customer_?(no|num|number|id)  client_?
(no|num|number|id)  cust_?(no|num|id)  employee_?(no|num|number|id)  emp_?(no|num|id)
staff_?(no|num|number|id)  payroll_?(no|number)  claim_?(no|num|number)  meter_?(no|number)
bel_?account(_?no)?  bws_?account(_?no)?  student_?(no|num|number|id)  n(o|um|ro)?(de_)?
(contrato|poliza|cliente|empleado)
```

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

POL-123456

→

MIF-194239

7.23 User name or social media

BZ_L1_USERNAME

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

User names, aliases and social media handles.

HOW IT IS FOUND

COLUMN NAME

BZ_L1_USERNAME – Path

70%

```
user_?name  username  login(_?(name|id))?  user_?id_?login  nick_?name  nickname  alias
screen_?name  handle  facebook  instagram  twitter  tiktok  linkedin  social_?media(_?
(handle|account|profile))?  telegram  usuario
```

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

@kenrick_g

→

@ricposl_j

7.24 Credential

BZ_L1_CREDENTIAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Passwords, PINs, password hashes, security answers, tokens and API keys.

HOW IT IS FOUND

COLUMN NAME

BZ_L1_CREDENTIAL - Path

90%

password passwd pwd pass_?word pass pin(_?(code|no|number))? passcode hash_?
password password_?hash secret secret_?(answer|question) security_?(answer|question)
access_?token refresh_?token api_?key otp contrasen[aa] contraseña clave *(except when
followed by `producto`, `prod`, `articulo`, `postal`)*

HOW IT IS MASKED

Every character becomes `x`. A credential has no reason to look real in a test environment.

BZ_REDACT

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

Secret#2024

→

XXXXXXXXXX

7.25 Geolocation

BZ_L1_GEOLOCATION

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude, together or in separate columns. Belize lies between 15.8° and 18.5° north and 87.4° and 89.3° west.

HOW IT IS FOUND

COLUMN NAME

BZ_L1_GEOLOCATION - Path

85%

lat latitude lon lng longitude coordinates? coord_?[xy] geo_
(lat|lon|lng|loc|location|position) geolocation gps(_?(location|position|coordinates))?
latitud coordenadas?

50%

long longitud

VALUE FORMAT BZ_L1_GEOLOCATION – Regex

PATTERN	STRENGTH	NOTES
1[5–8]\.\d{3,}\s*,\s*-8[7–9]\.\d{3,}		90%
1[5–8]\.\d{3,}		50%
-8[7–9]\.\d{3,}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the rest is masked: the place is generalized, not moved.

BZ_COORDINATE **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
17.251234,-88.759876	→ 17.257210,-88.778965

7.26 Free text

BZ_L1_FREE_TEXT

COLUMN NAME **DATA TYPE** **VALUE FORMAT** **FREE TEXT REDACTION**

WHAT IT IS

Remarks, comments, complaints, case notes and statements where personal data is written without structure.

HOW IT IS FOUND

COLUMN NAME BZ_L1_FREE_TEXT – Path

60% remarks? comments? notes? observations? narrative free_?text memo messages? *(except when followed by list E5)* complaint(_?(text|details|description))? description_?(of_)?
(case|complaint|incident|request|issue|problem|events) incident_
(details|description|narrative) case_?(notes?|summary|details) statement details
summary observaciones? comentarios? notas?

DATA TYPE BZ_L1_FREE_TEXT – Type

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT BZ_L1_FREE_TEXT – Regex

PATTERN	STRENGTH	NOTES
\d{3}-?\d{3}-?\d{3}	60%	anywhere in the value
[\w.+\\-]+@[\\w\\-]+\\. [A-Za-z]{2,}	70%	anywhere in the value
(\\+?501\\s)? [2–8]\\d{2}-\\d{4}	60%	anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

Free Text Redaction: social security numbers, e-mails, phone numbers, card numbers, plates and IPs become [DATA] , and the given names and surnames of the lists become [NAME] .

BZ_FREE_TEXT FREE TEXT REDACTION

Replaces the text matching 8 patterns with [DATA] , and the 858 terms of bz-text-names.txt with [NAME] .

EXAMPLES

VALUE

Customer Gillett, SSN 000123456, email
k.gillett@gmail.com, tel 622-4567.

MASKED

→

Customer [NAME], SSN [DATA], email [DATA],
tel [DATA].

Quasi-identifiers

Data that identifies no one on its own, but does in combination. Belize had 397,483 people in the 2022 census, spread over some two hundred villages and communities; 208 of the 221 places counted had fewer than 5,000 inhabitants, many fewer than 500. A birth date, a sex and one of those villages point at a handful of people. These attributes are generalized or shifted rather than replaced, and the data keeps its analytical value.

8.1 Birth date

BZ_L2_BIRTH_DATE

ESSENTIAL COLUMN NAME DATA TYPE DATE SHIFT

WHAT IT IS

The birth date, in date, timestamp or text columns.

HOW IT IS FOUND

COLUMN NAME BZ_L2_BIRTH_DATE – Path

90% dob d_o_b date_of_birth birth_date birthdate birthday born?(on|date) bdate
fecha?(de?)?nac(imiento)? fec?nac(imiento)? f?nac(imiento)? nacimiento

DATA TYPE BZ_L2_BIRTH_DATE – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 60 days back or forward: it breaks the link to the person and keeps ages and cohorts almost intact.

BZ_BIRTH_DATE DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	1985-08-05T00:00

8.2 Birth year

BZ_L2_BIRTH_YEAR

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The birth year alone.

HOW IT IS FOUND

COLUMN NAME BZ_L2_BIRTH_YEAR – Path

90% birth_year year_of_birth yob yr_of_birth an(i)o?(de?)?nac(imiento)? año?
(de?)?nac(imiento)?

DATA TYPE BZ_L2_BIRTH_YEAR – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit is mapped: 1985 becomes another year of the eighties.

BZ_YEAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	1980

8.3

Age

BZ_L2_AGE

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Ages in years, whole or with decimals.

HOW IT IS FOUND

COLUMN NAME

BZ_L2_AGE – Path

85%

age(_?(years|yrs|in_?years|at_?

(admission|death|entry|diagnosis|registration)|group|range|band|bracket|last_?birthday))?

years_?old edad(_?(actual|anos|años))?

DATA TYPE

BZ_L2_AGE – Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The tens digit stays and the units digit is mapped (37 becomes 3x). From 100 on, 90: extreme ages identify on their own.

BZ_AGE REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	35
104	→	90

8.4

Life event dates

BZ_L2_EVENT_DATE

COLUMN NAME

DATA TYPE

DATE SHIFT

WHAT IT IS

Dates of death, marriage, divorce, hiring and leaving a job, retirement, admission and discharge, diagnosis, arrest, conviction, naturalization and other personal events.

HOW IT IS FOUND

COLUMN NAME BZ_L2_EVENT_DATE - Path

80% `date_?of_?`
(death|marriage|divorce|hire|hiring|employment|engagement|termination|dismissal|resignation|retirement|admission|discharge|diagnosis|visit|consultation|delivery|arrest|conviction|sentence|sentencing|naturali[sz]ation|injury|surgery)
(death|marriage|divorce|hire|hiring|employment|employment_?start|start_?of_?employment|termination|separation|resignation|retirement|admission|discharge|diagnosis|visit|delivery|arrest|conviction|sentencing|naturali[sz]ation|pension_?start|injury|vaccination|surgery|immigration)_?date dod fecha_?(de_?)?
(defuncion|fallecimiento|matrimonio|divorcio|ingreso|egreso|contratacion|jubilacion|diagnostico)

DATA TYPE BZ_L2_EVENT_DATE - Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 30 days: less than the birth date, since they are often combined with it.

BZ_EVENT_DATE **DATE SHIFT**

Moves the date by -30 to 30 days.

EXAMPLES

VALUE	MASKED
2021-03-15	→ 2021-03-05T00:00

8.5

Sex

BZ_L2_SEX

COLUMN NAME **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

Registered sex in any notation: F / M , Female / Male , Woman / Man , and in Spanish.

HOW IT IS FOUND

COLUMN NAME BZ_L2_SEX - Path

85% `sex(_?(code|at_?birth|registered))?` `gender(_?code)?` (except when followed by *identity* , *expression*)
`sexo` `genero` (except when followed by *identidad*)

KNOWN VALUES BZ_L2_SEX - List

LIST	VALUES	STRENGTH	FIRST VALUES
bz-detect-sex.txt	12	50%	f, m, h, female, male, woman

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary: F / M stays F / M .

BZ_SEX **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_SEX_FEMALE_MALE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-sex-female-male.txt` , chosen by a keyed hash.

BZ_SEX_WOMAN_MAN **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-sex-woman-man.txt` , chosen by a keyed hash.

BZ_SEX_SPANISH **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-sex-spanish.txt` , chosen by a keyed hash.

BZ_SEX_MUJER_HOMBRE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-sex-mujer-hombre.txt` , chosen by a keyed hash.

BZ_SEX_F_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-sex-f-m.txt` , chosen by a keyed hash.

BZ_SEX_H_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-sex-h-m.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F	→	M
Male	→	Female

8.6 Town or village

BZ_L2_TOWN_VILLAGE

COLUMN NAME**KNOWN VALUES****DATA CLEANSING****WHAT IT IS**

The city, town, village or community where a person lives or was born. The 2022 census counted Belize City, Belmopan, seven towns and some two hundred villages and communities; 208 of the 221 places had fewer than 5,000 inhabitants.

HOW IT IS FOUND**COLUMN NAME**

BZ_L2_TOWN_VILLAGE - Path

85%

town village town_(or_)?village city_(town_)?village ctv community *(except when followed by service , group , organi[sz]ation , work)* locality settlement home_?town hometown place_?of_?birth birth_?place birthplace place_?of_?residence_(town|village) residence_(town|village|community) town_?of_?residence village_?of_?residence aldea comunidad localidad lugar_(de_)?nacimiento

50%

city ciudad municipality pueblo

KNOWN VALUES

BZ_L2_TOWN_VILLAGE - List

LIST**VALUES****STRENGTH****FIRST VALUES**

bz-detect-towns-
villages.txt

241

80%

Corozal Town, Altamira, Buena Vista, Calcutta, Caledonia,
Carolina

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A place under 5,000 inhabitants becomes the nearest place of its district with at least 5,000; larger ones stay. See *Where people live*.

BZ_TOWN_VILLAGE **DATA CLEANSING**

Replaces each value found in `bz-town-village-generalized.txt` (489 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE

MASKED

Crooked Tree	→	Ladyville
Hopkins	→	Dangriga
Belmopan	→	Belmopan

8.7 Neighbourhood

BZ_L2_NEIGHBOURHOOD

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

Neighbourhoods, subdivisions, housing schemes and land registration sections within a town: Lake Independence, Port Loyola, Salvapan.

HOW IT IS FOUND

COLUMN NAME

BZ_L2_NEIGHBOURHOOD - Path

85%

neighbou?rhood subdivision barrio colonia residential_?area area_?of_?residence
housing_?(area|scheme|estate) registration_?section reg_?section urbanizacion sector_?
residencial

HOW IT IS MASKED

Replaced by one of 30 neighbourhoods of Belize City and the towns.

BZ_NEIGHBOURHOOD SECURE LOOKUP

Replaces the value with one of the 30 values in `bz-neighbourhoods.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Yarborough	→	DFC Area
------------	---	----------

8.8 Nationality

BZ_L2_NATIONALITY

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Nationality, citizenship or country of birth. In a Belizean database, an uncommon nationality identifies.

HOW IT IS FOUND

COLUMN NAME

BZ_L2_NATIONALITY - Path

80%

nationality citizenship country_?of_?(birth|origin|citizenship|nationality) birth_?
country nacionalidad pais_?(de_?)?(nacimiento|origen) ciudadania

KNOWN VALUES

BZ_L2_NATIONALITY - List

LIST

VALUES STRENGTH FIRST VALUES

<code>bz-detect-nationalities.txt</code>	52	70%	Belizean, Guatemalan, Salvadoran, Honduran, Mexican, American
--	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by one of the 16 most common nationalities in Belize — Belizean, and then those of the largest foreign-born groups in the 2022 census: Guatemalan, Salvadoran, Honduran, American and Mexican.

BZ_NATIONALITY **SECURE LOOKUP**

Replaces the value with one of the 16 values in `bz-nationalities.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Guatemalan

→

Belizean

8.9

Marital status

BZ_L2_MARITAL_STATUS

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Marital and union status, in the 2022 census categories: never married, married, common-law union, visiting partner, divorced, widowed, legally separated.

HOW IT IS FOUND

COLUMN NAME

BZ_L2_MARITAL_STATUS – Path

85%

`marital_?status`

`civil_?status`

`union_?status`

`marriage_?status`

`relationship_?status`

`estado_?civil`

`edo_?civil`

KNOWN VALUES

BZ_L2_MARITAL_STATUS – List

LIST

VALUES

STRENGTH

FIRST VALUES

`bz-detect-marital-`
`status.txt`

25

70%

Never married, Married, Common-law union, Visiting partner,
Divorced, Widowed

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another of the seven categories.

BZ_MARITAL_STATUS **SECURE LOOKUP**

Replaces the value with one of the 7 values in `bz-marital-status.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Common-law union

→

Married

8.10

Occupation

BZ_L2_OCCUPATION

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

Occupation, profession or job title. A rare title (`Regional Operations Manager, Toledo`) is unique in the database.

HOW IT IS FOUND

COLUMN NAME BZ_L2_OCCUPATION – Path

80%	occupation	profession	job_?title	designation	job_?description_?title	post_?title
	position_?title	ocupaci[oó]n	profesi[oó]n	puesto		
50%	job	position	post	trade	(except when followed by <i>name</i> , <i>mark</i> , <i>licen[cs]e</i>)	
	cargo	(except when followed by <i>fijo</i> , <i>monto</i> , <i>valor</i>)				

HOW IT IS MASKED

Replaced by one of 40 common occupations.

BZ_OCCUPATION **SECURE LOOKUP**

Replaces the value with one of the 40 values in `bz-occupations.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Regional Operations Manager, Toledo	→	Graphic designer

8.11 Employer

BZ_L2_EMPLOYER

COLUMN NAME **SECURE LOOKUP**

WHAT IT IS

The name of the employer or workplace. In a small economy, an employer and a job title together often point at one person.

HOW IT IS FOUND

COLUMN NAME BZ_L2_EMPLOYER – Path

80%	employer(_?name)?	name_?of_?employer	employer_?business_?name	company_?of_?employment
	workplace	work_?place	place_?of_?(work employment)	employed_?(at by with)
	current_?employer	patrono	empleador	lugar_?(de_?)?trabajo

HOW IT IS MASKED

Replaced by one of 25 fictitious employers.

BZ_EMPLOYER **SECURE LOOKUP**

Replaces the value with one of the 25 values in `bz-employers.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Belize Electricity Limited	→	Southern Distributors Ltd.

8.12 Education

BZ_L2_EDUCATION

COLUMN NAME **KNOWN VALUES** **SECURE LOOKUP**

WHAT IT IS

The highest level of education, in the terms of the Belizean system: primary to Standard 6, secondary to Form 4, sixth form or junior college, vocational, associate, bachelor's, master's, doctorate.

HOW IT IS FOUND

COLUMN NAME BZ_L2_EDUCATION – Path

80% education(_?(level|attainment|status|completed))? educational_?(level|attainment)
highest_?(level_?(of_?))? (education|qualification|grade) level_?of_?education
qualification schooling grade_?completed escolaridad nivel_?(educativo|de_?estudios)

KNOWN VALUES BZ_L2_EDUCATION – List

LIST	VALUES	STRENGTH	FIRST VALUES
bz-detect-education.txt	29	60%	None, Preschool, Primary incomplete, Primary (Standard 6), Secondary incomplete, Secondary (Form 4)

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another of the 12 levels.

BZ_EDUCATION **SECURE LOOKUP**

Replaces the value with one of the 12 values in bz-education.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Sixth form / junior college	→ Secondary (Form 4)

8.13 School

BZ_L2_SCH00L

COLUMN NAME **SECURE LOOKUP**

WHAT IT IS

The name of the primary or high school, sixth form, junior college or university.

HOW IT IS FOUND

COLUMN NAME BZ_L2_SCH00L – Path

75% school(_?name)? name_?of_?school high_?school primary_?school secondary_?school
sixth_?form junior_?college college(_?name)? university(_?name)? institution_?attended
alma_?mater escuela colegio universidad

HOW IT IS MASKED

Replaced by one of 15 fictitious schools.

BZ_SCH00L **SECURE LOOKUP**

Replaces the value with one of the 15 values in bz-schools.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
St. John's College	→ Maya Mountain Junior College

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Number of children, dependants or household members.

HOW IT IS FOUND

COLUMN NAME

BZ_L2_DEPENDANTS – Path

80%

dependants?

dependents?

no_of_(children|dependants|dependents|kids)

num(ber)?_(of_)??

(children|dependants|dependents|kids)

children

household_(size|members)

persons_in_?

household

hijos

n(o|um|ro)_hijos

dependientes

DATA TYPE

BZ_L2_DEPENDANTS – Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Capped at 5: large households are rare, and a rare count identifies.

BZ_CAPPED_COUNT

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	5

Sensitive personal data

The categories of section 2 that are not health, financial or criminal data — which have groups of their own: racial or ethnic origin, political opinions, religious and similar beliefs, membership of a political body, trade union membership, genetic and biometric data, sexual orientation and sexual life — and, beyond the list, the language a person speaks and gender identity. Categorical columns keep their shape: a yes/no flag stays a flag, a numeric code gets other digits and any other value is replaced by one from its category's list. Where the values share no vocabulary, they are suppressed to `Not stated`.

9.1 Ethnic origin

BZ_L3_ETHNICITY

COLUMN NAME	KNOWN VALUES	REGEX DECOMPOSE
-------------	--------------	-----------------

WHAT IT IS

Ethnic group in the terms of the 2022 census — Mestizo/Hispanic/Latino (51.7%), Creole (25.2%), Maya (Q'eqchi', Mopan, Yucatec; 9.8%), Garifuna (4.0%), East Indian, Mennonite, Chinese and others —, often as a yes/no flag for indigenous status.

HOW IT IS FOUND

COLUMN NAME	BZ_L3_ETHNICITY - Path		
90%	<code>ethnic(ity _?group _?origin _?background _?identity)?</code>	<code>race</code>	<code>racial_?</code>
	<code>(origin group background)</code>	<code>indigenous(_?(status group people peoples))?</code>	<code>is_?indigenous</code>
	<code>maya_?(group people)</code>	<code>etnia</code>	<code>grupo_?etnico</code> <code>origen_?etnico</code> <code>raza</code>

KNOWN VALUES	BZ_L3_ETHNICITY - List		
LIST	VALUES	STRENGTH	FIRST VALUES
<code>bz-detect-ethnic-groups.txt</code>	43	90%	Mestizo/Hispanic/Latino, Creole, Maya Ketchi, Maya Mopan, Maya Yucatec, Garifuna
<code>bz-detect-flag.txt</code>	9	30%	y, n, yes, no, s, sí

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag in its vocabulary, a code gets other digits and any other value is replaced by one from the census list.

BZ_ETHNICITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_ETHNICITY_LIST

BZ_FLAG	REGEX DECOMPOSE
Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.	
<code>BZ_FLAG_YES_NO</code>	<code>SECURE LOOKUP</code>
Replaces the value with one of the 2 values in <code>bz-flag-yes-no.txt</code> , chosen by a keyed hash.	
<code>BZ_FLAG_SI_NO</code>	<code>SECURE LOOKUP</code>
Replaces the value with one of the 2 values in <code>bz-flag-si-no.txt</code> , chosen by a keyed hash.	
<code>BZ_FLAG_TRUE_FALSE</code>	<code>SECURE LOOKUP</code>
Replaces the value with one of the 2 values in <code>bz-flag-true-false.txt</code> , chosen by a keyed hash.	
<code>BZ_FLAG_Y_N</code>	<code>SECURE LOOKUP</code>
Replaces the value with one of the 2 values in <code>bz-flag-y-n.txt</code> , chosen by a keyed hash.	
<code>BZ_FLAG_S_N</code>	<code>SECURE LOOKUP</code>

Replaces the value with one of the 2 values in `bz-flag-s-n.txt` , chosen by a keyed hash.

BZ_FLAG_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-0-1.txt` , chosen by a keyed hash.

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

BZ_ETHNICITY_LIST **SECURE LOOKUP**

Replaces the value with one of the 14 values in `bz-ethnic-groups.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Garinagu	→	Not stated
Y	→	N

9.2 Language

BZ_L3_LANGUAGE

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The language a person speaks or grew up with: English, Spanish, Kriol, Maya Q'eqchi', Mopan or Yucatec, Garifuna, German (Plautdietsch) and others. Not in the section 2 list, but it reveals ethnic origin as directly as the ethnic group column.

HOW IT IS FOUND

COLUMN NAME BZ_L3_LANGUAGE - Path

90% `mother_?tongue` `first_?language` `native_?language` `home_?language` `language_?(spoken|at_?home|spoken_?at_?home|first|native|mother)` `languages_?spoken` `primary_?language` `lengua(_?materna)?` `idioma_?(materno|nativo)`

55% `language` `idioma`

KNOWN VALUES BZ_L3_LANGUAGE - List

LIST	VALUES	STRENGTH	FIRST VALUES
<code>bz-detect-languages.txt</code>	31	80%	English, Spanish, Kriol, Maya Q'eqchi', Maya Mopan, Maya Yucatec

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Like ethnic origin: flags and codes keep their shape, names are replaced by another language of the census list.

BZ_LANGUAGE **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_LANGUAGE_LIST` .

BZ_FLAG **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt` , chosen by a keyed hash.

BZ_FLAG_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-si-no.txt` , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-true-false.txt` , chosen by a keyed hash.

BZ_FLAG_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-y-n.txt` , chosen by a keyed hash.

BZ_FLAG_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-s-n.txt` , chosen by a keyed hash.

BZ_FLAG_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-0-1.txt` , chosen by a keyed hash.

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

BZ_LANGUAGE_LIST **SECURE LOOKUP**

Replaces the value with one of the 11 values in `bz-languages.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Garifuna	→ Other

9.3 Religion

BZ_L3_RELIGION

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Religion or denomination: Roman Catholic, Pentecostal, Seventh-day Adventist, Anglican, Mennonite, Baptist, Methodist, Nazarene, Jehovah's Witness, Hindu, Muslim, Bahá'í, Rastafarian, none.

HOW IT IS FOUND

COLUMN NAME

BZ_L3_RELIGION - Path

95%

`religion[a-z]*` `religious_?(affiliation|denomination|belief|beliefs|preference|group)`

`denomination` `faith` `church(_?(name|affiliation|member|membership|attended))?` `creed`

`congregation` `religi[oó]n` `credo` `iglesia`

KNOWN VALUES

BZ_L3_RELIGION - List

LIST

VALUES

STRENGTH

FIRST VALUES

`bz-detect-religions.txt`

50

90%

Roman Catholic, Pentecostal, Seventh-day Adventist, Anglican, Mennonite, Baptist

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

BZ_RELIGION **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: **BZ_RELIGION_LIST** .

BZ_FLAG **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt` , chosen by a keyed hash.

BZ_FLAG_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-si-no.txt` , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-true-false.txt` , chosen by a keyed hash.

BZ_FLAG_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-y-n.txt` , chosen by a keyed hash.

BZ_FLAG_S_N **SECURE LOOKUP**

	Replaces the value with one of the 2 values in <code>bz-flag-s-n.txt</code> , chosen by a keyed hash.
BZ_FLAG_0_1	SECURE LOOKUP
	Replaces the value with one of the 2 values in <code>bz-flag-0-1.txt</code> , chosen by a keyed hash.
BZ_CM_ALNUM	CHARACTER MAPPING
	Maps each character to another of its group (7 groups), keeping length and format.
BZ_RELIGION_LIST	SECURE LOOKUP
	Replaces the value with one of the 19 values in <code>bz-religions.txt</code> , chosen by a keyed hash.
EXAMPLES	
VALUE	MASKED
Salvation Army	→ Church of God

9.4

Beliefs of a similar nature

BZ_L3_BELIEF

COLUMN NAME	REGEX DECOMPOSE
WHAT IT IS	
Philosophical or moral convictions, conscientious objection and other beliefs of a similar nature to religious ones.	
HOW IT IS FOUND	
COLUMN NAME	BZ_L3_BELIEF - Path
90%	beliefs? philosophical_?(beliefs? convictions?) conscientious_?objection conscientious_?objector moral_?(beliefs? convictions?) personal_?convictions? worldview creencias?_(filosoficas? morales? personales) convicci[oó]n(es)? objecion_?(de_)?conciencia
HOW IT IS MASKED	
Suppressed to Not stated .	
BZ_SUPPRESSED_CATEGORY	REGEX DECOMPOSE
Tries 2 patterns in order and gives each part of the value its own action; when none matches: BZ_SUPPRESS .	
BZ_FLAG	REGEX DECOMPOSE
Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.	
BZ_FLAG_YES_NO	SECURE LOOKUP
Replaces the value with one of the 2 values in <code>bz-flag-yes-no.txt</code> , chosen by a keyed hash.	
BZ_FLAG_SI_NO	SECURE LOOKUP
Replaces the value with one of the 2 values in <code>bz-flag-si-no.txt</code> , chosen by a keyed hash.	
BZ_FLAG_TRUE_FALSE	SECURE LOOKUP
Replaces the value with one of the 2 values in <code>bz-flag-true-false.txt</code> , chosen by a keyed hash.	
BZ_FLAG_Y_N	SECURE LOOKUP
Replaces the value with one of the 2 values in <code>bz-flag-y-n.txt</code> , chosen by a keyed hash.	
BZ_FLAG_S_N	SECURE LOOKUP
Replaces the value with one of the 2 values in <code>bz-flag-s-n.txt</code> , chosen by a keyed hash.	
BZ_FLAG_0_1	SECURE LOOKUP
Replaces the value with one of the 2 values in <code>bz-flag-0-1.txt</code> , chosen by a keyed hash.	
BZ_CM_ALNUM	CHARACTER MAPPING
Maps each character to another of its group (7 groups), keeping length and format.	
BZ_SUPPRESS	SECURE LOOKUP
Replaces the value with one of the 1 values in <code>bz-not-stated.txt</code> , chosen by a keyed hash.	

EXAMPLES

VALUE

MASKED

Refuses blood transfusions

→ Not stated

9.5 Political opinion

BZ_L3_POLITICAL_OPINION

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Ideology, voting intention, party preference in surveys.

HOW IT IS FOUND

COLUMN NAME

BZ_L3_POLITICAL_OPINION - Path

90%

political_?(opinion|opinions|view|views|orientation|leaning|leanings|preference|ideology)
ideology voting_?intention vote_?intention intended_?vote party_?preference
preferred_?party swing_?voter opini[oó]n_?pol[ií]tica ideolog[ií]a intencion_?(de_?)?
voto

KNOWN VALUES

BZ_L3_POLITICAL_OPINION - List

LIST

VALUES STRENGTH FIRST VALUES

bz-detect-political-opinions.txt	19	70%	Left, Centre-left, Centre, Centre-right, Right, No preference
----------------------------------	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another position on a generic scale.

BZ_POLITICAL_OPINION

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_POLITICAL_OPINION_LIST .

BZ_FLAG REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-yes-no.txt , chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-si-no.txt , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-true-false.txt , chosen by a keyed hash.

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-y-n.txt , chosen by a keyed hash.

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-s-n.txt , chosen by a keyed hash.

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-0-1.txt , chosen by a keyed hash.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_POLITICAL_OPINION_LIST SECURE LOOKUP

Replaces the value with one of the 7 values in bz-political-opinions.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Centre-right

→ Right

9.6 Membership of a political body

BZ_L3_POLITICAL_MEMBERSHIP

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The party or political body a person belongs to or supports — a category section 2 names on its own, apart from political opinions.

HOW IT IS FOUND

COLUMN NAME

BZ_L3_POLITICAL_MEMBERSHIP – Path

95% political_?(party|body|membership|affiliation|group) party_?
(membership|member|affiliation|card|branch|division|supporter) member_of_?
(party|political_?(party|body)) partido(_?pol[í]tico)? afiliaci[oó]n_?pol[í]tica
militancia militante

50% party (except when followed by list E6)

KNOWN VALUES

BZ_L3_POLITICAL_MEMBERSHIP – List

LIST

VALUES

STRENGTH

FIRST VALUES

bz-detect-political-parties.txt	22	80%	People's United Party, United Democratic Party, Belize Progressive Party, Belize Justice Movement, People's Democratic Movement, People's National Party
---------------------------------	----	-----	--

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by one of the parties of the 2025 general election — People's United Party, United Democratic Party, Belize Progressive Party, Belize Justice Movement, People's Democratic Movement, People's National Party — or by independent or no party.

BZ_POLITICAL_PARTY

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_POLITICAL_PARTY_LIST .

BZ_FLAG

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-yes-no.txt , chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-si-no.txt , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-true-false.txt , chosen by a keyed hash.

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-y-n.txt , chosen by a keyed hash.

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-s-n.txt , chosen by a keyed hash.

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-0-1.txt , chosen by a keyed hash.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_POLITICAL_PARTY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-political-parties.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

United Democratic Party

→

United Democratic Party

9.7

Trade union membership

BZ_L3_TRADE_UNION

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Membership of a trade union or staff association, union dues, bargaining unit: BNTU, PSU, Christian Workers' Union and the other affiliates of the NTUCB.

HOW IT IS FOUND

COLUMN NAME

BZ_L3_TRADE_UNION - Path

95%

```
trade_?union(?:?(member|membership|name|dues))? union_?
(member|membership|affiliation|name|dues|fees|code|branch|local|representative)
unioni[sz]ed labou?r_?union bargaining_?unit collective?(agreement|bargaining) staff_?
association sindicato[a-z]* sindical(izado)? afiliaci[oó]n?sindical cuota?sindical
```

KNOWN VALUES

BZ_L3_TRADE_UNION - List

LIST

VALUES

STRENGTH

FIRST VALUES

bz-detect-trade-unions.txt

23

60%

BNTU, PSU, NTUCB, CWU, BWU, BEWU

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Not stated`.

BZ_SUPPRESSED_CATEGORY

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SUPPRESS`.

BZ_FLAG

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `keep`.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

BZ_CM_ALNUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_SUPPRESS **SECURE LOOKUP**

Replaces the value with one of the 1 values in `bz-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

BNTU

→

Not stated

9.8

Genetic data

BZ_L3_GENETIC

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Genetic profiles, sequences, mutations, karyotypes, paternity tests — in the Act's words, data on inherited or acquired genetic characteristics resulting from the analysis of a biological sample.

HOW IT IS FOUND

COLUMN NAME

BZ_L3_GENETIC – Path

90%

dna genetic[a-z]* genome genotyp[a-z]* gene_?(test|result|marker|panel) genetic_?
(test|marker|profile|result) mutation brca[12]? karyotype paternity_?test snp
haplotype newborn_?screening adn gen[ée]tic[oa]

HOW IT IS MASKED

Every character becomes X.

BZ_REDACT

REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

BRCA1 positive

→

XXXXXXXXXXXXXX

9.9

Biometric data

BZ_L3_BIOMETRIC

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Fingerprint, face, iris, palm or voice templates stored as text (hash, base64). The Social Security Board captures fingerprints and photographs when it issues a card.

HOW IT IS FOUND

COLUMN NAME

BZ_L3_BIOMETRIC – Path

90%

fingerprints? finger_?prints? thumb_?prints? biometric[a-z]* face_?
(template|encoding|id|print|hash) facial_?(template|recognition|id|image_?hash) iris(_?
(scan|template|code)))? retina(_?scan)? voice_?(print|template) palm_?print signature_?
(image|biometric|capture|pad) minutiae huellas(_?dactilar(es)))? biometri[a-z]*

DATA TYPE

BZ_L3_BIOMETRIC – Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character becomes `x` . Binary columns are out of reach: see *Limits*.

`BZ_REDACT` `REGEX DECOMPOSE`

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
A1B2C3D4E5F6	→	XXXXXXXXXXXX

9.10

Sexual orientation

BZ_L3_SEXUAL_ORIENTATION

`COLUMN NAME` `KNOWN VALUES` `REGEX DECOMPOSE`

WHAT IT IS

Sexual orientation, which section 2 names explicitly.

HOW IT IS FOUND

COLUMN NAME

BZ_L3_SEXUAL_ORIENTATION - Path

95%

sexual?(orientation|preference)orientation?sexualorient?sexualorientaci[oó]n?sexualpreferencia?sexual

KNOWN VALUES

BZ_L3_SEXUAL_ORIENTATION - List

LIST	VALUES	STRENGTH	FIRST VALUES
bz-detect-sexual-orientations.txt	15	80%	Heterosexual, Gay, Lesbian, Bisexual, Pansexual, Asexual

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

`BZ_SEXUAL_ORIENTATION` `REGEX DECOMPOSE`

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`BZ_SEXUAL_ORIENTATION_LIST` .

`BZ_FLAG` `REGEX DECOMPOSE`

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

`BZ_FLAG_YES_NO` `SECURE LOOKUP`

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt` , chosen by a keyed hash.

`BZ_FLAG_SI_NO` `SECURE LOOKUP`

Replaces the value with one of the 2 values in `bz-flag-si-no.txt` , chosen by a keyed hash.

`BZ_FLAG_TRUE_FALSE` `SECURE LOOKUP`

Replaces the value with one of the 2 values in `bz-flag-true-false.txt` , chosen by a keyed hash.

`BZ_FLAG_Y_N` `SECURE LOOKUP`

Replaces the value with one of the 2 values in `bz-flag-y-n.txt` , chosen by a keyed hash.

`BZ_FLAG_S_N` `SECURE LOOKUP`

Replaces the value with one of the 2 values in `bz-flag-s-n.txt` , chosen by a keyed hash.

`BZ_FLAG_0_1` `SECURE LOOKUP`

Replaces the value with one of the 2 values in `bz-flag-0-1.txt` , chosen by a keyed hash.

`BZ_CM_ALNUM` `CHARACTER MAPPING`

Maps each character to another of its group (7 groups), keeping length and format.

`BZ_SEXUAL_ORIENTATION_LIST` `SECURE LOOKUP`

Replaces the value with one of the 8 values in `bz-sexual-orientations.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Bisexual

→ Other

9.11 Sexual life

BZ_L3_SEXUAL_LIFE

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Sexual activity, behaviour and history.

HOW IT IS FOUND

COLUMN NAME

BZ_L3_SEXUAL_LIFE - Path

90%

sex(ual)?_?life sexual_?(activity|behavio(u)?r|history|partners?|practices?) sexually_
active number_of_?sexual_?partners age_?(at_)?first_?(sex|intercourse) vida_?sexual
conducta_?sexual actividad_?sexual

HOW IT IS MASKED

Suppressed to Not stated .

BZ_SUPPRESSED_CATEGORY

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: BZ_SUPPRESS .

BZ_FLAG

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-yes-no.txt , chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-si-no.txt , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-true-false.txt , chosen by a keyed hash.

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-y-n.txt , chosen by a keyed hash.

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-s-n.txt , chosen by a keyed hash.

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-0-1.txt , chosen by a keyed hash.

BZ_CM_ALNUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_SUPPRESS

SECURE LOOKUP

Replaces the value with one of the 1 values in bz-not-stated.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Active

→ Not stated

9.12 Gender identity

BZ_L3_GENDER_IDENTITY

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Gender identity and pronouns. Not in the section 2 list; treated as sensitive because it exposes people to the same discrimination.

HOW IT IS FOUND

COLUMN NAME

BZ_L3_GENDER_IDENTITY - Path

95%

gender_(identity|expression) preferred_?pronouns? pronouns? transgender trans_?status

identidad_?(de_?)?g[eé]nero g[eé]nero_?autopercebido

KNOWN VALUES

BZ_L3_GENDER_IDENTITY - List

LIST	VALUES	STRENGTH	FIRST VALUES
bz-detect-gender-identities.txt	14	70%	Woman, Man, Trans woman, Trans man, Non-binary, Gender fluid

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

BZ_GENDER_IDENTITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_GENDER_IDENTITY_LIST .

BZ_FLAG REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-yes-no.txt , chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-si-no.txt , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-true-false.txt , chosen by a keyed hash.

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-y-n.txt , chosen by a keyed hash.

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-s-n.txt , chosen by a keyed hash.

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-0-1.txt , chosen by a keyed hash.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_GENDER_IDENTITY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in bz-gender-identities.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Trans man	→ Gender fluid

Health records

Section 2 does not list health among the sensitive data, but the Act gives health records a place of their own: a health record is information on a person's physical or mental condition made by a health care professional (s. 2), medical purposes are a condition of their own for processing sensitive data (s. 10), and a small business providing health services is never exempt (s. 3). A diagnosis, an antiretroviral or a pregnancy exposes a person at least as much as the listed categories, and the set treats them the same way.

10.1 Health identifier

BZ_HEALTH_ID

COLUMN NAME	CHARACTER MAPPING
-------------	-------------------

WHAT IT IS

The number of the Belize Health Information System card required at public health facilities, National Health Insurance numbers, medical record, admission, prescription and sick-leave certificate numbers.

HOW IT IS FOUND

COLUMN NAME	BZ_HEALTH_ID – Path
85%	bhis(_?(no num number id card))? nhi(_?(no num number id card member_?(no id)))? medical_? record(_?(no num number))? mrn patient_(id no num number) chart_(no num number) health_(record card id)(_?(no num number))? hospital_(no num number) admission_(no num number) prescription_(no num number) sick_(note leave certificate)_?(no num number) medical_?certificate_?(no num number) expediente_?cl[ií]nico historia_? cl[ií]nica
55%	chart admission episode

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM	CHARACTER MAPPING
-------------	-------------------

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
BHIS-2024-00123	→ BS ED-7715-93610

10.2 Diagnosis

BZ_HEALTH_DIAGNOSIS

COLUMN NAME	VALUE FORMAT	REGEX DECOMPOSE
-------------	--------------	-----------------

WHAT IT IS

Diagnoses, as ICD-10 codes (F32.9 , B20) or text, and medical history, allergies and chronic conditions.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_DIAGNOSIS – Path

85% diagnos(is|es|tic)[a-z]* dx icd_?(10|11)?(_?code)? medical_?
 (condition|history|problem|diagnosis) health_?(condition|problem) chronic_
 (condition|disease|illness) illness(es)? disease[a-z]* comorbidit(y|ies) allerg(y|ies)
 cause_?of_?(death|admission|illness|injury|sick_?leave) reason_?for_
 (visit|admission|consultation|sick_?leave) presenting_?complaint chief_?complaint pre_
 existing_?conditions? diagn[oó]stico[a-z]* cie_?10 enfermedad(es)?

VALUE FORMAT BZ_HEALTH_DIAGNOSIS – Regex

PATTERN	STRENGTH	NOTES
[A-TV-Za-tv-z]\d{2}(\.\d{1,2} \d)?		50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code is replaced by another common code of the same format, with or without a decimal; text, by a common diagnosis. The real diagnosis does not survive.

BZ_DIAGNOSIS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

BZ_DIAGNOSIS_TEXT .

BZ_ICD10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in bz-icd10-decimal.txt , chosen by a keyed hash.

BZ_ICD10 SECURE LOOKUP

Replaces the value with one of the 37 values in bz-icd10.txt , chosen by a keyed hash.

BZ_FLAG REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-yes-no.txt , chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-si-no.txt , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-true-false.txt , chosen by a keyed hash.

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-y-n.txt , chosen by a keyed hash.

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-s-n.txt , chosen by a keyed hash.

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-0-1.txt , chosen by a keyed hash.

BZ_DIAGNOSIS_TEXT SECURE LOOKUP

Replaces the value with one of the 30 values in bz-diagnoses.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F32.9	→	J02.9
Major depression	→	Obesity

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Medications and active ingredients. Some reveal the diagnosis: an antiretroviral, an antipsychotic.

HOW IT IS FOUND

COLUMN NAME

BZ_HEALTH_MEDICATION – Path

85%

medications? medicines? drugs?_(name|prescribed) prescribed?(drugs?|medications?)
prescription?(drug|medication|item)s? active?ingredient dosage treatment?
(drug|medication) medicamentos? f[aá]rmacos? receta

KNOWN VALUES

BZ_HEALTH_MEDICATION – List

LIST	VALUES	STRENGTH	FIRST VALUES
bz-detect-medications.txt	51	70%	Paracetamol, Ibuprofen, Naproxen, Diclofenac, Metformin, Glibenclamide

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by one of 26 common medications.

BZ_MEDICATION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_MEDICATION_LIST .

BZ_FLAG REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-yes-no.txt , chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-si-no.txt , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-true-false.txt , chosen by a keyed hash.

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-y-n.txt , chosen by a keyed hash.

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-s-n.txt , chosen by a keyed hash.

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-0-1.txt , chosen by a keyed hash.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_MEDICATION_LIST SECURE LOOKUP

Replaces the value with one of the 26 values in bz-medications.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Sertraline 50 mg	→ Folic acid

10.4 Clinical text

BZ_HEALTH_CLINICAL_TEXT

COLUMN NAME **DATA TYPE** **FREE TEXT REDACTION**

WHAT IT IS

Progress notes, nursing notes, discharge summaries, triage notes and treatment plans.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_CLINICAL_TEXT – Path

85% `clinical_?notes? progress_?notes? nurs(e|ing)_?notes? doctors_?notes? physician_?notes? medical_?notes? discharge_?(summary|notes?) clinical_?summary history_?of_?present(ing)?_?illness hpi physical_?exam(ination)? assessment_?(and_)?plan treatment_?plan care_?plan triage_?notes? soap_?notes? anamnesis evoluci[oó]n(_?m[eé]dica)? nota_?m[eé]dica epicrisis`

DATA TYPE BZ_HEALTH_CLINICAL_TEXT – Type

Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

Free Text Redaction, as for free text: identity numbers, contact details and names are redacted. The clinical content stays; if it must go too, assign the column to a suppression domain.

BZ_FREE_TEXT **FREE TEXT REDACTION**

Replaces the text matching 8 patterns with [DATA], and the 858 terms of `bz-text-names.txt` with [NAME].

EXAMPLES

VALUE

MASKED

Patient Gillett, SSN 000123456, seen for headache.

→ Patient [NAME], SSN [DATA], seen for headache.

10.5 Test result

BZ_HEALTH_TEST_RESULT

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Laboratory and imaging results: HIV status, viral load, blood sugar, pregnancy or drug tests.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_TEST_RESULT – Path

80% `lab_?(result|test|value)s? test_?results? laboratory_?(result|test)s? hiv(_?(status|test|result))? viral_?load cd4(_?count)? blood_?(sugar|glucose|pressure) glucose hba1c cholesterol bmi pregnancy_?test drug_?(test|screen) covid_?(test|result) pcr_?result pap_?(smear|test)(_?result)? mammogram_?result x_?ray_?result resultado_?(examen|laboratorio|prueba)`

50% `result test`

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

Reactive

→

Muikyaya

10.6 Blood group

BZ_HEALTH_BLOOD_GROUP

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

ABO group and Rh factor.

HOW IT IS FOUND

COLUMN NAME

BZ_HEALTH_BLOOD_GROUP - Path

90%

blood_?(type|group) abo(_?rh)? rh_?factor rh grupo_?sangu[ií]neo tipo_?(de_)?sangre

KNOWN VALUES

BZ_HEALTH_BLOOD_GROUP - List

LIST

VALUES

STRENGTH

FIRST VALUES

bz-detect-blood-groups.txt

26

90%

A+, A-, B+, B-, AB+, AB-

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another of the eight groups.

BZ_BLOOD_GROUP

SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-blood-groups.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

0+

→

A-

10.7 Disability

BZ_HEALTH_DISABILITY

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Disability or functional limitation, in the domains the 2022 census asks about: seeing, hearing, walking, remembering or concentrating, self-care, communicating.

HOW IT IS FOUND

COLUMN NAME

BZ_HEALTH_DISABILITY - Path

90%

disabilit(y|ies)[a-z]* disabled impairments? handicap(ped)? special_?needs

functional_?limitations? difficulty_?

(seeing|hearing|walking|remembering|concentrating|self_?care|communicating) invalidity(_?

(status|grade))? discapacidad[a-z]*

KNOWN VALUES BZ_HEALTH_DISABILITY - List

LIST	VALUES	STRENGTH	FIRST VALUES
bz-detect-disabilities.txt	22	60%	Seeing, Hearing, Walking or climbing steps, Remembering or concentrating, Self-care, Communicating

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Flags and codes keep their shape; the value is replaced by another from the list.

BZ_DISABILITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_DISABILITY_LIST .

BZ_FLAG REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_DISABILITY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-disabilities.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Severe psychosocial disability	→ Communicating

10.8 Sexual and reproductive health

BZ_HEALTH_REPRODUCTIVE

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Pregnancy, weeks of gestation, miscarriages and abortions, contraception, fertility, antenatal care, sexually transmitted infections.

HOW IT IS FOUND

COLUMN NAME BZ_HEALTH_REPRODUCTIVE – Path

90% `pregnan(t|cy)[a-z]*` `gestation(al)?(_?age)?` `weeks_(of_)?(pregnancy|gestation)` `lmp`
`last_?menstrual_?period` `abortions?` `miscarriages?` `contracepti(on|ve)[a-z]*` `family_?`
`planning(_?method)?` `fertility` `infertility` `ivf` `gravida` `antenatal` `prenatal` `postnatal`
`postpartum` `sti` `sexually_?transmitted(_?infection)?` `embarazo` `aborto` `anticonceptivos?`
`planificaci[ó]n_?familiar`

HOW IT IS MASKED

Flags keep their shape; any other value becomes `Not stated`.

BZ_SUPPRESSED_CATEGORY **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_SUPPRESS`.

BZ_FLAG **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `keep`.

BZ_FLAG_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt`, chosen by a keyed hash.

BZ_FLAG_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-si-no.txt`, chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-true-false.txt`, chosen by a keyed hash.

BZ_FLAG_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-y-n.txt`, chosen by a keyed hash.

BZ_FLAG_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-s-n.txt`, chosen by a keyed hash.

BZ_FLAG_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-0-1.txt`, chosen by a keyed hash.

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

BZ_SUPPRESS **SECURE LOOKUP**

Replaces the value with one of the 1 values in `bz-not-stated.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

12 weeks pregnant

→

Not stated

Y

→

N

10.9 Mental health and addiction

BZ_HEALTH_MENTAL

COLUMN NAME **REGEX DECOMPOSE**

WHAT IT IS

Mental disorders, suicide attempts and self-harm, substance use and rehabilitation.

HOW IT IS FOUND

COLUMN NAME	BZ_HEALTH_MENTAL - Path
90%	mental_?(health illness disorder condition) psychiatr[a-z]* psycholog[a-z]* depression anxiety suicid[a-z]* self_?harm substance?(use abuse misuse) alcohol(ism _?use _? abuse _?dependence) drug?(use abuse addiction dependence) addiction[a-z]* rehab(ilitation)?_?(programme program centre center status) salud_?mental trastorno[a- z]* adicci[oó]n(es)?

HOW IT IS MASKED

Suppressed to Not stated .

BZ_SUPPRESSED_CATEGORY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: BZ_SUPPRESS .

BZ_FLAG REGEX DECOMPOSE
Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.
BZ_FLAG_YES_NO SECURE LOOKUP
Replaces the value with one of the 2 values in bz-flag-yes-no.txt , chosen by a keyed hash.
BZ_FLAG_SI_NO SECURE LOOKUP
Replaces the value with one of the 2 values in bz-flag-si-no.txt , chosen by a keyed hash.
BZ_FLAG_TRUE_FALSE SECURE LOOKUP
Replaces the value with one of the 2 values in bz-flag-true-false.txt , chosen by a keyed hash.
BZ_FLAG_Y_N SECURE LOOKUP
Replaces the value with one of the 2 values in bz-flag-y-n.txt , chosen by a keyed hash.
BZ_FLAG_S_N SECURE LOOKUP
Replaces the value with one of the 2 values in bz-flag-s-n.txt , chosen by a keyed hash.
BZ_FLAG_0_1 SECURE LOOKUP
Replaces the value with one of the 2 values in bz-flag-0-1.txt , chosen by a keyed hash.
BZ_CM_ALNUM CHARACTER MAPPING
Maps each character to another of its group (7 groups), keeping length and format.
BZ_SUPPRESS SECURE LOOKUP
Replaces the value with one of the 1 values in bz-not-stated.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Bipolar disorder	→ Not stated

Financial record or position

What makes the Belizean list unusual: a data subject's **financial record or position** is sensitive personal data (s. 2 (i)), with the same prohibition as religion or ethnic origin. It goes well beyond a bank account — a credit reference from the credit bureau the Central Bank licensed under the Credit Reporting Act, 2023, a loan in arrears, a salary, a social security benefit, a BOOST transfer or a poverty status. A template made for other laws treats most of these as ordinary data. Categories are replaced within their own notation; amounts are mapped into a plausible range unrelated to the real value.

11.1 Credit reference

BZ_FIN_CREDIT_REFERENCE

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Credit scores and reports, days past due, arrears, loan classification, written-off and non-performing loans. Belize's credit reporting system, run by a bureau the Central Bank licensed under the Credit Reporting Act, 2023, gathers them from banks and credit unions.

HOW IT IS FOUND

COLUMN NAME

BZ_FIN_CREDIT_REFERENCE – Path

90% credit?(score|rating|history|report|status|bureau|reference|risk|grade|standing) crif(_?(score|report|status))? delinquen(cy|t)(_?(status|days))? days?(past?due|in? arrears|overdue) dpd arrears(_?(status|days))? past?due(_?(days|status))? overdue?(days|status) default?(status|flag|indicator) defaulted written?off write?off(_?(status|flag))? collections?_?status bad?debt loan?(status|classification|grade) non?performing npl morosidad score?credit[oa]

HOW IT IS MASKED

A score gets other digits, a flag stays a flag and any status is replaced by another credit status.

BZ_CREDIT

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: BZ_CREDIT_STATUS .

BZ_CM_ALNUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_FLAG

REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-yes-no.txt , chosen by a keyed hash.

BZ_FLAG_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-si-no.txt , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-true-false.txt , chosen by a keyed hash.

BZ_FLAG_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-y-n.txt , chosen by a keyed hash.

BZ_FLAG_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-s-n.txt , chosen by a keyed hash.

BZ_FLAG_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-0-1.txt , chosen by a keyed hash.

BZ_CREDIT_STATUS SECURE LOOKUP

Replaces the value with one of the 10 values in `bz-credit-statuses.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
90 days past due	→	no credit history
745	→	471

11.2 Debt amount

BZ_FIN_DEBT

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Loan, mortgage and card balances, amounts in arrears, credit limits, instalments.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_DEBT - Path

85% `loan_?(amount|balance|principal|outstanding) outstanding_?`
`(balance|amount|debt|loan|principal) debt(_?(amount|total|balance))? amount_?`
`(owed|due|outstanding|in_?arrears|overdue) balance_?(owed|outstanding|due) arrears_?amount`
`credit_?limit mortgage_?(balance|amount) instal?lment(_?amount)? monthly_?`
`(payment|repayment) saldo_?(deudor|prestamo|pr[eé]stamo) monto_?(deuda|prestamo) deuda`

DATA TYPE BZ_FIN_DEBT - Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between BZ\$200 and BZ\$1,000,000.

BZ_DEBT_AMOUNT NUMERIC MAPPING

Maps the number to another between 200 and 1,000,000.

EXAMPLES

VALUE		MASKED
8500	→	5134

11.3 Salary and income

BZ_FIN_INCOME

COLUMN NAME DATA TYPE NUMERIC MAPPING

WHAT IT IS

Salary and wages, insurable earnings, household income.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_INCOME - Path

85% `salary salaries wages? income[a-z]* gross_?(pay|salary|income|earnings) net_?`
`(pay|salary|income|earnings) (monthly|annual|weekly|fortnightly)?`
`(income|salary|earnings|pay|wage) earnings remuneration basic_?(pay|salary) insurable_?`
`earnings household_?income take_?home_?pay salario sueldo ingresos?(_?[a-z]+)?`

DATA TYPE BZ_FIN_INCOME – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between BZ\$700 and BZ\$40,000.

BZ_INCOME **NUMERIC MAPPING**

Maps the number to another between 700 and 40,000.

EXAMPLES

VALUE		MASKED
2400	→	2459

11.4 Assets

BZ_FIN_ASSETS

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

Property and land value, savings and account balances, fixed deposits, investments and credit union shares, net worth.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_ASSETS – Path

85% net_?worth assets_?(value|total) total_?assets property_?value land_?value market_?value appraised_?value valuation_?amount savings(_?balance)? account_?balance deposit_?balance fixed_?deposit(_?amount)? investment_?(balance|value|amount) share_?(balance|capital) patrimonio valor_?(catastral|propiedad|comercial)

DATA TYPE BZ_FIN_ASSETS – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between BZ\$20,000 and BZ\$5,000,000.

BZ_ASSETS **NUMERIC MAPPING**

Maps the number to another between 20,000 and 5,000,000.

EXAMPLES

VALUE		MASKED
185000	→	477515

11.5 Pension

BZ_FIN_PENSION

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

Retirement, invalidity and survivors' pension amounts, the non-contributory pension, gratuities and provident fund balances.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_PENSION – Path

90% pension(_?(amount|payment|monthly|benefit?amount|balance))? monthly?pension retirement?
(pension|benefit|amount|balance) ncp?(amount|payment) survivors?_?pension(_?amount)?
invalidity?_?pension(_?amount)? gratuity(_?amount)? provident?fund(_?balance)?
pensi[oó]n(_?monto)? jubilaci[oó]n(_?monto)?

DATA TYPE BZ_FIN_PENSION – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between BZ\$100 and BZ\$10,000.

BZ_PENSION_AMOUNT **NUMERIC MAPPING**

Maps the number to another between 100 and 10,000.

EXAMPLES

VALUE	MASKED
680	→ 227

11.6 Social security benefit

BZ_FIN_SSB_BENEFIT

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

The benefit a person claims or receives from the Social Security Board: sickness, maternity allowance or grant, employment injury, invalidity, survivors', retirement, funeral grant, non-contributory pension. Most of them also reveal a health event.

HOW IT IS FOUND

COLUMN NAME BZ_FIN_SSB_BENEFIT – Path

90% ssb?(benefit|claim)(_?(type|status|category))? benefit?(type|claim|category|name|code)
claim?type (sickness|maternity|funeral|invalidity|survivors?|employment_
injury|disablement)?(benefit|allowance|grant|claim) social?security?(benefit|claim)(_?
type)? tipo?(de_)?beneficio

KNOWN VALUES BZ_FIN_SSB_BENEFIT – List

LIST	VALUES	STRENGTH	FIRST VALUES
bz-detect-ssb-benefits.txt	21	80%	Sickness benefit, Maternity allowance, Maternity grant, Employment injury benefit, Invalidity pension, Survivors' pension

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Flags and codes keep their shape; the benefit is replaced by another.

BZ_SSB_BENEFIT **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_SSB_BENEFIT_LIST .

BZ_FLAG **REGEX DECOMPOSE**

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt` , chosen by a keyed hash.

BZ_FLAG_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-si-no.txt` , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-true-false.txt` , chosen by a keyed hash.

BZ_FLAG_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-y-n.txt` , chosen by a keyed hash.

BZ_FLAG_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-s-n.txt` , chosen by a keyed hash.

BZ_FLAG_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-0-1.txt` , chosen by a keyed hash.

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

BZ_SSB_BENEFIT_LIST **SECURE LOOKUP**

Replaces the value with one of the 10 values in `bz-ssb-benefits.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Maternity allowance

→ **Survivors' pension**

11.7 Social programme

BZ_FIN_SOCIAL_PROGRAMME

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Beneficiaries of social assistance: BOOST cash transfers and the Food Assistance Programme of the Ministry of Human Development, the non-contributory pension, National Health Insurance. Being a beneficiary reveals poverty, old age or disability.

HOW IT IS FOUND

COLUMN NAME

BZ_FIN_SOCIAL_PROGRAMME - Path

90%

```
boost(?:beneficiary|programme|program|member|recipient))? food?(assistance|pantry)(?:
(programme|program|beneficiary|recipient))? pantry?(programme|program|beneficiary)
social?(programme|program|assistance|welfare|benefit|transfer)s? welfare?
(programme|program|recipient|status) cash?transfer beneficiary?of?(programme|program)
programme?beneficiary ncp?(beneficiary|recipient) non?contributory?pension?
(beneficiary|recipient) nhi?(enrolled|registered|beneficiary|status) human?development?
(programme|program|case) programa?social
```

KNOWN VALUES

BZ_FIN_SOCIAL_PROGRAMME - List

LIST

VALUES

STRENGTH

FIRST VALUES

bz-detect-social-programmes.txt	16	80%	BOOST, Food Assistance Programme, Non-Contributory Pension Programme, National Health Insurance, Other programme, None
bz-detect-flag.txt	9	30%	y, n, yes, no, s, sí

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Flags and codes keep their shape; the programme is replaced by another.

BZ_SOCIAL_PROGRAMME REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_SOCIAL_PROGRAMME_LIST .

BZ_FLAG REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt` , chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt` , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt` , chosen by a keyed hash.

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt` , chosen by a keyed hash.

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt` , chosen by a keyed hash.

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt` , chosen by a keyed hash.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_SOCIAL_PROGRAMME_LIST SECURE LOOKUP

Replaces the value with one of the 6 values in `bz-social-programmes.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Pantry programme

→ National Health Insurance

11.8 Poverty and socioeconomic status

BZ_FIN_POVERTY

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Poverty status (extremely poor, poor, vulnerable), income quintile or decile, means-test scores and vulnerability indexes.

HOW IT IS FOUND

COLUMN NAME

BZ_FIN_POVERTY - Path

90%

```
poverty(_?(status|level|line|index|score|category))? indigen(ce|t)(_?status)? socio_?
economic_?(status|level|index|group|class|score) wealth_?(index|quintile) income_?
(quintile|decile|bracket|band) quintile decile vulnerability_?(index|score) mpi means_?
test(_?(score|result))? pobreza nivel_?socioecon[ó]mico quintil decil
```

KNOWN VALUES

BZ_FIN_POVERTY - List

LIST

VALUES

STRENGTH

FIRST VALUES

bz-detect-poverty.txt

9

40%

extremely poor, indigent, poor, not poor, vulnerable, non poor

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A quintile or decile becomes another number of the same range, with its prefix; a status, another from the list.

BZ_POVERTY REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

BZ_POVERTY_STATUS .

BZ_QUINTILE SECURE LOOKUP

Replaces the value with one of the 5 values in bz-quintile.txt , chosen by a keyed hash.

BZ_DECILE_HIGH SECURE LOOKUP

Replaces the value with one of the 5 values in bz-decile-high.txt , chosen by a keyed hash.

BZ_DECILE SECURE LOOKUP

Replaces the value with one of the 10 values in bz-decile.txt , chosen by a keyed hash.

BZ_POVERTY_STATUS SECURE LOOKUP

Replaces the value with one of the 4 values in bz-poverty-statuses.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Extremely poor	→	Vulnerable
Quintile 2	→	Quintile 4

11.9 Housing tenure

BZ_FIN_HOUSING

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Whether the dwelling is owned, mortgaged, rented privately or from the government, rent free, leased or squatted, as the census asks.

HOW IT IS FOUND

COLUMN NAME

BZ_FIN_HOUSING - Path

95%

housing_?(tenure|status|type|situation) dwelling_?(tenure|ownership|type) home_?ownership
own_?or_?rent rent_?or_?own owns_?(home|house) squatt(er|ing)(_?status)? tenencia_
(de_?)(la_?)?vivienda tipo_?(de_?)?vivienda

55%

tenure

KNOWN VALUES

BZ_FIN_HOUSING - List

LIST

VALUES

STRENGTH

FIRST VALUES

bz-detect-housing- tenure.txt	20	60%	Owned, Owned with mortgage, Rented (private), Rented (government), Rent free, Leased
----------------------------------	----	-----	---

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Flags and codes keep their shape; the tenure is replaced by another from the list.

BZ_HOUSING REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: BZ_HOUSING_LIST .

BZ_FLAG REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-yes-no.txt , chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-si-no.txt , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-true-false.txt` , chosen by a keyed hash.

BZ_FLAG_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-y-n.txt` , chosen by a keyed hash.

BZ_FLAG_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-s-n.txt` , chosen by a keyed hash.

BZ_FLAG_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `bz-flag-0-1.txt` , chosen by a keyed hash.

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

BZ_HOUSING_LIST **SECURE LOOKUP**

Replaces the value with one of the 8 values in `bz-housing-tenure.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Family land

→

Rent free

Criminal record and proceedings

Section 2 makes sensitive both a criminal record and any proceedings for an offence committed or alleged — including their disposal and the sentence — so a charge that ended in acquittal is as protected as a conviction. Data on criminal convictions is processed only under the control of an official authority (s. 10(2)).

12.1 Criminal record and proceedings

BZ_PENAL_CRIMINAL_RECORD

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Criminal record, police record or clearance, convictions, offences, charges, arrests, remand, bail, verdicts and sentences — the record and the proceedings, whatever their outcome.

HOW IT IS FOUND

COLUMN NAME BZ_PENAL_CRIMINAL_RECORD - Path

95%	<code>criminal_?(record history conviction convictions status background charges? proceedings case_?(status outcome)) police_?(record certificate clearance report_?status) convictions?(_?(status record details))? convicted previous_?convictions offen[cs]es?(_? (type committed code description details))? charged_?with arrests?(_?(record history))? sentence(_?(imposed type length details))? incarcerat(ed ion) imprisonment remand(ed)?(_? status)? bail(_?status)? probation(_?status)? parole verdict acquitt(al ed) antecedentes_?penales record_?policial delitos? sentencia</code>
55%	<code>court_?(outcome disposal decision status) case_?(outcome disposal) disposal</code>

HOW IT IS MASKED

A flag stays a flag; any other value becomes a generic status: no criminal record, has criminal record, charged, case dismissed, acquitted, convicted or not stated.

BZ_CRIMINAL_RECORD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_CRIMINAL_RECORD_LIST .

BZ_FLAG REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt` , chosen by a keyed hash.

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-si-no.txt` , chosen by a keyed hash.

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt` , chosen by a keyed hash.

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt` , chosen by a keyed hash.

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-s-n.txt` , chosen by a keyed hash.

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-0-1.txt` , chosen by a keyed hash.

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

BZ_CRIMINAL_RECORD_LIST **SECURE LOOKUP**

Replaces the value with one of the 7 values in `bz-criminal-record.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Convicted of burglary, 2019	→ Acquitted

12.2 Case number

BZ_PENAL_CASE_NUMBER

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

Court, indictment, charge sheet, police report and occurrence numbers: C123/2023 , 456 of 2022 .

HOW IT IS FOUND

COLUMN NAME	BZ_PENAL_CASE_NUMBER – Path
90%	<code>court_?case_?(no num number)</code> <code>criminal_?case_?(no num number)</code> <code>indictment_?(no num number)</code> <code>charge_?sheet_?(no num number)</code> <code>police_?(report occurrence case)_?(no num number)</code> <code>occurrence_?(no num number)</code> <code>docket_?(no num number)</code> <code>claim_?no_?court</code> <code>inquest_?</code> <code>(no number)</code> <code>n(o um ro umero)_?(de_)?causa</code> <code>expediente_?(judicial penal)</code>
55%	<code>case_?(no num number ref reference)</code>

VALUE FORMAT	BZ_PENAL_CASE_NUMBER – Regex		
PATTERN	STRENGTH	NOTES	
[A-Z]{1,3}\s?\d{1,5}/\d{4}		50%	
(?i)\d{1,6}\s+of\s+\d{4}		50%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

BZ_CM_ALNUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
C123/2023	→ X275/5782

Where people live: towns and villages

With the population by city, town and village of the 2022 Population and Housing Census and the location of each place, the set knows the size, district and position of all 221 places the census counts.

- A **town or village** under 5,000 inhabitants becomes the nearest place of the same district with at least 5,000. Thirteen places reach that size: Belize City, San Pedro Town and Ladyville in Belize District; Belmopan, San Ignacio, Santa Elena and Benque Viejo del Carmen in Cayo; Corozal Town; Orange Walk Town and Trial Farm; Dangriga; Punta Gorda and Bella Vista in Toledo.
- The **district** stays: the smallest, Toledo, had 38,944 inhabitants.
- Distance is measured between the places' coordinates. Caye Caulker becomes San Pedro Town, Hopkins becomes Dangriga, Crooked Tree becomes Ladyville.
- Twenty-eight small places share their name with another place — there are four San Antonio and four Santa Cruz. A name is generalized only when every place bearing it is small; then it follows the largest of them, which may lie in another district. Santa Elena in Toledo keeps its name, because the Santa Elena of Cayo is a town, and so does the village of San Pedro in Corozal, because `San Pedro` is how San Pedro Town is written.
- Names are also recognized as they are commonly written: without *Town*, `Benque Viejo`, and the communities the census counts inside another one — `Mango Creek` is Independence, `San Lorenzo` is Orange Walk Town.

The result is always a real place, near the original, and every group of people who end up sharing a name holds at least 5,000 inhabitants. Names that are also given names or surnames, and the district names, are left out of the detection list, so that a surname column is not taken for villages.

Limits

- **Binary columns** — scans of the social security card or passport, fingerprint images, clinical PDFs in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **Electoral divisions stay**. The set does not mask the 31 constituencies, whose names identify few people on their own but narrow a village down in combination. Where a column holds them next to a birth date and sex, generalize it to the district.
- **Identity numbers keep no check digit**. The social security number has no public one, and the TIN's is not published, so neither is recomputed; applications that validate a TIN check digit may reject masked values.
- **Company TINs are masked too**. They cannot be told apart from a person's.
- **Passport, permit and licence numbers** have no public format and are masked character by character.
- **Data Cleansing leaves unknown values as they are**: a village spelled in a way the list does not have passes unchanged.
- **Villages sharing a name** across districts are generalized by the largest of them, and may end up in another district than the district column says.
- **Free text** is redacted token by token: a phone written with spaces is not found, and a given name that is also a common word (`Angel` , `Iris`) is redacted wherever it appears.
- **Children** — the Act protects persons under 16. A birth date moves at most 60 days, so few people cross their 16th or 18th birthday, but some do. Where that matters, split the rule by age group with Multi-

Column Condition.

- **Addresses** are replaced as a whole line. Street, neighbourhood, village and district in separate columns are masked independently and no longer form a coherent address.
- **Plates and VINs** keep their format, but not the VIN check digit.

15

Verification

Before publication the set was checked outside a Masking Engine:

- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 141 columns with the whole set at its assignment threshold — well named, badly named, and 32 columns that are not personal data — and again with the classifiers of the essential pack alone.
- The table that generalizes towns and villages was audited for all 221 places.
- The algorithms, run with the Delphix algorithm plugin, masked 145 sample values and 198 placeholders such as `N/A`, checking each output against its vocabulary, and 150 social security numbers for collisions. Each of the 90 algorithms also masked its own sample input.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

16

Sources

- Data Protection Act, 2021 — Act No. 45 of 2021, National Assembly of Belize, printed by the Government Printer (copy published by the Belize Companies and Corporate Affairs Registry).
- Population by district, city, town and village; ethnic group; languages spoken; religious affiliation; marital and union status; country of birth; dwelling ownership — 2022 Population and Housing Census, Statistical Institute of Belize.
- Coordinates of populated places — GeoNames (CC BY 4.0).
- Social security card and number, benefits — Social Security Board. Taxpayer identification number — Belize Tax Service, in the OECD register of tax identification numbers.
- Voter identification card — Elections and Boundaries Department. Parties of the 2025 general election — Elections and Boundaries Department.
- Credit Reporting System and Credit Reporting Act, 2023 — Central Bank of Belize. BOOST and the Food Assistance Programme — Ministry of Human Development, Families and Indigenous Peoples' Affairs.
- Belize Health Information System card — Ministry of Health and Wellness. Trade unions — National Trade Union Congress of Belize.
- Frequency of surnames and given names — Forebears. Telephone numbering — national numbering plan. Licence plates — Department of Transport.

APPENDIX A

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

BZ_ADDRESS SECURE LOOKUP

Replaces the value with one of the 3,000 values in `bz-addresses.txt`, chosen by a keyed hash.

Used by: `BZ_L1_ADDRESS`

CONFIGURATION

lookupFile	<code>bz-addresses.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_LOOKUP_FILE</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

BZ_AGE REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L2_AGE`

PATTERNS, TRIED IN ORDER

<code>(\d{3,})</code>	replace with <code>90</code>
<code>([1-9])(\d)(\.\d+)</code>	keep · <code>BZ_CM_ALNUM</code> · keep
<code>([1-9])(\d)</code>	keep · <code>BZ_CM_ALNUM</code>
<code>(\d)</code>	<code>BZ_CM_ALNUM</code>
otherwise	keep

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

BZ_ASSETS NUMERIC MAPPING

Maps the number to another between 20,000 and 5,000,000.

Used by: `BZ_FIN_ASSETS`

CONFIGURATION

minValue	<code>20000</code>
maxValue	<code>5000000</code>

BZ_BIRTH_DATE DATE SHIFT

Moves the date by -60 to 60 days.

Used by: `BZ_L2_BIRTH_DATE`

CONFIGURATION

minRange	<code>-60</code>
maxRange	<code>60</code>

unit	DAYS
roll	no

BZ_BLOOD_GROUP SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-blood-groups.txt`, chosen by a keyed hash.

Used by: `BZ_HEALTH_BLOOD_GROUP`

CONFIGURATION

lookupFile	<code>bz-blood-groups.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_CAPPED_COUNT REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L2_DEPENDANTS`

PATTERNS, TRIED IN ORDER

<code>([0-5])</code>	keep
<code>(\d+)</code>	replace with 5
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_CARD REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L1_PAYMENT_CARD`

PATTERNS, TRIED IN ORDER

<code>(\d[\d\s\~]{11,22}\d)</code>	<code>BZ_CARD_LUHN</code>
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_CARD_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: `BZ_CARD`

CONFIGURATION

minMaskedPositions	6
preserve	0

BZ_CM_ALNUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: BZ_L1_SOCIAL_SECURITY_NUMBER , BZ_L1_TIN , BZ_L1_PASSPORT , BZ_L1_VOTER_ID , BZ_L1_DRIVERS_LICENCE , BZ_L1_IMMIGRATION_DOCUMENT , BZ_L1_VITAL_RECORD , BZ_L1_ADDRESS_DETAIL , BZ_L1_BANK_ACCOUNT , BZ_L1_VIN , BZ_L1_CONTRACT_NUMBER , BZ_L1_USERNAME , BZ_HEALTH_ID , BZ_HEALTH_TEST_RESULT , BZ_PENAL_CASE_NUMBER , BZ_SUPPRESSED_CATEGORY , BZ_GIVEN_NAMES , BZ_SURNAMES , BZ_FULL_NAME , BZ_EMAIL , BZ_PHONE , BZ_PLATE , BZ_PARCEL , BZ_COORDINATE , BZ_YEAR , BZ_AGE , BZ_ETHNICITY , BZ_LANGUAGE , BZ_RELIGION , BZ_POLITICAL_OPINION , BZ_POLITICAL_PARTY , BZ_SEXUAL_ORIENTATION , BZ_GENDER_IDENTITY , BZ_MEDICATION , BZ_DISABILITY , BZ_CREDIT , BZ_SSB_BENEFIT , BZ_SOCIAL_PROGRAMME , BZ_HOUSING , BZ_CRIMINAL_RECORD

CONFIGURATION

characterGroups	0123456789 AEIOU BCDFGHJKLMNPQRSTUVWXYZ aeiou bcdfghjklmnpqrstvwxyz ÁÉÍÓÚú áéíóúü
caseSensitive	yes
minMaskedPositions	0

BZ_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: BZ_L1_DEVICE_ID , BZ_IP

CONFIGURATION

characterGroups	0123456789 abcdef ABCDEF ghijklmnopqrstuvwxyz GHIJKLMNOPQRSTUVWXYZ
caseSensitive	yes
minMaskedPositions	0

BZ_COORDINATE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: BZ_L1_GEOLOCATION

PATTERNS, TRIED IN ORDER

(-?\d{1,3}\.\d)(\d+)\s*,\s*(-?\d{1,3}\.\d)(\d+)	keep · BZ_CM_ALNUM · keep · BZ_CM_ALNUM
(-?\d{1,3}\.\d)(\d+)	keep · BZ_CM_ALNUM
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_CREDIT REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: BZ_CREDIT_STATUS .

Used by: BZ_FIN_CREDIT_REFERENCE

PATTERNS, TRIED IN ORDER

(\d{2,3})	BZ_CM_ALNUM
(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
otherwise	BZ_CREDIT_STATUS

CONFIGURATION

trimInput	yes
requireMask	no

BZ_CREDIT_STATUS SECURE LOOKUP

Replaces the value with one of the 10 values in `bz-credit-statuses.txt` , chosen by a keyed hash.

Used by: `BZ_CREDIT`

CONFIGURATION

lookupFile	<code>bz-credit-statuses.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

BZ_CRIMINAL_RECORD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`BZ_CRIMINAL_RECORD_LIST` .

Used by: `BZ_PENAL_CRIMINAL_RECORD`

PATTERNS, TRIED IN ORDER

<code>(?i)(yes no s[ii] true false [yns01])</code>	<code>BZ_FLAG</code>
<code>(\d{1,6})</code>	<code>BZ_CM_ALNUM</code>
otherwise	<code>BZ_CRIMINAL_RECORD_LIST</code>

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

BZ_CRIMINAL_RECORD_LIST SECURE LOOKUP

Replaces the value with one of the 7 values in `bz-criminal-record.txt` , chosen by a keyed hash.

Used by: `BZ_CRIMINAL_RECORD`

CONFIGURATION

lookupFile	<code>bz-criminal-record.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

BZ_DEBT_AMOUNT NUMERIC MAPPING

Maps the number to another between 200 and 1,000,000.

Used by: `BZ_FIN_DEBT`

CONFIGURATION

minValue	<code>200</code>
maxValue	<code>1000000</code>

BZ_DECILE SECURE LOOKUP

Replaces the value with one of the 10 values in `bz-decile.txt` , chosen by a keyed hash.

Used by: `BZ_POVERTY`

CONFIGURATION

lookupFile	bz-decile.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_DECILE_HIGH SECURE LOOKUP

Replaces the value with one of the 5 values in bz-decile-high.txt , chosen by a keyed hash.

Used by: BZ_POVERTY

CONFIGURATION

lookupFile	bz-decile-high.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_DIAGNOSIS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: BZ_DIAGNOSIS_TEXT .

Used by: BZ_HEALTH_DIAGNOSIS

PATTERNS, TRIED IN ORDER

([A-TV-Za-tv-z]\d{2}\.\d{1,2})	BZ_ICD10_DECIMAL
([A-TV-Za-tv-z]\d{2,3})	BZ_ICD10
(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
otherwise	BZ_DIAGNOSIS_TEXT

CONFIGURATION

trimInput	yes
requireMask	no

BZ_DIAGNOSIS_TEXT SECURE LOOKUP

Replaces the value with one of the 30 values in bz-diagnoses.txt , chosen by a keyed hash.

Used by: BZ_DIAGNOSIS

CONFIGURATION

lookupFile	bz-diagnoses.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_DISABILITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_DISABILITY_LIST .

Used by: BZ_HEALTH_DISABILITY

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM
otherwise	BZ_DISABILITY_LIST

CONFIGURATION

trimInput	yes
requireMask	no

BZ_DISABILITY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in bz-disabilities.txt , chosen by a keyed hash.

Used by: BZ_DISABILITY

CONFIGURATION

lookupFile	bz-disabilities.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_EDUCATION SECURE LOOKUP

Replaces the value with one of the 12 values in bz-education.txt , chosen by a keyed hash.

Used by: BZ_L2_EDUCATION

CONFIGURATION

lookupFile	bz-education.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

Used by: BZ_L1_EMAIL

PATTERNS, TRIED IN ORDER

([^\s]+)@([^\s]+)\.([A-Za-z]{2,24})	BZ_CM_ALNUM . BZ_CM_ALNUM . replace with test
otherwise	BZ_CM_ALNUM

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

BZ_EMPLOYER SECURE LOOKUP

Replaces the value with one of the 25 values in `bz-employers.txt` , chosen by a keyed hash.

Used by: `BZ_L2_EMPLOYER`

CONFIGURATION

lookupFile	<code>bz-employers.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_ETHNICITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_ETHNICITY_LIST` .

Used by: `BZ_L3_ETHNICITY`

PATTERNS, TRIED IN ORDER

<code>(?i)(yes no s[ií] true false [yns01])</code>	<code>BZ_FLAG</code>
<code>(\d{1,6})</code>	<code>BZ_CM_ALNUM</code>
otherwise	<code>BZ_ETHNICITY_LIST</code>

CONFIGURATION

trimInput	yes
requireMask	no

BZ_ETHNICITY_LIST SECURE LOOKUP

Replaces the value with one of the 14 values in `bz-ethnic-groups.txt` , chosen by a keyed hash.

Used by: `BZ_ETHNICITY`

CONFIGURATION

lookupFile	<code>bz-ethnic-groups.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_EVENT_DATE DATE SHIFT

Moves the date by -30 to 30 days.

Used by: `BZ_L2_EVENT_DATE`

CONFIGURATION

minRange	<code>-30</code>
maxRange	<code>30</code>
unit	<code>DAYS</code>
roll	no

BZ_FLAG REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: BZ_SUPPRESSED_CATEGORY , BZ_ETHNICITY , BZ_LANGUAGE , BZ_RELIGION , BZ_POLITICAL_OPINION , BZ_POLITICAL_PARTY , BZ_SEXUAL_ORIENTATION , BZ_GENDER_IDENTITY , BZ_DIAGNOSIS , BZ_MEDICATION , BZ_DISABILITY , BZ_CREDIT , BZ_SSB_BENEFIT , BZ_SOCIAL_PROGRAMME , BZ_HOUSING , BZ_CRIMINAL_RECORD

PATTERNS, TRIED IN ORDER

(?i)(yes no)	BZ_FLAG_YES_NO
(?i)(s[ií])	BZ_FLAG_SI_NO
(?i)(true false)	BZ_FLAG_TRUE_FALSE
(?i)([yn])	BZ_FLAG_Y_N
(?i)(s)	BZ_FLAG_S_N
([01])	BZ_FLAG_0_1
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_FLAG_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-0-1.txt , chosen by a keyed hash.

Used by: BZ_FLAG

CONFIGURATION

lookupFile	bz-flag-0-1.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FLAG_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-s-n.txt , chosen by a keyed hash.

Used by: BZ_FLAG

CONFIGURATION

lookupFile	bz-flag-s-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FLAG_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in bz-flag-si-no.txt , chosen by a keyed hash.

Used by: BZ_FLAG

CONFIGURATION

lookupFile	bz-flag-si-no.txt
------------	-------------------

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FLAG_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-true-false.txt` , chosen by a keyed hash.

Used by: `BZ_FLAG`

CONFIGURATION

lookupFile	bz-flag-true-false.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FLAG_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-y-n.txt` , chosen by a keyed hash.

Used by: `BZ_FLAG`

CONFIGURATION

lookupFile	bz-flag-y-n.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FLAG_YES_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-flag-yes-no.txt` , chosen by a keyed hash.

Used by: `BZ_FLAG`

CONFIGURATION

lookupFile	bz-flag-yes-no.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_FREE_TEXT FREE TEXT REDACTION

Replaces the text matching 8 patterns with `[DATA]` , and the 858 terms of `bz-text-names.txt` with `[NAME]` .

Used by: `BZ_L1_FREE_TEXT` , `BZ_HEALTH_CLINICAL_TEXT`

PATTERNS, TRIED IN ORDER

`(?<![\d\-\])\d{3}-\d{3}-\d{3}(?![\d\-\])`

(?<!\d)\d{9}(?!\\d)
[\w.+\-]+@[\\w\-]+(\. [\\w\-]+)+
(?<![\d\-])(\++?501-?)?[2-8]\d{2}-\d{4}(?![\d\-])
(?<!\d)(\++?501)?[2-8]\d{6}(?!\\d)
(?<!\d)\d{13,19}(?!\\d)
(?<![A-Za-z])(BMP CZL TOL BZ BC CY OW SC SP SI SE PG DG)-?[A-Z]?-?\d{3,5}(?![A-Za-z\d])
(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\\d)

CONFIGURATION

regExRedactValue	[DATA]
lookupFile	bz-text-names.txt
lookupFileRedactValue	[NAME]
isDenyList	yes

BZ_FULL_NAME REGEX DECOMPOSE

Tries 7 patterns in order and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

Used by: BZ_L1_FULL_NAME

PATTERNS, TRIED IN ORDER

([^,]+), \s*(. +)	BZ_SURNAMES · BZ_GIVEN_NAMES
(\S+)	BZ_GIVEN_NAME
(\S+)\s+(\S+)	BZ_GIVEN_NAME · BZ_SURNAME
(\S+)(\S+)([A-Za-z]\. ?)(\S+)(\S+)	BZ_GIVEN_NAME · keep · keep · keep · BZ_SURNAME
(\S+)\s+(\S+)\s+(\S+)	BZ_GIVEN_NAME · BZ_GIVEN_NAME · BZ_SURNAME
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	BZ_GIVEN_NAME · BZ_GIVEN_NAME · BZ_SURNAME · BZ_SURNAME
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	BZ_GIVEN_NAME · BZ_GIVEN_NAME · BZ_GIVEN_NAME · BZ_SURNAME · BZ_SURNAME
otherwise	BZ_CM_ALNUM

CONFIGURATION

trimInput	yes
requireMask	no

BZ_GENDER_IDENTITY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_GENDER_IDENTITY_LIST .

Used by: BZ_L3_GENDER_IDENTITY

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM
otherwise	BZ_GENDER_IDENTITY_LIST

CONFIGURATION

trimInput	yes
requireMask	no

BZ_GENDER_IDENTITY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in bz-gender-identities.txt , chosen by a keyed hash.

Used by: `BZ_GENDER_IDENTITY`

CONFIGURATION

lookupFile	<code>bz-gender-identities.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

`BZ_GIVEN_NAME` NAME

Replaces the name with one of the 208 names in `bz-given-names.txt`.

Used by: `BZ_GIVEN_NAMES`, `BZ_FULL_NAME`

CONFIGURATION

lookupFile	<code>bz-given-names.txt</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
filterAccent	<code>yes</code>
inputCaseSensitive	<code>no</code>

`BZ_GIVEN_NAMES` REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

Used by: `BZ_L1_GIVEN_NAME`, `BZ_FULL_NAME`

PATTERNS, TRIED IN ORDER

<code>(\S+)</code>	<code>BZ_GIVEN_NAME</code>
<code>(\S+)\s+(\S+)</code>	<code>BZ_GIVEN_NAME</code> · <code>BZ_GIVEN_NAME</code>
<code>(\S+)\s+(\S+)\s+(\S+)</code>	<code>BZ_GIVEN_NAME</code> · <code>BZ_GIVEN_NAME</code> · <code>BZ_GIVEN_NAME</code>
otherwise	<code>BZ_CM_ALNUM</code>

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

`BZ_HOUSING` REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `BZ_HOUSING_LIST`.

Used by: `BZ_FIN_HOUSING`

PATTERNS, TRIED IN ORDER

<code>(?i)(yes no s[ii] true false [yns01])</code>	<code>BZ_FLAG</code>
<code>(\d{1,6})</code>	<code>BZ_CM_ALNUM</code>
otherwise	<code>BZ_HOUSING_LIST</code>

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

`BZ_HOUSING_LIST` SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-housing-tenure.txt`, chosen by a keyed hash.

Used by: `BZ_HOUSING`

CONFIGURATION

lookupFile	bz-housing-tenure.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_ICD10 SECURE LOOKUP

Replaces the value with one of the 37 values in `bz-icd10.txt` , chosen by a keyed hash.

Used by: `BZ_DIAGNOSIS`

CONFIGURATION

lookupFile	bz-icd10.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_ICD10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `bz-icd10-decimal.txt` , chosen by a keyed hash.

Used by: `BZ_DIAGNOSIS`

CONFIGURATION

lookupFile	bz-icd10-decimal.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_INCOME NUMERIC MAPPING

Maps the number to another between 700 and 40,000.

Used by: `BZ_FIN_INCOME`

CONFIGURATION

minValue	700
maxValue	40000

BZ_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `BZ_CM_HEX` .

Used by: `BZ_L1_IP_ADDRESS`

PATTERNS, TRIED IN ORDER

<code>(\d{1,3})\.\(\d{1,3})\.\(\d{1,3})\.\(\d{1,3})</code>	<code>BZ_OCTET · BZ_OCTET · BZ_OCTET · BZ_OCTET</code>
otherwise	<code>BZ_CM_HEX</code>

CONFIGURATION

trimInput	yes
requireMask	no

BZ_LANGUAGE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: BZ_LANGUAGE_LIST .

Used by: BZ_L3_LANGUAGE

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM
otherwise	BZ_LANGUAGE_LIST

CONFIGURATION

trimInput	yes
requireMask	no

BZ_LANGUAGE_LIST SECURE LOOKUP

Replaces the value with one of the 11 values in bz-languages.txt , chosen by a keyed hash.

Used by: BZ_LANGUAGE

CONFIGURATION

lookupFile	bz-languages.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_MARITAL_STATUS SECURE LOOKUP

Replaces the value with one of the 7 values in bz-marital-status.txt , chosen by a keyed hash.

Used by: BZ_L2_MARITAL_STATUS

CONFIGURATION

lookupFile	bz-marital-status.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_MEDICATION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_MEDICATION_LIST .

Used by: BZ_HEALTH_MEDICATION

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM

otherwise	BZ_MEDICATION_LIST
-----------	--------------------

CONFIGURATION

trimInput	yes
requireMask	no

BZ_MEDICATION_LIST SECURE LOOKUP

Replaces the value with one of the 26 values in `bz-medications.txt` , chosen by a keyed hash.

Used by: `BZ_MEDICATION`

CONFIGURATION

lookupFile	bz-medications.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_NATIONALITY SECURE LOOKUP

Replaces the value with one of the 16 values in `bz-nationalities.txt` , chosen by a keyed hash.

Used by: `BZ_L2_NATIONALITY`

CONFIGURATION

lookupFile	bz-nationalities.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_NEIGHBOURHOOD SECURE LOOKUP

Replaces the value with one of the 30 values in `bz-neighbourhoods.txt` , chosen by a keyed hash.

Used by: `BZ_L2_NEIGHBOURHOOD`

CONFIGURATION

lookupFile	bz-neighbourhoods.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_OCCUPATION SECURE LOOKUP

Replaces the value with one of the 40 values in `bz-occupations.txt` , chosen by a keyed hash.

Used by: `BZ_L2_OCCUPATION`

CONFIGURATION

lookupFile	bz-occupations.txt
hashMethod	SHA256

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_OCTET NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: BZ_IP

CONFIGURATION

minValue	1
maxValue	254

BZ_PARCEL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

Used by: BZ_L1_LAND_PARCEL

PATTERNS, TRIED IN ORDER

(?i)(.*?block\s*(?:no\.\s*)?)(\d+)(.*?parcel\s*(?:no\.\s*)?)(\d+)(.*)	keep · BZ_CM_ALNUM · keep · BZ_CM_ALNUM · keep
otherwise	BZ_CM_ALNUM

CONFIGURATION

trimInput	yes
requireMask	no

BZ_PENSION_AMOUNT NUMERIC MAPPING

Maps the number to another between 100 and 10,000.

Used by: BZ_FIN_PENSION

CONFIGURATION

minValue	100
maxValue	10000

BZ_PHONE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

Used by: BZ_L1_PHONE

PATTERNS, TRIED IN ORDER

(\+?(?501\)?[\s-]?)?([2-8])(\d{2})([\s-]?)?(\d{4})	keep · keep · BZ_CM_ALNUM · keep · BZ_CM_ALNUM
otherwise	BZ_CM_ALNUM

CONFIGURATION

trimInput	yes
requireMask	no

BZ_PLATE REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: BZ_CM_ALNUM .

Used by: BZ_L1_LICENCE_PLATE

PATTERNS, TRIED IN ORDER

(BMP CZL TOL BZ BC CY OW SC SP SI SE PG DG) ([\s-]?)([A-Z])([\s-]?)(\d{3,5})	keep · keep · keep · keep · BZ_CM_ALNUM
(BMP CZL TOL BZ BC CY OW SC SP SI SE PG DG) ([\s-]?)(\d{3,5})	keep · keep · BZ_CM_ALNUM
([A-Z])([\s-]?)(\d{3,5})	keep · keep · BZ_CM_ALNUM
(\d{3,5})	BZ_CM_ALNUM
otherwise	BZ_CM_ALNUM

CONFIGURATION

trimInput	yes
requireMask	no

BZ_POLITICAL_OPINION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_POLITICAL_OPINION_LIST .

Used by: BZ_L3_POLITICAL_OPINION

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM
otherwise	BZ_POLITICAL_OPINION_LIST

CONFIGURATION

trimInput	yes
requireMask	no

BZ_POLITICAL_OPINION_LIST SECURE LOOKUP

Replaces the value with one of the 7 values in bz-political-opinions.txt , chosen by a keyed hash.

Used by: BZ_POLITICAL_OPINION

CONFIGURATION

lookupFile	bz-political-opinions.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_POLITICAL_PARTY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_POLITICAL_PARTY_LIST .

Used by: BZ_L3_POLITICAL_MEMBERSHIP

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM
otherwise	BZ_POLITICAL_PARTY_LIST

CONFIGURATION

trimInput	yes
requireMask	no

BZ_POLITICAL_PARTY_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in `bz-political-parties.txt` , chosen by a keyed hash.

Used by: `BZ_POLITICAL_PARTY`

CONFIGURATION

lookupFile	<code>bz-political-parties.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_POVERTY REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `BZ_POVERTY_STATUS` .

Used by: `BZ_FIN_POVERTY`

PATTERNS, TRIED IN ORDER

<code>([1-5])</code>	<code>BZ_QUINTILE</code>
<code>([6-9] 10)</code>	<code>BZ_DECILE_HIGH</code>
<code>(?i)(decile\s*)(\d{1,2})</code>	keep · <code>BZ_DECILE</code>
<code>(?i)(quintile\s*)([1-5])</code>	keep · <code>BZ_QUINTILE</code>
otherwise	<code>BZ_POVERTY_STATUS</code>

CONFIGURATION

trimInput	yes
requireMask	no

BZ_POVERTY_STATUS SECURE LOOKUP

Replaces the value with one of the 4 values in `bz-poverty-statuses.txt` , chosen by a keyed hash.

Used by: `BZ_POVERTY`

CONFIGURATION

lookupFile	<code>bz-poverty-statuses.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_QUINTILE SECURE LOOKUP

Replaces the value with one of the 5 values in `bz-quintile.txt` , chosen by a keyed hash.

Used by: `BZ_POVERTY`

CONFIGURATION

lookupFile	<code>bz-quintile.txt</code>
------------	------------------------------

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_REDACT REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: BZ_L1_CREDENTIAL , BZ_L3_GENETIC , BZ_L3_BIOMETRIC

PATTERNS, TRIED IN ORDER

(.+)	each character → X
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: BZ_RELIGION_LIST .

Used by: BZ_L3_RELIGION

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM
otherwise	BZ_RELIGION_LIST

CONFIGURATION

trimInput	yes
requireMask	no

BZ_RELIGION_LIST SECURE LOOKUP

Replaces the value with one of the 19 values in bz-religions.txt , chosen by a keyed hash.

Used by: BZ_RELIGION

CONFIGURATION

lookupFile	bz-religions.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SCHOOL SECURE LOOKUP

Replaces the value with one of the 15 values in bz-schools.txt , chosen by a keyed hash.

Used by: BZ_L2_SCHOOL

CONFIGURATION

lookupFile	bz-schools.txt
------------	----------------

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: BZ_L2_SEX

PATTERNS, TRIED IN ORDER

(?i)(female male)	BZ_SEX_FEMALE_MALE
(?i)(woman man)	BZ_SEX_WOMAN_MAN
(?i)(femenino masculino)	BZ_SEX_SPANISH
(?i)(mujer hombre)	BZ_SEX_MUJER_HOMBRE
(?i)([fm])	BZ_SEX_F_M
(?i)([hm])	BZ_SEX_H_M
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

BZ_SEX_F_M SECURE LOOKUP

Replaces the value with one of the 2 values in bz-sex-f-m.txt , chosen by a keyed hash.

Used by: BZ_SEX

CONFIGURATION

lookupFile	bz-sex-f-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX_FEMALE_MALE SECURE LOOKUP

Replaces the value with one of the 2 values in bz-sex-female-male.txt , chosen by a keyed hash.

Used by: BZ_SEX

CONFIGURATION

lookupFile	bz-sex-female-male.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-sex-h-m.txt` , chosen by a keyed hash.

Used by: `BZ_SEX`

CONFIGURATION

lookupFile	bz-sex-h-m.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-sex-mujer-hombre.txt` , chosen by a keyed hash.

Used by: `BZ_SEX`

CONFIGURATION

lookupFile	bz-sex-mujer-hombre.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX_SPANISH SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-sex-spanish.txt` , chosen by a keyed hash.

Used by: `BZ_SEX`

CONFIGURATION

lookupFile	bz-sex-spanish.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEX_WOMAN_MAN SECURE LOOKUP

Replaces the value with one of the 2 values in `bz-sex-woman-man.txt` , chosen by a keyed hash.

Used by: `BZ_SEX`

CONFIGURATION

lookupFile	bz-sex-woman-man.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SEXUAL_ORIENTATION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_SEXUAL_ORIENTATION_LIST .

Used by: BZ_L3_SEXUAL_ORIENTATION

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM
otherwise	BZ_SEXUAL_ORIENTATION_LIST

CONFIGURATION

trimInput	yes
requireMask	no

BZ_SEXUAL_ORIENTATION_LIST SECURE LOOKUP

Replaces the value with one of the 8 values in bz-sexual-orientations.txt , chosen by a keyed hash.

Used by: BZ_SEXUAL_ORIENTATION

CONFIGURATION

lookupFile	bz-sexual-orientations.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SOCIAL_PROGRAMME REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_SOCIAL_PROGRAMME_LIST .

Used by: BZ_FIN_SOCIAL_PROGRAMME

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM
otherwise	BZ_SOCIAL_PROGRAMME_LIST

CONFIGURATION

trimInput	yes
requireMask	no

BZ_SOCIAL_PROGRAMME_LIST SECURE LOOKUP

Replaces the value with one of the 6 values in bz-social-programmes.txt , chosen by a keyed hash.

Used by: BZ_SOCIAL_PROGRAMME

CONFIGURATION

lookupFile	bz-social-programmes.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SSB_BENEFIT REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

BZ_SSB_BENEFIT_LIST .

Used by: BZ_FIN_SSB_BENEFIT

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM
otherwise	BZ_SSB_BENEFIT_LIST

CONFIGURATION

trimInput	yes
requireMask	no

BZ_SSB_BENEFIT_LIST SECURE LOOKUP

Replaces the value with one of the 10 values in bz-ssb-benefits.txt , chosen by a keyed hash.

Used by: BZ_SSB_BENEFIT

CONFIGURATION

lookupFile	bz-ssb-benefits.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SUPPRESS SECURE LOOKUP

Replaces the value with one of the 1 values in bz-not-stated.txt , chosen by a keyed hash.

Used by: BZ_SUPPRESSED_CATEGORY

CONFIGURATION

lookupFile	bz-not-stated.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

BZ_SUPPRESSED_CATEGORY REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: BZ_SUPPRESS .

Used by: BZ_L3_BELIEF , BZ_L3_TRADE_UNION , BZ_L3_SEXUAL_LIFE , BZ_HEALTH_REPRODUCTIVE , BZ_HEALTH_MENTAL

PATTERNS, TRIED IN ORDER

(?i)(yes no s[ii] true false [yns01])	BZ_FLAG
(\d{1,6})	BZ_CM_ALNUM
otherwise	BZ_SUPPRESS

CONFIGURATION

trimInput	yes
requireMask	no

BZ_SURNAME NAME

Replaces the name with one of the 225 names in `bz-surnames.txt`.

Used by: `BZ_SURNAMES`, `BZ_FULL_NAME`

CONFIGURATION

lookupFile	<code>bz-surnames.txt</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
filterAccent	yes
inputCaseSensitive	no

BZ_SURNAMES REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: `BZ_CM_ALNUM`.

Used by: `BZ_L1_SURNAME`, `BZ_FULL_NAME`

PATTERNS, TRIED IN ORDER

<code>([^\s\-\-]+) (\-) ([^\s\-\-]+)</code>	<code>BZ_SURNAME</code> · keep · <code>BZ_SURNAME</code>
<code>(\S+)</code>	<code>BZ_SURNAME</code>
<code>(\S+) \s+ (\S+)</code>	<code>BZ_SURNAME</code> · <code>BZ_SURNAME</code>
<code>(\S+) \s+ (\S+) \s+ (\S+)</code>	<code>BZ_SURNAME</code> · <code>BZ_SURNAME</code> · <code>BZ_SURNAME</code>
otherwise	<code>BZ_CM_ALNUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

BZ_TOWN_VILLAGE DATA CLEANSING

Replaces each value found in `bz-town-village-generalized.txt` (489 pairs) by its counterpart; values not in the file stay as they are.

Used by: `BZ_L2_TOWN_VILLAGE`

CONFIGURATION

lookupFile	<code>bz-town-village-generalized.txt</code>
delimiter	<code> </code>
caseSensitive	yes
trimWhitespace	yes

BZ_YEAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `BZ_L2_BIRTH_YEAR`

PATTERNS, TRIED IN ORDER

<code>(\d{3}) (\d)</code>	keep · <code>BZ_CM_ALNUM</code>
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
bz-addresses.txt	3,000	BZ_ADDRESS	Lot 59, Hopeville, Punta Gorda · Lot 149, Boca del Rio, San Pedro Town · Mile 55 George Price Highway, Belmopan · Mile 9 George Price Highway, Hattieville
bz-blood-groups.txt	8	BZ_BLOOD_GROUP	A+ · A- · B+ · B-
bz-credit-statuses.txt	10	BZ_CREDIT_STATUS	Current · 30 days past due · 60 days past due · 90 days past due
bz-criminal-record.txt	7	BZ_CRIMINAL_RECORD_LIST	No criminal record · Has criminal record · Charged · Case dismissed
bz-decile-high.txt	5	BZ_DECILE_HIGH	6 · 7 · 8 · 9
bz-decile.txt	10	BZ_DECILE	1 · 2 · 3 · 4
bz-detect-blood-groups.txt	26	BZ_HEALTH_BLOOD_GROUP – List	A+ · A- · B+ · B-
bz-detect-disabilities.txt	22	BZ_HEALTH_DISABILITY – List	Seeing · Hearing · Walking or climbing steps · Remembering or concentrating
bz-detect-education.txt	29	BZ_L2_EDUCATION – List	None · Preschool · Primary incomplete · Primary (Standard 6)
bz-detect-ethnic-groups.txt	43	BZ_L3_ETHNICITY – List	Mestizo/Hispanic/Latino · Creole · Maya Ketchi · Maya Mopan
bz-detect-flag.txt	9	BZ_L3_ETHNICITY – List BZ_FIN_SOCIAL_PROGRAMME – List	y · n · yes · no
bz-detect-gender-identities.txt	14	BZ_L3_GENDER_IDENTITY – List	Woman · Man · Trans woman · Trans man
bz-detect-given-names.txt	208	BZ_L1_GIVEN_NAME – List BZ_L1_FULL_NAME – List	Maria · Jose · Juan · Carlos
bz-detect-housing-tenure.txt	20	BZ_FIN_HOUSING – List	Owned · Owned with mortgage · Rented (private) · Rented (government)
bz-detect-languages.txt	31	BZ_L3_LANGUAGE – List	English · Spanish · Kriol · Maya Q'eqchi'
bz-detect-marital-status.txt	25	BZ_L2_MARITAL_STATUS – List	Never married · Married · Common-law union · Visiting partner

FILE	LINES	USED BY	FIRST LINES
bz-detect-medications.txt	51	BZ_HEALTH_MEDICATION – List	Paracetamol · Ibuprofen · Naproxen · Diclofenac
bz-detect-nationalities.txt	52	BZ_L2_NATIONALITY – List	Belizean · Guatemalan · Salvadoran · Honduran
bz-detect-political-opinions.txt	19	BZ_L3_POLITICAL_OPINION – List	Left · Centre-left · Centre · Centre-right
bz-detect-political-parties.txt	22	BZ_L3_POLITICAL_MEMBERSHIP – List	People's United Party · United Democratic Party · Belize Progressive Party · Belize Justice Movement
bz-detect-poverty.txt	9	BZ_FIN_POVERTY – List	extremely poor · indigent · poor · not poor
bz-detect-religions.txt	50	BZ_L3_RELIGION – List	Roman Catholic · Pentecostal · Seventh-day Adventist · Anglican
bz-detect-sex.txt	12	BZ_L2_SEX – List	f · m · h · female
bz-detect-sexual-orientations.txt	15	BZ_L3_SEXUAL_ORIENTATION – List	Heterosexual · Gay · Lesbian · Bisexual
bz-detect-social-programmes.txt	16	BZ_FIN_SOCIAL_PROGRAMME – List	BOOST · Food Assistance Programme · Non-Contributory Pension Programme · National Health Insurance
bz-detect-ssb-benefits.txt	21	BZ_FIN_SSB_BENEFIT – List	Sickness benefit · Maternity allowance · Maternity grant · Employment injury benefit
bz-detect-surnames.txt	225	BZ_L1_SURNAME – List BZ_L1_FULL_NAME – List	Martinez · Garcia · Castillo · Lopez
bz-detect-towns-villages.txt	241	BZ_L2_TOWN_VILLAGE – List	Corozal Town · Altamira · Buena Vista · Calcutta
bz-detect-trade-unions.txt	23	BZ_L3_TRADE_UNION – List	BNTU · PSU · NTUCB · CWU
bz-diagnoses.txt	30	BZ_DIAGNOSIS_TEXT	Essential hypertension · Type 2 diabetes mellitus · Asthma · Low back pain
bz-disabilities.txt	8	BZ_DISABILITY_LIST	Seeing · Hearing · Walking or climbing steps · Remembering or concentrating
bz-education.txt	12	BZ_EDUCATION	None · Preschool · Primary incomplete · Primary (Standard 6)
bz-employers.txt	25	BZ_EMPLOYER	Caribbean Trading Company Ltd. · Cayo Valley Services Ltd. · Northern Construction Ltd. · Coastal Transport Ltd.
bz-ethnic-groups.txt	14	BZ_ETHNICITY_LIST	Mestizo/Hispanic/Latino · Creole · Maya Ketchi · Maya Mopan
bz-flag-0-1.txt	2	BZ_FLAG_0_1	0 · 1

FILE	LINES	USED BY	FIRST LINES
bz-flag-s-n.txt	2	BZ_FLAG_S_N	S · N
bz-flag-si-no.txt	2	BZ_FLAG_SI_NO	Sí · No
bz-flag-true-false.txt	2	BZ_FLAG_TRUE_FALSE	true · false
bz-flag-y-n.txt	2	BZ_FLAG_Y_N	Y · N
bz-flag-yes-no.txt	2	BZ_FLAG_YES_NO	Yes · No
bz-gender-identities.txt	8	BZ_GENDER_IDENTITY_LIST	Woman · Man · Trans woman · Trans man
bz-given-names.txt	208	BZ_GIVEN_NAME	Maria · Jose · Juan · Carlos
bz-housing-tenure.txt	8	BZ_HOUSING_LIST	Owned · Owned with mortgage · Rented (private) · Rented (government)
bz-icd10-decimal.txt	33	BZ_ICD10_DECIMAL	E11.9 · E78.5 · J45.9 · J06.9
bz-icd10.txt	37	BZ_ICD10	I10 · E11 · E78 · J45
bz-languages.txt	11	BZ_LANGUAGE_LIST	English · Spanish · Kriol · Maya Q'eqchi'
bz-marital-status.txt	7	BZ_MARITAL_STATUS	Never married · Married · Common-law union · Visiting partner
bz-medications.txt	26	BZ_MEDICATION_LIST	Paracetamol · Ibuprofen · Naproxen · Diclofenac
bz-nationalities.txt	16	BZ_NATIONALITY	Belizean · Guatemalan · Salvadoran · Honduran
bz-neighbourhoods.txt	30	BZ_NEIGHBOURHOOD	Lake Independence · Port Loyola · Collet · Mesopotamia
bz-not-stated.txt	1	BZ_SUPPRESS	Not stated
bz-occupations.txt	40	BZ_OCCUPATION	Clerk · Sales clerk · Shop assistant · Construction worker
bz-political-opinions.txt	7	BZ_POLITICAL_OPINION_LIST	Left · Centre-left · Centre · Centre-right
bz-political-parties.txt	8	BZ_POLITICAL_PARTY_LIST	People's United Party · United Democratic Party · Belize Progressive Party · Belize Justice Movement
bz-poverty-statuses.txt	4	BZ_POVERTY_STATUS	Extremely poor · Poor · Vulnerable · Not poor
bz-quintile.txt	5	BZ_QUINTILE	1 · 2 · 3 · 4
bz-religions.txt	19	BZ_RELIGION_LIST	Roman Catholic · Pentecostal · Seventh-day Adventist · Anglican

FILE	LINES	USED BY	FIRST LINES
bz-schools.txt	15	BZ_SCHOOL	Ebenezer Methodist Primary School · St. Joseph Anglican Primary School · Sacred Heart RC Primary School · Holy Family Primary School
bz-sex-f-m.txt	2	BZ_SEX_F_M	F · M
bz-sex-female-male.txt	2	BZ_SEX_FEMALE_MALE	Female · Male
bz-sex-h-m.txt	2	BZ_SEX_H_M	H · M
bz-sex-mujer-hombre.txt	2	BZ_SEX_MUJER_HOMBRE	Mujer · Hombre
bz-sex-spanish.txt	2	BZ_SEX_SPANISH	Femenino · Masculino
bz-sex-woman-man.txt	2	BZ_SEX_WOMAN_MAN	Woman · Man
bz-sexual-orientations.txt	8	BZ_SEXUAL_ORIENTATION_LIST	Heterosexual · Gay · Lesbian · Bisexual
bz-social-programmes.txt	6	BZ_SOCIAL_PROGRAMME_LIST	BOOST · Food Assistance Programme · Non-Contributory Pension Programme · National Health Insurance
bz-ssb-benefits.txt	10	BZ_SSB_BENEFIT_LIST	Sickness benefit · Maternity allowance · Maternity grant · Employment injury benefit
bz-surnames.txt	225	BZ_SURNAME	Martinez · Garcia · Castillo · Lopez
bz-text-names.txt	858	BZ_FREE_TEXT	Maria · MARIA · Jose · JOSE
bz-town-village-generalized.txt	489	BZ_TOWN_VILLAGE	Corozal Town Corozal Town · COROZAL TOWN COROZAL TOWN · Corozal Corozal · COROZAL COROZAL

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 product prod item article company business trade brand file street road avenue village town city district country bank branch plan campaign project service table column field user host server domain model category type school college institution course programme program subject document doc centre center unit clinic hospital area department dept position system app application group list report process event task profile role class object account drug medication diagnosis study benefit party union religion ethnicity language place store shop warehouse supplier vendor contract policy insurance org organi[sz]ation entity parameter variable method function index job script queue resource network device template image photo page site module menu option action permission tax currency issuer invoice payment form zone route line sector building display key tag label title code config setting firm employer estate parcel registration_?section producto articulo empresa archivo calle distrito pais banco escuela colegio documento servicio categoria tipo usuario customer cust client patient employee emp staff worker member student pupil insured beneficiary holder account_?holder policy_?holder mother father parent guardian spouse partner next_?of_?kin doctor physician nurse contact emergency_?contact guarantor debtor borrower applicant signatory witness representative owner tenant landlord victim complainant accused defendant donor heir person driver agent citizen elector voter taxpayer child dependant dependent relative officer teacher cliente paciente empleado beneficiario titular madre padre conyuge persona completos? y_?apellidos? apellidos?

E2 product prod item article company business trade brand file street road avenue village town city district country bank branch plan campaign project service table column field user host server domain model category type school college institution course programme program subject document doc centre center unit clinic hospital area department dept position system app application group list report process event task profile role class object account drug medication diagnosis study benefit party union religion ethnicity language place store shop warehouse supplier vendor contract policy insurance org organi[sz]ation entity parameter variable method function index job script queue resource network device template image photo page site module menu option action permission tax currency issuer invoice payment form zone route line sector building display key tag label title code config setting firm employer estate parcel registration_?section producto articulo empresa archivo calle distrito pais banco escuela colegio documento servicio categoria tipo usuario customer cust client patient employee emp staff worker member student pupil insured beneficiary holder account_?holder policy_?holder mother father parent guardian spouse partner next_?of_?kin doctor physician nurse contact emergency_?contact guarantor debtor borrower applicant signatory witness representative owner tenant landlord victim complainant accused defendant donor heir person driver agent citizen elector voter taxpayer child dependant dependent relative officer teacher cliente paciente empleado beneficiario titular madre padre conyuge persona full complete last first

E3 product prod item article company business trade brand file street road avenue village town city district country bank branch plan campaign project service table column field user host server domain model category type school college institution course programme program subject document doc centre center unit clinic hospital area department dept position system app application group list report process event task profile role class object account drug medication diagnosis study benefit party union religion ethnicity language place store shop warehouse supplier vendor contract policy insurance org organi[sz]ation entity parameter variable method function index job script queue resource network device template image photo page site module menu option action permission tax currency issuer invoice payment form zone route line sector building display key tag label title code config setting firm employer estate parcel registration_?section producto articulo empresa archivo calle distrito pais banco escuela colegio documento servicio categoria tipo usuario customer cust client patient employee emp staff worker member student pupil insured beneficiary holder account_?holder policy_?holder mother father parent guardian spouse partner next_?of_?kin doctor physician nurse contact emergency_?contact guarantor debtor borrower applicant signatory witness representative owner tenant landlord victim complainant accused defendant donor heir person driver agent citizen elector voter taxpayer child dependant dependent relative officer teacher cliente paciente empleado beneficiario titular madre padre conyuge persona completo y_?apellidos? apellidos?

E4 ip mac email e_?mail web url book type id

E5 id type code key no num number date status queue count log

E6 id key type role site ref code number no size

APPENDIX D

Profile set and classifiers

The profile set `BZ – Data Protection Act 2021 – v2` runs these 124 classifiers, with an assignment threshold of 60%.

Direct identifiers, quasi-identifiers, sensitive personal data (section 2), health records, financial record or position, and criminal record and proceedings, under the Data Protection Act, 2021 of Belize.

CLASSIFIER	KIND	DOMAIN
BZ_L1_SOCIAL_SECURITY_NUMBER – Path	COLUMN NAME	BZ_L1_SOCIAL_SECURITY_NUMBER
BZ_L1_SOCIAL_SECURITY_NUMBER – Regex	VALUE FORMAT	BZ_L1_SOCIAL_SECURITY_NUMBER
BZ_L1_TIN – Path	COLUMN NAME	BZ_L1_TIN
BZ_L1_PASSPORT – Path	COLUMN NAME	BZ_L1_PASSPORT
BZ_L1_PASSPORT – Regex	VALUE FORMAT	BZ_L1_PASSPORT
BZ_L1_VOTER_ID – Path	COLUMN NAME	BZ_L1_VOTER_ID
BZ_L1_DRIVERS_LICENCE – Path	COLUMN NAME	BZ_L1_DRIVERS_LICENCE
BZ_L1_IMMIGRATION_DOCUMENT – Path	COLUMN NAME	BZ_L1_IMMIGRATION_DOCUMENT
BZ_L1_VITAL_RECORD – Path	COLUMN NAME	BZ_L1_VITAL_RECORD
BZ_L1_GIVEN_NAME – Path	COLUMN NAME	BZ_L1_GIVEN_NAME
BZ_L1_GIVEN_NAME – List	KNOWN VALUES	BZ_L1_GIVEN_NAME
BZ_L1_SURNAME – Path	COLUMN NAME	BZ_L1_SURNAME
BZ_L1_SURNAME – List	KNOWN VALUES	BZ_L1_SURNAME
BZ_L1_FULL_NAME – Path	COLUMN NAME	BZ_L1_FULL_NAME
BZ_L1_FULL_NAME – List	KNOWN VALUES	BZ_L1_FULL_NAME
BZ_L1_EMAIL – Path	COLUMN NAME	BZ_L1_EMAIL
BZ_L1_EMAIL – Type	DATA TYPE	BZ_L1_EMAIL
BZ_L1_EMAIL – Regex	VALUE FORMAT	BZ_L1_EMAIL
BZ_L1_PHONE – Path	COLUMN NAME	BZ_L1_PHONE
BZ_L1_PHONE – Regex	VALUE FORMAT	BZ_L1_PHONE
BZ_L1_ADDRESS – Path	COLUMN NAME	BZ_L1_ADDRESS
BZ_L1_ADDRESS – Type	DATA TYPE	BZ_L1_ADDRESS
BZ_L1_ADDRESS – Regex	VALUE FORMAT	BZ_L1_ADDRESS
BZ_L1_ADDRESS_DETAIL – Path	COLUMN NAME	BZ_L1_ADDRESS_DETAIL
BZ_L1_BANK_ACCOUNT – Path	COLUMN NAME	BZ_L1_BANK_ACCOUNT
BZ_L1_PAYMENT_CARD – Path	COLUMN NAME	BZ_L1_PAYMENT_CARD
BZ_L1_PAYMENT_CARD – Regex	VALUE FORMAT	BZ_L1_PAYMENT_CARD
BZ_L1_IP_ADDRESS – Path	COLUMN NAME	BZ_L1_IP_ADDRESS
BZ_L1_IP_ADDRESS – Regex	VALUE FORMAT	BZ_L1_IP_ADDRESS
BZ_L1_DEVICE_ID – Path	COLUMN NAME	BZ_L1_DEVICE_ID

CLASSIFIER	KIND	DOMAIN
BZ_L1_DEVICE_ID – Regex	VALUE FORMAT	BZ_L1_DEVICE_ID
BZ_L1_LICENCE_PLATE – Path	COLUMN NAME	BZ_L1_LICENCE_PLATE
BZ_L1_LICENCE_PLATE – Regex	VALUE FORMAT	BZ_L1_LICENCE_PLATE
BZ_L1_VIN – Path	COLUMN NAME	BZ_L1_VIN
BZ_L1_VIN – Regex	VALUE FORMAT	BZ_L1_VIN
BZ_L1_LAND_PARCEL – Path	COLUMN NAME	BZ_L1_LAND_PARCEL
BZ_L1_LAND_PARCEL – Regex	VALUE FORMAT	BZ_L1_LAND_PARCEL
BZ_L1_CONTRACT_NUMBER – Path	COLUMN NAME	BZ_L1_CONTRACT_NUMBER
BZ_L1_USERNAME – Path	COLUMN NAME	BZ_L1_USERNAME
BZ_L1_CREDENTIAL – Path	COLUMN NAME	BZ_L1_CREDENTIAL
BZ_L1_GEOLOCATION – Path	COLUMN NAME	BZ_L1_GEOLOCATION
BZ_L1_GEOLOCATION – Regex	VALUE FORMAT	BZ_L1_GEOLOCATION
BZ_L1_FREE_TEXT – Path	COLUMN NAME	BZ_L1_FREE_TEXT
BZ_L1_FREE_TEXT – Type	DATA TYPE	BZ_L1_FREE_TEXT
BZ_L1_FREE_TEXT – Regex	VALUE FORMAT	BZ_L1_FREE_TEXT
BZ_L2_BIRTH_DATE – Path	COLUMN NAME	BZ_L2_BIRTH_DATE
BZ_L2_BIRTH_DATE – Type	DATA TYPE	BZ_L2_BIRTH_DATE
BZ_L2_BIRTH_YEAR – Path	COLUMN NAME	BZ_L2_BIRTH_YEAR
BZ_L2_BIRTH_YEAR – Type	DATA TYPE	BZ_L2_BIRTH_YEAR
BZ_L2_AGE – Path	COLUMN NAME	BZ_L2_AGE
BZ_L2_AGE – Type	DATA TYPE	BZ_L2_AGE
BZ_L2_EVENT_DATE – Path	COLUMN NAME	BZ_L2_EVENT_DATE
BZ_L2_EVENT_DATE – Type	DATA TYPE	BZ_L2_EVENT_DATE
BZ_L2_SEX – Path	COLUMN NAME	BZ_L2_SEX
BZ_L2_SEX – List	KNOWN VALUES	BZ_L2_SEX
BZ_L2_TOWN_VILLAGE – Path	COLUMN NAME	BZ_L2_TOWN_VILLAGE
BZ_L2_TOWN_VILLAGE – List	KNOWN VALUES	BZ_L2_TOWN_VILLAGE
BZ_L2_NEIGHBOURHOOD – Path	COLUMN NAME	BZ_L2_NEIGHBOURHOOD
BZ_L2_NATIONALITY – Path	COLUMN NAME	BZ_L2_NATIONALITY
BZ_L2_NATIONALITY – List	KNOWN VALUES	BZ_L2_NATIONALITY
BZ_L2_MARITAL_STATUS – Path	COLUMN NAME	BZ_L2_MARITAL_STATUS
BZ_L2_MARITAL_STATUS – List	KNOWN VALUES	BZ_L2_MARITAL_STATUS
BZ_L2_OCCUPATION – Path	COLUMN NAME	BZ_L2_OCCUPATION
BZ_L2_EMPLOYER – Path	COLUMN NAME	BZ_L2_EMPLOYER
BZ_L2_EDUCATION – Path	COLUMN NAME	BZ_L2_EDUCATION
BZ_L2_EDUCATION – List	KNOWN VALUES	BZ_L2_EDUCATION
BZ_L2_SCHOOL – Path	COLUMN NAME	BZ_L2_SCHOOL

CLASSIFIER	KIND	DOMAIN
BZ_L2_DEPENDANTS – Path	COLUMN NAME	BZ_L2_DEPENDANTS
BZ_L2_DEPENDANTS – Type	DATA TYPE	BZ_L2_DEPENDANTS
BZ_L3_ETHNICITY – Path	COLUMN NAME	BZ_L3_ETHNICITY
BZ_L3_ETHNICITY – List	KNOWN VALUES	BZ_L3_ETHNICITY
BZ_L3_LANGUAGE – Path	COLUMN NAME	BZ_L3_LANGUAGE
BZ_L3_LANGUAGE – List	KNOWN VALUES	BZ_L3_LANGUAGE
BZ_L3_RELIGION – Path	COLUMN NAME	BZ_L3_RELIGION
BZ_L3_RELIGION – List	KNOWN VALUES	BZ_L3_RELIGION
BZ_L3_BELIEF – Path	COLUMN NAME	BZ_L3_BELIEF
BZ_L3_POLITICAL_OPINION – Path	COLUMN NAME	BZ_L3_POLITICAL_OPINION
BZ_L3_POLITICAL_OPINION – List	KNOWN VALUES	BZ_L3_POLITICAL_OPINION
BZ_L3_POLITICAL_MEMBERSHIP – Path	COLUMN NAME	BZ_L3_POLITICAL_MEMBERSHIP
BZ_L3_POLITICAL_MEMBERSHIP – List	KNOWN VALUES	BZ_L3_POLITICAL_MEMBERSHIP
BZ_L3_TRADE_UNION – Path	COLUMN NAME	BZ_L3_TRADE_UNION
BZ_L3_TRADE_UNION – List	KNOWN VALUES	BZ_L3_TRADE_UNION
BZ_L3_GENETIC – Path	COLUMN NAME	BZ_L3_GENETIC
BZ_L3_BIOMETRIC – Path	COLUMN NAME	BZ_L3_BIOMETRIC
BZ_L3_BIOMETRIC – Type	DATA TYPE	BZ_L3_BIOMETRIC
BZ_L3_SEXUAL_ORIENTATION – Path	COLUMN NAME	BZ_L3_SEXUAL_ORIENTATION
BZ_L3_SEXUAL_ORIENTATION – List	KNOWN VALUES	BZ_L3_SEXUAL_ORIENTATION
BZ_L3_SEXUAL_LIFE – Path	COLUMN NAME	BZ_L3_SEXUAL_LIFE
BZ_L3_GENDER_IDENTITY – Path	COLUMN NAME	BZ_L3_GENDER_IDENTITY
BZ_L3_GENDER_IDENTITY – List	KNOWN VALUES	BZ_L3_GENDER_IDENTITY
BZ_HEALTH_ID – Path	COLUMN NAME	BZ_HEALTH_ID
BZ_HEALTH_DIAGNOSIS – Path	COLUMN NAME	BZ_HEALTH_DIAGNOSIS
BZ_HEALTH_DIAGNOSIS – Regex	VALUE FORMAT	BZ_HEALTH_DIAGNOSIS
BZ_HEALTH_MEDICATION – Path	COLUMN NAME	BZ_HEALTH_MEDICATION
BZ_HEALTH_MEDICATION – List	KNOWN VALUES	BZ_HEALTH_MEDICATION
BZ_HEALTH_CLINICAL_TEXT – Path	COLUMN NAME	BZ_HEALTH_CLINICAL_TEXT
BZ_HEALTH_CLINICAL_TEXT – Type	DATA TYPE	BZ_HEALTH_CLINICAL_TEXT
BZ_HEALTH_TEST_RESULT – Path	COLUMN NAME	BZ_HEALTH_TEST_RESULT
BZ_HEALTH_BLOOD_GROUP – Path	COLUMN NAME	BZ_HEALTH_BLOOD_GROUP
BZ_HEALTH_BLOOD_GROUP – List	KNOWN VALUES	BZ_HEALTH_BLOOD_GROUP
BZ_HEALTH_DISABILITY – Path	COLUMN NAME	BZ_HEALTH_DISABILITY
BZ_HEALTH_DISABILITY – List	KNOWN VALUES	BZ_HEALTH_DISABILITY
BZ_HEALTH_REPRODUCTIVE – Path	COLUMN NAME	BZ_HEALTH_REPRODUCTIVE
BZ_HEALTH_MENTAL – Path	COLUMN NAME	BZ_HEALTH_MENTAL

CLASSIFIER	KIND	DOMAIN
BZ_FIN_CREDIT_REFERENCE – Path	COLUMN NAME	BZ_FIN_CREDIT_REFERENCE
BZ_FIN_DEBT – Path	COLUMN NAME	BZ_FIN_DEBT
BZ_FIN_DEBT – Type	DATA TYPE	BZ_FIN_DEBT
BZ_FIN_INCOME – Path	COLUMN NAME	BZ_FIN_INCOME
BZ_FIN_INCOME – Type	DATA TYPE	BZ_FIN_INCOME
BZ_FIN_ASSETS – Path	COLUMN NAME	BZ_FIN_ASSETS
BZ_FIN_ASSETS – Type	DATA TYPE	BZ_FIN_ASSETS
BZ_FIN_PENSION – Path	COLUMN NAME	BZ_FIN_PENSION
BZ_FIN_PENSION – Type	DATA TYPE	BZ_FIN_PENSION
BZ_FIN_SSB_BENEFIT – Path	COLUMN NAME	BZ_FIN_SSB_BENEFIT
BZ_FIN_SSB_BENEFIT – List	KNOWN VALUES	BZ_FIN_SSB_BENEFIT
BZ_FIN_SOCIAL_PROGRAMME – Path	COLUMN NAME	BZ_FIN_SOCIAL_PROGRAMME
BZ_FIN_SOCIAL_PROGRAMME – List	KNOWN VALUES	BZ_FIN_SOCIAL_PROGRAMME
BZ_FIN_POVERTY – Path	COLUMN NAME	BZ_FIN_POVERTY
BZ_FIN_POVERTY – List	KNOWN VALUES	BZ_FIN_POVERTY
BZ_FIN_HOUSING – Path	COLUMN NAME	BZ_FIN_HOUSING
BZ_FIN_HOUSING – List	KNOWN VALUES	BZ_FIN_HOUSING
BZ_PENAL_CRIMINAL_RECORD – Path	COLUMN NAME	BZ_PENAL_CRIMINAL_RECORD
BZ_PENAL_CASE_NUMBER – Path	COLUMN NAME	BZ_PENAL_CASE_NUMBER
BZ_PENAL_CASE_NUMBER – Regex	VALUE FORMAT	BZ_PENAL_CASE_NUMBER