

Mexico — LFPDPPP

Discovering and masking Mexican personal data: direct identifiers with valid check digits, quasi-identifiers, the sensitive data of article 2 and the financial and patrimonial data of article 7.

83

DOMAINS

153

CLASSIFIERS

154

ALGORITHMS

Contents

The first sections explain what the set is for and how it works. The domain chapters then describe every domain: what it is, how its data is found and how it is masked, with examples. The appendices list every algorithm, file and classifier the set contains.

1	About this profile set
2	The LFPDPPP in brief
3	How sensitive data is discovered
4	How data is masked
5	Essential and extended packs
6	Domains at a glance

PART 7 · DIRECT IDENTIFIERS

7.1	CURP	MX_L1_CURP
7.2	RFC	MX_L1_RFC
7.3	Social security number (NSS)	MX_L1_NSS
7.4	INE voter key	MX_L1_CLAVE_ELECTOR
7.5	INE credential numbers	MX_L1_CREDENCIAL_INE
7.6	Given names	MX_L1_NOMBRE
7.7	Surnames	MX_L1_APELLIDO
7.8	Full name	MX_L1_NOMBRE_COMPLETO
7.9	E-mail	MX_L1_EMAIL
7.10	Phone number	MX_L1_TELEFONO
7.11	Address	MX_L1_DIRECCION
7.12	Address details	MX_L1_DIRECCION_COMPLEMENTO
7.13	CLABE	MX_L1_CLABE
7.14	Bank account	MX_L1_CUENTA_BANCARIA
7.15	Payment card	MX_L1_TARJETA
7.16	Passport	MX_L1_PASAPORTE
7.17	Immigration document	MX_L1_DOCUMENTO_MIGRATORIO
7.18	Professional license	MX_L1_CEDULA_PROFESIONAL
7.19	Driver's license	MX_L1_LICENCIA_CONDUCCIR
7.20	e.firma certificate	MX_L1_EFIRMA
7.21	IP address	MX_L1_IP
7.22	Device identifier	MX_L1_DISPOSITIVO
7.23	License plate	MX_L1_PLACA
7.24	Vehicle identification number	MX_L1_NIV
7.25	Contract and customer numbers	MX_L1_NUMERO_CONTRATO

7.26	Username and social media	MX_L1_USUARIO_RRSS
7.27	Credentials	MX_L1_CREDENCIAL
7.28	Geolocation	MX_L1_GEOLOCALIZACION
7.29	Free text	MX_L1_TEXTO_LIBRE

PART 8 · QUASI-IDENTIFIERS

8.1	Birth date	MX_L2_FECHA_NACIMIENTO
8.2	Birth year	MX_L2_ANIO_NACIMIENTO
8.3	Age	MX_L2_EDAD
8.4	Life event dates	MX_L2_FECHA_EVENTO
8.5	Sex	MX_L2_SEXO
8.6	Municipality	MX_L2_MUNICIPIO
8.7	Municipality code	MX_L2_CLAVE_MUNICIPIO
8.8	Locality	MX_L2_LOCALIDAD
8.9	Colonia	MX_L2_COLONIA
8.10	Postal code	MX_L2_CODIGO_POSTAL
8.11	Nationality	MX_L2_NACIONALIDAD
8.12	Marital status	MX_L2_ESTADO_CIVIL
8.13	Occupation	MX_L2_OCUPACION
8.14	Employer	MX_L2_EMPLEADOR
8.15	Schooling	MX_L2_ESCOLARIDAD
8.16	School	MX_L2_ESCUELA
8.17	School code (CCT)	MX_L2_CCT
8.18	Dependents and children	MX_L2_DEPENDIENTES

PART 9 · SENSITIVE DATA

9.1	Ethnic origin	MX_L3_ETNIA
9.2	Indigenous language	MX_L3 LENGUA_INDIGENA
9.3	Diagnosis	MX_L3_SALUD_DIAGNOSTICO
9.4	Medication	MX_L3_SALUD_MEDICAMENTO
9.5	Health record identifiers	MX_L3_SALUD_IDENTIFICADOR
9.6	Clinical notes	MX_L3_SALUD_TEXTO_CLINICO
9.7	Test results	MX_L3_SALUD_RESULTADO_EXAMEN
9.8	Blood type	MX_L3_SALUD_GRUPO_SANGUINEO
9.9	Disability	MX_L3_SALUD_DISCAPACIDAD
9.10	Sexual and reproductive health	MX_L3_SALUD_SEXUAL_REPRODUCTIVA
9.11	Mental health and addictions	MX_L3_SALUD_MENTAL_ADICCIONES
9.12	Biometric data	MX_L3_BIOMETRICO

9.13	Genetic information	MX_L3_INFORMACION_GENETICA
9.14	Sexual preference	MX_L3_PREFERENCIA_SEXUAL
9.15	Gender identity	MX_L3_IDENTIDAD_GENERO
9.16	Sexual life	MX_L3_VIDA_SEXUAL
9.17	Religion	MX_L3_RELIGION
9.18	Philosophical and moral beliefs	MX_L3_CREENCIA_FILOSOFICA_MORAL
9.19	Political opinions	MX_L3_OPINION_POLITICA
9.20	Party membership	MX_L3_AFILIACION_POLITICA
9.21	Union membership	MX_L3_AFILIACION_SINDICAL

PART 10 · FINANCIAL AND PATRIMONIAL DATA

10.1	Credit bureau record	MX_FIN_BURO_CREDITO
10.2	Debt amount	MX_FIN_MONTO_DEUDA
10.3	Monthly income	MX_FIN_INGRESO_MENSUAL
10.4	Daily wage (SDI, SBC)	MX_FIN_SALARIO_DIARIO
10.5	Assets	MX_FIN_PATRIMONIO
10.6	AFORE	MX_FIN_AFORE
10.7	Retirement and housing savings	MX_FIN_SALDO_RETIRO
10.8	Housing credit	MX_FIN_CREDITO_VIVIENDA
10.9	Social security coverage	MX_FIN_SEGURIDAD_SOCIAL
10.10	Social programs	MX_FIN_PROGRAMA_SOCIAL
10.11	Socioeconomic level	MX_FIN_NIVEL_SOCIOECONOMICO
10.12	Housing tenure	MX_FIN_VIVIENDA
10.13	Tax regime	MX_FIN_REGIMEN_FISCAL

PART 11 · CRIMINAL RECORDS

11.1	Criminal records	MX_PENAL_ANTECEDENTES
11.2	Case numbers	MX_PENAL_CAUSA
12	Check digits computed by the set	
13	Dates inside keys	
14	Limits	
15	Verification	
16	Sources	
A	Algorithms	
B	Files	
C	Exclusion lists	
D	Profile set and classifiers	

About this profile set

This profile set finds the personal data in a Mexican database and masks it, so that a non-production copy — for testing, development, training or analytics — no longer identifies anyone.

Masking only names and CURPs does not achieve that: a birth date, a sex and a small municipality single people out on their own. The set works in the same layers the risk does:

- **Direct identifiers** — CURP, RFC, NSS, INE voter key, names, contact details, CLABE and cards, documents, devices, vehicles, free text.
- **Quasi-identifiers** — birth date, age, sex, municipality, locality, colonia, postal code, occupation, employer, schooling.
- **Sensitive data** — ethnic origin and indigenous language, health, genetic information, religious, philosophical and moral beliefs, political opinions, sexual preference, and union membership.
- **Financial and patrimonial data** — credit bureau records, debts, income, assets, retirement savings, housing credit, social security, social programs, socioeconomic level, tax regime.
- **Criminal records** — records and case numbers.

On a Masking Engine the set is one profile set with its classifiers, the domains they vote for, the algorithms those domains name — and the algorithms those build on — and the lookup files they read. The appendices list every one of them with its full configuration.

The assignment threshold is 60%. An unambiguous column name reaches it alone; an ambiguous one — NOMBRE , RESULTADO , CIUDAD — needs the values to agree. A column with a meaningless name (CAMP01 , OBS) is still found when its values have a recognizable shape or vocabulary: a CURP, an RFC, an INE voter key, a CLABE, a plate, a municipality.

Column names are recognized in Spanish, in the abbreviations of Mexican systems (AP_PATERN0 , FEC_NAC , NUM_EXT , CVE_MUN , SDI), in the attribute names of CFDI 4.0 invoices (RfcReceptor , DomicilioFiscalReceptor , RegimenFiscalReceptor) and in English.

Before masking, inventory the binary columns (BLOB, images, PDF). Onboarding processes often store photos of the INE credential: the CURP and the voter key stay readable in the image. Report those columns as residual risk.

The LFPDPPP in brief

The Ley Federal de Protección de Datos Personales en Posesión de los Particulares was published in the Diario Oficial de la Federación on 20 March 2025 and took effect the next day, repealing the law of 2010. Its last amendment (14 November 2025) touched only its supplementary procedural rules. The INAI was dissolved: the authority is now the **Secretaría Anticorrupción y Buen Gobierno**. The public sector has its own law, the Ley General de Protección de Datos Personales en Posesión de Sujetos Obligados, issued the same day.

What matters for a copy of production data:

- **Personal data** is any information about an identified or identifiable person — identifiable directly or indirectly, through any information (art. 2, V).
- **Sensitive data** are those that touch the most intimate sphere of a person or whose misuse may lead to discrimination or serious risk. The law names, as examples and not as a closed list, data that may reveal racial or ethnic origin, present or future health, genetic information, religious, philosophical and moral

beliefs, political opinions and sexual preference (art. 2, VI). They need express written consent, and databases of sensitive data may only be created for legitimate, specific purposes (art. 8).

- **Financial and patrimonial data** need express consent (art. 7).
- **Purpose.** Data may only be processed for the purposes of the privacy notice; a different purpose needs new consent (art. 11). Development and testing are rarely among the purposes a customer agreed to.
- **Dissociation** — a procedure after which data can no longer be associated with the person nor, by their structure, content or level of detail, identify them (art. 2, IX). Consent is not required for data subjected to prior dissociation (art. 9, III).
- **Security.** Administrative, technical and physical measures proportional to the sensitivity of the data (art. 18); breaches that significantly affect people must be reported to them (art. 19); everyone involved keeps confidentiality (art. 20).
- **Sanctions.** Fines up to 320,000 times the UMA, which may be doubled for sensitive data (art. 59); prison of three months to five years for the crimes of chapter XII, doubled for sensitive data (arts. 62 to 64).

A test environment filled with production data is processing for a purpose the privacy notice does not cover, and holds sensitive and financial data outside the controls built for them. A dissociated copy is the route the law itself provides: that is what this set is for.

Two notes on the categories. The 2010 law listed **union membership** as sensitive; the 2025 text no longer names it. Its list is not exhaustive and union membership still exposes people to discrimination, so the set keeps it. **Biometric data** are not named either; they identify a person by definition and are treated as sensitive here.

This document describes technical controls. Whether a copy counts as dissociated is a legal assessment of the whole environment — its access, its retention, what else is joined to it — and not of the profile set alone.

3

How sensitive data is discovered

A profiling job looks at every column of its rule set and asks each classifier of the profile set how confident it is that the column belongs to its domain. The set uses the four classifier frameworks of the Masking Engine:

- **Column name** (Path) — regular expressions on the column name. Each rule has a match strength: the confidence it gives when it matches.
- **Data type** (Type) — accepts the column type and length, or rules the domain out. It never assigns a domain on its own.
- **Value format** (Regex) — tests a sample of the values against patterns, some with a check digit. The confidence follows the share of values that match.
- **Known values** (List) — looks the sampled values up in lists; for names, word by word.

Evidence from the name and from the values is combined per domain, and the column is assigned to the domain with the highest confidence when it reaches the assignment threshold of the profile set — **60%** here. Values that do not match a format or a list count against their domain by the classifier's reject strength.

Column-name rules are shown as their alternatives. They ignore case and must not be glued to other letters:

`rut` finds `RUT_CLIENTE` and `CLIENTE_RUT` but not `RUTA`. In them, `_?` is an optional underscore, `(a|b)` either form, `s?` an optional letter and `[a-z_]*` any continuation.

Profiling proposes; it does not decide. Review the domains assigned in the inventory before running a masking job, and look for columns the set left unassigned.

How data is masked

Each domain names one algorithm, which a masking job applies to every column the inventory assigns to the domain. Algorithms can be composed: a **Regex Decompose** splits a value into parts and gives each part its own action; a **String Algorithm Chain** applies algorithms one after another. The tree under each domain shows everything its algorithm uses; Appendix A has every configuration in full.

The algorithms are deterministic for their key: the same value masks the same way in every table, database and job, so joins between masked systems keep working — as long as every engine uses the same keys.

The masked examples in this document were produced with one particular key. On an engine with other keys the masked values differ; their shape does not.

Essential and extended packs

The set can be adopted whole or in part. The **extended pack** is everything this document describes. The **essential pack** is the minimum for the law — identity documents, names, contact details, address and birth date. To adopt only the essential pack, create on the engine just its domains, the classifiers that vote for them and the algorithms and files those use, and put only those classifiers in the profile set.

PACK	DOMAINS	CLASSIFIERS	ALGORITHMS	FILES
Essential	13	31	63	25
Extended	83	153	154	97

The essential pack holds these domains, marked **Essential** in the tables and chapters:

- CURP — `MX_L1_CURP`
- RFC — `MX_L1_RFC`
- Social security number (NSS) — `MX_L1_NSS`
- INE voter key — `MX_L1_CLAVE_ELECTOR`
- Given names — `MX_L1_NOMBRE`
- Surnames — `MX_L1_APELLIDO`
- Full name — `MX_L1_NOMBRE_COMPLETO`
- E-mail — `MX_L1_EMAIL`
- Phone number — `MX_L1_TELEFONO`
- Address — `MX_L1_DIRECCION`
- Address details — `MX_L1_DIRECCION_COMPLEMENTO`
- Passport — `MX_L1_PASAPORTE`
- Birth date — `MX_L2_FECHA_NACIMIENTO`

With fewer domains competing, a column that a domain of the extended pack would claim by its name can be proposed for an essential domain instead — a numeric code, for instance, can look like a telephone number. Review the profiling result.

Domains at a glance

Every domain of the set, how it is found and the algorithm that masks it.

DOMAIN	FOUND BY			ALGORITHM
DIRECT IDENTIFIERS				
CURP ESSENTIAL MX_L1_CURP	COLUMN NAME	DATA TYPE	VALUE FORMAT	MX_CURP
RFC ESSENTIAL MX_L1_RFC	COLUMN NAME	DATA TYPE	VALUE FORMAT	MX_RFC
Social security number (NSS) ESSENTIAL MX_L1_NSS	COLUMN NAME	DATA TYPE	VALUE FORMAT	MX_NSS
INE voter key ESSENTIAL MX_L1_CLAVE_ELECTOR	COLUMN NAME	DATA TYPE	VALUE FORMAT	MX_CLAVE_ELECTOR
INE credential numbers MX_L1_CREDENCIAL_INE	COLUMN NAME	VALUE FORMAT		MX_CM_ALFANUM
Given names ESSENTIAL MX_L1_NOMBRE	COLUMN NAME	KNOWN VALUES		MX_NOMBRES
Surnames ESSENTIAL MX_L1_APELLIDO	COLUMN NAME	KNOWN VALUES		MX_APELLIDOS
Full name ESSENTIAL MX_L1_NOMBRE_COMPLETO	COLUMN NAME	KNOWN VALUES		MX_NOMBRE_COMPLETO
E-mail ESSENTIAL MX_L1_EMAIL	COLUMN NAME	DATA TYPE	VALUE FORMAT	MX_EMAIL
Phone number ESSENTIAL MX_L1_TELEFONO	COLUMN NAME	VALUE FORMAT		MX_TELEFONO
Address ESSENTIAL MX_L1_DIRECCION	COLUMN NAME	DATA TYPE	VALUE FORMAT	MX_DIRECCION
Address details ESSENTIAL MX_L1_DIRECCION_COMPLEMENTO	COLUMN NAME			
CLABE MX_L1_CLABE	COLUMN NAME	DATA TYPE	VALUE FORMAT	MX_CLABE
Bank account MX_L1_CUENTA_BANCARIA	COLUMN NAME			
Payment card MX_L1_TARJETA	COLUMN NAME	VALUE FORMAT		MX_TARJETA
Passport ESSENTIAL MX_L1_PASAPORTE	COLUMN NAME	VALUE FORMAT		MX_CM_ALFANUM
Immigration document MX_L1_DOCUMENTO_MIGRATORIO	COLUMN NAME			
Professional license MX_L1_CEDULA_PROFESIONAL	COLUMN NAME	VALUE FORMAT		MX_CM_ALFANUM
Driver's license MX_L1_LICENCIA_CONDU CIR	COLUMN NAME			

DOMAIN	FOUND BY			ALGORITHM
e.firma certificate MX_L1_EFIRMA	COLUMN NAME	VALUE FORMAT		MX_CM_ALFANUM
IP address MX_L1_IP	COLUMN NAME	VALUE FORMAT		MX_IP
Device identifier MX_L1_DISPOSITIVO	COLUMN NAME	VALUE FORMAT		MX_CM_HEX
License plate MX_L1_PLACA	COLUMN NAME	VALUE FORMAT		MX_PLACA
Vehicle identification number MX_L1_NIV	COLUMN NAME	VALUE FORMAT		MX_CM_ALFANUM
Contract and customer numbers MX_L1_NUMERO_CONTRATO	COLUMN NAME			MX_CM_ALFANUM
Username and social media MX_L1_USUARIO_RRSS	COLUMN NAME			MX_CM_ALFANUM
Credentials MX_L1_CREDENCIAL	COLUMN NAME			MX_REDACTAR
Geolocation MX_L1_GEOLOCALIZACION	COLUMN NAME	VALUE FORMAT		MX_COORDENADA
Free text MX_L1_TEXTO_LIBRE	COLUMN NAME	DATA TYPE	VALUE FORMAT	MX_TEXTO_LIBRE
QUASI-IDENTIFIERS				
Birth date ESSENTIAL MX_L2_FECHA_NACIMIENTO	COLUMN NAME	DATA TYPE		MX_FECHA_NACIMIENTO
Birth year MX_L2_ANIO_NACIMIENTO	COLUMN NAME	DATA TYPE		MX_ANIO
Age MX_L2_EDAD	COLUMN NAME	DATA TYPE		MX_EDAD
Life event dates MX_L2_FECHA_EVENTO	COLUMN NAME	DATA TYPE		MX_FECHA_EVENTO
Sex MX_L2_SEXO	COLUMN NAME	KNOWN VALUES		MX_SEXO
Municipality MX_L2_MUNICIPIO	COLUMN NAME	KNOWN VALUES		MX_MUNICIPIO
Municipality code MX_L2_CLAVE_MUNICIPIO	COLUMN NAME	DATA TYPE	KNOWN VALUES	MX_CLAVE_MUNICIPIO
Locality MX_L2_LOCALIDAD	COLUMN NAME			MX_LOCALIDAD
Colonia MX_L2_COLONIA	COLUMN NAME			MX_COLONIA
Postal code MX_L2_CODIGO_POSTAL	COLUMN NAME	VALUE FORMAT		MX_CODIGO_POSTAL
Nationality MX_L2_NACIONALIDAD	COLUMN NAME	KNOWN VALUES		MX_NACIONALIDAD
Marital status MX_L2_ESTADO_CIVIL	COLUMN NAME	KNOWN VALUES		MX_ESTADO_CIVIL

DOMAIN	FOUND BY	ALGORITHM
Occupation MX_L2_OCUPACION	COLUMN NAME	MX_OCUPACION
Employer MX_L2_EMPLEADOR	COLUMN NAME	MX_EMPLEADOR
Schooling MX_L2_ESCOLARIDAD	COLUMN NAME KNOWN VALUES	MX_ESCOLARIDAD
School MX_L2_ESCUELA	COLUMN NAME	MX_ESCUELA
School code (CCT) MX_L2_CCT	COLUMN NAME VALUE FORMAT	MX_CM_ALFANUM
Dependents and children MX_L2_DEPENDIENTES	COLUMN NAME DATA TYPE	MX_CANTIDAD_ACOTADA
SENSITIVE DATA		
Ethnic origin MX_L3_ETNIA	COLUMN NAME KNOWN VALUES	MX_PUEBLO
Indigenous language MX_L3_LENGUA_INDIGENA	COLUMN NAME KNOWN VALUES	MX_LENGUA_INDIGENA
Diagnosis MX_L3_SALUD_DIAGNOSTICO	COLUMN NAME VALUE FORMAT	MX_DIAGNOSTICO
Medication MX_L3_SALUD_MEDICAMENTO	COLUMN NAME KNOWN VALUES	MX_MEDICAMENTO
Health record identifiers MX_L3_SALUD_IDENTIFICADOR	COLUMN NAME	MX_CM_ALFANUM
Clinical notes MX_L3_SALUD_TEXTO_CLINICO	COLUMN NAME DATA TYPE	MX_TEXTO_LIBRE
Test results MX_L3_SALUD_RESULTADO_EXAMEN	COLUMN NAME	MX_CM_ALFANUM
Blood type MX_L3_SALUD_GRUPO_SANGUINEO	COLUMN NAME KNOWN VALUES	MX_GRUPO_SANGUINEO
Disability MX_L3_SALUD_DISCAPACIDAD	COLUMN NAME KNOWN VALUES	MX_DISCAPACIDAD
Sexual and reproductive health MX_L3_SALUD_SEXUAL_REPRODUCTIVA	COLUMN NAME	MX_CATEGORIA_SUPRIMIDA
Mental health and addictions MX_L3_SALUD_MENTAL_ADICCIONES	COLUMN NAME	MX_CATEGORIA_SUPRIMIDA
Biometric data MX_L3_BIOMETRICO	COLUMN NAME DATA TYPE	MX_REDACTAR
Genetic information MX_L3_INFORMACION_GENETICA	COLUMN NAME	MX_REDACTAR
Sexual preference MX_L3_PREFERENCIA_SEXUAL	COLUMN NAME KNOWN VALUES	MX_PREFERENCIA_SEXUAL
Gender identity MX_L3_IDENTIDAD_GENERO	COLUMN NAME KNOWN VALUES	MX_IDENTIDAD_GENERO
Sexual life MX_L3_VIDA_SEXUAL	COLUMN NAME	MX_CATEGORIA_SUPRIMIDA

DOMAIN	FOUND BY		ALGORITHM
Religion MX_L3_RELIGION	COLUMN NAME	KNOWN VALUES	MX_RELIGION
Philosophical and moral beliefs MX_L3_CREENCIA_FILOSOFICA_MORAL	COLUMN NAME		MX_CATEGORIA_SUPRIMIDA
Political opinions MX_L3_OPINION_POLITICA	COLUMN NAME	KNOWN VALUES	MX_OPINION_POLITICA
Party membership MX_L3_AFILIACION_POLITICA	COLUMN NAME	KNOWN VALUES	MX_PARTIDO_POLITICO
Union membership MX_L3_AFILIACION_SINDICAL	COLUMN NAME	KNOWN VALUES	MX_CATEGORIA_SUPRIMIDA
FINANCIAL AND PATRIMONIAL DATA			
Credit bureau record MX_FIN_BURO_CREDITO	COLUMN NAME		MX_BURO_CREDITO
Debt amount MX_FIN_MONTO_DEUDA	COLUMN NAME	DATA TYPE	MX_MONTO_DEUDA
Monthly income MX_FIN_INGRESO_MENSUAL	COLUMN NAME	DATA TYPE	MX_INGRESO_MENSUAL
Daily wage (SDI, SBC) MX_FIN_SALARIO_DIARIO	COLUMN NAME	DATA TYPE	MX_SALARIO_DIARIO
Assets MX_FIN_PATRIMONIO	COLUMN NAME	DATA TYPE	MX_PATRIMONIO
AFORE MX_FIN_AFORE	COLUMN NAME	KNOWN VALUES	MX_AFORE
Retirement and housing savings MX_FIN_SALDO_RETIRO	COLUMN NAME	DATA TYPE	MX_SALDO_RETIRO
Housing credit MX_FIN_CREDITO_VIVIENDA	COLUMN NAME	KNOWN VALUES	MX_CREDITO_VIVIENDA
Social security coverage MX_FIN_SEGURIDAD_SOCIAL	COLUMN NAME	KNOWN VALUES	MX_SEGURIDAD_SOCIAL
Social programs MX_FIN_PROGRAMA_SOCIAL	COLUMN NAME	KNOWN VALUES	MX_PROGRAMA_SOCIAL
Socioeconomic level MX_FIN_NIVEL_SOCIOECONOMICO	COLUMN NAME	KNOWN VALUES	MX_NIVEL_SOCIOECONOMICO
Housing tenure MX_FIN_VIVIENDA	COLUMN NAME	KNOWN VALUES	MX_VIVIENDA
Tax regime MX_FIN_REGIMEN_FISCAL	COLUMN NAME		MX_REGIMEN_FISCAL
CRIMINAL RECORDS			
Criminal records MX_PENAL_ANTECEDENTES	COLUMN NAME		MX_ANTECEDENTES
Case numbers MX_PENAL_CAUSA	COLUMN NAME	VALUE FORMAT	MX_CM_ALFANUM

Direct identifiers

Data that identify a person on their own. The national keys — CURP, RFC, NSS, CLABE — keep a valid check digit after masking, because applications validate them and a test environment where they fail validation tests nothing.

7.1 CURP

MX_L1_CURP

- ESSENTIAL
- COLUMN NAME
- DATA TYPE
- VALUE FORMAT
- REGEX DECOMPOSE

WHAT IT IS

The Clave Única de Registro de Población: 18 characters built from the names (4 letters), the birth date, the sex, the state of birth, three internal consonants, a differentiator — a digit for people born before 2000, a letter after — and a check digit. HEGA850720MDFRRL04 . The key of almost every Mexican record, and a quasi-identifier in itself: it carries the birth date, sex and state.

HOW IT IS FOUND

COLUMN NAME

MX_L1_CURP - Path

90%

curp[a-z0-9_]*

c_?u_?r_?p

clave_?unica(_?de_?registro)?(_?de_?poblacion)?

curp_?(cte|cliente|emp|empleado|trab|trabajador|pac|paciente|alumno|benef|beneficiario|titular|asegurado|afiliado|derechohabiente|receptor|usuario|persona)

(cte|cliente|emp|trab|pac|alumno|benef|titular|asegurado)_?curp

DATA TYPE

MX_L1_CURP - Type

Accepts text (length 18 or more); any other type rules the domain out.

VALUE FORMAT

MX_L1_CURP - Regex

PATTERN	STRENGTH	NOTES
[A-Z][AEIOUX][A-Z]{2}\d{2}(0[1-9] 1[0-2])(0[1-9] 12)\d 3[01])[HMX](AS BC BS CC CL CM CS CH DF DG GT GR HG JC MC MN MS NT NL OC PL QT QR SP SL SR TC TS TL VZ YN ZS NE)[B-DF-HJ-NP-TV-Z]{3}[0-9A-Z]\d	100%	
[A-Z]{4}\d{6}[HMX][A-Z]{5}[0-9A-Z]\d	90%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

Letters become other letters (vowel for vowel, consonant for consonant), the birth date another valid date of the same decade, the sex and state other values, the consonants and differentiator other ones of their kind — and the check digit is recomputed, so every masked CURP passes validation. The mapping is one-to-one: a CURP used as a key cannot collide. See *Check digits computed by the set*.

MX_CURP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_CURP_VALIDA

STRING

ALGORITHM

CHAIN

Applies MX_CURP_CUERPO → MX_CURP_DV , in this order.

MX_CURP_CUERPO

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_FECHA_AAMDD

REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

MX_CM_ALFANUM

MX_MES NUMERIC MAPPING
Maps the number to another between 1 and 12.

MX_DIA_1_28 NUMERIC MAPPING
Maps the number to another between 1 and 28.

MX_MES_30_DIAS SECURE LOOKUP
Replaces the value with one of the 11 values in `mx-meses-30-dias.txt`, chosen by a keyed hash.

MX_DIA_29_30 NUMERIC MAPPING
Maps the number to another between 29 and 30.

MX_MES_31_DIAS SECURE LOOKUP
Replaces the value with one of the 7 values in `mx-meses-31-dias.txt`, chosen by a keyed hash.

MX_SEXO_H_M SECURE LOOKUP
Replaces the value with one of the 2 values in `mx-sexo-h-m.txt`, chosen by a keyed hash.

MX_ENTIDAD_CURP SECURE LOOKUP
Replaces the value with one of the 33 values in `mx-entidad-curp.txt`, chosen by a keyed hash.

MX_CURP_DV STRING ALGORITHM CHAIN
Applies `MX_CURP_DV_P1 → MX_CURP_DV_P2 → MX_CURP_DV_P3 → MX_CURP_DV_P4 → MX_CURP_DV_P5 → MX_CURP_DV_P6 → MX_CURP_DV_P7 → MX_CURP_DV_P8`, in this order. It is made of 16 algorithms that repeat the same step position by position; each one is in Appendix A.

EXAMPLES

VALUE		MASKED
HEGA850720MDFRRL04	→	WUVU800428HTLBZD88
L0PM030215HJCPRRA8	→	GIFW090514HTLHDLE3

7.2

RFC

MX_L1_RFC

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The Registro Federal de Contribuyentes: 13 characters for a person (4 letters, birth date, 2-character differentiator, check digit), 12 for a company. HEGA850720ABA . Appears in payroll, supplier and CFDI invoice tables.

HOW IT IS FOUND

COLUMN NAME

MX_L1_RFC - Path

90%

`rfc[a-z0-9]* r_?f_?c registro_?federal(_?de)?(_?contribuyentes)? rfc_?(cte|cliente|emp|empleado|trab|trabajador|prov|proveedor|receptor|emisor|titular|contribuyente|persona|pf|fisica) (cte|cliente|emp|trab|prov|receptor|emisor|titular)?_rfc tax_?id id_fiscal`

DATA TYPE

MX_L1_RFC - Type

Accepts text (length 10 or more); any other type rules the domain out.

VALUE FORMAT MX_L1_RFC – Regex

PATTERN	STRENGTH	NOTES
[A-ZÑ&]{4}\d{2}(0[1-9] 1[0-2])(0[1-9] 12)\d{3}(01)[A-Z0-9]{2}[0-9A]	100%	
[A-ZÑ&]{3}\d{2}(0[1-9] 1[0-2])(0[1-9] 12)\d{3}(01)[A-Z0-9]{2}[0-9A]	90%	
[A-ZÑ&]{4}\d{2}(0[1-9] 1[0-2])(0[1-9] 12)\d{3}(01)	60%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

Same treatment as the CURP, with the SAT's modulo 11 check digit, A included. A person's RFC shares its first ten characters with their CURP, and both are masked with the same algorithms: after masking they still share them. Company RFCs are masked too – a column mixes both, and the incorporation date of a small company can point to its owner. An RFC without differentiator (10 characters) keeps its shape.

MX_RFC REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_RFC_FISICA STRING ALGORITHM CHAIN

Applies MX_RFC_CUERPO_FISICA → MX_RFC_DV , in this order.

MX_RFC_CUERPO_FISICA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_FECHA_AAMDD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

MX_CM_ALFANUM .

MX_MES NUMERIC MAPPING

Maps the number to another between 1 and 12.

MX_DIA_1_28 NUMERIC MAPPING

Maps the number to another between 1 and 28.

MX_MES_30_DIAS SECURE LOOKUP

Replaces the value with one of the 11 values in mx-meses-30-dias.txt , chosen by a keyed hash.

MX_DIA_29_30 NUMERIC MAPPING

Maps the number to another between 29 and 30.

MX_MES_31_DIAS SECURE LOOKUP

Replaces the value with one of the 7 values in mx-meses-31-dias.txt , chosen by a keyed hash.

MX_RFC_DV STRING ALGORITHM CHAIN

Applies MX_RFC_DV_P1 → MX_RFC_DV_P2 → MX_RFC_DV_P3 → MX_RFC_DV_P4 → MX_RFC_DV_P5 → MX_RFC_DV_P6 , in this order. It is made of 12 algorithms that repeat the same step position by position; each one is in Appendix A.

MX_RFC_MORAL STRING ALGORITHM CHAIN

Applies MX_RFC_CUERPO_MORAL → MX_RFC_RELLENO → MX_RFC_DV → MX_RFC_SIN_RELLENO , in this order.

MX_RFC_CUERPO_MORAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

MX_RFC_RELLENO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

MX_RFC_RELLENO_TABLA DATA CLEANSING

Replaces each value found in mx-rfc-relleno.txt (38 pairs) by its counterpart; values not in the file stay as they are.

MX_RFC_SIN_RELLENO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

HEGA850720ABA

→

WUVU800428EX5

WMT970714R10

→

DHL950413V22

7.3

Social security number (NSS)

MX_L1_NSS

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The IMSS number: 11 digits holding the subdelegation, registration year, birth year, a sequence and a check digit. Present in every payroll and HR system.

HOW IT IS FOUND

COLUMN NAME

MX_L1_NSS - Path

90%

nss[a-z0-9]* n?s?s num(ero)??(de_)?seguro?social n(o|um|ro)?(seg|seguro)? soc(ial)? num(ero)??(de_)?seguridad?social numero?imss n(o|um|ro)?imss imss? (num|nss|no) afiliacion?imss nss? (trab|trabajador|emp|empleado|asegurado|derechohabiente)

DATA TYPE

MX_L1_NSS - Type

Accepts text (length 11 to 13) or number (length 10 to 11); any other type rules the domain out.

VALUE FORMAT

MX_L1_NSS - Regex

PATTERN

STRENGTH

NOTES

\d{11}

70% LUHN check digit

\d{2}-?\d{2}-?\d{2}-?\d{4}-?\d

40%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another NSS that passes the same Luhn check — the check of payment cards, which the Payment Card framework keeps valid. The mapping is one-to-one. Written with dashes, it is masked digit by digit, without a valid check digit.

MX_NSS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_NSS_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

12345678903

→

68774252859

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

The clave de elector of the INE credential: 6 consonants from the names, birth date, state number, sex and a 3-digit differentiator. GRHRAL85072009M100 . The INE credential is the most used identity document in Mexico.

HOW IT IS FOUND

COLUMN NAME

MX_L1_CLAVE_ELECTOR – Path

90%

clave_(de_)?elector

cve_?elector

clave_?electoral

clave_?ine

clave_?ife

elector_?

(clave|key)

voter_?key

DATA TYPE

MX_L1_CLAVE_ELECTOR – Type

Accepts text (length 18 or more); any other type rules the domain out.

VALUE FORMAT

MX_L1_CLAVE_ELECTOR – Regex

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

Consonants mapped, birth date through the same algorithm as in the CURP (so a person's CURP and voter key keep the same masked date), state and sex replaced, differentiator mapped. The key has no check digit.

MX_CLAVE_ELECTOR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_FECHA_AAMDD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_MES NUMERIC MAPPING

Maps the number to another between 1 and 12.

MX_DIA_1_28 NUMERIC MAPPING

Maps the number to another between 1 and 28.

MX_MES_30_DIAS SECURE LOOKUP

Replaces the value with one of the 11 values in mx-meses-30-dias.txt , chosen by a keyed hash.

MX_DIA_29_30 NUMERIC MAPPING

Maps the number to another between 29 and 30.

MX_MES_31_DIAS SECURE LOOKUP

Replaces the value with one of the 7 values in mx-meses-31-dias.txt , chosen by a keyed hash.

MX_ENTIDAD_NUMERO SECURE LOOKUP

Replaces the value with one of the 32 values in mx-entidad-numero.txt , chosen by a keyed hash.

MX_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in mx-sexo-h-m.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
GRHRAL85072009M100	→	WVBMIF80042822H896

7.5 INE credential numbers

MX_L1_CREDENCIAL_INE

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

The numbers that identify the physical credential: OCR (13 digits), CIC (9 digits), the citizen identifier and the issue number.

HOW IT IS FOUND

COLUMN NAME	MX_L1_CREDENCIAL_INE – Path	
85%	ocr(_?(ine ife credencial))? cic(_?(ine ife credencial))? id_?ciudadano identificador_?ciudadano folio_?(ine ife credencial credencial_?elector) n(o um ro)_?(credencial_?(de_?)?elector ine ife) num(ero)?_?(de_?)?(ine ife) credencial_?(ine ife elector para_?votar) ine ife numero_?vertical num_?emision	
55%	credencial identificacion_?oficial n(o um ro)_?identificacion	
VALUE FORMAT	MX_L1_CREDENCIAL_INE – Regex	
PATTERN	STRENGTH	NOTES
\d{13}		30%
\d{9}		20%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
1234567890123	→ 4957065550289

7.6 Given names

MX_L1_NOMBRE

ESSENTIAL COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

First and middle names (NOMBRES , PRIMER_NOMBRE), including compound names such as María Guadalupe or José Luis .

HOW IT IS FOUND

COLUMN NAME	MX_L1_NOMBRE – Path
85%	primer_?nombre segundo_?nombre nombres?_?(de_?)?pila nombre_?social first_?name given_?names? fname name_?first middle_?name nombre[12] nombres (except when followed by list E1) nom_?(pila trab emp)
50%	nombre (except when followed by list E2) nomb? (except when followed by list E3) name (except when followed by list E4)

KNOWN VALUES MX_L1_NOMBRE - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-nombres.txt	301	70%	María, Maria, José, Jose, Juan, Luis

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each word is replaced by a Mexican given name from a list of 255, keeping the number of words and the case.

More than three words are masked character by character.

MX_NOMBRES **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_NOMBRE_PILA **NAME**

Replaces the name with one of the 255 names in mx-nombres.txt .

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
María Guadalupe	→	Gloria Pedro
JOSÉ LUIS	→	ROSARIO RODOLFO

7.7 Surnames

MX_L1_APELLIDO

ESSENTIAL **COLUMN NAME** **KNOWN VALUES** **REGEX DECOMPOSE**

WHAT IT IS

Paternal and maternal surnames, in one column or two.

HOW IT IS FOUND

COLUMN NAME MX_L1_APELLIDO - Path

85% apellidos? apellido?(paterno|materno|pat|mat|uno|dos|[12]) ape?(pat|mat|paterno|materno|[12]) apeat apemat appat apmat ap?(pat|mat|paterno|materno) a?paterno a?materno paterno materno primer_apellido segundo_apellido last_name surname lname family_name second_last_name mother_last_name

KNOWN VALUES MX_L1_APELLIDO - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-apellidos.txt	423	70%	Hernández, Hernandez, García, Garcia, Martínez, Martinez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each word is replaced by one of the 337 most frequent Mexican surnames, keeping the number of words and the case.

MX_APELLIDOS **REGEX DECOMPOSE**

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_APELLIDO **NAME**

Replaces the name with one of the 337 names in mx-apellidos.txt .

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

Hernández López

MASKED

→

Lozano Salazar

7.8 Full name

MX_L1_NOMBRE_COMPLETO

ESSENTIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Given names and both surnames in one column, in Mexican order, or as `SURNAMES`, `NAMES`. Also the name of a titular, beneficiary, insured person or invoice receiver.

HOW IT IS FOUND

COLUMN NAME MX_L1_NOMBRE_COMPLETO - Path

90%	<code>nombre_?(completo compl full)</code> <code>nombres?_?y_?apellidos?</code> <code>nombres?_?apellidos?</code> <code>nombreakellido</code> <code>nom_?completo</code> <code>nomcompleto</code> <code>nombrecompleto</code> <code>full_?name</code> <code>fullname</code> <code>person_?</code> <code>name</code> <code>customer_?name</code> <code>employee_?name</code> <code>patient_?name</code> <code>nombre_?</code> <code>(cliente cte cli paciente pac trabajador trab empleado colaborador alumno estudiante afiliado </code> <code>asegurado derechohabiente beneficiario benef titular madre padre tutor conyuge pareja medico d</code> <code>otor profesional responsable contacto emergencia aval obligado coacreditado deudor acreditado</code> <code> remitente destinatario receptor firmante testigo representante apoderado propietario arrendat</code> <code>ario contratante victima denunciante imputado socio donante heredero persona pers conductor ch</code> <code>ofer vendedor ejecutivo agente solicitante usuario_?</code> <code>final ciudadano elector votante contribuyente jefe_?(de_)?</code> <code>familia hijo hija familiar dependiente)</code> <code>nombre_?razon_?social_?receptor</code>
60%	<code>titular</code> <code>beneficiario</code> <code>contacto_?emergencia</code> <code>conyuge</code> <code>tutor_?legal</code> <code>representante_?legal</code> <code>apoderado_?legal</code> <code>paciente</code> <code>victima</code> <code>asegurado</code> <code>contratante</code> <code>derechohabiente</code> <code>acreditado</code> <code>obligado_?solidario</code> <code>aval</code>
50%	<code>nombre</code> (except when followed by list E2) <code>name</code> (except when followed by list E4)

KNOWN VALUES MX_L1_NOMBRE_COMPLETO - List

LIST	VALUES	STRENGTH	FIRST VALUES
<code>mx-detectar-nombres.txt</code>	301	60%	María, Maria, José, Jose, Juan, Luis
<code>mx-detectar-apellidos.txt</code>	423	60%	Hernández, Hernandez, García, Garcia, Martínez, Martinez

Values are split into words, and each word is looked up.

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Given names become given names and surnames become surnames, by position: one word is a name, two are name and surname, three are name and two surnames, four are two names and two surnames. A comma separates surnames from names.

MX_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

MX_APELLIDOS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_APELLIDO NAME

Replaces the name with one of the 337 names in mx-apellidos.txt .

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_NOMBRE_PILA NAME

Replaces the name with one of the 255 names in mx-nombres.txt .

EXAMPLES

VALUE		MASKED
María Guadalupe Hernández López	→	Gloria Pedro Lozano Salazar
HERNÁNDEZ LÓPEZ, JUAN CARLOS	→	LOZANO SALAZAR, CECILIA GERARDO

7.9 E-mail

MX_L1_EMAIL

ESSENTIAL

COLUMN NAME

DATA TYPE

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Personal and work e-mail addresses.

HOW IT IS FOUND

COLUMN NAME

MX_L1_EMAIL - Path

85%

e_?mail[a-z0-9]* mail[a-z0-9]* correo(?:electronico)?[a-z0-9]* email_?address
correo_?(personal|laboral|contacto|receptor|cliente)

DATA TYPE

MX_L1_EMAIL - Type

Accepts text (length 5 or more); any other type rules the domain out.

VALUE FORMAT

MX_L1_EMAIL - Regex

PATTERN

[A-Za-z0-9._%+'\"-]+@[A-Za-z0-9.\-]+\.[A-Za-z]{2,24}

STRENGTH

100%

NOTES

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

The name and domain are mapped character by character and the top-level domain becomes .test , reserved for tests: a masked address can never receive mail.

MX_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
guadalupe.hernandez@gmail.com	→	koepupoqe.vadvamdul@pgoeb.test

7.10 Phone number

MX_L1_TELEFONO

- ESSENTIAL
- COLUMN NAME
- VALUE FORMAT
- REGEX DECOMPOSE

WHAT IT IS

Landlines and mobiles. Since August 2019 every Mexican number has 10 digits: a 2-digit area code for Mexico City, Guadalajara and Monterrey (55, 56, 33, 81), 3 digits elsewhere.

HOW IT IS FOUND

COLUMN NAME

MX_L1_TELEFONO - Path

85%

tel telefono[a-z0-9]* tel[eé]fono tel_?
(cel|casa|particular|oficina|trabajo|movil|contacto|fijo|recados) celular[a-z0-9]* cel
movil m[oó]vil whatsapp wa fax phone[a-z0-9]* mobile cellphone n(o|um|ro)?
tel(efono)? telef tlf lada extension

VALUE FORMAT

MX_L1_TELEFONO - Regex

PATTERN	STRENGTH	NOTES
(\+?52[\s-]?)?(1[\s-]?)?\((? (55 56 33 81)\)[\s-]?[d{4}[\s-]?[d{4}	90%	
(\+?52[\s-]?)?(1[\s-]?)?\((?[2-9]\d{2}\)[\s-]?[d{3}[\s-]?[d{4}	80%	
\+?\d[\d\s()\-]{7,15}	30%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The subscriber digits are masked; +52 , the old mobile 1 , the area code and the separators stay. A number that does not have the shape of a Mexican number is masked digit by digit.

MX_TELEFONO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
+52 55 1234 5678	→	+52 55 9707 7565
(222) 123 4567	→	(222) 957 9910

7.11 Address

MX_L1_DIRECCION

- ESSENTIAL
- COLUMN NAME
- DATA TYPE
- VALUE FORMAT
- SECURE LOOKUP

WHAT IT IS

The street line of an address: street, exterior and interior number, or block and lot (Mz. 12 Lt. 5).

HOW IT IS FOUND

COLUMN NAME MX_L1_DIRECCION - Path

80% direccion[a-z]* (except when followed by list E5) direcci[oó]n dir domicilio[a-z]* (except when followed by fiscal) calle(_?y?numero)? avenida address (except when preceded by mac, ip, e?mail, web, url) street addr (except when preceded by mac, ip, e?mail, web, url) dir_? (particular|comercial|laboral|envio|entrega|facturacion|cliente|paciente|trabajo) entre_? calles y?calle residencia lugar?(de_)?residencia home?address

DATA TYPE MX_L1_DIRECCION - Type

Accepts text (length 6 or more); any other type rules the domain out.

VALUE FORMAT MX_L1_DIRECCION - Regex

PATTERN	STRENGTH	NOTES
(?i)(av(enida)?\.? calle c\. privada priv\.? andador cerrada calzada calz\.? blvd\.? boulevard bulevar prolongaci[oó]n prol\.? carretera camino circuito retorno)\s+.\d+.*	80%	
[A-Za-zÁÉÍÓÚÑáéíóúñ'\.]{4,}\s(# no\.?\s)?\d{1,5}(\s*(int interior depto dpto local)\.?\s*\w+)?	40%	
(?i).\s(mz mza manzana)\.?\s*\d+\s*(lt lte lote)\.?\s*\d+	70%	

A value that matches none counts 20% against the domain.

HOW IT IS MASKED

Replaced by one of 3,000 fictitious Mexican addresses on common street names, with interior numbers and blocks and lots in realistic proportions.

MX_DIRECCION **SECURE LOOKUP**

Replaces the value with one of the 3,000 values in mx-direcciones.txt, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Av. Insurgentes Sur 1602 Int. 4	→ Calle Abasolo 7005

7.12 Address details

MX_L1_DIRECCION_COMPLEMENTO

ESSENTIAL **COLUMN NAME** **CHARACTER MAPPING**

WHAT IT IS

Exterior and interior numbers, block, lot, building or tower kept in their own columns.

HOW IT IS FOUND

COLUMN NAME MX_L1_DIRECCION_COMPLEMENTO - Path

70% n(o|um|ro|umero)?(ext|exterior|int|interior) num?ext num?int no?ext no?int numext numint exterior interior depto dpto manzana mza mz lote lt lte edificio torre casa?(num|no|numero) house?number apartment apt unit?number

HOW IT IS MASKED

Character by character, keeping length and format.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
Mz 12 Lt 5	→ Jj 37 Jp 7

7.13 CLABE

MX_L1_CLABE

COLUMN NAME DATA TYPE VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

The 18-digit standardized bank key: bank (3), plaza (3), account (11) and check digit. Used in every SPEI transfer and payroll deposit.

HOW IT IS FOUND

COLUMN NAME

MX_L1_CLABE – Path

90%

clabe[a-z0-9]*

cta_?clabe

cuenta_?clabe

clabe_?interbancaria

clave_?bancaria_?

estandarizada

cuenta_?interbancaria

clabe_?

(deposito|pago|cliente|beneficiario|trab|nomina)

DATA TYPE

MX_L1_CLABE – Type

Accepts text (length 18 or more) or number (length 18 or more); any other type rules the domain out.

VALUE FORMAT

MX_L1_CLABE – Regex

PATTERN	STRENGTH	NOTES
\d{18}		70%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The bank code stays, so reports by bank still add up; plaza and account are masked and the check digit (weights 3, 7, 1, modulo 10) recomputed. Every masked CLABE is valid and the mapping is one-to-one.

MX CLABE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

MX_CLABE_VALIDA CHECK DIGIT

Masks the digits with **MX_CLABE_CUERPO** and recomputes a modulus 10 check digit with weights 3 7 1 3 7 1 3 7 1 3 7 1 3 7 1 3 7.

MX_CLABE_CUERPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
002180700545678911	→	002141726834346236

7.14 Bank account

MX L1 CUENTA BANCARIA

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Account numbers other than the CLABE: checking, savings, payroll.

HOW IT IS FOUND

COLUMN NAME	MX_L1_CUENTA_BANCARIA – Path
85%	cuenta_? (bancaria banco cheques ahorro deposito abono pago destino origen nomina debito inversion) cta_?(bancaria banco cheques ahorro nomina) n(o um ro umero)?_(de_)?cuenta(_? (banco bancaria cheques nomina))? account_?(number no num nbr) bank_?account num_?cta no_?cta

HOW IT IS MASKED

Character by character, keeping length and format.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
0123456789	→ 8947251356

7.15 Payment card

MX_L1_TARJETA

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Credit and debit card numbers.

HOW IT IS FOUND

COLUMN NAME

MX_L1_TARJETA - Path

85%

tarjeta(_?(credito|debito|cred|deb|num|no|numero|bancaria))?

n(o|um|ro|umero)?tarjeta

pan

card_?(number|no|num)

credit_?card

cc_?(number|num)

tdc

tdd

num_?tdc

plastico

VALUE FORMAT

MX_L1_TARJETA - Regex

PATTERN	STRENGTH	NOTES
\d{13,19}	90%	LUHN check digit; after removing [\s\-]

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another card number that still passes the Luhn check. Values that do not look like a card pass unchanged instead of failing the row.

MX_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

MX_TARJETA_LUHN PAYMENT CARD
Replaces the card number with another that passes the Luhn check.

EXAMPLES

VALUE	MASKED
4152 3131 2345 6780	→ 1544 7874 9862 8904

7.16 Passport

MX_L1_PASAPORTE

ESSENTIAL COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

Mexican and foreign passport numbers.

HOW IT IS FOUND

COLUMN NAME MX_L1_PASAPORTE - Path

85% pasaporte[a-z]* passport[a-z]* n(o|um|ro|umero)?pasaporte pasap

VALUE FORMAT MX_L1_PASAPORTE - Regex

PATTERN	STRENGTH	NOTES
[A-Z]\d{8}		30%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length and format.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
G12345678	→ G27909346

7.17 Immigration document

MX_L1_DOCUMENTO_MIGRATORIO

COLUMN NAME CHARACTER MAPPING

WHAT IT IS

Temporary and permanent resident cards, immigration forms, visas and foreign identity numbers.

HOW IT IS FOUND

COLUMN NAME MX_L1_DOCUMENTO_MIGRATORIO - Path

80% tarjeta?(de_)?residente residente?(temporal|permanente) documento?migratorio doc?
migratorio forma?migratoria fm?[23] fmm n(o|um|ro)?(documento)?migratorio id?
extranjero documento?extranjero identificacion?extranjera dni visa n(o|um|ro)?visa
national?id

HOW IT IS MASKED

Character by character, keeping length and format.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
123456789	→ 110858568

7.18 Professional license

MX_L1_CEDULA_PROFESIONAL

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The number of the cédula profesional issued by the SEP. The registry is public: the number leads straight to the person's name.

HOW IT IS FOUND

COLUMN NAME	MX_L1_CEDULA_PROFESIONAL - Path		
85%	cedula_?profesional	ced_?prof	cedula_?(prof medica especialidad) n(o um ro)_?cedula cedula
VALUE FORMAT	MX_L1_CEDULA_PROFESIONAL - Regex		
PATTERN	STRENGTH		NOTES
\d{7,8}			30%
A value that matches none counts 30% against the domain.			

HOW IT IS MASKED

Character by character, keeping length.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED	
12345678	→	46916122

7.19 Driver's license

MX_L1_LICENCIA_CONducIR

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

State and federal driver's license numbers.

HOW IT IS FOUND

COLUMN NAME	MX_L1_LICENCIA_CONducIR - Path		
80%	licencia_?(de_?)(conducir manejo chofer automovilista motociclista federal)	n(o um ro)_?	
	licencia	licencia	driver_?license drivers_?license

HOW IT IS MASKED

Character by character, keeping length and format.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED	
A12345678	→	A67558943

7.20 e.firma certificate

MX_L1_EFIRMA

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The 20-digit serial number of an e.firma (FIEL) or digital seal certificate issued by the SAT.

HOW IT IS FOUND

COLUMN NAME MX_L1_EFIRMA - Path

85% e_?firma efirma fiel firma_?electronica(_?avanzada)? n(o|um|ro)_?certificado(_?
(sat|fiel|efirma|csd))? certificado_?(sat|fiel|efirma|digital) no_?certificado serial_?
certificado csd

VALUE FORMAT MX_L1_EFIRMA - Regex

PATTERN	STRENGTH	NOTES
0000[0-9]{16}		80%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping length.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
00001000000504465028	→ 24028511323899248367

7.21 IP address

MX_L1_IP

COLUMN NAME **VALUE FORMAT** **REGEX DECOMPOSE**

WHAT IT IS

IPv4 and IPv6 addresses of users and devices.

HOW IT IS FOUND

COLUMN NAME MX_L1_IP - Path

85% ip ip_
(address|addr|origen|destino|cliente|usuario|remota|publica|privada|acceso|conexion|login)
direccion_?ip dir_?ip ipv[46] remote_?addr client_?ip host_?ip

VALUE FORMAT MX_L1_IP - Regex

PATTERN	STRENGTH	NOTES
((25[0-5] 2[0-4]\d 1?\d?\d)\.){3}(25[0-5] 2[0-4]\d 1?\d?\d)	100%	
[0-9A-Fa-f]{1,4}(:[0-9A-Fa-f]{0,4}){2,7}	90%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Each IPv4 octet is mapped to a number from 1 to 254; an IPv6 address is mapped as hexadecimal.

MX_IP **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_HEX` .

`MX_OCTETO` **NUMERIC MAPPING**

Maps the number to another between 1 and 254.

`MX_CM_HEX` **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
189.203.4.10	→	160.148.8.16

7.22 Device identifier

MX_L1_DISPOSITIVO

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

IMEI, MAC address, advertising and session identifiers, device serial numbers.

HOW IT IS FOUND

COLUMN NAME MX_L1_DISPOSITIVO – Path

80% imei imsi iccid mac mac?address direccion?mac device?id id?dispositivo
dispositivo?id uuid?dispositivo advertising?id idfa gaid cookie(?id)? session?
id id?sesion serie?equipo n(o|um|ro)?serie?(equipo|celular|telefono)

VALUE FORMAT MX_L1_DISPOSITIVO – Regex

PATTERN	STRENGTH	NOTES
([0-9A-Fa-f]{2}[:\-]){5}[0-9A-Fa-f]{2}	100%	
\d{15}	80%	LUHN check digit

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Hexadecimal stays hexadecimal and digits stay digits, so the value keeps its format.

`MX_CM_HEX` **CHARACTER MAPPING**

Maps each character to another of its group (5 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
3c:22:fb:9a:10:e4	→	5e:83:bb:3c:31:f9

7.23 License plate

MX_L1_PLACA

COLUMN NAME VALUE FORMAT CHARACTER MAPPING

WHAT IT IS

Vehicle plates in the formats of NOM-001-SCT-2-2016 (URU-197-A), Mexico City (A-12-BCD) and older series.

HOW IT IS FOUND

COLUMN NAME

MX_L1_PLACA – Path

85%

placas?(_(vehiculo|auto|circulacion|vehicular|num|no|numero))?

n(o|um|ro)_?placas?

matricula(_(vehiculo|auto|vehicular))?

license_?plate

plate(_?number)?

tarjeta?(de_)?

circulacion

VALUE FORMAT

MX_L1_PLACA – Regex

PATTERN	STRENGTH	NOTES
[ABCDEFGHJKLMNPRSTUVWXYZ]{3}[\s-]?d{3}[\s-]?[ABCDEFGHJKLMNPRSTUVWXYZ]	100%	
[ABCDEFGHJKLMNPRSTUVWXYZ][\s-]?d{2}[\s-]?[ABCDEFGHJKLMNPRSTUVWXYZ]{3}	80%	
[ABCDEFGHJKLMNPRSTUVWXYZ]{3}[\s-]?d{2}[\s-]?d{2}	80%	
d{3}[\s-]?[ABCDEFGHJKLMNPRSTUVWXYZ]{3}	60%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Letters map among the letters plates use — never **I**, **0** or **Q** — and digits among digits: the masked plate is still a valid plate. The state series is not preserved.

MX_PLACA CHARACTER MAPPING

Maps each character to another of its group (3 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
URU-197-A	→ SGK-611-T

7.24 Vehicle identification number

MX_L1_NIV

COLUMN NAME

VALUE FORMAT

CHARACTER MAPPING

WHAT IT IS

The NIV (VIN), engine and chassis numbers and the REPUVE registration.

HOW IT IS FOUND

COLUMN NAME

MX_L1_NIV – Path

80%

niv

vin

n(o|um|ro|umero)_?(de_)?(serie|identificacion)_?(vehicular|vehiculo)

serie?

vehicul(o|ar)

n(o|um|ro)_?serie

numero_?serie

n(o|um|ro)_?motor

chasis

repuve

folio?

repuve

constancia_?repuve

vin_?number

VALUE FORMAT

MX_L1_NIV – Regex

HOW IT IS MASKED

Character by character, keeping length and format. The check digit of North American VINs is not recomputed.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

3VWFE21C04M000001

→

7VVCU97M86J091175

7.25 Contract and customer numbers

MX_L1_NUMERO_CONTRATO

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Contract, policy, credit, customer, member, employee and payroll numbers — internal keys that lead to a person in the source system.

HOW IT IS FOUND

COLUMN NAME

MX_L1_NUMERO_CONTRATO – Path

70%

```
contrato  n(o|u|m|r|o|u|m|e|r|o)_?contrato  p[ó]liza  n(o|u|m|r|o|u|m|e|r|o)_?poliza  n(o|u|m|r|o)_?
(de_)?credito(_?(infonavit|fovissste))?  credito_?(infonavit|fovissste)  n(o|u|m|r|o)_?
operacion  n(o|u|m|r|o|u|m|e|r|o)_?(de_)?socio  n(o|u|m|r|o|u|m|e|r|o)_?(de_)?cliente  id_?cliente
cve_?cliente  clave_?cliente  n(o|u|m|r|o|u|m|e|r|o)_?(de_)?empleado  num_?emp  no_?emp
n(o|u|m|r|o)_?nomina  n(o|u|m|r|o)_?afiliado  n(o|u|m|r|o)_?sinistro  n(o|u|m|r|o)_?(de_)?
matricula  matricula_?(alumno|estudiante)  n(o|u|m|r|o)_?expediente_?
(cliente|laboral|personal)  folio_?(contrato|poliza|credito|cliente)
```

HOW IT IS MASKED

Character by character, keeping length and format, so the same number masks the same way in every table.

MX_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

POL-123456

→

MIF-194239

7.26 Username and social media

MX_L1_USUARIO_RRSS

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Usernames, logins, aliases and social media handles.

HOW IT IS FOUND

COLUMN NAME

MX_L1_USUARIO_RRSS – Path

70%

```
usuario  username  user_?name  login  nick(name)?  alias  cuenta_?usuario  usr  facebook
instagram  twitter  tiktok  linkedin  red_?social  perfil_?
(facebook|instagram|twitter|linkedin|tiktok)  telegram  handle
```

HOW IT IS MASKED

Character by character, keeping length and format.

MX_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
@lupita_hdz	→	@numaje_hws

7.27 Credentials

MX_L1_CREDENTIAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Passwords and their hashes, PINs, tokens, API keys, the SAT CIEC password and security questions.

HOW IT IS FOUND

COLUMN NAME	MX_L1_CREDENTIAL – Path
90%	password passwd pwd pass contrasen[aa] contraseña clave[a-z]* <i>(except when followed by list E6)</i> pin nip ciec contrasena?(sat efirma fiel) hash_?password password_?hash secret token_?acceso access_?token refresh_?token api_?key otp respuesta_?secreta pregunta_? secreta

HOW IT IS MASKED

Every character becomes X . A credential has no place in a test environment.

MX_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
Secreta#2024	→	XXXXXXXXXXXX

7.28 Geolocation

MX_L1_GEOLOCALIZACION

COLUMN NAME VALUE FORMAT REGEX DECOMPOSE

WHAT IT IS

Latitude and longitude of homes, deliveries or devices.

HOW IT IS FOUND

COLUMN NAME	MX_L1_GEOLOCALIZACION – Path
85%	lat latitud latitude lon lng longitude coordenadas? coord_?[xy] geo_? (lat lon lng loc localizacion posicion) geolocalizacion ubicacion_?gps gps posicion_? gps
50%	longitud long

VALUE FORMAT MX_L1_GEOLOCALIZACION - Regex

PATTERN	STRENGTH	NOTES
(1[4-9] 2\d 3[0-3])\.\d{3,}\s*,\s*-(8[6-9] 9\d 1[01]\d)\.\d{3,}	90%	
(1[4-9] 2\d 3[0-3])\.\d{3,}	60%	
-(8[6-9] 9\d 1[01]\d)\.\d{3,}	70%	

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The integer part and first decimal stay — about 11 km — and the rest is masked: the place is generalized, not moved to another region.

MX_COORDENADA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
19.432608,-99.133209	→ 19.463593,-99.198278

7.29 Free text

MX_L1_TEXTO_LIBRE

COLUMN NAME **DATA TYPE** **VALUE FORMAT** **FREE TEXT REDACTION**

WHAT IT IS

Observations, comments, complaints, address references and notes where people write identifiers in the middle of a sentence.

HOW IT IS FOUND

COLUMN NAME MX_L1_TEXTO_LIBRE - Path

60% observaciones? obs comentarios? notas? detalle descripcion?
(caso|queja|reclamo|incidente|solicitud|problema|atencion|hechos) texto_?libre mensaje
queja reclamo referencias?(?domicilio)? motivo?(texto|detalle) narrativa relato
resumen?caso remarks comments? notes? free_?text memo bitacora

DATA TYPE MX_L1_TEXTO_LIBRE - Type

Accepts text (length 30 or more); any other type rules the domain out.

VALUE FORMAT MX_L1_TEXTO_LIBRE - Regex

PATTERN	STRENGTH	NOTES
[A-Z]{4}\d{6}[HMX][A-Z]{5}[0-9A-Z]\d	70%	anywhere in the value
[\w.+\\-]+@[\\w\\-]+\\. [A-Za-z]{2,}	70%	anywhere in the value
[A-ZÑ&]{4}\d{6}[A-Z0-9]{3}	60%	anywhere in the value
(\\+?52\\s?)?\\d{2,3}\\s?\\d{3,4}\\s?\\d{4}	50%	anywhere in the value

A value that matches none does not count against the domain.

HOW IT IS MASKED

CURPs, RFCs, INE voter keys, e-mails, 10-digit phones, NSS, card and CLABE numbers, plates and IPs are replaced by [DAT0] ; given names and surnames from the lists by [NOMBRE] .

MX_TEXT0_LIBRE **FREE TEXT REDACTION**

Replaces the text matching 9 patterns with `[DAT0]` , and the 1,436 terms of `mx-texto-nombres.txt` with `[NOMBRE]` .

EXAMPLES

VALUE		MASKED
Cliente Hernández, CURP HEGA850720MDFRRL04, correo g.hernandez@gmail.com, tel 5512345678.	→	Cliente [NOMBRE], CURP [DAT0], correo [DAT0], tel [DAT0].

Quasi-identifiers

Data that identify no one alone but do in combination. Mexico has 2,469 municipalities, and 1,505 of them had fewer than 20,000 inhabitants in 2020: a birth date, a sex and one of those municipalities point to a handful of people. These attributes are generalized or shifted rather than replaced, so the data keep their analytical value.

8.1 Birth date

MX_L2_FECHA_NACIMIENTO

ESSENTIAL COLUMN NAME DATA TYPE DATE SHIFT

WHAT IT IS

The strongest quasi-identifier: with sex and municipality it singles out most people.

HOW IT IS FOUND

COLUMN NAME MX_L2_FECHA_NACIMIENTO - Path

90% fecha?(de_)?nac(imiento)? fec?nac(imiento)? fch?nac f?nac(imiento|im)? fnac
fechanac(imiento)? fecnac nacimiento dob birth_date date_of_birth birthdate
birthday cumplean|ños

DATA TYPE MX_L2_FECHA_NACIMIENTO - Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 60 days, the same way in every table for the same date.

MX_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

EXAMPLES

VALUE		MASKED
1985-07-20	→	1985-08-05T00:00

8.2 Birth year

MX_L2_ANIO_NACIMIENTO

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

The year of birth stored on its own.

HOW IT IS FOUND

COLUMN NAME MX_L2_ANIO_NACIMIENTO - Path

90% an(i)?o?(de_)?nac(imiento)? año?(de_)?nac(imiento)? birth_year year_of_birth
ano_nacim

DATA TYPE MX_L2_ANIO_NACIMIENTO - Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the last digit is masked — with the same mapping as the year inside a CURP, RFC or voter key.

MX_ANIO **REGEX DECOMPOSE**

Matches one pattern and gives each part of the value its own action; when none matches: keep.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
1985	→	1980

8.3

Age

MX_L2_EDAD

COLUMN NAME **DATA TYPE** **REGEX DECOMPOSE**

WHAT IT IS

Age in years.

HOW IT IS FOUND

COLUMN NAME MX_L2_EDAD – Path

85% edad(_?

(actual|paciente|cliente|afiliado|asegurado|derechohabiente|beneficiario|ingreso|anos|años|cumplida))? age anos_?cumplidos rango_?(de_)?edad grupo_?(de_)?edad edad_?en_?anos

DATA TYPE MX_L2_EDAD – Type

Accepts number (length up to 6) or text (length up to 6); any other type rules the domain out.

HOW IT IS MASKED

The decade stays and the unit is masked (37 → 3x); 100 and over becomes 90, because very old ages are rare enough to identify.

MX_EDAD **REGEX DECOMPOSE**

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
37	→	35
104	→	90

8.4

Life event dates

MX_L2_FECHA_EVENTO

COLUMN NAME **DATA TYPE** **DATE SHIFT**

WHAT IT IS

Dates of death, marriage, hiring and dismissal, IMSS registration, disability leave, hospitalization, diagnosis, childbirth, arrest.

HOW IT IS FOUND

COLUMN NAME MX_L2_FECHA_EVENTO – Path

80% fecha_?(de_)?(defuncion|fallecimiento|muerte|matrimonio|divorcio|ingreso|alta_?
(imss|patronal|laboral)|baja(_?(imss|laboral)))?
|contratacion|contrato|egreso|despido|renuncia|jubilacion|pension|incapacidad|hospitalizacion|
alta_?
medica|diagnostico|atencion|consulta|parto|embarazo|detencion|sentencia|vacunacion|cirugia|est
udio|reingreso|antiguedad) fec_?
(defuncion|ingreso|alta|baja|egreso|contrato|atencion|diagnostico|incapacidad) fch_?
(ingreso|alta|baja|egreso) death_?date hire_?date termination_?date date_?of_?death
admission_?date discharge_?date

DATA TYPE MX_L2_FECHA_EVENTO – Type

Accepts date, TIMESTAMP or text (length 6 or more); any other type rules the domain out.

HOW IT IS MASKED

Shifted up to 30 days.

MX_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

EXAMPLES

VALUE

MASKED

2021-03-15

→

2021-03-05T00:00

8.5 Sex

MX_L2_SEX0

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Sex or gender as recorded: H / M , F / M , Hombre / Mujer , Masculino / Femenino .

HOW IT IS FOUND

COLUMN NAME MX_L2_SEX0 – Path

85% sexo(_?(biologico|registral|paciente|cliente|asegurado|trabajador))? sex g[eé]nero (except
when followed by *identidad* , *social* , *autopercebido*) gender cve_?sexo cod_?sexo

KNOWN VALUES MX_L2_SEX0 – List

LIST

VALUES

STRENGTH

FIRST VALUES

mx-detectar-sexo.txt

12

50%

h, m, f, x, hombre, mujer

A value that matches none counts 50% against the domain.

HOW IT IS MASKED

Replaced within its own vocabulary. H / M uses the same lookup as the sex inside a CURP or voter key, so the three stay consistent.

MX_SEX0 REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_SEX0_PALABRA SECURE LOOKUP

Replaces the value with one of the 2 values in mx-sexo-palabra.txt , chosen by a keyed hash.

MX_SEX0_MUJER_HOMBRE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-sexo-mujer-hombre.txt`, chosen by a keyed hash.

MX_SEX0_INGLES **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-sexo-ingles.txt`, chosen by a keyed hash.

MX_SEX0_H_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-sexo-h-m.txt`, chosen by a keyed hash.

MX_SEX0_F_M **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-sexo-f-m.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
M	→	H
Masculino	→	Femenino

8.6 Municipality

MX_L2_MUNICIPIO

COLUMN NAME

KNOWN VALUES

DATA CLEANSING

WHAT IT IS

Municipality or Mexico City borough. 1,505 of the 2,469 municipalities had fewer than 20,000 inhabitants in the 2020 census.

HOW IT IS FOUND

COLUMN NAME

MX_L2_MUNICIPIO - Path

85%

`municipio[a-z]* nom(bre)??(mun|mpio|municipio) mpio mun d?mpio mpio alcaldia delegacion (except when followed by list E7) demarcacion(_?territorial)? municipio? (residencia|nacimiento|domicilio)`

60%

`ciudad[a-z]* city town d?ciudad`

KNOWN VALUES

MX_L2_MUNICIPIO - List

LIST

VALUES

STRENGTH

FIRST VALUES

mx-detectar-municipios.txt	3,090	90%	Aguascalientes, Asientos, Calvillo, Cosío, Cosio, Jesús María
----------------------------	-------	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A municipality under 20,000 inhabitants becomes the nearest municipality of the same state that has at least 20,000; larger ones stay. The result is a real, nearby municipality. Names without accents and in capitals are recognized. A name shared by several municipalities is generalized only when all of them are small.

MX_MUNICIPIO **DATA CLEANSING**

Replaces each value found in `mx-municipio-generalizado.txt` (6,547 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE		MASKED
Santa María Tlahuitoltepec	→	Santa Lucía del Camino
Guadalajara	→	Guadalajara

COLUMN NAME DATA TYPE KNOWN VALUES DATA CLEANSING

WHAT IT IS

The 5-digit INEGI geostatistical code of a municipality (state + municipality), with or without the leading zero.

HOW IT IS FOUND

COLUMN NAME MX_L2_CLAVE_MUNICIPIO - Path

85% cve_?(geo|mun|mpio|municipio|inegi) clave_?(geo(estadistica)?|mun|mpio|municipio|inegi)(_?(inegi|municipal))? cod(igo)??(mun|mpio|municipio|inegi) id_?(mun|mpio|municipio) c_? mnpio municipio_?(cve|clave|id|cod|inegi) cvegeo

DATA TYPE MX_L2_CLAVE_MUNICIPIO - Type

Accepts number (length up to 5) or text (length up to 5); any other type rules the domain out.

KNOWN VALUES MX_L2_CLAVE_MUNICIPIO - List			
LIST	VALUES	STRENGTH	FIRST VALUES
mx-detector-clave-municipio.txt	2,758	50%	01001, 1001, 01002, 1002, 01003, 1003

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Generalized exactly like the municipality name, without the ambiguity of homonyms.

MX_CLAVE_MUNICIPIO DATA CLEANSING

Replaces each value found in mx-clave-municipio-generalizada.txt (2,758 pairs) by its counterpart; values not in the file stay as they are.

EXAMPLES

VALUE	MASKED
20426	→ 20006

COLUMN NAME SECURE LOOKUP

WHAT IT IS

Locality, town, ejido, rancho or community — often a few hundred inhabitants — and place of birth.

HOW IT IS FOUND

COLUMN NAME MX_L2_LOCALIDAD - Path

80% localidad[a-z]* nom(bre)?_?loc(alidad)? poblado ranch[oe]ria ejido comunidad (except when followed by indigena, religiosa) pueblo_?(residencia|origen) lugar_?(de_)?nacimiento origen_?(localidad|poblacion)

HOW IT IS MASKED

Replaced by the name of a municipality of over 100,000 inhabitants: still a place, no longer theirs.

MX_LOCALIDAD SECURE LOOKUP

Replaces the value with one of the 229 values in mx-localidades.txt, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

San Isidro Buenavista

→

Cuautla

8.9 Colonia

MX_L2_COLONIA

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

Colonia, fraccionamiento, barrio or housing unit: with the postal code, it narrows an address down to a few blocks.

HOW IT IS FOUND

COLUMN NAME

MX_L2_COLONIA – Path

85%

colonia[a-z]* nom(bre)?_?colonia fraccionamiento fracc barrio asentamiento d_?asenta nom_?asentamiento tipo_?asentamiento unidad_?habitacional conjunto_?habitacional ageb manzana_?inegi

HOW IT IS MASKED

Replaced by a common colonia name (Centro , Del Valle , Las Flores).

MX_COLONIA SECURE LOOKUP

Replaces the value with one of the 60 values in mx-colonias.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Santa María la Ribera

→

Las Flores

8.10 Postal code

MX_L2_CODIGO_POSTAL

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Five digits: the first two are the state or Mexico City borough. Also the fiscal address of CFDI invoices.

HOW IT IS FOUND

COLUMN NAME

MX_L2_CODIGO_POSTAL – Path

90%

cod(igo)?_?postal cp c_?p zip(_?code)? postal_?code codpostal d_?codigo domicilio_?fiscal(_?receptor)? lugar_?expedicion cp_?(fiscal|domicilio|receptor|emisor)

VALUE FORMAT

MX_L2_CODIGO_POSTAL – Regex

PATTERN

STRENGTH

NOTES

\d{5}

20%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

The first three digits stay and the last two become 00 (06760 → 06700).

MX_CODIGO_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

06760

→

06700

8.11 Nationality

MX_L2_NACIONALIDAD

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Nationality or country of birth. A foreign nationality is rare in most tables, and rarity identifies.

HOW IT IS FOUND

COLUMN NAME

MX_L2_NACIONALIDAD - Path

80%

nacionalidad nationality pais_?(de_)?(nacimiento|origen) ciudadania citizenship
country_of_birth extranjero

KNOWN VALUES

MX_L2_NACIONALIDAD - List

LIST

VALUES

STRENGTH

FIRST VALUES

mx-detectar-

64

70%

nacionalidades.txt

Mexicana, Estadounidense, Guatemalteca, Hondureña, Hondurena, Salvadoreña

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a nationality from a list of the most frequent in Mexico.

MX_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 20 values in mx-nacionalidades.txt, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Guatemalteca

→

Hondureña

8.12 Marital status

MX_L2_ESTADO_CIVIL

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Single, married, free union, separated, divorced, widowed.

HOW IT IS FOUND

COLUMN NAME

MX_L2_ESTADO_CIVIL - Path

85%

estado_civil edo_civil est_civil ecivil situacion_conyugal marital_status
civil_status

KNOWN VALUES MX_L2_ESTADO_CIVIL – List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-estado-civil.txt	19	70%	soltero, soltera, casado, casada, unión libre, union libre

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another marital status.

MX_ESTADO_CIVIL **SECURE LOOKUP**

Replaces the value with one of the 6 values in `mx-estado-civil.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Unión libre	→ Divorciado

8.13 Occupation

MX_L2_OCUPACION

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

Occupation, profession or position. A rare position identifies on its own.

HOW IT IS FOUND

COLUMN NAME MX_L2_OCUPACION – Path

80% ocupaci[oó]n profes[ió]n oficio puesto(_?(trabajo|laboral|actual))? (except when followed by votacion, venta, trabajo_?id) cargo (except when followed by list E8) job_?title occupation actividad_?(laboral|economica_?persona) categoria_?laboral

HOW IT IS MASKED

Replaced by one of 40 common occupations.

MX_OCUPACION **SECURE LOOKUP**

Replaces the value with one of the 40 values in `mx-ocupaciones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Gerente Regional Zona Sierra Tarahumara	→ Repartidor

8.14 Employer

MX_L2_EMPLEADOR

COLUMN NAME

SECURE LOOKUP

WHAT IT IS

Employer name or workplace.

HOW IT IS FOUND

COLUMN NAME MX_L2_EMPLEADOR – Path

80% empleador patron (except when followed by *busqueda*, *regex*, *expresion*) nombre_?patron razon_?social_?(patron|empleador) registro_?patronal_?nombre empresa_?(empleadora|trabajo|laboral) lugar_?(de_)?trabajo centro_?(de_)?trabajo employer dependencia_?laboral

HOW IT IS MASKED

Replaced by a fictitious Mexican company.

MX_EMPLEADOR **SECURE LOOKUP**

Replaces the value with one of the 25 values in `mx-empleadores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Petróleos Mexicanos

→

Ayuntamiento de Villa Nueva

8.15 Schooling

MX_L2_ESCOLARIDAD

COLUMN NAME

KNOWN VALUES

SECURE LOOKUP

WHAT IT IS

Highest level of schooling, in INEGI's categories.

HOW IT IS FOUND

COLUMN NAME MX_L2_ESCOLARIDAD – Path

80% escolaridad nivel_?(educativo|educacional|escolar|de_?estudios|academico) grado_?(de_)??estudios grado_?academico ultimo_?grado education_?level anos_?(de_)?escolaridad

KNOWN VALUES MX_L2_ESCOLARIDAD – List

LIST	VALUES	STRENGTH	FIRST VALUES
------	--------	----------	--------------

mx-detectar-escolaridad.txt	27	60%	Sin escolaridad, Preescolar, Primaria incompleta, Primaria completa, Secundaria incompleta, Secundaria completa
-----------------------------	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another level of the same scale.

MX_ESCOLARIDAD **SECURE LOOKUP**

Replaces the value with one of the 12 values in `mx-escolaridad.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Secundaria completa

→

Preparatoria o bachillerato

8.16 School

MX_L2_ESCUELA

COLUMN NAME **SECURE LOOKUP**

WHAT IT IS

Name of a school, high school or university.

HOW IT IS FOUND

COLUMN NAME MX_L2_ESCUELA – Path

75% escuela colegio plantel nombre?(escuela|plantel|colegio|institucion?educativa)
institucion?educativa universidad preparatoria secundaria primaria bachillerato
school(_?name)? jardin?de?ninos guarderia estancia?infantil

HOW IT IS MASKED

Replaced by a generic school name.

MX_ESCUELA **SECURE LOOKUP**

Replaces the value with one of the 15 values in `mx-escuelas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Instituto Cultural Tampico

→

Universidad Autónoma del Centro

8.17 School code (CCT)

MX_L2_CCT

COLUMN NAME **VALUE FORMAT** **CHARACTER MAPPING**

WHAT IT IS

The Clave de Centro de Trabajo of a school: state, type, number and a letter (09DPR1234X).

HOW IT IS FOUND

COLUMN NAME MX_L2_CCT – Path

85% cct clave?(de?)(centro?de?trabajo|escuela|plantel) cve?(cct|escuela|plantel)
centro?de?trabajo?clave

VALUE FORMAT MX_L2_CCT – Regex

PATTERN

STRENGTH

NOTES

`\d{2}[A-Z]{3}\d{4}[A-Z]`

90%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the format.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

09DPR1234X

→

79TPS0988Z

8.18 Dependents and children

MX_L2_DEPENDIENTES

COLUMN NAME DATA TYPE REGEX DECOMPOSE

WHAT IT IS

Number of economic dependents, children or household members.

HOW IT IS FOUND

COLUMN NAME

MX_L2_DEPENDIENTES - Path

80%

dependientes(_?economicos)? n(o|um|ro)?_dependientes num_?hijos n(o|um|ro)?_hijos cant_?hijos hijos integrantes_(del_)?(hogar|familia) n(o|um|ro)_?integrantes tamano_(del_)?hogar personas_(en_)?(el_)?hogar hijos_?nacidos_?vivos

DATA TYPE

MX_L2_DEPENDIENTES - Type

Accepts number (length up to 4) or text (length up to 4); any other type rules the domain out.

HOW IT IS MASKED

Values up to 5 stay; larger ones become 5, because large households are rare.

MX_CANTIDAD_ACOTADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE		MASKED
9	→	5

Sensitive data

The categories of article 2, section VI — ethnic origin, health, genetic information, beliefs, political opinions, sexual preference — together with gender identity, sexual life, biometrics and union membership. A categorical value is replaced by another of the same category, so the column keeps a realistic content; where the values share no vocabulary, they are suppressed.

9.1 Ethnic origin

MX_L3_ETNIA

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Indigenous people, Afro-Mexican self-identification or ethnic group. Named first in the sensitive data of article 2.

HOW IT IS FOUND

COLUMN NAME MX_L3_ETNIA - Path

90% etnia [eé]tnico origen_[eé]tnico grupo_[eé]tnico pueblo_?(indigena|originario|orig) autoadscripcion(_?(indigena|afromexicana|afro))? se_?considera_? (indigena|afromexican[oa]|afro) indigena ind[ií]gena afromexican[oa] afrodescendiente afro raza race ethnicity ethnic_?group comunidad_?indigena pertenencia_? (etnica|indigena)

KNOWN VALUES MX_L3_ETNIA - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-pueblos.txt	103	90%	Nahua, Maya, Zapoteco, Mixteco, Otomí, Otomi
mx-detectar-bandera.txt	8	30%	s, n, sí, si, no, y

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A yes/no flag stays a flag; a people becomes another from a list of the most numerous indigenous peoples and the Afro-Mexican people, including unlisted ones such as Kumiai .

MX_PUEBLO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_PUEBLO_LISTA .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX_PUEBLO_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 31 values in `mx-pueblos.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Kumiai	→	Tlapaneco
S	→	S

9.2 Indigenous language

`MX_L3 LENGUA INDIGENA`

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Whether a person speaks an indigenous language, and which. It reveals ethnic origin as surely as self-identification, and INEGI asks it in every census.

HOW IT IS FOUND

COLUMN NAME

`MX_L3 LENGUA INDIGENA` – Path

90%

`lengua(_?(indigena|materna|originaria))?` `habla_?(lengua_?)(indigena|originaria)` `hli`
`hablante_?(de_?)?lengua_?indigena` `idioma_?(indigena|materno|originario)` `lengua_?que_?`
`habla` `language_?indigenous` `native_?language`

KNOWN VALUES

`MX_L3 LENGUA INDIGENA` – List

LIST	VALUES	STRENGTH	FIRST VALUES
<code>mx-detectar-lenguas.txt</code>	57	80%	Náhuatl, Nahuatl, Maya, Tseltal, Tsotsil, Mixteco

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag; a language becomes another from a list of the most spoken.

`MX LENGUA INDIGENA`

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX LENGUA INDIGENA LISTA` .

`MX BANDERA`

REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX BANDERA SI NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

`MX BANDERA TRUE FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

`MX BANDERA S N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

`MX BANDERA Y N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

`MX BANDERA 0 1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

`MX CM ALFANUM`

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

`MX LENGUA INDIGENA LISTA`

SECURE LOOKUP

Replaces the value with one of the 27 values in `mx-lenguas.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Chocholteco

→ Cora

9.3 Diagnosis

MX_L3_SALUD_DIAGNOSTICO

COLUMN NAME

VALUE FORMAT

REGEX DECOMPOSE

WHAT IT IS

Diagnoses, ICD-10 codes, conditions, allergies and pathological history.

HOW IT IS FOUND

COLUMN NAME

MX_L3_SALUD_DIAGNOSTICO - Path

85%

diagn[oó]stico[a-z]* diag dx cie_?10 cie_?11 cod(igo)?_?cie cie icd_?10 icd
patolog[ií]a[a-z]* padecimiento[a-z]* enfermedad(es)?[a-z]* morbilidad condicion_
(medica|de_?salud|cronica) problema_?(de_?)?salud impresion_?diagnostica causa_
(incapacidad|muerte|defuncion|hospitalizacion|consulta) motivo_?(de_?)?
(consulta|hospitalizacion|incapacidad) comorbilidad(es)? antecedentes_
(medicos|patologicos|personales_?patologicos|heredofamiliares|clinicos) alergias?
enfermedad_?preexistente preexistencias? enfermedad_?cronica riesgo_?de_?trabajo

VALUE FORMAT

MX_L3_SALUD_DIAGNOSTICO - Regex

PATTERN

STRENGTH

NOTES

[A-TV-Za-tv-z]\d{2}(\.\d{1,2}|\d)?

50%

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An ICD-10 code becomes a common code in the same format (F32.9 → J45.9), a description a common diagnosis. The mapping hides the sensitive conditions — HIV, mental health, addictions — among ordinary ones.

MX_DIAGNOSTICO

REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

MX_DIAGNOSTICO_TEXTO .

MX_CIE10_DECIMAL

SECURE LOOKUP

Replaces the value with one of the 33 values in mx-cie10-decimal.txt , chosen by a keyed hash.

MX_CIE10

SECURE LOOKUP

Replaces the value with one of the 37 values in mx-cie10.txt , chosen by a keyed hash.

MX_BANDERA

REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO

SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE

SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N

SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N

SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1

SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

`MX_DIAGNOSTICO_TEXTO` **SECURE LOOKUP**

Replaces the value with one of the 30 values in `mx-diagnosticos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
F32.9	→	J02.9
Depresión mayor	→	Tendinitis

9.4 Medication

`MX_L3_SALUD_MEDICAMENTO`

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Prescribed medicines. An antiretroviral or an antipsychotic reveals the diagnosis.

HOW IT IS FOUND

COLUMN NAME

`MX_L3_SALUD_MEDICAMENTO` - Path

85% medicamentos? f[aá]rmacos? sustancia_?activa principio_?activo prescripci[oó]n
receta(_?medica)? tratamiento(_?farmacologico)? medication drug(_?name)? posologia
clave_?cuadro_?basico cuadro_?basico

KNOWN VALUES

`MX_L3_SALUD_MEDICAMENTO` - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar- medicamentos.txt	57	70%	Paracetamol, Ibuprofeno, Naproxeno, Metamizol, Ketorolaco, Diclofenaco

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by a common medicine.

`MX_MEDICAMENTO`

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX_MEDICAMENTO_LISTA` .

`MX_BANDERA` **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

`MX_BANDERA_SI_NO` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

`MX_BANDERA_TRUE_FALSE` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

`MX_BANDERA_S_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

`MX_BANDERA_Y_N` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

`MX_BANDERA_0_1` **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

`MX_CM_ALFANUM` **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

`MX_MEDICAMENTO_LISTA` **SECURE LOOKUP**

Replaces the value with one of the 26 values in `mx-medicamentos.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Sertralina 50 mg

→

Bezafibrato

9.5 Health record identifiers

MX_L3_SALUD_IDENTIFICADOR

COLUMN NAME

CHARACTER MAPPING

WHAT IT IS

Clinical file numbers (NOM-004-SSA3-2012), episode, prescription, bed and disability certificate numbers.

HOW IT IS FOUND

COLUMN NAME

MX_L3_SALUD_IDENTIFICADOR - Path

85%

expediente_?clinico n(o|um|ro|umero)_?expediente(_?clinico)? historia_?clinica
n(o|um|ro)_?historia nhc n(o|um|ro)_?episodio folio_?
(atencion|urgencias|receta|incapacidad|certificado_?(de_)?defuncion) n(o|um|ro)_?
incapacidad certificado_?(de_)?incapacidad serie_?folio_?incapacidad n(o|um|ro)_?(de_)?
cama n(o|um|ro)_?interconsulta n(o|um|ro)_?(de_)?receta agregado_?medico n(o|um|ro)_?
biopsia medical_?record_?number mrn

55%

expediente episodio cama

HOW IT IS MASKED

Character by character, keeping length and format.

MX_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE

MASKED

EXP-2024-00123

→

IRH-7843-85225

9.6 Clinical notes

MX_L3_SALUD_TEXTO_CLINICO

COLUMN NAME

DATA TYPE

FREE TEXT REDACTION

WHAT IT IS

Medical, progress, admission and discharge notes, current illness, physical examination — free text where names and CURPs appear.

HOW IT IS FOUND

COLUMN NAME

MX_L3_SALUD_TEXTO_CLINICO - Path

85%

nota_?(medica|de_?evolucion|evolucion|de_?ingreso|ingreso|de_?egreso|egreso|de_?
urgencias|urgencias|postoperatoria|preoperatoria|de_?enfermeria|clinica)s? notas_?
clinicas? padecimiento_?actual interrogatorio exploracion_?fisica evoluci[oó]n(_?
(medica|clinica))? epicrisis indicaciones(_?medicas)? resumen_?clinico resumen_?(de_)?
egreso historia_?(de_?la_)?enfermedad plan_?(de_)?tratamiento pronostico hallazgos
interpretacion clinical_?notes? progress_?notes?

DATA TYPE MX_L3_SALUD_TEXTO_CLINICO – Type

Accepts text (length 30 or more); any other type rules the domain out.

HOW IT IS MASKED

The same free text redaction as other text: identifiers become [DATO] , names [NOMBRE] . The clinical content stays.

MX_TEXTO_LIBRE **FREE TEXT REDACTION**

Replaces the text matching 9 patterns with [DATO] , and the 1,436 terms of mx-texto-nombres.txt with [NOMBRE] .

EXAMPLES

VALUE		MASKED
Paciente López, CURP HEGA850720MDFRRL04, acude por cefalea.	→	Paciente [NOMBRE], CURP [DATO], acude por cefalea.

9.7 Test results

MX_L3_SALUD_RESULTADO_EXAMEN

COLUMN NAME **CHARACTER MAPPING**

WHAT IT IS

Laboratory and imaging results: HIV, viral load, glucose, HbA1c, pregnancy and drug tests.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_RESULTADO_EXAMEN – Path

80%	resultado? (estudio examen laboratorio lab prueba pcr antigeno biopsia imagen vih covid papanicolaou mastografia) estudios?_(de_)?laboratorio vih hiv carga_viral cd4 glucosa glicemia hemoglobina(_glucosilada)? hba1c colesterol trigliceridos presion_arterial tension_arterial imc prueba?(covid embarazo vih antidoping toxicologica) antidoping lab_result
50%	resultado estudio

HOW IT IS MASKED

Character by character, keeping length and format.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE		MASKED
Reactivo	→	Quilqaju

9.8 Blood type

MX_L3_SALUD_GRUPO_SANGUINEO

COLUMN NAME **KNOWN VALUES** **SECURE LOOKUP**

WHAT IT IS

ABO group and Rh factor.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_GRUPO_SANGUINEO - Path

90% grupo_?sangu[ií]neo grupo_?sang tipo_?(de_)??sangre tipo_?sanguineo factor_?rh rh
blood_?type blood_?group

KNOWN VALUES MX_L3_SALUD_GRUPO_SANGUINEO - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-grupo-sanguineo.txt	26	90%	A+, A-, B+, B-, AB+, AB-

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another blood type.

MX_GRUPO_SANGUINEO **SECURE LOOKUP**

Replaces the value with one of the 8 values in `mx-grupo-sanguineo.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
0+	→ A-

9.9 Disability

MX_L3_SALUD_DISCAPACIDAD

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Type or degree of disability, in the categories of the 2020 census.

HOW IT IS FOUND

COLUMN NAME MX_L3_SALUD_DISCAPACIDAD - Path

90% discapacidad[a-z]* tipo_?(de_)??discapacidad grado_?(de_)??discapacidad certificado_?
(de_)?discapacidad persona_?con_?discapacidad pcd invalidez porcentaje_?(de_)?
invalidez pension_?(de_)?invalidez limitacion(_?(fisica|actividad))? disability
dependencia_?funcional nee necesidades_?educativas_?especiales condicion_?mental

KNOWN VALUES MX_L3_SALUD_DISCAPACIDAD - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-discapacidad.txt	26	60%	Caminar, subir o bajar, Ver, aun usando lentes, Oír, aun usando aparato auditivo, Oír, aun usando aparato auditivo, Hablar o comunicarse, Recordar o concentrarse

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag; a type becomes another census category.

MX_DISCAPACIDAD **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_DISCAPACIDAD_LISTA.

MX_BANDERA **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

MX_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

MX_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

MX_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

MX_DISCAPACIDAD_LISTA **SECURE LOOKUP**

Replaces the value with one of the 8 values in `mx-discapacidad.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Discapacidad psicosocial severa

→

Oír, aun usando aparato auditivo

9.10 Sexual and reproductive health

MX_L3_SALUD_SEXUAL_REPRODUCTIVA

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Pregnancy, gestational age, legal interruption of pregnancy, contraception, fertility, sexually transmitted infections.

HOW IT IS FOUND

COLUMN NAME

MX_L3_SALUD_SEXUAL_REPRODUCTIVA - Path

90%

```
embarazo embarazada gestaci[oó]n semanas_?(de_)?gestacion edad_?gestacional fum
fecha_?ultima_?menstruacion aborto ile ive interrupcion_?(legal_?|voluntaria_?)(del_)?
embarazo anticonceptivos? metodo_?(de_)?planificacion(_?familiar)? planificacion_
familiar fertilidad infertilidad reproduccion_?asistida gestas partos cesareas?
puerperio its ets infeccion_?(de_)?transmision_?sexual prep pregnan[a-z]*
contracepti[a-z]*
```

HOW IT IS MASKED

A flag stays a flag and a number gets other digits; anything else becomes Sin información .

MX_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_SUPRIMIR .

MX_BANDERA **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

MX_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

MX_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

MX_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

MX_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `mx-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Embarazo de 12 semanas	→	Sin información
S	→	S

9.11 Mental health and addictions

MX_L3_SALUD_MENTAL_ADICCIONES

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Psychiatric and psychological care, disorders, suicide risk, substance use and treatment.

HOW IT IS FOUND

COLUMN NAME

MX_L3_SALUD_MENTAL_ADICCIONES - Path

90%

```
salud_?mental  psiquiatri[a-z]*  psicologi[a-z]*  trastorno[a-z_]*  depresi[oó]n  ansiedad
suicid[a-z]*  autolesi[oó]n  adicci[oó]n(es)?  consumo_?(de_)?
(drogas|alcohol|sustancias|tabaco)  alcoholismo  farmacodependencia  drogadiccion
toxicomania  dependencia?(alcohol|drogas|sustancias)  cij  conadic  tratamiento_?
(adicciones|drogas|alcohol)  anexo?(rehabilitacion)?  mental_?health  substance_?
(use|abuse)
```

HOW IT IS MASKED

Suppressed to Sin información ; flags and codes keep their shape.

MX_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_SUPRIMIR .

MX_BANDERA **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

MX_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

MX_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

MX_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

MX_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `mx-sin-informacion.txt` , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Trastorno bipolar

→

Sin información

9.12 Biometric data

MX_L3_BIOMETRICO

COLUMN NAME

DATA TYPE

REGEX DECOMPOSE

WHAT IT IS

Fingerprint and facial templates, iris, voice and digitized signatures stored as text.

HOW IT IS FOUND

COLUMN NAME

MX_L3_BIOMETRICO - Path

90%

huella(_?(dactilar|digital))? huellas dactilar biometri[a-z]* template_?
(facial|biometrico|huella) rostro reconocimiento_?facial facial_?(template|id) iris
retina voz_?(huella|biometrica) firma_?(digitalizada|biometrica|autografa_?digital)
fingerprint face_?(id|template|encoding) palm_?print minucias

DATA TYPE

MX_L3_BIOMETRICO - Type

Accepts text; any other type rules the domain out.

HOW IT IS MASKED

Every character becomes `X`. Binary columns cannot be masked by the set; see *Limits*.

MX_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

A1B2C3D4E5F6

→

XXXXXXXXXXXX

9.13 Genetic information

MX_L3_INFORMACION_GENETICA

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

DNA profiles, genotypes, mutations, genetic screening and paternity tests — named by article 2.

HOW IT IS FOUND

COLUMN NAME

MX_L3_INFORMACION_GENETICA - Path

90%

adn dna genoma genotipo genetic[a-z]* gen[eé]tic[ao] informacion_?genetica
secuencia_?genetica marcador_?genetico perfil_?(genetico|biologico) mutacion(_?
genetica)? snp brca haplotipo cariotipo tamiz_?(genetico|metabolico) prueba_?(de_?)?
paternidad

HOW IT IS MASKED

Every character becomes `X`.

MX_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

EXAMPLES

VALUE

MASKED

BRCA1 positivo

→ XXXXXXXXXXXXXXXX

9.14 Sexual preference

MX_L3_PREFERENCIA_SEXUAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Sexual orientation — *preferencia sexual* in the words of the law.

HOW IT IS FOUND

COLUMN NAME

MX_L3_PREFERENCIA_SEXUAL - Path

95%

preferencia_?sexual orientaci[oó]n_?sexual sexual?(orientation|preference) orient_?
sexual pref_?sexual

KNOWN VALUES

MX_L3_PREFERENCIA_SEXUAL - List

LIST

VALUES

STRENGTH

FIRST VALUES

mx-detector-preferencia-sexual.txt	17	80%	Heterosexual, Homosexual, Lesbiana, Gay, Bisexual, Pansexual
------------------------------------	----	-----	--

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another value of the same scale.

MX_PREFERENCIA_SEXUAL

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_PREFERENCIA_SEXUAL_LISTA .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_PREFERENCIA_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in mx-preferencia-sexual.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Bisexual

→ Lesbiana

9.15 Gender identity

MX_L3_IDENTIDAD_GENERO

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Self-perceived gender identity and legal gender recognition.

HOW IT IS FOUND

COLUMN NAME

MX_L3_IDENTIDAD_GENERO - Path

95% identidad?(de_?)?g[eé]nero gender?identity g[eé]nero?(identidad|social|autopercibido) transg[eé]nero transexual persona?trans reconocimiento?(de_?)?identidad cambio?(de_?)?(sexo|genero) pronombres?

KNOWN VALUES

MX_L3_IDENTIDAD_GENERO - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-identidad-genero.txt	19	70%	Mujer, Hombre, Mujer trans, Hombre trans, No binario, Género fluido

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another value of the same scale.

MX_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_IDENTIDAD_GENERO_LISTA .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in mx-identidad-genero.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Hombre trans	→ No binario

9.16 Sexual life

MX_L3_VIDA_SEXUAL

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Sexual activity, behavior and history.

HOW IT IS FOUND

COLUMN NAME

MX_L3_VIDA_SEXUAL – Path

90%

vida_?sexual conducta_?sexual actividad_?sexual parejas?_?sexuales? practicas_?
sexuales inicio_?(de_)??vida_?sexual ivsa sexual_?(activity|behavior|history) historia_
sexual comportamiento_?sexual

HOW IT IS MASKED

Suppressed to Sin información .

MX_CATEGORIA_SUPRIMIDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_SUPRIMIR .

MX_BANDERA

REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in mx-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Activa

→

Sin información

9.17 Religion

MX_L3_RELIGION

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Religious affiliation — religious beliefs are named by article 2.

HOW IT IS FOUND

COLUMN NAME MX_L3_RELIGION – Path

95% religi[oó]n[a-z]* credo culto iglesia creencia_?religiosa confesion_?religiosa
denominacion_?religiosa asociacion_?religiosa religious_?affiliation comunidad_
religiosa

KNOWN VALUES MX_L3_RELIGION - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-religiones.txt	56	90%	Católica, Catolica, Protestante o cristiana evangélica, Protestante o cristiana evangelica, Pentecostal, Testigo de Jehová

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by a religion group of the 2020 census, including unlisted churches such as Luz del Mundo.

MX RFI TGT ON REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action: when none matches:

MX RELIGION LISTA.

MX BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX BANDERA SI NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

MX BANDERA TRUE FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

MX BANDERA S N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

MX BANDERA Y N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

MX BANDERA 0 1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

MX CM ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX RELIGION LISTA **SECURE LOOKUP**

Replaces the value with one of the 13 values in `mx-religiones.txt`, chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Luz del Mundo	→ Católica

9.18 Philosophical and moral beliefs

MX L3 CREENCIA FILOSOFICA MORAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Convictions, conscientious objection, ethical positions — the article 2 wording for beliefs that are not religious.

HOW IT IS FOUND

COLUMN NAME MX_L3_CREENCIA_FILOSOFICA_MORAL – Path

90% `creencias?_(?filosoficas?|morales?|personales) convicci[oó]n(es)?(_?(filosoficas?|morales?|eticas?|personales))?` `objecion?(de_)?conciencia` `postura?(etica|moral)` `valores?`
`personales` `filosofia?(de_)?vida` `cosmovision`

HOW IT IS MASKED

Suppressed to Sin información.

MX_CATEGORIA_SUPRIMIDA **REGEX DECOMPOSE**

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_SUPRIMIR.

MX_BANDERA **REGEX DECOMPOSE**

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

MX_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

MX_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

MX_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

MX_SUPRIMIR **SECURE LOOKUP**

Replaces the value with one of the 1 values in `mx-sin-informacion.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Rechaza transfusiones

→ Sin información

9.19 Political opinions

MX_L3_OPINION_POLITICA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Ideology, political position, voting intention and electoral preference.

HOW IT IS FOUND

COLUMN NAME MX_L3_OPINION_POLITICA – Path

90% `opini[oó]n(es)?_?pol[ií]ticas?` `ideolog[ií]a(_?politica)?` `posicion?politica` `postura?`
`politica` `tendencia?politica` `orientacion?politica` `preferencia?`
`(politica|electoral|partidista)` `intencion?(de_)?voto` `simpatia?(politica|partidista)`
`political?(view|orientation|opinion)`

KNOWN VALUES MX_L3_OPINION_POLITICA - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-opiniones-politicas.txt	14	70%	Izquierda, Centro izquierda, Centro, Centro derecha, Derecha, Sin preferencia

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another position of the same scale.

MX_OPINION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_OPINION_POLITICA_LISTA .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_OPINION_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in mx-opiniones-politicas.txt , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Centro derecha	→ Centro

9.20 Party membership

MX_L3_AFILIACION_POLITICA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Party membership or sympathy. A party list reveals political opinion.

HOW IT IS FOUND

COLUMN NAME MX_L3_AFILIACION_POLITICA - Path

95% partido(?:pol[í]tico)? militancia militante afiliaci[ó]n?
(politica|partidista|partido) afiliado?(a_)?partido padron?(de_)?militantes
political_?party party_?affiliation coalici[ó]n simpatizante

KNOWN VALUES MX_L3_AFILIACION_POLITICA – List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-partidos.txt	35	80%	Morena, Partido Acción Nacional, Partido Accion Nacional, Partido Revolucionario Institucional, Partido del Trabajo, Partido Verde Ecologista de México

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by one of the national parties registered in 2026, including those that lost registration (PRD).

MX_PARTIDO_POLITICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_PARTIDO_POLITICO_LISTA .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_PARTIDO_POLITICO_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in mx-partidos.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
Partido de la Revolución Democrática	→	Somos México

9.21 Union membership

MX_L3_AFILIACION_SINDICAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Union membership, union dues, section and unionized or trust worker status.

HOW IT IS FOUND

COLUMN NAME MX_L3_AFILIACION_SINDICAL – Path

95% sindicato[a-z]* sindical sindicalizado afiliaci[oó]n?sindical agremiado cuota?
sindical delegado?sindical seccion?sindical trabajador?(de?)?confianza tipo?(de?)?
trabajador?(sindicalizado|confianza) union?member(ship)? trade?union contrato?
colectivo

KNOWN VALUES

MX_L3_AFILIACION_SINDICAL - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-sindicatos.txt	16	60%	SNTE, CNTE, STPRM, SUTERM, CTM, CROC

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

A flag stays a flag; anything else becomes Sin información .

MX_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_SUPRIMIR .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in mx-sin-informacion.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
SNTE Sección 22	→	Sin información
S	→	S

Financial and patrimonial data

Article 7 requires express consent for financial and patrimonial data — a regime of its own, between ordinary and sensitive data, that GDPR-based templates do not have. It covers more than bank accounts: a credit bureau record, a daily wage, a housing credit, a social program or a tax regime tell as much about a person's economic situation as an income. Categories are replaced within their own notation; amounts are mapped into a plausible range with no link to the real value.

10.1 Credit bureau record

MX_FIN_BURO_CREDITO

COLUMN NAME

REGEX DECOMPOSE

WHAT IT IS

Buró de Crédito and Círculo de Crédito data: payment behaviour codes (MOP), score, arrears status, write-offs.

HOW IT IS FOUND

COLUMN NAME

MX_FIN_BURO_CREDITO – Path

90%

```
buro(_?(de_)?credito)? bur[oó] circulo_?(de_)?credito historial_?crediticio score(_?
(buro|crediticio|credito|riesgo|bc))? bc_?score puntaje_?(crediticio|buro|riesgo|credito)
calificacion_?(crediticia|buro|riesgo) mop forma_?de_?pago_?buro clave_?(de_)?
observacion morosidad moroso morosa atraso dias_?(de_)?atraso dias_?(de_)?mora
cartera_?vencida quebranto estatus_?(credito|crediticio|cartera) estado_?(de_)?
(cuenta_)?(credito|crediticio|cartera) credit_?score delinquen[a-z]* reestructura
insolvencia concurso_?mercantil
```

HOW IT IS MASKED

A MOP code becomes another MOP code, a 3-digit score other digits, a status another status.

MX_BURO_CREDITO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

MX_ESTADO_CREDITICIO .

MX_MOP SECURE LOOKUP

Replaces the value with one of the 9 values in `mx-mop.txt`, chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

MX_ESTADO_CREDITICIO **SECURE LOOKUP**

Replaces the value with one of the 10 values in `mx-estado-crediticio.txt`, chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
MOP 05	→	MOP 04
650	→	807

10.2 Debt amount

MX_FIN_MONTO_DEUDA

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

Outstanding balance, amount owed, credit limit, minimum payment.

HOW IT IS FOUND

COLUMN NAME MX_FIN_MONTO_DEUDA – Path

85% `monto_?(deuda|adeudo|adeudado|vencido|quebranto|credito|prestamo|financiado) adeudo(_?(total|vigente|vencido))? deuda(_?(total|vigente|vencida))? saldo_?(deudor|insoluto|vencido|credito|prestamo|tarjeta|adeudo) limite_?(de_)?credito linea_?(de_)?credito pago_?minimo debt(_?amount)? outstanding_?balance`

DATA TYPE MX_FIN_MONTO_DEUDA – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between 1,000 and 5,000,000.

MX_MONTO_DEUDA **NUMERIC MAPPING**

Maps the number to another between 1,000 and 5,000,000.

EXAMPLES

VALUE		MASKED
85000	→	78007

10.3 Monthly income

MX_FIN_INGRESO_MENSUAL

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

Salary, perceptions, net pay, household income.

HOW IT IS FOUND

COLUMN NAME MX_FIN_INGRESO_MENSUAL – Path

85% `suel``do[a-z]*` (except when followed by `diario`, `base_?cotizacion`)   `salario[a-z]*` (except when followed by `diario`, `base_?(de_)?cotizacion`, `minimo_?(general|profesional|zona)`)   `remuneraci``oó``n[a-z]*`
`ingreso_?(mensual|neto|bruto|familiar|del_?hogar|hogar|per_?`
`capita|total|promedio|declarado|laboral|comprobable|anual)` `ingresos(_?[a-z]+)?`
`percepciones?(_?(totales|gravadas|exentas))?` `total_?percepciones` `neto_?a_?pagar` `nomina_?`
`(neta|bruta)` `gasto_?(mensual|familiar)` `capacidad_?(de_)?pago` `salary` `wage` `income`
`gross_?pay` `net_?pay`

DATA TYPE MX_FIN_INGRESO_MENSUAL – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between 8,000 and 250,000.

MX_INGRESO_MENSUAL **NUMERIC MAPPING**

Maps the number to another between 8,000 and 250,000.

EXAMPLES

VALUE		MASKED
18500	→	10882

10.4 Daily wage (SDI, SBC)

MX_FIN_SALARIO_DIARIO

COLUMN NAME **DATA TYPE** **NUMERIC MAPPING**

WHAT IT IS

The integrated daily wage and the contribution base wage used by the IMSS — the way Mexican payrolls store pay.

HOW IT IS FOUND

COLUMN NAME MX_FIN_SALARIO_DIARIO – Path

90% `sdi` `sbc` `salario_?diario(_?integrado)?` `suel``do_?diario`   `salario_?base_?(de_)?cotizacion`
`sal_?(diario|base|integrado)` `sd_?integrado` `cuota_?diaria` `daily_?wage`

DATA TYPE MX_FIN_SALARIO_DIARIO – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between 280 and 3,000.

MX_SALARIO_DIARIO **NUMERIC MAPPING**

Maps the number to another between 280 and 3,000.

EXAMPLES

VALUE		MASKED
452	→	586

10.5 Assets

MX_FIN_PATRIMONIO

COLUMN NAME	DATA TYPE	NUMERIC MAPPING
-------------	-----------	-----------------

WHAT IT IS

Net worth, cadastral and appraisal values, investments and savings.

HOW IT IS FOUND

COLUMN NAME MX_FIN_PATRIMONIO – Path

85% patrimonio(_?(neto|total))? valor_?
(catastral|comercial|avaluo|inmueble|propiedad|vivienda|vehiculo|de_?la_?garantia) avaluo
bienes?(inmuebles|muebles) valor_?bienes activos?(personales|totales) saldo_
(inversion|ahorro|cuenta) monto?(inversion|ahorro) net_?worth assets

DATA TYPE MX_FIN_PATRIMONIO – Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between 200,000 and 30,000,000.

MX_PATRIMONIO NUMERIC MAPPING

Maps the number to another between 200,000 and 30,000,000.

EXAMPLES

VALUE	MASKED
1850000	→ 4398071

10.6 AFORE

MX_FIN_AFORE

COLUMN NAME	KNOWN VALUES	REGEX DECOMPOSE
-------------	--------------	-----------------

WHAT IT IS

The retirement fund administrator, and the pension regime.

HOW IT IS FOUND

COLUMN NAME MX_FIN_AFORE – Path

95% afore nombre?afore cve?afore clave?afore administradora?(de_)?fondos?(para_el_)?
retiro sar siefore cuenta?individual?(afore|retiro) regimen?(de_)?pension(_(ley_?
73|ley_97)))? pension_fund

KNOWN VALUES MX_FIN_AFORE – List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-afores.txt	27	90%	Afore Azteca, Afore Banamex, Afore Coppel, Afore Inbursa, Afore Invercap, PensionISSSTE

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by one of the ten AFORES authorized by CONSAR in 2026.

MX_AFORE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_AFORE_LISTA .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt`, chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt`, chosen by a keyed hash.

MX_BANDERA_S_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt`, chosen by a keyed hash.

MX_BANDERA_Y_N **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt`, chosen by a keyed hash.

MX_BANDERA_0_1 **SECURE LOOKUP**

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt`, chosen by a keyed hash.

MX_CM_ALFANUM **CHARACTER MAPPING**

Maps each character to another of its group (7 groups), keeping length and format.

MX_AFORE_LISTA **SECURE LOOKUP**

Replaces the value with one of the 11 values in `mx-afores.txt`, chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Afore Coppel

→ **Afore Principal**

10.7 Retirement and housing savings

MX_FIN_SALDO_RETIRO

COLUMN NAME

DATA TYPE

NUMERIC MAPPING

WHAT IT IS

Balances of the retirement and housing subaccounts, voluntary savings, pension amounts.

HOW IT IS FOUND

COLUMN NAME

MX_FIN_SALDO_RETIRO - Path

90%

saldo_?(afore|retiro|rcv|subcuenta|vivienda|infonavit|fovissste|sar|cuenta_
individual|voluntario) subcuenta_?(de_?)(retiro|vivienda|rcv) aportaciones?_
(voluntarias|patronales|infonavit) monto_?pension pension_?(mensual|monto) retiro_
cesantia_?vejez rcv ahorro_?voluntario retirement_?balance

DATA TYPE

MX_FIN_SALDO_RETIRO - Type

Accepts number; any other type rules the domain out.

HOW IT IS MASKED

Mapped to an amount between 5,000 and 5,000,000.

MX_SALDO_RETIRO **NUMERIC MAPPING**

Maps the number to another between 5,000 and 5,000,000.

EXAMPLES

VALUE

MASKED

385000

→ **797256**

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Infonavit, Fovissste, Cofinavit or bank mortgage, and payroll discount notices.

HOW IT IS FOUND

COLUMN NAME

MX_FIN_CREDITO_VIVIENDA - Path

90%

tipo?(de_)?credito?(vivienda|hipotecario) credito?(vivienda|hipotecario) hipoteca
infonavit fovissste cofinavit mejoravit descuento?infonavit factor?(de_)?descuento
aviso?(de_)?retencion mortgage

KNOWN VALUES

MX_FIN_CREDITO_VIVIENDA - List

LIST

VALUES

STRENGTH

FIRST VALUES

mx-detectar-credito-vivienda.txt	20	80%	Crédito Infonavit, Credito Infonavit, Crédito Fovissste, Credito Fovissste, Cofinavit, Crédito hipotecario bancario
----------------------------------	----	-----	---

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another type of housing credit.

MX_CREDITO_VIVIENDA

REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_CREDITO_VIVIENDA_LISTA .

MX_BANDERA

REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX_CM_ALFANUM

CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_CREDITO_VIVIENDA_LISTA

SECURE LOOKUP

Replaces the value with one of the 6 values in mx-credito-vivienda.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Mejoravit

→ Cofinavit

10.9 Social security coverage

MX_FIN_SEGURIDAD_SOCIAL

COLUMN NAME KNOWN VALUES REGEX DECOMPOSE

WHAT IT IS

Derechohabiencia: IMSS, ISSSTE, IMSS-Bienestar, Pemex, armed forces, private insurance, none. It reveals formal or informal work.

HOW IT IS FOUND

COLUMN NAME

MX_FIN_SEGURIDAD_SOCIAL - Path

90%

derechohabiencia derecho_?habiencia afiliacion_?(a_?)(servicios_?de_?salud|seguridad_?social) institucion_?(de_?)(seguridad_?social|salud) servicio_?medico seguridad_?social regimen_?(de_?)?seguridad_?social seguro_?(medico|de_?salud|popular) imss_?bienestar insabi umf unidad_?medica_?familiar health_?insurance

KNOWN VALUES

MX_FIN_SEGURIDAD_SOCIAL - List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-seguridad-social.txt	22	80%	IMSS, ISSSTE, ISSSTE estatal, IMSS-Bienestar, Pemex, Sedena

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

Replaced by another institution of the same list.

MX_SEGURIDAD_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_SEGURIDAD_SOCIAL_LISTA .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_SEGURIDAD_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-seguridad-social.txt` , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
ISSSTE	→	ISSSTE estatal

10.10 Social programs

MX_FIN_PROGRAMA_SOCIAL

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Beneficiaries of the Programas para el Bienestar and their predecessors: pensions, scholarships, Sembrando Vida, Jóvenes Construyendo el Futuro.

HOW IT IS FOUND

COLUMN NAME

MX_FIN_PROGRAMA_SOCIAL - Path

90%

programa_?(social|del_?bienestar|bienestar|federal|de_?apoyo|gobierno) programas_?sociales
beneficiario_?(de_?)?(programa|pension|beca|apoyo) apoyo_
(social|gubernamental|bienestar|economico) pension_?(bienestar|adultos_
mayores|mujeres|discapacidad|65) beca_?(bienestar|benito_?juarez|rita_?cetina) becas?_
bienestar jovenes_?construyendo jcf sembrando_?vida prospera oportunidades progresa
padron_?(de_?)?beneficiarios tarjeta_?bienestar social_?program

KNOWN VALUES

MX_FIN_PROGRAMA_SOCIAL - List

LIST

VALUES

STRENGTH

FIRST VALUES

mx-	37	80%	Pensión para el Bienestar de las Personas Adultas Mayores, Pension para el Bienestar de las Personas Adultas Mayores, Pensión Mujeres Bienestar, Pension Mujeres Bienestar,
detectar-			Pensión para el Bienestar de las Personas con Discapacidad, Pension para el Bienestar de las Personas con Discapacidad
programas			
.txt			

A value that matches none counts 40% against the domain.

HOW IT IS MASKED

A flag stays a flag; a program becomes another program of 2026.

MX_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_PROGRAMA_SOCIAL_LISTA .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in mx-programas-sociales.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Prospera

→

Jóvenes Escribiendo el Futuro

10.11 Socioeconomic level

MX_FIN_NIVEL_SOCIOECONOMICO

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

AMAI socioeconomic level (A/B to E), income decile or quintile, marginalization and poverty indicators.

HOW IT IS FOUND

COLUMN NAME

MX_FIN_NIVEL_SOCIOECONOMICO - Path

90%

```
nse nivel_?socioeconomico nivel_?socio_?economico estrato(_?socioeconomico)? clase_?
social decil(_?(de_?)?ingresos?)? quintil(_?(de_?)?ingresos?)? grado_?(de_?)?marginacion
indice_?(de_?)?marginacion marginacion rezago_?social pobreza(_?
(extrema|moderada|multidimensional))? carencias_?sociales? vulnerabilidad(_?(por_?
ingresos|social))? socioeconomic_?level
```

KNOWN VALUES

MX_FIN_NIVEL_SOCIOECONOMICO - List

LIST

VALUES

STRENGTH

FIRST VALUES

mx-detectar-nse.txt

13

40%

a/b, ab, c+, c, c-, d+

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

An AMAI level becomes another, a quintile another quintile, a decile another decile.

MX_NIVEL_SOCIOECONOMICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX_NSE .

MX_QUINTIL SECURE LOOKUP

Replaces the value with one of the 5 values in mx-quintil.txt , chosen by a keyed hash.

MX_DECIL_ALTO SECURE LOOKUP

Replaces the value with one of the 5 values in mx-decil-alto.txt , chosen by a keyed hash.

MX_DECIL SECURE LOOKUP

Replaces the value with one of the 10 values in mx-decil.txt , chosen by a keyed hash.

MX_NSE SECURE LOOKUP

Replaces the value with one of the 7 values in mx-nse.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

C-

→

E

Decil 8

→

Decil 10

10.12 Housing tenure

MX_FIN_VIVIENDA

COLUMN NAME

KNOWN VALUES

REGEX DECOMPOSE

WHAT IT IS

Whether the home is owned, being paid, rented, lent or in litigation, and its conditions.

HOW IT IS FOUND

COLUMN NAMEMX_FIN_VIVIENDA – Path

95%

tenencia_?(de_?)(la_?)?vivienda

tipo_?(de_?)?vivienda

situacion_?(de_?la_?)?vivienda

vivienda_?(propia|rentada|prestada)

condicion_?(de_?)(la_?)?vivienda

material_?(de_?)?(la_?)?vivienda

piso_?de_?tierra

hacinamiento

asentamiento_?irregular

housing_?(type|tenure|status)

KNOWN VALUESMX_FIN_VIVIENDA – List

LIST	VALUES	STRENGTH	FIRST VALUES
mx-detectar-vivienda.txt	15	60%	Propia, Propia en proceso de pago, Rentada o alquilada, Prestada, Intestada o en litigio, Otra situación

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Replaced by another tenure of the census scale.

MX_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_VIVIENDA_LISTA .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-vivienda.txt` , chosen by a keyed hash.

EXAMPLES

VALUE	MASKED
Asentamiento irregular	→ Propia

10.13 Tax regime

MX_FIN_REGIMEN_FISCAL

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

The SAT tax regime of an individual (CFDI catalog `c_RegimenFiscal`): wages, rent, business activity, RESICO. It reveals the source of a person's income.

HOW IT IS FOUND

COLUMN NAME	MX_FIN_REGIMEN_FISCAL - Path
90%	regimen_?fiscal(_?receptor)? c_?regimen_?fiscal cve_?regimen clave_?regimen(_?fiscal)? regimen_?(sat tributario) tax_?regime

HOW IT IS MASKED

A code becomes another individual regime code, a description another description; 626 - ... keeps both parts.

MX_REGIMEN_FISCAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_REGIMEN_FISCAL_NOMBRE .

MX_REGIMEN_FISCAL_CLAVE SECURE LOOKUP

Replaces the value with one of the 13 values in mx-regimen-fiscal-clave.txt , chosen by a keyed hash.

MX_REGIMEN_FISCAL_NOMBRE SECURE LOOKUP

Replaces the value with one of the 13 values in mx-regimen-fiscal-nombre.txt , chosen by a keyed hash.

EXAMPLES

VALUE		MASKED
626 - Régimen Simplificado de Confianza	→	612 - Sin obligaciones fiscales

Criminal records

Not named by the LFPDPPP, but among the data most likely to lead to discrimination, which is what article 2 describes as sensitive. They are handled with the same care.

11.1 Criminal records

MX_PENAL_ANTECEDENTES

COLUMN NAME REGEX DECOMPOSE

WHAT IT IS

Criminal records, sentences, offenses, pretrial detention, arrest warrants.

HOW IT IS FOUND

COLUMN NAME MX_PENAL_ANTECEDENTES – Path

95% antecedentes(_?(penales|judiciales|policiacos|criminales|no?penales))? *(except when followed by list E9)* carta?(de_?)?no?antecedentes constancia?(de_?)?(no_?)?antecedentes sentencia(_?condenatoria)? sentenciad[oa] condena(do|da)? delitos? tipo?(de_?)?delito reincidente reincidencia imputad[oa] vinculado?a?proceso vinculacion?a?proceso prision?preventiva pena reclusion interno centro?penitenciario cereso libertad?condicional criminal?record conviction offen[cs]e detenid[oa] orden?de?aprehension medida?cautelar violencia?familiar

HOW IT IS MASKED

A flag stays a flag; anything else becomes a generic status.

MX_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_ANTECEDENTES_LISTA .

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-si-no.txt , chosen by a keyed hash.

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-true-false.txt , chosen by a keyed hash.

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-s-n.txt , chosen by a keyed hash.

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-y-n.txt , chosen by a keyed hash.

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in mx-bandera-0-1.txt , chosen by a keyed hash.

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

MX_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 3 values in mx-antecedentes.txt , chosen by a keyed hash.

EXAMPLES

VALUE

MASKED

Sentenciado por robo

→ Sin información

11.2 Case numbers

MX_PENAL_CAUSA

COLUMN NAME	VALUE FORMAT	CHARACTER MAPPING
-------------	--------------	-------------------

WHAT IT IS

Investigation folders, preliminary inquiries, criminal case and appeal numbers (123/2024).

HOW IT IS FOUND

COLUMN NAME	MX_PENAL_CAUSA - Path		
90%	carpeta_(de_)?investigacion n(o um ro)_?carpeta averiguacion_?previa n(o um ro)_?averiguacion causa_?penal n(o um ro umero)_(de_)?causa expediente_(judicial penal) n(o um ro)_?expediente_(judicial penal) toca_?penal n(o um ro)_?toca amparo_(n(o um ro))? n(o um ro)_(de_)?denuncia folio_?denuncia case_?number		
VALUE FORMAT	MX_PENAL_CAUSA - Regex		
PATTERN	STRENGTH	NOTES	
[A-Z]{2,6}(/[A-Z0-9\-\]{1,12}){2,}/\d{2,6}[/\-\]\d{2,4}	80%		
\d{1,5}/\d{4}	50%		

A value that matches none counts 30% against the domain.

HOW IT IS MASKED

Character by character, keeping the format.

MX_CM_ALFANUM	CHARACTER MAPPING
---------------	-------------------

Maps each character to another of its group (7 groups), keeping length and format.

EXAMPLES

VALUE	MASKED
123/2024	→ 845/5120

Check digits computed by the set

Mexican applications validate their keys, and a masked key that fails validation breaks the test it was meant for. Two keys are covered by the plugin's own frameworks: the CLABE by Check Digit (weights 3, 7, 1, modulo 10), and the NSS by Payment Card, since its check digit is Luhn — the check of payment cards. The CURP and the RFC need more:

- **CURP** — every character counts, letters included (0–9, A–N → 10–23, Ñ 24, 0–Z → 25–36), with weights 18 down to 2, modulo 10. Check Digit reads letters in base 36, where 0–Z are worth one less.
- **RFC** — the SAT table (& 24, space 37, Ñ 38), weights 13 down to 2, modulo 11, with 10 written A. A company RFC counts as if preceded by a space. Check Digit writes a result of 10 as 0 and does not accept & or Ñ.

For these two the set computes the check digit itself. After the body is masked, a running sum travels through the value two characters at a time: a lookup table turns *sum + next two characters* into *those characters + new sum*, and the last table writes the check digit in place. Each table lists only what its positions can hold — digits for the date, letters for the names — so the CURP takes 8 steps and the RFC 6, each a Regex Decompose and a Data Cleansing file generated with the set, in a single String Algorithm Chain.

Every masked CURP, RFC and NSS is valid, and the mapping stays one-to-one — a key cannot collide with another. The cost is paid per value, per step, not per algorithm configured. Measured with the plugin outside the engine, on a laptop, a CURP masks in about 11 µs, an RFC in about 9 and an NSS in about 3, against about 2 for a Character Mapping: some 90,000 CURPs per second per thread. Half of the CURP's cost is its body — the date, and the keyed lookups for sex and state; the check digit is the other half. An engine's throughput depends on its hardware and job settings.

Dates inside keys

CURP, RFC and the INE voter key carry the birth date as YYMMDD. Leaving it would leave the strongest quasi-identifier in the key; changing its digits freely would produce dates that do not exist.

The decade stays and the unit of the year is masked, as in a birth year column. The month goes through a one-to-one mapping of 1–12, the day through one of 1–28, 29–30 among themselves, and a 31st keeps a 31-day month. The result is always a real date, and two different dates never become the same.

The same algorithm masks the date in the three keys, so a person's CURP, RFC and voter key keep agreeing with each other. They do not agree with the birth date column, which moves by up to 60 days: no algorithm can see two columns at once.

Limits

- **Binary columns** — photos of INE credentials, fingerprint images, clinical PDFs stored in BLOBs — cannot be masked by these algorithms. Inventory them and report them as residual risk.
- **Keys and the columns they derive from.** The letters of a masked CURP or RFC no longer come from the masked name, and its date is not the masked birth date. Where an application recomputes the CURP from the name, it will not match.

- **Inconvenient words.** RENAPO replaces some offensive letter combinations at the start of a CURP; a masked CURP may form one. It still passes the check digit.
- **Lowercase or formatted keys** — a CURP in lower case, an NSS with dashes — are masked character by character, without a valid check digit.
- **Municipalities** spelled in a way the list does not know pass unchanged. A name shared by a large and a small municipality stays as it is; the 5-digit code has no such ambiguity. A 3-digit municipality code without its state is not generalized.
- **Free text** is redacted word by word: a phone number written with spaces (55 1234 5678) is not found there, and a given name that is also a common word (Luz , Paz , Rosa) is redacted wherever it appears.
- **Minors** — a birth date moves at most 60 days, so few people cross their 18th birthday, but some do. Where that matters, split the rule by age group with Multi-Column Condition.
- **Addresses** are replaced as a whole line. Street, colonia, postal code and municipality in separate columns are masked independently and no longer form a coherent address.
- **Plates and VINs** keep their format but not the state series or the VIN check digit.

15

Verification

Before publication the set was checked outside a Masking Engine:

- Every classifier configuration was reviewed against what a Masking Engine accepts.
- Profiling was simulated on 151 columns with the whole set at its assignment threshold — well named, badly named, and 26 columns that are not personal data — and again with the classifiers of the essential pack alone.
- The algorithms, run with the Delphix algorithm plugin, masked 350 sample values and 228 placeholders such as S/D . Random CURPs, RFCs, NSS and CLABEs were checked for a valid check digit and a valid date, 150 of each for collisions, and pairs of CURP and RFC of the same person for agreement.

Every column was assigned as expected and every value masked as expected. Before using the set on real data, run a profiling job and a masking job on a representative copy.

16

Sources

- Ley Federal de Protección de Datos Personales en Posesión de los Particulares — DOF 20 March 2025, last amendment DOF 14 November 2025 (Cámara de Diputados). The 2010 law, DOF 5 July 2010, for comparison.
- CURP structure and check digit — Registro Nacional de Población (RENAPO).
- RFC check digit — Servicio de Administración Tributaria (SAT). Tax regime catalog `c_RegimenFiscal` — SAT, CFDI 4.0.
- NSS structure — Instituto Mexicano del Seguro Social (IMSS). CLABE — Banco de México and the Asociación de Bancos de México.
- INE voter key — Instituto Nacional Electoral. National political parties, including the registration of Partido Paz and Somos México on 1 July 2026 — INE.
- Municipalities, geostatistical codes, coordinates and population — INEGI, Censo de Población y Vivienda 2020. Religion, disability, schooling and housing categories — the same census.

- Most frequent surnames — INE and RENAPO registers. Given names — INEGI and name frequency registers.
- Indigenous peoples — Instituto Nacional de los Pueblos Indígenas, Catálogo Nacional de Pueblos y Comunidades Indígenas y Afromexicanas (2024).
- AFOREs — Comisión Nacional del Sistema de Ahorro para el Retiro (CONSAR), 2026. Social programs — Programas para el Bienestar, Government of Mexico, 2026.
- Socioeconomic levels — Asociación Mexicana de Agencias de Inteligencia de Mercado y Opinión (AMAI).
- Ten-digit dialing — Instituto Federal de Telecomunicaciones, 3 August 2019. Postal codes — Correos de México (SEPOMEX). License plates — NOM-001-SCT-2-2016.

Algorithms

Every algorithm of the set in alphabetical order, with its configuration. The one a domain names is the top of its tree; the others are building blocks.

MX_AFORE REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_AFORE_LISTA .

Used by: MX_FIN_AFORE

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	MX_BANDERA
(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_AFORE_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_AFORE_LISTA SECURE LOOKUP

Replaces the value with one of the 11 values in mx-afores.txt , chosen by a keyed hash.

Used by: MX_AFORE

CONFIGURATION

lookupFile	mx-afores.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ANIO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_L2_ANIO_NACIMIENTO

PATTERNS, TRIED IN ORDER

(\d{3})(\d)	keep · MX_CM_ALFANUM
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_ANTECEDENTES REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_ANTECEDENTES_LISTA .

Used by: MX_PENAL_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	MX_BANDERA
(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_ANTECEDENTES_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_ANTECEDENTES_LISTA SECURE LOOKUP

Replaces the value with one of the 3 values in `mx-antecedentes.txt` , chosen by a keyed hash.

Used by: `MX_ANTECEDENTES`

CONFIGURATION

lookupFile	mx-antecedentes.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_APELLIDO NAME

Replaces the name with one of the 337 names in `mx-apellidos.txt` .

Used by: `MX_APELLIDOS` , `MX_NOMBRE_COMPLETO`

CONFIGURATION

lookupFile	mx-apellidos.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

MX_APELLIDOS REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

Used by: `MX_L1_APELLIDO` , `MX_NOMBRE_COMPLETO`

PATTERNS, TRIED IN ORDER

(\S+)	MX_APELLIDO
(\S+)\s+(\S+)	MX_APELLIDO · MX_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	MX_APELLIDO · MX_APELLIDO · MX_APELLIDO
otherwise	MX_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

MX_BANDERA REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_CATEGORIA_SUPRIMIDA` , `MX_PUEBLO` , `MX LENGUA INDIGENA` , `MX_DIAGNOSTICO` , `MX_MEDICAMENTO` , `MX_DISCAPACIDAD` , `MX_PREFERENCIA_SEXUAL` , `MX_IDENTIDAD_GENERO` , `MX_RELIGION` , `MX_OPINION_POLITICA` , `MX_PARTIDO_POLITICO` ,

MX_BURO_CREDITO , MX_AFORE , MX_CREDITO_VIVIENDA , MX_SEGURIDAD_SOCIAL , MX_PROGRAMA_SOCIAL , MX_VIVIENDA , MX_ANTECEDENTES

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no)	MX_BANDERA_SI_NO
(?i)(true false)	MX_BANDERA_TRUE_FALSE
(?i)([sn])	MX_BANDERA_S_N
(?i)(y)	MX_BANDERA_Y_N
([01])	MX_BANDERA_0_1
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_BANDERA_0_1 SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-0-1.txt` , chosen by a keyed hash.

Used by: `MX_BANDERA`

CONFIGURATION

lookupFile	<code>mx-bandera-0-1.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_BANDERA_S_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-s-n.txt` , chosen by a keyed hash.

Used by: `MX_BANDERA`

CONFIGURATION

lookupFile	<code>mx-bandera-s-n.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_BANDERA_SI_NO SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-si-no.txt` , chosen by a keyed hash.

Used by: `MX_BANDERA`

CONFIGURATION

lookupFile	<code>mx-bandera-si-no.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

MX_BANDERA_TRUE_FALSE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-true-false.txt` , chosen by a keyed hash.

Used by: `MX_BANDERA`

CONFIGURATION

lookupFile	<code>mx-bandera-true-false.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

MX_BANDERA_Y_N SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-bandera-y-n.txt` , chosen by a keyed hash.

Used by: `MX_BANDERA`

CONFIGURATION

lookupFile	<code>mx-bandera-y-n.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

MX_BURO_CREDITO REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches:

`MX_ESTADO_CREDITICIO` .

Used by: `MX_FIN_BURO_CREDITO`

PATTERNS, TRIED IN ORDER

<code>(0[0-7] 9[679])</code>	<code>MX_MOP</code>
<code>(?i)(mop\s*)(0[0-7] 9[679])</code>	<code>keep · MX_MOP</code>
<code>(\d{3})</code>	<code>MX_CM_ALFANUM</code>
<code>(?i)(s[ií] no true false [sny01])</code>	<code>MX_BANDERA</code>
<code>otherwise</code>	<code>MX_ESTADO_CREDITICIO</code>

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

MX_CANTIDAD_ACOTADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `keep`.

Used by: `MX_L2_DEPENDIENTES`

PATTERNS, TRIED IN ORDER

<code>([0-5])</code>	<code>keep</code>
<code>(\d+)</code>	<code>replace with 5</code>

otherwise	keep
-----------	------

CONFIGURATION

trimInput	yes
requireMask	no

MX_CATEGORIA_SUPRIMIDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_SUPRIMIR` .

Used by: `MX_L3_SALUD_SEXUAL_REPRODUCTIVA` , `MX_L3_SALUD_MENTAL_ADICCIONES` , `MX_L3_VIDA_SEXUAL` , `MX_L3_CREENCIA_FILOSOFICA_MORAL` , `MX_L3_AFILIACION_SINDICAL`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false [sny01])</code>	<code>MX_BANDERA</code>
<code>(\d{1,6})</code>	<code>MX_CM_ALFANUM</code>
otherwise	<code>MX_SUPRIMIR</code>

CONFIGURATION

trimInput	yes
requireMask	no

MX_CIE10 SECURE LOOKUP

Replaces the value with one of the 37 values in `mx-cie10.txt` , chosen by a keyed hash.

Used by: `MX_DIAGNOSTICO`

CONFIGURATION

lookupFile	<code>mx-cie10.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_LOOKUP_FILE</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_CIE10_DECIMAL SECURE LOOKUP

Replaces the value with one of the 33 values in `mx-cie10-decimal.txt` , chosen by a keyed hash.

Used by: `MX_DIAGNOSTICO`

CONFIGURATION

lookupFile	<code>mx-cie10-decimal.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_LOOKUP_FILE</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_CLABE REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

Used by: `MX_L1_CLABE`

PATTERNS, TRIED IN ORDER

<code>(\d{18})</code>	<code>MX_CLABE_VALIDA</code>
-----------------------	------------------------------

otherwise	MX_CM_ALFANUM
CONFIGURATION	
trimInput	yes
requireMask	no

MX_CLABE_CUERPO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CLABE_VALIDA

PATTERNS, TRIED IN ORDER

(\d{3})(\d{14})	keep · MX_CM_ALFANUM
otherwise	keep

CONFIGURATION	
trimInput	yes
requireMask	no

MX_CLABE_VALIDA CHECK DIGIT

Masks the digits with MX_CLABE_CUERPO and recomputes a modulus 10 check digit with weights 3 7 1 3 7 1 3 7 1 3 7 1 3 7 1 3 7 .

Used by: MX_CLABE

CONFIGURATION	
weightList	3 7 1 3 7 1 3 7 1 3 7 1 3 7 1 3 7
modulusNumber	10
checkDigitIndex	17
calculateChecksumRightToLeft	no
numDigitsForCheckdigitCalculation	17
numericAlgorithm	MX_CLABE_CUERPO
inputHandlingConfig.characterHandling	STANDARD
inputHandlingConfig.invalidInputHandling	ERROR
inputHandlingConfig.shortInputHandling	FALLBACK
inputHandlingConfig.padCharacter	0
inputHandlingConfig.trimWhitespace	yes

MX_CLAVE_ELECTOR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

Used by: MX_L1_CLAVE_ELECTOR

PATTERNS, TRIED IN ORDER

([A-Z]{6})(\d{6})(\d{2})([HM])(\d{3})	MX_CM_ALFANUM · MX_FECHA_AAMDD · MX_ENTIDAD_NUMERO · MX_SEXO_H_M · MX_CM_ALFANUM
otherwise	MX_CM_ALFANUM

CONFIGURATION	
trimInput	yes
requireMask	no

MX_CLAVE_MUNICIPIO DATA CLEANSING

Replaces each value found in `mx-clave-municipio-generalizada.txt` (2,758 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_L2_CLAVE_MUNICIPIO`

CONFIGURATION

lookupFile	<code>mx-clave-municipio-generalizada.txt</code>
delimiter	<code>,</code>
caseSensitive	<code>yes</code>
trimWhitespace	<code>yes</code>

MX_CM_ALFANUM CHARACTER MAPPING

Maps each character to another of its group (7 groups), keeping length and format.

Used by: `MX_L1_CREDENCIAL_INE`, `MX_L1_DIRECCION_COMPLEMENTO`, `MX_L1_CUENTA_BANCARIA`, `MX_L1_PASAPORTE`, `MX_L1_DOCUMENTO_MIGRATORIO`, `MX_L1_CEDULA_PROFESIONAL`, `MX_L1_LICENCIA_CONducir`, `MX_L1_EFIRMA`, `MX_L1_NIV`, `MX_L1_NUMERO_CONTRATO`, `MX_L1_USUARIO_RRSS`, `MX_L2_CCT`, `MX_L3_SALUD_IDENTIFICADOR`, `MX_L3_SALUD_RESULTADO_EXAMEN`, `MX_PENAL_CAUSA`, `MX_CATEGORIA_SUPRIMIDA`, `MX_FECHA_AAMMDD`, `MX_CURP_CUERPO`, `MX_CURP`, `MX_RFC_CUERPO_FISICA`, `MX_RFC_CUERPO_MORAL`, `MX_RFC`, `MX_NSS`, `MX_CLAVE_ELECTOR`, `MX_NOMBRES`, `MX_APELLIDOS`, `MX_NOMBRE_COMPLETO`, `MX_EMAIL`, `MX_TELEFONO`, `MX_CLABE_CUERPO`, `MX_CLABE`, `MX_COORDENADA`, `MX_ANIO`, `MX_EDAD`, `MX_CODIGO_POSTAL`, `MX_PUEBLO`, `MX LENGUA_INDIGENA`, `MX_MEDICAMENTO`, `MX_DISCAPACIDAD`, `MX_PREFERENCIA_SEXUAL`, `MX_IDENTIDAD_GENERO`, `MX_RELIGION`, `MX_OPINION_POLITICA`, `MX_PARTIDO_POLITICO`, `MX_BURO_CREDITO`, `MX_AFORE`, `MX_CREDITO_VIVIENDA`, `MX_SEGURIDAD_SOCIAL`, `MX_PROGRAMA_SOCIAL`, `MX_VIVIENDA`, `MX_ANTECEDENTES`

CONFIGURATION

characterGroups	<code>0123456789 AEIOU BCDFGHIJKLMNOPQRSTUVWXYZ aeiou bcdfghjklmnpqrstvwxyz ÁÉÍÓÚÚ áéíóúü</code>
caseSensitive	<code>yes</code>
minMaskedPositions	<code>0</code>

MX_CM_HEX CHARACTER MAPPING

Maps each character to another of its group (5 groups), keeping length and format.

Used by: `MX_L1_DISPOSITIVO`, `MX_IP`

CONFIGURATION

characterGroups	<code>0123456789 abcdef ABCDEF ghijklmnopqrstuvwxyz GHIJKLMNOPQRSTUVWXYZ</code>
caseSensitive	<code>yes</code>
minMaskedPositions	<code>0</code>

MX_CODIGO_POSTAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM`.

Used by: `MX_L2_CODIGO_POSTAL`

PATTERNS, TRIED IN ORDER

<code>(\d{3})(\d{2})</code>	<code>keep · replace with 00</code>
otherwise	<code>MX_CM_ALFANUM</code>

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

MX_COLONIA SECURE LOOKUP

Replaces the value with one of the 60 values in `mx-colonias.txt` , chosen by a keyed hash.

Used by: `MX_L2_COLONIA`

CONFIGURATION

lookupFile	mx-colonias.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_COORDENADA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L1_GEOLOCALIZACION`

PATTERNS, TRIED IN ORDER

<code>(-?\d{1,3}\.\d)(\d+)\s*,\s*(-?\d{1,3}\.\d)(\d+)</code>	keep · <code>MX_CM_ALFANUM</code> · keep · <code>MX_CM_ALFANUM</code>
<code>(-?\d{1,3}\.\d)(\d+)</code>	keep · <code>MX_CM_ALFANUM</code>
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CREDITO_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX_CREDITO_VIVIENDA_LISTA` .

Used by: `MX_FIN_CREDITO_VIVIENDA`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false [sny01])</code>	<code>MX_BANDERA</code>
<code>(\d{1,6})</code>	<code>MX_CM_ALFANUM</code>
otherwise	<code>MX_CREDITO_VIVIENDA_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

MX_CREDITO_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-credito-vivienda.txt` , chosen by a keyed hash.

Used by: `MX_CREDITO_VIVIENDA`

CONFIGURATION

lookupFile	mx-credito-vivienda.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_CURP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

Used by: MX_L1_CURP

PATTERNS, TRIED IN ORDER

([A-Z]{4}\d{6} [HMX] [A-Z]{5} [0-9A-Z]\d)	MX_CURP_VALIDA
otherwise	MX_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_CUERPO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_VALIDA

PATTERNS, TRIED IN ORDER

([A-Z]) ([A-Z]) ([A-Z]{2}) (\d{6}) ([HM]) ([A-Z]{2}) ([A-Z]{3}) ([0-9A-Z]) (\d)	MX_CM_ALFANUM · MX_CM_ALFANUM · MX_CM_ALFANUM · MX_FECHA_AAMMDD · MX_SEXO_H_M · MX_ENTIDAD_CURP · MX_CM_ALFANUM · MX_CM_ALFANUM · replace with 0
([A-Z]) ([A-Z]) ([A-Z]{2}) (\d{6}) (X) ([A-Z]{2}) ([A-Z]{3}) ([0-9A-Z]) (\d)	MX_CM_ALFANUM · MX_CM_ALFANUM · MX_CM_ALFANUM · MX_FECHA_AAMMDD · keep · MX_ENTIDAD_CURP · MX_CM_ALFANUM · MX_CM_ALFANUM · replace with 0
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV STRING ALGORITHM CHAIN

Applies MX_CURP_DV_P1 → MX_CURP_DV_P2 → MX_CURP_DV_P3 → MX_CURP_DV_P4 → MX_CURP_DV_P5 → MX_CURP_DV_P6 → MX_CURP_DV_P7 → MX_CURP_DV_P8 , in this order.

Used by: MX_CURP_VALIDA

CONFIGURATION

algorithmReferences[1]	MX_CURP_DV_P1
algorithmReferences[2]	MX_CURP_DV_P2
algorithmReferences[3]	MX_CURP_DV_P3
algorithmReferences[4]	MX_CURP_DV_P4
algorithmReferences[5]	MX_CURP_DV_P5
algorithmReferences[6]	MX_CURP_DV_P6
algorithmReferences[7]	MX_CURP_DV_P7
algorithmReferences[8]	MX_CURP_DV_P8

MX_CURP_DV_P1 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{0})(.{2})(.*)	keep · MX_CURP_DV_T1 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P2 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{2})(.{3})(.*)	keep · MX_CURP_DV_T2 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P3 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · MX_CURP_DV_T3 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P4 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · MX_CURP_DV_T4 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P5 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · MX_CURP_DV_T5 · keep
------------------	-----------------------------

otherwise	keep
-----------	------

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P6 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{10})(.{4})(.*)	keep · MX_CURP_DV_T6 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P7 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{13})(.{3})(.*)	keep · MX_CURP_DV_T7 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_P8 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_CURP_DV

PATTERNS, TRIED IN ORDER

(.{15})(.{4})(.*)	keep · MX_CURP_DV_T8 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_CURP_DV_T1 DATA CLEANSING

Replaces each value found in mx-curp-dv-1.txt (676 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX_CURP_DV_P1

CONFIGURATION

lookupFile	mx-curp-dv-1.txt
delimiter	,

caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T2 DATA CLEANSING

Replaces each value found in `mx-curp-dv-2.txt` (6,760 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P2`

CONFIGURATION

lookupFile	<code>mx-curp-dv-2.txt</code>
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T3 DATA CLEANSING

Replaces each value found in `mx-curp-dv-3.txt` (1,000 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P3`

CONFIGURATION

lookupFile	<code>mx-curp-dv-3.txt</code>
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T4 DATA CLEANSING

Replaces each value found in `mx-curp-dv-4.txt` (1,000 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P4`

CONFIGURATION

lookupFile	<code>mx-curp-dv-4.txt</code>
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T5 DATA CLEANSING

Replaces each value found in `mx-curp-dv-5.txt` (1,000 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P5`

CONFIGURATION

lookupFile	<code>mx-curp-dv-5.txt</code>
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_CURP_DV_T6 DATA CLEANSING

Replaces each value found in `mx-curp-dv-6.txt` (20,280 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P6`

CONFIGURATION

lookupFile	<code>mx-curp-dv-6.txt</code>
delimiter	<code>,</code>
caseSensitive	<code>yes</code>
trimWhitespace	<code>yes</code>

MX_CURP_DV_T7 DATA CLEANSING

Replaces each value found in `mx-curp-dv-7.txt` (6,760 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P7`

CONFIGURATION

lookupFile	<code>mx-curp-dv-7.txt</code>
delimiter	<code>,</code>
caseSensitive	<code>yes</code>
trimWhitespace	<code>yes</code>

MX_CURP_DV_T8 DATA CLEANSING

Replaces each value found in `mx-curp-dv-8.txt` (9,360 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_CURP_DV_P8`

CONFIGURATION

lookupFile	<code>mx-curp-dv-8.txt</code>
delimiter	<code>,</code>
caseSensitive	<code>yes</code>
trimWhitespace	<code>yes</code>

MX_CURP_VALIDA STRING ALGORITHM CHAIN

Applies `MX_CURP_CUERPO` → `MX_CURP_DV`, in this order.

Used by: `MX_CURP`

CONFIGURATION

algorithmReferences[1]	<code>MX_CURP_CUERPO</code>
algorithmReferences[2]	<code>MX_CURP_DV</code>

MX_DECIL SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-decil.txt`, chosen by a keyed hash.

Used by: `MX_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	<code>mx-decil.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

MX_DECIL_ALTO SECURE LOOKUP

Replaces the value with one of the 5 values in `mx-decil-alto.txt` , chosen by a keyed hash.

Used by: `MX_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	mx-decil-alto.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_DIA_1_28 NUMERIC MAPPING

Maps the number to another between 1 and 28.

Used by: `MX_FECHA_AAMDD`

CONFIGURATION

minValue	1
maxValue	28

MX_DIA_29_30 NUMERIC MAPPING

Maps the number to another between 29 and 30.

Used by: `MX_FECHA_AAMDD`

CONFIGURATION

minValue	29
maxValue	30

MX_DIAGNOSTICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches:

`MX_DIAGNOSTICO_TEXTO` .

Used by: `MX_L3_SALUD_DIAGNOSTICO`

PATTERNS, TRIED IN ORDER

<code>([A-TV-Za-tv-z]\d{2}\.\d{1,2})</code>	<code>MX_CIE10_DECIMAL</code>
<code>([A-TV-Za-tv-z]\d{2,3})</code>	<code>MX_CIE10</code>
<code>(?i)(s[ií] no true false [sny01])</code>	<code>MX_BANDERA</code>
otherwise	<code>MX_DIAGNOSTICO_TEXTO</code>

CONFIGURATION

trimInput	yes
requireMask	no

MX_DIAGNOSTICO_TEXTO SECURE LOOKUP

Replaces the value with one of the 30 values in `mx-diagnostics.txt` , chosen by a keyed hash.

Used by: `MX_DIAGNOSTICO`

CONFIGURATION

lookupFile	mx-diagnostics.txt
------------	--------------------

hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_DIRECCION SECURE LOOKUP

Replaces the value with one of the 3,000 values in `mx-direcciones.txt` , chosen by a keyed hash.

Used by: `MX_L1_DIRECCION`

CONFIGURATION

lookupFile	<code>mx-direcciones.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_DISCAPACIDAD REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX_DISCAPACIDAD_LISTA` .

Used by: `MX_L3_SALUD_DISCAPACIDAD`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false [sny01])</code>	<code>MX_BANDERA</code>
<code>(\d{1,6})</code>	<code>MX_CM_ALFANUM</code>
otherwise	<code>MX_DISCAPACIDAD_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

MX_DISCAPACIDAD_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in `mx-discapacidad.txt` , chosen by a keyed hash.

Used by: `MX_DISCAPACIDAD`

CONFIGURATION

lookupFile	<code>mx-discapacidad.txt</code>
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_EDAD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L2_EDAD`

PATTERNS, TRIED IN ORDER

(\d{3,})	replace with 90
([1-9])(\d)(\.\d+)	keep · MX_CM_ALFANUM · keep
([1-9])(\d)	keep · MX_CM_ALFANUM
(\d)	MX_CM_ALFANUM
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_EMAIL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

Used by: MX_L1_EMAIL

PATTERNS, TRIED IN ORDER

([^@\s]+)@([^\s]+\.[A-Za-z]{2,24})	MX_CM_ALFANUM · MX_CM_ALFANUM · replace with test
otherwise	MX_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

MX_EMPLEADOR SECURE LOOKUP

Replaces the value with one of the 25 values in mx-empleadores.txt , chosen by a keyed hash.

Used by: MX_L2_EMPLEADOR

CONFIGURATION

lookupFile	mx-empleadores.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ENTIDAD_CURP SECURE LOOKUP

Replaces the value with one of the 33 values in mx-entidad-curp.txt , chosen by a keyed hash.

Used by: MX_CURP_CUERPO

CONFIGURATION

lookupFile	mx-entidad-curp.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ENTIDAD_NUMERO SECURE LOOKUP

Replaces the value with one of the 32 values in mx-entidad-numero.txt , chosen by a keyed hash.

Used by: `MX_CLAVE_ELECTOR`

CONFIGURATION

lookupFile	mx-entidad-numero.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ESCOLARIDAD SECURE LOOKUP

Replaces the value with one of the 12 values in `mx-escolaridad.txt`, chosen by a keyed hash.

Used by: `MX_L2_ESCOLARIDAD`

CONFIGURATION

lookupFile	mx-escolaridad.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ESCUELA SECURE LOOKUP

Replaces the value with one of the 15 values in `mx-escuelas.txt`, chosen by a keyed hash.

Used by: `MX_L2_ESCUELA`

CONFIGURATION

lookupFile	mx-escuelas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ESTADO_CIVIL SECURE LOOKUP

Replaces the value with one of the 6 values in `mx-estado-civil.txt`, chosen by a keyed hash.

Used by: `MX_L2_ESTADO_CIVIL`

CONFIGURATION

lookupFile	mx-estado-civil.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_ESTADO_CREDITICIO SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-estado-crediticio.txt`, chosen by a keyed hash.

Used by: `MX_BURO_CREDITO`

CONFIGURATION

lookupFile	mx-estado-credificio.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_FECHA_AAMDD REGEX DECOMPOSE

Tries 4 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

Used by: MX_CURP_CUERPO , MX_RFC_CUERPO_FISICA , MX_RFC_CUERPO_MORAL , MX_RFC , MX_CLAVE_ELECTOR

PATTERNS, TRIED IN ORDER

(\d)(\d)(0[1-9] 1[0-2])(0[1-9] 1\d 2[0-8])	keep · MX_CM_ALFANUM · MX_MES · MX_DIA_1_28
(\d)(\d)(0[13-9] 1[0-2])(29 30)	keep · MX_CM_ALFANUM · MX_MES_30_DIAS · MX_DIA_29_30
(\d)(\d)(0[13578] 1[02])(31)	keep · MX_CM_ALFANUM · MX_MES_31_DIAS · keep
(\d)(\d)(02)(29)	keep · MX_CM_ALFANUM · keep · replace with 28
otherwise	MX_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

MX_FECHA_EVENTO DATE SHIFT

Moves the date by -30 to 30 days.

Used by: MX_L2_FECHA_EVENTO

CONFIGURATION

minRange	-30
maxRange	30
unit	DAYS
roll	no

MX_FECHA_NACIMIENTO DATE SHIFT

Moves the date by -60 to 60 days.

Used by: MX_L2_FECHA_NACIMIENTO

CONFIGURATION

minRange	-60
maxRange	60
unit	DAYS
roll	no

MX_GRUPO_SANGUINEO SECURE LOOKUP

Replaces the value with one of the 8 values in mx-grupo-sanguineo.txt , chosen by a keyed hash.

Used by: MX_L3_SALUD_GRUPO_SANGUINEO

CONFIGURATION

lookupFile	mx-grupo-sanguineo.txt
------------	------------------------

hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_IDENTIDAD_GENERO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_IDENTIDAD_GENERO_LISTA .

Used by: MX_L3_IDENTIDAD_GENERO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	MX_BANDERA
(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_IDENTIDAD_GENERO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_IDENTIDAD_GENERO_LISTA SECURE LOOKUP

Replaces the value with one of the 8 values in mx-identidad-genero.txt , chosen by a keyed hash.

Used by: MX_IDENTIDAD_GENERO

CONFIGURATION

lookupFile	mx-identidad-genero.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_INGRESO_MENSUAL NUMERIC MAPPING

Maps the number to another between 8,000 and 250,000.

Used by: MX_FIN_INGRESO_MENSUAL

CONFIGURATION

minValue	8000
maxValue	250000

MX_IP REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: MX_CM_HEX .

Used by: MX_L1_IP

PATTERNS, TRIED IN ORDER

(\d{1,3})\.(\d{1,3})\.(\d{1,3})\.(\d{1,3})	MX_OCTETO . MX_OCTETO . MX_OCTETO . MX_OCTETO
otherwise	MX_CM_HEX

CONFIGURATION

trimInput	yes
requireMask	no

MX_LENGUA_INDIGENA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_LENGUA_INDIGENA_LISTA .

Used by: MX_L3_LENGUA_INDIGENA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	MX_BANDERA
(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_LENGUA_INDIGENA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_LENGUA_INDIGENA_LISTA SECURE LOOKUP

Replaces the value with one of the 27 values in mx-lenguas.txt , chosen by a keyed hash.

Used by: MX_LENGUA_INDIGENA

CONFIGURATION

lookupFile	mx-lenguas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_LOCALIDAD SECURE LOOKUP

Replaces the value with one of the 229 values in mx-localidades.txt , chosen by a keyed hash.

Used by: MX_L2_LOCALIDAD

CONFIGURATION

lookupFile	mx-localidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_LOOKUP_FILE
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_MEDICAMENTO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_MEDICAMENTO_LISTA .

Used by: MX_L3_SALUD_MEDICAMENTO

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	MX_BANDERA
-----------------------------------	------------

(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_MEDICAMENTO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_MEDICAMENTO_LISTA SECURE LOOKUP

Replaces the value with one of the 26 values in `mx-medicamentos.txt`, chosen by a keyed hash.

Used by: `MX_MEDICAMENTO`

CONFIGURATION

lookupFile	mx-medicamentos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_MES NUMERIC MAPPING

Maps the number to another between 1 and 12.

Used by: `MX_FECHA_AAMDD`

CONFIGURATION

minValue	1
maxValue	12

MX_MES_30_DIAS SECURE LOOKUP

Replaces the value with one of the 11 values in `mx-meses-30-dias.txt`, chosen by a keyed hash.

Used by: `MX_FECHA_AAMDD`

CONFIGURATION

lookupFile	mx-meses-30-dias.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_MES_31_DIAS SECURE LOOKUP

Replaces the value with one of the 7 values in `mx-meses-31-dias.txt`, chosen by a keyed hash.

Used by: `MX_FECHA_AAMDD`

CONFIGURATION

lookupFile	mx-meses-31-dias.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

MX_MONTO_DEUDA NUMERIC MAPPING

Maps the number to another between 1,000 and 5,000,000.

Used by: **MX_FIN_MONTO_DEUDA**

CONFIGURATION

minValue	1000
maxValue	5000000

MX_MOP SECURE LOOKUP

Replaces the value with one of the 9 values in **mx-mop.txt** , chosen by a keyed hash.

Used by: **MX_BURO_CREDITO**

CONFIGURATION

lookupFile	mx-mop.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_MUNICIPIO DATA CLEANSING

Replaces each value found in **mx-municipio-generalizado.txt** (6,547 pairs) by its counterpart; values not in the file stay as they are.

Used by: **MX_L2_MUNICIPIO**

CONFIGURATION

lookupFile	mx-municipio-generalizado.txt
delimiter	
caseSensitive	yes
trimWhitespace	yes

MX_NACIONALIDAD SECURE LOOKUP

Replaces the value with one of the 20 values in **mx-nacionalidades.txt** , chosen by a keyed hash.

Used by: **MX_L2_NACIONALIDAD**

CONFIGURATION

lookupFile	mx-nacionalidades.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_NIVEL_SOCIOECONOMICO REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: **MX_NSE** .

Used by: **MX_FIN_NIVEL_SOCIOECONOMICO**

PATTERNS, TRIED IN ORDER

([1-5])	MX_QUINTIL
([6-9] 10)	MX_DECIL_ALTO
(?i)(decil\s*)(\d{1,2})	keep · MX_DECIL
otherwise	MX_NSE

CONFIGURATION

trimInput	yes
requireMask	no

MX_NOMBRE_COMPLETO REGEX DECOMPOSE

Tries 6 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

Used by: MX_L1_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

([^\,]+),\s*(.+))	MX_APELLIDOS · MX_NOMBRES
(\S+)	MX_NOMBRE_PILA
(\S+)\s+(\S+)	MX_NOMBRE_PILA · MX_APELLIDO
(\S+)\s+(\S+)\s+(\S+)	MX_NOMBRE_PILA · MX_APELLIDO · MX_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	MX_NOMBRE_PILA · MX_NOMBRE_PILA · MX_APELLIDO · MX_APELLIDO
(\S+)\s+(\S+)\s+(\S+)\s+(\S+)\s+(\S+)	MX_NOMBRE_PILA · MX_NOMBRE_PILA · MX_NOMBRE_PILA · MX_APELLIDO · MX_APELLIDO
otherwise	MX_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

MX_NOMBRE_PILA NAME

Replaces the name with one of the 255 names in mx-nombres.txt .

Used by: MX_NOMBRES , MX_NOMBRE_COMPLETO

CONFIGURATION

lookupFile	mx-nombres.txt
maskedValueCase	PRESERVE_INPUT
filterAccent	yes
inputCaseSensitive	no

MX_NOMBRES REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: MX_CM_ALFANUM .

Used by: MX_L1_NOMBRE , MX_NOMBRE_COMPLETO

PATTERNS, TRIED IN ORDER

(\S+)	MX_NOMBRE_PILA
(\S+)\s+(\S+)	MX_NOMBRE_PILA · MX_NOMBRE_PILA
(\S+)\s+(\S+)\s+(\S+)	MX_NOMBRE_PILA · MX_NOMBRE_PILA · MX_NOMBRE_PILA
otherwise	MX_CM_ALFANUM

CONFIGURATION

trimInput	yes
requireMask	no

MX_NSE SECURE LOOKUP

Replaces the value with one of the 7 values in `mx-nse.txt` , chosen by a keyed hash.

Used by: `MX_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	<code>mx-nse.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_LOOKUP_FILE</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_NSS REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

Used by: `MX_L1_NSS`

PATTERNS, TRIED IN ORDER

<code>(\d{11})</code>	<code>MX_NSS_LUHN</code>
otherwise	<code>MX_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

MX_NSS_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: `MX_NSS`

CONFIGURATION

preserve	<code>0</code>
----------	----------------

MX_OCTETO NUMERIC MAPPING

Maps the number to another between 1 and 254.

Used by: `MX_IP`

CONFIGURATION

minValue	<code>1</code>
maxValue	<code>254</code>

MX_OCUPACION SECURE LOOKUP

Replaces the value with one of the 40 values in `mx-ocupaciones.txt` , chosen by a keyed hash.

Used by: `MX_L2_OCUPACION`

CONFIGURATION

lookupFile	<code>mx-ocupaciones.txt</code>
hashMethod	<code>SHA256</code>

maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_OPINION_POLITICA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_OPINION_POLITICA_LISTA .

Used by: MX_L3_OPINION_POLITICA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	MX_BANDERA
(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_OPINION_POLITICA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_OPINION_POLITICA_LISTA SECURE LOOKUP

Replaces the value with one of the 7 values in mx-opiniones-politicas.txt , chosen by a keyed hash.

Used by: MX_OPINION_POLITICA

CONFIGURATION

lookupFile	mx-opiniones-politicas.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_PARTIDO_POLITICO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_PARTIDO_POLITICO_LISTA .

Used by: MX_L3_AFILIACION_POLITICA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	MX_BANDERA
(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_PARTIDO_POLITICO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_PARTIDO_POLITICO_LISTA SECURE LOOKUP

Replaces the value with one of the 10 values in mx-partidos.txt , chosen by a keyed hash.

Used by: MX_PARTIDO_POLITICO

CONFIGURATION

lookupFile	mx-partidos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_PATRIMONIO NUMERIC MAPPING

Maps the number to another between 200,000 and 30,000,000.

Used by: MX_FIN_PATRIMONIO

CONFIGURATION

minValue	200000
maxValue	30000000

MX_PLACA CHARACTER MAPPING

Maps each character to another of its group (3 groups), keeping length and format.

Used by: MX_L1_PLACA

CONFIGURATION

characterGroups	ABCDEFGHIJKLMNPRSTUVWXYZ abcdefghijklmnpqrstuvwxyz 0123456789
caseSensitive	yes

MX_PREFERENCIA_SEXUAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_PREFERENCIA_SEXUAL_LISTA .

Used by: MX_L3_PREFERENCIA_SEXUAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	MX_BANDERA
(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_PREFERENCIA_SEXUAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_PREFERENCIA_SEXUAL_LISTA SECURE LOOKUP

Replaces the value with one of the 9 values in mx-preferencia-sexual.txt , chosen by a keyed hash.

Used by: MX_PREFERENCIA_SEXUAL

CONFIGURATION

lookupFile	mx-preferencia-sexual.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_PROGRAMA_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

MX_PROGRAMA_SOCIAL_LISTA .

Used by: MX_FIN_PROGRAMA_SOCIAL

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	MX_BANDERA
(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_PROGRAMA_SOCIAL_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_PROGRAMA_SOCIAL_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in mx-programas-sociales.txt , chosen by a keyed hash.

Used by: MX_PROGRAMA_SOCIAL

CONFIGURATION

lookupFile	mx-programas-sociales.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_PUEBLO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_PUEBLO_LISTA .

Used by: MX_L3_ETNIA

PATTERNS, TRIED IN ORDER

(?i)(s[ií] no true false [sny01])	MX_BANDERA
(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_PUEBLO_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_PUEBLO_LISTA SECURE LOOKUP

Replaces the value with one of the 31 values in mx-pueblos.txt , chosen by a keyed hash.

Used by: MX_PUEBLO

CONFIGURATION

lookupFile	mx-pueblos.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

MX_QUINTIL SECURE LOOKUP

Replaces the value with one of the 5 values in `mx-quintil.txt`, chosen by a keyed hash.

Used by: `MX_NIVEL_SOCIOECONOMICO`

CONFIGURATION

lookupFile	<code>mx-quintil.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

MX_REDACTAR REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L1_CREDENCIAL`, `MX_L3_BIOMETRICO`, `MX_L3_INFORMACION_GENETICA`

PATTERNS, TRIED IN ORDER

<code>(.+) </code>	each character → <code>X</code>
otherwise	keep

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

MX_REGIMEN_FISCAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX_REGIMEN_FISCAL_NOMBRE`.

Used by: `MX_FIN_REGIMEN_FISCAL`

PATTERNS, TRIED IN ORDER

<code>(6\d{2})</code>	<code>MX_REGIMEN_FISCAL_CLAVE</code>
<code>(6\d{2})(\s*[—]\s*)(.+)</code>	<code>MX_REGIMEN_FISCAL_CLAVE</code> · keep · <code>MX_REGIMEN_FISCAL_NOMBRE</code>
otherwise	<code>MX_REGIMEN_FISCAL_NOMBRE</code>

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

MX_REGIMEN_FISCAL_CLAVE SECURE LOOKUP

Replaces the value with one of the 13 values in `mx-regimen-fiscal-clave.txt`, chosen by a keyed hash.

Used by: `MX_REGIMEN_FISCAL`

CONFIGURATION

lookupFile	<code>mx-regimen-fiscal-clave.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>

trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_REGIMEN_FISCAL_NOMBRE SECURE LOOKUP

Replaces the value with one of the 13 values in `mx-regimen-fiscal-nombre.txt` , chosen by a keyed hash.

Used by: `MX_REGIMEN_FISCAL`

CONFIGURATION

lookupFile	<code>mx-regimen-fiscal-nombre.txt</code>
hashMethod	SHA256
maskedValueCase	<code>PRESERVE_LOOKUP_FILE</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_RELIGION REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_RELIGION_LISTA` .

Used by: `MX_L3_RELIGION`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false [sny01])</code>	<code>MX_BANDERA</code>
<code>(\d{1,6})</code>	<code>MX_CM_ALFANUM</code>
otherwise	<code>MX_RELIGION_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

MX_RELIGION_LISTA SECURE LOOKUP

Replaces the value with one of the 13 values in `mx-religiones.txt` , chosen by a keyed hash.

Used by: `MX_RELIGION`

CONFIGURATION

lookupFile	<code>mx-religiones.txt</code>
hashMethod	SHA256
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

MX_RFC REGEX DECOMPOSE

Tries 3 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

Used by: `MX_L1_RFC`

PATTERNS, TRIED IN ORDER

<code>([A-ZÑ&]{4}\d{6}[A-Z0-9]{2}[0-9A])</code>	<code>MX_RFC_FISICA</code>
<code>([A-ZÑ&]{3}\d{6}[A-Z0-9]{2}[0-9A])</code>	<code>MX_RFC_MORAL</code>
<code>([A-ZÑ&])([A-ZÑ&])([A-ZÑ&]{2})(\d{6})</code>	<code>MX_CM_ALFANUM · MX_CM_ALFANUM · MX_CM_ALFANUM · MX_FECHA_AAMMDD</code>
otherwise	<code>MX_CM_ALFANUM</code>

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_CUERPO_FISICA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_FISICA

PATTERNS, TRIED IN ORDER

<code>([A-ZÑ&])([A-ZÑ&])([A-ZÑ&]{2})(\d{6})([A-Z0-9]{2})([0-9A])</code>	<code>MX_CM_ALFANUM · MX_CM_ALFANUM · MX_CM_ALFANUM · MX_FECHA_AAMMDD · MX_CM_ALFANUM · replace with 0</code>
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_CUERPO_MORAL REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_MORAL

PATTERNS, TRIED IN ORDER

<code>([A-ZÑ&]{3})(\d{6})([A-Z0-9]{2})([0-9A])</code>	<code>MX_CM_ALFANUM · MX_FECHA_AAMMDD · MX_CM_ALFANUM · replace with 0</code>
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_DV STRING ALGORITHM CHAIN

Applies MX_RFC_DV_P1 → MX_RFC_DV_P2 → MX_RFC_DV_P3 → MX_RFC_DV_P4 → MX_RFC_DV_P5 → MX_RFC_DV_P6 , in this order.

Used by: MX_RFC_FISICA , MX_RFC_MORAL

CONFIGURATION

algorithmReferences[1]	MX_RFC_DV_P1
algorithmReferences[2]	MX_RFC_DV_P2
algorithmReferences[3]	MX_RFC_DV_P3
algorithmReferences[4]	MX_RFC_DV_P4
algorithmReferences[5]	MX_RFC_DV_P5
algorithmReferences[6]	MX_RFC_DV_P6

MX_RFC_DV_P1 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_DV

PATTERNS, TRIED IN ORDER

<code>(.{0})(.{2})(.*)</code>	<code>keep · MX_RFC_DV_T1 · keep</code>
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_DV_P2 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_DV

PATTERNS, TRIED IN ORDER

(.{2})(.{3})(.*)	keep · MX_RFC_DV_T2 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_DV_P3 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_DV

PATTERNS, TRIED IN ORDER

(.{4})(.{3})(.*)	keep · MX_RFC_DV_T3 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_DV_P4 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_DV

PATTERNS, TRIED IN ORDER

(.{6})(.{3})(.*)	keep · MX_RFC_DV_T4 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_DV_P5 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_DV

PATTERNS, TRIED IN ORDER

(.{8})(.{3})(.*)	keep · MX_RFC_DV_T5 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
-----------	-----

requireMask	no
-------------	----

MX_RFC_DV_P6 REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_DV

PATTERNS, TRIED IN ORDER

(.{10})(.{4})(.*)	keep · MX_RFC_DV_T6 · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_DV_T1 DATA CLEANSING

Replaces each value found in mx-rfc-dv-1.txt (812 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX_RFC_DV_P1

CONFIGURATION

lookupFile	mx-rfc-dv-1.txt
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_RFC_DV_T2 DATA CLEANSING

Replaces each value found in mx-rfc-dv-2.txt (8,624 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX_RFC_DV_P2

CONFIGURATION

lookupFile	mx-rfc-dv-2.txt
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_RFC_DV_T3 DATA CLEANSING

Replaces each value found in mx-rfc-dv-3.txt (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX_RFC_DV_P3

CONFIGURATION

lookupFile	mx-rfc-dv-3.txt
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_RFC_DV_T4 DATA CLEANSING

Replaces each value found in mx-rfc-dv-4.txt (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX_RFC_DV_P4

CONFIGURATION

lookupFile	mx-rfc-dv-4.txt
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_RFC_DV_T5 DATA CLEANSING

Replaces each value found in mx-rfc-dv-5.txt (1,100 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX_RFC_DV_P5

CONFIGURATION

lookupFile	mx-rfc-dv-5.txt
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_RFC_DV_T6 DATA CLEANSING

Replaces each value found in mx-rfc-dv-6.txt (14,256 pairs) by its counterpart; values not in the file stay as they are.

Used by: MX_RFC_DV_P6

CONFIGURATION

lookupFile	mx-rfc-dv-6.txt
delimiter	,
caseSensitive	yes
trimWhitespace	yes

MX_RFC_FISICA STRING ALGORITHM CHAIN

Applies MX_RFC_CUERPO_FISICA → MX_RFC_DV , in this order.

Used by: MX_RFC

CONFIGURATION

algorithmReferences[1]	MX_RFC_CUERPO_FISICA
algorithmReferences[2]	MX_RFC_DV

MX_RFC_MORAL STRING ALGORITHM CHAIN

Applies MX_RFC_CUERPO_MORAL → MX_RFC_RELLENO → MX_RFC_DV → MX_RFC_SIN_RELLENO , in this order.

Used by: MX_RFC

CONFIGURATION

algorithmReferences[1]	MX_RFC_CUERPO_MORAL
algorithmReferences[2]	MX_RFC_RELLENO
algorithmReferences[3]	MX_RFC_DV
algorithmReferences[4]	MX_RFC_SIN_RELLENO

MX_RFC_RELLENO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: MX_RFC_MORAL

PATTERNS, TRIED IN ORDER

<code>(.){11}</code>	<code>MX_RFC_RELLENO_TABLA</code> · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_RFC_RELLENO_TABLA DATA CLEANSING

Replaces each value found in `mx-rfc-relleño.txt` (38 pairs) by its counterpart; values not in the file stay as they are.

Used by: `MX_RFC_RELLENO`

CONFIGURATION

lookupFile	<code>mx-rfc-relleño.txt</code>
delimiter	<code>,</code>
caseSensitive	yes
trimWhitespace	yes

MX_RFC_SIN_RELLENO REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_RFC_MORAL`

PATTERNS, TRIED IN ORDER

<code>(_){12}</code>	remove · keep
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

MX_SALARIO_DIARIO NUMERIC MAPPING

Maps the number to another between 280 and 3,000.

Used by: `MX_FIN_SALARIO_DIARIO`

CONFIGURATION

minValue	<code>280</code>
maxValue	<code>3000</code>

MX_SALDO_RETIRO NUMERIC MAPPING

Maps the number to another between 5,000 and 5,000,000.

Used by: `MX_FIN_SALDO_RETIRO`

CONFIGURATION

minValue	<code>5000</code>
maxValue	<code>5000000</code>

MX_SEGURIDAD_SOCIAL REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches:

`MX_SEGURIDAD_SOCIAL_LISTA` .

Used by: `MX_FIN_SEGURIDAD_SOCIAL`

PATTERNS, TRIED IN ORDER

<code>(?i)(s[ií] no true false [sny01])</code>	<code>MX_BANDERA</code>
<code>(\d{1,2})</code>	<code>MX_CM_ALFANUM</code>
otherwise	<code>MX_SEGURIDAD_SOCIAL_LISTA</code>

CONFIGURATION

trimInput	yes
requireMask	no

`MX_SEGURIDAD_SOCIAL_LISTA` SECURE LOOKUP

Replaces the value with one of the 10 values in `mx-seguridad-social.txt`, chosen by a keyed hash.

Used by: `MX_SEGURIDAD_SOCIAL`

CONFIGURATION

lookupFile	<code>mx-seguridad-social.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_LOOKUP_FILE</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

`MX_SEXO` REGEX DECOMPOSE

Tries 5 patterns in order and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L2_SEXO`

PATTERNS, TRIED IN ORDER

<code>(?i)(femenino masculino)</code>	<code>MX_SEXO_PALABRA</code>
<code>(?i)(mujer hombre)</code>	<code>MX_SEXO_MUJER_HOMBRE</code>
<code>(?i)(female male)</code>	<code>MX_SEXO_INGLES</code>
<code>(?i)([hm])</code>	<code>MX_SEXO_H_M</code>
<code>(?i)(f)</code>	<code>MX_SEXO_F_M</code>
otherwise	keep

CONFIGURATION

trimInput	yes
requireMask	no

`MX_SEXO_F_M` SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-f-m.txt`, chosen by a keyed hash.

Used by: `MX_SEXO`

CONFIGURATION

lookupFile	<code>mx-sexo-f-m.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	no
trimWhitespaceFromInput	yes

trimWhitespaceInLookupFile	yes
----------------------------	-----

MX_SEXO_H_M SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-h-m.txt` , chosen by a keyed hash.

Used by: `MX_CURP_CUERPO` , `MX_CLAVE_ELECTOR` , `MX_SEXO`

CONFIGURATION

lookupFile	<code>mx-sexo-h-m.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

MX_SEXO_INGLES SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-ingles.txt` , chosen by a keyed hash.

Used by: `MX_SEXO`

CONFIGURATION

lookupFile	<code>mx-sexo-ingles.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

MX_SEXO_MUJER_HOMBRE SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-mujer-hombre.txt` , chosen by a keyed hash.

Used by: `MX_SEXO`

CONFIGURATION

lookupFile	<code>mx-sexo-mujer-hombre.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

MX_SEXO_PALABRA SECURE LOOKUP

Replaces the value with one of the 2 values in `mx-sexo-palabra.txt` , chosen by a keyed hash.

Used by: `MX_SEXO`

CONFIGURATION

lookupFile	<code>mx-sexo-palabra.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_INPUT</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>

trimWhitespaceInLookupFile	yes
----------------------------	-----

MX_SUPRIMIR SECURE LOOKUP

Replaces the value with one of the 1 values in `mx-sin-informacion.txt` , chosen by a keyed hash.

Used by: `MX_CATEGORIA_SUPRIMIDA`

CONFIGURATION

lookupFile	<code>mx-sin-informacion.txt</code>
hashMethod	<code>SHA256</code>
maskedValueCase	<code>PRESERVE_LOOKUP_FILE</code>
inputCaseSensitive	<code>no</code>
trimWhitespaceFromInput	<code>yes</code>
trimWhitespaceInLookupFile	<code>yes</code>

MX_TARJETA REGEX DECOMPOSE

Matches one pattern and gives each part of the value its own action; when none matches: keep.

Used by: `MX_L1_TARJETA`

PATTERNS, TRIED IN ORDER

<code>(\d[\d\s-]{11,22}\d)</code>	<code>MX_TARJETA_LUHN</code>
otherwise	<code>keep</code>

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

MX_TARJETA_LUHN PAYMENT CARD

Replaces the card number with another that passes the Luhn check.

Used by: `MX_TARJETA`

CONFIGURATION

minMaskedPositions	<code>6</code>
preserve	<code>0</code>

MX_TELEFONO REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: `MX_CM_ALFANUM` .

Used by: `MX_L1_TELEFONO`

PATTERNS, TRIED IN ORDER

<code>(\+?52[\s-]?)?(1[\s-]?)?\((? (?:55 56 33 81)\)?[\s-]?)\(\d{4}\)([\s-]?) \(\d{4}\)</code>	<code>keep · keep · keep · MX_CM_ALFANUM · keep · MX_CM_ALFANUM</code>
<code>(\+?52[\s-]?)?(1[\s-]?)?\((?[2-9]\d{2}\)\)? [\s-]?\(\d{3}\)([\s-]?)\(\d{4}\)</code>	<code>keep · keep · keep · MX_CM_ALFANUM · keep · MX_CM_ALFANUM</code>
otherwise	<code>MX_CM_ALFANUM</code>

CONFIGURATION

trimInput	<code>yes</code>
requireMask	<code>no</code>

MX_TEXTO_LIBRE FREE TEXT REDACTION

Replaces the text matching 9 patterns with [DATO] , and the 1,436 terms of mx-texto-nombres.txt with [NOMBRE] .

Used by: MX_L1_TEXTO_LIBRE , MX_L3_SALUD_TEXTO_CLINICO

PATTERNS, TRIED IN ORDER

[A-Z]{4}\d{6}[HMX][A-Z]{5}[0-9A-Z]\d
[A-ZÑ&]{3,4}\d{6}[A-Z0-9]{2}[0-9A]
[A-Z]{6}\d{8}[HM]\d{3}
[\w.+\\-]+@[\\w\\-]+(\\. [\\w\\-]+)+
(?<!\d)(\+?52)?1?\d{10}(?!\\d)
(?<!\d)\d{11}(?!\\d)
(?<!\d)\d{13,19}(?!\\d)
(?<![A-Za-z])([A-HJ-NPR-Z]{3}-?\d{3}-?[A-HJ-NPR-Z])(?![A-Za-z])
(?<!\d)(\d{1,3}\.){3}\d{1,3}(?!\\d)

CONFIGURATION

regExRedactValue	[DATO]
lookupFile	mx-texto-nombres.txt
lookupFileRedactValue	[NOMBRE]
isDenyList	yes

MX_VIVIENDA REGEX DECOMPOSE

Tries 2 patterns in order and gives each part of the value its own action; when none matches: MX_VIVIENDA_LISTA .

Used by: MX_FIN_VIVIENDA

PATTERNS, TRIED IN ORDER

(?i)(s[íí] no true false [sny01])	MX_BANDERA
(\d{1,6})	MX_CM_ALFANUM
otherwise	MX_VIVIENDA_LISTA

CONFIGURATION

trimInput	yes
requireMask	no

MX_VIVIENDA_LISTA SECURE LOOKUP

Replaces the value with one of the 6 values in mx-vivienda.txt , chosen by a keyed hash.

Used by: MX_VIVIENDA

CONFIGURATION

lookupFile	mx-vivienda.txt
hashMethod	SHA256
maskedValueCase	PRESERVE_INPUT
inputCaseSensitive	no
trimWhitespaceFromInput	yes
trimWhitespaceInLookupFile	yes

APPENDIX B

Files

The lookup and detection files the set reads. On a Masking Engine each one is uploaded with the object that reads it — the lookup file of a Secure Lookup or Data Cleansing algorithm, the value list of a List classifier — and referenced by that object's configuration.

FILE	LINES	USED BY	FIRST LINES
mx-afores.txt	11	MX_AFORE_LISTA	Afore Azteca · Afore Banamex · Afore Coppel · Afore Inbursa
mx-antecedentes.txt	3	MX_ANTECEDENTES_LISTA	Sin antecedentes penales · Con antecedentes penales · Sin información
mx-apellidos.txt	337	MX_APELLIDO	Hernández · García · Martínez · López
mx-bandera-0-1.txt	2	MX_BANDERA_0_1	0 · 1
mx-bandera-s-n.txt	2	MX_BANDERA_S_N	S · N
mx-bandera-si-no.txt	2	MX_BANDERA_SI_NO	Sí · No
mx-bandera-true-false.txt	2	MX_BANDERA_TRUE_FALSE	true · false
mx-bandera-y-n.txt	2	MX_BANDERA_Y_N	Y · N
mx-cie10-decimal.txt	33	MX_CIE10_DECIMAL	E11.9 · E78.5 · J45.9 · J06.9
mx-cie10.txt	37	MX_CIE10	I10 · E11 · E78 · J45
mx-clave-municipio-generalizada.txt	2,758	MX_CLAVE_MUNICIPIO	01001,01001 · 1001,1001 · 01002,01002 · 1002,1002
mx-colonias.txt	60	MX_COLONIA	Centro · Del Valle · San Miguel · Santa María
mx-credito-vivienda.txt	6	MX_CREDITO_VIVIENDA_LISTA	Crédito Infonavit · Crédito Fovissste · Cofinavit · Crédito hipotecario bancario
mx-curp-dv-1.txt	676	MX_CURP_DV_T1	AA,AA0 · AB,AB7 · AC,AC4 · AD,AD1
mx-curp-dv-2.txt	6,760	MX_CURP_DV_T2	OAA,AA0 · OAB,AB5 · OAC,AC0 · OAD,AD5
mx-curp-dv-3.txt	1,000	MX_CURP_DV_T3	000,000 · 001,013 · 002,026 · 003,039
mx-curp-dv-4.txt	1,000	MX_CURP_DV_T4	000,000 · 001,011 · 002,022 · 003,033
mx-curp-dv-5.txt	1,000	MX_CURP_DV_T5	000,000 · 001,019 · 002,028 · 003,037

FILE	LINES	USED BY	FIRST LINES
mx-curp-dv-6.txt	20,280	MX_CURP_DV_T6	0HAA,HAA6 · 0HAB,HAB2 · 0HAC,HAC8 · 0HAD,HAD4
mx-curp-dv-7.txt	6,760	MX_CURP_DV_T7	0AA,AA0 · 0AB,AB4 · 0AC,AC8 · 0AD,AD2
mx-curp-dv-8.txt	9,360	MX_CURP_DV_T8	0A00,A00 · 0A10,A18 · 0A20,A26 · 0A30,A34
mx-decil-alto.txt	5	MX_DECIL_ALTO	6 · 7 · 8 · 9
mx-decil.txt	10	MX_DECIL	1 · 2 · 3 · 4
mx-detectar-afores.txt	27	MX_FIN_AFORE – List	Afore Azteca · Afore Banamex · Afore Coppel · Afore Inbursa
mx-detectar-apellidos.txt	423	MX_L1_APELLIDO – List MX_L1_NOMBRE_COMPLETO – List	Hernández · Hernandez · García · Garcia
mx-detectar-bandera.txt	8	MX_L3_ETNIA – List	s · n · sí · si
mx-detectar-clave-municipio.txt	2,758	MX_L2_CLAVE_MUNICIPIO – List	01001 · 1001 · 01002 · 1002
mx-detectar-credito-vivienda.txt	20	MX_FIN_CREDITO_VIVIENDA – List	Crédito Infonavit · Credito Infonavit · Crédito Fovissste · Credito Fovissste
mx-detectar-discapacidad.txt	26	MX_L3_SALUD_DISCAPACIDAD – List	Caminar, subir o bajar · Ver, aun usando lentes · Oír, aun usando aparato auditivo · Oír, aun usando aparato auditivo
mx-detectar-escolaridad.txt	27	MX_L2_ESCOLARIDAD – List	Sin escolaridad · Preescolar · Primaria incompleta · Primaria completa
mx-detectar-estado-civil.txt	19	MX_L2_ESTADO_CIVIL – List	soltero · soltera · casado · casada
mx-detectar-grupo-sanguineo.txt	26	MX_L3_SALUD_GRUPO_SANGUINEO – List	A+ · A- · B+ · B-
mx-detectar-identidad-genero.txt	19	MX_L3_IDENTIDAD_GENERO – List	Mujer · Hombre · Mujer trans · Hombre trans
mx-detectar-lenguas.txt	57	MX_L3 LENGUA_INDIGENA – List	Náhuatl · Nahuatl · Maya · Tseltal
mx-detectar-medicamentos.txt	57	MX_L3_SALUD_MEDICAMENTO – List	Paracetamol · Ibuprofeno · Naproxeno · Metamizol
mx-detectar-municipios.txt	3,090	MX_L2_MUNICIPIO – List	Aguascalientes · Asientos · Calvillo · Cosío

FILE	LINES	USED BY	FIRST LINES
mx-detectar-nacionalidades.txt	64	MX_L2_NACIONALIDAD – List	Mexicana · Estadounidense · Guatemalteca · Hondureña
mx-detectar-nombres.txt	301	MX_L1_NOMBRE – List MX_L1_NOMBRE_COMPLETO – List	María · Maria · José · Jose
mx-detectar-nse.txt	13	MX_FIN_NIVEL_SOCIOECONOMICO – List	a/b · ab · c+ · c
mx-detectar-opiniones-politicas.txt	14	MX_L3_OPINION_POLITICA – List	Izquierda · Centro izquierda · Centro · Centro derecha
mx-detectar-partidos.txt	35	MX_L3_AFILIACION_POLITICA – List	Morena · Partido Acción Nacional · Partido Accion Nacional · Partido Revolucionario Institucional
mx-detectar-preferencia-sexual.txt	17	MX_L3_PREFERENCIA_SEXUAL – List	Heterosexual · Homosexual · Lesbiana · Gay
mx-detectar-programas.txt	37	MX_FIN_PROGRAMA_SOCIAL – List	Pensión para el Bienestar de las Personas Adultas Mayores · Pension para el Bienestar de las Personas Adultas Mayores · Pensión Mujeres Bienestar · Pension Mujeres Bienestar
mx-detectar-pueblos.txt	103	MX_L3_ETNIA – List	Nahua · Maya · Zapoteco · Mixteco
mx-detectar-religiones.txt	56	MX_L3_RELIGION – List	Católica · Catolica · Protestante o cristiana evangélica · Protestante o cristiana evangelica
mx-detectar-seguridad-social.txt	22	MX_FIN_SEGURIDAD_SOCIAL – List	IMSS · ISSSTE · ISSSTE estatal · IMSS-Bienestar
mx-detectar-sexo.txt	12	MX_L2_SEXO – List	h · m · f · x
mx-detectar-sindicatos.txt	16	MX_L3_AFILIACION_SINDICAL – List	SNTE · CNTE · STPRM · SUTERM
mx-detectar-vivienda.txt	15	MX_FIN_VIVIENDA – List	Propia · Propia en proceso de pago · Rentada o alquilada · Prestada
mx-diagnosticos.txt	30	MX_DIAGNOSTICO_TEXT0	Hipertensión arterial sistémica · Diabetes mellitus tipo 2 · Asma · Lumbalgia
mx-direcciones.txt	3,000	MX_DIRECCION	Calle Belisario Domínguez 681 · Calle Coahuila 741 · Calle Marte 348 Int. 17 · Xicoténcatl 1448
mx-discapacidad.txt	8	MX_DISCAPACIDAD_LISTA	Caminar, subir o bajar · Ver, aun usando lentes · Oír, aun usando aparato auditivo · Hablar o comunicarse
mx-empleadores.txt	25	MX_EMPLEADOR	Comercializadora del Bajío S.A. de C.V. · Servicios Integrales del Norte S.A. de C.V. · Constructora Sierra Madre S.A. de C.V. · Transportes Golfo Pacífico S.A. de C.V.
mx-entidad-curp.txt	33	MX_ENTIDAD_CURP	AS · BC · BS · CC

FILE	LINES	USED BY	FIRST LINES
mx-entidad-numero.txt	32	MX_ENTIDAD_NUMERO	01 · 02 · 03 · 04
mx-escolaridad.txt	12	MX_ESCOLARIDAD	Sin escolaridad · Preescolar · Primaria incompleta · Primaria completa
mx-escuelas.txt	15	MX_ESCUELA	Escuela Primaria Miguel Hidalgo · Escuela Primaria Rural Emiliano Zapata · Escuela Secundaria Técnica No. 14 · Telesecundaria Josefa Ortiz de Domínguez
mx-estado-civil.txt	6	MX_ESTADO_CIVIL	Soltero · Casado · Unión libre · Separado
mx-estado-crediticio.txt	10	MX_ESTADO_CREDITICIO	Al corriente · Atraso de 1 a 29 días · Atraso de 30 a 59 días · Atraso de 60 a 89 días
mx-grupo-sanguineo.txt	8	MX_GRUPO_SANGUINEO	A+ · A- · B+ · B-
mx-identidad-genero.txt	8	MX_IDENTIDAD_GENERO_LISTA	Mujer · Hombre · Mujer trans · Hombre trans
mx-lenguas.txt	27	MX LENGUA INDIGENA_LISTA	Náhuatl · Maya · Tseltal · Tsotsil
mx-localidades.txt	229	MX_LOCALIDAD	Aguascalientes · Jesús María · Ensenada · Mexicali
mx-medicamentos.txt	26	MX_MEDICAMENTO_LISTA	Paracetamol · Ibuprofeno · Naproxeno · Metamizol
mx-meses-30-dias.txt	11	MX_MES_30_DIAS	01 · 03 · 04 · 05
mx-meses-31-dias.txt	7	MX_MES_31_DIAS	01 · 03 · 05 · 07
mx-mop.txt	9	MX_MOP	01 · 02 · 03 · 04
mx-municipio-generalizado.txt	6,547	MX_MUNICIPIO	Aguascalientes Aguascalientes · AGUASCALIENTES AGUASCALIENTES · Asientos Asientos · ASIENTOS ASIENTOS
mx-nacionalidades.txt	20	MX_NACIONALIDAD	Mexicana · Estadounidense · Guatemalteca · Hondureña
mx-nombres.txt	255	MX_NOMBRE_PILA	María · José · Juan · Luis
mx-nse.txt	7	MX_NSE	A/B · C+ · C · C-
mx-ocupaciones.txt	40	MX_OCUPACION	Empleado administrativo · Comerciante · Vendedor · Obrero
mx-opiniones-politicas.txt	7	MX_OPINION_POLITICA_LISTA	Izquierda · Centro izquierda · Centro · Centro derecha
mx-partidos.txt	10	MX_PARTIDO_POLITICO_LISTA	Morena · Partido Acción Nacional · Partido Revolucionario Institucional · Partido del Trabajo

FILE	LINES	USED BY	FIRST LINES
mx-preferencia-sexual.txt	9	MX_PREFERENCIA_SEXUAL_LISTA	Heterosexual · Homosexual · Lesbiana · Gay
mx-programas-sociales.txt	13	MX_PROGRAMA_SOCIAL_LISTA	Pensión para el Bienestar de las Personas Adultas Mayores · Pensión Mujeres Bienestar · Pensión para el Bienestar de las Personas con Discapacidad · Beca Universal Rita Cetina
mx-pueblos.txt	31	MX_PUEBLO_LISTA	Nahua · Maya · Zapoteco · Mixteco
mx-quintil.txt	5	MX_QUINTIL	1 · 2 · 3 · 4
mx-regimen-fiscal-clave.txt	13	MX_REGIMEN_FISCAL_CLAVE	605 · 606 · 607 · 608
mx-regimen-fiscal-nombre.txt	13	MX_REGIMEN_FISCAL_NOMBRE	Sueldos y Salarios e Ingresos Asimilados a Salarios · Arrendamiento · Régimen de Enajenación o Adquisición de Bienes · Demás ingresos
mx-religiones.txt	13	MX_RELIGION_LISTA	Católica · Protestante o cristiana evangélica · Pentecostal · Testigo de Jehová
mx-rfc-dv-1.txt	812	MX_RFC_DV_T1	AA,AA8 · AB,AB9 · AC,ACA · AD,AD0
mx-rfc-dv-2.txt	8,624	MX_RFC_DV_T2	OAA,AA1 · OAB,AB0 · OAC,ACA · OAD,AD9
mx-rfc-dv-3.txt	1,100	MX_RFC_DV_T3	000,000 · 001,018 · 002,025 · 003,032
mx-rfc-dv-4.txt	1,100	MX_RFC_DV_T4	000,000 · 001,016 · 002,021 · 003,037
mx-rfc-dv-5.txt	1,100	MX_RFC_DV_T5	000,000 · 001,014 · 002,028 · 003,031
mx-rfc-dv-6.txt	14,256	MX_RFC_DV_T6	0000,000 · 0010,019 · 0020,027 · 0030,035
mx-rfc-relleno.txt	38	MX_RFC_RELLENO_TABLA	0,0 · 1,1 · 2,2 · 3,3
mx-seguridad-social.txt	10	MX_SEGURIDAD_SOCIAL_LISTA	IMSS · ISSSTE · ISSSTE estatal · IMSS-Bienestar
mx-sexo-f-m.txt	2	MX_SEXO_F_M	F · M
mx-sexo-h-m.txt	2	MX_SEXO_H_M	H · M
mx-sexo-ingles.txt	2	MX_SEXO_INGLES	Female · Male
mx-sexo-mujer-hombre.txt	2	MX_SEXO_MUJER_HOMBRE	Mujer · Hombre
mx-sexo-palabra.txt	2	MX_SEXO_PALABRA	Femenino · Masculino

FILE	LINES	USED BY	FIRST LINES
mx-sin-informacion.txt	1	MX_SUPRIMIR	Sin información
mx-texto-nombres.txt	1,436	MX_TEXTO_LIBRE	María · MARÍA · Maria · MARIA
mx-vivienda.txt	6	MX_VIVIENDA_LISTA	Propia · Propia en proceso de pago · Rentada o alquilada · Prestada

Exclusion lists

Words that keep a column-name rule from matching when they follow it — so that `NOMBRE_PRODUCTO` is not taken for a person's name.

E1 producto prod articulo art item empresa emp compania razon comercial fantasia archivo arch file calle via colonia col municipio mpio mun alcaldia delegacion localidad estado edo entidad region ciudad pais banco sucursal plaza plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo colegio escuela plantel establecimiento institucion afore curso carrera materia documento doc centro unidad umf clinica hospital area depto departamento puesto sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua lugar local tienda almacen bodega proveedor prov convenio contrato poliza seguro aseguradora org organizacion dependencia entidad parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso regimen concepto impuesto moneda emisor comprobante cfdi uso pago forma metodo zona ruta linea giro actividad rama sector cliente cte cli paciente pac trabajador trab empleado colaborador alumno estudiante afiliado asegurado derechohabiente beneficiario benef titular madre padre tutor conyuge pareja medico doctor profesional responsable contacto emergencia aval obligado coacreditado deudor acreditado remitente destinatario receptor firmante testigo representante apoderado propietario arrendatario contratante victima denunciante imputado socio donante heredero persona pers conductor chofer vendedor ejecutivo agente solicitante usuario_?final ciudadano elector votante contribuyente jefe_(de_)?familia hijo hija familiar dependiente completos? y_?apellidos? apellidos?

E2 producto prod articulo art item empresa emp compania razon comercial fantasia archivo arch file calle via colonia col municipio mpio mun alcaldia delegacion localidad estado edo entidad region ciudad pais banco sucursal plaza plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo colegio escuela plantel establecimiento institucion afore curso carrera materia documento doc centro unidad umf clinica hospital area depto departamento puesto sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua lugar local tienda almacen bodega proveedor prov convenio contrato poliza seguro aseguradora org organizacion dependencia entidad parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso regimen concepto impuesto moneda emisor comprobante cfdi uso pago forma metodo zona ruta linea giro actividad rama sector cliente cte cli paciente pac trabajador trab empleado colaborador alumno estudiante afiliado asegurado derechohabiente beneficiario benef titular madre padre tutor conyuge pareja medico doctor profesional responsable contacto emergencia aval obligado coacreditado deudor acreditado remitente destinatario receptor firmante testigo representante apoderado propietario arrendatario contratante victima denunciante imputado socio donante heredero persona pers conductor chofer vendedor ejecutivo agente solicitante usuario_?final ciudadano elector votante contribuyente jefe_(de_)?familia hijo hija familiar dependiente completo compl full y_?apellidos? apellidos?

-
- E3** producto prod articulo art item empresa emp compania razon comercial fantasia archivo arch file calle via colonia col municipio mpio mun alcaldia delegacion localidad estado edo entidad region ciudad pais banco sucursal plaza plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo colegio escuela plantel establecimiento institucion afore curso carrera materia documento doc centro unidad umf clinica hospital area depto departamento puesto sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua lugar local tienda almacen bodega proveedor prov convenio contrato poliza seguro aseguradora org organizacion dependencia entidad parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso regimen concepto impuesto moneda emisor comprobante cfdi uso pago forma metodo zona ruta linea giro actividad rama sector completo
-
- E4** producto prod articulo art item empresa emp compania razon comercial fantasia archivo arch file calle via colonia col municipio mpio mun alcaldia delegacion localidad estado edo entidad region ciudad pais banco sucursal plaza plan campana proyecto servicio equipo tabla columna campo usuario user host servidor dominio marca modelo categoria tipo colegio escuela plantel establecimiento institucion afore curso carrera materia documento doc centro unidad umf clinica hospital area depto departamento puesto sistema app aplicacion grupo lista reporte informe proceso evento tarea perfil rol clase objeto cuenta medicamento farmaco diagnostico estudio programa beneficio partido sindicato religion etnia pueblo lengua lugar local tienda almacen bodega proveedor prov convenio contrato poliza seguro aseguradora org organizacion dependencia entidad parametro variable metodo funcion indice job script cola recurso red dispositivo plantilla template imagen foto pagina sitio modulo menu opcion accion permiso regimen concepto impuesto moneda emisor comprobante cfdi uso pago forma metodo zona ruta linea giro actividad rama sector
-
- E5** ip mac web url correo mail electronica email
-
- E6** producto prod serv prodserv articulo sucursal interna tipo registro primaria foranea elector electoral unica bancaria interbancaria municipio mun entidad ent localidad loc escuela centro cct clues sat producto servicio unidad plaza banco pais moneda regimen uso cfdi postal lada zona ageb area
-
- E7** imss issste sat federal estatal regional administrativa
-
- E8** fijo variable monto adicional servicio tarifa valor cuenta extra automatico recurrente domiciliado
-
- E9** medicos patologicos personales_?patologicos heredofamiliares gineco obstetricos familiares clinicos academicos laborales crediticios comerciales generales
-

APPENDIX D

Profile set and classifiers

The profile set `MX – LFPDPPP – v2` runs these 153 classifiers, with an assignment threshold of 60%.

Identificadores directos, cuasi-identificadores, datos sensibles (art. 2, VI) y datos financieros y patrimoniales (art. 7) de la LFPDPPP 2025.

CLASSIFIER	KIND	DOMAIN
<code>MX_L1_CURP – Path</code>	COLUMN NAME	<code>MX_L1_CURP</code>
<code>MX_L1_CURP – Type</code>	DATA TYPE	<code>MX_L1_CURP</code>
<code>MX_L1_CURP – Regex</code>	VALUE FORMAT	<code>MX_L1_CURP</code>
<code>MX_L1_RFC – Path</code>	COLUMN NAME	<code>MX_L1_RFC</code>
<code>MX_L1_RFC – Type</code>	DATA TYPE	<code>MX_L1_RFC</code>
<code>MX_L1_RFC – Regex</code>	VALUE FORMAT	<code>MX_L1_RFC</code>
<code>MX_L1_NSS – Path</code>	COLUMN NAME	<code>MX_L1_NSS</code>
<code>MX_L1_NSS – Type</code>	DATA TYPE	<code>MX_L1_NSS</code>
<code>MX_L1_NSS – Regex</code>	VALUE FORMAT	<code>MX_L1_NSS</code>
<code>MX_L1_CLAVE_ELECTOR – Path</code>	COLUMN NAME	<code>MX_L1_CLAVE_ELECTOR</code>
<code>MX_L1_CLAVE_ELECTOR – Type</code>	DATA TYPE	<code>MX_L1_CLAVE_ELECTOR</code>
<code>MX_L1_CLAVE_ELECTOR – Regex</code>	VALUE FORMAT	<code>MX_L1_CLAVE_ELECTOR</code>
<code>MX_L1_CREDENCIAL_INE – Path</code>	COLUMN NAME	<code>MX_L1_CREDENCIAL_INE</code>
<code>MX_L1_CREDENCIAL_INE – Regex</code>	VALUE FORMAT	<code>MX_L1_CREDENCIAL_INE</code>
<code>MX_L1_NOMBRE – Path</code>	COLUMN NAME	<code>MX_L1_NOMBRE</code>
<code>MX_L1_NOMBRE – List</code>	KNOWN VALUES	<code>MX_L1_NOMBRE</code>
<code>MX_L1_APELLIDO – Path</code>	COLUMN NAME	<code>MX_L1_APELLIDO</code>
<code>MX_L1_APELLIDO – List</code>	KNOWN VALUES	<code>MX_L1_APELLIDO</code>
<code>MX_L1_NOMBRE_COMPLETO – Path</code>	COLUMN NAME	<code>MX_L1_NOMBRE_COMPLETO</code>
<code>MX_L1_NOMBRE_COMPLETO – List</code>	KNOWN VALUES	<code>MX_L1_NOMBRE_COMPLETO</code>
<code>MX_L1_EMAIL – Path</code>	COLUMN NAME	<code>MX_L1_EMAIL</code>
<code>MX_L1_EMAIL – Type</code>	DATA TYPE	<code>MX_L1_EMAIL</code>
<code>MX_L1_EMAIL – Regex</code>	VALUE FORMAT	<code>MX_L1_EMAIL</code>
<code>MX_L1_TELEFONO – Path</code>	COLUMN NAME	<code>MX_L1_TELEFONO</code>
<code>MX_L1_TELEFONO – Regex</code>	VALUE FORMAT	<code>MX_L1_TELEFONO</code>
<code>MX_L1_DIRECCION – Path</code>	COLUMN NAME	<code>MX_L1_DIRECCION</code>
<code>MX_L1_DIRECCION – Type</code>	DATA TYPE	<code>MX_L1_DIRECCION</code>
<code>MX_L1_DIRECCION – Regex</code>	VALUE FORMAT	<code>MX_L1_DIRECCION</code>
<code>MX_L1_DIRECCION_COMPLEMENTO – Path</code>	COLUMN NAME	<code>MX_L1_DIRECCION_COMPLEMENTO</code>
<code>MX_L1_CLABE – Path</code>	COLUMN NAME	<code>MX_L1_CLABE</code>
<code>MX_L1_CLABE – Type</code>	DATA TYPE	<code>MX_L1_CLABE</code>

CLASSIFIER	KIND	DOMAIN
MX_L1_CLABE – Regex	VALUE FORMAT	MX_L1_CLABE
MX_L1_CUENTA_BANCARIA – Path	COLUMN NAME	MX_L1_CUENTA_BANCARIA
MX_L1_TARJETA – Path	COLUMN NAME	MX_L1_TARJETA
MX_L1_TARJETA – Regex	VALUE FORMAT	MX_L1_TARJETA
MX_L1_PASAPORTE – Path	COLUMN NAME	MX_L1_PASAPORTE
MX_L1_PASAPORTE – Regex	VALUE FORMAT	MX_L1_PASAPORTE
MX_L1_DOCUMENTO_MIGRATORIO – Path	COLUMN NAME	MX_L1_DOCUMENTO_MIGRATORIO
MX_L1_CEDULA_PROFESIONAL – Path	COLUMN NAME	MX_L1_CEDULA_PROFESIONAL
MX_L1_CEDULA_PROFESIONAL – Regex	VALUE FORMAT	MX_L1_CEDULA_PROFESIONAL
MX_L1_LICENCIA_CONducIR – Path	COLUMN NAME	MX_L1_LICENCIA_CONducIR
MX_L1_EFIRMA – Path	COLUMN NAME	MX_L1_EFIRMA
MX_L1_EFIRMA – Regex	VALUE FORMAT	MX_L1_EFIRMA
MX_L1_IP – Path	COLUMN NAME	MX_L1_IP
MX_L1_IP – Regex	VALUE FORMAT	MX_L1_IP
MX_L1_DISPOSITIVO – Path	COLUMN NAME	MX_L1_DISPOSITIVO
MX_L1_DISPOSITIVO – Regex	VALUE FORMAT	MX_L1_DISPOSITIVO
MX_L1_PLACA – Path	COLUMN NAME	MX_L1_PLACA
MX_L1_PLACA – Regex	VALUE FORMAT	MX_L1_PLACA
MX_L1_NIV – Path	COLUMN NAME	MX_L1_NIV
MX_L1_NIV – Regex	VALUE FORMAT	MX_L1_NIV
MX_L1_NUMERO_CONTRATO – Path	COLUMN NAME	MX_L1_NUMERO_CONTRATO
MX_L1_USUARIO_RRSS – Path	COLUMN NAME	MX_L1_USUARIO_RRSS
MX_L1_CREDENCIAL – Path	COLUMN NAME	MX_L1_CREDENCIAL
MX_L1_GEOLOCALIZACION – Path	COLUMN NAME	MX_L1_GEOLOCALIZACION
MX_L1_GEOLOCALIZACION – Regex	VALUE FORMAT	MX_L1_GEOLOCALIZACION
MX_L1_TEXTO_LIBRE – Path	COLUMN NAME	MX_L1_TEXTO_LIBRE
MX_L1_TEXTO_LIBRE – Type	DATA TYPE	MX_L1_TEXTO_LIBRE
MX_L1_TEXTO_LIBRE – Regex	VALUE FORMAT	MX_L1_TEXTO_LIBRE
MX_L2_FECHA_NACIMIENTO – Path	COLUMN NAME	MX_L2_FECHA_NACIMIENTO
MX_L2_FECHA_NACIMIENTO – Type	DATA TYPE	MX_L2_FECHA_NACIMIENTO
MX_L2_ANIO_NACIMIENTO – Path	COLUMN NAME	MX_L2_ANIO_NACIMIENTO
MX_L2_ANIO_NACIMIENTO – Type	DATA TYPE	MX_L2_ANIO_NACIMIENTO
MX_L2_EDAD – Path	COLUMN NAME	MX_L2_EDAD
MX_L2_EDAD – Type	DATA TYPE	MX_L2_EDAD
MX_L2_FECHA_EVENTO – Path	COLUMN NAME	MX_L2_FECHA_EVENTO
MX_L2_FECHA_EVENTO – Type	DATA TYPE	MX_L2_FECHA_EVENTO
MX_L2_SEX0 – Path	COLUMN NAME	MX_L2_SEX0

CLASSIFIER	KIND	DOMAIN
MX_L2_SEX0 - List	KNOWN VALUES	MX_L2_SEX0
MX_L2_MUNICIPIO - Path	COLUMN NAME	MX_L2_MUNICIPIO
MX_L2_MUNICIPIO - List	KNOWN VALUES	MX_L2_MUNICIPIO
MX_L2_CLAVE_MUNICIPIO - Path	COLUMN NAME	MX_L2_CLAVE_MUNICIPIO
MX_L2_CLAVE_MUNICIPIO - Type	DATA TYPE	MX_L2_CLAVE_MUNICIPIO
MX_L2_CLAVE_MUNICIPIO - List	KNOWN VALUES	MX_L2_CLAVE_MUNICIPIO
MX_L2_LOCALIDAD - Path	COLUMN NAME	MX_L2_LOCALIDAD
MX_L2_COLONIA - Path	COLUMN NAME	MX_L2_COLONIA
MX_L2_CODIGO_POSTAL - Path	COLUMN NAME	MX_L2_CODIGO_POSTAL
MX_L2_CODIGO_POSTAL - Regex	VALUE FORMAT	MX_L2_CODIGO_POSTAL
MX_L2_NACIONALIDAD - Path	COLUMN NAME	MX_L2_NACIONALIDAD
MX_L2_NACIONALIDAD - List	KNOWN VALUES	MX_L2_NACIONALIDAD
MX_L2_ESTADO_CIVIL - Path	COLUMN NAME	MX_L2_ESTADO_CIVIL
MX_L2_ESTADO_CIVIL - List	KNOWN VALUES	MX_L2_ESTADO_CIVIL
MX_L2_OCUPACION - Path	COLUMN NAME	MX_L2_OCUPACION
MX_L2_EMPLEADOR - Path	COLUMN NAME	MX_L2_EMPLEADOR
MX_L2_ESCOLARIDAD - Path	COLUMN NAME	MX_L2_ESCOLARIDAD
MX_L2_ESCOLARIDAD - List	KNOWN VALUES	MX_L2_ESCOLARIDAD
MX_L2_ESCUELA - Path	COLUMN NAME	MX_L2_ESCUELA
MX_L2_CCT - Path	COLUMN NAME	MX_L2_CCT
MX_L2_CCT - Regex	VALUE FORMAT	MX_L2_CCT
MX_L2_DEPENDIENTES - Path	COLUMN NAME	MX_L2_DEPENDIENTES
MX_L2_DEPENDIENTES - Type	DATA TYPE	MX_L2_DEPENDIENTES
MX_L3_ETNIA - Path	COLUMN NAME	MX_L3_ETNIA
MX_L3_ETNIA - List	KNOWN VALUES	MX_L3_ETNIA
MX_L3 LENGUA_INDIGENA - Path	COLUMN NAME	MX_L3 LENGUA_INDIGENA
MX_L3 LENGUA_INDIGENA - List	KNOWN VALUES	MX_L3 LENGUA_INDIGENA
MX_L3_SALUD_DIAGNOSTICO - Path	COLUMN NAME	MX_L3_SALUD_DIAGNOSTICO
MX_L3_SALUD_DIAGNOSTICO - Regex	VALUE FORMAT	MX_L3_SALUD_DIAGNOSTICO
MX_L3_SALUD_MEDICAMENTO - Path	COLUMN NAME	MX_L3_SALUD_MEDICAMENTO
MX_L3_SALUD_MEDICAMENTO - List	KNOWN VALUES	MX_L3_SALUD_MEDICAMENTO
MX_L3_SALUD_IDENTIFICADOR - Path	COLUMN NAME	MX_L3_SALUD_IDENTIFICADOR
MX_L3_SALUD_TEXTO_CLINICO - Path	COLUMN NAME	MX_L3_SALUD_TEXTO_CLINICO
MX_L3_SALUD_TEXTO_CLINICO - Type	DATA TYPE	MX_L3_SALUD_TEXTO_CLINICO
MX_L3_SALUD_RESULTADO_EXAMEN - Path	COLUMN NAME	MX_L3_SALUD_RESULTADO_EXAMEN
MX_L3_SALUD_GRUPO_SANGUINEO - Path	COLUMN NAME	MX_L3_SALUD_GRUPO_SANGUINEO
MX_L3_SALUD_GRUPO_SANGUINEO - List	KNOWN VALUES	MX_L3_SALUD_GRUPO_SANGUINEO

CLASSIFIER	KIND	DOMAIN
MX_L3_SALUD_DISCAPACIDAD – Path	COLUMN NAME	MX_L3_SALUD_DISCAPACIDAD
MX_L3_SALUD_DISCAPACIDAD – List	KNOWN VALUES	MX_L3_SALUD_DISCAPACIDAD
MX_L3_SALUD_SEXUAL_REPRODUCTIVA – Path	COLUMN NAME	MX_L3_SALUD_SEXUAL_REPRODUCTIVA
MX_L3_SALUD_MENTAL_ADICCIONES – Path	COLUMN NAME	MX_L3_SALUD_MENTAL_ADICCIONES
MX_L3_BIOMETRICO – Path	COLUMN NAME	MX_L3_BIOMETRICO
MX_L3_BIOMETRICO – Type	DATA TYPE	MX_L3_BIOMETRICO
MX_L3_INFORMACION_GENETICA – Path	COLUMN NAME	MX_L3_INFORMACION_GENETICA
MX_L3_PREFERENCIA_SEXUAL – Path	COLUMN NAME	MX_L3_PREFERENCIA_SEXUAL
MX_L3_PREFERENCIA_SEXUAL – List	KNOWN VALUES	MX_L3_PREFERENCIA_SEXUAL
MX_L3_IDENTIDAD_GENERO – Path	COLUMN NAME	MX_L3_IDENTIDAD_GENERO
MX_L3_IDENTIDAD_GENERO – List	KNOWN VALUES	MX_L3_IDENTIDAD_GENERO
MX_L3_VIDA_SEXUAL – Path	COLUMN NAME	MX_L3_VIDA_SEXUAL
MX_L3_RELIGION – Path	COLUMN NAME	MX_L3_RELIGION
MX_L3_RELIGION – List	KNOWN VALUES	MX_L3_RELIGION
MX_L3_CREENCIA_FILOSOFICA_MORAL – Path	COLUMN NAME	MX_L3_CREENCIA_FILOSOFICA_MORAL
MX_L3_OPINION_POLITICA – Path	COLUMN NAME	MX_L3_OPINION_POLITICA
MX_L3_OPINION_POLITICA – List	KNOWN VALUES	MX_L3_OPINION_POLITICA
MX_L3_AFILIACION_POLITICA – Path	COLUMN NAME	MX_L3_AFILIACION_POLITICA
MX_L3_AFILIACION_POLITICA – List	KNOWN VALUES	MX_L3_AFILIACION_POLITICA
MX_L3_AFILIACION_SINDICAL – Path	COLUMN NAME	MX_L3_AFILIACION_SINDICAL
MX_L3_AFILIACION_SINDICAL – List	KNOWN VALUES	MX_L3_AFILIACION_SINDICAL
MX_FIN_BURO_CREDITO – Path	COLUMN NAME	MX_FIN_BURO_CREDITO
MX_FIN_MONTO_DEUDA – Path	COLUMN NAME	MX_FIN_MONTO_DEUDA
MX_FIN_MONTO_DEUDA – Type	DATA TYPE	MX_FIN_MONTO_DEUDA
MX_FIN_INGRESO_MENSUAL – Path	COLUMN NAME	MX_FIN_INGRESO_MENSUAL
MX_FIN_INGRESO_MENSUAL – Type	DATA TYPE	MX_FIN_INGRESO_MENSUAL
MX_FIN_SALARIO_DIARIO – Path	COLUMN NAME	MX_FIN_SALARIO_DIARIO
MX_FIN_SALARIO_DIARIO – Type	DATA TYPE	MX_FIN_SALARIO_DIARIO
MX_FIN_PATRIMONIO – Path	COLUMN NAME	MX_FIN_PATRIMONIO
MX_FIN_PATRIMONIO – Type	DATA TYPE	MX_FIN_PATRIMONIO
MX_FIN_AFORE – Path	COLUMN NAME	MX_FIN_AFORE
MX_FIN_AFORE – List	KNOWN VALUES	MX_FIN_AFORE
MX_FIN_SALDO_RETIRO – Path	COLUMN NAME	MX_FIN_SALDO_RETIRO
MX_FIN_SALDO_RETIRO – Type	DATA TYPE	MX_FIN_SALDO_RETIRO
MX_FIN_CREDITO_VIVIENDA – Path	COLUMN NAME	MX_FIN_CREDITO_VIVIENDA
MX_FIN_CREDITO_VIVIENDA – List	KNOWN VALUES	MX_FIN_CREDITO_VIVIENDA
MX_FIN_SEGURIDAD_SOCIAL – Path	COLUMN NAME	MX_FIN_SEGURIDAD_SOCIAL

CLASSIFIER	KIND	DOMAIN
MX_FIN_SEGURIDAD_SOCIAL - List	KNOWN VALUES	MX_FIN_SEGURIDAD_SOCIAL
MX_FIN_PROGRAMA_SOCIAL - Path	COLUMN NAME	MX_FIN_PROGRAMA_SOCIAL
MX_FIN_PROGRAMA_SOCIAL - List	KNOWN VALUES	MX_FIN_PROGRAMA_SOCIAL
MX_FIN_NIVEL_SOCIOECONOMICO - Path	COLUMN NAME	MX_FIN_NIVEL_SOCIOECONOMICO
MX_FIN_NIVEL_SOCIOECONOMICO - List	KNOWN VALUES	MX_FIN_NIVEL_SOCIOECONOMICO
MX_FIN_VIVIENDA - Path	COLUMN NAME	MX_FIN_VIVIENDA
MX_FIN_VIVIENDA - List	KNOWN VALUES	MX_FIN_VIVIENDA
MX_FIN_REGIMEN_FISCAL - Path	COLUMN NAME	MX_FIN_REGIMEN_FISCAL
MX_PENAL_ANTECEDENTES - Path	COLUMN NAME	MX_PENAL_ANTECEDENTES
MX_PENAL_CAUSA - Path	COLUMN NAME	MX_PENAL_CAUSA
MX_PENAL_CAUSA - Regex	VALUE FORMAT	MX_PENAL_CAUSA