



JavaScript HTML DOM EventListener

[< Previous](#)[Next >](#)

The addEventListener() method

Example

Add an event listener that fires when a user clicks a button:

```
"color:black">"color:red">
document."color:black">getElementById("color:brown">"myBtn")."c
olor:black">addEventListener("color:brown">"click",
displayDate);
```

[Try it Yourself »](#)

The addEventListener() method attaches an event handler to the specified element.

The addEventListener() method attaches an event handler to an element without overwriting existing event handlers.

You can add many event handlers to one element.

You can add many event handlers of the same type to one element, i.e two "click" events.

You can add event listeners to any DOM object not only HTML elements. i.e the window object.

The `addEventListener()` method makes it easier to control how the event reacts to bubbling.

When using the `addEventListener()` method, the JavaScript is separated from the HTML markup, for better readability and allows you to add event listeners even when you do not control the HTML markup.

You can easily remove an event listener by using the `removeEventListener()` method.

Syntax

```
element.addEventListener(event, function, useCapture);
```

The first parameter is the type of the event (like "click" or "mousedown").

The second parameter is the function we want to call when the event occurs.

The third parameter is a boolean value specifying whether to use event bubbling or event capturing. This parameter is optional.

Note that you don't use the "on" prefix for the event; use "click" instead of "onclick".

Add an Event Handler to an Element

Example

Alert "Hello World!" when the user clicks on an element:

```
"color:black">"color:red">
element."color:black">addEventListener("color:brown">"click",
"color:mediumblue">function(){ alert("color:brown">"Hello
World!"); });
```

Try it Yourself »

You can also refer to an external "named" function:

Example

Alert "Hello World!" when the user clicks on an element:

```
"color:black">"color:red">
element."color:black">addEventListener("color:brown">"click",
myFunction);

"color:mediumblue">function myFunction() {
    alert ("color:brown">"Hello World!");
}
```

Try it Yourself »



Add Many Event Handlers to the Same Element

The `addEventListener()` method allows you to add many events to the same element, without overwriting existing events:

Example

```
"color:black">"color:red">
element."color:black">addEventListener("color:brown">"click",
myFunction);
"color:red">
element."color:black">addEventListener("color:brown">"click",
mySecondFunction);
"color:red">
```

[Try it Yourself »](#)

You can add events of different types to the same element:

Example

```
"color:black">
element."color:black">addEventListener("color:brown">"mouseover", myFunction);
element."color:black">addEventListener("color:brown">"click", mySecondFunction);
element."color:black">addEventListener("color:brown">"mouseout", myThirdFunction);
```

[Try it Yourself »](#)

Add an Event Handler to the Window Object

The `addEventListener()` method allows you to add event listeners on any HTML DOM object such as HTML elements, the HTML document, the window object, or other objects that support events, like the `xmlHttpRequest` object.

Example

Add an event listener that fires when a user resizes the window:

```
"color:black">
window."color:black">addEventListener("color:brown">"resize",
"color:mediumbblue">function() {
"color:red">
    document."color:black">getElementById("color:brown">"demo")
."color:black">innerHTML = sometext;
"color:red"> });"color:red">
```

Try it Yourself »

Passing Parameters

When passing parameter values, use an "anonymous function" that calls the specified function with the parameters:

Example

```
"color:black">
element."color:black">addEventListener("color:brown">"click",
"color:mediumbblue">function() { myFunction(p1, p2);
});"color:red">
```

Try it Yourself »

Event Bubbling or Event Capturing?

There are two ways of event propagation in the HTML DOM, bubbling and capturing.

Event propagation is a way of defining the element order when an event occurs. If you have a <p> element inside a <div> element, and the user clicks on the <p> element, which element's "click" event should be handled first?

In *bubbling* the inner most element's event is handled first and then the outer: the <p> element's click event is handled first, then the <div> element's click event.

In *capturing* the outer most element's event is handled first and then the inner: the

<div> element's click event will be handled first, then the <p> element's click event.

With the `addEventListener()` method you can specify the propagation type by using the "useCapture" parameter:

```
addEventListener(event, function, useCapture);
```

The default value is false, which will use the bubbling propagation, when the value is set to true, the event uses the capturing propagation.

Example

```
"color:black">
document."color:black">getElementById("color:brown">"myP")."color:black">addEventListener("color:brown">"click", myFunction, "color:mediumblue">true);
document."color:black">getElementById("color:brown">"myDiv")."color:black">addEventListener("color:brown">"click", myFunction, "color:mediumblue">true);"color:red">
```

[Try it Yourself »](#)

The removeEventListener() method

The `removeEventListener()` method removes event handlers that have been attached with the `addEventListener()` method:






Example

```
"color:black">
element."color:black">removeEventListener("color:brown">"mouseover", myFunction);
```

[Try it Yourself »](#)

Browser Support

The numbers in the table specifies the first browser version that fully supports these methods.

Method					
<code>addEventListener()</code>	1.0	9.0	1.0	1.0	7.0
<code>removeEventListener()</code>	1.0	9.0	1.0	1.0	7.0

Note: The `addEventListener()` and `removeEventListener()` methods are not supported in IE 8 and earlier versions and Opera 6.0 and earlier versions. However, for these specific browser versions, you can use the `attachEvent()` method to attach an event handlers to the element, and the `detachEvent()` method to remove it:

```
element.attachEvent(event, function);  
element.detachEvent(event, function);
```

Example

Cross-browser solution:

```
"color:black"> "color:mediumblue">var x =  
document."color:black">getElementById("color:brown">"myBtn");  
"color:mediumblue">if (x."color:black">addEventListener)  
{  
    "color:red"> "color:green">// For all  
major browsers, except IE 8 and earlier  
    x."color:black">addEventListener("color:brown">"click",  
myFunction);  
} "color:mediumblue">else "color:mediumblue">if  
(x."color:black">attachEvent) {  
    "color:red">  
"color:green">// For IE 8 and earlier versions  
    x."color:black">attachEvent("color:brown">"onclick",  
myFunction);  
}"color:red">
```

HTML DOM Event Object Reference

For a list of all HTML DOM events, look at our complete [HTML DOM Event Object Reference](#).

[◀ Previous](#)[Next ▶](#)

COLOR PICKER



HOW TO

Tabs
Dropdowns
Accordions
Convert Weights
Animated Buttons
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE



CERTIFICATES

HTML, CSS, JavaScript, PHP, jQuery, Bootstrap and XML.

[Read More »](#)



Get Certified
in HTML, CSS
and JavaScript



Learn How to Build a Website





[REPORT ERROR](#)
[PRINT PAGE](#)
[FORUM](#)
[ABOUT](#)

Top 10 Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[SQL Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Angular Tutorial](#)
[How To Tutorial](#)

Top 10 References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[SQL Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)
[AngularJS Reference](#)

Top 10 Examples

[HTML Examples](#)
[CSS Examples](#)

[JavaScript Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[HTML DOM Examples](#)
[PHP Examples](#)
[jQuery Examples](#)
[Angular Examples](#)
[XML Examples](#)

Web Certificates

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[jQuery Certificate](#)
[PHP Certificate](#)
[Bootstrap Certificate](#)
[XML Certificate](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2018 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

