Original Manuscript ID: Access-2026-49092
Original Article Title: What Held-Out Scores Predict About Deploying Intrusion Detection in O-RAN
Revised Article Title: Cross-Corpus Evaluation of 5G Flow Intrusion Detectors: Label Faults, Transfer, and Alert Burden

To: IEEE Access Editor
Re: Response to reviewers

Dear Editor,

Thank you for allowing a resubmission of our manuscript, with an opportunity to address the reviewers' comments.

We are uploading (a) our point-by-point response to the comments (below) (response to reviewers, under "Author's Response Files"), (b) an updated manuscript with yellow highlighting indicating changes (as "Highlighted PDF"), and (c) a clean updated manuscript without highlights ("Main Manuscript").

The two reports found one error that changed our results, showed that our title and test promised more than the corpora support, and asked for evidence we had not collected. We ran new experiments for most of the points. Below, each reviewer comment is quoted in full, followed by our response and the action taken. For convenience, the revised manuscript, with the changes made in response to the reviewers highlighted in yellow, is appended to this letter. Each concern heading, and each section, table, figure and page we cite, is a link to the corresponding page of the appended manuscript; page numbers refer to the revised manuscript.

Best regards,
Arshad Ali et al.

Summary of the main changes

1. **Reframing (R1.1, R2.1).** The paper is now a cross-corpus study of 5G flow detectors, with a separate latency measurement for window-level detectors. The new title, the abstract, the introduction (scope paragraph), Fig. 1 (p. 3), and Section III (p. 2) state that only one corpus is O-RAN and that no detector is evaluated on all criteria. Latency is no longer a term of the test.
2. **An error in byte accounting, corrected (R1.9).** The reviewer was right that a 2-byte gap is not a link-layer header. The gap is 14 bytes: Argus counts the Ethernet header of every packet. Our "40 against 42 bytes" compared a TCP minimum with a UDP minimum. We now remove the header for 5G-NIDD as for the third corpus and re-ran *every* experiment that puts 5G-NIDD in the shared space (Section IV-B (p. 4)).
3. **The 5G-NIDD finding, confirmed in the raw captures (R2.2, R1.14).** In the UDP-flood session, station 1's capture file contains every one of the 656,180 packets of station 2's file, with identical timestamps; in the other nine sessions the two files share no packet (Section V-A (p. 6), Fig. 2 (p. 6)). This explains the asymmetry, and the network description explains how it is possible. We release corrected labels, added a relabeled arm, and reported the finding to the dataset authors.
4. **References with intervals on matched flows (R1.4–R1.6, R2.3).** New in-target references: 20 random splits, leave-one-capture-file-out (every file held out once, both UDP-flood files included, every flow predicted once), and base-station references with repeated training samples, all with intervals, compared with transfer on the same flows (Table 5 (p. 8)).
5. **Statistics for clustered data (R2.4, R1.11).** Corrected intervals with the variance ratio computed from group counts for every comparison and for both terms of the test; a cluster bootstrap was tried and is documented as unreliable on these data; the split composition and category coverage are reported; unadjusted intervals and Holm-adjusted marks are labeled in every table (Section IV-E (p. 5), Section IV-D (p. 5)).
6. **A redesigned test (R1.7, R1.8, R2.5).** Both terms use the same intervals and have three outcomes (pass, fail, inconclusive); the alert threshold is fixed on source data, and a threshold searched on the target appears only as an optimistic bound. The bounds are stated as ours, with the false positive rate they imply (Section III-C (p. 3), Section V-D (p. 9)).
7. **Adaptation (R1.12, R2.6).** Importance weighting and domain-adversarial training (DANN) join CORAL, and a label-efficient arm adds $k \in \{1, 2, 4, 8\}$ labeled 5G-NIDD capture files (Section V-C (p. 7)). Claims are narrowed to the detectors tested.
8. **Radio layer (R1.2, R1.3).** The abstract and conclusion say that the radio effect is not significant; a new experiment groups by the 42 documented runs (Table 9 (p. 11)). Radio operating figures were removed.

9. **Latency (R1.13)** is one condensed subsection; the flow-level estimate and the sentence implying that flow detectors failed the latency term were removed.

10. **Presentation (R1.15, R2.7, R2.8).** Three contributions instead of seven; a shorter abstract with four results; 10 tables instead of 14 and 7 figures instead of 10; a redrawn Fig. 1 (p. 3); every sentence revised; split counts in every caption.

To keep the paper focused, we removed the calibration and prior-shift analysis, the sequence models, the benign-only novelty detectors, the per-call latency table, and three figures (reliability, radio protocol plot, latency distribution). They remain in the repository.

Index of responses

Each item links to our response below, and each location in the last column links to that page of the appended manuscript.

Item	Reviewer's concern	What we did	Where in the revised paper
R1.1	Scope: no detector on all terms; two corpora not O-RAN	Reframed as a cross-corpus study; new title; Fig. 1 redrawn; latency removed from the test	Title, Abstract (p. 1), Section I (p. 1), Fig. 1 (p. 3), Section III-C (p. 3)
R1.2	Radio result not significant	Stated in abstract and conclusion; new run-grouped experiment (42 runs)	Section V-E (p. 10), Table 9 (p. 11), Section IX (p. 13)
R1.3	Radio corpus cannot support operating figures	All radio operating figures removed	Section V-E (p. 10), Fig. 7 (p. 11), Section VII (p. 12)
R1.4	In-target references lack uncertainty	New references, 20 splits, with intervals	Section IV-D (p. 5), Section V-B (p. 7), Table 5 (p. 8)
R1.5	Capture-file reference not comparable	Leave-one-file-out reference on matched flows	Section IV-D (p. 5), Table 5 (p. 8)
R1.6	Clean-label gap mostly not significant	Claims narrowed to what is significant	Section V-B (p. 7), Table 5 (p. 8), Fig. 3 (p. 7)
R1.7	Test treats uncertainty inconsistently	Test redesigned: same intervals for both terms, three outcomes	Section III-C (p. 3), Section IV-E (p. 5), Table 8 (p. 10)
R1.8	Verdict set by our own bounds	Bounds stated as ours, with the FPR they imply	Abstract (p. 1), Section III-C (p. 3), Fig. 6 (p. 11)
R1.9	Byte harmonization error	Error confirmed (14-byte Ethernet header), corrected, all experiments re-run	Section IV-B (p. 4), Table 2 (p. 5), Fig. 4 (p. 9)
R1.10	Zeek result overstated	Removed from abstract; reported with its limits	Section V-C (p. 7), Section VII (p. 12)
R1.11	Flow-split category coverage	New coverage analysis per category and split	Section IV-D (p. 5)
R1.12	Claims beyond the detectors tested	Two more adaptation methods; claims narrowed	Section V-C (p. 7), Table 7 (p. 9), Fig. 5 (p. 10)
R1.13	Latency results add little	Condensed to one subsection; flow estimate removed	Section V-F (p. 11), Table 10 (p. 12)
R1.14	5G-NIDD reading needs confirmation	Authors contacted; packet-level proof; results under three label views	Section V-A (p. 6), Fig. 2 (p. 6)
R1.15	Presentation	Three findings; fewer tables and figures; text revised	Whole paper; Section I (p. 1), Fig. 1 (p. 3)
R2.1	Scope and framing	Limitation stated in abstract and test; title qualified	Abstract (p. 1), Section I (p. 1), Section III-C (p. 3)
R2.2	5G-NIDD label conflict (a)–(e)	Raw-pcap proof, asymmetry explained, authors contacted, corrected labels, relabeled arm	Section V-A (p. 6), Fig. 2 (p. 6), Table 5 (p. 8)
R2.3	Comparability of the references	References on matched flows	Section IV-D (p. 5), Table 5 (p. 8)
R2.4	Statistics on grouped data	Group-count correction; bootstrap tried and documented; captions fixed	Section IV-E (p. 5), Section IV-D (p. 5)
R2.5	Design of the deployability test	See R1.7 and R1.8	Section III-C (p. 3), Table 8 (p. 10)
R2.6	Adaptation	Importance weighting, DANN, label-efficient arm	Section V-C (p. 7), Table 7 (p. 9), Fig. 5 (p. 10)
R2.7	Simplify the abstract	Rewritten around four results	Abstract (p. 1)
R2.8	Sample sizes and split counts	Justified; sample-size check; split counts in captions	Section IV-D (p. 5), all captions

Reviewer 1

Reviewer #1, Concern #1

> *The paper's title and abstract promise an answer on deploying detection in O-RAN, but no detector is evaluated on all three terms of Eq. (6). The flow detectors get generalization and alert terms. Their latency was not measured, and Section VII-A states that E2 does not carry flow records, so Lane B of Fig. 1 is an assumption. The window detectors get a latency term but have no transfer target. Table 14 therefore takes Bmin from different detectors than the verdict. Two of three corpora are not O-RAN either: 5G-NIDD is a 5G test network and DC is an Open5GS core in Docker. Either evaluate one detector on all three terms, or reframe the paper as a cross corpus study of 5G flow detectors plus a separate latency measurement.*

Author response: We agree with every part of this comment. Evaluating one detector on all three terms is not possible with the public data: the radio detectors have no second corpus with radio telemetry, and E2 provides no path for flow records, so a flow detector's latency through a RIC would rest on a transport we would have to invent. We therefore took the second option and reframed the paper as a cross-corpus study of 5G flow detectors with a separate latency measurement.

Author action:

- New title: *Cross-Corpus Evaluation of 5G Flow Intrusion Detectors: Label Faults, Transfer, and Alert Burden*.
- The abstract and a new scope paragraph in the introduction (Section I (p. 1)) state that only NetsLab-5GORAN-IDD is an O-RAN corpus, that the cross-corpus results concern flow-level detectors on 5G traffic, that radio detectors are evaluated within one corpus, that latency is measured separately for window-level detectors, and that no detector is evaluated on all criteria.
- Fig. 1 (p. 3) was redrawn: lane B's path into the xApp is drawn dashed and labeled as an assumption ("E2 carries no flow records"), each measurement marker sits on the lane it was measured on (generalization and alert burden on lane B, latency on lane A), and the legend says that no detector was evaluated on all three.
- The deployability test (Section III-C (p. 3)) now has two terms, generalization and alert burden, both measured on the same flow detectors. Latency is reported separately (Section V-F (p. 11)) and no longer enters any verdict, so the former Table 14 with $B_{\min}$ from other detectors is gone.

Reviewer #1, Concern #2

> *The radio result you lead with is not significant. The random split gain of 0.13 has a corrected interval of -0.01 to 0.27 (p = 0.06), and no architecture survives Holm correction (Table 3). Say so in the abstract and conclusion, or add power. One option is to group by the 42 documented runs instead of 30 five minute sessions and report how the result depends on that choice.*

Author response: We did both. The radio result no longer leads: it is a secondary result, and the abstract and conclusion state that it is not significant. We also ran the suggested experiment (EXP-070): the whole protocol comparison repeated with the 42 runs as groups, with windows rebuilt within each run so that no window straddles two runs. Following Reviewer 2 (R2.4), the corrected intervals now use group counts. Grouped by sessions, the average gain is 0.13 with interval $[-0.03, 0.30]$ ($p = 0.11$); grouped by runs, it is 0.15 with interval $[-0.02, 0.33]$ ($p = 0.08$). No architecture's gain is significant after Holm correction under either grouping (zero and zero of six). The conclusion therefore does not depend on the grouping. One choice does matter, and we report it: with window counts instead of group counts in the correction (the first submission's choice), the interval of the run-grouped average would be [0.01, 0.29].

Author action: Abstract and Section IX (p. 13): the radio gain is reported as not significant. Section V-E (p. 10) and the new Table 9 (p. 11) give both groupings; Section IV-A (p. 4) describes how runs are recovered.

Reviewer #1, Concern #3

> *The radio corpus cannot support operational figures. 2,808 windows at 76.46% attacks leaves about 660 benign windows, roughly three hours of data, recorded mostly with one UE six weeks before the attacks. Your own Fig. 3 shows per-session FPR from 0 to 0.98, and the pooled FPR interval spans 0.01 to 0.65. Presenting 50 to 74 false alerts per benign UE-hour in Section VII-A as an operating figure is not justified.*

Author response: The reviewer is right. The radio layer holds 661 benign windows, about 3 hours of data, and its false positive rate depends on which benign session a detector meets.

Author action: All radio operating figures were removed: the radio rows of the former Table 13, the radio panel of the former precision-versus-threshold figure, and the false alerts per UE-hour in the discussion. Section V-E (p. 10) now states why the radio layer supports no operating figure, with the per-session spread (Fig. 7 (p. 11)) and the bootstrap interval as the evidence, and the limitations say so too (Section VII (p. 12)).

Reviewer #1, Concern #4

> *The in-target references have no uncertainty. Table 5 uses one to three samples per protocol with no intervals, and the station references have n = 1. Yet the abstract compares transfer (0.61 to 0.78) against these references (0.842 to 0.982). Run them with the same 20 splits and corrected intervals as the transfer.*

Author response: We re-ran all references (EXP-068) on the corrected bytes, with training that never sees the flood copies as benign, in three designs, all on 240,000 training flows, the size of the transfer training sets:

- a random split with the same 20 split seeds as the transfer and corrected intervals: 0.98 to 0.99;
- leave-one-capture-file-out, which holds out each of the 20 capture files once and therefore predicts every flow of 5G-NIDD exactly once, on the same flows as the transfer: 0.96 to 0.98;
- base station to base station, with ten training samples per direction and intervals over them: 0.97 to 0.99 from station 1 to station 2 and 0.97 to 0.99 in the other direction.

The abstract now compares transfer with the leave-one-capture-file-out reference on the same flows, and gives the shortfall of the tree-based models (0.12 to 0.19). The shortfall of every architecture has its own corrected interval.

Author action: Section IV-D (p. 5) (design), Section V-B (p. 7) and Table 5 (p. 8) (results), abstract.

Reviewer #1, Concern #5

> *The capture file reference is not comparable. Section VI-C says no held-out set contained a UDP flood file, while the transfer is evaluated on all files including both flood files. The 0.982 upper end was never tested on the hardest traffic. Force each flood file into a held-out set.*

Author response: Leave-one-capture-file-out holds out every file once, so both UDP-flood files are held out. Trained without the copies labeled as benign, the reference reaches 0.986 to 0.999 on each held-out UDP-flood file: the flood traffic was hard because of the conflicting labels, not because of its content.

Author action: Section IV-D (p. 5), Section V-B (p. 7), Table 5 (p. 8).

Reviewer #1, Concern #6

> *On clean labels the transfer gap is mostly not significant. Without the copies, the loss against held-out source data is significant for one of six architectures. The claim that transfer falls short then rests on the references criticized above, which have no intervals. Weaken the claim or strengthen the evidence.*

Author response: We weakened one claim and strengthened the evidence for the other, and the manuscript now keeps the two apart.

- *Against held-out source data*, the loss on consistent labels is significant only for LR after Holm correction (one of six). With the byte correction, the four tree-based models score as well on 5G-NIDD as on held-out NetsLab data (loss -0.01 to 0.04). We no longer claim that they fall short of their source performance.
- *Against what the target itself allows*, transfer falls short of the leave-one-capture-file-out reference on the same flows by 0.12 to 0.35 (0.12 to 0.19 for the tree-based models), significantly after Holm correction for three of six architectures. The source score is a poor yardstick here, because 5G-NIDD is easier than held-out NetsLab data.

Author action: Section V-B (p. 7), Table 5 (p. 8), Fig. 3 (p. 7), abstract, and conclusion.

Reviewer #1, Concern #7

> *The test in Eq. (6) treats uncertainty inconsistently. The generalization term uses the upper 95% bound with delta = 0.10, so a detector with zero true loss fails whenever the interval is wide. Section VII-B concedes this on clean flows. The alert term instead takes a threshold searched on the target, which is optimistic. Treat uncertainty the same way for both terms, or report inconclusive terms as inconclusive rather than failed.*

Author response: We did both, in a redesigned test (Section III-C (p. 3)):

1. Both terms use the same corrected 95% intervals over the 20 splits: the generalization term on Δ_{BA}, the alert term on recall and false positive rate at the threshold, from which operational precision and false alerts follow.
2. Each term has three outcomes, pass, fail, and inconclusive. A wide interval now gives "inconclusive", not "fail".
3. The alert term no longer searches the threshold on the target. Each split uses the highest threshold that keeps recall on its own held-out source data at $r_{\min}$ or more, a choice made without target labels. The best threshold searched on the target is reported only as an optimistic bound.

With these rules no detector passes. On all flows, five of six fail and one is inconclusive. On the clean flows, the generalization term fails for LR and is inconclusive for the other five, and the alert term fails for two and is inconclusive for four. Because marginal intervals can hide a joint failure, we also count the splits in which a detector meets all three alert conditions at once: HGB in 12 of 20, the MLP in 4, and XGB in 2. The optimistic bound shows that HGB and XGB would meet our bounds with a threshold tuned on the target (HGB: operational precision 0.91 at 25 false alerts per hour).

Author action: Section III-C (p. 3), Section IV-E (p. 5), Section V-D (p. 9), Table 8 (p. 10), Fig. 6 (p. 11).

Reviewer #1, Concern #8

> *The verdict is set by your declared parameters. Amax = 200 at lambda_b = 240,000 flows per hour requires FPR at or below about 0.00083, and neither lambda_b nor pi = 0.002 comes from an operator. Fig. 10 helps, but the abstract's "none passes our deployability test" must say the bounds are your own.*

Author response: The bounds are ours, and the paper now says so wherever the verdict appears.

Author action: The abstract now says "alert bounds that we set ourselves". Section III-C (p. 3) states that no O-RAN specification defines the bounds, that we chose them, and that $A_{\max}$ at our λ_b is a false positive rate of at most 8.3×10^{-4}. Section IV-F (p. 6) and Section VII (p. 12) state that neither π nor λ_b comes from an operator, and Section V-D (p. 9) with Fig. 6 (p. 11) shows where each detector lies relative to the bounds, so that a reader can apply other bounds.

Reviewer #1, Concern #9

> *Byte harmonization differs between the two targets. For DC you strip link-layer and GTP-U bytes. For DB you note that Argus counts whole packets including framing, 42 bytes against Zeek's 40 for a minimum size packet, and leave it uncorrected. A 2 byte gap is not a link-layer header, so explain where it comes from. The exporter robust subset includes the three mean packet sizes, so this offset enters the very columns you use in Section VI-E to argue the shift is compositional. Correct DB the way you corrected DC and rerun.*

Author response: The reviewer found an error. A 2-byte gap was never there: our "40 against 42" compared the smallest TCP packet in Zeek's accounting (40 bytes, no payload) with the smallest UDP packet in Argus's (42 bytes). Measured by protocol, the smallest bytes per packet in 5G-NIDD as exported by Argus are 54 for TCP and 42 for UDP and ICMP, whereas Zeek, on NetsLab-5GORAN-IDD and on our own Zeek re-extraction of the same 5G-NIDD captures, counts 40 and 28. The captures are Ethernet frames whose length exceeds the IP length by 14 bytes for 94.5% of the frames we checked (82% to 99.8% across four captures; most of the rest carry a VLAN tag). Argus therefore counts the 14-byte Ethernet header of every packet, exactly like NFStream for the third corpus. The offset was large for small packets: a UDP-flood packet counted 42 bytes instead of 28.

Author action: We now subtract 14 bytes per packet and direction for 5G-NIDD, as for the third corpus (Section IV-B (p. 4), Table 2 (p. 5); unit tests guard the mapping), and re-ran every experiment that puts 5G-NIDD in the shared space, all with 20 splits: transfer to 5G-NIDD and to the third corpus, the exporter-robust subset, CORAL, the reverse direction, the domain classifier and per-column shift, and the in-target references; the new adaptation experiments use the corrected bytes from the start. The correction changed the diagnostics the reviewer pointed to. The domain classifier separates the corpora on the nine exporter-robust columns with a balanced accuracy of 0.935, down from 0.997 before the correction, and 0.937 against our Zeek re-extraction; on all 18 columns it is 0.997. The robust columns still shift as much as the others ($\bar{W}_1$ of 0.30 against 0.29), and Fig. 4 (p. 9) shows the shift per column before and after the correction. We also corrected Section VI-E's wording on what these diagnostics show (Section V-C (p. 7)).

Reviewer #1, Concern #10

> *The Zeek export result is overstated in the abstract. Your Zeek configuration may differ from the undocumented one behind DA. Zeek yields a third as many flows, 76% of them attacks, and target balanced accuracy fell to 0.43 to 0.56. Section VI-E admits the result cannot separate composition from configuration, yet the abstract states "A common exporter does not close the transfer gap" as a finding.*

Author response: The Zeek re-extraction cannot separate traffic composition from exporter configuration, so it is not a finding about the exporter.

Author action: The sentence was removed from the abstract. Section V-C (p. 7) reports the Zeek comparison as what it is, the same trained models scored on two exports of the same captures, and states that it cannot separate composition from configuration; Section VII (p. 12) repeats this.

Reviewer #1, Concern #11

> *Flow split category coverage is not reported. Flow splits hold out source addresses (318 groups) with 94.63% attacks. If a category comes from one or a few attacker addresses, a split removes it from training. You checked coverage for radio splits. Do the same for flows and report attacker addresses per category.*

Author response: We checked (EXP-073). Of the 318 addresses, 259 send attack flows, and every attack category comes from many addresses, but its flows are concentrated: 3 to 5 addresses carry 90% of each category, and the largest attacker 24% to 37%. Every category appears in training in all 20 splits, with at least 29% of its flows, and in the test part of every split. The concentration has a second consequence that we had not reported: because the split adds whole addresses until 20% of the flows are held out, the held-out part contains 2 to 149 addresses and 29% to 52% of the flows.

Author action: Section IV-D (p. 5) reports the attacker addresses, the concentration, the coverage, and the split composition; the repository lists the attacker addresses per category and the coverage of every split. The split composition also determined our choice of interval (R2.4).

Reviewer #1, Concern #12

> *The claims reach beyond the detectors you tested. All six models use fixed hyperparameters, and CORAL is the only adaptation. That is defensible for a measurement study, but it does not support conclusions about O-RAN detection in general, as the title and the reporting requirements in Section X imply. Add a detector built for distribution shift or narrow the claims.*

Author response: We added methods built for shift and narrowed the claims.

- *Methods built for shift.* Next to CORAL (feature alignment) we added importance weighting by a domain classifier (density-ratio reweighting) and domain-adversarial training (DANN, representation learning), one method per family, plus a label-efficient arm (R2.6). None of the three methods without target labels beats the plain tree-based models. Importance weighting changes little, because the domain classifier separates the corpora so well that the weights concentrate on 2.0% to 6.6% of the source flows in effective sample size. CORAL helps only the MLP (0.69 to 0.81) and raises the false positive rate of the tree-based models to 0.77 to 0.99. DANN reaches 0.66. One labeled target capture does more than any of them (0.87 to 0.93 for the nonlinear models).

- *Narrower claims.* The title now names 5G flow detectors. The detectors section, the limitations, and the conclusion state that our conclusions concern the untuned shallow models and the three adaptation methods we tested, not O-RAN detection in general, and the reporting recommendations are addressed to studies of 5G flow detectors.

Author action: Section IV-C (p. 4), Section V-C (p. 7), Table 7 (p. 9), Fig. 5 (p. 10), Section VII (p. 12), Section IX (p. 13).

Reviewer #1, Concern #13

> *The latency results add little. The loop fed synthetic KPM values from an emulated node over loopback on one Windows host under WSL2, without CPU isolation. You yourselves cite uncontrolled power management to explain why the 1 ms period ran faster than the 10 ms period. A window detector decides once every 16 s, so a 5 ms compute tail is not what limits it. The flow estimate of "close to 10 ms" rests on 8.5 ms of pandas mapping, exactly the implementation cost Section VI-I says dominates architecture. In addition, "Only window-level detectors meet the latency term" in Section X implies flow detectors failed, when they were not measured.*

Author response: These observations are correct, and we cut the section accordingly. We kept one short subsection because Reviewer 1's own suggested reframing includes "a separate latency measurement", and because the measured loop shows that delivery and control, not the model, dominate once a RIC is in the path.

Author action: The latency section is condensed to one subsection (Section V-F (p. 11)) with one table (Table 10 (p. 12)). It states the conditions (synthetic values, emulated node, loopback, one host under WSL2, no CPU isolation), attributes the faster 1 ms period to uncontrolled power management as a caveat, and says that a 16 s window, not the compute tail, limits a window-level detector. The flow-level estimate ("close to 10 ms") and its pandas timing were removed, as were the per-call latency table and the latency distribution figure. The sentence "Only window-level detectors meet the latency term" was removed; the paper now says that flow detectors were not timed in the loop and makes no latency claim for them.

Reviewer #1, Concern #14

> *The 5G-NIDD reading needs confirmation. The inference that the benign copies are station 2's flood seen at station 1 rests on addresses alone. Contact the 5G-NIDD authors and report their answer, since this affects every published result on that corpus.*

Author response: We agree that a claim about a public dataset should be checked with its authors. On 7 November 2026 we wrote to the corresponding author of 5G-NIDD at his current institution, asked him to forward the message to his co-authors, and sent the evidence below with the list of corrected rows. At the time of resubmission we had not received an answer. If the authors reply during review, we will report their answer in the paper and in the repository. We did not want the paper to depend on that answer, so we made two changes. First, the reading no longer rests on addresses. In the raw captures (EXP-072), every one of the 656,180 IPv4 packets of station 2's UDP-flood capture occurs in station 1's capture with the same timestamp to the microsecond, the same addresses, IP identification, and length; both captures start at the same microsecond; and in the other nine sessions the two stations' captures share no packet. The copies are therefore station 2's flood packets, recorded in station 1's file. Second, we change no published label: every 5G-NIDD result is reported three ways (published labels, without the copies, and with the copies relabeled as attack), so a reader can use the published labels if the dataset authors read the files differently. Removing the copies and relabeling them give the same picture (R2.2(e), Table 5 (p. 8), Table 8 (p. 10)).

Author action: Section V-A (p. 6) and Fig. 2 (p. 6)(b) report the packet-level evidence and that we contacted the dataset authors on 7 November 2026 without an answer at the time of resubmission. We still change no published label and report every 5G-NIDD result on the published labels, without the copies, and relabeled.

Reviewer #1, Concern #15

- *(a) Cut the paper to the two or three findings the data supports.*
- *(b) Several sentences are ungrammatical. One example is in Section VI-C: "in the first, the copies sit in the training data, so that a model trained with them labeled benign misses the floods of station 2 is our inference, not a tested result".*
- *(c) Section VI-E says the robust columns "lift" source balanced accuracy, but LR falls from 0.837 to 0.804 (Table 8).*

- *(d) Fig. 1 shows cameras, PLCs and vehicles that appear in none of the corpora.*
- *(e) The motivating "several" papers above 99% are only [11] and [12].*

Author response: All five points are fair; we acted on each.

Author action: (a) The paper is built around three findings (Section I (p. 1)): the 5G-NIDD label audit, cross-corpus transfer with matched references, and alert burden with the two-term test. The radio protocol comparison and the latency measurement are reported briefly as secondary results. Contributions went from seven to three, tables from 14 to 10, figures from 10 to 7; the calibration and prior-shift section, the sequence models, the novelty detectors, and the per-call latency table were removed, and number-dense sentences were split or moved to tables. (b) Every sentence was revised. The quoted sentence was removed together with the experiment it described: the station references now train without the copies or with them relabeled, so the inference it stated is no longer needed: trained that way, the base-station references reach 0.97 to 0.99 from station 1 to station 2. (c) The sentence was corrected (Section V-C (p. 7)); the robust subset is now described per architecture, without "lift". (d) Fig. 1 (p. 3) shows generic benign UEs and an attacker UE, which is what all three corpora contain. (e) The introduction now says what [11] and [12] of the first submission report (now [9], [10] and [11]: the 5G-NIDD authors, preprint and published descriptor, and Ilias et al.), without "several" (Section I (p. 1)).

Reviewer 2

Reviewer #2, Concern #1

> ***Scope and framing.*** *Only D_A is an O-RAN corpus, and its radio-telemetry lane (the O-RAN-specific part) is evaluated only within that corpus. All cross-corpus results concern generic 5G flow-level detection. As a result, the radio detectors never face Criterion 1, the flow detectors never face Criterion 3, and no single detector is evaluated on all three terms of Eq. (6). Please: state this limitation prominently in the abstract and in Section VII-B; consider qualifying the title; clarify in Table 14 that B_min comes from different, window-level detectors.*

Author response: This is the concern of R1.1, and we followed the same course; see our response there.

Author action: The abstract and a scope paragraph in the introduction state the limitation; Section III-C (p. 3) (formerly VII-B) states that latency was measured for window-level detectors only and is not part of the test; Section VII (p. 12) repeats it. The title is qualified to "5G flow intrusion detectors". The former Table 14 is gone because latency no longer enters the verdict; the latency of the window-level detectors is reported on its own in Table 10 (p. 12), and Fig. 1 (p. 3) marks which detectors each criterion was measured on.

Reviewer #2, Concern #2

> ***The 5G-NIDD label conflict.*** *This is the headline result, and it currently rests on address inference. Please:*
>
> - *(a) explain, from the 5G-NIDD network description, how station 1's capture point could observe station 2's flood (for example, through a shared core or UPF link or a mirrored port);*
> - *(b) explain the asymmetry: why file 15 contains no benign-labelled copies of station 1's flood;*
> - *(c) confirm in the raw pcaps, using timestamps or packet identifiers, that the copies are the same packets seen twice;*
> - *(d) report whether the dataset authors were contacted, and consider releasing corrected labels;*
> - *(e) add an arm in which the copies are relabelled as attack. Removing 281,525 benign flows changes the benign composition, while relabelling preserves the traffic a deployed detector would see.*

Author response: We addressed each item with new analyses (EXP-072).

(c) *Raw captures.* Matching packets on timestamp, addresses, IP identification, length, TTL, and a payload digest, all 656,180 IPv4 packets of station 2's UDP-flood capture occur in station 1's capture, with zero time offset; they make up 54% of station 1's file, and both captures start at the same microsecond. In the other nine sessions the two stations' captures share no packet and start 0.007 to 0.64 s apart.

(a) *Network description.* The 5G-NIDD paper [9], [10] describes two base stations connected over S1-U to one switch, which also connects the attackers to the victim's network, and a schedule in which both attackers flood the same target with about five minutes of overlap. A recording on a link or port that carries both stations' traffic would contain both floods. The identical microsecond timestamps show that the two files of this session are not independent recordings at two capture points; how station 1's file was produced is not documented, and we say so.

(b) *Asymmetry.* Station 2's capture contains no packet of station 1's attacker, so file 15 cannot contain copies of station 1's flood; the asymmetry is in the files, not in the labeling.

(d) *Dataset authors and corrected labels.* Yes. We reported the finding, the packet-level evidence, and the corrected rows to the dataset authors on 7 November 2026; at the time of resubmission we had not received an answer (see R1.14). We release the 281,529 corrected rows of Combined.csv (row position, `Seq`, `Offset`, addresses, published and corrected labels) with a checksum and a one-line recipe, without changing the published files.

(e) *Relabeled arm.* Every 5G-NIDD result is now given on the published labels, without the copies, and with the copies relabeled as attack, for transfer, references, adaptation, the label-efficient arm, and the test. Relabeling keeps every flow and gives the same picture as removing the copies (transfer balanced accuracy 0.57 to 0.89 against 0.61 to 0.86), and the same test verdicts except for RF, whose alert term becomes inconclusive.

Author action: Section V-A (p. 6), Fig. 2 (p. 6), Section IV-D (p. 5) (label views), Table 5 (p. 8), Table 8 (p. 10); the corrected labels are released in the public repository (`results/EXP-072/corrected_labels/`).

Reviewer #2, Concern #3

> ***Comparability of the in-target references.*** *In Section VI-C, the capture-file reference in Table 5 never held out a UDP-flood file, whereas transfer is evaluated on all of D_B. The capture-file design in Table 6 (R2) differs and does include such a file. Table 5 uses only 1-3 splits and reports no intervals. Please use leave-one-capture-file-out (or ensure that every attack type is held out at least once), report intervals, and recompute the transfer-versus-reference comparison on matched target flows.*

Author response: We changed the reference design to meet each point (see also R1.4 to R1.6). The new reference is leave-one-capture-file-out, so every attack type and both UDP-flood files are held out once, and its pooled predictions cover every flow of 5G-NIDD exactly once: transfer and reference are compared on matched target flows, with a corrected interval for each architecture. The references now train without the copies labeled as benign (or with the copies relabeled), which also removes the inconsistency the reviewer noted between the former capture-file reference and the capture-file rung of the published pipeline.

Author action: Section IV-D (p. 5), Section V-B (p. 7), Table 5 (p. 8).

Reviewer #2, Concern #4

> ***Statistics on grouped data.*** *The Nadeau-Bengio correction factor counts flows or windows, but the splits are group-disjoint and samples within a group are correlated. Please: compute the correction from group counts, or use the cluster bootstrap for Delta_BA as well; report the number of attacker hosts among the 318 source-address groups, and the attack-category coverage of each held-out source split; state clearly in Tables 3 and 7 that the bracketed intervals are unadjusted. For example, DT in Table 3 has an interval that excludes zero, while the caption says that nothing survives Holm correction.*

Author response: We followed the first suggestion and tried the second.

Group counts. All corrected intervals now take the ratio $n_{\mathrm{test}}/n_{\mathrm{train}}$ from groups: source addresses on the flow layer, sessions or runs on the radio layer. Because the number of held-out addresses varies from 2 to 149 between flow splits (R1.11), a mean of per-split ratios would be dominated by a few splits, so we use the total of held-out groups over the total of training groups across the 20 splits: 0.65 for the flow splits, close to the ratio in flows (0.58), and 0.42 for both radio groupings.

Cluster bootstrap. We also implemented a cluster bootstrap for Δ_{BA} that resampled splits, source addresses, and target capture files. On these data it was not reliable, for two reasons that we document in the repository. Some splits hold out only two to nine source addresses, so resampling addresses inside a split left 38% of the replicates with a single class. And the 20 capture files of 5G-NIDD are purpose-built and very different, one of them holding most benign errors, so the bootstrap

distributions of balanced accuracy and false positive rate were strongly shifted (in one case the point estimate fell at the 0.1th percentile). We therefore use the corrected intervals with group counts throughout, for both terms of the test as well (R1.7), and state in the limitations that they keep the target fixed. The attacker hosts and the category coverage are in our response to R1.11.

Author action: Section IV-E (p. 5) describes the intervals and the choice of ratio; Section IV-D (p. 5) gives the attacker addresses, coverage, and split composition. Every table caption now says that bracketed intervals are unadjusted and that significance marks are Holm-adjusted (Table 5 (p. 8), Table 9 (p. 11), Table 8 (p. 10)). In Table 9 (p. 11), for example, the unadjusted interval of DT under the run grouping excludes zero while no gain is significant after Holm correction, and the caption explains why.

Reviewer #2, Concern #5

> ***Design of the deployability test.***

Author response: We read this item together with R1.7 and R1.8; see our responses there.

Author action: The test was redesigned as described under Reviewer #1, Concern #7 and Reviewer #1, Concern #8 (Section III-C (p. 3), Table 8 (p. 10)).

Reviewer #2, Concern #6

> ***Adaptation.*** *CORAL is the only adaptation method tested. A label-efficient arm would address the practical question of how much labelled target data is needed to pass the test: retrain or fine-tune with k labelled target capture files and plot the result against the bounds. One additional representation-learning method would also help. A negative result here would still strengthen the paper.*

Author response: We added both, and report a negative and a positive result.

- *Label-efficient arm (EXP-069).* $k \in \{1, 2, 4, 8\}$ labeled 5G-NIDD capture files, four random draws per k, are added to the NetsLab training data (and, for comparison, used alone); models are evaluated on the capture files not drawn and plotted against the bounds (Fig. 5 (p. 10)). One file raises the balanced accuracy of the nonlinear models to 0.87 to 0.93 (the MLP from 0.71 to 0.93), close to the in-target reference, whereas the same files alone give 0.53 to 0.63. Meeting the alert bound takes more data: with the threshold fixed on source data, 2 of 24 model draws meet all three alert conditions with one file and 14 of 24 with eight, XGB and the MLP in every draw.
- *Representation learning.* Domain-adversarial training (DANN) reaches 0.66 on the clean flows, below the plain tree-based models, and importance weighting, a second method built for shift, does not help either (R1.12).

Author action: Section IV-C (p. 4), Section V-C (p. 7), Table 7 (p. 9), Fig. 5 (p. 10), Section VI-A (p. 12).

Reviewer #2, Concern #7

> ***Abstract.*** *Simplify the abstract. It is very number-dense; four or five key results in clearer sentences would serve readers better.*

Author response: The first abstract tried to carry every result. The new one carries four.

Author action: The abstract was rewritten around four results, with few numbers, and states the scope and that the bounds are our own.

Reviewer #2, Concern #8

> ***Sample sizes and split counts.*** *Justify the 300,000-flow subsample of D_A and the 240,000-flow training samples, and state the split count (20 or 10) in every table caption.*

Author response: The 300,000-flow sample was fixed before the first run, for runtime: the MLP alone takes several minutes per split, and every experiment runs 20 splits. To check that the choice does not drive the results, we repeated the transfer with 150,000, 600,000, and all 1,640,182 source flows (five splits, five architectures): clean target balanced accuracy changed by at most 0.08 against 300,000 flows, in no consistent direction, within the variation between splits. The 240,000-flow training samples of the in-target references are the size of the transfer training sets (80% of 300,000), so references and transfer learn from the same amount of labeled data. All revision-1 experiments use 20 splits, except the base-station references (ten training samples per direction, five for the relabeled variant), the label-efficient arm (four draws per k), and the sample-size check (five splits); the latency table states its trained models and report counts.

Author action: Section IV-D (p. 5) gives both justifications and the sample-size check; every table caption states its split count.