



uiri_ims

Data Dictionary

Server: PHP-MySQL
Author: Intern-Admin
Date: 2026-06-30 07:27:02
Version: 1.0

Table of Contents

1. Introduction	1
2. Server: UIRI_mydb (MySQL)	2
2.1. Database: uri_idms	2
2.1.1. Tables	2
2.1.1.1. Table: audit_log	2
2.1.1.2. Table: branches	3
2.1.1.3. Table: categories	3
2.1.1.4. Table: departments	4
2.1.1.5. Table: equipment_maintenance	5
2.1.1.6. Table: goods_received_notes	6
2.1.1.7. Table: inventory_items	7
2.1.1.8. Table: inventory_requests	9
2.1.1.9. Table: login_history	10
2.1.1.10. Table: notifications	12
2.1.1.11. Table: permissions	12
2.1.1.12. Table: procurement_requests	13
2.1.1.13. Table: purchase_orders	14
2.1.1.14. Table: rate_limits	15
2.1.1.15. Table: reports	16
2.1.1.16. Table: role_permissions	17
2.1.1.17. Table: roles	17
2.1.1.18. Table: sections	18
2.1.1.19. Table: settings	19
2.1.1.20. Table: stock_transactions	19
2.1.1.21. Table: suppliers	20
2.1.1.22. Table: transfer_items	21
2.1.1.23. Table: transfers	22
2.1.1.24. Table: user_permissions	23
2.1.1.25. Table: users	24

1. Introduction

A data dictionary is a collection of metadata such as object name, data type, size, classification, and relationships with other data assets. It is used by data administrators, analysts, and engineers to understand and trust data assets. It helps in the creation of authentic, transparent, and consistent data throughout the organization.

In this data dictionary, following servers are chosen for documentation:

UIRI_mydb (MySQL)

For each server, definitions of tables (entities/collections), views, functions are listed in order. Detailed properties of data elements (data type, size, nullability, optionality, indexes, foreign keys, constraints) are organized in tabular format.

2. Server: UIRI_mydb (MySQL)

Version: 10.4.32-MariaDB

1 database is listed below.

2.1. Database: uiri_idms

Database objects to be listed: 25 tables

2.1.1. Tables

2.1.1.1. Table: audit_log

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	user_id	int(11)		Index: idx_audit_user
3	branch_id	int(11)		Index: fk_audit_branch
4	action	varchar(100)	✓	Index: idx_audit_action
5	table_name	varchar(50)		
6	record_id	int(11)		
7	details	text		
8	ip_address	varchar(45)		
9	created_at	timestamp	✓	Default: current_timestamp() Index: idx_audit_created

Indexes

Name	Type	Method	Fields
fk_audit_branch	NORMAL	BTREE	branch_id
idx_audit_user	NORMAL	BTREE	user_id
idx_audit_action	NORMAL	BTREE	action
idx_audit_created	NORMAL	BTREE	created_at

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_audit_branch	branch_id	uiri_idms.branches	id	SET NULL	RESTRICT
fk_audit_user	user_id	uiri_idms.users	id	SET NULL	RESTRICT

2.1.1.2. Table: branches

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	name	varchar(100)	✓	Index: name
3	location	varchar(200)	✓	
4	address	text		
5	phone	varchar(30)		
6	email	varchar(150)		
7	is_headquarters	tinyint(1)		Default: 0
8	is_active	tinyint(1)		Default: 1
9	created_at	timestamp	✓	Default: current_timestamp()
10	updated_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
name	UNIQUE	BTREE	name

2.1.1.3. Table: categories

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	name	varchar(100)	✓	Index: name

3	description	text		
4	created_at	timestamp	✓	Default: current_timestamp()
5	updated_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
name	UNIQUE	BTREE	name

2.1.1.4. Table: departments

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	branch_id	int(11)	✓	Index: uq_department_code_branc...
3	name	varchar(150)	✓	
4	code	varchar(50)		Index: uq_department_code_branc...
5	manager_name	varchar(150)		
6	contact_email	varchar(150)		
7	description	text		
8	section_manager_id	int(11)		Index: fk_departments_section_ma...
9	department_manager_id	int(11)		Index: fk_departments_departmen...
10	is_active	tinyint(1)		Default: 1
11	created_at	timestamp	✓	Default: current_timestamp()
12	updated_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
------	------	--------	--------

uq_department_code_branch	UNIQUE	BTREE	branch_id, code
fk_departments_section_manager	NORMAL	BTREE	section_manager_id
fk_departments_department_manager	NORMAL	BTREE	department_manager_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_departments_branch	branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT
fk_departments_department_manager	department_manager_id	uiri_idms.users	id	SET NULL	RESTRICT
fk_departments_section_manager	section_manager_id	uiri_idms.users	id	SET NULL	RESTRICT

2.1.1.5. Table: equipment_maintenance

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	equipment_name	varchar(200)	✓	
3	equipment_type	varchar(100)	✓	
4	branch_id	int(11)	✓	Index: idx_maintenance_branch
5	assigned_to	int(11)		Index: fk_maintenance_user
6	maintenance_date	date	✓	
7	next_service_date	date		
8	service_cost	decimal(15, 2)		Default: 0.00
9	status	varchar(30)		Default: 'Scheduled' Index: idx_maintenance_status

10	description	text		
11	created_at	timestamp	✓	Default: current_timestamp()
12	updated_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
fk_maintenance_user	NORMAL	BTREE	assigned_to
idx_maintenance_branch	NORMAL	BTREE	branch_id
idx_maintenance_status	NORMAL	BTREE	status

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_maintenance_branch	branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT
fk_maintenance_user	assigned_to	uiri_idms.users	id	SET NULL	RESTRICT

2.1.1.6. Table: goods_received_notes

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	grn_code	varchar(50)		Index: grn_code
3	purchase_order_id	int(11)	✓	Index: fk_grn_purchase_order
4	received_by	int(11)	✓	Index: fk_grn_received_by
5	received_date	date	✓	
6	remarks	text		
7	created_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
------	------	--------	--------

grn_code	UNIQUE	BTREE	grn_code
fk_grn_purchase_order	NORMAL	BTREE	purchase_order_id
fk_grn_received_by	NORMAL	BTREE	received_by

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_grn_purchase_order	purchase_order_id	uiri_idms.purchase_orders	id	RESTRICT	RESTRICT
fk_grn_received_by	received_by	uiri_idms.users	id	RESTRICT	RESTRICT

2.1.1.7. Table: inventory_items

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	branch_id	int(11)	✓	Index: idx_items_branch
3	department_id	int(11)		Index: idx_items_department
4	section_id	int(11)		Index: idx_items_section
5	category_id	int(11)	✓	Index: idx_items_category
6	supplier_id	int(11)		Index: idx_items_supplier
7	item_code	varchar(50)	✓	Index: item_code idx_items_code
8	asset_code	varchar(100)		
9	qr_code	varchar(100)		
10	name	varchar(200)	✓	
11	brand_model	varchar(200)		
12	description	text		
13	unit	varchar(30)		Default: 'piece'
14	unit_price	decimal(15, 2)		Default: 0.00

15	current_stock	int(11)		Default: 0
16	minimum_stock	int(11)		Default: 5
17	asset_type	varchar(50)		Default: 'Consumable'
18	asset_status	varchar(50)		Default: 'Available'
19	asset_condition	varchar(50)		Default: 'New'
20	funding_source	varchar(150)		
21	storage_location	varchar(150)		
22	estimated_value	decimal(15, 2)		Default: 0.00
23	purchase_date	date		
24	warranty_date	date		
25	supporting_file	varchar(255)		
26	image	varchar(255)		
27	is_active	tinyint(1)		Default: 1
28	created_by	int(11)		Index: <code>fk_items_created_by</code>
29	created_at	timestamp	✓	Default: <code>current_timestamp()</code>
30	updated_at	timestamp	✓	Default: <code>current_timestamp()</code>

Indexes

Name	Type	Method	Fields
item_code	UNIQUE	BTREE	item_code
fk_items_created_by	NORMAL	BTREE	created_by
idx_items_branch	NORMAL	BTREE	branch_id
idx_items_department	NORMAL	BTREE	department_id
idx_items_section	NORMAL	BTREE	section_id
idx_items_category	NORMAL	BTREE	category_id
idx_items_supplier	NORMAL	BTREE	supplier_id
idx_items_code	NORMAL	BTREE	item_code

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
------	--------	------------------	-------------------	-----------	-----------

fk_items_branch	branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT
fk_items_category	category_id	uiri_idms.categories	id	RESTRICT	RESTRICT
fk_items_created_by	created_by	uiri_idms.users	id	SET NULL	RESTRICT
fk_items_department	department_id	uiri_idms.departments	id	SET NULL	RESTRICT
fk_items_section	section_id	uiri_idms.sections	id	SET NULL	RESTRICT
fk_items_supplier	supplier_id	uiri_idms.suppliers	id	SET NULL	RESTRICT

2.1.1.8. Table: inventory_requests

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	user_id	int(11)	✓	Index: idx_requests_user
3	branch_id	int(11)	✓	Index: idx_requests_branch
4	department_id	int(11)		Index: fk_requests_department
5	item_id	int(11)	✓	Index: fk_requests_item
6	quantity	int(11)	✓	
7	reason	text		
8	status	enum		Default: 'Pending' Index: idx_requests_status
9	requested_at	timestamp	✓	Default: current_timestamp()
10	approved_by	int(11)		Index: fk_requests_approved_by
11	approved_at	timestamp		
12	processed_by	int(11)		Index: fk_requests_processed_by

13	processed_at	timestamp		
14	remarks	text		

Indexes

Name	Type	Method	Fields
fk_requests_department	NORMAL	BTREE	department_id
fk_requests_item	NORMAL	BTREE	item_id
fk_requests_approved_by	NORMAL	BTREE	approved_by
fk_requests_processed_by	NORMAL	BTREE	processed_by
idx_requests_user	NORMAL	BTREE	user_id
idx_requests_status	NORMAL	BTREE	status
idx_requests_branch	NORMAL	BTREE	branch_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_requests_approved_by	approved_by	uiri_idms.users	id	SET NULL	RESTRICT
fk_requests_branch	branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT
fk_requests_department	department_id	uiri_idms.departments	id	SET NULL	RESTRICT
fk_requests_item	item_id	uiri_idms.inventory_items	id	RESTRICT	RESTRICT
fk_requests_processed_by	processed_by	uiri_idms.users	id	SET NULL	RESTRICT
fk_requests_user	user_id	uiri_idms.users	id	RESTRICT	RESTRICT

2.1.1.9. Table: login_history

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	

2	user_id	int(11)		Index: fk_login_history_user
3	branch_id	int(11)		Index: fk_login_history_branch
4	section_id	int(11)		Index: fk_login_history_section
5	department_id	int(11)		Index: fk_login_history_department...
6	success	tinyint(1)	✓	Default: 0
7	ip_address	varchar(45)		
8	user_agent	varchar(255)		
9	details	text		
10	created_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
fk_login_history_user	NORMAL	BTREE	user_id
fk_login_history_branch	NORMAL	BTREE	branch_id
fk_login_history_department	NORMAL	BTREE	department_id
fk_login_history_section	NORMAL	BTREE	section_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_login_history_branch	branch_id	uiri_idms.branches	id	SET NULL	RESTRICT
fk_login_history_department	department_id	uiri_idms.departments	id	SET NULL	RESTRICT
fk_login_history_section	section_id	uiri_idms.sections	id	SET NULL	RESTRICT
fk_login_history_user	user_id	uiri_idms.users	id	SET NULL	RESTRICT

2.1.1.10. Table: notifications

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	user_id	int(11)		Index: idx_notifications_user
3	branch_id	int(11)		Index: idx_notifications_branch
4	type	varchar(50)	✓	Index: idx_notifications_type
5	title	varchar(150)	✓	
6	message	text		
7	link	varchar(255)		
8	is_read	tinyint(1)		Default: 0
9	created_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
idx_notifications_user	NORMAL	BTREE	user_id
idx_notifications_branch	NORMAL	BTREE	branch_id
idx_notifications_type	NORMAL	BTREE	type

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_notifications_branch	branch_id	uiri_idms.branches	id	CASCADE	RESTRICT
fk_notifications_user	user_id	uiri_idms.users	id	CASCADE	RESTRICT

2.1.1.11. Table: permissions

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	

2	name	varchar(100)	✓	Index: name
3	description	varchar(255)		
4	created_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
name	UNIQUE	BTREE	name

2.1.1.12. Table: procurement_requests

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	request_code	varchar(50)		Index: request_code
3	branch_id	int(11)	✓	Index: fk_procurement_branch
4	requested_by	int(11)	✓	Index: fk_procurement_user
5	supplier_id	int(11)		Index: fk_procurement_supplier
6	title	varchar(200)	✓	
7	description	text		
8	requested_date	date	✓	
9	status	varchar(30)		Default: 'Pending'
10	remarks	text		
11	created_at	timestamp	✓	Default: current_timestamp()
12	updated_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
request_code	UNIQUE	BTREE	request_code

fk_procurement_branch	NORMAL	BTREE	branch_id
fk_procurement_user	NORMAL	BTREE	requested_by
fk_procurement_supplier	NORMAL	BTREE	supplier_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_procurement_branch	branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT
fk_procurement_supplier	supplier_id	uiri_idms.suppliers	id	SET NULL	RESTRICT
fk_procurement_user	requested_by	uiri_idms.users	id	RESTRICT	RESTRICT

2.1.1.13. Table: purchase_orders

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	po_code	varchar(50)		Index: po_code
3	procurement_request_id	int(11)	✓	Index: fk_purchase_procurement
4	supplier_id	int(11)	✓	Index: fk_purchase_supplier
5	branch_id	int(11)	✓	Index: fk_purchase_branch
6	created_by	int(11)	✓	Index: fk_purchase_user
7	order_date	date	✓	
8	expected_delivery	date		
9	status	varchar(30)		Default: 'Draft'
10	remarks	text		
11	created_at	timestamp	✓	Default: current_timestamp()
12	updated_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
po_code	UNIQUE	BTREE	po_code
fk_purchase_procurement	NORMAL	BTREE	procurement_request_id
fk_purchase_supplier	NORMAL	BTREE	supplier_id
fk_purchase_branch	NORMAL	BTREE	branch_id
fk_purchase_user	NORMAL	BTREE	created_by

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_purchase_branch	branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT
fk_purchase_procurement	procurement_request_id	uiri_idms.procurement_requests	id	RESTRICT	RESTRICT
fk_purchase_supplier	supplier_id	uiri_idms.suppliers	id	RESTRICT	RESTRICT
fk_purchase_user	created_by	uiri_idms.users	id	RESTRICT	RESTRICT

2.1.1.14. Table: rate_limits

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	identifier	varchar(190)	✓	Index: idx_rate_identifier
3	action	varchar(50)		Default: 'login'
4	ip_address	varchar(45)		
5	created_at	timestamp	✓	Default: current_timestamp() Index: idx_rate_created

Indexes

Name	Type	Method	Fields
------	------	--------	--------

idx_rate_identifier	NORMAL	BTREE	identifier
idx_rate_created	NORMAL	BTREE	created_at

2.1.1.15. Table: reports

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	report_type	varchar(50)	✓	
3	title	varchar(150)		
4	generated_by	int(11)		Index: <code>fk_reports_generated_by</code>
5	branch_id	int(11)		Index: <code>fk_reports_branch</code>
6	category_id	int(11)		Index: <code>fk_reports_category</code>
7	date_from	date		
8	date_to	date		
9	file_path	varchar(255)		
10	created_at	timestamp	✓	Default: <code>current_timestamp()</code>

Indexes

Name	Type	Method	Fields
fk_reports_generated_by	NORMAL	BTREE	generated_by
fk_reports_branch	NORMAL	BTREE	branch_id
fk_reports_category	NORMAL	BTREE	category_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_reports_branch	branch_id	uiri_idms.branches	id	SET NULL	RESTRICT

fk_reports_category	category_id	uiri_idms.categories	id	SET NULL	RESTRICT
fk_reports_generated_by	generated_by	uiri_idms.users	id	SET NULL	RESTRICT

2.1.1.16. Table: role_permissions

Fields

Pos	Name	Type	Not Null	Others
1	role_id 	int(11)	✓	
2	permission_id 	int(11)	✓	Index: fk_role_permissions_permiss...

Indexes

Name	Type	Method	Fields
fk_role_permissions_permission	NORMAL	BTREE	permission_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_role_permissions_permission	permission_id	uiri_idms.permissions	id	CASCADE	RESTRICT
fk_role_permissions_role	role_id	uiri_idms.roles	id	CASCADE	RESTRICT

2.1.1.17. Table: roles

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	name	varchar(50)	✓	Index: name
3	description	text		

Indexes

Name	Type	Method	Fields
name	UNIQUE	BTREE	name

2.1.1.18. Table: sections

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	branch_id	int(11)	✓	Index: fk_sections_branch
3	department_id	int(11)	✓	Index: uq_section_code_departme...
4	name	varchar(150)	✓	
5	code	varchar(50)		Index: uq_section_code_departme...
6	description	text		
7	is_active	tinyint(1)		Default: 1
8	created_at	timestamp	✓	Default: current_timestamp()
9	updated_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
uq_section_code_department	UNIQUE	BTREE	department_id, code
fk_sections_branch	NORMAL	BTREE	branch_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_sections_branch	branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT
fk_sections_department	department_id	uiri_idms.departments	id	RESTRICT	RESTRICT

2.1.1.19. Table: settings

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	setting_key	varchar(100)	✓	Index: setting_key
3	setting_value	text		
4	updated_by	int(11)		Index: fk_settings_updated_by
5	updated_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
setting_key	UNIQUE	BTREE	setting_key
fk_settings_updated_by	NORMAL	BTREE	updated_by

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_settings_updated_by	updated_by	uiri_idms.users	id	SET NULL	RESTRICT

2.1.1.20. Table: stock_transactions

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	item_id	int(11)	✓	Index: idx_stock_item
3	branch_id	int(11)	✓	Index: idx_stock_branch
4	user_id	int(11)	✓	Index: fk_stock_user
5	transaction_type	enum	✓	Index: idx_stock_type
6	quantity	int(11)	✓	
7	unit_price	decimal(15, 2)		Default: 0.00

8	reference_number	varchar(100)		
9	destination_branch_id	int(11)		Index: <code>fk_stock_destination_branc...</code>
10	remarks	text		
11	transaction_date	date	✓	Index: <code>idx_stock_date</code>
12	created_at	timestamp	✓	Default: <code>current_timestamp()</code>
13	updated_at	timestamp	✓	Default: <code>current_timestamp()</code>

Indexes

Name	Type	Method	Fields
fk_stock_user	NORMAL	BTREE	user_id
fk_stock_destination_branch	NORMAL	BTREE	destination_branch_id
idx_stock_item	NORMAL	BTREE	item_id
idx_stock_branch	NORMAL	BTREE	branch_id
idx_stock_date	NORMAL	BTREE	transaction_date
idx_stock_type	NORMAL	BTREE	transaction_type

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_stock_branch	branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT
fk_stock_destination_branch	destination_branch_id	uiri_idms.branches	id	SET NULL	RESTRICT
fk_stock_item	item_id	uiri_idms.inventory_items	id	RESTRICT	RESTRICT
fk_stock_user	user_id	uiri_idms.users	id	RESTRICT	RESTRICT

2.1.1.21. Table: suppliers

Fields

Pos	Name	Type	Not Null	Others
-----	------	------	----------	--------

1	id 	int(11) Auto Increment	✓	
2	company_name	varchar(150)	✓	
3	contact_person	varchar(100)		
4	email	varchar(150)		
5	phone	varchar(30)		
6	address	text		
7	tin_number	varchar(50)		
8	is_active	tinyint(1)		Default: 1
9	created_at	timestamp	✓	Default: current_timestamp()
10	updated_at	timestamp	✓	Default: current_timestamp()

2.1.1.22. Table: transfer_items

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	transfer_id	int(11)	✓	Index: <code>fk_transfer_items_transfer</code>
3	item_id	int(11)	✓	Index: <code>fk_transfer_items_item</code>
4	quantity	int(11)	✓	
5	remarks	text		

Indexes

Name	Type	Method	Fields
fk_transfer_items_transfer	NORMAL	BTREE	transfer_id
fk_transfer_items_item	NORMAL	BTREE	item_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_transfer_items_item	item_id	uiri_idms.inventory_items	id	RESTRICT	RESTRICT
fk_transfer_items_transfer	transfer_id	uiri_idms.transfers	id	CASCADE	RESTRICT

2.1.1.23. Table: transfers

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	transfer_code	varchar(50)	✓	Index: transfer_code
3	from_branch_id	int(11)	✓	Index: idx_transfers_from_branch
4	to_branch_id	int(11)	✓	Index: idx_transfers_to_branch
5	requested_by	int(11)	✓	Index: fk_transfers_requested_by
6	approved_by	int(11)		Index: fk_transfers_approved_by
7	status	enum		Default: 'Requested' Index: idx_transfers_status
8	request_date	date	✓	
9	approved_date	date		
10	dispatched_date	date		
11	received_date	date		
12	remarks	text		
13	created_at	timestamp	✓	Default: current_timestamp()
14	updated_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
transfer_code	UNIQUE	BTREE	transfer_code
fk_transfers_requested_by	NORMAL	BTREE	requested_by
fk_transfers_approved_by	NORMAL	BTREE	approved_by
idx_transfers_from_branch	NORMAL	BTREE	from_branch_id
idx_transfers_to_branch	NORMAL	BTREE	to_branch_id
idx_transfers_status	NORMAL	BTREE	status

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_transfers_approved_by	approved_by	uiri_idms.users	id	SET NULL	RESTRICT
fk_transfers_from	from_branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT
fk_transfers_requested_by	requested_by	uiri_idms.users	id	RESTRICT	RESTRICT
fk_transfers_to	to_branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT

2.1.1.24. Table: user_permissions

Fields

Pos	Name	Type	Not Null	Others
1	user_id 	int(11)	✓	
2	permission_id 	int(11)	✓	Index: fk_user_permissions_permiss...

Indexes

Name	Type	Method	Fields
fk_user_permissions_permission	NORMAL	BTREE	permission_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_user_permissions_permission	permission_id	uiri_idms.permissions	id	CASCADE	RESTRICT
fk_user_permissions_user	user_id	uiri_idms.users	id	CASCADE	RESTRICT

2.1.1.25. Table: users

Fields

Pos	Name	Type	Not Null	Others
1	id 	int(11) Auto Increment	✓	
2	branch_id	int(11)	✓	Index: fk_users_branch
3	section_id	int(11)		Index: fk_users_section
4	department_id	int(11)		Index: fk_users_department
5	role_id	int(11)	✓	Index: fk_users_role
6	full_name	varchar(150)	✓	
7	email	varchar(150)		Index: email
8	username	varchar(80)	✓	Index: username
9	password	varchar(255)	✓	
10	phone	varchar(30)		
11	profile_photo	varchar(255)		
12	email_verified	tinyint(1)		Default: 1
13	is_active	tinyint(1)		Default: 1
14	last_login	datetime		
15	failed_login_attempts	int(11)		Default: 0
16	last_login_attempt	datetime		
17	password_reset_token	varchar(255)		
18	token_expiry	datetime		
19	remember_token	varchar(255)		
20	created_at	timestamp	✓	Default: current_timestamp()
21	updated_at	timestamp	✓	Default: current_timestamp()

Indexes

Name	Type	Method	Fields
username	UNIQUE	BTREE	username
email	UNIQUE	BTREE	email
fk_users_branch	NORMAL	BTREE	branch_id
fk_users_department	NORMAL	BTREE	department_id
fk_users_section	NORMAL	BTREE	section_id
fk_users_role	NORMAL	BTREE	role_id

Foreign Keys

Name	Fields	Referenced Table	Referenced Fields	On Delete	On Update
fk_users_branch	branch_id	uiri_idms.branches	id	RESTRICT	RESTRICT
fk_users_department	department_id	uiri_idms.departments	id	SET NULL	RESTRICT
fk_users_role	role_id	uiri_idms.roles	id	RESTRICT	RESTRICT
fk_users_section	section_id	uiri_idms.sections	id	SET NULL	RESTRICT