

Pseudocode Conventions

This version of the document is dated 2020-05-04.

[Peter Occil](#)

1 Introduction

This document explains the conventions and common functions used in some of my articles that use pseudocode.

2 Contents

- **Introduction**
- **Contents**
- **Symbols**
- **Loops**
- **Lists and Files**
- **Functions**
- **Pseudocode Notes**
- **License**

3 Symbols

In addition to the familiar +, -, * (multiplication), and / (division) operators, other symbols are defined below.

- π is the constant π , the ratio of a circle's circumference to its diameter.
- `nothing` indicates the absence of a value. It corresponds to `null` in Java, C#, and JavaScript, `nil` in Ruby, and `None` in Python.
- `true` and `false` are the two Boolean values.
- `==` means "is equal to".
- `!=` means "is not equal to".
- The `<<` operator in the pseudocode is a bitwise left shift, with both sides of the operator being integers. If each side is 0 or greater, it is the same as multiplying the left-hand side by 2^n , where n is the right-hand side.
- The `>>` operator in the pseudocode is a bitwise right shift, with both sides of the operator being integers. If each side is 0 or greater, it is the same as dividing the left-hand side by 2^n , where n is the right-hand side, and discarding the fractional part of the result.
- The `|` operator in the pseudocode is a bitwise OR operator between two integers. It combines the bits of both integers so that each bit is set in the result if the corresponding bit is set on either or both sides of the operator.

4 Loops

Pseudocode may use `while` loops, which are self-explanatory.

Pseudocode may also use for loops, defined as follows:

- for X in Y...Z; [[Statements]] ; end is shorthand for X = Y; while X < Z; [[Statements]]; X = X + 1; end.
- for X in Y...Z: [[Single-Statement]] is shorthand for X = Y; while X < Z; [[Single-Statement]]; X = X + 1; end.

5 Lists and Files

In the pseudocode, lists are indexed starting with 0. That means the first item in the list has index 0, the second item in the list has index 1, and so on, up to the last item, whose index is the list's size minus 1.

In this context, a *list* is to be understood as a resizable array of items, not as a linked list.

A *list* can be expressed by wrapping items in brackets; for example, [0, 1, 2] is a three-item list.

- NewList() or [] creates a new empty list.
- AddItem(list, item) adds the item item to the list list.
- size(list) returns the size of the list list.
- list[k] refers to the item at index k of the list list.
- GetNextLine(file) is a method that gets the next line from a file, or returns nothing if the end of the file was reached.

6 Functions

- sin(a), cos(a), and tan(a) are the sine, cosine, and tangent of the angle a, respectively, where a is in radians.
- atan2(y, x) is—
 - the inverse tangent of y/x, in radians, if x > 0,
 - π plus the inverse tangent of y/x, in radians, if y >= 0 and x < 0,
 - $-\pi$ plus the inverse tangent of y/x, in radians, if y < 0 and x < 0,
 - $-\pi$ divided by 2 if y < 0 and x == 0,
 - π divided by 2 if y > 0 and x == 0, and
 - 0 if y == 0 and x == 0.
- pow(a, b) is the number a raised to the power b.
- abs(a) is the absolute value of a; it makes negative numbers non-negative.
- sqrt(a) is the square root of a, and is equivalent to pow(a, 0.5).
- floor(a) is the highest integer that is less than or equal to a.
- round(a) is the closest integer to a or, if two integers are tied for closest, the integer among them that is farther from 0.
- ln(a) is the natural logarithm of a. It corresponds to the Math.log method in Java and JavaScript.
- exp(a) is the number e (base of natural logarithms) raised to the power a.
- rem(a, b) is the part of b that does not divide evenly into a, where the result has the sign of b. This operation is equivalent to a - floor(a / b) * b.
- min(a, b) is the smaller of a and b.
- max(a, b) is the larger of a and b.

Notes:

- The inverse sine, in radians, of a is equivalent to atan2(a, sqrt(1.0 - a * a)).
- The inverse cosine, in radians, of a is equivalent to atan2(sqrt(1.0 - a * a), a).

7 Pseudocode Notes

In the pseudocode:

- Divisions do not round to an integer. (In some programming languages, division of two integers results in an integer, which may be rounded differently depending on the language. For instance, Python's and Ruby's integer division does a floor rounding on the result of division, while Java's discards the fractional part of the result of division.)
- The pseudocode shown is not guaranteed to cover all error handling, such as recovery from overflows, out-of-bounds memory accesses, divisions by zero, unexpected infinity values, and other errors that might happen in a particular implementation.
- The pseudocode shown is not guaranteed to yield high performance in a particular implementation, either in time or memory. Implementations are free to deviate from the pseudocode as long as they produce the same results as the pseudocode, except that—
 - arithmetic operations, `rem`, `sqrt`, `ln`, `exp`, `pow`, `sin`, `cos`, `tan`, and `atan2` must return a result that is at least substantially close to the correctly rounded result, and
 - arithmetic operations, `abs`, `sqrt`, `floor`, `round`, and `rem`, if implemented in fixed-precision number formats, must return the correctly rounded result.
- Unless noted otherwise, the pseudocode does not care how a particular implementation stores integers and non-integers (e.g., as floating-point, fixed-point, decimal, binary, two's-complement, ones'-complement, Chinese remainder theorem, or otherwise).

8 License

This page is licensed under [Creative Commons Zero](#).