

# Essentials of SVG

This version of the document is dated 2020-12-24.

The following short note explains the most useful things to know when writing vector graphics to SVG.

First, we start with a skeleton of an SVG file (which uses the XML data format):

```
<svg width='300px' height='300px' viewBox='0 0 100 100'  
  xmlns='http://www.w3.org/2000/svg'>  
  <circle style='stroke:none;fill:red' cx='10' cy='10' r='2' />  
  <path style='stroke:black;fill:none' d='M10 10L20 20 L30 10Z' />  
</svg>
```

In this very simple example, there are already several useful things we can see here:

- width and height give the size of the SVG in pixels relative to the host document.
- viewBox gives the size of the shape in SVG units (not pixels). It has four numbers giving the left side, top side, width, and height. Y coordinates run downwards.
- circle draws a circle. cx, cy, and r gives the center's X coordinate, its Y coordinate, and its radius, all in SVG units.
- path gives the shape of the path in a compact form specified as the d attribute. Each path is broken up into commands, which are [detailed further in the SVG specification](#). The most important of these are perhaps M, L, and Z: the M command moves the pen; the L command draws with the pen, moving it to a new position; and the Z command closes the shape by drawing with the pen straight to the shape's beginning. In general, numbers given in the path specification is in SVG units, relative to the SVG document itself.
- style gives styling instructions for the path or circle. Perhaps the most important style rules are stroke, fill, and stroke-width, and the following are examples of the style attribute, which are mostly self-explanatory: style='stroke:red;stroke-width:1px', style='stroke:none;', style='fill:blue;', style='fill:none;' (here px means an SVG unit, relative to the SVG document itself).

An SVG document can have any number of path and/or circle elements, and each one is a separate shape. Finally, each path and circle element can have a transform attribute, which describes an optional geometric transformation. The attribute's value is made up of [one or more commands](#) described further in the SVG specification. The commands, which are followed in the order written, include "translate(x,y)" which moves the zero-point; "rotate(d)" which rotates the coordinate system by d degrees, and "scale(x)" which scales the coordinates by a factor of x. Examples of the attribute include transform='translate(3, 5)', transform='rotate(90)', and transform=' translate(2, 2) scale(2)'.

## 1 License

Any copyright to this page is released to the Public Domain. In case this is not possible, this page is also licensed under [Creative Commons Zero](#).