A Developer Diary {about:"code learn and share"}



Home

Data Science

Java

JavaScript

jBPM

Tools

Tips

About

February 20, 2016 By Abhisek Jana — Leave a Comment (Edit)

Create iWatch Activity Chart using d3.js



In this tutorial we will **Create iWatch Activity Chart using d3.js**. Here we will use almost all the features we have learnt so far on Pie Chart. We will create multiple functions to reuse the code as much as possible.

Lets look at the details in the chart.

UI Elements:

- 1. 3 Background Elements
- 2. 3 Foreground Elements
- 3. Multiple Shadows and Gradients
- 4. 3 PNG Images

We will first set the width and height. Then set a color scale. After that create the svg element.

var w=300,h=300; var outerRadius=(w/2);

```
Create iWatch Activity Chart using d3.js - A Developer Diary
var width=30,gap=2;
var innerRadius=outerRadius-30;
var color=["#e90b3a", "#a0ff03", "#1ad5de"];
var svg=d3.select("#chart")
     append("svg")
     .attr({
         width:w,
         height:h,
         class: 'shadow'
    }).append('g')
     .attr({
         transform: 'translate('+w/2+','+h/2+')'
    });
Now lets create a JSON object for the 3 sets of activities. We have name for each activity type, the initial value, color and
icon.
var circles=[
         {name: 'activity1', percent: 70, color: '#e90b3a', icon: 'stand.png'},
         {name: 'activity2', percent:80, color: '#a0ff03', icon: 'walk.png'},
         {name: 'activity3', percent:65, color: '#1ad5de', icon: 'run.png'}
];
Next create the gradent and drop shadow definitions. You can find the below functions later in this tutorial.
createGradient(svg,'#fe08b5','#ff1410','gradient');
createDropShadow(svg, 'dropShadow',4,1,1);
The following section is very important. We will iterate through the JSON object, calculate the innerRadius and call
createCircle() function to create both the background and foreground elements for each activity. Don't worry about the
createCircle() function, we will create them in a min.
The outermost activity has a gradient, we will check if i = 0 and call addGradient() function. Afterwards, we will call
addDropShadow() and addStartImage().
for(var i=0;i < circles.length;++i){</pre>
    if(i>0){
         outerRadius=innerRadius-gap;
     }
     innerRadius=outerRadius-width;
circles[i].chart=createCircle(svg,outerRadius,innerRadius,circles[i].color,circles[i].percent);
     if(i==0){
```

```
addGradient(circles[i].chart.path,'gradient');
}

addDropShadow(circles[i].chart.path,'dropShadow');
addStartImage(svg,'https://www.adeveloperdiary.com/wp-
content/uploads/2015/11/'+circles[i].icon,outerRadius);
}
```

Let's create the createCircle() function. It accepts the svg element we already created, outer and inner radius, color and initial value.

We will calculate the ratio based on the percent. Then add the background arc and path element. Repeate the same for the foreground as well. Set the <code>endAngle</code> to <code>0</code> for the foreground. Add the <code>transition()</code> function to the foreground path element.

The createCircle() returns a JSON Object which contains both the path and arc object for the foreground element.

var createCircle=function(svg,outerRadius,innerRadius,color,percent){

```
var ratio=percent/100;
var arcBackground=d3.svg.arc()
        .innerRadius(innerRadius)
        .outerRadius(outerRadius)
        .startAngle(0)
        .endAngle(2*Math.PI);
var pathBackground=svg.append('path')
        .attr({
            d:arcBackground
        })
        .style({
            fill:color,
            opacity:.2
        });
var arcForeground=d3.svg.arc()
        .innerRadius(innerRadius)
        .outerRadius(outerRadius)
        .cornerRadius(20)
        .startAngle(-0.05);
var pathForeground=svg.append('path')
        .datum({endAngle:0})
        .attr({
            d:arcForeground
        })
        .style({
            fill:color
```

We need use the <code>arcTween()</code> function for each activity since all of them will have seperate values and they need to animate independently. Here is the function. This is straightforward.

```
var arcTween=function(transition, newAngle,arc) {
    transition.attrTween("d", function (d) {
        var interpolate = d3.interpolate(d.endAngle, newAngle);
        return function (t) {
            d.endAngle = interpolate(t);
            return arc(d);
        };
    });
};
```

Find the addGradient() and addDropShadow() functions. Both the functions accepts the path object and an id. We already have created the gradient and drop shadow definitions, so we just need to set the fill and filter property.

```
var addGradient=function(path,id){
   path.style({
        fill:"url('#"+id+"')"
   });
};

var addDropShadow=function(path,id){
   path.style({
        filter:"url('#"+id+"')"
   });
};
```

Next create the addStartImage() function to add the png image. We will add an image element with xlink:href as the image URL. Then we will will move the image to the correct location using the outerRadius.

```
height:20,
             transform:'translate(0,'+ (-outerRadius+6) +')'
    });
};
Believe or not, we are done with the chart creation. Now we just need to animate it. We will animate all 3 foregrounds.
var updateData=function(){
    for(var i=0;i < circles.length;++i) {</pre>
        updateChart(circles[i].chart.path,circles[i].chart.arc,Math.floor((Math.random())
* 60) + 20));
    }
    setTimeout(updateData, 1500);
};
setTimeout(updateData,1500);
var updateChart= function (path,arc,percent) {
    var ratio=percent/100;
    path.transition()
             .duration(1500)
             .ease('elastic')
             .call(arcTween,((2*Math.PI))*ratio,arc);
};
```

Lets look at the demo now:



Here are the createGradient() and createDropShadow() function.

```
var createGradient=function(svg,color1,color2,id){
    var defs = svg.append("defs");
    var gradient=defs.append("linearGradient")
            .attr("id", id)
            .attr("x1", "0%")
            .attr("v1". "100%")
            .attr("x2", "50%")
            .attr("y2", "0%")
            .attr("spreadMethod", "pad");
    gradient.append("svg:stop")
            .attr("offset", "0%")
            .attr("stop-color", color1)
            .attr("stop-opacity", 1);
    gradient.append("svg:stop")
            .attr("offset", "100%")
            .attr("stop-color", color2)
            .attr("stop-opacity", 1);
};
var createDropShadow=function(svg,id,stdDeviation,dx,dy){
    var defs = svg.append("defs");
    var filter = defs.append("filter")
            .attr("id", id);
    filter.append("feGaussianBlur")
            .attr("in", "SourceAlpha")
            .attr("stdDeviation", stdDeviation)
            .attr("result", "blur");
    filter.append("fe0ffset")
            .attr("in", "blur")
            .attr("dx", dx)
            .attr("dy", dy)
            .attr("result", "offsetBlur");
    var feMerge = filter.append("feMerge");
    feMerge.append("feMergeNode")
            .attr("in", "offsetBlur");
    feMerge.append("feMergeNode")
            .attr("in", "SourceGraphic");
};
```

Find the full code in github.


Related



Create a Simple Pie Chart using D3.js In "D3.js"




How to create Progress chart using d3.js In "D3.js"



Create 3D Donut Chart using D3.js
In "D3.js"

Filed Under: D3.js, JavaScript Tagged With: actity, chart, d3.js, Donut Charts, example, iwatch, JavaScript, Learn, Pie Chart, Programming, Progress Chart



Leave a Reply

Logged in as Abhisek Jana. Edit your profile. Log out? Required fields are marked *

Comment *

Post Comment

This site uses Akismet to reduce spam. Learn how your comment data is processed.

Copyright © 2024 A Developer Diary