

[Practice](#)[Compete](#)[Jobs](#)[Rank](#)[Leaderboard](#)

gadhiya

[Dashboard](#) > [Algorithms](#) > [Dynamic Programming](#) > Candies

Badge Progress



Points: 4727.88 Rank: 491

Candies

by HackerRank

Problem

[Submissions](#)[Leaderboard](#)[Discussions](#)[Editorial](#)

Alice is a kindergarten teacher. She wants to give some candies to the children in her class. All the children sit in a line (their positions are fixed), and each of them has a rating score according to his or her performance in the class. Alice wants to give at least 1 candy to each child. If two children sit next to each other, then the one with the higher rating must get more candies. Alice wants to save money, so she needs to minimize the total number of candies given to the children.

Input Format

The first line of the input is an integer N , the number of children in Alice's class. Each of the following N lines contains an integer that indicates the rating of each child.

Constraints

- $1 \leq N \leq 10^5$
- $1 \leq \text{rating}_i \leq 10^5$

Output Format

Output a single line containing the minimum number of candies Alice must buy.

Sample Input 0

```
3
1
2
2
```

Sample Output 0

```
4
```

Explanation 0

Here 1, 2, 2 is the rating. Note that when two children have equal rating, they are allowed to have different number of candies. Hence optimal distribution will be 1, 2, 1.

Sample Input 1

```
10
2
4
2
6
1
7
8
9
```

2
1**Sample Output 1**

19

Explanation 1

Optimal distribution will be 1, 2, 1, 2, 1, 2, 3, 4, 2, 1

[f](#) [t](#) [in](#)


Submissions: 27338

Max Score: 50

Difficulty: Medium

Rate This Challenge:

☆☆☆☆☆

[More](#)Current Buffer (saved locally, editable)  

Java 8



```
1 import java.io.*;
2 import java.util.*;
3
4 public class Solution {
5
6     public static void main(String[] args) {
7
8         Scanner scan = new Scanner(System.in);
9         int N = scan.nextInt();
10
11         long output = 0;
12
13         int[] candy = new int[N];
14         int[] arr = new int[N];
15
16         for(int i = 0 ; i < N ; i++){
17             int a = scan.nextInt();
18             arr[i] = a;
19
20             if( i == 0 || (a <= arr[i - 1])){
21                 candy[i] = 1;
22             }
23             else if(a > arr[i - 1]){
24                 candy[i] = candy[i - 1] + 1;
25             }
26         }
27
28         int previousValue = 1;
29         int[] candy2 = new int[N];
30
31         for(int i = N - 1; i >= 0 ; i--){
32
33             if(i == N - 1 || (arr[i] <= arr[i + 1])){
34                 candy2[i] = 1;
35             }else{
36                 candy2[i] = candy2[i + 1] + 1;
37             }
38
39             output = output + Math.max(candy[i],candy2[i]);
40
41         }
42
43         System.out.println(output);
44
45     }
46 }
```

```
47  
48 }
```

Line: 1 Col: 1

[Upload Code as File](#)

Test against custom input

Run Code

Submit Code

Copyright © 2017 HackerRank. All Rights Reserved

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Interview Prep](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)