

Exam answer June 2013

written by

slex04



The Marketplace to Buy and Sell your Study Material

On Stuvia you will find the most extensive lecture summaries written by your fellow students. Avoid resits and get better grades with material written specifically for your studies.

www.stuvia.com

Section A :

Question 1 : 3
 Question 2 : 4
 Question 3 : 2
 Question 4 : 3
 Question 5 : 1
 Question 6 : 4
 Question 7 : 3
 Question 8 : 3
 Question 9 : 2
 Question 10 : 4

Section B :

Question 1.a :

The purpose : Continue to increase the value of (s) by the value of the variable (n) per loop until n is greater than 5.

Question 1.b :

The purpose : Continue to increase the value of (c) by 1 per loop (five loops in total) when a specific element in the (numbers) array which the index variable (i) points to is not equal to zero.

Question 2.a.i :

Line 8 : year == 2010, code == 't', book == 1, discount == 0.20
 Line 9 : year == 2010, code == 't', book == 1, discount == 0.20
 Line 10 (10 -> 17) : year == 2010, code == 't', book == 1, discount == 0.20
 Line 18 : year == 2010, code == 't', book == 1, discount == 0.20
 Line 20 (18 -> 20) : year == 2010, code == 't', book == 0, discount == 0.20

	year	code		
line 6	<input data-bbox="411 1435 539 1480" type="text" value="?"/>	<input data-bbox="564 1435 692 1480" type="text" value="?"/>		
	year	code	book	discount
line 7	<input data-bbox="411 1554 539 1599" type="text" value="?"/>	<input data-bbox="564 1554 692 1599" type="text" value="?"/>	<input data-bbox="718 1554 845 1599" type="text" value="1"/>	<input data-bbox="871 1554 1034 1599" type="text" value="0.20"/>
	year	code	book	discount
line 8	<input data-bbox="411 1673 539 1718" type="text" value="2010"/>	<input data-bbox="564 1673 692 1718" type="text" value="'t'"/>	<input data-bbox="718 1673 845 1718" type="text" value="1"/>	<input data-bbox="871 1673 1034 1718" type="text" value="0.20"/>
	year	code	book	discount
line	<input data-bbox="411 1792 539 1836" type="text"/>	<input data-bbox="564 1792 692 1836" type="text"/>	<input data-bbox="718 1792 845 1836" type="text"/>	<input data-bbox="871 1792 1034 1836" type="text"/>
	year	code	book	discount
line	<input data-bbox="411 1910 539 1955" type="text"/>	<input data-bbox="564 1910 692 1955" type="text"/>	<input data-bbox="718 1910 845 1955" type="text"/>	<input data-bbox="871 1910 1034 1955" type="text"/>
	year	code	book	discount
line	<input data-bbox="411 2029 539 2074" type="text"/>	<input data-bbox="564 2029 692 2074" type="text"/>	<input data-bbox="718 2029 845 2074" type="text"/>	<input data-bbox="871 2029 1034 2074" type="text"/>

Question 2.a.ii :

2010 b 1 0.35

Question 2.b.i :

Line 7 : card1 == "JackOfClubs", card1P == "JackOfClubs", card2 == "Joker", card2P == "Joker", score == 100, scoreP == 0
 Line 8 : card1 == "JackOfClubs", card1P == "JackOfClubs", card2 == "Joker", card2P == "Joker", score == 100, scoreP == 0
 Line 9 (9 -> 13) : card1 == "JackOfClubs", card1P == "JackOfClubs", card2 == "Joker", card2P == "Joker", score == 100, scoreP == 0

	[card1]	card1P	[card2] card2P	[score]	scoreP
line 31->4	"JackOfClubs"	"JackOfClubs"	"JackOfClubs"	100	100
line 6	"JackOfClubs"	"JackOfClubs"	"Joker"	100	100
line 7	"JackOfClubs"	"JackOfClubs"	"Joker"	100	0
line					
line					

Question 2.b.ii :

card2P = "AceOfHearts";
 scoreP = 100;

Question 2.b.iii :

JackOfClubs 5OfClubs 100

Question 3 :

```
switch(nrWheels)
{
    case 2 : count2 = 1; break;
    case 4 : count4 = 1; break;
    default : if(nrWheels > 4) countMore = 1; break;
};
```

Question 4 :

```

name = 'B';
while(name == 'B' || name == 'E')
{
    cout << "Which one's product was sold? (B or E) : ";
    cin >> name;
    if(name == 'B' || name == 'E')
    {
        cout << "Enter sale : ";
        cin >> sale;
        if(name == 'B') bSales += sale;
        else eSales += sale;
    }
}

```

Question 5 :

```

if(time < 1) interest = 0.025;
else if(time < 2) interest = 0.030;
else if(time < 3) interest = 0.035;
else if(time < 4) interest = 0.040;
else if(time < 5) interest = 0.045;
else interest = 0.0475;

```

Question 6 :

```

float calcAverage(float sales[NUM_DAYS])
{
    float total = 0;
    for(int i = 0; i < NUM_DAYS; i++)
        total += sales[i];
    return total / (float) NUM_DAYS;
}

```

Question 7.a :

```
int training[4][3];
```

Question 7.b :

```
int training[4][3];
```

```
int max;
```

```

for(int i = 0; i < 4; i++)
{
    max = training[i][0];
    for(int j = 1; j < 3; j++)
        if(training[i][j] > max)
            max = training[i][j];
    cout << "The longest distance covered in week " << i + 1 << " was " << max << endl;
}

```

Question 8.a :

```
void check(int v1, double v2);
double mult(double v1, double v2);
void time(int &hrs, int &minutes, int &seconds);
int countlets(string str, char letter);
```

Question 8.b :

The differences :

- + The doubleNum1 takes a reference variable as an argument. Has no return value.
- + The doubleNum2 takes a normal variable as an argument. Has int return value.

How to call them :

```
int a = 15;
doubleNum1(a);
a = doubleNum2(15);
a = doubleNum2(a);
```

Question 8.c :

```
int cube(int a)
{
    return a * a * a;
}
```

```
answer = cube(n);
```

Question 9.a :

A R 9.99

A R 1.11

Question 9.b :

```
void read_Shoe_Record(ShoeType &new_Shoe)
{
    cout << "Enter style : ";
    cin >> new_Shoe.style;
    cout << "Enter price : ";
    cin >> new_Shoe.price;
}
```

Question 10 :

```
string changeCase(string senP)
{
    for(int i = 0; i < senP.size(); i++)
    {
        if(islower(senP[i])) senP[i] = toupper(senP[i]);
        else senP[i] = tolower(senP[i]);
    }
    return senP;
}
```