

base pool
4447 pairs

2 archs x 3 seeds
B=1000 k=75 a=1.0

B1: which embedder?
dinoL518 — but the
best silhouette is only
0.1600: a weak partition

C1: targeting, or
concentration?
destroying the signal costs
+0.0073 of a d (targeted
wins 13/20) — a coin flip

A0

unpadded —
unclean control

A2

authors' duplicates
— clean control

B

random 1000 renders

C10

ES-targeted
— “Ours”

CSHUF

signal destroyed

CINV

signal reversed

EXP ABC bar: $B \pm 2\hat{\sigma} = 0.017933$

0.7010

0.7077

0.7134

EXP T2 bar ± 0.005533

0.7185

0.7170

0.7193

0.700 0.705 0.710 0.715 0.720

S_{α} on COD10K-test (primary endpoint), SINet, mean of 3 seeds

Every arm lies inside its own bar. $\Delta(C-B) = +0.005034$ against 0.017933 (EXP ABC, §FIG), and with the allocation shape held exactly fixed the real, destroyed and reversed arms are indistinguishable in 12 of 12 cells against a bar $3.24 \times$ tighter (EXP T2, §FIG).

SINet-v2 agrees on every verdict, and reverses the sign of $\Delta(C-B)$ to -0.000399 .

no effect resolvable at this sensitivity
a null bounded by power, on an
exhausted foreground pool (§FIG)
— not a demonstration of absence

What does travel: the pixel-over-structure ordering holds for every
uncertainty signal tested, 8/8 (§FIG).



data object



deterministic op.



trained



frozen / offline



pre-registered



post-hoc reading



$|\Delta| \leq 2\hat{\sigma}$: unresolved



gate / decision



forward



feedback (contribution)



offline, out of loop



rejected path