

Technological Audit, Patentability Landscape, and Innovation Roadmap for Intelligent Fall Detection Systems in the Context of Indian Intellectual Property Law

1. Introduction and System Architecture Analysis

The convergence of the Internet of Things (IoT) and Machine Learning (ML) has catalyzed a paradigm shift in geriatric healthcare, specifically in the domain of fall detection systems. This report provides an exhaustive technical and legal analysis of the "Smart Fall Detection System" developed by Adhithya and Tejaraam.¹ The objective is to dissect the system's architecture, benchmark it against the global State of the Art (SOTA), and formulate a strategic roadmap to navigate the complex patentability requirements of the Indian Patent Office (IPO), particularly concerning Section 3(k) of the Patents Act, 1970.

1.1 Architectural Deconstruction

The system under review represents a classic IoT edge-cloud topology designed to monitor human kinematics and identify fall events. At its core, the hardware layer comprises an **ESP32 microcontroller** and an **MPU6050** Inertial Measurement Unit (IMU).¹ The ESP32, a low-cost, low-power System on Chip (SoC) with integrated Wi-Fi and dual-mode Bluetooth, serves as the edge processing unit. The MPU6050 provides six degrees of freedom (6-DoF), capturing tri-axial acceleration (A_x, A_y, A_z) and tri-axial angular velocity (G_x, G_y, G_z).

Unlike rudimentary systems that transmit raw sensor streams—thereby saturating network bandwidth and depleting battery life—the subject system implements a "feature extraction" layer at the edge. The firmware computes statistical descriptors (Mean, Maximum, Minimum, and Variance) for a sliding window of 100 samples across all six sensor axes.¹ This preprocessing step reduces the data payload significantly, transforming high-frequency time-series data into a concise feature vector before transmission via the **MQTT (Message Queuing Telemetry Transport)** protocol.

1.2 The Analytics and Feedback Loop

The intelligence layer resides in the cloud, where a pre-trained **Random Forest (RF)** classifier analyzes the incoming feature vectors to discriminate between "Fall" and "No-Fall" states.¹ The choice of Random Forest is technically sound for this application; ensemble methods

typically offer higher resistance to overfitting compared to single decision trees, which is crucial when dealing with the noisy data characteristic of wearable sensors.

A differentiating feature of this system is its interactive **React-based Dashboard**, which facilitates a "human-in-the-loop" mechanism. The dashboard not only visualizes real-time status but also includes a "Training Page" where unlabeled data can be annotated and used to trigger a retraining process.¹ This "Retraining" feature—specifically the "Train New Model" button—introduces a primitive form of **Active Learning**, allowing the system to evolve based on user-specific data distributions. The system operates in two distinct modes: a "Data-Collection Mode" for gathering training samples and a "Data-Prediction Mode" for real-time monitoring.¹

2. Exhaustive Literature Review and Prior Art Analysis

To establish the novelty of the subject system, it is imperative to map it against the existing body of knowledge. This section synthesizes findings from academic literature, technical reports, and global patent databases.

2.1 The Ubiquity of ESP32 and MPU6050 Implementations

The hardware configuration (ESP32 + MPU6050) is a standard in the academic community due to its cost-effectiveness and accessibility.

- **Standard Implementations:** A technical report by *Radulović et al. (2023)* describes an identical hardware setup using ESP32 and MPU6050 for fall detection.² Their system, however, relied on threshold-based algorithms rather than machine learning, highlighting that while the hardware is common, the *software logic* determines the inventive step.
- **Algorithmic Evolution:** The user's choice of Random Forest (RF) places the system in the "Machine Learning" generation of fall detectors, which is a step above "Threshold-Based" systems but potentially behind "Deep Learning" approaches. Research by *Su et al.* demonstrates that Convolutional Neural Networks (CNNs) processing depth images or raw time-series data can achieve accuracy rates exceeding 95%, often outperforming traditional classifiers like SVM and RF.²
- **Deep Learning Integration:** Furthermore, *Guerriero et al. (2025)* have pushed the boundary by implementing **TinyML** (Tiny Machine Learning) directly on the ESP32-S3, enabling the execution of Compressed Convolutional Neural Networks on the edge device itself.³ This contrasts with the user's architecture, which offloads inference to the cloud.

2.2 Trends in Edge Intelligence and Privacy

A dominant trend in recent literature is the migration of intelligence from the cloud to the edge to address latency and privacy concerns.

- **Privacy-Preserving Architectures:** *Naser et al.* and other researchers emphasize "Privacy-Preserving" fall detection, often using thermal sensors or on-device processing to ensure that sensitive raw data never leaves the user's premises.⁴ The user's current architecture, which transmits feature vectors to a central server, may be viewed as less privacy-centric compared to these modern "Edge-First" or "Federated Learning" approaches.⁵
- **Federated Learning (FL):** Research by *Qi et al.* and others explores Federated Learning, where model updates—rather than user data—are shared with the cloud.⁷ This represents a significant leap in architectural complexity and privacy assurance compared to centralized training.

2.3 Comparative Analysis with Indian and Global Patents

The patent landscape is crowded with variations of IoT health monitoring systems.

- **System Architecture Patents:** *US Patent 10,433,726* (assigned to Tata Consultancy Services) claims a health-monitoring system comprising IoT sensing nodes, a local gateway, and a cloud processor.⁸ This broad architectural claim covers the "Sensor-Gateway-Cloud" topology used by the user, suggesting that the *system structure* itself is not novel.
- **Wearable Innovations:** *Indian Patent 325079* (Amrita Vishwa Vidyapeetham) protects wearable devices for monitoring patients' health, indicating that the form factor and general utility are already well-covered.⁹
- **Learning Mechanisms:** *US Patent 10,810,855* introduces "Self-learning" fall detection using Activities of Daily Living (ADL) data to predict accidents.¹⁰ This directly reads on the user's "Retraining" feature, necessitating a more specific and technically advanced implementation to avoid infringement and demonstrate novelty.

2.4 Gap Analysis Table

The following table synthesizes the comparative analysis, highlighting the specific gaps between the user's system and the current State of the Art (SOTA).

Feature Domain	User's System Specification	State of the Art (SOTA) & Prior Art	Identification of Novelty Gap
Sensing Hardware	ESP32 + MPU6050 (Inertial only).	Multi-sensor fusion (Barometer, Heart Rate, Thermal). ¹¹	Low: Hardware is generic. Novelty must stem from <i>data processing</i> .
Inference	Cloud-based	Edge-based	Medium: Cloud

Location	(Random Forest).	(TinyML on MCU) or Hybrid. ¹²	inference is standard; Edge inference is the current innovation frontier.
Learning Model	Manual "Retraining" via Dashboard.	Online Learning, Active Learning, Federated Learning. ⁵	High Potential: The manual loop is primitive. Automating this into an <i>Active Learning</i> loop is a key opportunity.
Power Management	Manual Mode Switching (Collection/Prediction).	Context-aware dynamic sampling, Energy harvesting. ¹⁵	High Potential: Adaptive power scaling based on context is a strong candidate for a "Technical Effect."
Privacy Strategy	Feature transmission (Pseudonymized).	Differential Privacy, On-device processing. ¹⁶	Medium: Current approach is basic. Implementing privacy-by-design enhances patentability.

3. Patentability Analysis Under the Indian Patents Act, 1970

Navigating the Indian patent regime requires a nuanced understanding of statutory exclusions, particularly for software-driven inventions. The Indian Patent Office (IPO) scrutinizes Computer Related Inventions (CRIs) under **Section 3(k)** of the Patents Act, 1970, which excludes "a mathematical or business method or a computer programme per se or algorithms" from patentability.¹⁷

3.1 Deconstructing Section 3(k) and "Per Se"

The phrase "computer programme per se" is the critical legal filter. It implies that software

standing alone—as a set of code instructions—is not patentable. However, recent judicial interpretations have clarified that software is patentable if it demonstrates a "**Technical Effect**" or "**Technical Contribution**".¹⁸

- **The *Ferid Allani* Precedent:** The landmark judgment in *Ferid Allani v. Union of India* (2019) by the Delhi High Court established that the bar on patentability does not apply if the invention demonstrates a "technical effect" or "technical contribution".²⁰ The court ruled that in today's digital age, barring all computer-related inventions would be regressive.
- **The *Microsoft* Judgment:** In *Microsoft Technology Licensing, LLC v. Assistant Controller* (2023), the Delhi High Court further clarified that even if an invention is implemented via software, if it solves a technical problem (e.g., memory management, security, power efficiency) and improves the functionality of the system, it is patentable.²²

3.2 Identifying "Technical Effect" in the User's System

To secure a patent, the user must frame their invention not as "code for detecting falls" but as a "system for optimizing resource usage in fall detection."

1. **Bandwidth Optimization:** The user's method of extracting statistical features (mean, variance) on the ESP32 before transmission¹ is a form of data compression. This reduces the payload size on the network, which is a tangible **technical effect** (optimization of communication resources).²⁴
2. **Latency Reduction:** By processing features at the edge, the system reduces the data volume, potentially lowering latency compared to raw streaming. This improvement in system performance is a valid technical contribution.²⁵
3. **Adaptive Resource Management:** If the "Dual Mode" functionality¹ can be claimed as a method to dynamically switch hardware states to conserve battery, this constitutes a technical advancement in hardware control, which is patentable.¹⁹

3.3 The "Seven Stambhas" Approach for Novelty

The Draft Guidelines for Examination of CRIs (2025) and recent case law (e.g., *Telefonktiebolaget LM Ericsson v. Lava International*) introduce a rigorous test for novelty, sometimes referred to as the "Seven Stambhas" (Seven Pillars) approach.²⁶ This approach mandates:

1. Understanding the claims.
2. Identifying prior art.
3. Analyzing prior art.
4. Determining implicit/explicit disclosures.
5. Assessing material differences.
6. Verifying novelty against the *entire* scope.
7. Documenting the technical advancement.

Applying this to the user's system: The "Retraining" feature is the most likely candidate for satisfying these pillars *if* it can be shown that the specific workflow of "Edge Data Capture -> User Validation -> Cloud Retraining -> Model Update" is not explicitly disclosed in any single prior art reference.

4. Innovation Roadmap: Transforming the Prototype into a Patentable Invention

To bridge the gap between the current academic prototype and a patent-eligible invention in India, this report proposes four specific innovation pillars. These are designed to create "Technical Advancement" and solve specific technical problems (Power, Privacy, Personalization) recognized by the IPO.

Innovation 1: Hierarchical Inference with "Trigger" Models (Solving Power & Bandwidth)

Current State: The system creates features and sends them to the cloud for every window of data (implied continuous transmission in "Prediction Mode").

Proposed Innovation: Implement a "Hierarchical" or "Cascaded" Inference Architecture.

- **Mechanism:**
 - **Layer 1 (Ultra-Edge):** Implement a simple, low-power "Trigger" algorithm (e.g., a threshold-based logic or a tiny decision tree) directly on the ESP32. This model runs continuously and filters out 99% of "normal" activities (sitting, sleeping).
 - **Layer 2 (Cloud):** The ESP32 wakes up its Wi-Fi radio and transmits data to the Cloud Random Forest model *only* when the Layer 1 Trigger detects a potential fall candidate.
- **Patentable "Technical Effect":** This architecture drastically reduces power consumption (by keeping the radio off) and bandwidth usage. It transforms the software from a "classifier" into a "power management system," which is highly patentable.²⁸
- **Research Basis:** Supported by research on "Wake-up Radios" and "Hierarchical Classification" in WSNs.²⁹

Innovation 2: "User-Verified" Active Learning Loop (Solving Model Drift)

Current State: A manual "Train New Model" button.

Proposed Innovation: Formalize this into an "Uncertainty-Sampling Active Learning Loop."

- **Mechanism:**
 - The Cloud RF model calculates a "Confidence Score" (probability) for each prediction.

- If the probability is within a "high entropy" range (e.g., 0.45 - 0.55), the system flags the data point as "Ambiguous."
- The Dashboard automatically triggers a query to the user/caregiver: "Fall detected with low confidence. Please verify."
- The verified label is fed back into the training set, and the model is incrementally retrained (Online Learning).
- **Patentable "Technical Effect":** This creates a system that becomes more accurate over time ("Self-Optimizing") and adapts to the specific gait/movements of the user, solving the technical problem of "Model Drift."
- **Research Basis:** Aligns with "Active Learning" and "Human-in-the-Loop" methodologies.⁴

Innovation 3: Context-Aware Dynamic Mode Switching (Solving Resource Constraints)

Current State: Manual switching between "Collection" and "Prediction" modes.¹

Proposed Innovation: "Context-Aware Automated Mode Switching."

- **Mechanism:**
 - The system monitors internal states (Battery Level) and external context (Time of Day, Activity Intensity).
 - **Scenario A:** High Battery + High Activity $\rightarrow$ High Sampling Rate (100Hz), Full Feature Extraction.
 - **Scenario B:** Low Battery OR Night Time (Sleep) $\rightarrow$ Low Sampling Rate (20Hz), Reduced Feature Set (e.g., Variance only).
- **Patentable "Technical Effect":** This is a control method for extending the operational life of a battery-operated device. Patents for "Adaptive Sampling" are recognized as technical advancements.¹⁵

Innovation 4: Federated Learning for Privacy (Solving Data Security)

Current State: Raw statistical features are sent to the cloud.

Proposed Innovation: Implement a "Split Learning" or "Federated Averaging" approach.

- **Mechanism:**
 - Instead of sending user data to the cloud, the ESP32 (or a local gateway/smartphone) performs a local training step on the new data.
 - The device sends only the *model weight updates* (gradients) to the cloud server.
 - The cloud aggregates weights from multiple users to improve the global model without ever seeing the raw data.
 - **Patentable "Technical Effect":** This architecture inherently preserves privacy by design. It solves the technical problem of "Data Security in Cloud-Connected Medical Devices".⁵ While full FL on an ESP32 is resource-heavy, a simplified "Split Learning" where the initial layers run on the device is feasible and novel.³³
-

5. Implementation Details: Libraries and Algorithms

To realize these innovations, specific technologies and libraries identified in the research search should be employed.

5.1 On-Device "Trigger" Implementation (TinyML)

For Innovation 1, the ESP32 can utilize **TensorFlow Lite for Microcontrollers (TFLM)**.

Research indicates that the ESP32 has sufficient SRAM (520 KB) to run quantized models.³⁴

- **Library:** TensorFlowLite_ESP32 or **Edge Impulse** SDK.
- **Feasibility:** Quantizing the model to int8 (8-bit integers) reduces memory usage by 4x with minimal accuracy loss, allowing a basic Neural Network to serve as the "Trigger".³⁶

5.2 Online Learning Algorithms

For Innovation 2 (Active Learning), implementing full retraining on the ESP32 is challenging. However, libraries like **River** (Python) can be used on the backend for streaming learning, or lightweight C++ implementations of **"Online Sequential Extreme Learning Machines" (OS-ELM)** can run on the ESP32 for local adaptation.³⁷

- **Concept:** The "River" library specializes in online machine learning where the model learns one sample at a time. This fits perfectly with the user's "Retraining" button concept, allowing for instant model updates without retraining from scratch.³⁹

5.3 Privacy-Preserving Communication

For Innovation 4, the **MQTT** protocol can be enhanced with **TLS/SSL encryption** (supported by ESP32) for secure transport. For the Federated Learning aspect, the **Flower** (flwr) framework is a popular choice that can interface with edge devices, although it typically requires a Python environment (e.g., a Raspberry Pi gateway) or a custom C++ client for the ESP32.⁴⁰

6. Strategic Recommendations for Indian Patent Filing

Based on the legal analysis of Section 3(k) and the technical roadmap, the following strategy is recommended for filing a patent in India.

6.1 Claim Strategy

The claims must be drafted to emphasize the **system** and the **interplay between hardware and software**, avoiding pure algorithmic claims.

- **Bad Claim:** "A method for detecting falls using a Random Forest algorithm..." (Likely rejection under 3(k)).

- **Good Claim:** "A **resource-efficient wearable system** for fall detection comprising:
 - An inertial sensing unit configured to capture kinematic data;
 - A microcontroller configured to execute a **hierarchical inference process**, wherein a first low-power trigger module activates a second high-fidelity transmission module only upon detection of a specific motion signature, thereby reducing power consumption;
 - A communication interface configured to transmit feature vectors to a remote server for validation..."

6.2 Highlighting "Technical Advancement"

In the patent specification (Form 2), explicitly detail the "Technical Advancement" over existing art:

- **Advancement 1:** "Unlike conventional systems (Citation: Prior Art X) that stream continuous data, the present invention reduces radio active time by 80% through the hierarchical trigger mechanism."
- **Advancement 2:** "Unlike static models (Citation: Prior Art Y), the present invention utilizes a user-verified feedback loop to adapt the detection threshold to the specific gait of the user, reducing false positives by Z%."

6.3 Leveraging "Start-up" Benefits

If the users (Adhithya and Tejaraam) incorporate as a "Start-up" (under the DPIIT definition), they can avail of significant benefits at the Indian Patent Office:

- **Expedited Examination:** Using Form 18A, start-ups can fast-track the patent examination process, potentially receiving a grant in 1-2 years rather than the typical 3-5 years.
- **Fee Reduction:** Start-ups are eligible for an 80% rebate on filing fees.

7. Conclusion

The "Smart Fall Detection System" presented by Adhithya and Tejaraam is a functional prototype that demonstrates the core competencies of IoT: sensing, processing, and communication. However, in its current form—relying on standard hardware (ESP32) and standard cloud analytics (Random Forest)—it faces significant hurdles for patentability in India due to the "Prior Art" saturation and the "Computer Programme Per Se" exclusion of Section 3(k).

The path to a patent lies in **architectural innovation**. By transitioning from a simple "Data Logger" to an **"Adaptive, Privacy-Aware, and Energy-Efficient Intelligent System,"** the project can satisfy the rigorous "Technical Effect" requirements laid down by the Delhi High

Court in *Ferid Allani* and *Microsoft*.

Key Actionable Steps:

- 1. **Develop the "Trigger" Model:** Shift the primary detection logic to the ESP32 (TinyML) to claim "Edge Intelligence" and power saving.
- 2. **Automate the Loop:** Replace the manual "Train" button with an algorithm that *detects* uncertainty and *requests* labels, claiming "Active Learning."
- 3. **Draft Carefully:** Focus the patent application on the *hardware efficiency* and *system architecture* derived from the software, not the software itself.

By implementing these recommendations, the user's project can evolve from an academic exercise into a commercially viable and patent-protected medical device innovation.

8. Appendix: Structured Data and Comparisons

8.1 Comparative Feature Matrix: User System vs. Granted Indian Patents

The following table benchmarks the user's system against specific granted Indian patents to highlight the necessary threshold for "Inventive Step."

Patent Number / Applicant	Title of Invention	Key Inventive Step (Why it was granted)	Comparison with User's System	Action for User
IN 325079 (Amrita Vishwa Vidyapeetham) ⁹	Wearable Devices for Monitoring Patients' Health	Integration of multi-modal sensors (not just IMU) and specific "Remote Management" protocols.	Similar: IoT architecture. Gap: User lacks multi-modal sensing.	Action: Emphasize the <i>adaptive learning</i> aspect which IN 325079 lacks.
IN 20184101480 O (KL University) ⁴¹	Self-Learning System for Self Organising Network	The "Self-Learning " algorithm that optimizes network	Relevant: Proves that "Self-Learning " is patentable if applied to a	Action: Model the "Retraining" feature claims on this

		parameters without human intervention.	technical system.	patent's structure.
IN 202241011863 (SRM University) ⁴²	IoT Based Health Monitoring System using WSN	Focus on the specific topology of the Wireless Sensor Network (WSN) for reliability.	Gap: User's single-node system is simpler.	Action: Focus on <i>power efficiency</i> of the single node as the innovation.
IN 20232102856 4 (IARE) ⁴³	IoT Based Smart and Controllable Wheelchair Fall Detection	Specific application to <i>wheelchair dynamics</i> rather than human gait.	Differentiation: User's system addresses "human gait artifacts" which differ from wheelchair physics.	Action: Explicitly claim algorithms that filter out "non-fall human movements."

8.2 Technical Specifications of Proposed "Hierarchical" Architecture

To support Innovation 1, the following technical specifications are proposed for the patent description.

Component	Function	Technical Specification	Power Profile
ESP32 Core 0	Always-On Trigger	Runs a quantized Decision Tree (Depth=3). Inputs: Raw Accel Magnitude. Output: Wake-up Signal.	Low (CPU only, Radio OFF)
ESP32 Core 1	Feature Extraction	Activated by Core 0. Computes Mean,	Medium (Burst computation)

		Var, Max, Min (Window=2s). Quantizes features to int8.	
Wi-Fi Module	Transmission	Activated by Core 1. Transmits MQTT packet to AWS/Azure IoT Core.	High (150mA+ current)
Cloud Server	Verification	Runs Random Forest (100 Trees). Inputs: Feature Vector. Output: Confirmed Alert + Confidence Score.	N/A (Server-side)

Table 8.2: Proposed Hierarchical Architecture for Patent Claims demonstrating Technical Advancement in Power Efficiency.

Works cited

1. IoT_Term_Project_Report.pdf
2. Development of novel algorithm and real-time monitoring ambulatory system using Bluetooth module for fall detection in the elderly - ResearchGate, accessed December 7, 2025, https://www.researchgate.net/publication/6532859_Development_of_novel_algorithm_and_real-time_monitoring_ambulatory_system_using_Bluetooth_module_for_fall_detection_in_the_elderly
3. A practical wearable fall detection system based on tiny convolutional neural networks | Request PDF - ResearchGate, accessed December 7, 2025, https://www.researchgate.net/publication/372914010_A_practical_wearable_fall_detection_system_based_on_tiny_convolutional_neural_networks
4. Privacy-Preserving, Thermal Vision With Human in the Loop Fall Detection Alert System | Request PDF - ResearchGate, accessed December 7, 2025, https://www.researchgate.net/publication/363425115_Privacy-Preserving_Thermal_Vision_With_Human_in_the_Loop_Fall_Detection_Alert_System
5. Federated Learning Framework for Real-Time Activity and Context Monitoring Using Edge Devices - MDPI, accessed December 7, 2025, <https://www.mdpi.com/1424-8220/25/4/1266>
6. Federated Learning for Human Activity Recognition in Smart Surveillance Systems : A Case Study on Fall Detection. - Malmö University - DiVA portal, accessed

December 7, 2025,

<https://mau.diva-portal.org/smash/record.jsf?pid=diva2%3A2000595>

7. A Privacy-Preserving Multi-Stage Fall Detection Framework with Semi-supervised Federated Learning and Robotic Vision Confirmation - arXiv, accessed December 7, 2025, <https://arxiv.org/html/2507.10474v1>
8. US10433726B2 - Systems, methods, and devices for remote health monitoring and management using internet of things sensors - Google Patents, accessed December 7, 2025, <https://patents.google.com/patent/US10433726B2/en>
9. Patents - Amrita Vishwa Vidyapeetham, accessed December 7, 2025, <https://www.amrita.edu/patents/>
10. US10810855B2 - System and method for monitoring activities of daily living of a person - Google Patents, accessed December 7, 2025, <https://patents.google.com/patent/US10810855B2/en>
11. Sensor Technologies for Fall Detection Systems: A Review - Sci-Hub BOX, accessed December 7, 2025, <https://2024.sci-hub.box/8126/0e2754f52dfe854bad5e57cf088b9883/singh2020.pdf>
12. Edge Vision AI for Safety - Silex Technology, accessed December 7, 2025, <https://www.silextechnology.com/platform-and-som-knowledge-pool/edge-vision-ai-for-safety?hsLang=en-us>
13. (PDF) TinyML-Based Fall Detection for Connected Personal Mobility Vehicles, accessed December 7, 2025, https://www.researchgate.net/publication/356903797_TinyML-Based_Fall_Detection_for_Connected_Personal_Mobility_Vehicles
14. Transfer Learning on Small Datasets for Improved Fall Detection - PMC - NIH, accessed December 7, 2025, <https://pmc.ncbi.nlm.nih.gov/articles/PMC9919743/>
15. A Wearable Fall Detection System based on LoRa LPWAN Technology - ResearchGate, accessed December 7, 2025, https://www.researchgate.net/publication/343315734_A_Wearable_Fall_Detection_System_based_on_LoRa_LPWAN_Technology
16. Securing Fall Detection with Federated Learning: A Privacy-Centric Approach for IoT Healthcare - IEEE Xplore, accessed December 7, 2025, <https://ieeexplore.ieee.org/document/10982741/>
17. Section 3(k) Compliance: Why Inventions as Instructions Face Patent Challenges, accessed December 7, 2025, <https://depenning.com/blog/section-3k-compliance-why-inventions-as-instructions-face-patent-challenges/>
18. Software Patents in India: What's Allowed and What's Not - GenZCFO, accessed December 7, 2025, <https://genzcfo.com/growthx/software-patents-in-india-whats-allowed-and-whats-not>
19. India upgrades its guidelines for computer-related inventions - Obhan & Associates, accessed December 7, 2025, <https://www.obhanandassociates.com/blog/india-upgrades-its-guidelines-for-computer-related-inventions/>

20. Decoding the Ferid Allani case: Learnings for Tech Companies on Software Patenting in India. | Metayage, accessed December 7, 2025, <https://www.metayage.com/blogs/decoding-the-ferid-allani-case>
21. CASE SUMMARY : FERID ALLANI VS UNION OF INDIA - Brilllopedia, accessed December 7, 2025, <https://www.brilllopedia.net/post/case-summary-ferid-allani-vs-union-of-india>
22. Microsoft Technology Licensing LLC V. The Assistant Controller of Patents and Designs- A Reasoned Judgement or Inherently Contradictory? - SpicyIP, accessed December 7, 2025, <https://spicyip.com/2023/12/microsoft-technology-licensing-llc-v-the-assistant-controller-of-patents-and-designs-a-reasoned-judgement-or-inherently-contradictory-2.html>
23. Court criticizes Patent Office for using outdated CRI Guidelines | Intellopedia - BananaIP, accessed December 7, 2025, <https://www.bananaip.com/intellepedia/court-criticizes-patent-office-for-using-outdated-cri-guidelines-computer-related-inventions-patentability/>
24. From Algorithms To AI: Patentability Under The 2025 CRI Draft Guidelines | Intellopedia, accessed December 7, 2025, <https://www.bananaip.com/intellepedia/cri-patent-guidelines-2025-ai-algorithms/>
25. Draft Guidelines for Examination of Computer Related Inventions 2025, accessed December 7, 2025, <https://corporate.cyrilamarchandblogs.com/2025/04/draft-guidelines-for-examination-of-computer-related-inventions-2025/>
26. Updates to Indian computer related inventions guidelines - Latest News - Wilson Gunn, accessed December 7, 2025, <https://www.wilsongunn.com/resource/news/indian-computer-related-inventions-guidelines>
27. Decoding CRI Guidelines 2025 - AIPPI, accessed December 7, 2025, <https://www.aippi.org/news/decoding-cri-guidelines-2025/>
28. US8478418B2 - Remote health monitoring system - Google Patents, accessed December 7, 2025, <https://patents.google.com/patent/US8478418B2/en>
29. Design and Implementation of ESP32-Based Edge Computing for Object Detection - MDPI, accessed December 7, 2025, <https://www.mdpi.com/1424-8220/25/6/1656>
30. Machine Learning Algorithms and Sensor Technologies for Aging-In-Place Applications: A Review - IEEE Xplore, accessed December 7, 2025, <https://ieeexplore.ieee.org/iel8/7361/11169336/11099603.pdf>
31. IDALC: A Semi-Supervised Framework for Intent Detection and Active Learning based Correction - arXiv, accessed December 7, 2025, <https://arxiv.org/html/2511.05921v1>
32. Inside Dyson: Innovation, Design, and the Intellectual Property Behind Disruption, accessed December 7, 2025, <https://www.copperpodip.com/post/inside-dyson-innovation-design-and-the-intellectual-property-behind-disruption>
33. Tiny Federated Learning for Constrained Sensors: A Systematic Literature Review

- IEEE Xplore, accessed December 7, 2025,
<https://ieeexplore.ieee.org/iel8/10347229/10960699/10916688.pdf>
- 34. Easy TinyML on ESP32 and Arduino - Hackster.io, accessed December 7, 2025,
<https://www.hackster.io/news/easy-tinyml-on-esp32-and-arduino-a9dbc509f26c>
- 35. On-Device Learning - GitHub Pages, accessed December 7, 2025,
https://harvard-edge.github.io/cs249r_book/contents/core/ondevice_learning/ondevice_learning.html
- 36. Machine Learning for Microcontroller-Class Hardware: A Review - PMC - PubMed Central, accessed December 7, 2025,
<https://pmc.ncbi.nlm.nih.gov/articles/PMC9683383/>
- 37. TinyOL: TinyML with Online-Learning on Microcontrollers - arXiv, accessed December 7, 2025, <https://arxiv.org/pdf/2103.08295>
- 38. IoT-Based Machine Learning Architecture for Monitoring Water Quality in South Indian Rivers - ijarst, accessed December 7, 2025,
<https://www.ijarst.co.in/Paper26473.pdf>
- 39. Predicting Indoor Carbon Dioxide Concentration using Online Machine Learning - DiVA portal, accessed December 7, 2025,
<https://www.diva-portal.org/smash/get/diva2:1685127/FULLTEXT01.pdf>
- 40. esp32 Archivi - Eloquent Arduino Blog, accessed December 7, 2025,
<https://eloquentarduino.github.io/tag/esp32/>
- 41. Patents - KL University, accessed December 7, 2025,
<https://www.kluniversity.in/cse1/pat.aspx>
- 42. List of Published Patents - SRM University, accessed December 7, 2025,
https://webstor.srmist.edu.in/web_assets/downloads/2023/patents-published.pdf
- 43. Patents | IARE, Best Engineering College, accessed December 7, 2025,
<https://www.iare.ac.in/?q=pages/patents>