



# Transactions

**Database System Concepts, 6<sup>th</sup> Ed.**

©Silberschatz, Korth and Sudarshan

See [www.db-book.com](http://www.db-book.com) for conditions on re-use



# Transaction Concept

- A **transaction** is a *unit* of program execution that accesses and possibly updates various data items.
- E.g. transaction to transfer \$50 from account A to account B:
  1. **read**(A)
  2.  $A := A - 50$
  3. **write**(A)
  4. **read**(B)
  5.  $B := B + 50$
  6. **write**(B)
- Two main issues to deal with:
  - Failures of various kinds, such as hardware failures and system crashes
  - Concurrent execution of multiple transactions



# Example of Fund Transfer

- Transaction to transfer \$50 from account A to account B:
  1. **read**(A)
  2.  $A := A - 50$
  3. **write**(A)
  4. **read**(B)
  5.  $B := B + 50$
  6. **write**(B)
- **Atomicity requirement**
  - if the transaction fails after step 3 and before step 6, money will be “lost” leading to an inconsistent database state
    - ▶ Failure could be due to software or hardware
  - the system should ensure that updates of a partially executed transaction are not reflected in the database
- **Durability requirement** — once the user has been notified that the transaction has completed (i.e., the transfer of the \$50 has taken place), the updates to the database by the transaction must persist even if there are software or hardware failures.



# Example of Fund Transfer (Cont.)

- Transaction to transfer \$50 from account A to account B:
  1. **read**(A)
  2.  $A := A - 50$
  3. **write**(A)
  4. **read**(B)
  5.  $B := B + 50$
  6. **write**(B)
- **Consistency requirement** in above example:
  - the sum of A and B is unchanged by the execution of the transaction
- In general, consistency requirements include
  - ▶ Explicitly specified integrity constraints such as primary keys and foreign keys
  - ▶ Implicit integrity constraints
    - e.g. sum of balances of all accounts, minus sum of loan amounts must equal value of cash-in-hand
  - A transaction must see a consistent database.
  - During transaction execution the database may be temporarily inconsistent.
  - When the transaction completes successfully the database must be consistent
    - ▶ Erroneous transaction logic can lead to inconsistency



# Example of Fund Transfer (Cont.)

- **Isolation requirement** — if between steps 3 and 6, another transaction T2 is allowed to access the partially updated database, it will see an inconsistent database (the sum  $A + B$  will be less than it should be).

**T1**

1. **read**(A)
2.  $A := A - 50$
3. **write**(A)
4. **read**(B)
5.  $B := B + 50$
6. **write**(B)

**T2**

read(A), read(B), print(A+B)

- Isolation can be ensured trivially by running transactions **serially**
  - that is, one after the other.
- However, executing multiple transactions concurrently has significant benefits, as we will see later.



# ACID Properties

A **transaction** is a unit of program execution that accesses and possibly updates various data items. To preserve the integrity of data the database system must ensure:

- **Atomicity.** Either all operations of the transaction are properly reflected in the database or none are.
- **Consistency.** Execution of a transaction in isolation preserves the consistency of the database.
- **Isolation.** Although multiple transactions may execute concurrently, each transaction must be unaware of other concurrently executing transactions. Intermediate transaction results must be hidden from other concurrently executed transactions.
  - That is, for every pair of transactions  $T_i$  and  $T_j$ , it appears to  $T_i$  that either  $T_j$  finished execution before  $T_i$  started, or  $T_j$  started execution after  $T_i$  finished.
- **Durability.** After a transaction completes successfully, the changes it has made to the database persist, even if there are system failures.




# Transaction State

- **Active** – the initial state; the transaction stays in this state while it is executing
- **Partially committed** – after the final statement has been executed.
- **Failed** -- after the discovery that normal execution can no longer proceed.
- **Aborted** – after the transaction has been rolled back and the database restored to its state prior to the start of the transaction. Two options after it has been aborted:
  - restart the transaction
    - ▶ can be done only if no internal logical error
  - kill the transaction
- **Committed** – after successful completion.



# Transaction State (Cont.)







# Concurrent Executions

- Multiple transactions are allowed to run concurrently in the system. Advantages are:
  - **increased processor and disk utilization**, leading to better transaction *throughput*
    - ▶ E.g. one transaction can be using the CPU while another is reading from or writing to the disk
  - **reduced average response time** for transactions: short transactions need not wait behind long ones.
- **Concurrency control schemes** – mechanisms to achieve isolation
  - that is, to control the interaction among the concurrent transactions in order to prevent them from destroying the consistency of the database



# Schedules

- **Schedule** – a sequences of instructions that specify the chronological order in which instructions of concurrent transactions are executed
  - a schedule for a set of transactions must consist of all instructions of those transactions
  - must preserve the order in which the instructions appear in each individual transaction.
- A transaction that successfully completes its execution will have a commit instructions as the last statement
  - by default transaction assumed to execute commit instruction as its last step
- A transaction that fails to successfully complete its execution will have an abort instruction as the last statement



# Schedule 1

- Let  $T_1$  transfer \$50 from  $A$  to  $B$ , and  $T_2$  transfer 10% of the balance from  $A$  to  $B$ .
- A **serial** schedule in which  $T_1$  is followed by  $T_2$  :

$T_1$	$T_2$
read ( $A$ ) $A := A - 50$ write ( $A$ ) read ( $B$ ) $B := B + 50$ write ( $B$ ) commit	read ( $A$ ) $temp := A * 0.1$ $A := A - temp$ write ( $A$ ) read ( $B$ ) $B := B + temp$ write ( $B$ ) commit



# Schedule 2

- A serial schedule where  $T_2$  is followed by  $T_1$

$T_1$	$T_2$
read (A) $A := A - 50$ write (A) read (B) $B := B + 50$ write (B) commit	read (A) $temp := A * 0.1$ $A := A - temp$ write (A) read (B) $B := B + temp$ write (B) commit



# Schedule 3

- Let  $T_1$  and  $T_2$  be the transactions defined previously. The following schedule is not a serial schedule, but it is *equivalent* to Schedule 1.

$T_1$	$T_2$
read (A) $A := A - 50$ write (A)	read (A) $temp := A * 0.1$ $A := A - temp$ write (A)
read (B) $B := B + 50$ write (B) commit	read (B) $B := B + temp$ write (B) commit

In Schedules 1, 2 and 3, the sum  $A + B$  is preserved.



# Schedule 4

- The following concurrent schedule does not preserve the value of  $(A + B)$ .

$T_1$	$T_2$
read (A) $A := A - 50$	read (A) $temp := A * 0.1$ $A := A - temp$ write (A) read (B)
write (A) read (B) $B := B + 50$ write (B) commit	         $B := B + temp$ write (B) commit



# Serializability

- **Basic Assumption** – Each transaction preserves database consistency.
- Thus serial execution of a set of transactions preserves database consistency.
- A (possibly concurrent) schedule is serializable if it is equivalent to a serial schedule. Different forms of schedule equivalence give rise to the notions of:
  1. **conflict serializability**
  2. **view serializability**



# Conflicting Instructions

- Instructions  $I_i$  and  $I_j$  of transactions  $T_i$  and  $T_j$  respectively, **conflict** if and only if there exists some item  $Q$  accessed by both  $I_i$  and  $I_j$ , and at least one of these instructions wrote  $Q$ .
  1.  $I_i = \text{read}(Q)$ ,  $I_j = \text{read}(Q)$ .  $I_i$  and  $I_j$  don't conflict.
  2.  $I_i = \text{read}(Q)$ ,  $I_j = \text{write}(Q)$ . They conflict.
  3.  $I_i = \text{write}(Q)$ ,  $I_j = \text{read}(Q)$ . They conflict
  4.  $I_i = \text{write}(Q)$ ,  $I_j = \text{write}(Q)$ . They conflict
- Intuitively, a conflict between  $I_i$  and  $I_j$  forces a (logical) temporal order between them.
  - If  $I_i$  and  $I_j$  are consecutive in a schedule and they do not conflict, their results would remain the same even if they had been interchanged in the schedule.





# Conflict Serializability

- If a schedule  $S$  can be transformed into a schedule  $S'$  by a series of swaps of non-conflicting instructions, we say that  $S$  and  $S'$  are **conflict equivalent**.
- We say that a schedule  $S$  is **conflict serializable** if it is conflict equivalent to a serial schedule



# Conflict Serializability (Cont.)

- Schedule 3 can be transformed into Schedule 6, a serial schedule where  $T_2$  follows  $T_1$ , by series of swaps of non-conflicting instructions. Therefore Schedule 3 is conflict serializable.

$T_1$	$T_2$
read (A) write (A)	read (A) write (A)
read (B) write (B)	read (B) write (B)

Schedule 3

$T_1$	$T_2$
read (A) write (A) read (B) write (B)	read (A) write (A) read (B) write (B)

Schedule 6



# Conflict Serializability (Cont.)

- Example of a schedule that is not conflict serializable:

$T_3$	$T_4$
read ( $Q$ )	write ( $Q$ )
write ( $Q$ )	

- We are unable to swap instructions in the above schedule to obtain either the serial schedule  $\langle T_3, T_4 \rangle$ , or the serial schedule  $\langle T_4, T_3 \rangle$ .



# View Serializability

- Let  $S$  and  $S'$  be two schedules with the same set of transactions.  $S$  and  $S'$  are **view equivalent** if the following three conditions are met, for each data item  $Q$ ,
  1. If in schedule  $S$ , transaction  $T_i$  reads the initial value of  $Q$ , then in schedule  $S'$  also transaction  $T_i$  must read the initial value of  $Q$ .
  2. If in schedule  $S$  transaction  $T_i$  executes **read**( $Q$ ), and that value was produced by transaction  $T_j$  (if any), then in schedule  $S'$  also transaction  $T_i$  must read the value of  $Q$  that was produced by the same **write**( $Q$ ) operation of transaction  $T_j$ .
  3. The transaction (if any) that performs the final **write**( $Q$ ) operation in schedule  $S$  must also perform the final **write**( $Q$ ) operation in schedule  $S'$ .

As can be seen, view equivalence is also based purely on **reads** and **writes** alone.



# View Serializability (Cont.)

- A schedule  $S$  is **view serializable** if it is view equivalent to a serial schedule.
- Every conflict serializable schedule is also view serializable.
- Below is a schedule which is view-serializable but *not* conflict serializable.

$T_{27}$	$T_{28}$	$T_{29}$
read ( $Q$ )	write ( $Q$ )	
write ( $Q$ )		write ( $Q$ )

- What serial schedule is above equivalent to?
- Every view serializable schedule that is not conflict serializable has **blind writes**.