



# **Relational Databases (contd.)**

**Database System Concepts, 6<sup>th</sup> Ed.**

©Silberschatz, Korth and Sudarshan

See [www.db-book.com](http://www.db-book.com) for conditions on re-use



# Integrity Constraints

- Integrity constraints guard against accidental damage to the database, by ensuring that authorized changes to the database do not result in a loss of data consistency.
  - A checking account must have a balance greater than \$10,000.00
  - A salary of a bank employee must be at least \$4.00 an hour
  - A customer must have a (non-null) phone number



# Integrity Constraints on a Single Relation

- not null
- primary key
- unique
- **check** (P), where P is a predicate



# Not Null and Unique Constraints

## ■ not null

- Declare *name* and *budget* to be **not null**

*name* **varchar(20) not null**

*budget* **numeric(12,2) not null**

## ■ unique ( $A_1, A_2, \dots, A_m$ )

- The unique specification states that the attributes

$A_1, A_2, \dots, A_m$

form a candidate key.

- Candidate keys are permitted to be null (in contrast to primary keys).



# The check clause

## ■ **check** (P)

where P is a predicate

Example: ensure that semester value is one of fall, winter, spring or summer:

```
create table section (  
    course_id varchar (8),  
    sec_id varchar (8),  
    semester varchar (6),  
    year numeric (4,0),  
    building varchar (15),  
    room_number varchar (7),  
    time slot id varchar (4),  
    primary key (course_id, sec_id, semester, year),  
    check (semester in ('Fall', 'Winter', 'Spring', 'Summer'))  
);
```



# Referential Integrity

- Ensures that a value that appears in one relation for a given set of attributes also appears for a certain set of attributes in another relation.
  - Example: If “Biology” is a department name appearing in one of the tuples in the *instructor* relation, then there exists a tuple in the *department* relation for “Biology”.
- Let A be a set of attributes. Let R and S be two relations that contain attributes A and where A is the primary key of S. A is said to be a **foreign key** of R if for any values of A appearing in R these values also appear in S.



# Cascading Actions in Referential Integrity

- **create table** *course* (  
    *course\_id* **char**(5),  
    *title* **varchar**(20),  
    *dept\_name* **varchar**(20),  
    **primary key** (*course\_id*)  
    **foreign key** (*dept\_name*) **references** *department*)
- **create table** *course* (  
    ...  
    *dept\_name* **varchar**(20),  
    **foreign key** (*dept\_name*) **references** *department*  
        **on delete cascade**  
        **on update cascade**,  
    ...  
)
- alternative actions to cascade: **set null, set default**



# Triggers

- A **trigger** is a statement that is executed automatically by the system as a side effect of a modification to the database.
- To design a trigger mechanism, we must:
  - Specify the conditions under which the trigger is to be executed.
  - Specify the actions to be taken when the trigger executes.
- Triggers introduced to SQL standard in SQL:1999, but supported even earlier using non-standard syntax by most databases.
  - Syntax illustrated here may not work exactly on your database system; check the system manuals





# Trigger Example

- E.g. *time\_slot\_id* is not a primary key of *timeslot*, so we cannot create a foreign key constraint from *section* to *timeslot*.
- Alternative: use triggers on *section* and *timeslot* to enforce integrity constraints

**create trigger** *timeslot\_check1* **after insert on** *section*

**referencing new row as** *nrow*

**for each row**

**when** (*nrow.time\_slot\_id* **not in** (

**select** *time\_slot\_id*

**from** *time\_slot*)) */\* time\_slot\_id not present in time\_slot \*/*

**begin**

**rollback**

**end;**



# Trigger Example Cont.

```
create trigger timeslot_check2 after delete on timeslot  
  referencing old row as orow  
  for each row  
  when (orow.time_slot_id not in (  
    select time_slot_id  
    from time_slot)  
    /* last tuple for time slot id deleted from time slot */  
    and orow.time_slot_id in (  
      select time_slot_id  
      from section)) /* and time_slot_id still referenced from section */  
  begin  
    rollback  
  end;
```



# Triggering Events and Actions in SQL

- Triggering event can be **insert**, **delete** or **update**
- Triggers on update can be restricted to specific attributes
  - **E.g., after update of *takes* on *grade***
- Values of attributes before and after an update can be referenced
  - **referencing old row as** : for deletes and updates
  - **referencing new row as** : for inserts and updates
- Triggers can be activated before an event, which can serve as extra constraints. E.g. convert blank grades to null.

```
create trigger setnull_trigger before update of takes  
referencing new row as nrow  
for each row  
when (nrow.grade = ' ')  
begin atomic  
    set nrow.grade = null;  
end;
```



# Trigger to Maintain `credits_earned` value

- **create trigger** *credits\_earned* **after update of** *takes on* (*grade*)  
referencing new row as *nrow*  
referencing old row as *orow*  
**for each row**  
**when** *nrow.grade* <> 'F' **and** *nrow.grade* **is not null**  
    **and** (*orow.grade* = 'F' **or** *orow.grade* **is null**)  
**begin atomic**  
    **update** *student*  
    **set** *tot\_cred* = *tot\_cred* +  
        (**select** *credits*  
          **from** *course*  
          **where** *course.course\_id* = *nrow.course\_id*)  
    **where** *student.id* = *nrow.id*;  
**end;**



# When Not To Use Triggers

- Triggers were used earlier for tasks such as
  - maintaining summary data (e.g., total salary of each department)
  - Replicating databases by recording changes to special relations (called **change** or **delta** relations) and having a separate process that applies the changes over to a replica
- There are better ways of doing these now:
  - Databases today provide built in materialized view facilities to maintain summary data
  - Databases provide built-in support for replication
- Encapsulation facilities can be used instead of triggers in many cases
  - Define methods to update fields
  - Carry out actions as part of the update methods instead of through a trigger
- Risk of unintended execution of triggers, for example, when
  - loading data from a backup copy
  - replicating updates at a remote site
  - Trigger execution can be disabled before such actions.
- Other risks with triggers:
  - Error leading to failure of critical transactions that set off the trigger
  - Cascading execution



# Views

- In some cases, it is not desirable for all users to see the entire logical model (that is, all the actual relations stored in the database.)
- Consider a person who needs to know an instructors name and department, but not the salary. This person should see a relation described, in SQL, by

```
select ID, name, dept_name  
from instructor
```

- A **view** provides a mechanism to hide certain data from the view of certain users.
- Any relation that is not of the conceptual model but is made visible to a user as a “virtual relation” is called a **view**.



# View Definition

- A view is defined using the **create view** statement which has the form

**create view** *v* **as** < query expression >

where <query expression> is any legal SQL expression. The view name is represented by *v*.

- Once a view is defined, the view name can be used to refer to the virtual relation that the view generates.
- View definition is not the same as creating a new relation by evaluating the query expression
  - Rather, a view definition causes the saving of an expression; the expression is substituted into queries using the view.



# Example Views

- A view of instructors without their salary  
**create view** *faculty* **as**  
    **select** *ID, name, dept\_name*  
    **from** *instructor*
- Find all instructors in the Biology department  
**select** *name*  
**from** *faculty*  
**where** *dept\_name* = 'Biology'
- Create a view of department salary totals  
**create view** *departments\_total\_salary*(*dept\_name, total\_salary*) **as**  
    **select** *dept\_name, sum (salary)*  
    **from** *instructor*  
    **group by** *dept\_name*;





# Views Defined Using Other Views

- **create view** *physics\_fall\_2009* **as**  
    **select** *course.course\_id, sec\_id, building, room\_number*  
    **from** *course, section*  
    **where** *course.course\_id = section.course\_id*  
          **and** *course.dept\_name = 'Physics'*  
          **and** *section.semester = 'Fall'*  
          **and** *section.year = '2009'*;
- **create view** *physics\_fall\_2009\_watson* **as**  
    **select** *course\_id, room\_number*  
    **from** *physics\_fall\_2009*  
    **where** *building = 'Watson'*;



# View Expansion

- Expand use of a view in a query/another view

```
create view physics_fall_2009_watson as  
(select course_id, room_number  
from (select course.course_id, building, room_number  
      from course, section  
      where course.course_id = section.course_id  
           and course.dept_name = 'Physics'  
           and section.semester = 'Fall'  
           and section.year = '2009')  
where building = 'Watson';
```



# Update of a View

- Add a new tuple to *faculty* view which we defined earlier

**insert into *faculty* values** ('30765', 'Green', 'Music');

This insertion must be represented by the insertion of the tuple

('30765', 'Green', 'Music', null)

into the *instructor* relation



# Some Updates cannot be Translated Uniquely

- **create view** *instructor\_info* **as**  
    **select** *ID, name, building*  
    **from** *instructor, department*  
    **where** *instructor.dept\_name= department.dept\_name;*
- **insert into** *instructor\_info* **values** ('69987', 'White', 'Taylor');
  - ▶ which department, if multiple departments in Taylor?
  - ▶ what if no department is in Taylor?
- Most SQL implementations allow updates only on simple views
  - The **from** clause has only one database relation.
  - The **select** clause contains only attribute names of the relation, and does not have any expressions, aggregates, or **distinct** specification.
  - Any attribute not listed in the **select** clause can be set to null
  - The query does not have a **group** by or **having** clause.



# More Problems

- **create view** *history\_instructors* **as**  
    **select** \*  
    **from** *instructor*  
    **where** *dept\_name*= 'History';
- What happens if we insert ('25566', 'Brown', 'Biology', 100000) into *history\_instructors*?



# Materialized Views

- Certain database systems allow view relations to be stored
- View Maintenance
  - If the actual relations used in the view definition change, the view is kept up to date.
- Applications that use a view frequently benefit from materialized views
- Fast response for view-based queries