# Static and Dynamic List
# Chapter 4

notes.arpanadhikari7.com.np

Presented by: Er. Aruna Chhatkuli

Nepal College of Information Technology,
Balkumari, Lalitpur




Available on notes.arpanadhikari7.com.np

# Introduction

## List

- List is an ordered set consisting of number of elements to which addition, deletion operation can be done on the elements.

- The first element of the list is called the head of list whereas the last element is called tail of the list.




notes.arpanadhikari7.com.np




Available on notes.arpanadhikari7.com.np

# Introduction

## List

- The next element of the head of the list is called successor and the previous element is called the predecessor.
- So a head doesn't have a predecessor and a tail doesn't have successor and the element in between has both one successor and predecessor.




notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Basic operation on List

1. Traversing an array list.
2. Searching an element in the list.
3. Insertion of an element in the list.
4. Deletion of an element in the list

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Traversing an array List

- Take an array of size 10 which has 5 elements

| 10 | 20 | 30 | 40 | 50 |
|---|---|---|---|---|

Traversing an array list:-

- Here each element can be found through indeed no. of array & is incremented by 1.

  When, index =0.

Then, Arr[0] = 10 ⇒ determines 1st element in array.

Index = index +1.

Then, Arr[index]= 20.

notes.arpanadhikari7.com.np

- In this way we can transverse each element of array by incrementing the index by 1 until index is not greater than no. of elements.



Available on notes.arpanadhikari7.com.np

# Searching in an array list

## Searching in an array list:-

- For searching an element, we first travers the array list and while traversing, we compare each element of array with the given element.

```
int i, item;
for (i=0;i<n:i++)
{
        if(item==arr[i])
        {
                printf("Element Found");
                return;
        }
}
```

notes.arpanadhikari7.com.np




Available on notes.arpanadhikari7.com.np

# Insertion of the element in list

## Insertion can be done in two ways:

1. Insertion at end
2. Insertion in between

### Insertion at end




- Set the array index to the total no. of elements in the array and then insert the element

notes.arpanadhikari7.com.np


- index= total no. of elements (i.e. 5)
- Arr[index] = value of inserted element



Available on notes.arpanadhikari7.com.np

# Insertion of the element in list

## Insertion in between




- Shift right one position all array elements from last element to the array element before which we want to insert the element.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Insertion of the element in list

**Variables we are using here:**

1. **arr :** Name of the array.
2. **size :** Size of the array (i.e., total number of elements in the array)
3. **i :** Loop counter or counter variable for the for loop.
4. **x :** The data element to be insert.
5. **pos :** The position where we wish to insert the element.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Insertion of the element in list

The following algorithm inserts a data element x into a *given position* pos *(position specified by the programmer)* in a linear array arr.

**Algorithm to Insert an element in an Array:**

1. Start
2. [Reset size of the array. ] set size = size + 1
3. [Initialize counter variable. ] Set i = size – 1
4. For i = size - 1 to i >= pos – 1
   I. [Move $i^{th}$ element forward. ] set arr[i+1] = arr[i]
   II. [Decrease counter. ] Set i = i – 1
   III. [End of step 4 loop. ]
5. [Insert element. ] Set arr[pos-1] = x
6. Stop.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Insertion of the element in list

```
int temp, item, pos,n;
if(pos==n){
printf("List overflow");
return;
}
if(pos > n+1)
{
printf("Enter position less than or
equal to %d", n+1);
        return;
}
if(pos == n+1){          // Insertion at end

        arr[n] = item;
        n = n+1
        return;
}
temp = n-1;    // Insertion in between

while(temp>=position-1) {

        arr[temp+1] = arr[temp];
        Temp- - ;
}
arr[position-1] = item;
n=n+1;
```


notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Deletion at end

**Deletion of the last element:-**




Traverse the array last and if the item is last item of the array, then delete that element & decrease the total no of element by 1,


notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Deletion in between

- First traverse the array list & compare array element with the element which is to be deleted.
- shift left one position from the next element to the last element of array
- decrease the total no. of elements by 1.






Available on notes.arpanadhikari7.com.np

# Deletion in between

```
int temp, position , item, n;
If (n= = 0)     // present or not element
{
printf("list underflow");
Return;
}
If (item == arr [n-1]) //deletion at the end.
{
n = n- 1;
return;
}
temp = position -1;
While (temp < = n -1)
{
Arr [temp] = arr [temp +1]
temp + + ;
}
n = n -1;
Return;
}
```

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Advantages and Disadvantages of List

## Advantages

Easy to compute the address of the array through the index.

## Disadvantages of list

- Use of contiguous list which is time consuming.
- As array size is declared, we cannot take elements more than the array size.
- If the elements are less than the size of array, then there is wastage of memory.
- Too many shift operation on insertion and deletion.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# STATIC IMPLEMENTATION OF LIST

- Static implementation can be implemented using arrays.
- It is very simple method but it has Static implementation.
- Once a size is declared, it cannot be change during the program execution. It is also not efficient for memory utilization.
- When array is declared, memory allocated is equal to the size of the array.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# STATIC IMPLEMENTATION OF LIST

- The vacant space of array also occupiers the memory space.
- In both cases, if we store fewer arguments than declared, the memory is wasted and if more elements are stored than declared, array cannot be expanded.
- **It is suitable only when exact numbers of elements are to be stored.**

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# DYNAMIC IMPLEMENTATION OF LIST

- In static implementation of memory allocation, we cannot alter (increase or decrease) the size of an array and the memory allocation is fixed.

- There is a special data structure called linked list that provides a more flexible storage system and it does not required the use of array.

- **The advantage of a list over an array occurs when it is necessary to insert or delete an element in the middle of a group of other elements.**


notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# LINKED LIST

- A **linked list** is a **linear collection** of **specially designed data structure, called nodes**, **linked** to one another by means of **pointer**.
- Each node is divided into 2 parts: the first part contains information of the element and the second part contains address of the next node in the link list.




notes.arpanadhikari7.com.np

Fig1: Node



Available on notes.arpanadhikari7.com.np

# LINKED LIST





Fig2: Linked List

- Above Fig2 shows that the schematic diagram of a linked list with 3 nodes. Each node is divide with two parts.
- The left part of each node contains the data items and the right part represents the address of the next node.
- The next pointer of the **last node** contains a special value, called the NULL pointer, which does not point to any address of the node.
- That is NULL pointer indicates the end of the linked list.
- **START pointer** will hold the address of the 1st node in the list.
- **START =NULL if there is no list (i.e.; NULL list or empty list).**



Available on notes.arpanadhikari7.com.np

# Representation of Linked List

- List Suppose we want to store a list of integer numbers using linked list. Then it can be schematically represented as:





Fig3: Linked List Representation

➢We can declare linear linked list as follows:

```
struct Node{
        int data;                   //instead of data we also use info
        struct Node *Next;          //instead of Next we also use link
}; typedef struct Node *NODE;
```

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Advantages and Disadvantages of Linked List

Linked list have many **advantages** and some of them are:

1. Linked list are **dynamic data structure**. That is, they can grow or shrink during the execution of a program.
2. **Efficient memory utilization:** In linked list (or dynamic) representation, **memory is not pre allocated**. Memory is **allocated whenever it is required**. And it is **deallocated** (or removed) when it is not needed.
3. Insertion and deletion are easier and efficient. Linked list provides **flexibility** in **inserting a data item** at a **specified position** and **deletion** of a data item from the **given position**.
4. Many **complex applications** can be easily **carried out** with **linked list.**

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Advantages and Disadvantages of Linked List

Linked list have many **disadvantages** and some of them are:

1. **More memory:** to store an integer number, a node with integer data and address field is allocated. That is more memory space is needed.
2. Access to an arbitrary data item is little bit cumbersome and also time consuming.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Operations on Linked List (Primitive Operations)

The primitive operations performed on Linked list is as follows:

1. Creation
2. Insertion
3. Deletion
4. Traversing
5. Searching
6. Find Previous
7. Concatenation

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Operations on Linked List (Primitive Operations)

- **Creation** operation is used to create a linked list. Once a linked list is created with one node, insertion operation can be used to add more elements in a node.

```
Struct node{
int info;
Struct node *link;    //which is self referential structure also known as structure pointer
}
```

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Operations on Linked List (Primitive Operations)

- **Insertion** operation is used to **insert a new node** at any **specified location** in the linked list.
- A new node may be inserted:
  i. At the beginning of the linked list
  ii. At the end of the linked list
  iii. At any specified position in between in a linked list

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Operations on Linked List (Primitive Operations)

- **Deletion** operation is used to delete an item (or node) from the linked list.

- A node may be deleted from the
  i. Beginning of a linked list
  ii. End of a linked list
  iii. Specified location of the linked list

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Operations on Linked List (Primitive Operations)

- **Traversing** is the process of going through all the nodes from one end to another end of a linked list.

- In a singly linked list we can **visit from left to right**, **forward traversing**, nodes only.

- But in doubly linked list **forward and backward** traversing is possible.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Operations on Linked List (Primitive Operations)

- **Concatenation** is the process of appending the second list to the end of the first list.
- Consider a list **A** having **n** nodes and **B** with **m** nodes.
- Then the operation concatenation will place the **1st node of B in the (n+1) the node in A.**
- After concatenation **A** will contain **(n+m)** nodes.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Types of Linked List

Following are the types of Linked list depending upon the arrangements of the nodes:

1. Singly Linked List
2. Doubly linked List
3. Circular Linked List
    i. Circular Singly Linked List
    ii. Circular Doubly Linked List

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# SINGLY LINKED LIST

- All the nodes in a singly linked list are arranged sequentially by linking with a pointer.
- A singly linked list can grow or shrink, because it is a dynamic data structure.
- The following figure explains the different operations on Singly Linked List.





Fig4: Create a node with Data (30)






Fig5: Insert a node with Data (40) at the end

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# SINGLY LINKED LIST








Fig6: Insert a node with Data (10) at the beginning

Fig7: Insert a node with Data (20) at 2nd position





Fig8: Insert a node with Data (50) at the end

Output → 10, 20, 30, 40, 50

Fig9: Traversing the nodes from left to right

notes.arpanadhikari7.com.np




Fig10: Delete 3rd node from the



Available on notes.arpanadhikari7.com.np

# SINGLY LINKED LIST

## Algorithm For Inserting A Node:





Fig11: Insertion of New Node at specific position

- Suppose **START** is the first position in linked list. Let **DATA** be the element to be inserted in the new node.
- **POS** is the position where the new node is to be inserted. **TEMP** is a temporary pointer to hold the node address.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np


# Insert a Node at the beginning of Linked List

1. Read DATA to be inserted
2. Create a NewNode
3. NewNode → DATA = DATA
4. If (START equal to NULL)
   i. NewNode → next = NULL
   ii. start = Newnode.
5. Else

i. NewNode → next = START

ii. START = NewNode

7. Exit





notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Insert a Node at the end of Linked List

1. Read DATA to be inserted
2. Create a NewNode
3. NewNode → DATA = DATA
4. NewNode → Next = NULL
5. If (SATRT equal to NULL)
   a. START = NewNode
6. Else
   a. TEMP = START
   b. While (TEMP → Next not equal to NULL)
      i. TEMP = TEMP → Next
7. TEMP → Next = NewNode
8. Exit





notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Insert a Node at any specified position of Linked List


1. Read DATA and POS to be inserted.
2. Initialize TEMP = START; and count = 1.
3. Repeat the step 3 for (count = 1; count <pos-1; count++)
   a. TEMP = TEMP->Next
   b. If (TEMP ==NULL)
      i. Display “Node in the list less than the position”
      ii. Exit
4. Create a New Node
5. NewNode → DATA = DATA
6. NewNode → Next = TEMP → Next
7. TEMP → Next = NewNode
8. Exit




notes.arpanadhikari7.com.np




Available on notes.arpanadhikari7.com.np





position = 2 Node to be inserted = 6

```
for (int i=1;i<(pos - 1); i++)
{ curr = curr → next; }
```


As i = 1 is not less than (position - 1) = 2 - 1, loop will terminate




Make newNode → next = curr → next




Make curr → next = newnode




notes.arpanadhikari7.com.np

## Final linked list






Available on notes.arpanadhikari7.com.np

# Algorithm For Display All Nodes

- Suppose START is the address of the first node in the linked list. Following algorithm will visit all nodes from the START node to the end.

1. Start.
2. If (START is equal to NULL)
   i. Display “The list is Empty”
   ii. Exit
3. Initialize TEMP = START
4. Repeat the step 4 and 5 until (TEMP->next !=NULL)
   i. Display “TEMP → DATA”
   ii. TEMP = TEMP → Next
5. Display TEMP-> DATA
6. Exit

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# SINGLY LINKED LIST

## Algorithm For Deleting A Node





Fig12: Deletion of Node

- Suppose START is the first position in linked list.
- Let DATA be the element to be deleted.
- previous, current is a temporary pointer to hold the node address.



Available on notes.arpanadhikari7.com.np


# Deletion in singly linked list at beginning

## Algorithm

- **Step 1:** IF HEAD = NULL

  Write UNDERFLOW
  Go to Step 5
  [END OF IF]

- **Step 2:** SET PTR = HEAD
- **Step 3:** SET HEAD = HEAD -> NEXT
- **Step 4:** FREE PTR
- **Step 5:** EXIT





notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# SINGLY LINKED LIST: Algorithm For Deleting A Last Node

- **Step 1:** IF HEAD == NULL
  Write UNDERFLOW
  Go to Step 8
  [END OF IF]
- **Step 2:** SET PTR = HEAD
- **Step 3:** Repeat Steps 4 and 5 while (PTR -> NEXT!= NULL)
  - **Step 4:** SET PTR1 = PTR
  - **Step 5:** SET PTR = PTR -> NEXT
  - [END OF LOOP]
- **Step 6:** SET PTR1-> NEXT = NULL
- **Step 7:** FREE PTR
- **Step 8:** EXIT




Deleting a node from the last


notes.arpanadhikari7.com.np




Available on notes.arpanadhikari7.com.np

# Algorithm For Deleting at specified position

1. Enter the position POS
2. Set previous = current=START
3. Set i=0
4. while (i<POS-1)
   i. Previous = current
   ii. current=current->next
   iii. i++
5. previous->next=current->next
6. Free(current)
7. Exit




notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Algorithm For Searching A Node

1. Read the DATA to be searched
2. Initialize TEMP = START; POS =1;
3. DO the step 4, 5 and 6.
4. If (TEMP → DATA is equal to DATA)
   i. Display “The data is found at POS”
   ii. Exit
5. TEMP = TEMP → Next
6. POS = POS+1
7. WHILE(TEMP->next!=NULL)
8. If (TEMP is equal to NULL)
   i. Display “The data is not found in the list”
9. Exit

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

## Stack Using Linked List

The following figure shows that the implementation of stack using linked list:





Fig13: Push (10)





Fig14: Push (20)





Fig15: Push (30)








Fig16: X = Pop (i.e. X=30)

Fig17: Push (40)

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Algorithm For Push Operation

Suppose TOP is a pointer, which is pointing towards the topmost element of the stack. TOP is NULL when the stack is empty. DATA is the data item to be pushed.

1. Read the DATA to be pushed
2. Create a New Node
3. NewNode → DATA = DATA
4. If(TOP == NULL)
   i. TOP = NewNode
   ii. NewNode → Next = NULL
5. Else
   i. NewNode → Next = TOP
   ii. TOP = NewNode
6. Exit

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Algorithm For Pop Operation

- Algorithm For POP Operation Suppose TOP is a pointer, which is pointing towards the topmost element of the stack.
- TOP is NULL when the stack is empty.
- TEMP is pointer variable to hold any nodes address. DATA is the information on the node which is just deleted.

1. if (TOP is equal to NULL)
   a. Display “The stack is empty”
2. Else
   a. TEMP = TOP
   b. Display “The popped element TOP → DATA”
   c. TOP = TOP → Next
   d. TEMP → Next = NULL
   e. Free(TEMP)
3. Exit

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Queue Using Linked List

The following figure shows that the implementation issues of Queue using linked list.




Fig18: Enqueue (10)





Fig19: Enqueue (20)





Fig20: Enqueue (30)





Fig21: Enqueue (20)

notes.arpanadhikari7.com.np





Fig22: X = Dequeue (i.e. X = 10)



Available on notes.arpanadhikari7.com.np

# Algorithm for insert an element into a Queue

- ❖REAR is a pointer in queue where the new elements are added.
- ❖FRONT is a pointer, which is pointing to the queue where the elements are popped. DATA is an element to be pushed.

1. Start.
2. Read the DATA element to be pushed.
3. Create a New Node.
4. NewNode → DATA = DATA
5. NewNode → Next = NULL
6. If(FRONT==NULL && REAR == NULL)
   i. FRONT = NewNode
   ii. REAR = NewNode
7. If(REAR not equal to NULL)
   i. REAR → next = NewNode;
8. REAR =NewNode;
9. Exit

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

## Algorithms for delete an element from the queue

- REAR is a pointer in queue where the new elements are added.
- FRONT is a pointer, which is pointing to the queue where the elements are popped. DATA is an element popped from the queue.

1. Start.
2. If (FRONT is equal to NULL)
   i. Display “The Queue is empty”
3. Else
   i. Display “The popped element is FRONT → DATA”
   ii. If (FRONT is not equal to REAR)
      a. Temp = front
      b. FRONT = FRONT → Next
      c. Free(temp)
   iii. Else
      a. FRONT = NULL;
4. Exit

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

## Advantages and Advantages of Singly Linked List

## Advantages of Singly Linked List

1. Accessibility of a node in the forward direction is easier.
2. Insertion and deletion of node are easier.

## Disadvantages of Singly Linked List

1. Can insert only after a referenced node.
2. Removing node requires pointer to previous node.
3. Can traverse list only in the forward direction.

notes.arpanadhikari7.com.np




Available on notes.arpanadhikari7.com.np

# Doubly Link List

- A doubly linked list is one in which all nodes are linked together by multiple links which help in accessing both the successor (next) and predecessor (previous) node for any arbitrary node within the list.

- Every nodes in the doubly linked list has three fields: LeftPointer(Prev), RightPointer(Next) and DATA.




notes.arpanadhikari7.com.np




Available on notes.arpanadhikari7.com.np

# Doubly Link List

- Prev will point to the node in the left side (or previous node) i.e. Prev will hold the address of the previous node. Next will point to the node in the right side (or next node), i.e. Next will hold the address of next node.
- DATA will store the information of the node.

```
struct Node  {
    int data;
    struct Node* next;
    struct Node* prev;
};
```




notes.arpanadhikari7.com.np

Fig23:Doubly Link List



Available on notes.arpanadhikari7.com.np

# Doubly Link List

❖Representation of Doubly Linked List Following declaration can represent doubly linked list

```
struct Node {
        int data;
        struct Node *Next;
        struct Node *Prev;
};
struct Node *NODE;
```

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Doubly Linked List

- All the primitive operations performed on singly linked list can also be performed on doubly linked list.
- The following figures shows that the insertion and deletion of nodes.




Fig25: Add (20)





Fig26: Insert (30) at the end





Fig27: Insert (10) at the Beginning




Fig28: Delete a node at the 2nd position (Delete 20 at 2nd position)


notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

## Algorithm for Inserting a Node in doubly linked list

- Suppose START is the first position in linked list.
- Let DATA be the element to be inserted in the new node.
- POS is the position where the NewNode is to be inserted.
- TEMP is a temporary pointer to hold the node address.




notes.arpanadhikari7.com.np


Fig29: Insert a node at the 2nd position



Available on notes.arpanadhikari7.com.np

# Insertion in doubly linked list at beginning

1. START
2. CREATE NEW_NODE
3. NEW_NODE->DATA = DATA
4. IF(HEAD == NULL)
   i. HEAD = NEW_NODE
   ii. NEW_NODE->PREV = NULL
   iii. NEW_NODE->NEXT = NULL
5. ELSE
   i. NEW_NODE -> PREV = NULL
   ii. NEW_NODE -> NEXT = HEAD
   iii. HEAD -> PREV = NEW_NODE
   iv. HEAD = NEW_NODE
6. EXIT




Insertion into doubly linked list at beginning

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Insertion in doubly linked list at End

**Step 1:** CREATE NEW_NODE

**Step 2:** SET NEW_NODE -> DATA = DATA

**Step 3:** IF (HEAD == NULL)

SET HEAD = NEWNODE

NEW_NODE -> NEXT = NULL

NEW_NODE->PREV = NULL

**Step 4 ELSE**

SET TEMP = HEAD

while (TEMP -> NEXT != NULL)

SET TEMP = TEMP -> NEXT


[END OF LOOP]

**Step 5:** SET TEMP -> NEXT = NEW_NODE

**Step 6:** SET NEW_NODE -> PREV = TEMP

Step 7: SET NEW_NODE ->NEXT = NULL

**Step 7:** EXIT




Insertion into doubly linked list at the end

notes.arpanadhikari7.com.np




Available on notes.arpanadhikari7.com.np

# Algorithm for Inserting a Node at specified position in doubly linked list

1. Start.
2. Read the DATA and POS
3. Initialize TEMP = START, i=1;
4. While((i<POS-1) and (TEMP is not equal to NULL) )
   i. TEMP = TEMP → Next
   ii. i++
5. If (TEMP not equal to NULL) and (i equal to POS-1)
   i. Create a New Node
   ii. NewNode → DATA = DATA
   iii. NewNode → Next = TEMP → Next
   iv. NewNode → Prev = TEMP
   v. (TEMP → Next) → Prev = NewNode
   vi. TEMP → Next = New Node
6. Else
   a. Display “Position NOT found”
7. Exit.

notes.arpanadhikari7.com.np




Insertion into doubly linked list after specified node



Available on notes.arpanadhikari7.com.np

# Algorithm for Deleting a Node in doubly linked list

- Suppose START is the address of the first node in the linked list.
- Let POS is the position of the node to be deleted.
- TEMP is the temporary pointer to hold the address of the node.
- After deletion, DATA will contain the information on the deleted node.





Fig30: Delete a node at the 2nd position

notes.arpanadhikari7.com.np




Available on notes.arpanadhikari7.com.np

# Algorithm for Deleting a Node at beginning in doubly linked list

- **STEP 1:** IF HEAD = NULL

  WRITE UNDERFLOW
  GOTO STEP 6
- **STEP 2:** SET PTR = HEAD
- **STEP 3:** SET HEAD = HEAD → NEXT
- **STEP 4:** SET HEAD → PREV = NULL
- **STEP 5:** FREE PTR
- **STEP 6:** EXIT




Deletion in doubly linked list from beginning

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# An algorithm to delete last element in double linked list


- **Step 1:** IF HEAD = NULL

  Write UNDERFLOW
  Go to Step 6
  [END OF IF]
- **Step 2:** SET TEMP = HEAD
- **Step 3:** REPEAT STEP 4 WHILE TEMP->NEXT != NULL

  SET TEMP = TEMP->NEXT

  [END OF LOOP]
- **Step 4:** SET (TEMP ->PREV)-> NEXT = NULL
- **Step 5:** FREE TEMP
- **Step 6:** EXIT

notes.arpanadhikari7.com.np




Deletion in doubly linked list at the end




Available on notes.arpanadhikari7.com.np

# Algorithm for Deleting a Node in specified position

1. **Step 1:**IF HEAD = NULL
   Write UNDERFLOW
   Go to Step 7
   [END OF IF]
2. **Step 2:** SET TEMP = HEAD
3. **Step 3:** Repeat Step 4 while (TEMP -> DATA != ITEM)
   SET PTR = TEMP
   SET TEMP = TEMP->NEXT
   [END OF LOOP]
4. **Step 4:** SET PTR->NEXT = TEMP->NEXT
5. **Step 5:** SET (TEMP->NEXT)->PREV = PTR
6. **Step 6:** FREE TEMP
7. **Step 7:** EXIT

notes.arpanadhikari7.com.np




Deletion of a specified node in doubly linked list



Available on notes.arpanadhikari7.com.np

# CIRCULAR LINKED LIST

- A circular linked list is one, which has no beginning and no end.

- A singly linked list can be made a circular linked list by simply storing the address of the very first node in the linked field of the last node.

- Circular linked lists also make our implementation easier, because they eliminate the boundary conditions associated with the beginning and end of the list, thus eliminating the special case code required to handle these boundary conditions.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# CIRCULAR LINKED LIST






Fig31: Circular Linked List

A circular doubly linked list has both the successor pointer and predecessor pointer in circular manner as shown in the following Fig.




notes.arpanadhikari7.com.np

Fig32: Circular Doubly Linked List



Available on notes.arpanadhikari7.com.np

# CIRCULAR LINKED LIST ALGORITHM

Inserting a node at the beginning (Insert_First(START,Item)

1. start
2. Create a Newnode
3. IF START is equal to NULL then
   a. Set Newnode->data = item
   b. Set NewNode->next = Newnode
   c. Set START = Newnode
   d. Set Last = Newnode
   e. Exit
4. Else
   1. Set Newnode ->data = Item
   2. Set Newnode->next = Start
   3. Set START = Newnode
   4. Set last->next = Start.
5. Stop

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Inserting a node at the End (Insert_End(START,Item)

1. Start.
2. Create a Newnode.
3. If START is equal to NULL, then
    a. Newnode->data = Item
    b. Newnode->next = Newnode
    c. START = Newnode
    d. LAST = Newnode
    e. Exit.
4. Else
    i. Newnode->data = Item
    ii. Last->next = Newnode
    iii. Last = Newnode
    iv. Last->next = START
5. Stop.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Deleting a node from beginning (Delete_First(START)

1. Start.
2. Declare a temporary node, ptr
3. If START is equal to NULL, then
    i. Display empty Circular queue
    ii. Exit
4. Else
    1. Ptr = START
    2. START = START->next
    3. Display, Element deleted is , ptr->data
    4. Last->next = START
    5. Free (ptr)
5. Stop.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Deleting a Node from End (Delete_End(START)

1. Start.
2. Declare a temporary node , ptr
3. If START is equal to NULL , then
   i. Print Circular list empty
   ii. Exit
4. ELSE
   i. Ptr = START
   ii. Repeat iii and iv while(ptr !=Last)
   iii. Ptr1 = ptr
   iv. Ptr = ptr->next
   v. Print element deleted is ptr->data
   vi. Ptr1->next = ptr->next
   vii. Last = ptr1
   viii. Free(ptr)
5. Stop.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Generalized Linked List

## Why Generalized Linked List?

- Generalized linked lists are used because although the efficiency of polynomial operations using linked list is good but still, the disadvantage is that the linked list is unable to use *multiple variable polynomial equation* efficiently.
- It helps us to represent multi-variable polynomial along with the list of elements.

```
typedef struct node {
    char c;                         //Data
    int index;                      //Flag
    struct node *next, *down;       //Next & Down pointer
}GLL;
```


notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Generalized Linked List

## Example of GLL {List representation} *( a, (b, c), d)*




- When first field is 0, it indicates that the second field is variable.
- If first field is 1 means the second field is a down pointer, means some list is starting.

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Generalized Linked List

## Polynomial Representation using Generalized Linked List

The typical node structure will be:




- Here Flag = 0 means *variable* is present
- Flag = 1 means *down pointer* is present
- Flag = 2 means *coefficient* and *exponent* is present


notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Generalized Linked List

***Example:*** $9x^5 + 7xy^4 + 10xz$




notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Generalized Linked List

❖For example, the abstract list represented by following figure may be represented as: list = (8,16,'g', 99,'b')





*Fig35 (a): Generalized Linked List*

notes.arpanadhikari7.com.np

❖The null list is denoted by an empty parenthesis pair such as ( ).



Available on notes.arpanadhikari7.com.np

# Generalized Linked List

❖Thus the list of the following figure is represented as:

list = (8,(5,7,(18,3,6),( ),5),2,(6,8))





*Fig35 (b): Generalized Linked List*

notes.arpanadhikari7.com.np




Available on notes.arpanadhikari7.com.np

# Polynomials using singly linked list (Application of Linked List)

- Different operations, such as addition, subtraction, division and multiplication of polynomials can be performed using linked list.
- Following example shows that the polynomial addition using linked list.
- In the linked representation of polynomials, each term is considered as a node.
- And such a node contains three fields: coefficient field, exponent field and Link field.

```
Struct polynode{
        int coeff;
        int expo;
        struct polynode *next;
};
```




notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np

# Polynomials using singly linked list (Application of Linked List)

- Consider two polynomials f(x) and g(x); it can be represented using linked list as follows.

$$f(x) = ax^3 + bx + c$$
$$g(x) = mx^4 + nx^3 + ox^2 + px + q$$





Fig33: Polynomial Representation in Linked List

These two polynomials can be added by h(x) = f(x) + g(x) = mx^4 + (a + n) x^3 + ox^2 + (b + p)x + (c + q) i.e.; adding the constants of the corresponding polynomials of the same exponentials. h(x) can be represented as

notes.arpanadhikari7.com.np





*Fig34: Addition of polynomials*



Available on notes.arpanadhikari7.com.np

# Thank you!!!!!

notes.arpanadhikari7.com.np



Available on notes.arpanadhikari7.com.np