Rajalakshmi Engineering College

Name: Adhithya varun

Email: 240801008@rajalakshmi.edu.in

Roll no: 240801008

Phone: null Branch: REC

Department: I ECE FA

Batch: 2028

Degree: B.E - ECE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 5

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

Input Format

The first line contains an integer n, representing the number of items to be initially entered into the inventory.

The second line contains n integers, each representing the unique identification number of an item separated by spaces.

The third line contains an integer p, representing the position of the item to be deleted from the inventory.

Output Format

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If p is an invalid position, the output prints "Invalid position. Try again."

If p is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

Sample Test Case

```
Input: 4
1 2 3 4
5
Output: Data entered in the list:
node 1: 1
node 2: 2
node 3: 3
node 4: 4
Invalid position. Try again.

Answer
```

void DIListcreation(int n) {

^^

240801000

240801008

```
240801008
                                                      240801008
       if (n >= 1)
     {
         stnode = (struct node *)malloc(sizeof(struct node));
         scanf("%d", &num);
         stnode->num = num;
                                                                                  240801008
         stnode->preptr = NULL;
         stnode->nextptr = NULL;
         ennode = stnode;
         for (i = 2; i \le n; i++)
     {
            fnNode = (struct node *)malloc(sizeof(struct node));
            scanf("%d", &num);
rnNode->preptr = ennode;
fnNode->nextptr = NULL;
ennode->nextptr = fnNi- '
ennode - f
                                                                                  240801008
            ennode->nextptr = fnNode;
     }
     }
     }
     void DIListDeleteFirstNode()
240861008
                           240801008
                                                                                  240801008
                                                      240801008
```

```
240801008
                                                     240801008
 struct node *toDel;
if (stnode == *'''
        if (stnode == NULL) return;
        toDel = stnode;
        stnode = stnode->nextptr;
        if (stnode != NULL)
          stnode->preptr = NULL;
        else
          ennode = NULL;
        free(toDel);
     }
                                                                                240801008
     void DIListDeleteLastNode() {
        struct node *toDel;
        if (ennode == NULL) return;
        toDel = ennode;
        ennode = ennode->preptr;
        if (ennode != NULL)
          ennode->nextptr = NULL;
        else
          stnode = NULL;
                                                                               240801008
                                                     240801008
        free(toDel);
     void DIListDeleteAnyNode(int pos)
     {
        struct node *curNode;
        int i;
        if (pos == 1)
240801008
                                                                                240801008
                                                     240801008
```

```
DIListDeleteFirstNode();
          return;
        curNode = stnode;
        for (i = 1; i < pos && curNode != NULL; i++)
     {
           curNode = curNode->nextptr;
        if (curNode == NULL) return;
        if (curNode->nextptr == NULL)
     {
          DlListDeleteLastNode();
     } else
          curNode->preptr->nextptr = curNode->nextptr;
curNode->nextptr->preptr = curNode->nrentri
free(curNode);
     }
     }
     void displayDlList(int a)
240861008
```

```
240801008
                                                                                240801008
struct node *tmp;
int n = 1;
      if (a == 1)
         printf("Data entered in the list:\n");
      if (a == 2)
         printf("\nAfter deletion the new list:\n");
      tmp = stnode;
      while (tmp != NULL)
    {
                                                                                 240801008
        printf(" node %d : %d\n", n, tmp->num);
         tmp = tmp->nextptr;
    }
    }
                                                                         Marks: 10/10
    Status: Correct
```

240801008

2,40801008

240801008

240801008

240801008

240801008

240801008

240801008