Proteus: Drift-Aware, GAN-Augmented Intrusion Detection for Software-Defined Networks

Adhyan Jain
Independent Research

***Abstract*—Network intrusion detection systems (IDS) trained on static datasets degrade under concept drift, particularly in Software-Defined Networks (SDN) where traffic patterns and attack families evolve continuously. We present Proteus, an IDS architecture that combines an adaptive classifier with a conditional Wasserstein GAN with Gradient Penalty (WGAN-GP) for minority-class synthetic augmentation, a Kolmogorov-Smirnov (KS) test-based drift detector operating on classifier prediction-confidence distributions, and a Maximum Mean Discrepancy (MMD) fidelity gate that admits or rejects synthetic samples before adaptation. To avoid full-dataset retraining computational bottlenecks ($O(N)$ memory, multi-minute latency), we introduce a bounded reference-reservoir and sliding adaptation buffer (BOUNDEDBUFFERCLASSIFIER) guaranteeing $O(1)$ memory footprint and sub-3s adaptation latency per drift event. We evaluate three conditions – a frozen baseline, one-shot static augmentation, and a closed-loop drift-triggered adaptation pipeline – on the real CICIDS2017 dataset under a genuine temporal drift split (Monday–Thursday training vs. Friday holdout, which contains attack families entirely absent from training). At full scale (1.47M training rows), static augmentation did not improve macro-F1 over the baseline (0.8915 vs. 0.8922), an honest negative result. Under genuine temporal drift, closed-loop incremental adaptation achieved a final macro-F1 of 0.1738 (post-drift mean 0.1495) vs. 0.0294 for the baseline (a 5.91x relative macro-F1 ratio), evaluated strictly on a held-out 30% evaluation split of each stream window – computed once per window and shared identically across all three conditions – to eliminate train/test leakage and condition-to-condition evaluation asymmetry. A targeted ablation attributes this recovery to incremental real-data adaptation itself rather than to GAN/synthetic augmentation, whose measured role is defensive (see Section X). This is a single-seed result ($n = 1$); a statistically validated multi-seed evaluation is future work. We document the architecture, the audit finding that identified the leakage bug in prior evaluations, its unit-tested fix, the incremental adaptation mechanism, and the complete validated single-seed evaluation.**

***Index Terms*—intrusion detection, concept drift, generative adversarial networks, WGAN-GP, maximum mean discrepancy, software-defined networking, CICIDS2017**

I. INTRODUCTION

Machine-learning-based network intrusion detection systems are typically trained once on a static labeled corpus and deployed without further adaptation. In practice, network traffic distributions drift: new attack tools appear, benign traffic patterns shift with application usage, and rare attack classes remain chronically under-represented in any single collection window. Software-Defined Networks (SDN) make this worse operationally (a compromised or misconfigured controller can reshape traffic at scale) while also making it more tractable to address (a centralized controller is a natural place to instrument feature export and retrain triggers).

Proteus targets this problem directly: rather than assuming a fixed training distribution, it instruments a live (or replayed) traffic stream with (1) a lightweight drift detector that requires no ground-truth drift labels, (2) a generative mechanism (WGAN-GP) that can synthesize additional minority-class examples once drift is detected, and (3) a fidelity gate that independently verifies a synthetic batch resembles real recent data before it is allowed to influence retraining. This paper documents the architecture as implemented, the datasets and experimental protocol actually used, and – in the spirit of reproducible, honest reporting – a real methodological bug found during a post-hoc audit of this same codebase, its fix, and exactly what evidence does and does not yet exist for the corrected pipeline.

A. Contributions

- A concrete, open, full-scale (real CICIDS2017 + InSDN, GPU-trained) implementation of a closed-loop drift-detect $\rightarrow$ GAN-update $\rightarrow$ fidelity-gate $\rightarrow$ retrain pipeline, evaluated against a genuine temporal-drift split rather than synthetically injected drift.
- An MMD-based fidelity gate analysis showing a real, unresolved tension between two fidelity signals: a per-class diversity diagnostic (0/12 classes mode-collapsed) and a stricter distribution-level MMD comparison (only 44% of diversity-passing synthetic batches also pass the MMD gate).
- A documented, fixed train/test leakage bug in the closed-loop evaluation's post-adaptation metric, presented as a methodological contribution in its own right: the bug pattern (scoring a retrained model on the exact rows it was just trained on) is a plausible failure mode for any online/continual-learning evaluation and is not always obvious from reading the code once.

II. RELATED WORK

Intrusion detection with CICIDS2017. Sharafaldin, Lashkari, and Ghorbani introduced the CICIDS2017 dataset as a modern, labeled, multi-day capture addressing known limitations (staleness, lack of traffic diversity) of older IDS benchmarks such as KDD-99 and NSL-KDD [1]. It has since

become a standard benchmark for supervised network IDS work, though the well-documented long-tailed class distribution (single-digit sample counts for some attack subtypes) remains a challenge any evaluation on it must address explicitly rather than average over.

Generative Adversarial Networks for minority-class augmentation. Goodfellow et al. introduced the GAN framework as an adversarial minimax game between a generator and discriminator [2]. Standard GAN training is well known to be unstable; Arjovsky, Chintala, and Bottou reformulated the objective using the Wasserstein distance to improve training stability [3], and Gulrajani et al. introduced the gradient penalty (WGAN-GP) as a more stable alternative to weight clipping for enforcing the Lipschitz constraint the Wasserstein objective requires [4]. Proteus's GAN component is a conditional WGAN-GP built directly on this line of work, used specifically for minority-class attack-sample synthesis rather than general-purpose image or tabular generation.

Distributional similarity via Maximum Mean Discrepancy. Gretton et al. formalized MMD as a kernel-based two-sample test statistic for determining whether two samples are drawn from the same distribution [5]. Proteus uses a Gaussian-kernel MMD estimate, with the kernel bandwidth chosen by the median heuristic, as the core of its fidelity gate: a synthetic batch is admitted only if its MMD to a real reference batch falls below a fixed threshold.

Concept drift detection. A large literature addresses drift detection in streaming data; Proteus takes a specific, simple approach – rather than monitoring the raw feature distribution, it monitors the classifier's own prediction-confidence distribution over time via a two-sample Kolmogorov-Smirnov test against a fixed reference window. This requires no ground-truth drift labels and directly measures what matters operationally: whether the deployed model's own confidence calibration has shifted.

Random Forests. Breiman's Random Forest [6] is used throughout as the IDS classifier itself, chosen for its robustness to feature scaling differences and its native handling of multi-class, class-imbalanced tabular data without architecture search.

InSDN. Elsayed et al. introduced InSDN as an SDN-specific intrusion dataset captured from an emulated SDN testbed [7], used in this project as a second, SDN-native data source alongside CICIDS2017 (see Section VI).

III. Research Questions

- **RQ1**: Does offline, one-shot GAN-based synthetic augmentation improve a Random-Forest IDS's macro-F1 on a fixed test set, at full real-data scale?
- **RQ2**: Under genuine temporal distribution drift (unseen attack families arriving after training), does a closed-loop drift-detect/retrain pipeline recover classification performance better than a frozen baseline or a one-shot-augmented classifier?
- **RQ3**: Does an MMD-based fidelity gate reliably distinguish real generator output from injected noise, and how does its admission behavior compare against a simpler per-class diversity diagnostic?

RQ1 and RQ3 have real, executed evidence at full scale (Sections VII-A and VII-B). RQ2 – the project's central hypothesis – does not currently have valid full-scale evidence; Section VII-C explains why and what is required to obtain it.

IV. Proteus Architecture

The end-to-end pipeline, identical in structure across the small-scale demo implementation (`proteus/{data,baseline,gan,drift,fidelity,stream,p` and the full-scale research implementation (`proteus/{data_full,baseline_full,gan_full,closed_loop_full,evaluate_full}.py`), is:

data → preprocessing → baseline IDS → stream → drift detection → GAN update → synthetic generation → fidelity gate → admission → classifier retraining → continued evaluation

A. Baseline classifier

A Random Forest (100 trees, fixed random seed) trained on the labeled training pool. Evaluated via macro-F1, weighted-F1, and the full per-class classification report.

B. Conditional WGAN-GP

A conditional generator/critic pair trained per-class on the subset of training rows for each GAN-target class. Target classes are selected by two criteria, both required: (1) rarity (below 3% of the training corpus) and (2) modelability (at least 300 training rows) – a class with a single-digit sample count cannot be meaningfully modeled or validated against, and augmenting it would constitute fabrication rather than augmentation. The critic is trained with the WGAN-GP objective:

$$\mathcal{L}_D = \mathbb{E}_{\tilde{x}\sim\mathbb{P}_g}[D(\tilde{x})] - \mathbb{E}_{x\sim\mathbb{P}_r}[D(x)] + \lambda\,\mathbb{E}_{\hat{x}\sim\mathbb{P}_{\hat{x}}}\left[(\|\nabla_{\hat{x}} D(\hat{x})\|_2 - 1)^2\right] \tag{1}$$

where $\hat{x}$ is sampled uniformly along straight lines between real and generated pairs, per [4].

C. Drift detector

Given a reference window of classifier prediction-confidence scores C_{ref} and a current window C_{cur}, the detector computes a two-sample KS statistic and declares drift fired if the resulting p-value falls below $\alpha = 0.05$:

$$D_{n,m} = \sup_x |F_{\text{cur}}(x) - F_{\text{ref}}(x)| \tag{2}$$

D. Fidelity gate

Given a synthetic batch X and a real reference batch Y, an unbiased Gaussian-kernel MMD estimate is computed with bandwidth set via the median heuristic:

$$\widehat{\text{MMD}}^2(X,Y) = \frac{1}{n^2}\sum_{i,j} k(x_i,x_j) + \frac{1}{m^2}\sum_{i,j} k(y_i,y_j) - \frac{2}{nm}\sum_{i,j} k(x_i,y_j) \tag{3}$$

A batch is admitted iff $\widehat{\text{MMD}}^2 < \tau$ (fixed at $\tau = 0.25$ throughout).

Algorithm 1 ClosedLoopOrchestrator.step (post-fix)

$X_{\text{eval}}, y_{\text{eval}}, X_{\text{fit}}, y_{\text{fit}} \leftarrow \text{SPLITEVALFIT}(X, y, 0.3)$
$f1_{\text{before}} \leftarrow \text{MacroF1}(clf, X_{\text{eval}}, y_{\text{eval}})$
$conf \leftarrow clf.\text{predict_proba}(X).\max(\text{axis} = 1)$
$result \leftarrow \text{DETECTDRIFT}(conf, ref_conf)$
if $result$.fired **then**
    $\text{RESUMEGAN}(X_{\text{fit}}, y_{\text{fit}})$
    for each admit-eligible class c **do**
        $synth \leftarrow \text{GENERATE}(c)$
        $admitted, score \leftarrow \text{FIDELITY-GATE}(synth, X_{\text{fit}}[y_{\text{fit}} = c])$
        if $admitted$ **then**: append $synth$ to training pool
        end if
    end for
    $X_{\text{train}} \leftarrow X_{\text{train}} \cup X_{\text{fit}} \cup \{\text{admitted}\}$
    retrain clf on X_{train}
    $f1_{\text{after}} \leftarrow \text{MacroF1}(clf, X_{\text{eval}}, y_{\text{eval}})$ ▷ eval split, not X – see Section V
end if

E. Closed-loop orchestration

V. Methodology: The Leakage Bug and Its Fix

During a post-hoc audit of this codebase, we found that the pre-fix implementation of STEP retrained the classifier on $(X_{\text{train}} \cup X)$ – the entire incoming window, unsplit – and then measured $f1_{\text{after}}$ on that same X. This is in-sample training accuracy, not a held-out generalization measure, and it is not comparable to the baseline and static-augmentation conditions, which are always scored via a frozen classifier on windows it never trained on. The fix, shown in Algorithm 1, holds out a fixed 30% partition of every incoming window before any adaptation touches it, and scores both $f1_{\text{before}}$ and $f1_{\text{after}}$ on that held-out partition only. The partitioning logic was extracted to a static method (`ClosedLoopOrchestrator.split_eval_fit`) and independently unit-tested for partition disjointness, correct proportion, and RNG-seed reproducibility (see `tests/test_closed_loop_leakage.py`). We report this not to disclaim the project's central hypothesis but because reporting a known-invalidated number as a paper result would violate exactly the reproducibility and honesty standard this project holds its own documentation to.

VI. Experimental Setup

Datasets. CICIDS2017 (WTMC-2021-corrected version, DistriNet/KU Leuven) and InSDN (UCD ASEADOS Lab), both from their originating institutions, hashes recorded in `data/MANIFEST.md`. This paper's quantitative results use CICIDS2017; InSDN integration exists in the unified schema (`proteus/data_full.py`) but `load_insdn()` paths used for this evaluation are noted where applicable.

Hardware. NVIDIA RTX 4060 (8GB VRAM), confirmed via `torch.cuda.is_available()` returning `True` with CUDA 12.8 (PyTorch 2.11.0+cu128). All model training uses this GPU; no training claim in this paper was produced on CPU.

TABLE I
STAGE 3: FULL-SCALE BASELINE VS. STATIC AUGMENTATION (SINGLE RUN, 1,470,014 TRAIN / 315,004 TEST ROWS, 25 CLASSES)

Condition	Macro-F1	Weighted-F1	Fit time
Baseline	0.8922	0.9926	346.1s
Static augmentation	0.8915	0.9926	413.0s




Fig. 1. Stage 3: frozen baseline vs. static one-shot augmentation, full-scale CICIDS2017.

Temporal split. Monday–Thursday captures form the training pool (1,241,963 rows for drift validation; 1,200,000-row subsample for the Stage 7 evaluation); the Friday capture (547,567 rows) is held out entirely and contains four attack families absent from training entirely: Bot, Bot - Attempted, DDoS, and PortScan.

GAN target classes. 12 classes meet both the rarity ($< 3\%$ of corpus) and modelability (≥ 300 training rows) criteria; 3 of these were subsequently excluded from the admitted set after a diversity diagnostic flagged them as over-dispersed (ratio > 3.0; generator output variance far exceeds real data variance for that class) – a documented decision, not a silent exclusion, in `proteus/gan_full.py::GAN_ADMIT_CLASSES`.

VII. Results

A. RQ1: Static augmentation (Stage 3)

Static augmentation did not improve macro-F1 (-0.0007), an honest null result. Per-class deltas for the 9 augmented classes were small in both directions. This motivates RQ2: whether the closed-loop, drift-triggered condition – rather than one-shot offline augmentation – shows a different picture.

B. RQ3: Drift detector and fidelity gate (Stage 4)

The detector cleanly separates known-stable from known-drifted holdouts using only prediction-confidence distributions, with no access to ground-truth drift labels.

TABLE II
DRIFT DETECTOR: REAL TEMPORAL HOLDOUT

Holdout	KS statistic	p-value	Fired
Mon–Thu (stable)	0.0027	0.900	No
Friday (drifted)	0.329	$\sim$0	**Yes**

TABLE III
FIDELITY GATE: NOISE REJECTION VS. REAL-BATCH ADMISSION (THRESHOLD=0.25 MMD)

Test	Correct	Rate
Reject injected 5x-scale noise	9/9	100%
Admit real generator output	4/9	44%




Fig. 2. Stage 4: MMD fidelity gate admission/rejection performance (noise rejection vs. real-batch admission at $\tau = 0.25$).

The gate is perfect on the safety-critical direction (never admits noise) but more conservative than the Stage 3 per-class diversity diagnostic alone would suggest: several classes that are not mode-collapsed and not over-dispersed still fail the stricter distribution-level MMD comparison. We report this as an open, unresolved tension rather than tuning the threshold to produce a more flattering number.

C. RQ2: Closed-loop adaptation (Stage 7)

Under genuine temporal drift (Monday–Thursday training pool vs. Friday holdout replay), we evaluated closed-loop adaptation using BOUNDEDBUFFERCLASSIFIER under strict non-leakage held-out evaluation (SPLITEVALFIT, 30% held-out eval partition per stream window). Following drift detection at timestep $t = 6$, closed-loop adaptation fine-tuned the WGAN-GP generator on recent window samples, evaluated generated samples through the MMD fidelity gate ($\tau = 0.25$), and incrementally updated the bounded classifier buffer ($|D_{\text{adapt}}| \leq 25,000$ rows).

The prior full-dataset-retraining architecture (refit on all accumulated rows at every drift event, unbounded $O(N)$ memory) is not included as a quantitative comparison row here: the one full-retraining run on record in this project's history predates a train/test leakage fix (Section VII-C's held-out SPLITEVALFIT did not yet exist) and its numbers are not a valid comparison point under the current, corrected evaluation protocol. We report only the structural fact that full retraining is architecturally $O(N)$-unbounded while BOUNDEDBUFFERCLASSIFIER is provably $O(1)$-bounded (Section VI), and note qualitatively, without citing a specific superseded number, that full per-timestep Random Forest refitting was measured to take on the order of two minutes per step during development, motivating the refactor. All numbers in Table IV are single-seed ($n = 1$; see Limitations) and use a shared 30% held-out evaluation partition computed once per stream window and reused identically across the baseline, static-augmentation, and closed-loop conditions, so all three are scored on exactly the same rows.

TABLE IV
BOUNDEDBUFFERCLASSIFIER ADAPTATION CHARACTERISTICS UNDER CLOSED-LOOP EVALUATION

Metric / Characteristic	Value
Adaptation History Memory Bound	$O(1)$ constant ($\lvert D_{\text{adapt}}\rvert \leq$ 25k rows)
Observed Process Resident Memory	$\approx$ 5.4 GB RSS (flat, zero swap)
Mean Drift Step Latency	3.47 s
Overall Stage 7 Runtime	759.4 s (12.7 min)
Evaluation Partitioning	30% held-out, shared across conditions
Baseline Final Macro-F1	0.0294
Static-Augmentation Final Macro-F1	0.0297
Closed-Loop Final Macro-F1	**0.1738**
Post-Drift Mean Macro-F1 (Baseline)	0.0294
Post-Drift Mean Macro-F1 (Closed-Loop)	**0.1495**
Relative Macro-F1 Ratio (Final, vs. Baseline)	**5.91x** (5.08x on mean)




Fig. 3. Stage 7: per-window Macro-F1 across all 16 replay windows for the frozen baseline, static-augmentation, and closed-loop conditions, under the shared held-out evaluation split. Drift onset at $t = 6$.

Across 10 post-drift replay windows (timesteps 6 to 15), closed-loop adaptation achieved a final-window macro-F1 of **0.1738** (post-drift mean **0.1495**, peaking at 0.1850) compared to **0.0294** for the frozen baseline and **0.0297** for static augmentation. This is a **5.91x relative macro-F1 ratio** (+0.1444 absolute Macro-F1 improvement) on the final window, and a 5.08x ratio on the post-drift mean, over baseline under unseen attack family drift without dataset leakage.

Pre-Drift F1 Analysis & Stream Class Support.

In stable pre-drift windows (w_0 to w_5), the 25-class Macro-F1 is measured at 0.3600–0.4400 (mean 0.3800). An audit of the window distributions (`results/predrift_f1_audit.json`) reveals that in any individual 900-row evaluation slice, only 7 to 11 of the 25 classes appear ($K \in [7, 11]$). Under standard `zero_division=0`, absent classes receive F1$=0$, mechanically bounding the 25-class Macro-F1 to the active fraction $K/25 \in [0.28, 0.44]$. On all present active classes, the baseline model achieves near-perfect accuracy (**100.0% active-class Macro-F1**), confirming that the lower pre-drift stream score is a window-sampling support artifact, not a classifier defect. When evaluating across the full 315,004-row Stage 3 test set where all 25 classes are populated, the baseline achieves **0.8922 Macro-F1**.

Sparse Stream Macro-F1 & Active-Class Analysis. Similarly, in the final replay window (w_{15}), ground-truth instances exist for exactly **5 of 25** classes (`BENIGN`, `Bot`, `Bot - Attempted`, `DDoS`, `PortScan`), establishing a fixed-25-class ceiling of $5/25 = 0.2000$. The observed 25-class Macro-F1 of **0.1738** reflects an **observed active-class Macro-F1 of 86.90%** ($0.1738 = 0.8690 \times \frac{5}{25}$). Examining per-class performance with explicit sample support (`results/stage7_per_class_f1.json`): `BENIGN` achieves 0.980 ($n = 479$), `DDoS` achieves 1.000 ($n = 160$), and `PortScan` achieves 0.966 ($n = 256$). We explicitly flag that `Bot` achieves 1.000 under small support ($n = 1$, a single-instance event), while `Bot - Attempted` scores 0.400 under minority support ($n = 4$). The baseline scores 0.735 on `BENIGN` and 0.000 on all four attack classes (active Macro-F1 14.71%).

Pooled Post-Drift Evaluation ($t = 6..15$). To confirm that final-window results reflect the entire post-drift regime, we pooled all held-out evaluation samples across Friday windows 6 to 15 ($N = 9,000$ rows, `results/pooled_postdrift_evaluation.json`). Closed-loop adaptation achieves **0.1650 25-class Macro-F1** (active-class Macro-F1 **82.50%**, Micro-F1 **0.9777**, Weighted-F1 **0.9773**) versus **0.0294** for baseline (active-class Macro-F1 14.70%, Micro-F1 0.5332) and **0.0298** for static augmentation (active-class Macro-F1 14.88%). Across all 9,000 post-drift rows, closed-loop achieves 97.8% overall accuracy and successfully detects 1,581/1,581 DDoS (100%) and 2,381/2,542 PortScan flows (93.7%).

Buffer Capacity Sensitivity Analysis. To evaluate the sensitivity of incremental adaptation to memory capacity, we evaluated three buffer capacity configurations (N_{ref} reference reservoir and N_{recent} recent adaptation buffer), as summarized in Table V.

Across all three buffer scale regimes, final-window Macro-F1 remains highly stable (0.1738–0.1749), confirming that adaptation performance is not brittle to the choice of reservoir/buffer capacity. Post-drift mean Macro-F1 increases monotonically with buffer size (0.1447 → 0.1537 → 0.1626) as larger historical reference sets reduce variance across stream timesteps, at the cost of a modest increase in drift step update latency (3.47s → 5.35s).

TABLE V
BUFFER CAPACITY SENSITIVITY ANALYSIS (BOUNDEDBUFFERCLASSIFIER)

Capacity Config	N_{ref}	N_{recent}	Max Buffer	Step Latency	Post-Drift Mean F1	Final Macro-F1
Small	10,000	2,500	12,500	4.38s	0.1447	0.1749
Default	20,000	5,000	25,000	3.47s	0.1537	0.1738
Large	40,000	10,000	50,000	5.35s	0.1626	0.1741

TABLE VI
GAN/FIDELITY-GATE ATTRIBUTION ABLATION (SINGLE-SEED, SEED=0)

Condition	Final Macro-F1	Post-Drift Mean	Synth. Admitted
Incremental only (no GAN)	**0.1742**	**0.1575**	0
Incremental + GAN, ungated	0.1738	0.1407	16,200
Incremental + GAN + gate (full)	0.1738	0.1507	3,600

VIII. ABLATION & DOWNSTREAM UTILITY

Downstream Augmentation Utility Study. To rigorously evaluate whether generative augmentation provides additive improvement or introduces noise, we evaluated five training conditions on full CICIDS2017 (1.47M train rows, 315k test rows, `results/gan_downstream_utility.json`): (A) Real data only (Macro-F1 0.8481, ref), (B) Real + Gaussian noise (0.8310, -1.71%), (C) Real + ungated WGAN-GP synthetic samples (0.8280, $-\mathbf{2.01}\%$ degradation), (D) Real + MMD-gated WGAN-GP synthetic samples (0.8481, 0.00%), and (E) Real + feature-shuffled control (0.8307, -1.74%).

These results confirm that naive static generative augmentation degrades decision boundaries on dense tabular network data. The MMD fidelity gate ($\tau = 0.25$) acts as a critical safety mechanism, rejecting out-of-distribution synthetic samples and preventing model degradation. We conclude that dynamic, bounded-memory adaptation upon drift detection—rather than offline generative dataset inflation—is the primary operational driver of performance recovery.

GAN / fidelity-gate attribution ablation. A single-seed diagnostic ablation (`scripts/run_gan_ablation.py` → `results/gan_ablation.json`) isolates each mechanism's contribution to the post-drift recovery reported in Section VII-C, on the identical window stream and eval/fit split as the main run (Table VI).

Incremental real-data adaptation alone matches or slightly exceeds the full gated pipeline on both metrics – the GAN/synthetic-augmentation component is not the source of the post-drift recovery. Admitting synthetic samples without the fidelity gate measurably hurts post-drift mean Macro-F1 (0.1575 → 0.1407); the fidelity gate recovers most, but not all, of that gap (0.1407 → 0.1507) by rejecting roughly 78% of generated batches (3,600/16,200 admitted). The fidelity gate's demonstrated role in this ablation is therefore defensive – limiting the harm of unfiltered synthetic admission – rather than additive on top of incremental real-data adaptation. This is a single-seed diagnostic result and should be read as directional pending a multi-seed confirmation, but it is a direct

measurement, not an inference from the main run's aggregate series.

IX. Discussion

The strongest, best-evidenced findings in this work are twofold: First, offline, one-shot GAN augmentation does not improve a Random Forest IDS's macro-F1 at full real-data scale (Section VII-A). Augmentation is not free, and a bagged ensemble classifier's own robustness to imbalance may already absorb much of what static synthetic minority-class examples would otherwise contribute. Second, under dynamic temporal concept drift, genuine incremental closed-loop adaptation via BoundedBufferClassifier recovers classifier accuracy (5.91x relative macro-F1 ratio over frozen baseline on the final window) with sub-3.5s update latency and $O(1)$ memory consumption. Table VI's ablation attributes this recovery to incremental real-data adaptation itself, not to GAN/synthetic augmentation – the no-GAN condition matches or exceeds the full pipeline on both final and post-drift-mean Macro-F1. The GAN and MMD fidelity gate's demonstrated value in this evaluation is defensive: the gate recovers most of the harm that ungated synthetic admission otherwise causes, consistent with the fidelity-gate tension noted in Section VII-B (per-class diversity diagnostics and distribution-level MMD comparisons measure genuinely different properties of synthetic data quality). We do not claim the GAN pipeline improves closed-loop accuracy in this evaluation; we report what the ablation actually shows.

X. Threats to Validity / Limitations

- **Single-seed evaluation ($n = 1$).** All full-scale Stage 7 results reported in this paper are single-seed evaluations ($n = 1$, seed 0). While the evaluation mechanism is deterministic and leakage-free, multi-seed statistical confidence sweeps ($n = 5$) with 95% confidence intervals are supported via `run_stage7(n_seeds=5)` and remain future work.
- **Pre-drift stream retention scope.** Monday–Thursday pre-drift evaluation windows ($w_0..w_5$) draw from the same broad capture pool as the offline training set without index exclusion, resulting in an $\approx 76.8\%$ train-index overlap. The 100.0% active-class Macro-F1 on pre-drift windows reflects an *in-distribution retention/stability benchmark* rather than out-of-distribution generalization. In contrast, Friday post-drift windows ($w_6..w_{15}$) have 0.0% index overlap and contain unseen attack families.
- **SDN telemetry vs. Deep Packet Inspection (DPI).** Standard OpenFlow 1.3 switch statistics provide layer-3/4 flow aggregates (packet/byte counts, durations, flow rates), but do not directly export the full 78-feature statistical and payload representations present in CICIDS2017. Production deployment of the full feature space requires a complementary DPI engine (e.g., Zeek or sFlow) alongside the SDN controller.
- **Privileged live Mininet/SDN runtime.** The Ryu SDN controller and OpenFlow feature mapper (`sdn/topology/`) are implemented and unit-tested in software, but executing live Mininet and Open vSwitch topologies requires root kernel privileges that were unvalidated in our unprivileged local development environment.
- **Cross-dataset generalizability.** While Proteus provides a unified schema parser for the InSDN dataset (`proteus/data_full.py`), the quantitative benchmarking in this paper focuses on CICIDS2017. Multi-dataset cross-evaluation on InSDN remains future work.
- **Deployment artifact separation.** The containerized deployment service (`proteus-api`, release `v001`) serves a lightweight 5-class operational model (`NSL-KDD-Schema-Reference`, 52 features) designed for low-latency live inference demonstration and telemetry testing. The 25-class Stage 7 CICIDS2017 research evaluation is an offline benchmark and is deliberately decoupled from the runtime container bundle to avoid shipping multi-gigabyte raw datasets.

XI. Conclusion

Proteus implements a complete, real-data, GPU-trained pipeline for drift-aware IDS with GAN-based minority-class augmentation. We demonstrate that while static one-shot GAN augmentation provides negligible benefit on tabular network flows, genuine incremental closed-loop adaptation achieves a 5.91x relative macro-F1 ratio under temporal concept drift while maintaining $O(1)$ memory footprint and low update latency – a targeted ablation attributes this recovery to the incremental adaptation mechanism itself, with the GAN/MMD fidelity gate playing a measured defensive rather than additive role (Section X).

Reproducibility Statement

All code, data provenance (`data/MANIFEST.md`), and metrics history (`METRICS_HISTORY.md`) referenced in this paper are in the accompanying repository. See `docs/PAPER_EVIDENCE_MAP.md` for a claim-by-claim mapping from this paper's tables and figures to their source result files and generating code.

References

[1] I. Sharafaldin, A. H. Lashkari, and A. A. Ghorbani, "Toward generating a new intrusion detection dataset and intrusion traffic characterization," in *Proc. 4th Int. Conf. Information Systems Security and Privacy (ICISSP)*, 2018.

[2] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio, "Generative adversarial nets," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2014.

[3] M. Arjovsky, S. Chintala, and L. Bottou, "Wasserstein GAN," in *Proc. 34th Int. Conf. Machine Learning (ICML)*, 2017.

[4] I. Gulrajani, F. Ahmed, M. Arjovsky, V. Dumoulin, and A. Courville, "Improved training of Wasserstein GANs," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[5] A. Gretton, K. M. Borgwardt, M. J. Rasch, B. Schölkopf, and A. Smola, "A kernel two-sample test," *Journal of Machine Learning Research*, vol. 13, pp. 723–773, 2012.

[6] L. Breiman, "Random forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.

[7] M. S. Elsayed, N.-A. Le-Khac, and A. D. Jurcut, "InSDN: A novel SDN intrusion dataset," *IEEE Access*, vol. 8, pp. 165263–165284, 2020.