

**Programming Challenges**

Roman Valiusenko

roman.valiusenko@gmail.com

**Abstract**

This is a collection of literate programs. If you are unfamiliar with the idea of literate programming please refer [1]. These programs are my solutions to the programming tasks from the "Programming Challenges" book[2] which in turn is a collection of problems from the UVa Online Judge hosted by University of Valladolid<sup>1</sup>.

**Contents**

<b>1</b>	<b>Chapter 1</b>	<b>1</b>
1.1	The $3n + 1$ Problem . . . . .	1
1.2	Minesweeper . . . . .	4
1.3	The Trip . . . . .	6
1.4	LC Display . . . . .	7
1.5	Graphical Editor . . . . .	11
1.6	Interpreter . . . . .	14
1.7	Check The Check . . . . .	16
1.8	Australian Voting . . . . .	20
<b>2</b>	<b>Chapter 2</b>	<b>22</b>
2.1	Jolly Jumper . . . . .	22
2.2	Crypt Kicker . . . . .	23
<b>3</b>	<b>Chapter 3</b>	<b>29</b>
3.1	Crypt Kicker II . . . . .	29
3.2	File Fragmentation . . . . .	31
<b>4</b>	<b>Chapter 4</b>	<b>33</b>
4.1	Bridge . . . . .	33
4.2	ShellSort . . . . .	34
<b>5</b>	<b>Chapter 5</b>	<b>36</b>
5.1	Primary Arithmetic . . . . .	36
5.2	Reverse And Add . . . . .	38
5.3	The Archeologists' Dilemma . . . . .	39
5.4	Ones . . . . .	41
5.5	A Multiplication Game . . . . .	43
<b>6</b>	<b>Chapter 7</b>	<b>45</b>
6.1	Light, More Light . . . . .	45
<b>7</b>	<b>License</b>	<b>48</b>

---

<sup>1</sup>If you are going to submit any of these programs to the UVa Online Judge make sure the class name is Main and that it's not in any package; For the class names I use problem names, and I put everything into my package com.rvprg.pc)

# 1 Chapter 1

## 1.1 The $3n + 1$ Problem

This task is not difficult if you notice that all the lengths of the sequences can easily be calculated up front. Then all that is needed is to lookup the pre-calculated table to find out the maximum lengths for the given input numbers.

(I noticed though that I could have simply calculated the values on the file without any tricks. The reason why I have done a more sophisticated algorithm is that at first I thought the input number may go up to 1M, but in reality, according to the problem statement, they won't exceed 10000. So I solved a more tricky problem.)

So let's start with the definitions of the array that will hold all the **lengths** and the **reader** that will be used to read the input data.

```
1a  <3n+1 1a>≡
    package com.rvprg.pc;

    <1.1 Imports 1b>

    class Collatz {
        private static int MAX = 1000000;
        private int[] lengths = new int[MAX];
        private static final BufferedReader reader =
            new BufferedReader(new InputStreamReader(System.in));
        <1.1 Helpers 2b>
        <1.1 Constructor 3a>
        <1.1 Input/Output 3c>
    }
```

We need the necessary imports:

```
1b  <1.1 Imports 1b>≡
    import java.io.BufferedReader;
    import java.io.InputStreamReader;
```

The idea is to hold the lengths of the sequences in the **lengths**, but because the sequence member can sometimes go over 1M we will need to store them somewhere temporarily. For that a **surplus** hash map will be used. Its contents will be thrown away once the sequence lengths were computed.

So we write two helper methods: **set** and **get**. Both take an **index** and **surplus** hash map and depending on the index value either use the array or the hash map to set or get a value.

```
2a  <1.1 Imports 1b>+≡
    import java.util.HashMap;
```

```

2b  <1.1 Helpers 2b>≡
    int get(long index, HashMap<Long, Integer> surplus) {
        return (index < MAX) ? lengths[(int) index] :
            (surplus.containsKey(index) ? surplus.get(index) : 0);
    }

    void set(long index, int value, HashMap<Long, Integer> surplus) {
        if (index < MAX) {
            lengths[(int) index] = value;
        } else {
            surplus.put(index, value);
        }
    }
}

```

Now we can easily pre-calculate all the lengths using the helper methods `set` and `get`, but we must not re-calculate the lengths for the indexes that we have calculated already.

We calculate a member of the sequence at each step using the definition. Each time we calculate a new member of the sequence we push it onto the `stack`. We stop if we notice that we already have the length calculated for that specific value or when we reach 1. Now all the values that are on the stack are potential inputs, that is they are all potential initial ns. We use this knowledge to update elements in the `lengths`:

```

2c  <1.1 Imports 1b>+≡
    import java.util.ArrayDeque;
    import java.util.Deque;

3a  <1.1 Constructor 3a>≡
    Collatz() {
        final HashMap<Long, Integer> surplus = new HashMap<Long, Integer>();
        lengths[1] = 1;
        for (long i = 2; i < MAX; ++i) {
            final Deque<Long> stack = new ArrayDeque<Long>();
            long n = i;
            int len = 2;
            while (n != 1) {
                stack.push(n);
                int prev = get(n, surplus);
                if (prev > 0) {
                    len = prev;
                    break;
                }
                n = n % 2 == 0 ? n / 2 : n * 3 + 1;
            }
            while (!stack.isEmpty()) {
                set(stack.pop(), len++, surplus);
            }
        }
    }
}

```

Processing the input is easy but cumbersome<sup>2</sup>:

```
3b  <1.1 Imports 1b>+≡
    import java.util.stream.IntStream;

3c  <1.1 Input/Output 3c>≡
    public static void main(String[] args) {
        Collatz s = new Collatz();
        String input;
        while ((input = reader.readLine()) != null &&
            !input.trim().equalsIgnoreCase("")) {
            List<String> str = Arrays.stream(input.trim().split(" "))
                .filter(x -> !x.equals(""))
                .collect(Collectors.toList());
            int x[] = new int[] { Integer.parseInt(str.get(0)),
                Integer.parseInt(str.get(1)) };
            System.out.println(x[0] + " " + x[1] + " " +
                IntStream.rangeClosed(Math.min(x[0], x[1]), Math.max(x[0],
                    x[1])).map(v -> s.lengths[v]).max().getAsInt());
        }
    }
```

## 1.2 Minesweeper

This task is trivial: We simply count the number of mines around each cell. There are eight cells around each cell that we need to inspect. If our cell is  $(x, y)$ , then we check  $(x-1, y-1)$ ,  $(x, y-1)$  and so on, and count the number of cells that have '\*' in them.

Our program structure is simple as usual:

```
4a  <Minesweeper 4a>≡
    package com.rvprg.pc;

    <1.2 Imports 4b>

    class Minesweeper {
        <1.2 Constants 4c>
        <1.2 Main 5>
    }
```

Of course, we need a reader, so we define it next. Then we need to define the constants. We are going to split the lines by spaces, so let's have it as a constant. We also define an array of the offsets **p** to determine the cells around a given cell.

```
4b  <1.2 Imports 4b>≡
    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
```

---

<sup>2</sup>It turns out that the UVa Judge tends to give some extra spaces here and there in the input, so we need to make sure we account for some sporadic spaces in the input. This was my first submission and it took me seven attempts before I got past that super annoying "Runtime Error", because the judge was giving some extra spaces between the values which my program was not taking into account.

```
4c  <1.2 Constants 4c>≡
    private static final BufferedReader reader =
        new BufferedReader(new InputStreamReader(System.in));
    private static final String SPACE = " ";
    private static final int[][] p = new int[][] {
        { -1, -1 }, { 0, -1 }, { 1, -1 }, { -1, 0 },
        { 1, 0 }, { -1, 1 }, { 0, 1 }, { 1, 1 }
    };
```

Now let's write the main method. I'll deliberately use one-dimensional array instead of the two-dimensional, and I will use a couple of helper lambdas. One, `count`, to count the mines around a cell, and another, `mine`, which returns a cell value for the given coordinates.

```
4d  <1.2 Imports 4b>+≡
    import static java.util.Arrays.stream;
    import static java.util.stream.Collectors.joining;
    import static java.util.stream.Collectors.toList;
    import static java.util.stream.IntStream.range;
    import java.util.List;
    import java.util.function.IntBinaryOperator;
    import java.util.function.IntUnaryOperator;
```

```

5  <1.2 Main 5>≡
    public static void main(String[] args) throws IOException {
        int lineNum = 0;
        String currentLine = INPUT_END;
        while ((currentLine = reader.readLine()) != null) {
            if (currentLine.equalsIgnoreCase("")) {
                continue;
            }
            List<Integer> nm = stream(currentLine.split(SPACE))
                .filter(x -> !x.equals(""))
                .map(Integer::parseInt)
                .collect(toList());
            int n = nm.get(0);
            int m = nm.get(1);
            if (n == 0 && m == 0) {
                break;
            }

            final int[] field = reader.lines().limit(n)
                .collect(joining()).chars().map(x -> x == '*' ? -1 : 0).toArray();

            final IntBinaryOperator mine =
                (x, y) -> (x < 0 || x > (n - 1) || y < 0 || y > (m - 1)) ? 0 : field[x * m + y];

            final IntUnaryOperator count = (i) -> range(0, p.length)
                .map(j -> Math.abs(mine.applyAsInt(i / m + p[j][0], i % m + p[j][1]))).sum();

            int[] result = range(0, field.length)
                .map(x -> field[x] >= 0 ? count.applyAsInt(x) : field[x]).toArray();

            if (lineNum > 0) {
                System.out.println();
            }

            System.out.println("Field #" + (++lineNum) + ":");
            for (int i = 0; i < n; ++i) {
                for (int j = 0; j < m; ++j) {
                    System.out.print(result[i * m + j] == -1 ? "*" : result[i * m + j]);
                }
                System.out.println();
            }
        }
    }
}

```

### 1.3 The Trip

This task is much more fun than the previous two. The important thing that we should note for ourselves is that we are not going to use the floating point types to do the calculations.

```
6a  <The Trip 6a>≡
    package com.rvprg.pc;

    <1.3 Imports 6b>

    class TheTrip {
        <1.3 Calculation 6c>
        <1.3 Input/Output 7c>
    }
```

First thing we need to do is to calculate the average spend, don't we? Because we know that the input is a list of how much each of `n` students spent, let's define a function that takes this list of values and returns the minimum amount of money asked in the problem. Of course, the types will be `long`. And we can immediately cover the degenerate case of a input consisting of one element:

```
6b  <1.3 Imports 6b>≡
    import static java.util.Arrays.stream;

6c  <1.3 Calculation 6c>≡
    static long calculate(long[] values) {
        if (values.length == 1)
            return 0;
        long total = stream(values).sum();
        <1.3 Finding the minimum 6e>
    }
```

Now we need to partition the students into two groups: One group of students that will be giving money (those that spent less than group average) and the ones who will be receiving the money (those that spent more than the group average). But the `total` won't always divide without a remainder. So we divide the `total` by the number of students to get the quotient and the remainder, and we partition only using the quotient; that is group 1 will contain spends  $x$  such that  $x - \text{quotient} \leq 0$ , and group 2 will have the others.

```
6d  <1.3 Imports 6b>+≡
    import static java.lang.Math.abs;
    import static java.util.stream.Collectors.partitioningBy;
    import java.util.List;
    import java.util.Map;

6e  <1.3 Finding the minimum 6e>≡
    long quotient = total / values.length;
    long remainder = total % values.length;
    Map<Boolean, List<Long>> diff =
        stream(values).map(x -> x - quotient).boxed().collect(partitioningBy(x -> x > 0));
```

So what do we do with the **remainder**? These are those cents that we need to finally re-distribute among the members of the two groups. Note that the **remainder** will always be less than **n**. We choose the following strategy: We distribute these cents to the group that spent less than or equal to the **quotient**, the remaining cents are finally distributed to group 2. This is captured in the following code:

```
7a  <1.3 Finding the minimum 6e>+≡
    long sum = abs(diff.get(false).stream().reduce(Long::sum).get());
    long len = diff.get(true).size();
    remainder = len <= remainder ? remainder - len : 0;
    return sum + remainder;
```

All we need to do now is to write input reading, which is trivial:

```
7b  <1.3 Imports 6b>+≡
    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.math.BigDecimal;

7c  <1.3 Input/Output 7c>≡
    public static void main(String[] args) throws IOException {
        BufferedReader r = new BufferedReader(new InputStreamReader(System.in));
        int n = 0;
        while ((n = Integer.parseInt(r.readLine().trim())) > 0) {
            long[] values = r.lines().limit(n).map(x -> x.replaceAll("\\.",
                "").trim()).mapToLong(Long::parseLong).toArray();
            System.out.println("$" + BigDecimal.valueOf(calculate(values), 2));
        }
    }
```

## 1.4 LC Display

This task may seem quite involved at first sight, because you may start thinking about two-dimensional patterns and scaling functions. But in reality this task is much easier if you notice that the digits can be constructed not in a top to bottom (or bottom to up) row-by-row manner, but in a columnar manner; at the same time scaling becomes very easy.

```
7d  <LC Display 7d>≡
    package com.rvprg.pc;

    <1.4 Imports 8a>

    class LCDisplay {
        <1.4 Constants 8b>
        <1.4 Conversion 9a>
        <1.4 Input/Output 8c>
    }
```



Each LCD digit has 7 segments: Two in the first and the third columns and three in the second column. Let's encode our digits:

Digit	Binary	Hex
0	11 101 11	77
1	00 000 11	03
2	10 111 01	5D
3	00 111 11	1F
4	01 010 11	2B
5	01 111 10	3E
6	11 111 10	7E
7	00 001 11	07
8	11 111 11	7F
9	01 111 11	3F

Since we know that the input ends in two zeros we define this string constant plus a couple of other string constants.

```

8a  <1.4 Imports 8a>≡
    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.util.stream.Stream;

8b  <1.4 Constants 8b>≡
    private static final BufferedReader reader = new BufferedReader(new InputStreamReader(System.in));
    private static final String INPUT_END = "0 0";
    private static final String EMPTY = "";
    private static final String SPACE = " ";
    private static final byte[] pattern = new byte[] {
        0x77, 0x03, 0x5d, 0x1f, 0x2b, 0x3e, 0x7e, 0x07, 0x7f, 0x3f
    };

```

The array `pattern` for the given digit `i` returns bits that correspond to the segments, so for example `digits[5]` would return segments for digit 5. We will be using masks to discover which bits are set and not set.

But let's write input/output first as this is very easy. At the same time, let's assume our method that converts a string into LCD style digits is called `segments`. This method takes two arguments, the digits string and `scale`. Let's assume it returns list of strings which we can simply output to the console.

```

8c  <1.4 Input/Output 8c>≡
    public static void main(String[] args) throws IOException {
        String currentLine = INPUT_END;
        while ((currentLine = reader.readLine()) != null &&
            !currentLine.trim().equalsIgnoreCase(INPUT_END)) {
            List<String> input = Arrays.stream(currentLine.trim().split(SPACE))
                .filter(x -> !x.equals(""))
                .collect(Collectors.toList());
            segments(input.get(1), Integer.valueOf(input.get(0))).stream()
                .forEach(System.out::println);
            System.out.println();
        }
    }

```

Now all that's left is to implement `segments`.

```
9a  <1.4 Conversion 9a>≡
    private static List<String> segments(final String digits, final int scale) {
        <1.4 Helpers 9c>
        <1.4 Process 10e>
        <1.4 Return 10g>
    }
```

The idea is simple: We check bit 6 and bit 5 of the pattern and construct ASCII representation of the first column, then we check bit 4, 3, and 2 and construct the middle column, finally we check bit 1 and 0 to construct the last column. Of course, we need to take into account the scaling.

So let's have a look at an example. Let's say we need to construct digit 2 with scale 3. First, we get the pattern value `pattern[2]=5D`, or 1011101. Then, we start with the masks 40 and 20 to see which segments are on in the first column (bit 6 and bit 5); so, `40 & 5D = 1` and `20 & 5D = 0`, which means that the first segment is on and the second is off, so we output `└┐`. Because our scale is 3, we output `|` and `└` three times, so we end up with `└||┐`. Similarly we construct the third column, but we use different masks: 02 and 01.

OK, let's write some helpers already before we get back to producing the middle column. We will need some function that replicates a specified string *n* times. There's a Java function `nCopies` that does that, so we will use it. However, it returns a list of strings, therefore we use `join` function to join that into a single string using `EMPTY` as a delimiter. Let's write that:

```
9b  <1.4 Imports 8a>+≡
    import static java.lang.String.join;
    import static java.util.Collections.nCopies;
    import java.util.function.Function;

9c  <1.4 Helpers 9c>≡
    Function<String, String> g = x -> join(EMPTY, nCopies(scale, x));
```

Note that we use the fact that the `scale` is captured in the closure.

OK, we also need a mapping function that checks which bits are on and off in the given value using the list of masks. Depending on whether bits are on or off it returns ASCII character `|` or `└`. It will be a stream of such characters:

```
9d  <1.4 Helpers 9c>+≡
    BiFunction<Stream<Integer>, Byte, Stream<String>> h =
        (m, x) -> m.map(mask -> (x & mask) > 0 ? "|" : SPACE);
```

Here `m` is a stream of masks, and `x` is the value `pattern[i]` for some `i`. Note the function returns a stream as well.

Now we can write a function that constructs a column of our LCD digit. Let's call it `k`:

```
9e  <1.4 Imports 8a>+≡
    import static java.util.stream.Collectors.joining;
    import java.util.function.BiFunction;

9f  <1.4 Helpers 9c>+≡
    BiFunction<Stream<Integer>, Byte, String> k =
        (m, d) -> SPACE + h.apply(m, d).map(x -> g.apply(x)).collect(joining(SPACE)) + SPACE;
```

Note SPACES around (as per requirement) and that the segments within a column are joined by a space.

So far so good. Basically we can now write function `f` that takes a digit pattern `pattern[i]` and returns a stream of strings (in fact, the columns of our LCD digits).

```
10a  <1.4 Imports 8a>+≡
      import static java.util.stream.Collectors.toList;
      import static java.util.stream.Stream.of;
      import java.util.Arrays;

10b  <1.4 Helpers 9c>+≡
      final int digitHeight = scale * 2 + 3;
      Function<Byte, Stream<String>> f = x -> Arrays.asList(
        of(k.apply(of(0x40, 0x20), x)),
        <1.4 Middle Column Construction 10c>,
        of(k.apply(of(0x02, 0x01), x)),
        of(join(EMPTY, nCopies(digitHeight, SPACE))))
        .stream().reduce(Stream::concat).get();
```

Also note the last line which adds spaces between consecutive digits.

Finally, let's get back to the middle of the digit. To construct it, we will re-use exactly the same functions we've already defined. We use `h` to obtain the segments that are on and off. Note though that `h` returns `|` symbols, not the dashes, which are used to indicate horizontal LCD segments. So we will need to replace all occurrences of vertical bars with dashes. It's easy to see that the number of spaces between the horizontal segments will be exactly `scale`, which is already captured in the `g` function implementation. Finally, all we need to do, is to replicate the middle column `scale` times. All this can be very easily implemented like so:

```
10c  <1.4 Middle Column Construction 10c>≡
      nCopies(scale, h.apply(of(0x10, 0x08, 0x04), x)
        .collect(joining(g.apply(SPACE))).replace('|', '-')).stream()
```

Now we can map the string of digits using our `f` function:

```
10d  <1.4 Imports 8a>+≡
      import java.util.List;

10e  <1.4 Process 10e>≡
      List<String> segments = digits.chars().map(x -> x - '0').boxed()
        .flatMap(x -> f.apply(pattern[x])).collect(toList());
```

But remember, this gives us a list of columns of the LCD digits, not rows, so before returning it we need a little post-processing: For each column we take the last characters, concatenate these last characters into a string, and add to a list; then we take the next to the last characters and do the same, and so on:

```
10f  <1.4 Imports 8a>+≡
      import static java.util.stream.IntStream.range;
      import static java.util.stream.IntStream.rangeClosed;

10g  <1.4 Return 10g>≡
      return rangeClosed(1, digitHeight).boxed()
        .map(j -> digitHeight - j).map(j -> range(0, segments.size() - 1).boxed()
          .map(i -> Character.toString(segments.get(i).charAt(j))).collect(joining()))).collect(toList());
```

And that completes the program.

## 1.5 Graphical Editor

Very straightforward task. The only difficult part being the `fill` operation, but I leave it without comments either as the code is self-explanatory.

```
11  <Graphical Editor 11>≡
    package com.rvprg.pc;

    import static java.util.Arrays.stream;
    import static java.util.stream.Collectors.toList;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.util.ArrayDeque;
    import java.util.Deque;
    import java.util.List;

    public class GraphicalEditor {
        private static final BufferedReader reader = new BufferedReader(
            new InputStreamReader(System.in));
        private int[] [] canvas;
        private int m = 0, n = 0;

        private void clear() {
            for (int i = 0; i < n; ++i) {
                for (int j = 0; j < m; ++j) {
                    canvas[j][i] = '0';
                }
            }
        }

        private void execute(List<String> command) {
            int x, y1, y2, y, x1, x2, c;
            switch (command.get(0)) {
                case "I":
                    m = Integer.parseInt(command.get(1));
                    n = Integer.parseInt(command.get(2));
                    canvas = new int[m][n];
                    clear();
                    break;
                case "C":
                    clear();
                    break;
                case "L":
                    x = Integer.parseInt(command.get(1)) - 1;
                    y = Integer.parseInt(command.get(2)) - 1;
                    canvas[x][y] = command.get(3).charAt(0);
                    break;
                case "V":
                    x = Integer.parseInt(command.get(1)) - 1;
```

```
        y1 = Integer.parseInt(command.get(2)) - 1;
        y2 = Integer.parseInt(command.get(3)) - 1;
        c = command.get(4).charAt(0);
        for (y = Math.min(y1, y2); y <= Math.max(y1, y2); ++y) {
            canvas[x][y] = c;
        }
        break;
    case "H":
        x1 = Integer.parseInt(command.get(1)) - 1;
        x2 = Integer.parseInt(command.get(2)) - 1;
        y = Integer.parseInt(command.get(3)) - 1;
        c = command.get(4).charAt(0);
        for (x = Math.min(x1, x2); x <= Math.max(x1, x2); ++x) {
            canvas[x][y] = c;
        }
        break;
    case "K":
        x1 = Integer.parseInt(command.get(1)) - 1;
        y1 = Integer.parseInt(command.get(2)) - 1;
        x2 = Integer.parseInt(command.get(3)) - 1;
        y2 = Integer.parseInt(command.get(4)) - 1;
        c = command.get(5).charAt(0);
        for (x = x1; x <= x2; ++x) {
            for (y = y1; y <= y2; ++y) {
                canvas[x][y] = c;
            }
        }
        break;
    case "F":
        x = Integer.parseInt(command.get(1)) - 1;
        y = Integer.parseInt(command.get(2)) - 1;
        int newColor = command.get(3).charAt(0);
        int oldColor = canvas[x][y];
        fill(new Point(x, y), oldColor, newColor);
        break;
    case "S":
        String name = command.get(1);
        System.out.println(name);
        for (int i = 0; i < n; ++i) {
            for (int j = 0; j < m; ++j) {
                System.out.print((char) canvas[j][i]);
            }
            System.out.println();
        }
        break;
    default:
        break;
}

private static class Point {
    final int x, y;
```

```

        public Point(int x, int y) {
            this.x = x;
            this.y = y;
        }
    }

    private void fill(Point pt, int oldColor, int newColor) {
        if (canvas[pt.x][pt.y] != oldColor || oldColor == newColor) {
            return;
        }
        Deque<Point> q = new ArrayDeque<>();
        q.addLast(pt);
        canvas[pt.x][pt.y] = newColor;
        while (!q.isEmpty()) {
            pt = q.pop();
            if (pt.x + 1 < m && canvas[pt.x + 1][pt.y] == oldColor) {
                canvas[pt.x + 1][pt.y] = newColor;
                q.addLast(new Point(pt.x + 1, pt.y));
            }
            if (pt.x - 1 >= 0 && canvas[pt.x - 1][pt.y] == oldColor) {
                canvas[pt.x - 1][pt.y] = newColor;
                q.addLast(new Point(pt.x - 1, pt.y));
            }
            if (pt.y + 1 < n && canvas[pt.x][pt.y + 1] == oldColor) {
                canvas[pt.x][pt.y + 1] = newColor;
                q.addLast(new Point(pt.x, pt.y + 1));
            }
            if (pt.y - 1 >= 0 && canvas[pt.x][pt.y - 1] == oldColor) {
                canvas[pt.x][pt.y - 1] = newColor;
                q.addLast(new Point(pt.x, pt.y - 1));
            }
        }
    }

    public static void main(String[] args) throws IOException {
        GraphicalEditor editor = new GraphicalEditor();
        String currentLine;
        while ((currentLine = reader.readLine()) != null) {
            List<String> command = stream(currentLine.trim().split(" "))
                .filter(x -> !x.equals(""))
                .collect(toList());
            if (command.get(0).equalsIgnoreCase("X")) {
                break;
            }
            editor.execute(command);
        }
    }
}

```

## 1.6 Interpreter

This task is disappointingly straightforward.

```

14  <Interpreter 14>≡
    package com.rvprg.pc;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.util.ArrayList;
    import java.util.List;

    class Interpreter {
        private static final BufferedReader reader =
            new BufferedReader(new InputStreamReader(System.in));

        private static int interpret(List<Integer> input) {
            int[] reg = new int[10];
            int[] ram = new int[1000];
            for (int i = 0; i < input.size(); ++i) {
                ram[i] = input.get(i);
            }
            int pc = 0;
            int r = 0;
            while (ram[pc] != 100) {
                int op = ram[pc];
                int c = (op / 100) % 10;
                pc = (pc + 1) % 1000;
                r++;
                switch (c) {
                    case 2:
                        reg[(op / 10) % 10] = op % 10;
                        break;
                    case 3:
                        reg[(op / 10) % 10] = (reg[(op / 10) % 10] + (op % 10)) % 1000;
                        break;
                    case 4:
                        reg[(op / 10) % 10] = (reg[(op / 10) % 10] * (op % 10)) % 1000;
                        break;
                    case 5:
                        reg[(op / 10) % 10] = reg[op % 10];
                        break;
                    case 6:
                        reg[(op / 10) % 10] = (reg[(op / 10) % 10] + reg[op % 10]) % 1000;
                        break;
                    case 7:
                        reg[(op / 10) % 10] = (reg[(op / 10) % 10] * reg[op % 10]) % 1000;
                        break;
                    case 8:
                        reg[(op / 10) % 10] = ram[reg[op % 10]];
                        break;
                    case 9:
                        ram[reg[op % 10]] = reg[(op / 10) % 10];
                }
            }
        }
    }

```

```
        break;
    case 0:
        if (reg[op % 10] != 0) {
            pc = reg[(op / 10) % 10];
        }
        break;
    }
}

return r + 1;
}

public static void main(String[] args) throws IOException {
    int n = Integer.valueOf(reader.readLine().trim());
    reader.readLine();
    String currentLine;
    for (int i = 0; i < n; ++i) {
        List<Integer> input = new ArrayList<Integer>();
        while ((currentLine = reader.readLine()) != null &&
            !currentLine.trim().equalsIgnoreCase("")) {
            input.add(Integer.parseInt(currentLine.trim()));
        }
        System.out.println(interpret(input));
        if (i < n - 1) {
            System.out.println();
        }
    }
}
```



## 1.7 Check The Check

This task is trivial.

```

16  <Check The Check 16>≡
    package com.rvprg.pc;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;

    public class CheckTheCheck {
        private static final BufferedReader reader = new BufferedReader(
            new InputStreamReader(System.in));
        private static final int BOARD_SIZE = 8;

        private static final int[][] king = new int[][] {
            { -1, -1 }, { 0, -1 }, { 1, -1 }, { -1, 0 }, { 1, 0 }, { -1, 1 },
            { 0, 1 }, { 1, 1 }
        };
        private static final int[][] knight = new int[][] {
            { -2, -1 }, { -1, -2 }, { 1, -2 }, { 2, -1 }, { 2, 1 }, { 1, 2 },
            { -1, 2 }, { -2, 1 }
        };
        private static final int[][] bishop = new int[][] {
            { 1, 1 }, { -1, -1 }, { -1, 1 }, { 1, -1 }
        };
        private static final int[][] rook = new int[][] {
            { 1, 0 }, { -1, 0 }, { 0, 1 }, { 0, -1 }
        };
        private static final int[][] queen = new int[][] {
            { 1, 0 }, { -1, 0 }, { 0, 1 }, { 0, -1 }, { 1, 1 }, { -1, -1 },
            { -1, 1 }, { 1, -1 }
        };
        private static final int[][] white_pawn = new int[][] {
            { -1, -1 }, { -1, 1 }
        };
        private static final int[][] black_pawn = new int[][] {
            { 1, -1 }, { 1, 1 }
        };

        private static boolean isWithinBounds(int d, int v) {
            if (d == 0) {
                return true;
            }
            return d > 0 ? (v < BOARD_SIZE) : (v >= 0);
        }

        private static void check(int di, int dj, int i, int j, int[][] board,
            int[][] attackBoard) {
            int c = j + dj;
            int r = i + di;
            while (isWithinBounds(dj, c) && isWithinBounds(di, r)) {
                attackBoard[r][c] = 1;
            }
        }
    }

```

```

        if (board[r][c] != '.')
            break;
        r += di;
        c += dj;
    }
}

private static void check(int[][] d, int i, int j, int[][] board,
    int[][] attackBoard) {
    if (d == king || d == knight || d == black_pawn || d == white_pawn) {
        for (int k = 0; k < d.length; ++k) {
            if ((i + d[k][0] >= 0 && i + d[k][0] < BOARD_SIZE) &&
                (j + d[k][1] >= 0 && j + d[k][1] < BOARD_SIZE)) {
                attackBoard[i + d[k][0]][j + d[k][1]] = 1;
            }
        }
        return;
    }

    for (int k = 0; k < d.length; ++k) {
        check(d[k][0], d[k][1], i, j, board, attackBoard);
    }
}

private static int[] locate(int v, int[][] board) {
    for (int i = 0; i < BOARD_SIZE; ++i) {
        for (int j = 0; j < BOARD_SIZE; ++j) {
            if (board[i][j] == v) {
                return new int[] { i, j };
            }
        }
    }
    return null;
}

private static String checkTheCheck(int[][] board) {
    int[][] attackBoardWhites = new int[BOARD_SIZE][BOARD_SIZE];
    int[][] attackBoardBlacks = new int[BOARD_SIZE][BOARD_SIZE];

    for (int i = 0; i < BOARD_SIZE; ++i) {
        for (int j = 0; j < BOARD_SIZE; ++j) {
            if (board[i][j] == 'R' || board[i][j] == 'r') {
                check(rook, i, j, board, board[i][j] == 'R'
                    ? attackBoardWhites : attackBoardBlacks);
            }
            if (board[i][j] == 'B' || board[i][j] == 'b') {
                check(bishop, i, j, board, board[i][j] == 'B'
                    ? attackBoardWhites : attackBoardBlacks);
            }
            if (board[i][j] == 'K' || board[i][j] == 'k') {
                check(king, i, j, board, board[i][j] == 'K'
                    ? attackBoardWhites : attackBoardBlacks);
            }
        }
    }
}

```

```

        if (board[i][j] == 'N' || board[i][j] == 'n') {
            check(knight, i, j, board, board[i][j] == 'N'
                ? attackBoardWhites : attackBoardBlacks);
        }
        if (board[i][j] == 'Q' || board[i][j] == 'q') {
            check(queen, i, j, board, board[i][j] == 'Q'
                ? attackBoardWhites : attackBoardBlacks);
        }
        if (board[i][j] == 'P' || board[i][j] == 'p') {
            boolean isWhite = board[i][j] == 'P';
            check(isWhite ? white_pawn : black_pawn, i, j, board,
                isWhite ? attackBoardWhites : attackBoardBlacks);
        }
    }
}

int[] wk = locate('K', board);
int[] bk = locate('k', board);

boolean bkCheck = (attackBoardWhites[bk[0]][bk[1]] == 1);
boolean wkCheck = (attackBoardBlacks[wk[0]][wk[1]] == 1);

if (wkCheck) {
    return "white king is in check.";
}
if (bkCheck) {
    return "black king is in check.";
}

return "no king is in check.";
}

public static void main(String[] args) throws IOException {
    boolean empty = true;
    int game = 1;
    do {
        int[][] board = new int[BOARD_SIZE][BOARD_SIZE];
        empty = true;
        for (int i = 0; i < BOARD_SIZE; ++i) {
            String currentLine = reader.readLine();
            for (int j = 0; j < BOARD_SIZE; ++j) {
                board[i][j] = currentLine.charAt(j);
                empty = empty && board[i][j] == '.';
            }
        }
        if (empty) {
            break;
        }
        System.out.println("Game #" + game + ": " + checkTheCheck(board));
        game++;
    } while (reader.readLine().trim().equals(""));
}
}

```



## 1.8 Australian Voting

This task is very straightforward.

Let's sort out input/output first as usual. We will assume our function that does the election is called `elect`, and that it takes two arguments, a list of candidates and a list of ballots, and returns a list of those who win the election. Note the `ballots` is a list of dequeues, that's because we will be checking the next candidate in the ranking, and note that we subtract one from each index in the ballots, this is for easier access to the arrays, as they are indexed from 0.

```
20  <Australian Voting 20>≡
    package com.rvprg.pc;

    import static java.util.Arrays.stream;
    import static java.util.stream.Collectors.toList;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.util.ArrayDeque;
    import java.util.ArrayList;
    import java.util.Deque;
    import java.util.List;
    <1.8 Imports 21e>

    class AustralianVoting {
        private static final String EMPTY = "";
        private static final BufferedReader reader =
            new BufferedReader(new InputStreamReader(System.in));

        private static List<String> elect(List<String> candidates, List<Deque<Integer>> ballots) {
            <1.8 Implementation 21a>
        }

        public static void main(String[] args) throws IOException {
            int n = Integer.valueOf(reader.readLine().trim());
            reader.readLine();
            for (int i = 0; i < n; ++i) {
                int count = Integer.valueOf(reader.readLine().trim());
                List<String> candidates = reader.lines().limit(count).collect(toList());
                List<Deque<Integer>> ballots = new ArrayList<Deque<Integer>>();
                String currentLine = EMPTY;
                while ((currentLine = reader.readLine()) != null && !currentLine.equalsIgnoreCase(EMPTY)) {
                    ballots.add(new ArrayDeque<Integer>(stream(currentLine.trim().split(" "))
                        .filter(x -> !x.equals(EMPTY))
                        .map(Integer::parseInt).map(x -> x - 1).collect(toList())));
                }
                elect(candidates, ballots).forEach(System.out::println);
                if (i < n - 1) {
                    System.out.println();
                }
            }
        }
    }
```

```
}

```

Now let's implement `elect` function. First we need to figure out the majority. That's easy as that's simply the half of the ballots plus one.

```
21a <1.8 Implementation 21a>≡
    final int majority = ballots.size() / 2 + 1;

```

Because candidates in the ballots are numbered by their indexes in the table, let's have an array of `ints`, which will hold the number of votes.

```
21b <1.8 Implementation 21a>+=
    final int[] counter = new int[candidates.size()];

```

Now let's count votes for the candidates specified as first in the ballots:

```
21c <1.8 Implementation 21a>+=
    ballots.stream().map(Deque::peek).forEach(x -> counter[x]++);

```

After this point two things may happen: We will have somebody who got the majority of the votes, in which case we know the winner (or winners), or not, in which case we repeat the procedure described in the problem statement.

```
21d <1.8 Implementation 21a>+=
    while (true) {
        <1.8 Election loop 21f>
    }

```

OK, because some candidates may get equal number of votes we need to group them by votes. This is pretty easy:

```
21e <1.8 Imports 21e>≡
    import static java.util.stream.Collectors.groupingBy;
    import static java.util.stream.IntStream.range;
    import java.util.Map;

```

```
21f <1.8 Election loop 21f>≡
    Map<Integer, List<Integer>> result = range(0, candidates.size()).boxed()
        .filter(x -> counter[x] >= 0).collect(groupingBy(i -> counter[i], toList()));

```

Pay attention to the candidates who got zeros votes, because those will need to go through the elimination process too.

Now we need to find out who got the most votes and who got the least:

```
21g <1.8 Election loop 21f>+=
    int max = result.keySet().stream().max(Integer::compareTo).get();
    int min = result.keySet().stream().min(Integer::compareTo).get();

```

It's easy to see that if  $max \geq majority$  or  $max = min$ , then we know the winner:

```
21h <1.8 Election loop 21f>+=
    if (max >= majority || max == min) {
        return result.get(max).stream().map(x -> candidates.get(x)).collect(toList());
    }

```

Otherwise we need to re-distribute the votes. We get the indexes of the candidates who got the least votes and mark them as having -1 votes in the `counter` array so that we never consider them again in our filters.

```
21i <1.8 Election loop 21f>+=
    List<Integer> eliminated = result.get(min);
    eliminated.forEach(x -> counter[x] = -1);

```

Now we need to remove the eliminated candidates from the ballots. However it needs to be done carefully. We make note of who is currently the first in the ballot. If after the elimination process the first in the rank has changed, we need to take that into account. This is captured in the following chunk:

```
22a  <1.8 Election loop 21f>+≡
      ballots.forEach(b -> {
        int first = b.peek();
        eliminated.forEach(x -> b.remove(x));
        counter[b.peek()] += (first != b.peek()) ? 1 : 0;
      });
```

## 2 Chapter 2

### 2.1 Jolly Jumper

This task must be a joke.

```
22b  <Jolly Jumpers 22b>≡
      package com.rvprg.pc;

      import static java.lang.Math.abs;
      import static java.util.Arrays.stream;
      import static java.util.stream.Collectors.toList;
      import static java.util.stream.IntStream.range;

      import java.io.BufferedReader;
      import java.io.IOException;
      import java.io.InputStreamReader;
      import java.util.List;

      class JollyJumpers {
        private static final BufferedReader reader =
          new BufferedReader(new InputStreamReader(System.in));

        public static void main(String[] args) throws IOException {
          String currentLine;
          while ((currentLine = reader.readLine()) != null) {
            List<Integer> nums = stream(currentLine.trim().split(" ")).filter(x -> !x.equals(""))
              .skip(1).map(Integer::parseInt).collect(toList());
            int[] diffs = range(0, nums.size() - 1)
              .map(i -> abs(nums.get(i) - nums.get(i + 1))).distinct().sorted().toArray();
            boolean isJolly = range(0, diffs.length).boxed()
              .map(i -> diffs[i] == i + 1).reduce(true, (x, y) -> x && y);
            System.out.println(diffs.length == nums.size() - 1 && isJolly ? "Jolly" : "Not jolly");
          }
        }
      }
```

## 2.2 Crypt Kicker

This task is a lot of fun! To solve it we are going to need a very good bookkeeping discipline.

Let's outline the general strategy. First thing to do is to group the words by length. Then we need to come up with a method to compare a dictionary word and an encrypted word by looking at their patterns. So we somehow need to tell if the words "abbc" has a similar pattern as "xyyz". But this is very easy: we scan a word from left to right and output an index of the first occurrence of the character, or current index if it's the first occurrence. So for example "abbc" and "xyyz" would both have a pattern 1 2 2 3. Using a pattern and the word length we can find words from the dictionary that could be the potential matches for an encrypted word.

We start with the longest word (if multiple words of the same length, then any words of such length) and we find all the words from the dictionary that have the same length, the same pattern, and agree with the mapping found so far. By the mapping found so far we mean the following: if some previous word has been matched with a candidate, we note the mapping. So if we matched "abbc" with "xyyz" we now know that a maps to x, b maps to y, and c maps to z. This means that if we are now trying to match another word, say "zy", we can eliminate candidates such as "bc", because we now assume that z maps to c, not b. Once we filtered all the potential candidates we try to match the first candidate from the list and move on to the next word. If at any step we fail to find any candidate word, we return one step back, and try another word in the list, if the list is exhausted, we move one step back again. If we exhausted all the lists, then the decryption is impossible. For simplicity of implementation we will implement it as a recursion.

OK, now we just need to write code.

First input/output. The main class will be initialized by a dictionary and will have just one method `decrypt` that will take a string and return either a decrypted text or stars, as per problem statement.

```
23  <Crypt Kicker 23>≡
    package com.rvprg.pc;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;

    <2.4 Imports 24a>

    class CryptKicker {
        private static final BufferedReader reader =
            new BufferedReader(new InputStreamReader(System.in));

        <2.4 Variables 24f>

        <2.4 Constructor 24g>

        <2.4 Methods 24b>

        public static void main(String[] args) throws IOException {
            String currentLine;
            final int size = Integer.parseInt(reader.readLine().trim());
            final List<String> dictionary = reader.lines().limit(size).collect(toList());
            CryptKicker cryptKicker = new CryptKicker(dictionary);
```



```

        while ((currentLine = reader.readLine()) != null &&
               !currentLine.trim().equals("")) {
            System.out.println(cryptKicker.decrypt(currentLine));
        }
    }
}

```

Let's write the method that gives us the pattern of a given word. This method does exactly the thing we've described above.

```

24a  <2.4 Imports 24a>≡
      import static java.util.stream.Collectors.toList;
      import static java.util.stream.IntStream.range;

24b  <2.4 Methods 24b>≡
      private static List<Integer> getPattern(String word) {
          return range(0, word.length()).map(i -> word.indexOf(word.charAt(i)))
              .boxed().collect(toList());
      }

```

And let's add a helper method that for a given list of words gives a map. (Note that we take distinct words as the words in the input dictionary aren't necessarily unique.)

```

24c  <2.4 Imports 24a>+≡
      import static java.util.function.Function.identity;
      import static java.util.stream.Collectors.toMap;
      import java.util.List;
      import java.util.Map;
      import java.util.Deque;

24d  <2.4 Methods 24b>+≡
      private static Map<String, List<Integer>> getPatterns(Deque<String> words) {
          return words.stream().distinct().collect(
              toMap(identity(), CryptKicker::getPattern));
      }

```

Now we can do the constructor. In the constructor we will group the words by length and get their patterns.

```

24e  <2.4 Imports 24a>+≡
      import static java.util.stream.Collectors.groupingBy;
      import java.util.ArrayDeque;

24f  <2.4 Variables 24f>≡
      private final Map<Integer, List<String>> dictionary;
      private final Map<String, List<Integer>> patterns;

24g  <2.4 Constructor 24g>≡
      public CryptKicker(List<String> inputDictionary) {
          dictionary = inputDictionary.stream()
              .collect(groupingBy(String::length));
          patterns = getPatterns(new ArrayDeque<>(inputDictionary));
      }

```

We will also need a function to compare two given patterns. This is easy:

```
25a  <2.4 Imports 24a>+≡
      import static java.lang.Math.abs;

25b  <2.4 Methods 24b>+≡
      private static boolean compare(List<Integer> a, List<Integer> b) {
          return a.size() == b.size() &&
              range(0, a.size()).map(i -> abs(a.get(i) - b.get(i))).sum() == 0;
      }
```

Let's sort out the variables that we are going to need. We will need a map that will hold patterns of the encrypted words for the given input string.

```
25c  <2.4 Variables 24f>+≡
      private Map<String, List<Integer>> encryptedPatterns;
```

This variable could have been passed around via argument to the methods, because this variable's contents depend on each encrypted input line. But I have chosen to just have this as a private member.

We will also need to keep track of the words that have been mapped.

```
25d  <2.4 Imports 24a>+≡
      import java.util.HashSet;
      import java.util.Set;

25e  <2.4 Variables 24f>+≡
      private final Set<String> mappedWords = new HashSet<>();
```

And we will need the mappings themselves. We will keep both the direct mapping and the reversed mappings in the arrays, where an index is the ASCII character code and the value is another ASCII character code. Because ASCII characters for the lower case letters go from 97 to 122 it should be enough to just create an array of no more than 128 bytes. We could have created a smaller array, but in that case we would need to adjust the indexes which would clutter the code unnecessarily.

The `counter` array will keep track of how many words have used this character mapping so far. This is needed because we will be mapping and unmapping the words multiple times during the search. An empty array will denote unsuccessful mapping.

```
25f  <2.4 Variables 24f>+≡
      private static final int MAX_SIZE = 128;
      private static final int[] NOT_FOUND = new int[0];
      private final int[] dirMapping = new int[MAX_SIZE];
      private final int[] revMapping = new int[MAX_SIZE];
      private final int[] counter = new int[MAX_SIZE];
```

Let's implement `mapWord` and `unmapWord` methods. Note that they keep track (with help of `counter`) of how many words have used a specific character mapping.

```
26a  <2.4 Methods 24b>+≡
    private void mapWord(String e, String c) {
        mappedWords.add(c);
        for (int i = 0; i < e.length(); ++i) {
            dirMapping[e.charAt(i)] = c.charAt(i);
            counter[e.charAt(i)]++;
            revMapping[c.charAt(i)] = e.charAt(i);
        }
    }

    private void unmapWord(String e, String c) {
        mappedWords.remove(c);
        for (int i = 0; i < e.length(); ++i) {
            counter[e.charAt(i)]--;
            if (counter[e.charAt(i)] == 0) {
                revMapping[dirMapping[e.charAt(i)]] = 0;
                dirMapping[e.charAt(i)] = 0;
            }
        }
    }
}
```

We need to keep track of these mapping and `counter` because of the filtering. For example, if we mapped the word "abc" to "xyz" and the word "ab" to "xy", we now know that a maps to x, b maps to y, and c maps to z. So we can find that the word's "ab" mapping to "xy" is a valid mapping and so we can map that too. If for some reason we unmap the word "abc", our mapping arrays should still keep the mapping of a to x, and b to y, because we haven't unmapped the word "ab".

Now let's implement the filtering. This function take an encrypted word and does the following filtering. First, it gets all the words from the dictionary of the same length. Then it filters out the words that have been mapped already and the words that don't have the same pattern. Next, it checks if this word agrees with the mapping (may be partial) of the mappings found so far. If the word passes all this filtering, it is add to the list, which then returned as the result.

```
26b  <2.4 Imports 24a>+≡
    import java.util.ArrayList;
```

```

27a  <2.4 Methods 24b>+≡
    private List<String> filter(String encrypted) {
        List<String> matchedWords = new ArrayList<String>();
        for (String word : dictionary.get(encrypted.length())) {
            if (mappedWords.contains(word) ||
                !compare(encryptedPatterns.get(encrypted), patterns.get(word))) {
                continue;
            }

            boolean matched = true;
            for (int i = 0; i < word.length() && matched; ++i) {
                boolean unmapped = dirMapping[encrypted.charAt(i)] == 0;
                boolean mapped = dirMapping[encrypted.charAt(i)] == word.charAt(i);
                boolean unused = revMapping[word.charAt(i)] == 0;
                matched = (unmapped && unused) || mapped;
            }
            if (matched) {
                matchedWords.add(word);
            }
        }
        return matchedWords;
    }

```

We can now implement the recursive search method. It takes a deque of encrypted words and then tries to map them to the dictionary. (A deque because it has convenient methods such as `pop` and `push`.) This method assumes that the words in the deque are sorted by length in descending order.

```

27b  <2.4 Methods 24b>+≡
    private boolean map(Deque<String> encryptedWords) {
        if (encryptedWords.isEmpty()) {
            return true;
        }
        String encryptedWord = encryptedWords.pop();
        List<String> words = filter(encryptedWord);
        for (String candidate : words) {
            mapWord(encryptedWord, candidate);
            if (map(encryptedWords)) {
                return true;
            }
            unmapWord(encryptedWord, candidate);
        }
        encryptedWords.push(encryptedWord);
        return false;
    }

```

Let's add another helper method that will do the clearing up and initialization of the data structures:

```

27c  <2.4 Imports 24a>+≡
    import java.util.Arrays;

```

```

28a  <2.4 Methods 24b>+≡
      private int[] findMapping(Deque<String> encryptedWords) {
          encryptedPatterns = getPatterns(encryptedWords);
          mappedWords.clear();
          Arrays.fill(dirMapping, 0);
          Arrays.fill(revMapping, 0);
          Arrays.fill(counter, 0);
          return map(encryptedWords) ? dirMapping : NOT_FOUND;
      }

```

Finally, we can now implement `decrypt` method:

```

28b  <2.4 Imports 24a>+≡
      import static java.util.Comparator.comparing;

28c  <2.4 Methods 24b>+≡
      public String decrypt(String input) {
          StringBuilder result = new StringBuilder();
          int[] mapping = findMapping(
              new ArrayDeque<>(Arrays.stream(input.trim().split(" "))
                  .filter(x -> !x.equals(""))
                  .distinct()
                  .sorted(comparing(String::length).reversed())
                  .collect(toList())));
          input.chars().map(c -> c != ' ' ? (mapping != NOT_FOUND ? mapping[c] : '*') : c)
              .forEachOrdered(x -> result.append((char) x));
          return result.toString();
      }

```

## 3 Chapter 3

### 3.1 Crypt Kicker II

This task is much easier than Crypt Kicker. Here we have a very well known pangram "the quick brown fox jumps over the lazy dog". A pangram is a sentence that uses every letter of the alphabet at least once. So all we need to do is to locate the pangram in the input lines. We will use exactly the same technique as we used while solving the original Crypt Kicker problem.

```
29  <Crypt Kicker II 29>≡
    package com.rvprg.pc;

    import static java.lang.Math.abs;
    import static java.util.stream.Collectors.toList;
    import static java.util.stream.IntStream.range;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.util.ArrayList;
    import java.util.Arrays;
    import java.util.List;

    class CryptKickerII {
        private static final BufferedReader reader =
            new BufferedReader(new InputStreamReader(System.in));
        private final int[] mapping = new int[128];
        private static final String pangram = "the quick brown fox jumps over the lazy dog";
        private static final String pangramSpaces = pangram.replaceAll("[^ ]", ".");
        private static final List<Integer> pangramPattern = getPattern(pangram);

        private static List<Integer> getPattern(String word) {
            return range(0, word.length()).map(i -> word.indexOf(word.charAt(i)))
                .boxed().collect(toList());
        }

        private static boolean compare(List<Integer> a, List<Integer> b) {
            return a.size() == b.size() && range(0, a.size())
                .map(i -> abs(a.get(i) - b.get(i))).sum() == 0;
        }

        private boolean isPangram(String input) {
            String line = String.join(" ", Arrays.stream(input.trim()
                .split(" ")).filter(x -> !x.equals("")).collect(toList()));
            return compare(pangramPattern, getPattern(line.toString())) &&
                line.replaceAll("[^ ]", ".").equalsIgnoreCase(pangramSpaces);
        }

        public List<String> decrypt(List<String> input) {
            Arrays.fill(mapping, 0);
            List<String> output = new ArrayList<String>();
            String encryptedPangram = input.stream()
```

```

        .filter(x -> isPangram(x)).findFirst().orElse("");
    if (encryptedPangram.equalsIgnoreCase("")) {
        output.add("No solution.");
        return output;
    }

    for (int i = 0; i < encryptedPangram.length(); ++i) {
        mapping[encryptedPangram.charAt(i)] = pangram.charAt(i);
    }

    return input.stream().map(x -> {
        StringBuilder result = new StringBuilder();
        x.chars().map(c -> c != ' ' ? mapping[c] : c)
            .forEachOrdered(c -> result.append((char) c));
        return result.toString();
    }).collect(toList());
}

public static void main(String[] args) throws IOException {
    String currentLine;
    final int n = Integer.parseInt(reader.readLine().trim());
    reader.readLine();
    CryptKickerII cryptKicker = new CryptKickerII();
    for (int i = 0; i < n; ++i) {
        List<String> input = new ArrayList<String>();
        while ((currentLine = reader.readLine()) != null &&
            !currentLine.trim().equalsIgnoreCase("")) {
            input.add(currentLine);
        }
        cryptKicker.decrypt(input).forEach(System.out::println);
        if (i < n - 1) {
            System.out.println();
        }
    }
}

```

### 3.2 File Fragmentation

Let's sort out input/output assuming that our function `restore` takes a list of strings (i.e. shards) and returns the restored string (i.e. original file). Input is rather straightforward and, unfortunately, due to the format of the input data, isn't very concise.

```

31  <File Fragmentation 31>≡
    package com.rvprg.pc;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.util.ArrayList;
    import java.util.List;
    <3.6 Imports 32a>

    class FileFragmentation {
        private static final BufferedReader reader =
            new BufferedReader(new InputStreamReader(System.in));

        <3.6 Helpers 32e>

        private static String restore(List<String> fragments) {
            <3.6 Implementation 32b>
        }

        public static void main(String[] args) throws IOException {
            int n = Integer.parseInt(reader.readLine());
            reader.readLine();
            for (int i = 0; i < n; ++i) {
                List<String> fragments = new ArrayList<String>();
                do {
                    String s = reader.readLine();
                    if (s == null || s.equalsIgnoreCase("")) {
                        break;
                    }
                    fragments.add(s);
                } while (true);
                System.out.println(restore(fragments));
                if (i < n - 1) {
                    System.out.println();
                }
            }
        }
    }

```



So how do we restore the files? It's easy to see that if we sort the shards by length and then take the largest shard and the shortest one we will end up with a potential original file. But there may be numerous smallest shards and numerous largest shards, so we will need to try them one by one. This is not that bad as it seems at first sight. This is because we only need to try one largest shard with  $n$  shortest shards in the worst case, having only two cases: The long shard goes first and the short goes after it or vice versa. Once we got a candidate original file we simply try to fit the rest of the shards. This can be done very easily. We simply partition our candidate file at every point and then check if the list contains these shards, and if it does, we mark that. Once we found every shard in the list in this way we know that the original file was the same as our candidate file. Otherwise we try the next smallest shard. We continue until we fit every shard. This algorithm will always find the original file because of how the problem is formulated.

OK, so first thing we need to do is to sort the shards by length:

32a `<3.6 Imports 32a>≡`  
`import static java.util.Comparator.comparing;`

32b `<3.6 Implementation 32b>≡`  
`fragments.sort(comparing(String::length));`

Then we find the largest (any will do) and get the list of the smallest shards:

32c `<3.6 Imports 32a>+≡`  
`import static java.util.stream.Collectors.toList;`

32d `<3.6 Implementation 32b>+≡`  
`String large = fragments.get(fragments.size() - 1);`  
`List<String> smallest = fragments.stream().filter(`  
`x -> x.length() == fragments.get(0).length()).collect(toList());`

Let's write `fit` function that takes a list of shards and a candidate and returns true or false depending on whether those shards could be fit with this candidate file or not. This is implemented in accordance to the algorithm described earlier.

32e `<3.6 Helpers 32e>≡`  
`private static boolean fit(List<String> fragments, String candidate) {`  
`List<String> temp = new ArrayList<String>(fragments);`  
`for (int i = 1; i < candidate.length() && !temp.isEmpty(); ++i) {`  
`final int j = i;`  
`temp.removeIf(x -> x.equalsIgnoreCase(candidate.substring(0, j)));`  
`temp.removeIf(x -> x.equalsIgnoreCase(candidate.substring(j)));`  
`}`  
`return temp.isEmpty();`  
`}`

For the largest and every smallest shard we try to fit the rest of the shards using `fit` function trying both cases: `large + small`, and `small + large`.

32f `<3.6 Implementation 32b>+≡`  
`for (String small : smallest) {`  
`if (fit(fragments, large + small)) {`  
`return large + small;`  
`} else if (fit(fragments, small + large)) {`  
`return small + large;`  
`}`  
`}`  
`return "Impossible";`

In accordance to the problem statement "Impossible" should never be returned, unless the input is malformed for any reason.

## 4 Chapter 4

### 4.1 Bridge

This task is quite tricky. But before trying to solve it, let's just sort out input/output to get it out of the way.

We will assume that we have a method `getStrategy` that takes a list of integers (crossing times) and returns two lists. The first list holds crossing times going from left to right, and the second list holds crossing times from right to left. (We assume the group of people starts on the left side of the bridge.) Let's assume there's a `printResult` method that takes that output of `getStrategy` and prints it out in the format specified in the problem statement.

```
33  <Bridge 33>≡
    package com.rvporg.pc;

    <4.3 Imports (never defined)>
    import static java.util.stream.Collectors.toList;
    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.util.List;

    class Bridge {
        private static final BufferedReader reader =
            new BufferedReader(new InputStreamReader(System.in));
        private static final int LEFT_RIGHT = 0;
        private static final int RIGHT_LEFT = 1;
        <4.3 Variables (never defined)>

        <4.3 Methods (never defined)>

        public static void main(String[] args) throws IOException {
            int n = Integer.valueOf(reader.readLine().trim());
            reader.readLine();
            for (int i = 0; i < n; ++i) {
                int count = Integer.valueOf(reader.readLine().trim());
                List<Integer> input = reader.lines().map(String::trim)
                    .limit(count).map(Integer::parseInt).collect(toList());
                printResult(getStrategy(input));
                if (i < n - 1) {
                    reader.readLine();
                    System.out.println();
                }
            }
        }
    }

    TBD.
```

## 4.2 ShellSort

The key to this problem answer is to note that all the items in the stack above the one that is about to be moved will move down. Therefore we just need to find all such elements, and everything else will need to be moved using the operation described in the problem statement.

Let's start with the input/output assuming that we have `getStrategy` method which takes `input` array and the `target` array and returns an answer, i.e. a list of items that need to be moved to the top:

```
34  <ShellSort 34>≡
    package com.rvpgrg.pc;

    import static java.util.stream.Collectors.toList;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.util.Collections;
    import java.util.List;

    class ShellSort {
        private static final BufferedReader reader =
            new BufferedReader(new InputStreamReader(System.in));

        private static List<String> getStrategy(List<String> input, List<String> target) {
            <4.7 Implementation 35>
        }

        public static void main(String[] args) throws IOException {
            int n = Integer.valueOf(reader.readLine().trim());
            for (int i = 0; i < n; ++i) {
                int count = Integer.valueOf(reader.readLine().trim());
                List<String> input = reader.lines().limit(count).collect(toList());
                List<String> target = reader.lines().limit(count).collect(toList());
                getStrategy(input, target).forEach(System.out::println);
                System.out.println();
            }
        }
    }
```

OK, let's get to the implementation of the method that finds the optimal strategy. We start from the bottom of the lists and work towards the top, comparing the items. The idea is that we move sequentially in the **target** array and move towards the top in the **input** array potentially skipping some elements until we hit the start of the array. The index in the **target** array, at which we broke the loop, will be the point that will divide the **target** array into two parts: Elements above it are the elements that will need to be moved, elements below do not need to be moved.

```
35  <4.7 Implementation 35>≡
    int i = input.size() - 1;
    int j = target.size() - 1;
    while (i >= 0 && j >= 0) {
        while (j >= 0 && !target.get(i).equals(input.get(j))) {
            j--;
        }
        if (j < 0) {
            break;
        }
        i--;
        j--;
    }
    List<String> output = target.subList(0, i + 1);
    Collections.reverse(output);
    return output;
```

## 5 Chapter 5

### 5.1 Primary Arithmetic

This task is trivial.

```

36  <Primary Arithmetic 36>≡
    package com.rvprg.pc;

    import static java.util.stream.Collectors.toList;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.util.Arrays;
    import java.util.Comparator;
    import java.util.List;

    public class PrimaryArithmetic {
        private static final BufferedReader reader = new BufferedReader(
            new InputStreamReader(System.in));

        private static int[] asArray(String input, int pad) {
            int[] a = new int[input.length() + pad];
            for (int i = 0; i < input.length(); ++i) {
                a[i] = input.charAt(input.length() - i - 1) - '0';
            }
            return a;
        }

        public static int count(List<String> input) {
            int[] a = asArray(input.get(0), 0);
            int[] b = asArray(input.get(1),
                input.get(0).length() - input.get(1).length());
            int carry = 0;
            int count = 0;
            for (int i = 0; i < a.length; ++i) {
                int c = a[i] + b[i] + carry;
                if (c >= 10) {
                    carry = 1;
                    count++;
                } else {
                    carry = 0;
                }
            }
            return count;
        }

        public static String toMessage(int count) {
            if (count == 0) {
                return "No carry operation.";
            } else if (count == 1) {
                return "1 carry operation.";
            } else {

```

```
        return count + " carry operations.";
    }
}

public static void main(String[] args) throws IOException {
    String currentLine;
    while ((currentLine = reader.readLine()) != null) {
        List<String> input = Arrays
            .stream(currentLine.trim().split(" "))
            .filter(x -> !x.equals(" "))
            .sorted(Comparator.comparing(String::length).reversed())
            .collect(toList());
        if (input.get(0).equals("0") && input.get(1).equals("0")) {
            break;
        }
        System.out.println(toMessage(count(input)));
    }
}
```

## 5.2 Reverse And Add

This task is trivial.

```

38  <Reverse And Add 38>≡
    package com.rvprg.pc;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;

    class ReverseAndAdd {
        private static final BufferedReader reader = new BufferedReader(
            new InputStreamReader(System.in));

        private static long reverse(long value) {
            long reversed = 0;
            while (value > 9) {
                reversed = reversed * 10 + (value % 10);
                value /= 10;
            }
            reversed = reversed * 10 + value;
            return reversed;
        }

        private static boolean isPalindrome(long value) {
            return value == reverse(value);
        }

        public static long[] calculate(long value) {
            int count = 0;
            do {
                value = value + reverse(value);
                count++;
            } while (!isPalindrome(value));
            return new long[] { count, value };
        }

        public static void main(String[] args) throws IOException {
            int n = Integer.parseInt(reader.readLine().trim());
            for (int i = 0; i < n; ++i) {
                long v = Integer.parseInt(reader.readLine().trim());
                long[] res = calculate(v);
                System.out.println(res[0] + " " + res[1]);
            }
        }
    }

```

### 5.3 The Archeologists' Dilemma

Unlike the previous two tasks, this task is quite challenging.

Let's paraphrase this task in mathematical terms. For a given number  $v$  find positive integers  $m$  and  $n$  such that

$$v \cdot 10^n \leq 2^m < (v + 1) \cdot 10^n$$

where  $n \geq l(v) + 1$ , and  $l(v)$  is the number of digits in  $v$ .

Let's take common logarithms on that inequality

$$\log(v \cdot 10^n) \leq \log(2^m) < \log((v + 1) \cdot 10^n)$$

which is the same as

$$\log(v) + \log(10^n) \leq \log(2^m) < \log(v + 1) + \log(10^n)$$

and

$$\log(v) + n \cdot \log(10) \leq m \cdot \log(2) < \log(v + 1) + n \cdot \log(10)$$

which is the same as

$$\log(v) + n \leq m \cdot \log(2) < \log(v + 1) + n.$$

This solves the task, because all we need to do now is to iterate on  $n$  starting with  $n = l(v) + 1$ . For a given  $n$  we find an initial  $m$  by using the left part of the inequality, so

$$m = \lfloor \frac{\log(v) + n}{\log(2)} \rfloor$$

Then we increment  $m$  while  $\log(v) + n \geq m \cdot \log(2)$ . Once this loop stops, we check if  $m \cdot \log(2) < \log(v + 1) + n$ , and if so,  $m$  is the answer. Otherwise, we increment  $n$  and start everything all over again.

```
39  <The Archeologists Dilemma 39>≡
    package com.rvporg.pc;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.math.BigDecimal;

    public class TheArcheologistsDilemma {
        private static final BufferedReader reader = new BufferedReader(
            new InputStreamReader(System.in));

        private static long calculate(long v) {
            long n = BigDecimal.valueOf(v).precision() + 1;
            final double left = Math.log10(v);
            final double right = Math.log10(v + 1);
            final double log10_2 = Math.log10(2);
            while (true) {
                long m = (long) Math.floor((left / log10_2) + n / log10_2);
                while (left + n > (log10_2 * m)) {
```



```
        m++;
    }
    if (right + n > (log10_2 * m)) {
        return m;
    }
    n++;
}

}

public static void main(String[] args) throws IOException {
    String currentLine;
    while ((currentLine = reader.readLine()) != null) {
        System.out.println(calculate(Long.parseLong(currentLine.trim())));
    }
}

}
```

## 5.4 Ones

This is a little nice problem but it may take some time to come up with a proper solution. Obviously these "minimum multiples" of  $n$  can quickly become too large, and so we can't use the standard types of the language to do the calculations. The next natural idea would be to try to use `BigInteger` and repeatedly do  $x = x \times 10 + 1$  and then checking  $x \% n == 0$  until it becomes `true`. But this is not a solution, it's too slow.

Another idea would be to come up with some clever "divisibility rules" to see if a given  $n$  divides a number that has only 1s in it. But this is a dead end too.

Of course, the general idea is to simply test if  $x \% n == 0$  for a given  $n$  where  $x$  is a number consisting of 1s only.

To do that we can simply do long division and keep appending 1s to the remainder until it doesn't divide without a remainder.

Before we implement the long division, let's write input/output:

```
41a  <Ones 41a>≡
      package com.rvprg.pc;

      import java.io.BufferedReader;
      import java.io.IOException;
      import java.io.InputStreamReader;

      class Ones {
          private static final BufferedReader reader =
              new BufferedReader(new InputStreamReader(System.in));

          private static int calculate(int n) {
              <5.4 Calculation 41b>
          }

          public static void main(String[] args) throws IOException {
              reader.lines().map(Integer::parseInt)
                      .map(Ones::calculate)
                      .forEach(System.out::println);
          }
      }
```

We implement the case when  $n$  is 1 first:

```
41b  <5.4 Calculation 41b>≡
      if (n == 1) {
          return 1;
      }
```

Any other number can be calculated using the long division.

Let's workout a small example. Let's say we want to find the minimum multiple for  $n = 91$ . We start with  $s = 11$  and  $r = 11$ . But clearly because  $s < n$  we need to append one more 1,  $s = r \times 10 + 1$ , so now  $s = 111$ , and  $r = s - (n * \lfloor s/n \rfloor)$ , so  $r = 20$ ; and since  $r \neq 0$  we continue by extending  $s = r \times 10 + 1$  and then repeat the steps until  $r = 0$ . But note though that  $r = s - (n * \lfloor s/n \rfloor)$  is equivalent to  $r = s \% n$ .

OK, now we can capture that in code:

```
42 <5.4 Calculation 41b>+=  
    int l = 0;  
    int r = 0;  
    do {  
        r = (r * 10 + 1) % n;  
        l++;  
    } while (r > 0);  
    return l;
```

Brilliant.

## 5.5 A Multiplication Game

Unfortunately I couldn't come up with anything more clever than a recursive algorithm that tries all the possible multipliers at each step and chooses the one that leads to the win. Because a direct recursive algorithm without any optimization would be awfully slow, we need some memoization. This is possible, because many multipliers would lead to the same value, so we can cache them, we just need to keep track of whose turn it is at this moment of time. For that we will have a list of two maps, one for each player, and the map will map a value to the result.

The program is quite compact:

```
43  <A Multiplication Game 43>≡
    package com.rvprg.pc;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    import java.util.ArrayList;
    import java.util.HashMap;
    import java.util.List;

    class MultiplicationGame {
        private static final BufferedReader reader = new BufferedReader(
            new InputStreamReader(System.in));

        private static int solve(long p, long n, int t,
            List<HashMap<Long, Integer>> memo) {
            if (p >= n) {
                return t - 1;
            }

            int s = t % 2;
            for (int i = 9; i >= 2; --i) {
                int result = 0;
                long next = p * i;
                if (memo.get(s).containsKey(next)) {
                    result = memo.get(s).get(next);
                } else {
                    result = solve(next, n, t + 1, memo);
                    memo.get(s).put(next, result);
                }
                if (result % 2 == t % 2) {
                    return result;
                }
            }

            return t + 1;
        }

        public static void main(String[] args) throws IOException {
            String currentLine;
```

```
while ((currentLine = reader.readLine()) != null) {
    long input = Long.parseLong(currentLine.trim());
    List<HashMap<Long, Integer>> memo = new ArrayList<>();
    memo.add(new HashMap<Long, Integer>());
    memo.add(new HashMap<Long, Integer>());
    System.out.println(
        solve(1, input, 1, memo) % 2 == 0 ? "Ollie wins."
        : "Stan wins.");
    }
}
```

## 6 Chapter 7

### 6.1 Light, More Light

With this tasks we are basically asked to find the number of divisors of the given number. Once we know the number of divisors, we can figure out the last bulb state by checking if the number of the divisors is even or odd.

Let's sort out the input/output first as usual. We assume that we have `calculate` method that returns the number of divisors for a given number.

```
45 <Light, More Light 45>≡
    package com.rvprg.pc;

    import java.io.BufferedReader;
    import java.io.IOException;
    import java.io.InputStreamReader;
    <7.1 Imports 46a>

    class LightMoreLight {
        private static final BufferedReader reader = new BufferedReader(
            new InputStreamReader(System.in));
        <7.1 Variables 46b>

        LightMoreLight() {
            <7.1 Constructor 46c>
        }

        public long calculate(long value) {
            <7.1 Implementation 47>
        }

        public static void main(String[] args) throws IOException {
            LightMoreLight l = new LightMoreLight();
            String currentLine;
            while ((currentLine = reader.readLine()) != null &&
                !currentLine.trim().equals("0")) {
                long value = Long.parseLong(currentLine.trim());
                System.out.println(l.calculate(value) % 2 == 0 ? "no" : "yes");
            }
        }
    }
```

OK, to figure out the number of divisors we will use the fundamental theorem of arithmetic. This theorem states that: Every integer greater than one either is prime itself or is the product of prime numbers, and that this product is unique, up to the order of the factors. To find the prime factorization we can use a straightforward algorithm: simply by dividing a number by the primes less than the number itself, trying them one by one.

Since we need to know the prime numbers, let's pre-calculate them first in the constructor. We won't need primes larger than  $\sqrt{2^{32}-1}$ , but we'll define a constant MAX\_PRIMES a bit larger than that. We will use a classic algorithm for finding prime numbers, the sieve of Eratosthenes algorithm.

```

46a  <7.1 Imports 46a>≡
      import java.util.ArrayList;
      import java.util.BitSet;
      import java.util.List;

46b  <7.1 Variables 46b>≡
      private final List<Long> primes;
      private final static int MAX_PRIMES = 70000;

46c  <7.1 Constructor 46c>≡
      BitSet bits = new BitSet(MAX_PRIMES);
      for (int i = 2; i < Math.sqrt(MAX_PRIMES); ++i) {
          if (!bits.get(i)) {
              int k = 0;
              int ii = i * i;
              int j = ii + k * i;
              while (j < MAX_PRIMES) {
                  bits.set(j);
                  k++;
                  j = ii + k * i;
              }
          }
      }
      primes = new ArrayList<Long>();
      for (int i = 2; i < bits.length(); ++i) {
          if (!bits.get(i)) {
              primes.add((long) i);
          }
      }

```

Now the interesting part: In fact we don't need the prime numbers of the factorization, we only need their exponents to find out the number of divisors.

To see why, consider a number of the form  $v = p_1^n$ . The divisors of this number are  $1, p_1, p_1^2, p_1^3, \dots, p_1^n$ ; therefore the number of the divisors is  $n + 1$ .

Consider a number of the form  $v = p_1^n p_2^m$ , its divisors are:

1	$p_1$	$p_1^2$	...	$p_1^n$
$p_2$	$p_1 p_2$	$p_1^2 p_2$	...	$p_1^n p_2$
$p_2^2$	$p_1 p_2^2$	$p_1^2 p_2^2$	...	$p_1^n p_2^2$
...	...	...	...	...
$p_2^m$	$p_1 p_2^m$	...	...	$p_1^n p_2^m$

Therefore the number of its divisors is  $(n + 1)(m + 1)$ .

Generally the number of the divisors for a number  $v = p_1^n p_2^m \dots p_k^l$  is  $(n+1)(m+1) \dots (l+1)$ .

47  $\langle 7.1$  Implementation 47  $\rangle \equiv$

```
List<Long> factors = new ArrayList<Long>();
for (int i = 0; i < primes.size() && value > 1 &&
    (primes.get(i) * primes.get(i)) <= value; ++i) {
    long p = 0;
    while (value % primes.get(i) == 0) {
        value /= primes.get(i);
        p++;
    }
    if (p > 0) {
        factors.add(p);
    }
}
if (value > 1) {
    factors.add(1L);
}
return factors.stream().map(x -> x + 1).reduce(1L, (a, b) -> a * b);
```



This concludes the program.

## 7 License

Copyright©2017 Roman Valiušenko

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## References

- [1] Donald E. Knuth, Literate Programming, The Computer Journal, 1984, pp 97–111
- [2] Skiena, Steven S, Revilla, Miguel A., Programming Challenges, 2003

---

## Definitions

<1.3 Calculation 6c> 6a, 6c  
 <5.4 Calculation 41b> 41a, 41b, 42  
 <1.2 Constants 4c> 4a, 4c  
 <1.4 Constants 8b> 7d, 8b  
 <1.1 Constructor 3a> 1a, 3a  
 <2.4 Constructor 24g> 23, 24g  
 <7.1 Constructor 46c> 45, 46c  
 <1.4 Conversion 9a> 7d, 9a  
 <1.8 Election loop 21f> 21d, 21f, 21g, 21h, 21i, 22a  
 <1.3 Finding the minimum 6e> 6c, 6e, 7a  
 <1.1 Helpers 2b> 1a, 2b  
 <1.4 Helpers 9c> 9a, 9c, 9d, 9f, 10b  
 <3.6 Helpers 32e> 31, 32e  
 <1.8 Implementation 21a> 20, 21a, 21b, 21c, 21d  
 <3.6 Implementation 32b> 31, 32b, 32d, 32f  
 <4.7 Implementation 35> 34, 35  
 <7.1 Implementation 47> 45, 47  
 <1.1 Imports 1b> 1a, 1b, 2a, 2c, 3b  
 <1.2 Imports 4b> 4a, 4b, 4d  
 <1.3 Imports 6b> 6a, 6b, 6d, 7b  
 <1.4 Imports 8a> 7d, 8a, 9b, 9e, 10a, 10d, 10f  
 <1.8 Imports 21e> 20, 21e  
 <2.4 Imports 24a> 23, 24a, 24c, 24e, 25a, 25d, 26b, 27c, 28b  
 <3.6 Imports 32a> 31, 32a, 32c  
 <4.3 Imports (never defined)> 33  
 <7.1 Imports 46a> 45, 46a  
 <1.1 Input/Output 3c> 1a, 3c  
 <1.3 Input/Output 7c> 6a, 7c  
 <1.4 Input/Output 8c> 7d, 8c  
 <1.2 Main 5> 4a, 5  
 <2.4 Methods 24b> 23, 24b, 24d, 25b, 26a, 27a, 27b, 28a, 28c  
 <4.3 Methods (never defined)> 33  
 <1.4 Middle Column Construction 10c> 10b, 10c  
 <1.4 Process 10e> 9a, 10e  
 <1.4 Return 10g> 9a, 10g  
 <2.4 Variables 24f> 23, 24f, 25c, 25e, 25f  
 <4.3 Variables (never defined)> 33  
 <7.1 Variables 46b> 45, 46b  
 <A Multiplication Game 43> 43  
 <Australian Voting 20> 20

⟨ <i>Bridge</i> 33⟩	<u>33</u>
⟨ <i>Check The Check</i> 16⟩	<u>16</u>
⟨ <i>Crypt Kicker</i> 23⟩	<u>23</u>
⟨ <i>Crypt Kicker II</i> 29⟩	<u>29</u>
⟨ <i>File Fragmentation</i> 31⟩	<u>31</u>
⟨ <i>Graphical Editor</i> 11⟩	<u>11</u>
⟨ <i>Interpreter</i> 14⟩	<u>14</u>
⟨ <i>Jolly Jumpers</i> 22b⟩	<u>22b</u>
⟨ <i>LC Display</i> 7d⟩	<u>7d</u>
⟨ <i>Light, More Light</i> 45⟩	<u>45</u>
⟨ <i>Minesweeper</i> 4a⟩	<u>4a</u>
⟨ <i>Ones</i> 41a⟩	<u>41a</u>
⟨ <i>Primary Arithmetic</i> 36⟩	<u>36</u>
⟨ <i>Reverse And Add</i> 38⟩	<u>38</u>
⟨ <i>ShellSort</i> 34⟩	<u>34</u>
⟨ <i>The Archeologists Dilemma</i> 39⟩	<u>39</u>
⟨ <i>The Trip</i> 6a⟩	<u>6a</u>
⟨ <i>3n+1</i> 1a⟩	<u>1a</u>

**Index**