

NAEOS Getting Started

Version 3.6.0

NAEOS Foundation

2026-10-04

Prerequisites

- Go 1.26.6+ (for `go install` method)
- A terminal with basic command-line knowledge

Installation

Choose one of these methods:

Go Install

```
go install github.com/NAEOS-foundation/naeos/cmd/naeos@latest
```

Docker

```
docker pull ghcr.io/naeos-foundation/naeos:latest
docker run --rm -v $(pwd):/workspace ghcr.io/naeos-foundation/naeos:latest naeos version
```

Build from Source

```
git clone https://github.com/NAEOS-foundation/naeos.git
cd naeos
go build ./cmd/naeos/
```

Your First Pipeline

1. Create a specification file

Create `spec.yaml`:

```
project: my-app
modules:
  - name: auth
    path: ./auth
  - name: api
    path: ./api
    dependencies: [auth]
services:
  - name: gateway
    kind: http
    port: 8080
generation:
  languages: [go, typescript]
```

2. Initialize configuration

```
naeos init
```

3. Run the pipeline

```
naeos run --input-file spec.yaml
```

4. Generate AI context

```
naeos context --input-file spec.yaml
```

5. Compile for AI assistants

```
naeos ai compile --input-file spec.yaml --target opencode
```

Verify the result

After `naeos run`, the generated project is written to the configured output directory (typically `./generated`). Confirm the pipeline produced the expected structure:

```
find generated -maxdepth 2 -type f | sort
```

You should see a project README, language-specific files, and configuration artifacts. The exact file list depends on the languages and modules in your specification.

For a complete, isolated example that validates output automatically, run the CLI demo:

```
go build -o naeos ./cmd/naeos  
./examples/demo-cli/run-demo.sh
```

The demo writes `context.md`, `summary.md`, and generated artifacts under `examples/demo-cli/.run/`.

Troubleshooting

- If `naeos` is not found after `go install`, add `$(go env GOPATH)/bin` to your `PATH`, or use the binary built from source.
- If validation fails, check the reported field and compare the specification with the Spec Language guide.
- If generation succeeds but files are not where expected, inspect `naeos.yaml` and its `output_dir` value.

Next Steps

- Explore the CLI Reference for all available commands
- Read about the Architecture to understand how NAEOS works
- Check out the Features page for a complete overview

Download

- Getting Started PDF