

PT. IMC TEKNO INDONESIA

INJECTION MOLDING CONDITION STANDARD

QUALITY CONTROL	ENGINEERING	PRODUCTION	PREPARED BY
			NURRONI

DATE : 10 JULI 2026

STATUS :

TRIAL

V

 MASS PRO

PART NAME : REFLECTOR

PART NO. : 22642-8F039

CUSTOMER : PT. INDONESIA KOITO

INJECTION MACHINE

MC no/Ton.: 52/220T SCREW Ø : 50 mm

MODEL : FN5000-50A

CONTROLLER : NC 9000

MATERIAL

NAME : PC MAKROLON

GRADE : 2405 901510 MAS048

COLOUR : BLACK

DRY UP TM : 4 H

DRY UP TMP : 120 °C

REGRIND : - %

MASTER BATCH : - %

PART

CAVITY : 2/2

TOTAL WEIGHT : 149,718 g

PART WEIGHT :

1

 66,662 g

g

g

g

g

RUNNER WEIGHT : 15,003 g

ANNEALING STANDARD :

PART WEIGHT :

2

 68,053 g

g

g

g

g

MOLD

MTC SETTING : 80 °C

MTC ACTUAL TEMP. : 80 °C

CHILLER TMP :

MOLD ACTUAL TEMPERATURE (± 5) °C

CAVITY SIDE : 85 °C

CORE SIDE : 82 °C

< INJ / MTG >

1. INJ TM

2. COOL TM

3. CYC ST TM

4. MTG ST. TM

5. NOZZLE BWD TM

10 sec

20 sec

0,2 sec

- sec

- sec

6. V5

7. V4

8. V3

9. V2

10. V1

25 %

35 %

40 %

20 %

10 %

11. TP2

12. S5

13. S4

14. S3

15. S2

16. S1

17. SM

18. SD

0,3 sec

10 mm

20 mm

25 mm

30 mm

50 mm

75 mm

3 mm

19. P3

20. P2

21. P1

22. VS

23. BACK PRESSURE

40 %

60 %

40 %

85 %

10 kgf

BARREL TEMPERATURE (± 10) °C

NOZZLE

Set 285 °C

Act 285 °C

FRONT

Set 310 °C

Act 310 °C

< OPEN CLOSE >

1. HI MILD CLS V

2. CLAMP SLOW V

3. LOW MLD CLS P

3. HI MLD CLS P

25 %

25 %

15 %

85 %

5. OPEN SLOW

6. HI MLD OPEN V

7. PRI OPEN V

8 PRI OPEN TM

20 %

30 %

25 %

1 %

MIDDLE

Set 290 °C

Act 290 °C

< EJECTOR >

1. EJECT PRES

2. FWD EV1

3. COUNT

4. START TM

35 %

30 %

1 %

0,9 %

5. MOMENT STOP

6. BWD EV 4

7. BWD PRES

8. STOP TM

1ST LAST

95 %

95 %

0,8 %

9. REPEAT EJECT EV 3

85 %

REAR

Set 280 °C

Act 288 °C

FEEDER TEMPERATURE (± 10) °C

°C

Limit Switch			Rev.No	Date	Description	Prod	PE	QC
LS 5	Eject forward stop	mm	△					
LS 14	Eject backward stop	mm						
LS 3	High Pressure Selection	mm	△					
LS 2	Low pressure mold clamping	mm						
LS 8	Mold opening slow down	mm	△					
LS 4	Mold opening stop	mm						

INJECTION MOLDING CONDITION STANDARD

*Referensi Pengisian Std. & Act. MCS

✓ ROBOT RUNNER SETTING

v	RE- TRACK
---	-----------

[illegible]

	USE ROBOT RUNNER	
	NOT USE ROBOT RUNNER	
	RE- TRACK	
	NO RE-TRACK	
	EJECTOR OPERATING	
	NORMAL	☐ OVERRIDE
	MONITOR	
	COUNTER	
	NOZZLE NOT LEAKING	

FLOW COOLING SYSTEM

[illegible]

LIMIT MATERIAL STAY IN HOPPER

	Kg
--	----