

PT. IMC TEKNO INDONESIA

INJECTION MOLDING CONDITION STANDARD

QUALITY CONTROL	ENGINEERING	PRODUCTION	PREPARED BY
			SUDIN K

DATE : 28 JULI 2026

STATUS : ☒ TRIAL ☐ MASS PRO

PART NAME : SHAFT COMP WATER PUMP TL.3

PART NO. : 17510-12K01

CUSTOMER : PT. SUZUKI INDOMOBIL MOTOR

INJECTION MACHINE

MC no/Ton.: 29/60T SCREW Ø: 28 mm

MODEL : PS60E9A

CONTROLLER : NC 9000

MATERIAL

NAME : PA AMILAN

GRADE : CM3001 G30

COLOUR : BLACK

DRY UP TM : 4 H

DRY UP TMP : 90 °C

REGRIND : - %

MASTER BATCH : - %

PART

CAVITY : 2/2

TOTAL WEIGHT : 23,249 g

PART WEIGHT : ☒ 5 8,875 g ☐ g ☐ g ☐ g

RUNNER WEIGHT : 5,518 g

ANNEALING STANDARD :

: ☒ 6 8,856 g ☐ g ☐ g ☐ g

MOLD

MTC SETTING : 80 °C

MTC ACTUAL TEMP. : 80 °C

CHILLER TMP : °C

MOLD ACTUAL TEMPERATURE (± 5) °C

CAVITY SIDE : 80 °C

CORE SIDE : 75 °C

< INJ / MTG >

1. INJ TM 2. COOL TM 3. CYC ST TM 4. MTG ST. TM 5. NOZZLE BWD TM

6 sec 30 sec - sec - sec - sec

6. V5 7. V4 8. V3 9. V2 10. V1

5 % 10 % 15 % 30 % 40 %

11. TP2 12. S5 13. S4 14. S3 15. S2 16. S1 17. SM 18. SD

1,5 sec 8 mm 10 mm 15 mm 25 mm 30 mm 45 mm 5 mm

19. P3 20. P2 21. P1 22. VS 23. BACK PRESSURE

30 % 35 % 85 % 70 % 10 kgf

BARREL TEMPERATURE (± 10) °C

NOZZLE

Set 280 °C

Act 280 °C

FRONT

Set 290 °C

Act 290 °C

MIDDLE

Set 280 °C

Act 280 °C

REAR

Set 275 °C

Act 275 °C

< OPEN CLOSE >

1. HI MILD CLS V 2. CLAMP SLOW V 3. LOW MLD CLS P 3. HI MLD CLS P

25 % 20 % 10 % 85 %

5. OPEN SLOW 6. HI MLD OPEN V 7. PRI OPEN V 8 PRI OPEN TM

15 % 20 % 15 % 0,2 %

< EJECTOR >

1. EJECT PRES 2. FWD EV1 3. COUNT 4. START TM

- % 20 % 1 % 0,2 %

5. MOMENT STOP 6. BWD EV 4 7. BWD PRES 8. STOP TM

1ST LAST 20 % - % 0,2 %

9. REPEAT EJECT EV 3

- %

FEEDER TEMPERATURE (± 10) °C

°C

Limit Switch			Rev.No	Date	Description	Prod	PE	QC
LS 5	Eject forward stop	mm	△					
LS 14	Eject backward stop	mm						
LS 3	High Pressure Selection	mm	△					
LS 2	Low pressure mold clamping	mm						
LS 8	Mold opening slow down	mm	△					
LS 4	Mold opening stop	mm						

INJECTION MOLDING CONDITION STANDARD

* DATA STATISTIC

[illegible]

✓	ROBOT RUNNER SETTING	
✓	RE- TRACK	
	USE ROBOT RUNNER	
	NOT USE ROBOT RUNNER	
	RE- TRACK	
	NO RE-TRACK	
	EJECTOR OPERATING	
	NORMAL	☐ OVERVERRIDE
	MONITOR	
	COUNTER	
	NOZZLE NOT LEAKING	

NOTE : TO MOLD --> FULL MTC

	Kg
--	----