

Attn :

Issue date	30-Jul-26
------------	-----------

Part No	7P925-X7502
---------	-------------

Part Name	PROTECTOR UPR RAIL
-----------	--------------------

Material Used	PP AP03B + MB 707 B8 PLAST 2% BLACK
---------------	-------------------------------------

	KNOWN	APPROVED	CHECKED	PREPARED
	 (Mgr. PE)	 AGREP-G	 R22a	 AGREP-H

TRIAL ITEM

PURPOSE

☒ New Molding	☒ Material
☐ Modification	☐ Setting Condition
☐ Repair	☐ Others

CHANGE MATERIAL

JUDGEMENT

OK



Comment:

~ PART WEIGHT

CAV 1 : 1.930 g	CAV 5 : 1.944 g
CAV2 : 1.928 g	CAV 6 : 1.936 g
CAV 3 : 1.932 g	CAV 7 : 1.934 g
CAV 4 : 1.935 g	CAV 8 : 1.939 g

~BEFORE : AP APG20 P3S JN3699P BLACK

~AFTER : PP AP03B + MB 707 R8 PLAST 2%
BLACK

GENERAL TOLERANCE

Note : ● : Under ● Trial
 ● : Over ○ Sample

DIMENSION CHECK

BEFORE CHANGE MATERIAL

				Table 1																	
No		Spec		Equipment	1	JUDG	2	JUDG	3	JUDG	4	JUDG	5	JUDG	6	JUDG	7	JUDG	8	JUDG	
1		18,40	+ _{0,2} - _{0,2}	CALIPER	18,54	OK	18,53	OK	18,52	OK	18,51	OK	18,54	OK	18,54	OK	18,53	OK	18,51	OK	
2		1,80	+ ₀ - _{0,2}	CALIPER	1,78	OK	1,80	OK	1,76	OK	1,79	OK	1,77	OK	1,79	OK	1,79	OK	1,76	OK	
3		9,0	+ _{0,3} - ₀	CALIPER	9,08	OK	9,08	OK	9,07	OK	9,08	OK	9,08	OK	9,08	OK	9,06	OK	9,05	OK	
4		1,80	+ ₀ - _{0,2}	CALIPER	1,79	OK	1,79	OK	1,76	OK	1,79	OK	1,78	OK	1,79	OK	1,79	OK	1,76	OK	
5		6,80	+ _{0,2} - ₀	VMS	6,904	OK	6,914	OK	6,844	OK	6,855	OK	6,886	OK	6,894	OK	6,912	OK	6,815	OK	
6		5,0	+ _{0,2} - ₀	CALIPER	5,03	OK	5,04	OK	5,05	OK	5,03	OK	5,04	OK	5,03	OK	5,04	OK	5,04	OK	
7		15,50	+ _{0,3} - _{0,3}	VMS	15,701	OK	15,604	OK	15,698	OK	15,633	OK	15,684	OK	15,712	OK	15,684	OK	15,694	OK	
8		18,70	+ _{0,3} - _{0,3}	VMS	18,886	OK	18,828	OK	18,876	OK	18,891	OK	18,912	OK	18,834	OK	18,887	OK	18,928	OK	

AFTER CHANGE MATERIAL

[illegible]

APPEARANCE CHECK

[illegible]

FM. EG. C03-007 (Rev.1 to 30 Nov 2021)

	: Spec Minim		: Spec Max
--	--------------	--	------------

INITIAL POINT : O : OK X : NG