

PT. IMC TEKNO INDONESIA

INJECTION MOLDING CONDITION STANDARD

QUALITY CONTROL	ENGINEERING	PRODUCTION	PREPARED BY
			NURRONI

DATE : 27 JULI 2026

STATUS : ☒ TRIAL ☐ MASS PRO

PART NAME : PROTECTOR UPPER RAIL

PART NO. : 409259-0035-RA8

CUSTOMER : PT. TOYOTA BOSHOKU

INJECTION MACHINE

MC no/Ton.: 05/110T SCREW Ø : 36 mm

MODEL : FN2000-18A

CONTROLLER : NC 9000

MATERIAL

NAME : PP

GRADE : AP03B + MB 707 R8

COLOUR : BLACK

DRY UP TM : 2 H

DRY UP TMP : 80 °C

REGRIND : - %

MASTER BATCH : 2 %

PART

CAVITY : 8/8

TOTAL WEIGHT : 23,283 g

PART WEIGHT : ☒ 1 1,930 g ☒ 3 1,932 g ☒ 5 1,944 g ☒ 7 1,934 g

RUNNER WEIGHT : 7,805 g

ANNEALING STANDARD :

2 1,928 g 4 1,935 g 6 1,936 g 8 1,939 g

MOLD

MTC SETTING : - °C

MTC ACTUAL TEMP. : - °C

CHILLER TMP : °C

MOLD ACTUAL TEMPERATURE (± 5) °C

CAVITY SIDE : 35 °C

CORE SIDE : 35 °C

< INJ / MTG >

1. INJ TM 2. COOL TM 3. CYC ST TM 4. MTG ST. TM 5. NOZZLE BWD TM

3 sec 15 sec 0,2 sec - sec - sec

6. V5 7. V4 8. V3 9. V2 10. V1

10 % 15 % 20 % 25 % 30 %

11. TP2 12. S5 13. S4 14. S3 15. S2 16. S1 17. SM 18. SD

1 sec 8 mm 10 mm 15 mm 20 mm 30 mm 35 mm 5 mm

19. P3 20. P2 21. P1 22. VS 23. BACK PRESSURE

15 % 20 % 65 % 75 % 10 kgf

BARREL TEMPERATURE (± 10) °C

NOZZLE

Set 190 °C

Act 190 °C

FRONT

Set 200 °C

Act 200 °C

MIDDLE

Set 190 °C

Act 190 °C

REAR

Set 185 °C

Act 185 °C

< OPEN CLOSE >

1. HI MILD CLS V 2. CLAMP SLOW V 3. LOW MLD CLS P 3. HI MLD CLS P

25 % 20 % 10 % 95 %

5. OPEN SLOW 6. HI MLD OPEN V 7. PRI OPEN V 8 PRI OPEN TM

15 % 25 % 15 % 0,2 %

< EJECTOR >

1. EJECT PRES 2. FWD EV1 3. COUNT 4. START TM

45 % 35 % 2 % 0,2 %

5. MOMENT STOP 6. BWD EV 4 7. BWD PRES 8. STOP TM

1ST LAST 55 % 55 % - %

9. REPEAT EJECT EV 3

65 %

FEEDER TEMPERATURE (± 10) °C

°C

Limit Switch			Rev.No	Date	Description	Prod	PE	QC
LS 5	Eject forward stop	mm	△					
LS 14	Eject backward stop	mm						
LS 3	High Pressure Selection	mm	△					
LS 2	Low pressure mold clamping	mm						
LS 8	Mold opening slow down	mm	△					
LS 4	Mold opening stop	mm						

INJECTION MOLDING CONDITION STANDARD

*Referensi Pengisian Std. & Act. MCS

✓ ROBOT RUNNER SETTING

v	RE- TRACK
---	-----------

[illegible]

	USE ROBOT RUNNER	
	NOT USE ROBOT RUNNER	
	RE- TRACK	
	NO RE-TRACK	
	EJECTOR OPERATING	
	NORMAL	☐ OVERRIDE
	MONITOR	
	COUNTER	
	NOZZLE NOT LEAKING	

FLOW COOLING SYSTEM

This image shows a full page of blank, lined paper. It features approximately 20 evenly spaced horizontal grey lines across its entire width, providing a template for handwriting practice or general note-taking. The margins are consistent on all sides.

LIMIT MATERIAL STAY IN HOPPER

	Kg
--	----