

PT IMC TEKNO INDONESIA INJECTION MOLDING CONDITION STANDARD				Quality Control	Engineering	Production	Prepared By																																				
							SUDIN K																																				
Date : 26-Mei-26 Status : ☐ TRIAL ☒ MASS PRO Part Name : CASE NO.2 TL.2 Mold Code : ADD 87 Part No : 1411-06440-B Customer : PT. AISAN Mc No/Ton : 20/50T		Material : PBT DURANEX Grade : 330HR Dry Temp : 12 °C Time : 4 Hrs Colour : ORANGE Master Batch : - Regrind : -		Part Weight : <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td>●</td><td>3,199 g</td><td></td><td></td><td>g</td></tr> <tr><td>●●</td><td>3,193 g</td><td></td><td></td><td>g</td></tr> <tr><td>●●●</td><td>3,196 g</td><td></td><td></td><td>g</td></tr> <tr><td>●●●●</td><td>3,194 g</td><td></td><td></td><td>g</td></tr> </table>				●	3,199 g			g	●●	3,193 g			g	●●●	3,196 g			g	●●●●	3,194 g			g																
●	3,199 g			g																																							
●●	3,193 g			g																																							
●●●	3,196 g			g																																							
●●●●	3,194 g			g																																							
		Runner Weight : 3,260 g Total Weight : 16,042 g Cavity : <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="height: 20px;"></td></tr> </table>																																									
MTC SETTING : 80 °C		MTC ACTUAL TEMP. : 80 °C		CHILLER TMP : - °C																																							
MOLD ACTUAL TEMPERATURE : - (± 5) °C		CAVITY SIDE : 78 °C		CORE SIDE : 75 °C																																							
CLAMP																																											
Mold Open Open / close speed Standart <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td style="width: 25%;">Limit</td> <td style="width: 25%;">2nd</td> <td style="width: 25%;">1st</td> <td style="width: 25%;"></td> </tr> <tr> <td>220</td> <td>120</td> <td>10</td> <td>mm</td> </tr> <tr> <td>Velocity</td> <td>20</td> <td>15</td> <td>10 %</td> </tr> </table>				Limit	2nd	1st		220	120	10	mm	Velocity	20	15	10 %	Mold clamp <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td style="width: 25%;">1st</td> <td style="width: 25%;">2nd</td> <td style="width: 25%;">Mold Clamp</td> <td style="width: 25%;"></td> </tr> <tr> <td>128</td> <td>10</td> <td>1,35</td> <td>mm</td> </tr> <tr> <td>Pos vel.</td> <td>25</td> <td>20</td> <td>15 %</td> </tr> </table>				1st	2nd	Mold Clamp		128	10	1,35	mm	Pos vel.	25	20	15 %												
Limit	2nd	1st																																									
220	120	10	mm																																								
Velocity	20	15	10 %																																								
1st	2nd	Mold Clamp																																									
128	10	1,35	mm																																								
Pos vel.	25	20	15 %																																								
EJECTOR Interval sec Mode Normal Ej.count 2 cnt				Retract <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td style="width: 50%;">POSITION</td> <td style="width: 50%;">1 sec</td> </tr> <tr> <td>Velocity</td> <td>50 %</td> </tr> </table>				POSITION	1 sec	Velocity	50 %																																
POSITION	1 sec																																										
Velocity	50 %																																										
Step 1 Pos 10 Vel 20				Eject <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr><td style="width: 50%;">36 mm</td></tr> <tr><td style="width: 50%;">37,5 %</td></tr> </table>				36 mm	37,5 %																																		
36 mm																																											
37,5 %																																											
INJECTION																																											
Hold press Velocity 10 <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td style="width: 25%;">4th</td> <td style="width: 25%;">3rd</td> <td style="width: 25%;">2nd</td> <td style="width: 25%;">1st</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> <td>5,5</td> </tr> <tr> <td>Time</td> <td>-</td> <td>-</td> <td>435</td> </tr> <tr> <td>Pres.</td> <td>-</td> <td>-</td> <td>Mpa</td> </tr> </table>				4th	3rd	2nd	1st	-	-	-	5,5	Time	-	-	435	Pres.	-	-	Mpa	No. of Stages 5V-4P Filling Time 6,5 sec Filling Press. 1800 Filling Mpa <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td style="width: 20%;">5th</td> <td style="width: 20%;">4th</td> <td style="width: 20%;">3rd</td> <td style="width: 20%;">2nd</td> <td style="width: 20%;">1st</td> </tr> <tr> <td>7,5</td> <td>12</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Post vel.</td> <td>30</td> <td>40</td> <td>50</td> <td>50</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>mm/s</td> </tr> </table>				5th	4th	3rd	2nd	1st	7,5	12	20	20	20	Post vel.	30	40	50	50					mm/s
4th	3rd	2nd	1st																																								
-	-	-	5,5																																								
Time	-	-	435																																								
Pres.	-	-	Mpa																																								
5th	4th	3rd	2nd	1st																																							
7,5	12	20	20	20																																							
Post vel.	30	40	50	50																																							
				mm/s																																							
Cooling 8 sec Interval 1 sec				Switch Action Mode Remove <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr><td style="width: 50%;">POSITION</td></tr> <tr><td style="width: 50%;">NORMAL</td></tr> <tr><td style="width: 50%;">STANDART</td></tr> <tr><td style="width: 50%;">POSITION</td></tr> </table>				POSITION	NORMAL	STANDART	POSITION																																
POSITION																																											
NORMAL																																											
STANDART																																											
POSITION																																											
Pull back <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td>- mm</td></tr> <tr><td>25 mm/sec</td></tr> </table>				- mm	25 mm/sec	Slow down Plast <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td style="width: 25%;">18</td> <td style="width: 25%;">26</td> <td style="width: 25%;"></td> <td style="width: 25%;"></td> </tr> <tr> <td>-</td> <td>100</td> <td>0</td> <td>Mpa</td> </tr> <tr> <td>-</td> <td>120</td> <td>50</td> <td>rpm</td> </tr> </table>				18	26			-	100	0	Mpa	-	120	50	rpm																						
- mm																																											
25 mm/sec																																											
18	26																																										
-	100	0	Mpa																																								
-	120	50	rpm																																								
pos Back Press. Rev.				Pull Back Plast <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr><td style="width: 50%;">3 mm</td></tr> <tr><td style="width: 50%;">25 mm/sec</td></tr> <tr><td style="width: 50%;">Delay -</td></tr> </table>				3 mm	25 mm/sec	Delay -																																	
3 mm																																											
25 mm/sec																																											
Delay -																																											
TEMPERATURE																																											
Melt Proces Lowerd Supervision range ± Heater ON/OFF <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr><td style="width: 25%;">15</td></tr> <tr><td style="width: 25%;">5</td></tr> <tr><td style="width: 25%;">4</td></tr> <tr><td style="width: 25%;">ZONE</td></tr> <tr><td style="width: 25%;">3</td></tr> <tr><td style="width: 25%;">2</td></tr> <tr><td style="width: 25%;">1</td></tr> </table>				15	5	4	ZONE	3	2	1	Water <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr><td style="width: 25%;">250</td></tr> <tr><td style="width: 25%;">245</td></tr> <tr><td style="width: 25%;">-</td></tr> <tr><td style="width: 25%;">10</td></tr> <tr><td style="width: 25%;">10</td></tr> <tr><td style="width: 25%;">ON</td></tr> <tr><td style="width: 25%;">ON</td></tr> <tr><td style="width: 25%;">ON</td></tr> <tr><td style="width: 25%;">ON</td></tr> </table>				250	245	-	10	10	ON	ON	ON	ON																				
15																																											
5																																											
4																																											
ZONE																																											
3																																											
2																																											
1																																											
250																																											
245																																											
-																																											
10																																											
10																																											
ON																																											
ON																																											
ON																																											
ON																																											
screw interlock 15 min				Abnormal heater process LOWERED TEMPERATURE																																							
SET UP																																											
Resin change Screw Nozzle 28 OPEN				Hold Pressure Time 2 sec Pos 1 mm Pres. 20 Mpa vel. 30 mm/sec																																							
				Filling Pos 3 32 mm Back pres ref 5 Mpa 10 rpm																																							
Pull back 3 32 mm Back pres ref 5 Mpa 10 rpm				Plast Pos 3 32 mm Back pres ref 5 Mpa 10 rpm																																							
Clamp force 48 mold space mm				Purge mode Auto purge No. ofshots ON 5 Purge plast alarm time shots ON 60 sec																																							

PT. IMC TEKNO INDONESIA
INJECTION MOLDING CONDITION STANDARD

*Referensi Pengisian Std. & Act. MCS

* DATA STATISTIC

NO	DESCRIPTION		UNIT	STD	TOLERANSI
	TEMPERATURE				
01 a	Zone 15		°C	-	±10
b	Zone 5		°C	250	±10
c	Zone 4		°C	245	±10
d	Zone 3		°C	-	±10
e	Zone 2		°C	240	±10
f	Zone 1		°C	235	±10
	Mold Temperature				
02	Core		°C	75	±5
03	Cavity		°C	78	±5
04	MTC		°C	80	±10
	INJECTION				
05 a	Filling Press		Mpa	1800	±10
06 a	Velocity	1st	%	50	±10
b		2nd	%	50	±10
c		3rd	%	50	±10
d		4th	%	40	±10
e		5th	%	30	±10
07 a	Injection Stroke	1st	mm	20	±10
b		2nd	mm	20	±10
c		3rd	mm	20	±10
d		4th	mm	12	±10
e		5th	mm	7,5	±10
	HOLDING				
08 a	Press	1st	Mpa	435	±10
b		2nd	Mpa	-	±10
c		3rd	Mpa	-	±10
d		4th	Mpa	-	±10
09 a	Time	1st	sec	5,5	±10
b		2nd	sec	-	±10
c		3rd	sec	-	±10
d		4th	sec	-	±10
10	Cooling Time		sec	8	±0
	Material Stroke				
11 a	Position	1st	mm	18	±10
b		2nd	mm	26	±10
c		1st	Mpa	100	±10
d		2nd	Mpa	0	±10
12	Plast		mm	26	±5
13	Pull Back		mm	3	±5
	HOPPER DRYER				
14	TEMPERATURE		°C	120	±10
	PART				
15	Cav.No		Pcs	4/4	
16	Part Weight / Shoot		Gr	12,782	
17	Runner Weight / Shoot		Gr	3,260	
18	Total Weight / Shoot		Gr	16,042	

[illegible]

FLOW COOLING SYSTEM

	ROBOT RUNNER SETTING	
	RE- TRACK	
	USE ROBOT RUNNER	
	NOT USE ROBOT RUNNER	
	RE- TRACK	
	NO RE-TRACK	
	EJECTOR OPERATING	
	NORMAL	VERRIDE
	MONITOR	
	COUNTER	
	NOZZLE NOT LEAKING	

LIMIT MATERIAL STAY IN HOPPER

	Kg/Jam
--	--------

KOSUME MATERIAL/JAM

	Kg/Jam
--	--------