

PT. IMC TEKNO INDONESIA

INJECTION MOLDING CONDITION STANDARD

QUALITY CONTROL	ENGINEERING	PRODUCTION	PREPARED BY
ALREADY SIGN			
WAHYU J			SUDIN K

DATE : 25 MEI 2026

STATUS : ☒ TRIAL ☐ MASS PRO

PART NAME : PRIMARY BOBBIN TL.2

PART NO. : T0323169-D

CUSTOMER : PT. DIAMOND ELECTRIC INDONESIA

INJECTION MACHINE

MC no/Ton.: 37/80T SCREW Ø: 36 mm

MODEL : FE80S12ASE

CONTROLLER : NC 9000

MATERIAL

NAME : PPE SABIC	GRADE : IGN320-GY3381	COLOUR : GREY
DRY UP TM : 4 H	DRY UP TMP : 120 °C	REGRIND : - %
MASTER BATCH : - %		

PART

CAVITY : 4/4	TOTAL WEIGHT : 22,419 g
PART WEIGHT : ☒ 21 2,478 g ☒ 23 2,473 g ☐ g ☐ g	RUNNER WEIGHT : 12,526 g
: ☒ 22 2,478 g ☒ 24 2,464 g ☐ g ☐ g	ANNEALING STANDARD :

MOLD

MTC SETTING : 70 °C	MTC ACTUAL TEMP. : 70 °C	CHILLER TMP : °C
MOLD ACTUAL TEMPERATURE (± 5) °C	CAVITY SIDE : 68 °C	CORE SIDE : 60 °C

< INJ / MTG >

1. INJ TM 6 sec	2. COOL TM 20 sec	3. CYC ST TM 0,2 sec	4. MTG ST. TM - sec	5. NOZZLE BWD TM - sec			
6. V5 45 %	7. V4 60 %	8. V3 80 %	9. V2 - %	10. V1 - %			
11. TP2 1 sec	12. S5 8 mm	13. S4 20 mm	14. S3 30 mm	15. S2 - mm	16. S1 - mm	17. SM 38 mm	18. SD 5 mm
	19. P3 25 %	20. P2 35 %	21. P1 80 %	22. VS 65 %	23. BACK PRESSURE 15 kgf		

BARREL TEMPERATURE (± 10) °C

NOZZLE

Set 325 °C

Act 325 °C

FRONT

Set 335 °C

Act 337 °C

MIDDLE

Set 320 °C

Act 320 °C

REAR

Set 310 °C

Act 312 °C

< OPEN CLOSE >

1. HI MILD CLS V 25 %	2. CLAMP SLOW V 20 %	3. LOW MLD CLS P 15 %	3. HI MLD CLS P 95 %
5. OPEN SLOW 20 %	6. HI MLD OPEN V 25 %	7. PRI OPEN V 20 %	8 PRI OPEN TM 0,2 %

< EJECTOR >

1. EJECT PRES - %	2. FWD EV1 25 %	3. COUNT 3 %	4. START TM 0,2 %
5. MOMENT STOP 1ST LAST	6. BWD EV 4 - %	7. BWD PRES 20 %	8. STOP TM 0,2 %
9. REPEAT EJECT EV 3 - %			

FEEDER TEMPERATURE (± 10) °C

°C

Limit Switch			Rev.No	Date	Description	Prod	PE	QC
LS 5	Eject forward stop	mm	△					
LS 14	Eject backward stop	mm						
LS 3	High Pressure Selection	mm	△					
LS 2	Low pressure mold clamping	mm						
LS 8	Mold opening slow down	mm	△					
LS 4	Mold opening stop	291,5 mm						

INJECTION MOLDING CONDITION STANDARD

*Referensi Pengisian Std. & Act. MCS

√ ROBOT RUNNER SETTING

v	RE- TRACK
---	-----------

[illegible]

	USE ROBOT RUNNER	
	NOT USE ROBOT RUNNER	
	RE- TRACK	
	NO RE-TRACK	
	EJECTOR OPERATING	
	NORMAL	☐ OVERRIDE
	MONITOR	
	COUNTER	
	NOZZLE NOT LEAKING	

FLOW COOLING SYSTEM

This image shows a full page of blank, lined paper. It features approximately 20 evenly spaced horizontal black lines across the entire width of the page, typical of notebook or legal stationery. The margins are consistent on all sides, and there is no handwriting or other markings present.

LIMIT MATERIAL STAY IN HOPPER

	Kg
--	----