

PT. IMC TEKNO INDONESIA  
INJECTION MOLDING CONDITION STANDARD

|                 |             |            |                                   |
|-----------------|-------------|------------|-----------------------------------|
| QUALITY CONTROL | ENGINEERING | PRODUCTION | PREPARED BY<br><div>SUDIN K</div> |
|-----------------|-------------|------------|-----------------------------------|

DATE : 21 MEI 2026

STATUS : ☐ TRIAL ☒ MASSPRO

PART NAME : BOBBIN

PART NO. : 819AP30B0

CUSTOMER : PT. YASUNAGA

INJECTION MACHINE

MC no/Ton.: 50/180T SCREW Ø : 50      MODEL : FN4000-50A      CONTROLLER : TACT

MATERIAL

|                     |                    |                  |
|---------------------|--------------------|------------------|
| NAME : PBT TORAYCON | GRADE : 1101 G30   | COLOUR : NATURAL |
| DRYUP TM : 4 H      | DRYUP TMP : 120 °C | REGRIND : - %    |
| MASTER BATCH : - %  |                    |                  |

PART

|                                                 |                          |
|-------------------------------------------------|--------------------------|
| CAVITY : 2/2                                    | TOTAL WEIGHT : 41,507 gr |
| PART WEIGHT : ① 18,563 gr <input type="radio"/> | RUNNER WEIGHT : 4,486 gr |
| (± 0.15 gr) : ② 18,485 gr <input type="radio"/> | ANNEALING STANDARD : -   |

MOLD

|                                 |                        |                    |
|---------------------------------|------------------------|--------------------|
| MTC SET : - °C                  | MTC ACTUAL TEMP : - °C | CHILLER TMP : - °C |
| MOLD ACTUAL TEMPERATURE (± 5°C) | CAV.SIDE : 35 °C       | CORE SIDE : 35 °C  |

MAIN DATA

|                                                                                                                                                                    |                                                                                                                                                                                                                                                                       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div>INJ TM</div> <div>INJECT 4 sec</div> <div>COOL 20 sec</div> <div>CYC START 0,2 sec</div> <div>MTG START TM - sec</div>                                        | <div>V6 - %</div> <div>V5 5 %</div> <div>V4 20 %</div> <div>V3 25 %</div> <div>V2 30 %</div> <div>V1 15 %</div> <div>5 Step</div> <div>SV5 - mm</div> <div>SV4 10 mm</div> <div>SV3 12 mm</div> <div>SV2 15 mm</div> <div>SV1 20 mm</div> <div>SM 25 mm</div>         |
| <div>CLOSE</div> <div>HI V 25 %</div> <div>LOW V 20 %</div> <div>L V L P 100 mm</div> <div>H P CL 1,60 mm</div> <div>LOW P 15 %</div> <div>HI P 95 KN</div>        | <div>HOLD</div> <div>Pp3 - %</div> <div>Pp2 30 %</div> <div>Pp1 40 %</div> <div>TP2 -</div> <div>TP1 1 s</div> <div>2 Step</div> <div>PRESSURE</div> <div>PV3 - %</div> <div>PV2 - %</div> <div>PV1 60 %</div> <div>Sp2 -</div> <div>Sp1 - mm</div> <div>1 Step</div> |
| <div>OPEN</div> <div>OPEN END V 20 %</div> <div>HI V1 25 %</div> <div>OPN ST 15 %</div> <div>OPN STP 195 mm</div> <div>SLW DSTNC 80 mm</div> <div>HI V 50 mm</div> | <div>10 %</div> <div>60 rpm</div> <div>PB1 V-P CHG</div> <div>VS1</div> <div>POS 8 mm</div> <div>Decomp V 5</div> <div>Decomp Before MTG</div> <div>SD 5 mm</div> <div>Stroke -</div>                                                                                 |

|                                                                                                                                                                                                                |            |         |          |         |         |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|---------|----------|---------|---------|
| <div>EJECT</div> <div>PATTERN 1</div> <div>FWD EV1 40 %</div> <div>FWD STOP 70 mm</div> <div>EJT TMG -</div> <div>STOP TM -</div>                                                                              | ( ± 10 )°C | * FRONT | * MIDDLE | * REAR1 | * REAR2 |
| <div>TEMP</div> <div>NOZZLE</div> <div>Setting 260 °C</div> <div>Actual 260 °C</div> <div>* HEAD - °C</div> <div>* FRONT 255 °C</div> <div>* MIDDLE 250 °C</div> <div>* REAR 245 °C</div> <div>FEED - °C</div> |            |         |          |         |         |

| Limit Switch | Rev. No                    | Date | Description | Prod | PE | QC |
|--------------|----------------------------|------|-------------|------|----|----|
| LS 5         | Eject forward stop         | mm   | △           |      |    |    |
| LS 14        | Eject backward stop        | mm   |             |      |    |    |
| LS 3         | High Pressure Selection    | mm   | △           |      |    |    |
| LS 2         | Low pressure mold clamping | mm   |             |      |    |    |
| LS 8         | Mold opening slow down     | mm   | △           |      |    |    |
| LS 4         | Mold opening stop          | mm   |             |      |    |    |

## INJECTION MOLDING CONDITION STANDARD

\*Referensi Pengisian Std. & Act. MCS

## \* DATA STATISTIC

[illegible]

## FLOW COOLING SYSTEM

|   |                      |                                   |
|---|----------------------|-----------------------------------|
| ✓ | ROBOT RUNNER SETTING |                                   |
| ✓ | RE- TRACK            |                                   |
|   | USE ROBOT RUNNER     |                                   |
|   | NOT USE ROBOT RUNNER |                                   |
|   | RE- TRACK            |                                   |
|   | NO RE-TRACK          |                                   |
|   | EJECTOR OPERATING    |                                   |
|   | NORMAL               | <input type="checkbox"/> OVERRIDE |
|   | MONITOR              |                                   |
|   | COUNTER              |                                   |
|   | NOZZLE NOT LEAKING   |                                   |

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

### LIMIT MATERIAL STAY IN HOPPER

|   |    |
|---|----|
| 0 | Kg |
|---|----|