

PT. IMC TEKNO INDONESIA

INJECTION MOLDING CONDITION STANDARD

QUALITY CONTROL	ENGINEERING	PRODUCTION	PREPARED BY
			NURRONI

DATE : 26 MEI 2026

STATUS : ☐ TRIAL ☒ MASS PRO

PART NAME : COVER SHOULDER BELT ANCHOR TL.2

PART NO. : 5071248

CUSTOMER ; PT. AUTOLIV INDONESIA

INJECTION MACHINE

MC no/Ton.: 03/80T SCREW Ø: 45 mm

MODEL : FE80S18ASE

CONTROLLER : NC 9000

MATERIAL

NAME : PP TRILENEN

GRADE : HI 10 H0 + MB 707 R8

COLOUR : BLACK

DRY UP TM : 3 H

DRY UP TMP : °C

REGRIND : - %

MASTER BATCH : 2 %

PART

CAVITY : 2/2

TOTAL WEIGHT : 15,880 g

PART WEIGHT : 3 6,789 g

RUNNER WEIGHT : 2,456 g

ANNEALING STANDARD :

4 6,635 g

MOLD

MTC SETTING : 50 °C

MTC ACTUAL TEMP. : 50 °C

CHILLER TMP : °C

MOLD ACTUAL TEMPERATURE (± 5) °C

CAVITY SIDE : 50 °C

CORE SIDE : 48 °C

< INJ / MTG >

1. INJ TM 2. COOL TM 3. CYC ST TM 4. MTG ST. TM 5. NOZZLE BWD TM

5 sec 10 sec 0,2 sec 3 sec - sec

6. V5 7. V4 8. V3 9. V2 10. V1

10 % 15 % 10 % 8 % 8 %

11. TP2 12. S5 13. S4 14. S3 15. S2 16. S1 17. SM 18. SD

1 sec 7 mm 10 mm 12 mm 15 mm 23 mm 25 mm 3 mm

19. P3 20. P2 21. P1 22. VS 23. BACK PRESSURE

30 % 55 % 85 % 85 % 10 kgf

BARREL TEMPERATURE (± 10) °C

NOZZLE

Set 185 °C

Act 185 °C

FRONT

Set 200 °C

Act 200 °C

MIDDLE

Set 190 °C

Act 190 °C

REAR

Set 185 °C

Act 185 °C

< OPEN CLOSE >

1. HI MILD CLS V 2. CLAMP SLOW V 3. LOW MLD CLS P 3. HI MLD CLS P

25 % 25 % 20 % 85 %

5. OPEN SLOW 6. HI MLD OPEN V 7. PRI OPEN V 8 PRI OPEN TM

25 % 45 % 25 % 0,2 %

< EJECTOR >

1. EJECT PRES 2. FWD EV1 3. COUNT 4. START TM

45 % 35 % 1 % 0,2 %

5. MOMENT STOP 6. BWD EV 4 7. BWD PRES 8. STOP TM

1ST LAST 50 % 50 % 0,1 %

9. REPEAT EJECT EV 3

45 %

FEEDER TEMPERATURE (± 10) °C

°C

Limit Switch			Rev.No	Date	Description	Prod	PE	QC
LS 5	Eject forward stop	mm	△					
LS 14	Eject backward stop	mm						
LS 3	High Pressure Selection	mm	△					
LS 2	Low pressure mold clamping	mm						
LS 8	Mold opening slow down	mm	△					
LS 4	Mold opening stop	mm						

INJECTION MOLDING CONDITION STANDARD

*Referensi Pengisian Std. & Act. MCS

✓	ROBOT RUNNER SETTING	
✓	RE- TRACK	
	USE ROBOT RUNNER	
	NOT USE ROBOT RUNNER	
	RE- TRACK	
	NO RE-TRACK	
	EJECTOR OPERATING	
	NORMAL	☐ OVERRIDE
	MONITOR	
	COUNTER	
	NOZZLE NOT LEAKING	

[illegible]

FLOW COOLING SYSTEM

This image shows a full page of blank, lined paper. It features approximately 20 horizontal blue or grey lines spaced evenly apart, typical of notebook paper. The lines extend across the entire width of the page, leaving small margins at the top and bottom. There are no vertical lines, text, or other markings on the page.

LIMIT MATERIAL STAY IN HOPPER

	Kg
--	----