

PT. IMC TEKNO INDONESIA

INJECTION MOLDING CONDITION STANDARD

QUALITY CONTROL	ENGINEERING	PRODUCTION	PREPARED BY
ALREADY SIGN			
WAHYU J			ENDANG S

DATE : 02 JUNI 2026

STATUS : TRIAL V MASS PRO

PART NAME : SECONDARY BOBBIN TL.4 (FK0478)

PART NO. : T0323080-M

CUSTOMER : PT. DIAMOND ELECTRIC INDONESIA

INJECTION MACHINE

MC no/Ton.: 31/110T SCREW Ø: 45 mm

MODEL : FN2000-25A

CONTROLLER : NC 9000

MATERIAL

NAME : PPE IUPIACE	GRADE : GH20-9801H	COLOUR : GREY
DRY UP TM : 4 H	DRY UP TMP : 120 °C	REGRIND : - %
MASTER BATCH : - %		

PART

CAVITY : 4/4	TOTAL WEIGHT : 31,738 g
PART WEIGHT : 41 3,270 g 43 3,271 g	RUNNER WEIGHT : 18,650 g
: 42 3,275 g 44 3,272 g	ANNEALING STANDARD :

MOLD

HEATER SET : 70 °C	HEATER ACT TEMP. : 70 °C	CHILLER TMP : °C
MOLD ACTUAL TEMPERATURE (± 5) °C	CAVITY SIDE : 75 °C	CORE SIDE : 72 °C

< INJ / MTG >

1. INJ TM 8 sec	2. COOL TM 20 sec	3. CYC ST TM 0,3 sec	4. MTG ST. TM - sec	5. NOZZLE BWD TM - sec			
6. V5 35 %	7. V4 65 %	8. V3 75 %	9. V2 - %	10. V1 - %			
11. TP2 1 sec	12. S5 8 mm	13. S4 10 mm	14. S3 15 mm	15. S2 - mm	16. S1 - mm	17. SM 35 mm	18. SD 5 mm
	19. P3 25 %	20. P2 55 %	21. P1 85 %	22. VS 65 %	23. BACK PRESSURE 12 kgf		

BARREL TEMPERATURE (± 10) °C

NOZZLE

Set 310 °C

Act 309 °C

FRONT

Set 320 °C

Act 320 °C

MIDDLE

Set 320 °C

Act 320 °C

REAR

Set 295 °C

Act 295 °C

< OPEN CLOSE >

1. HI MILD CLS V 20 %	2. CLAMP SLOW V 25 %	3. LOW MLD CLS P 30 %	3. HI MLD CLS P 95 %
5. OPEN SLOW 20 %	6. HI MLD OPEN V 30 %	7. PRI OPEN V 20 %	8 PRI OPEN TM %

< EJECTOR >

1. EJECT PRES 20 %	2. FWD EV1 15 %	3. COUNT 3 %	4. START TM - %
5. MOMENT STOP 1ST LAST	6. BWD EV 4 55 %	7. BWD PRES 55 %	8. STOP TM 0,5 %
9. REPEAT EJECT EV 3 55 %			

FEEDER TEMPERATURE (± 10) °C

°C

Limit Switch			Rev.No	Date	Description	Prod	PE	QC
LS 5	Eject forward stop	mm	△					
LS 14	Eject backward stop	mm						
LS 3	High Pressure Selection	mm	△					
LS 2	Low pressure mold clamping	mm						
LS 8	Mold opening slow down	mm	△					
LS 4	Mold opening stop	mm						

INJECTION MOLDING CONDITION STANDARD

*Referensi Pengisian Std. & Act. MCS

✓ ROBOT RUNNER SETTING

v	RE- TRACK
---	-----------

[illegible]

	USE ROBOT RUNNER
	NOT USE ROBOT RUNNER
	RE- TRACK
	NO RE-TRACK
	EJECTOR OPERATING
	NORMAL ☐ OVERRIDE
	MONITOR
	COUNTER
	NOZZLE NOT LEAKING

FLOW COOLING SYSTEM

This image shows a full page of blank, lined paper. It features approximately 20 horizontal blue or grey lines spaced evenly apart, typical of notebook paper. The lines extend across the entire width of the page, leaving small margins at the top and bottom. There are no vertical lines, text, or other markings on the page.

LIMIT MATERIAL STAY IN HOPPER

	Kg
--	----