

PT. IMC TEKNO INDONESIA
INJECTION MOLDING CONDITION STANDARD

DATE : 13 MEI 2026
STATUS : ☒ TRIAL ☐ MASSPRO
PART NAME : SECONDARY BOBBIN TL.3 (FK0580)
PART NO. : T0323170D
CUSTOMER : PT. DIAMOND

QUALITY CONTROL	ENGINEERING	PRODUCTION	PREPARED BY
	WAHYU J		ENDANG S

INJECTION MACHINE

MC no/Ton.: 06/140T SCREW Ø : 45 MODEL : FN3000-25A CONTROLLER : TACT

MATERIAL

NAME : PPE SABIC GRADE : IGN320-GY3381 COLOUR : GREY
DRYUP TM : 4 H DRYUP TMP : 120 °C REGRIND : - %
MASTER BATCH : - %

PART

CAVITY : 4/4
PART WEIGHT : (31) 6,204 gr (33) 6,190 gr ☐ gr ☐ gr
(± 0.15 gr) : (32) 6,195 gr (34) 6,185 gr ☐ gr ☐ gr
TOTAL WEIGHT : 44,200 gr
RUNNER WEIGHT : 19,426 gr
ANNEALING STANDARD : -

MOLD

HEATER SET : 80 °C HEATER ACT TEMP : 80 °C CHILLER TMP : - °C
MOLD ACTUAL TEMPERATURE (± 5°C) CAV.SIDE : 78 °C CORE SIDE : 75 °C

MAIN DATA

INJ TM

INJECT 8 sec

COOL 25 sec

CYC START 0,2 sec

MTG START TM - sec

CLOSE

HI V 25 %

LOW V 15 %

L V L P 100 mm

H P CL 1,50 mm

LOW P 20 %

HI P 85 KN

OPEN

OPEN END V 25 %

HI V1 30 %

OPN ST 30 %

OPN STP 350 mm

SLW DSTNC 220 mm

HI V 15 mm

V6 - %

V5 - %

V4 - %

V3 55 %

V2 65 %

V1 75 %

3 Step

SV5 - mm

SV4 - mm

SV3 - mm

SV2 15 mm

SV1 25 mm

SM 46 mm

HOLD

Pp3 - %

Pp2 75 %

Pp1 55 %

TP2 -

TP1 - s

2 Step

15 %

75 rpm

PB1 V-P CHG

POS 6.5 mm

VS1

PRESSURE

PV3 - %

PV2 - %

PV1 85 %

Sp2 -

Sp1 - mm

1 Step

Decomp V

Decomp Before MTG -

SD 3 mm

Stroke -

EJECT

PATTERN 1

FWD EV1 55 %

FWD STOP 43 mm

EJT TMG -

STOP TM -

(± 10)°C

TEMP

NOZZLE

Setting 350 °C

Actual 350 °C

* FRONT

* HEAD - °C

* MIDDLE

* FRONT 325 °C

* MIDDLE 325 °C

* REAR1

* REAR 325 °C

* REAR2

* REAR 295 °C

FEED

- °C

INJECTION MOLDING CONDITION STANDARD

* DATA STATISTIC

[illegible]

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

✓	ROBOT RUNNER SETTING	
✓	RE- TRACK	
	USE ROBOT RUNNER	
	NOT USE ROBOT RUNNER	
	RE- TRACK	
	NO RE-TRACK	
	EJECTOR OPERATING	
	NORMAL	☐ OVERRIDE
	MONITOR	
	COUNTER	
	NOZZLE NOT LEAKING	

0	Kg
---	----