

PT. IMC TEKNO INDONESIA
INJECTION MOLDING CONDITION STANDARD

QUALITY CONTROL	ENGINEERING	PRODUCTION	PREPARED BY
ALREADY SIGN			
WAHYU J			NURRONI

DATE : 22 MEI 2026

STATUS : ☒ TRIAL ☐ MASSPRO

PART NAME : COVER FRAME FRONT

PART NO. : 1947756-00

CUSTOMER : PT. INDONESIA EPSON INDUSTRY

INJECTION MACHINE

MC no/Ton.: 21/110T SCREW Ø : 40 MODEL : FNX110 III-18A CONTROLLER : TACT

MATERIAL

NAME : PS-HI	GRADE : STYOLUTION PS 495F	COLOUR : EBCK
DRYUP TM : 4 H	DRYUP TMP : 90 °C	REGRIND : - %
MASTER BATCH : - %		

PART

CAVITY : 4/4	TOTAL WEIGHT : 58,249 gr
PART WEIGHT : ☒ 10,980 gr ☒ 11,017 gr ☐ ☐	RUNNER WEIGHT : 14,252 gr
(± 0.15 gr) : ☒ 10,980 gr ☒ 11,020 gr ☐ ☐	ANNEALING STANDARD : -

MOLD

MTC SET : 50 °C	MTC ACTUAL TEMP : 50 °C	CHILLER TMP : - °C
MOLD ACTUAL TEMPERATURE (± 5°C)	CAV.SIDE : 50 °C	CORE SIDE : 48 °C

MAIN DATA

INJ TM INJECT 4 sec COOL 10 sec CYC START 0,2 sec MTG START TM - sec		FILL V6 - % V5 - % V4 - % V3 20 % V2 30 % V1 45 % 3 Step SV5 - mm SV4 - mm SV3 - mm SV2 15 mm SV1 35 mm SM 56 mm					
CLOSE HI V 35 % LOW V 20 % L V L P 80 mm H P CL 1,00 mm LOW P 20 % HI P 9,8 KN		HOLD Pp3 - % Pp2 30 % Pp1 25 % TP2 - TP1 1 s 2 Step			PRESSURE PV3 - % PV2 - % PV1 65 % Sp2 - Sp1 - mm 1 Step		
OPEN OPEN END V 20 % HI V1 25 % OPN ST 20 % OPN STP 315 mm SLW DSTNC 25 mm HI V 10 mm		10 % 200 rpm PB1 V-P CHG POS 8 mm			Decomp V 20 Decomp Before MTG 20 SD 1 mm Stroke 0,5		

EJECT	PATTERN 1	FWD EV1 15 %	FWD STOP 35 mm	EJT TMG -	STOP TM -
(± 10)°C	* FRONT	* MIDDLE	* REAR1	* REAR2	
TEMP	NOZZLE	* HEAD	* FRONT	* MIDDLE	* REAR
Setting	225 °C	225 °C	230 °C	235 °C	225 °C
Actual	225 °C	225 °C	230 °C	235 °C	225 °C
					FEED 52,8 °C

Limit Switch		Rev. No	Date	Description	Prod	PE	QC
LS 5	Eject forward stop	mm	△				
LS 14	Eject backward stop	mm	△				
LS 3	High Pressure Selection	mm	△				
LS 2	Low pressure mold clamping	mm	△				
LS 8	Mold opening slow down	mm	△				
LS 4	Mold opening stop	mm	△				

INJECTION MOLDING CONDITION STANDARD

* DATA STATISTIC

[illegible]

✓	ROBOT RUNNER SETTING	
✓	RE- TRACK	
	USE ROBOT RUNNER	
	NOT USE ROBOT RUNNER	
	RE- TRACK	
	NO RE-TRACK	
	EJECTOR OPERATING	
	NORMAL	☐ OVERRIDE
	MONITOR	
	COUNTER	
	NOZZLE NOT LEAKING	

CAVITY

CORE

PLATE RUNNER

0	Kg
---	----