


- **(DFA)** $M = (Q, \Sigma, \delta, q_0, F)$, $\delta : Q \times \Sigma \rightarrow Q$.
- **(NFA)** $M = (Q, \Sigma, \delta, q_0, F)$, $\delta : Q \times \Sigma_\varepsilon \rightarrow \mathcal{P}(Q)$.
- **(GNFA)** $(Q, \Sigma, \delta, q_0, q_a)$,
 $\delta : (Q \setminus \{q_a\}) \times (Q \setminus \{q_{\text{start}}\}) \rightarrow \mathcal{R}$ (where
 $\mathcal{R} = \{\text{Regex over } \Sigma\}$)
- **(DFA \rightsquigarrow GNFA \rightsquigarrow Regex)**



- $\{w = a^{2^k}\}; \quad k = \lfloor \log_2 |w| \rfloor, s = a^{2^k} = xyz.$
 $2^k = |xyz| < |xy^2z| \leq |xyz| + |xy| \leq 2^k + p < 2^{k+1}.$
- $\{a^p : p \text{ is prime}\}; \quad s = a^t = xyz \text{ for prime } t \geq p.$
 $r := |y| > 0$
- $\{www : w \in \Sigma^*\}; s = a^p b a^p b a^p = xyz = a^{|x|+|y|+m} b a^p b a^p b$
 $, m \geq 0, \text{ but } xy^2z = a^{|x|+2|y|+m} b a^p b a^p b \notin L.$
- $\{a^{2^n} b^3 a^n\}; s = a^{2^p} b^3 a^p = xyz = a^{|x|+|y|+m} b^3 a^p a^p,$
 $m > 0, \text{ but } xy^2z = a^{2^p+|y|} b^3 a^p a^p \notin L.$

- (the following are **non-regular** but **CFL**)
- $\{w = w^R\}; \quad s = 0^p 10^p = xyz.$ then
 $xy^2z = 0^{p+|y|}10^p \notin L.$
- $\{a^n b^n\}; \quad s = a^p b^p = xyz,$ where $|y| > 0$ and $|xy| \leq p.$
Then $xy^2z = a^{p+|y|}b^p \notin L.$
- $\{w : \#_a(w) > \#_b(w)\}; s = a^p b^{p+1}, |s| = 2p + 1 > p.$

- $\{w = a^{2^k}\}; \quad k = \lfloor \log_2 |w| \rfloor, s = a^{2^k} = xyz.$
 $2^k = |xyz| < |xy^2z| \leq |xyz| + |xy| \leq 2^k + p < 2^{k+1}.$
- $\{a^p : p \text{ is prime}\}; \quad s = a^t = xyz \text{ for prime } t \geq p.$
 $r := |y| > 0$
- $\{www : w \in \Sigma^*\}; s = a^p b a^p b a^p = xyz = a^{|x|+|y|+m} b a^p b a^p b$
 $, m \geq 0, \text{ but } xy^2z = a^{|x|+2|y|+m} b a^p b a^p b \notin L.$
- $\{a^{2^n} b^3 a^n\}; s = a^{2^p} b^3 a^p = xyz = a^{|x|+|y|+m} b^3 a^p a^p,$
 $m > 0, \text{ but } xy^2z = a^{2^p+|y|} b^3 a^p a^p \notin L.$

- **(CFG \rightsquigarrow CNF) (1.)** Add a new start variable S_0 and a rule $S_0 \rightarrow S$. **(2.)** Remove ε -rules of the form $A \rightarrow \varepsilon$ (except for $S_0 \rightarrow \varepsilon$). and remove A 's occurrences on the RH of a rule (e.g.: $R \rightarrow uAvAw$ becomes $R \rightarrow uAvAw \mid uAvw \mid uvAw \mid uvw$, where $u, v, w \in (V \cup \Sigma)^*$). **(3.)** Remove unit rules $A \rightarrow B$ then whenever $B \rightarrow u$ appears, add $A \rightarrow u$, unless this was a unit rule previously removed. ($u \in (V \cup \Sigma)^*$). **(4.)** Replace each rule $A \rightarrow u_1u_2 \cdots u_k$ where $k \geq 3$ and $u_i \in (V \cup \Sigma)$, with the rules $A \rightarrow u_1A_1, A_1 \rightarrow u_2A_2, \dots,$

- For $i = 0, 1, \dots, m-1$, we have $(r_i, b) \in \delta(r_i, w_{i+1}, a)$, where $s_i = at$ and $s_{i+1} = bt$ for some $a, b \in \Gamma_\varepsilon$ and $t \in \Gamma^*$; (3.) $r_m \in F$.
- (PDA transition)** " $a, b \rightarrow c$ ": **reads** a from the input (or read nothing if $a = \varepsilon$). **pops** b from the stack (or pops nothing if $b = \varepsilon$). **pushes** c onto the stack (or pushes nothing if $c = \varepsilon$)
- $R \in \text{REG} \wedge C \in \text{CFL} \implies R \cap C \in \text{CFL}$. (pf. construct PDA $P' = P_C \times D_R$.)

- (the following are **CFL but non-regular**)
- $\{w : w = w^R\}; S \rightarrow aSa \mid bSb \mid a \mid b \mid \varepsilon$
- $\{w : w \neq w^R\}; S \rightarrow aSa \mid bSb \mid aXb \mid bXa;$
 $X \rightarrow aX \mid bX \mid \varepsilon$
- $\{ww^R\} = \{w : w = w^R \wedge |w| \text{ is even}\}; S \rightarrow aSa \mid bSb \mid \varepsilon$
- $\{wa^n w^R\}; S \rightarrow aSa \mid bSb \mid M; M \rightarrow aM \mid \varepsilon$
- $\{w\#x : w^R \subseteq x\}; S \rightarrow AX; A \rightarrow 0A0 \mid 1A1 \mid \#X; X \rightarrow$
- $\{w : \#_w(a) > \#_w(b)\}; S \rightarrow TaT; T \rightarrow TT \mid aTb \mid bTa \mid$
- $\{w : \#_w(a) \geq \#_w(b)\}; S \rightarrow SS \mid aSb \mid bSa \mid a \mid \varepsilon$

- $\{a^n b^m \mid m \leq n \leq 3m\}; S \rightarrow aSb \mid aaSb \mid aaaSb \mid \varepsilon;$
- (a) $\{a^n b^m \mid n \leq m\}; S \rightarrow aSb \mid \varepsilon$
- $\{a^n b^m \mid n > m\}; S \rightarrow aSb \mid aS \mid a$
- $\{a^n b^m \mid n \geq m \geq 0\}; S \rightarrow aSb \mid aS \mid a \mid \varepsilon$
- b. $\{a^i b^j c^k \mid i + j = k\}; S \rightarrow aSc \mid X; X \rightarrow bXc \mid \varepsilon$
- $\{xy \mid |x| = |y|, x \neq y\};$
 $S \rightarrow AB \mid BA; A \rightarrow a \mid aAa \mid aAb \mid bAa \mid aAb; B \rightarrow b \mid aBa \mid aBb \mid$
- (the following are both **CFL** and **regular**)
- $\{w \mid \#_w(a) \geq 3\}; S \rightarrow XaXaXaX; X \rightarrow aX \mid bX \mid \varepsilon$

- $\{w = a^n b^n c^n\}$; $s = a^p b^p b^p = uvxyz$. vxy can't contain all of a, b, c thus uv^2xy^2z must pump one of them less than the others.

- $L = \{w w^R w : w \in \{a, b\}^*\}$
 $\{w \mid \#_w(a) = \#_w(b) = \#_w(c)\}$: (pf. since
 $\text{Regular} \cap \text{CFL} \in \text{CFL}$, but
 $\{a^* b^* c^*\} \cap L = \{a^n b^n c^n\} \notin \text{CFL}$)

- **(TM)** $M = (Q, \Sigma_{\text{input}} \subseteq \Gamma, \Gamma_{\text{tape}}, \delta, q_0, q_{\text{acc}}, q_{\text{rej}})$, where $\sqsubseteq \subseteq \Gamma$, $\sqsubseteq \notin \Sigma$, $q_{\text{rej}} \neq q_{\text{acc}}$, $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$
- **(recognizable)** \mathbb{A} if $w \in L$, \overline{w} loops if $w \notin L$; A is **co-recognizable** if \overline{A} is recognizable.
- $L \in \text{RECOGNIZABLE} \iff L \leq_m \text{ATM}$.
- Every inf. recognizable lang. has an inf. dec. subset.
- **(decidable)** \mathbb{A} if $w \in L$, \overline{w} if $w \notin L$.
- $L \in \text{DECIDABLE} \iff L \leq_m 0^*1^*$.

- $DFA \equiv NFA \equiv GNFA \equiv REG \subset NPDA \equiv CFG \subset DTM \equiv NTM$
- $f: \Sigma^* \rightarrow \Sigma^*$ is **computable** if $\exists M_{TM}: \forall w \in \Sigma^*, M$ halts on w and outputs $f(w)$ on its tape.
- If $A \leq_m B$ and B is decidable, then A is dec.
- If $A \leq_m B$ and A is undecidable, then B is undec.
- If $A \leq_m B$ and B is recognizable, then A is rec.
- If $A \leq_m B$ and A is unrecognizable, then B is unrec.
- (transitivity) If $A \leq_m B$ and $B \leq_m C$, then $A \leq_m C$.
- $A \leq_m B \iff \bar{A} \leq_m \bar{B}$ (esp. $A \leq_m \bar{A} \iff \bar{A} \leq_m A$)
- If $A \leq_m \bar{A}$ and $A \in \text{RECOGNIZABLE}$, then $A \in \text{DEC}$.

<ul style="list-style-type: none"> (unrecognizable) $\overline{A_{TM}}, \overline{EQ_{TM}}, EQ_{CFG}, \overline{HALT_{TM}}, REG_{TM}, E_{TM}, EQ_{TM}, ALL_{CFG}, EQ_{CFG}$ (recognizable but undecidable) $A_{TM}, HALT_{TM}, \overline{EQ_{CFG}}, \overline{E_{TM}}, \{\langle M, k \rangle \mid \exists x (M(x) \text{ halts in } \geq k \text{ steps})\}$ (decidable) $A_{DFA}, A_{NFA}, A_{REG}, E_{DFA}, EQ_{DFA}, A_{CFG}, E_{CFG}, A_{LBA}, ALL_{DFA} = \{\langle D \rangle \mid L(D) = \Sigma^*\}, A_{\varepsilon CFG} = \{\langle G \rangle \mid \varepsilon \in L(G)\}$ Examples of Deciders: $INFINITE_{DFA}$: "On n-state DFA $\langle A \rangle$: const. DFA B s.t. $L(B) = \Sigma^{\geq n}$; const. DFA C s.t. $L(C) = L(A) \cap L(B)$; if 	<ul style="list-style-type: none"> $L(C) \neq \emptyset$ (by E_{DFA}) A; O/W, \overline{R}" $\{\langle D \rangle \mid \nexists w \in L(D) : \#1(w) \text{ is odd}\}$: "On $\langle D \rangle$: const. DFA A s.t. $L(A) = \{w \mid \#1(w) \text{ is odd}\}$; const. DFA B s.t. $L(B) = L(D) \cap L(A)$; if $L(B) = \emptyset$ (E_{DFA}) A; O/W \overline{R}" $\{\langle R, S \rangle \mid R, S \text{ are regex}, L(R) \subseteq L(S)\}$: "On $\langle R, S \rangle$: const. DFA D s.t. $L(D) = L(R) \cap \overline{L(S)}$; if $L(D) = \emptyset$ (by E_{DFA}) A; O/W, \overline{R}" $\{\langle D_{DFA}, R_{REG} \rangle \mid L(D) = L(R)\}$: "On $\langle D, R \rangle$: convert R to DFA D_R; if $L(D) = L(D_R)$ (by EQ_{DFA}) A; O/W, \overline{R}" $\{\langle D_{DFA} \rangle \mid L(D) = (L(D))^{\mathbb{R}}\}$: "On $\langle D \rangle$: const. DFA $D^{\mathbb{R}}$ s.t. $L(D^{\mathbb{R}}) = (L(D))^{\mathbb{R}}$; if $L(D) = L(D^{\mathbb{R}})$ (by EQ_{DFA}), 	<ul style="list-style-type: none"> A; O/W, \overline{R}" $\{\langle M, k \rangle \mid \exists x (M(x) \text{ runs for } \geq k \text{ steps})\}$: "On $\langle M, k \rangle$: (foreach $w \in \Sigma^{\leq k+1}$: if $M(w)$ not halt within k steps, A); O/W, \overline{R}" $\{\langle M, k \rangle \mid \exists x (M(x) \text{ halts in } \leq k \text{ steps})\}$: "On $\langle M, k \rangle$: (foreach $w \in \Sigma^{\leq k+1}$: run $M(w)$ for $\leq k$ steps, if halts, A); O/W, \overline{R}" $\{\langle M_{DFA} \rangle \mid L(M) = \Sigma^*\}$: "On $\langle M \rangle$: const. DFA $M^c = (L(M))^c$; if $L(M^c) = \emptyset$ (by E_{DFA}) A; O/W \overline{R}." $\{\langle R_{REG} \rangle \mid \exists s, t \in \Sigma^* : w = s111t \in L(R)\}$: "On $\langle R \rangle$: const. DFA D s.t. $L(D) = \Sigma^*111\Sigma^*$; const. DFA C s.t. $L(C) = L(R) \cap L(D)$; if $L(C) \neq \emptyset$ (E_{DFA}) A; O/W \overline{R}"
--	---	--

Mapping Reduction: $A \leq_m B$ if $\exists f : \Sigma^* \rightarrow \Sigma^* : \forall w \in \Sigma^*, w \in A \iff f(w) \in B$ and f is computable.

<ul style="list-style-type: none"> $A_{TM} \leq_m \{\langle M_{TM} \rangle \mid L(M) = (L(M))^{\mathbb{R}}\}$; $f(\langle M, w \rangle) = \langle M', w \rangle$, where $M' =$ "On x, if $x \notin \{01, 10\}, \overline{R}$; if $x = 01$, return $M(x)$; if $x = 10$, A." $A_{TM} \leq_m L = \{\langle M, D \rangle \mid L(M) = L(D)\}$; $f(\langle M, w \rangle) = \langle M', D \rangle$, where $M' =$ "On x: if $x = w$ return $M(x)$; O/W, \overline{R};" D is DFA s.t. $L(D) = \{w\}$. $A \leq_m HALT_{TM}$; $f(w) = \langle M, \varepsilon \rangle$, where $M =$ "On x: if $w \in A$, halt; if $w \notin A$, loop;" $A_{TM} \leq_m CFL_{TM} = \{\langle M \rangle \mid L(M) \text{ is CFL}\}$; $f(\langle M, w \rangle) = \langle N \rangle$, where $N =$ "On x: if $x = a^n b^n c^n$, A; O/W, return $M(w)$;" $A \leq_m B = \{0w : w \in A\} \cup \{1w : w \notin A\}$; $f(w) = 0w$. $E_{TM} \leq_m USELESS_{TM}$; $f(\langle M \rangle) = \langle M, q_{\mathbf{A}} \rangle$ $A_{TM} \leq_m REGULAR_{TM}$; $f(\langle M, w \rangle) = \langle M', w \rangle$, $M' =$ "On 	<ul style="list-style-type: none"> $x \in \{0, 1\}^*$: if $x = 0^n 1^n$, A; O/W, return $M(w)$;" $A_{TM} \leq_m EQ_{TM}$; $f(\langle M, w \rangle) = \langle M_1, M_2 \rangle$, where $M_1 =$ "A all"; $M_2 =$ "On x: return $M(w)$;" $A_{TM} \leq_m \overline{EQ_{TM}}$; $f(\langle M, w \rangle) = \langle M_1, M_2 \rangle$, where $M_1 =$ "\overline{R} all"; $M_2 =$ "On x: return $M(w)$;" $ALL_{CFG} \leq_m EQ_{CFG}$; $f(\langle G \rangle) = \langle G, H \rangle$, s.t. $L(H) = \Sigma^*$. $A_{TM} \leq_m \{\langle M_{TM} \rangle \mid L(M) = 1\}$; $f(\langle M, w \rangle) = \langle M', w \rangle$, where $M' =$ "On x: if $x = x_0$, return $M(w)$; O/W, \overline{R};" (where $x_0 \in \Sigma^*$ is fixed). $\overline{A_{TM}} \leq_m E_{TM}$; $f(\langle M, w \rangle) = \langle M', w \rangle$, where $M' =$ "On x: if $x \neq w$, \overline{R}; O/W, return $M(w)$;" $A_{TM} \leq_m \{\langle M_{TM} \rangle \mid L(M) = 1\}$; $\overline{HALT_{TM}} \leq_m \{\langle M_{TM} \rangle \mid L(M) \leq 3\}$; $f(\langle M, w \rangle) = \langle M', w \rangle$, where $M' =$ "On x: A if $M(w)$ halts" $HALT_{TM} \leq_m \{\langle M_{TM} \rangle \mid L(M) \geq 3\}$; $f(\langle M, w \rangle) = \langle M', w \rangle$, where $M' =$ "On x: A if $M(w)$ halts" 	<ul style="list-style-type: none"> <math>\overline{HALT_{TM}} \leq_m \{\langle M_{TM} \rangle \mid M \text{ A all even num.}\}</math>; $f(\langle M, w \rangle) = \langle M', w \rangle$, where $M' =$ "On x: \overline{R} if $M(w)$ halts within x. O/W, A" $\overline{HALT_{TM}} \leq_m \{\langle M_{TM} \rangle \mid L(M) \text{ is finite}\}$; $f(\langle M, w \rangle) = \langle M', w \rangle$, where $M' =$ "On x: A if $M(w)$ halts" $\overline{HALT_{TM}} \leq_m \{\langle M_{TM} \rangle \mid L(M) \text{ is infinite}\}$; $f(\langle M, w \rangle) = \langle M', w \rangle$, where $M' =$ "On x: \overline{R} if $M(w)$ halts within x steps. O/W, A" $HALT_{TM} \leq_m \{\langle M_1, M_2 \rangle : \varepsilon \in L(M_1) \cup L(M_2)\}$; $f(\langle M, w \rangle) = \langle M', M' \rangle$, $M' =$ "On x: A if $M(w)$ halts" $HALT_{TM} \leq_m \overline{E_{TM}}$; $f(\langle M, w \rangle) = \langle M', w \rangle$, where $M' =$ "On x: if $x \neq w$ \overline{R}; else, A if $M(w)$ halts" $HALT_{TM} \leq_m \{\langle M_{TM} \rangle \mid \exists x : M(x) \text{ halts in } > \langle M \rangle \text{ steps}\}$; $f(\langle M, w \rangle) = \langle M', w \rangle$, where $M' =$ "On x: if $M(w)$ halts, make $\langle M \rangle + 1$ steps and then halt; O/W, loop"
--	--	--

$$P = \bigcup_{k \in \mathbb{N}} \text{TIME}(n^k) \subseteq NP = \bigcup_{k \in \mathbb{N}} \text{NTIME}(n^k) = \{L \mid L \text{ is decidable by a PT verifier}\} \supseteq \text{NP-complete} = \{B \mid B \in NP, \forall A \in NP, A \leq_P B\}.$$

<ul style="list-style-type: none"> ((Running time) decider M is a $f(n)$-time TM.) $f : \mathbb{N} \rightarrow \mathbb{N}$, where $f(n)$ is the max. num. of steps that DTM (or NTM) M takes on any n-length input (and any branch of any n-length input. resp.). (verifier for L) TM V s.t. $L = \{w \mid \exists c : V(\langle w, c \rangle) = \mathbf{A}\}$; (certificate for $w \in L$) str. c s.t. $V(\langle w, c \rangle) = \mathbf{A}$. $f : \Sigma^* \rightarrow \Sigma^*$ is PT computable if there exists a PT TM M s.t. for every $w \in \Sigma^*$, M halts with $f(w)$ on its tape. 	<ul style="list-style-type: none"> If $A \leq_P B$ and $B \in P$, then $A \in P$. If $A \leq_P B$ and $B \leq_P A$, then A and B are PT equivalent, denoted $A \equiv_P B$. \equiv_P is an equiv. relation on NP. $P \setminus \{\emptyset, \Sigma^*\}$ is an equiv. class of \equiv_P. $ALL_{DFA}, CONNECTED, TRIANGLE, L(G_{CFG}), RELPRIME, \overrightarrow{PATH}_{s \rightarrow t} \in P$ $CNF_2 \in P$: (alg. $\forall x \in \phi$: (1) If x occurs 1-2 times in same clause \rightarrow del cl.; (2) If x is twice in 2 cl. \rightarrow del 	<p>both cl.; (3) Similar to (2) for \overline{x}; (4) Replace any $(x \vee y), (\neg x \vee z)$ with $(y \vee z)$; $(y, z$ may be $\varepsilon)$; (5) If $(x) \wedge (\neg x)$ found, \overline{R}. (6) If $\phi = \varepsilon$, A);</p> <ul style="list-style-type: none"> $CLIQUE, SUBSET-SUM, SAT, 3SAT, \overrightarrow{COVER}, HAMPATH, UHAMATH, 3COLOR \in \text{NP-complete}$. $\emptyset, \Sigma^* \notin \text{NP-complete}$. If $B \in \text{NP-complete}$ and $B \in P$, then $P = \text{NP}$. If $B \in \text{NPC}$ and $C \in \text{NP}$ s.t. $B \leq_P C$, then $C \in \text{NPC}$. If $P = \text{NP}$, then $\forall A \in P \setminus \{\emptyset, \Sigma^*\}, A \in \text{NP-complete}$.
--	---	---

Polytime Reduction: $A \leq_P B$ if $\exists f : \Sigma^* \rightarrow \Sigma^* : \forall w \in \Sigma^*, w \in A \iff f(w) \in B$ and f is polytime computable.

<ul style="list-style-type: none"> $SAT \leq_P DOUBLE-SAT$; $f(\phi) = \phi \wedge (x \vee \neg x)$ $3SAT \leq_P 4SAT$; $f(\phi) = \phi'$, where ϕ' is obtained from the CNF ϕ by adding a new var. x to each clause, and adding a new clause $(\neg x \vee \neg x \vee \neg x \vee \neg x)$. $3SAT \leq_P CNF_3$; $f(\langle \phi \rangle) = \phi'$. If $\#_{\phi}(x) = k > 3$, replace x with x_1, \dots, x_k, and add $(\overline{x_1} \vee x_2) \wedge \dots \wedge (\overline{x_k} \vee x_1)$. $SUBSET-SUM \leq_P SET-PARTITION$; $f(\langle x_1, \dots, x_m, t \rangle) = \langle x_1, \dots, x_m, S - 2t \rangle$, where S sum of x_1, \dots, x_m, and t is the target subset-sum. $3COLOR \leq_P \overline{3COLOR}$; $f(\langle G \rangle) = \langle G' \rangle$, $G' = G \cup K_4$ $\overrightarrow{COVER}_k \leq_P WVC$; $f(\langle G, k \rangle) = (G, w, k), \forall v \in V(G), w(v) =$ (dir.) $HAM-PATH \leq_P 2HAM-PATH$; $f(\langle G, s, t \rangle) = \langle G', s', t' \rangle$, where $V' = V \cup \{s', t', a, b, c, d\}$, 	<ul style="list-style-type: none"> $E' = E \cup \{(s', a), (a, b), (b, s)\} \cup \{(s', b), (b, a), (a, s)\} \cup \{(t, c), (c, d), (d, t')\} \cup \{(t, d), (d, c), (c, t')\}$. (undir.) $CLIQUE_k \leq_P \overline{HALF-CLIQUE}_{\lfloor V /2 \rfloor}$; $f(\langle G = (V, E), k \rangle) = \langle G' = (V', E') \rangle$, if $k = \frac{ V }{2}, E = E', V' = V$. if $k > \frac{ V }{2}, V' = V \cup \{j = 2k - V \text{ new nodes}\}$. if $k < \frac{ V }{2}, V' = V \cup \{j = V - 2k \text{ new nodes}\}$ and $E' = E \cup \{\text{edges for new nodes}\}$ (dir.) $\overrightarrow{HAM-PATH}_{s \rightarrow t} \leq_P \overline{HAM-CYCLE}$; $f(\langle G, s, t \rangle) = \langle G', s, t \rangle$ where $V' = V \cup \{x\}$, $E' = E \cup \{(t, x), (x, s)\}$ $HAM-CYCLE \leq_P UHAMCYCLE$; $f(\langle G \rangle) = \langle G' \rangle$. For each $u, v \in V$: u is replaced by u_{in}, u_{mid}, u_{out}; (v, u) replaced by $\{v_{out}, u_{in}\}, \{u_{in}, u_{mid}\}$; and (u, v) by $\{u_{out}, v_{in}\}, \{u_{mid}, u_{out}\}$. $UHAMPATH \leq_P \overline{PATH}_{\geq k}$; 	<ul style="list-style-type: none"> $f(\langle G, a, b \rangle) = \langle G, a, b, k = V(G) - 1 \rangle$ $\overrightarrow{COVER}_k \leq_P \overline{CLIQUE}_k$; $f(\langle G, k \rangle) = \langle G^c = (V, E^c), V - k \rangle$ $CLIQUE_k \leq_P \{\langle G, t \rangle : G \text{ has } 2t\text{-clique}\}$; $f(\langle G, k \rangle) = \langle G', t = \lceil k/2 \rceil \rangle$, $G' = G$ if k is even; $G' = G \cup \{v\}$ (v connected to all G nodes) if k is odd. $CLIQUE_k \leq_P \overline{CLIQUE}_k$; $f(\langle G, k \rangle) = \langle G', k + 2 \rangle$, where $G' = G \cup \{v_{n+1}, v_{n+2}\}$ and v_{n+1}, v_{n+2} are con. to all G nodes. $\overrightarrow{COVER}_k \leq_P \overline{DOMINATING-SET}_k$; $f(\langle G, k \rangle) = \langle G', k \rangle$, where $V' = \{\text{non-isolated node in } V\} \cup \{v_e : e \in E\}$, $E' = E \cup \{(v_e, u), (v_e, w) : e = (u, w) \in E\}$. $CLIQUE \leq_P \overline{INDEP-SET}$; $SET-COVER \leq_P \overline{COVER}$; $3SAT \leq_P \overline{SET-SPLITTING}$; $INDEP-SET \leq_P \overline{COVER}$
--	--	---

Counterexamples

<ul style="list-style-type: none"> $A \leq_m B$ and $B \in \text{REG}$, but, $A \notin \text{REG}$: $A = \{0^n 1^n \mid n \geq 0\}, B = \{1\}, f : A \rightarrow B, f(w) = \begin{cases} 1 & \text{if } w \in A \\ 0 & \text{if } w \notin A \end{cases}$ $L \in \text{CFL}$ but $\overline{L} \notin \text{CFL}$: $L = \{x \mid \forall w \in \Sigma^*, x \neq ww\}, \overline{L} = \{ww \mid w \in \Sigma^*\}$. $L_1, L_2 \in \text{CFL}$ but $L_1 \cap L_2 \notin \text{CFL}$: $L_1 = \{a^n b^n c^m\}, L_2 = \{a^m b^n c^n\}, L_1 \cap L_2 = \{a^n b^n c^n\}$. $L_1 \in \text{CFL}, L_2$ is infinite, but $L_1 \setminus L_2 \notin \text{REG}$: $L_1 = \Sigma^*, L_2 = \{a^n b^n \mid n \geq 0\}, L_1 \setminus L_2 = \{a^m b^n \mid m \neq n\}$. 	<ul style="list-style-type: none"> $L_1, L_2 \in \text{REG}, L_1 \not\subseteq L_2, L_2 \not\subseteq L_1$, but, $(L_1 \cup L_2)^* = L_1^* \cup L_2^*$: $L_1 = \{a, b, ab\}, L_2 = \{a, b, ba\}$. $L_1 \in \text{REG}, L_2 \notin \text{REG}$, but, $L_1 \cap L_2 \in \text{REG}$, and $L_1 \cup L_2 \in \text{REG}$: $L_1 = L(a^* b^*)$, $L_2 = \{a^n b^n \mid n \geq 0\}$. $L_1, L_2, L_3, \dots \in \text{REG}$, but, $\bigcup_{i=1}^{\infty} L_i \notin \text{REG}$: $L_i = \{a^i b^i\}, \bigcup_{i=1}^{\infty} L_i = \{a^n b^n \mid n \geq 0\}$. $L_1 \cdot L_2 \in \text{REG}$, but $L_1 \notin \text{REG}$: $L_1 = \{a^n b^n \mid n \geq 0\}, L_2 = \Sigma^*$. $L_2 \in \text{CFL}$, and $L_1 \subseteq L_2$, but $L_1 \notin \text{CFL}$: $\Sigma = \{a, b, c\}, L_1 = \{a^n b^n c^n \mid n \geq 0\}, L_2 = \Sigma^*$. 	<ul style="list-style-type: none"> $L_1, L_2 \in \text{DECIDABLE}$, and $L_1 \subseteq L \subseteq L_2$, but $L \in \text{UNDECIDABLE}$: $L_1 = \emptyset, L_2 = \Sigma^*, L$ is some undecidable language over Σ. $L_1 \in \text{REG}, L_2 \notin \text{CFL}$, but $L_1 \cap L_2 \in \text{CFL}$: $L_1 = \{\varepsilon\}, L_2 = \{a^n b^n c^n \mid n \geq 0\}$. $L^* \in \text{REG}$, but $L \notin \text{REG}$: $L = \{a^p \mid p \text{ is prime}\}, L^* = \Sigma^* \setminus \{a\}$. $A \not\leq_m \overline{A}$: $A = A_{TM} \in \text{RECOGNIZABLE}, \overline{A} = \overline{A_{TM}} \notin \text{RECOG}$. $A \notin \text{DEC.}, A \leq_m \overline{A}$: $L \in \text{CFL}, L \cap L^{\mathbb{R}} \notin \text{CFL} : L = \{a^n b^n a^m\}$.
--	---	---