Digital Twins for Industrial Edge 4.0: Concepts and Tools

Adika Bintang Sulaeman

adika.sulaeman@aalto.fi

Tutor: Prof. Hong-Linh Truong

Abstract

Industry 4.0 is expected to be the next big phase in industry. Digital twins, defined as digital representations of physical objects such as machines, have an important role in Industry 4.0. This paper discusses the digital twin in the context of Industry 4.0 as well as the supporting technologies for digital twins such as the Internet of Things (IoT), cloud computing, fog and edge computing, as well as the software architecture for digital twins.

KEYWORDS: Digital Twin, Industrial Internet of Things, Industry 4.0

1 Introduction

Industry 4.0 is the next big phase in industry. With industry 4.0, it is possible to gather real-time data from the machines that run in industry and process the data into something meaningful and useful. Industry 4.0 mainly consists of three supporting technologies: IoT, Cyber-Physical Systems (CPS), and Smart Factories [4]. The combination of these technologies builds interconnected devices forming digital twins.

A digital twin models a physical object by creating a digital representation using real-time data [6]. The data is gathered throughout its life-

cycle and used as the source to monitor, learn from, and enhance decision making. A digital twin enables engineers to monitor and understand how the machines behave once it is released and run by users. Furthermore, engineers can analyze the data and predict the future performance of the machines.

There are some use cases of digital twins for Industry 4.0. Consider a Printed Circuit Board (PCB) printer for electronic manufacturers. The PCB printer must be very precise, because the smallest error by the laser cutter may lead to PCB flaws. A digital twin enables engineers and technicians to monitor and analyze the data to predict the time when the spare parts wear out. Another example would be monitoring the jet engine of airplanes. By analyzing data gathered in real-time, engineers and technicians may predict failures in jet systems, which will lead to the reduction of airplane incidents. Furthermore, digital twins may give feedback to the engineers who design the machine to help them realize an agile development system.

The main value that the digital twin delivers is an understanding of product performance [6]. By understanding performance, manufacturers may detect and understand faults better, create an effective maintenance schedule, troubleshoot machines remotely, and decide appropriate add-on services.

The digital twin has some challenges in its development and implementation. In [1], the author has stated a number of challenges such as data consistency between the real physical assets and the digital representation, as well as connectivity and security concerns of cloud computing for digital twins. Software architectural aspects such as internal structure, APIs, integration, and runtime environment are also critical challenges for digital twins [5].

1.1 Scope and Goals

This paper aims to review the concept of digital twins for Industry 4.0 as well as the tools and challenges to implement digital twins. The role of the IoT, software deployment technologies, API, and cloud computing in digital twins will be the main focus of this paper.

1.2 Structure

The rest of this paper is organized as follows. Section 2 discusses the tools for digital twins, i.e. the roles of IoT, containers, API, and cloud computing for the digital twin. Section 3 concludes this review paper.

2 Technologies for Digital Twins

2.1 Edge Computing, Fog Computing and Cloud Computing Integration for Digital Twins

Digital Twins and CPS can be divided into three levels according to location of the services: unit level, system level, and System of System (SoS) level [7]. Unit level is the level where local data processing is done by the CPS. The concept of production line, smart factory, and shop floor lies on system level. SoS level is the level which integrates the different systems from system level. Edge computing, fog computing and cloud computing may help integrate the three levels of Digital Twin Systems.

Edge devices, such as the computing resources of the CPS itself, is the source of data. Those devices may also be able to do computation without having to send the data to remote location to reduce latency. Edge computing operation does not always rely on network connection to operate. Therefore, hard real-time response is possible if the computation is done on the edge.

System level may take benefits of fog computing. Fog computing brings the concept of bringing programs to the data, and not vice versa. Fog computing does the computation and storage to the edge network. In this way, the long latency processing that usually comes with cloud computing can be avoided. Human-machine interface and information management systems such as Customer Relationship Management (CRM) cab be connected to the fog computing. However, the capability of devices in fog computing is limited compared to the cloud computing devices. Therefore, at some point, the processing must be done on cloud platform.

Cloud platform may help digital twin systems in integrating the systems from the system level. Long-term and massive data storage is handled by cloud computing. It provides architectural flexibility and utilization of external parties to be involved in further value creation.

This system architecture has some challenges that needs to be solved.

The number of edge and fog devices deployed must be increased. Furthermore, their processing power and storage capacities must be improved to handle more computation. As the computation is done physically close to the users, the security of this systems also require further research.

2.2 Cloud Technologies for Digital Twins

Digital twins may take advantages of cloud technologies. The digital twin can be modeled as a Digital Twin-as-a-Service (DTaaS) [2]. In DTaaS, the cloud platform has a number of levels of abstractions.

The first level is the digital twin users, who perceive the digital twins as a software service. At the level of the digital twin developer, the cloud platform provides the resources for the development of digital twins as a Platform-as-a-Service (PaaS) model. One of the resources needed by the developers is computing services for specific data operation. These computing services are represented as microservices provided by computing service developers. The computing services are run on a containers provided by the cloud infrastructure providers.

Ciavotta et. al. [3] proposed a microservice-based middleware for digital factory with digital interface in it, named MAYA Platform. The digital interface in that digital factory refers to the digital twin. The designed middleware focuses on enabling interoperability between enterprise applications and CPS.

MAYA Platform is a distributed platform consisting of three main components: MAYA Communication Layer (MCL) for aggregation, discovery, orchestration and communication among CPSs; MAYA Support Infrastructure (MSI) for managing the Digital Twins, enabling definition, data processing, and dismissal with miroservice and Big Data technologies; MAYA Simulation Framework (MSF) for simulation and real-to-digital synchronization of the Digital Twins.

The usage scenario of MAYA Platform can be described as the following:

- New CPS devices are registered manually.
- The CPS logs in on MSI.
- MAYA Platform sets up the Digital Twin Functional Model
- The communication is established between CPS and MSI. The CPS

sends data to the platform.

- The Functional Model creates updates periodically of the corresponding Digital Twin.
- The MSF performs the simulation by accessing the simulation model of the Digital Twin.

The key focus of the MAYA Platform design is on the MSI. The authors chose microservices because it provides agility, isolation, resilience and elasticity. However, the author also mentioned about the challenges of microservice for this platform, i.e, the difficulties of managing distributed data and the increasing complexity of the software system. Big Data is also part of the MSI. The platform may take benefits of Big Data technologies such as simple but reliable processing, multi-paradigm and general purpose, robust, and scalable.

2.3 Software Architecture

Software Web Services and Augmented Reality (AR) may help in visualizing the Digital Twins [8]. Data gathered from CPS is stored in data repositories. Web services are implemented to retrieve the data from the repositories, and the data is visualized using AR.

The architecture of the software for Digital Twins visualization can be divided into five layers. The first layer is the device layer, which is a software layer composed by the devices, such as computers, tablets and mobile devices, accessing the system to see the visualization. The second layer is the user interface layer, which can be an AR interface. The third layer is the web service layer using RESTful web service. The forth layer is the query layer, which is responsible for retrieving the data from the data repositories. Finally, the fifth layer is the data repository layer.

3 Conclusion

To be added.

References

- [1] Diethelm Bienhaus. Patterns for the industrial internet/industrie 4.0. In *Proceedings of the 22nd European Conference on Pattern Languages of Programs*, page 17. ACM, 2017.
- [2] Kirill Borodulin, Gleb Radchenko, Aleksandr Shestakov, Leonid Sokolinsky, Andrey Tchernykh, and Radu Prodan. Towards digital twins cloud platform: Microservices and computational workflows to rule a smart factory. In Proceedings of the 10th International Conference on Utility and Cloud Computing, pages 209–210. ACM, 2017.
- [3] Michele Ciavotta, Marino Alge, Silvia Menato, Diego Rovere, and Paolo Pedrazzoli. A microservice-based middleware for the digital factory. *Procedia Manufacturing*, 11:931–938, 2017.
- [4] Mario Hermann, Tobias Pentek, and Boris Otto. Design principles for industrie 4.0 scenarios. In *System Sciences (HICSS)*, 2016 49th Hawaii International Conference on, pages 3928–3937. IEEE, 2016.
- [5] Somayeh Malakuti and Sten Grüner. Architectural aspects of digital twins in iiot systems. In *Proceedings of the 12th European Conference on Software Architecture: Companion Proceedings*, page 12. ACM, 2018.
- [6] Matthew Mikkel and Jen Clark. Cheat sheet: What is digital twin? internet of things blog. https://www.ibm.com/blogs/internet-of-things/iot-cheat-sheet-digital-twin/, January 2018. (Accessed on 01/30/2019).
- [7] Qinglin Qi, Dongming Zhao, T Warren Liao, and Fei Tao. Modeling of cyber-physical systems and digital twin based on edge computing, fog computing and cloud computing towards smart manufacturing. In *ASME 2018 13th International Manufacturing Science and Engineering Conference*, pages V001T05A018–V001T05A018. American Society of Mechanical Engineers, 2018.
- [8] Greyce Schroeder, Charles Steinmetz, Carlos Eduardo Pereira, Ivan Muller, Natanael Garcia, Danubia Espindola, and Ricardo Rodrigues. Visualising the digital twin using web services and augmented reality. In 2016 IEEE 14th International Conference on Industrial Informatics (INDIN), pages 522– 527. IEEE, 2016.