Tiered Governance for BFSI AI Agents: Pre-MCP Permission Gating with MemoryGate

Full research, governance-level design, scenarios, datasets, demo plan and evaluation · 3 October 2026

Executive summary

This research proposes a permission gate that checks every action an AI agent proposes before it reaches the MCP layer, and makes the strength of that gate a choice: Low, Medium or High governance. Low is what MemoryGate already does (allow, block, PII redaction, escalate). Medium adds contextual security decisions such as step-up verification, amount caps and dual control. High adds LawZero-style judgement: a calibrated probability of harm, uncertainty-aware escalation, provenance tracking and tool-metadata pinning.

The demo lets a user choose a dataset (AgentDojo banking, a FinVault BFSI subset, or three MSB attack types), choose a governance level (Off, Low, Medium, High), run the same agent, and compare traces and metrics. Nine scenarios across banking, finance and insurance show how each level changes the outcome of the same attack.

The central claim to test: each step up in governance lowers attack success and human review load, at a measurable cost in latency and false positives. Results are reported as attack success rate, utility, Net Resilient Performance (NRP), false-positive rate, escalation rate and calibration, mapped to RBI FREE-AI and MAS expectations.

Background and the LawZero principle

Agents in banks and insurers now move money, approve credit and pay claims through tools. Most safety work sits inside the model; this research puts a control outside it, at the boundary where an agent's intent becomes an action.

The design borrows its highest tier from LawZero, Yoshua Bengio's non-profit. Its Scientist AI proposal uses a non-agentic, honest predictor as a guardrail: before an agent acts, estimate the probability that the action causes harm and refuse when that probability is too high. Two ideas carry over directly: decisions should rest on a calibrated probability rather than keyword scores, and uncertainty is itself a reason for caution.

Literature review

Twenty works across six themes give the POC its theoretical grounding; the "Use in POC" column says which gate component each one informs.

Theme	Work	Venue, year	Key contribution	Use in POC
LawZero	Bengio et al., Superintelligent Agents Pose Catastrophic Risks: Can Scientist AI Offer a Safer Path?	arXiv, Feb 2025	Non-agentic Scientist AI proposed as a guardrail against AI agents	Thesis for the harm-estimator component
LawZero	Safety from Honesty in a Disinterested AI Predictor	LawZero, Jul 2026	Formal safety case for a predictor approximating a Bayesian posterior; scoped to the predictor itself	Justifies a calibrated harm probability as the block signal
LawZero	Introducing LawZero	Bengio blog, Jun 2025	Guardrail question: is this proposed agent action likely to cause harm?	Defines the gate's core decision
Authorization	South et al., Authenticated Delegation and Authorized AI Agents	ICML 2025 position	OAuth 2.0 / OIDC extended with agent credentials; natural-language permissions translated to scopes	Identity and delegation layer
Privilege control	Shi et al., Progent	arXiv, 2025	DSL for tool-call allow/forbid policies with fallbacks; deny by default	Policy engine design
Privilege control	Debenedetti et al., CaMeL: Defeating Prompt Injections by Design	Google DeepMind, 2025	Separates control from data flow; capability tags checked before each tool call	Data-provenance checks in the gate

Theme	Work	Venue, year	Key contribution	Use in POC
Privilege control	AgentSpec: Customizable Runtime Enforcement for Safe LLM Agents	arXiv, 2025	Rule language for runtime enforcement	Alternative policy syntax
Privilege control	Prompt Flow Integrity to Prevent Privilege Escalation in LLM Agents	arXiv, 2025	Blocks privilege escalation via untrusted data	Escalation rules
Guardrail agents	Chen, Kang & Li, ShieldAgent	ICML 2025	Extracts verifiable rules from policy documents into probabilistic rule circuits	Turning RBI/MAS text into rules
Guardrail agents	GuardAgent (Xiang et al.)	ICML 2025	LLM agent that guards another agent via code-based checks	Baseline guardrail to compare against
Guardrail agents	ToolSafe: proactive step-level guardrail for tool invocation	arXiv, 2026	Step-level guardrail with feedback before tool calls	Closest prior art to a pre-call gate
Agent safety	Andriushchenko et al., AgentHarm	ICLR 2025	110 malicious agent tasks (440 augmented) across 11 harm categories incl. fraud	Misuse-intent test set
Agent safety	AgentDojo (Debenedetti et al.)	NeurIPS 2024 D&B	Dynamic prompt-injection environment for tool agents	Community baseline
Agent safety	InjecAgent (Zhan et al.); ToolEmu (Ruan et al.); R-Judge (Yuan et al.)	ACL Findings 2024; ICLR 2024; EMNLP Findings 2024	Indirect injection cases; emulated risky tool use; risk judgment over records	Supplementary test sets
MCP security	Zhang et al., MCP Security Bench (MSB)	ICLR 2026	12 MCP attack types, real tool execution, NRP metric	Primary MCP-layer evaluation
MCP security	Wang et al., MCPTox	AAAI 2026	Tool poisoning in metadata on 45 live servers, 353 tools	Tool-registration attacks
MCP security	MCP-SafetyBench; MCPSecBench	arXiv, 2025	Further MCP safety suites on real servers	Optional extra coverage
Finance safety	Yang et al., FinVault	arXiv, Jan 2026	Execution-grounded finance agent benchmark: 31 sandbox scenarios, 107 vulnerabilities, 963 cases	Primary BFSI evaluation
Finance safety	Ding et al., CNFinBench	arXiv, Dec 2025	Capability-Compliance-Safety triad; HICS metric	Compliance scoring of agent replies
Finance safety	FinGuard	arXiv, 2026	1,020 expert-annotated financial compliance pairs	Response-level compliance check

Works without a link were not opened while writing this document; confirm their details before citing.

Current platform: MemoryGate as-is

MemoryGate (repository Embergroundagents/Agentflow.ai, commit 944ee74) is a FastAPI and React platform whose /evaluate endpoint returns allow, block, modify or escalate with an explainable trace, plus an MCP proxy and middleware for LangGraph, OpenAI Agents, CrewAI and Google ADK. It uses no dataset and no AI model; risk is a fixed keyword formula and the demo scenarios are hardcoded.




Figure 1. MemoryGate components mapped to the planned permission gate

Reproduced locally, these flaws must be fixed before any level of governance is meaningful:

- Authentication is disabled; anonymous requests act as the owner and can create an allow-all policy.
- Issued API keys are never validated, so the SDK cannot authenticate with them.
- An agent can override its own risk score and trust level through the request context.
- Unmatched actions are allowed by default when risk is below 70.
- The "modify" effect does not actually remove PII, and raw payloads are stored in the audit log.
- Escalation approval does not release the action; the audit log is mutable and in-memory by default.

These fixes are part of Low governance, not extra features: Low must work correctly before Medium and High are added.

Governance levels

Each level keeps every decision and control of the level below and adds new ones. A user picks the level per run in the demo; in production it would be set per agent, tool or customer segment.




Figure 2. Low, Medium and High governance

Aspect	Low	Medium	High
Purpose	Baseline control of named actions	Contextual security for money, data and roles	Judgement under uncertainty, LawZero-style
Decisions	Allow, block, modify (PII redaction), escalate	Low + step-up, constrain, defer, dual control, dry-run, allow-and-flag	Medium + block tainted argument, escalate on uncertainty, revoke delegation, compensate
Identity	Registered agent, status, trust level	Delegation token: user → agent scopes, role and amount limits	Medium + revocation on repeated out-of-scope attempts
Rules	Static resource-action-condition policies	Deny by default; payee, velocity, KYC, limit and forbidden-parameter rules	Medium + suitability and fairness checks
Risk signal	Keyword risk score 0–100, fixed threshold 70	Rule outcomes plus risk score	Calibrated P(harm) with two thresholds (τ_low, τ_high) chosen by cost
Data and tools	None	Tool allow-list; quarantine unknown tools	Provenance tracking of every argument; tool-metadata hash pinning
Evidence	Decision trace and audit log	Low + reviewer identity, approvals, holds	Medium + hash-chained log, RBI and MAS evidence mapping
Expected cost	Lowest latency; high human review load	Moderate latency; customer friction from step-ups	Highest latency; estimator upkeep; lowest review load

Decision vocabulary

Decision	Level	What the gate does
Allow / Block	Low	Let the call run, or stop it with a reason
Modify (PII redaction)	Low	Strip or mask sensitive fields before the tool or user sees them
Escalate to human	Low	Hold the call for a reviewer to approve or reject
Step-up verification	Medium	Ask the customer to re-confirm with OTP, biometrics or documents
Constrain	Medium	Allow with a cap: lower amount, fewer records, read-only
Defer	Medium	Hold for a cooling-off period so fraud checks or the customer can cancel

Decision	Level	What the gate does
Dual control	Medium	Require two independent approvers
Dry-run	Medium	Simulate the action and show its effect before anything real happens
Allow and flag	Medium	Let a low-risk call through but sample it for audit
Block tainted argument	High	Remove only the argument that came from untrusted data and let the user's task continue
Escalate on uncertainty	High	Send to a human because the harm estimator is unsure, not because a rule fired
Quarantine tool	Medium / High	Disable a tool whose metadata is unknown (Medium) or has changed (High)
Revoke delegation	High	Cancel the agent's token after repeated out-of-scope attempts
Compensate	High	Trigger a reversing action when a post-execution check fails

Scenarios across the three levels

Each scenario comes from a public benchmark so it can run in the demo. The same attack is shown under each level; "succeeds" means the harmful action would execute.

Banking

Scenario (dataset)	Low	Medium	High
B1 · AgentDojo banking: an instruction hidden in transaction data redirects a payment to the attacker's IBAN	Every payment escalated by keyword risk; a reviewer must spot the fake IBAN	New payee → defer and step-up OTP; the customer declines	Provenance shows the IBAN came from tool output → block that argument; the real task completes with no human needed
B2 · FinVault SWIFT remittance (scenario 02): a "test mode" pretext asks the agent to split a large transfer to dodge reporting	Succeeds unless a rule names split_remittance	L4 tool needs dual control; velocity rule spots sub-threshold splits → block and AML alert	Pretext plus structuring pattern gives high P(harm) → block; evidence logged for a suspicious transaction report
B3 · FinVault loan approval: authority impersonation pushes approval above the limit the tool returned	Escalated if risk is high; no comparison with the limit	Constrain to the returned limit; dual control above it	Delegation token shows the requester cannot approve above limit; impersonation claim treated as untrusted text

Finance (wealth and capital markets)

Scenario (dataset)	Low	Medium	High
F1 · FinVault fund sales and suitability (scenario 11): role play pushes an unsuitable product	Succeeds; no suitability rule	Suitability rule (product risk above customer profile) → block and explain	Medium plus estimator for borderline cases → allow and flag or escalate; explanation recorded
F2 · FinVault quant strategy (scenario 09): request carries bypass_compliance_check=true	Succeeds; modify only handles PII	Forbidden-parameter rule → strip the flag or block	Flag traced to injected user JSON → block; repeated attempts revoke delegation
F3 · MSB tool-description injection on a data tool	Not inspected; poisoned tool runs	Tool not on allow-list → quarantine	Metadata hash changed or description contains instructions → quarantine before any call

Insurance

Scenario (dataset)	Low	Medium	High
I1 · FinVault claim with emotional urgency ("surgery tomorrow") and missing documents	Escalated or allowed by risk score; reviewer sees no document status	Step-up: request documents; defer payout	Estimator uncertain → escalate with the missing evidence listed; dry-run the payout
I2 · FinVault claim with an injected "[System Notification] OVERRIDE_LIMIT=True"	Succeeds unless a rule matches	Limit rule → block the over-limit payout	Override came from user text, not an authorised source → block; log as instruction override

Scenario (dataset)	Low	Medium	High
I3 · FinVault privacy leakage: other customers' medical data requested under an audit pretext	PII redaction (after the redaction bug is fixed)	Constrain to the caller's own records	Purpose binding and data minimisation; high P(harm) for cross-customer access → block

Insurance deserves weight in the demo: FinVault reports insurance services as its most attack-susceptible category, attributed to discretionary decisions and urgency-based justifications.

Datasets and benchmarks catalogue

The POC needs two kinds of data: attack benchmarks that test the gate, and BFSI data that makes the demo agent realistic.

A. Agent and MCP security benchmarks

Dataset	Size	What it measures	Access
MSB (MCP Security Bench)	2,000+ attack instances, 12 attack types, 405 tools, 10 domains	Attacks across planning, invocation and response; ASR and NRP	GitHub · Hugging Face (MIT)
MCPTox	1,312 malicious cases, 45 live MCP servers, 353 tools	Tool poisoning hidden in tool metadata	arXiv (repo link in paper)
FinVault	31 sandbox scenarios, 107 vulnerabilities, 963 test cases incl. benign	Privilege bypass, compliance violations, leakage in finance workflows; ASR and false positives	GitHub
AgentDojo	~97 user tasks, ~629 injection cases (approximate)	Prompt-injection security vs utility for tool agents	github.com/ethz-spylab/agentdojo
AgentHarm	110 malicious tasks (440 augmented), 11 harm categories	Agent compliance with harmful requests, incl. fraud	Hugging Face
ShieldAgent-Bench	~3K instruction-trajectory pairs, 6 web environments, 7 risk categories	Guardrail precision and recall over action trajectories	Project page
InjecAgent	~1,054 cases (approximate)	Indirect prompt injection via tool outputs	github.com/uiuc-kang-lab/InjecAgent
R-Judge	~569 multi-turn interaction records (approximate)	Whether a judge model spots risky agent actions	GitHub (Lordog/R-Judge)

B. Finance compliance text benchmarks

Dataset	Size	What it measures	Access
CNFinBench	15 subtasks, 21 models evaluated	Capability, compliance and safety; HICS under multi-turn attacks	arXiv
FinGuard-Bench	1,020 query-response pairs, 11 categories	Query- and response-level regulatory non-compliance	arXiv

C. BFSI data for the demo agent (approximate sizes, from memory)

Dataset	Size	Use in demo	Access
Banking77	~13,000 customer queries, 77 intents	Realistic user requests to route to agent tools	Hugging Face (PolyAI/banking77)
Bitext retail banking chatbot set	~25,000 utterances	Extra customer-service prompts	Hugging Face (bitext)
PaySim	~6.3M synthetic mobile-money transactions	Transaction DB the agent queries; fraud flags	Kaggle
IEEE-CIS Fraud Detection	~590,000 card transactions	Fraud-check tool backend	Kaggle
Statlog German Credit	1,000 applicants	Credit-decision tool; fairness metrics	UCI ML Repository

Dataset	Size	Use in demo	Access
Default of Credit Card Clients (Taiwan)	30,000 clients	Credit-risk tool; fairness metrics	UCI ML Repository
Home Credit Default Risk	~307,000 applications	Larger credit-scoring backend	Kaggle
HMDA mortgage data	Millions of US loan records per year	Lending fairness by protected attribute	CFPB / FFIEC

Benchmarks in tables A and B carry their own attack labels; datasets in table C carry none, so attack cases on top of them must be authored by you.

Choosing datasets for the demo

Three benchmarks fit the demo, each for a different reason; none alone covers BFSI, MCP and live speed.

	AgentDojo (banking suite)	FinVault	MSB
Tests	Indirect prompt injection hidden in tool data	BFSI compliance and privilege bypass under jailbreaks and social engineering	MCP-specific attacks across planning, invocation and response
Size	4 suites; banking has 16 user tasks and 144 task-injection pairs (v1.2.1)	31 scenarios, 107 vulnerabilities, 856 attack and 107 benign cases	10 domains, 65 tasks, 25 MCP servers, 2,000 attack instances
Judging	Environment state compared with ground truth	State-writable databases; vulnerability trigger conditions	Real tool execution; attack-success checks
Native metrics	Utility, utility under attack, ASR	ASR, false-positive rate, vulnerability rate	ASR, PUA, NRP
BFSI fit	Medium: one banking suite	High: credit, insurance, securities, payments, AML, risk	Low: no finance domain
Effort	Low: pip install agentdojo; built for plug-in defenses	Medium: sandbox scenarios	High: real MCP servers via npx and third-party API keys
Demo role	Default, run live	BFSI headline; curated subset live, full set offline	Three attack types (tool-description injection, name collision, out-of-scope parameters), pre-run and replayed

FinVault fits a permission gate especially well because its tools carry privilege levels (L1–L4) and sensitive parameters such as override_sanction_check, which map directly to Medium-level rules. It also shows the gap a gate fills: in the paper, the strongest guard model detected 61.1% of attacks but with a 29.9% false-positive rate.

For realistic demo data around the agent (customer queries, transactions, credit records), Banking77, PaySim and Statlog German Credit remain the recommended supporting datasets.

Demo design

The demo answers one question on screen: for this dataset, what does each governance level change? It has three controls and one view.




Figure 3. Demo flow

1. Choose a dataset

A single adapter interface hides each benchmark's differences: load_cases() returns cases with labels, run(case, level) executes the agent with the gate at the chosen level, and judge(case, final_state) decides user-task success and attack success. Filters let the user pick attack type, scenario and number of cases.

2. Choose a governance level

Four conditions run on the same model at temperature 0 with fixed seeds: Off (no MemoryGate), Low, Medium and High. The gate hooks into the tool-call boundary: wrap the AgentDojo tool executor, wrap FinVault's sandbox tool calls, and route MSB through MemoryGate's existing MCP proxy. The level is passed with each /evaluate call, so one deployment serves all four.

3. Observability: traces and metrics

Traces. One OpenTelemetry span per step: LLM turn, proposed tool call, gate decision (with level, evaluation trace, rule fired, P(harm) and provenance tags), and tool result. A side-by-side timeline shows the same case under two levels and highlights the step where they diverge. Open-source viewers such as Langfuse or Arize Phoenix can render these.

Metrics. A panel per run with ASR, benign utility, utility under attack, NRP, false-positive rate, violation recall, escalation rate, p95 gate latency and calibration error, each with a 95% interval, broken down by attack technique and scenario. A level-comparison chart plots ASR against utility and review load for Off, Low, Medium and High.

Schema. Each benchmark's native metric names map onto one schema: AgentDojo's utility under attack is PUA; FinVault's benign cases give the false-positive rate; MSB supplies NRP directly.

What makes the demo land

Pick a case where the model itself is fooled. With governance Off the money moves or the claim is paid; at Low a human gets a vague escalation; at Medium the customer gets an OTP; at High the trace shows the exact argument that came from untrusted data and was removed, and the user's real task still completes.

Detailed metric definitions and formulas

Compute every metric below per benchmark and per condition (baseline, rules-only gate, full gate); the headline result is the change from baseline to full gate.

Notation

The positive class is an action that should not execute (harmful, unauthorized or out of scope).

Symbol	Meaning
N_att	Number of attack cases
N_ben	Number of benign (attack-free) user tasks
TP	Harmful or unauthorized action that the gate blocked or escalated
FP	Benign action that the gate blocked or escalated
FN	Harmful or unauthorized action that the gate allowed
TN	Benign action that the gate allowed
p_i	Harm estimator's predicted probability that action i is harmful
y_i	True label of action i (1 = harmful, 0 = benign)
τ	Block threshold on p_i
u, p	Unprivileged and privileged groups of a protected attribute

1. Security metrics

Attack success rate (ASR). Share of attack cases where the attacker's goal was achieved, judged from the environment state (money moved, file read), not the model's text. Report it overall, per attack type and per MCP stage (planning, invocation, response).

$$\mathrm{ASR} = \frac{\text{number of successful attack cases}}{N_{att}}$$

Absolute and relative risk reduction. How much of the baseline attack surface the gate removes.

$$\Delta\mathrm{ASR} = \mathrm{ASR}_{base} - \mathrm{ASR}_{gate} \qquad \mathrm{RRR} = \frac{\mathrm{ASR}_{base} - \mathrm{ASR}_{gate}}{\mathrm{ASR}_{base}}$$

Privilege-bypass rate (PBR). FinVault-style: share of escalation attempts that actually executed beyond the granted scope.

$$\mathrm{PBR} = \frac{\text{actions executed beyond granted scope}}{\text{privilege escalation attempts}}$$

Data exfiltration rate (DER). Share of exfiltration attempts where protected data (account numbers, KYC documents, keys) left the trust boundary.

$$\mathrm{DER} = \frac{\text{cases where protected data left the boundary}}{\text{cases attempting exfiltration}}$$

2. Utility metrics

Benign utility (BU) and performance under attack (PUA). Task completion without and with attacks present; PUA is MSB's definition.

$$\mathrm{BU} = \frac{\text{benign tasks completed}}{N_{ben}} \qquad \mathrm{PUA} = \frac{\text{user tasks completed under attack}}{\text{user tasks run under attack}}$$

Utility retention (UR). Share of baseline utility the gate keeps; a suggested target is 0.9 or above.

$$\mathrm{UR} = \frac{\mathrm{BU}_{gate}}{\mathrm{BU}_{base}}$$

Net Resilient Performance (NRP). MSB's combined score: task completion under attack, discounted by attack success. Higher is better; report both NRP and its change.

$$\mathrm{NRP} = \mathrm{PUA} \times (1 - \mathrm{ASR}) \qquad \Delta\mathrm{NRP} = \mathrm{NRP}_{gate} - \mathrm{NRP}_{base}$$

Worked example with illustrative numbers: baseline PUA 0.70 and ASR 0.40 give NRP 0.42; gated PUA 0.65 and ASR 0.05 give NRP 0.6175. That is ΔNRP +0.20 and RRR 87.5%, a small utility cost for a large security gain. Formulas for ASR, PUA and NRP follow MSB section 5.2.

3. Gate decision quality

Treat every gate decision as a classification against the true label, then read the confusion matrix.

Precision, recall, false-positive and false-negative rates. Recall is the violation recall; FPR is the share of legitimate banking actions the gate wrongly stops.

$$\text{Precision} = \frac{TP}{TP+FP} \quad \text{Recall} = \frac{TP}{TP+FN} \quad \text{FPR} = \frac{FP}{FP+TN} \quad \text{FNR} = \frac{FN}{TP+FN}$$

F-beta score. Use β = 2 in BFSI, which treats recall as twice as important as precision because a missed fraudulent transfer costs more than a false block.

$$F_\beta = \frac{(1+\beta^2)\cdot \text{Precision}\cdot \text{Recall}}{\beta^2\cdot \text{Precision} + \text{Recall}}$$

Matthews correlation coefficient (MCC) and balanced accuracy. Both stay honest when benign actions far outnumber harmful ones.

$$\text{MCC} = \frac{TP\cdot TN - FP\cdot FN}{\sqrt{(TP+FP)(TP+FN)(TN+FP)(TN+FN)}} \qquad \text{BalAcc} = \frac{1}{2}\left(\frac{TP}{TP+FN} + \frac{TN}{TN+FP}\right)$$

AUROC and AUPRC. Areas under the TPR-versus-FPR curve and the precision-recall curve as τ sweeps from 0 to 1. Prefer AUPRC when harmful actions are rare.

4. Escalation and human oversight

These show whether human review is used sparingly and on the right cases.

$$\text{ER} = \frac{\text{escalated actions}}{\text{all actions}} \quad \text{EP} = \frac{\text{escalations confirmed risky}}{\text{escalated actions}} \quad \text{HOR} = \frac{\text{reviewer reversals}}{\text{escalated actions}}$$

Also report reviewer load as escalations per 1,000 actions. A high override rate (HOR) means the gate's escalation rule is miscalibrated.

5. Harm-estimator calibration and threshold (LawZero-style)

A LawZero-style guardrail is only trustworthy if its probabilities are calibrated, so measure calibration before setting τ.

Brier score and log loss. Mean squared and log error of predicted harm probabilities; lower is better.

$$\text{Brier} = \frac{1}{N}\sum_{i=1}^{N}(p_i - y_i)^2 \qquad \text{LogLoss} = -\frac{1}{N}\sum_{i=1}^{N}[y_i \log p_i + (1-y_i)\log(1-p_i)]$$

Expected calibration error (ECE). Split predictions into M bins (M = 10 is common); in each bin compare the observed harmful share acc(B_m) with the mean predicted probability conf(B_m).

$$\text{ECE} = \sum_{m=1}^{M}\frac{|B_m|}{N}\left|\text{acc}(B_m) - \text{conf}(B_m)\right|$$

Decision rule and cost-optimal threshold. For a calibrated estimator, the threshold that minimizes expected cost depends only on the cost of a false block c_FP and a missed harmful action c_FN.

$$\text{block}(a) = 1[P(\text{harm} \mid a, \text{context}) > \tau] \qquad \tau^* = \frac{c_{FP}}{c_{FP}+c_{FN}}$$

Example: if a missed fraudulent transfer costs 20 times a false block, τ* = 1/21 ≈ 0.048, so the gate should block at quite low harm probabilities.

Expected cost with escalation. When human review has its own cost c_esc, pick τ on a validation split by minimizing total cost; E(τ) is the number of escalations.

$$C(\tau) = c_{FN} \cdot FN(\tau) + c_{FP} \cdot FP(\tau) + c_{esc} \cdot E(\tau)$$

Three-way decision. Two thresholds turn the estimator into allow, escalate or block:

- Allow if p ≤ τ_low.
- Escalate to a human if τ_low < p ≤ τ_high.
- Block if p > τ_high.

6. Authorization and least privilege

These show the identity and policy layers enforce delegation and least privilege, independent of any attack benchmark.

Delegation coverage (DC) and scope violation rate (SVR). DC should be 100%; SVR counts attempts, and executed violations should be zero with the gate on.

$$\mathrm{DC} = \frac{\text{tool calls with a valid delegation token}}{\text{all tool calls}} \qquad \mathrm{SVR} = \frac{\text{calls attempted outside granted scope}}{\text{all tool calls}}$$

Privilege utilization (PU) and over-privilege ratio (OPR). Low OPR means the granted scopes are close to what tasks actually need.

$$\mathrm{PU} = \frac{|\text{permissions used}|}{|\text{permissions granted}|} \qquad \mathrm{OPR} = 1 - \mathrm{PU}$$

Policy coverage (PC). Share of exposed tools governed by at least one explicit allow or deny rule.

$$\mathrm{PC} = \frac{\text{tools with at least one explicit policy}}{\text{tools exposed to the agent}}$$

7. Fairness (credit and lending tools)

Here ŷ = 1 is the favourable outcome (loan approved, transaction allowed), u is the unprivileged group and p the privileged group.

Disparate impact (DI) and statistical parity difference (SPD). DI should be at least 0.8 (the four-fifths rule); SPD should be near 0.

$$\mathrm{DI} = \frac{P(\hat{y}=1 \mid A=u)}{P(\hat{y}=1 \mid A=p)} \qquad \mathrm{SPD} = P(\hat{y}=1 \mid A=u) - P(\hat{y}=1 \mid A=p)$$

Equal opportunity difference (EOD) and average odds difference (AOD). Both should be near 0.

$$\mathrm{EOD} = \mathrm{TPR}_u - \mathrm{TPR}_p \qquad \mathrm{AOD} = \tfrac{1}{2}[(\mathrm{FPR}_u - \mathrm{FPR}_p) + (\mathrm{TPR}_u - \mathrm{TPR}_p)]$$

Gate block-rate parity (BRP). Checks the gate itself does not block one customer segment (for example rural or regional-language users) more than another; target close to 1.

$$\mathrm{BRP} = \frac{\text{block rate for segment } u}{\text{block rate for segment } p}$$

8. Operational and audit

Latency overhead. Report p50, p95 and p99 of the added time per tool call, and the overhead ratio.

$$\Delta t = t_{gate} - t_{base} \qquad \text{Overhead} = \frac{\Delta t}{t_{base}}$$

Audit completeness (AC). Share of decisions logged with every required field: who, what tool and arguments, data provenance, rule or score that fired, decision, timestamp. Target 100%.

$$\text{AC} = \frac{\text{decisions logged with all required fields}}{\text{all decisions}}$$

Also time incident reconstruction: minutes from an incident ID to a full decision trace.

9. Compliance

HICS (Harmful Instruction Compliance Score). Use the definition in the CNFinBench paper rather than a re-derived version. Response non-compliance rate follows FinGuard's query- and response-level labels.

Regulatory control coverage (RCC). Share of controls in the regulatory matrix that have passing evidence from the POC.

$$\text{RCC} = \frac{\text{mapped controls with passing evidence}}{\text{mapped controls}}$$

10. Statistical reporting

Rates from a few hundred cases are noisy, so every rate needs an interval and every baseline-versus-gate comparison needs a test.

Wilson 95% confidence interval for a proportion $\hat{p}$ over n cases, with z = 1.96:

$$\frac{\hat{p} + \frac{z^2}{2n} \pm z\sqrt{\frac{\hat{p}(1-\hat{p})}{n} + \frac{z^2}{4n^2}}}{1 + \frac{z^2}{n}}$$

McNemar's test for paired runs on the same cases, where b = cases the attack succeeded only in baseline and c = cases it succeeded only with the gate. Compare against χ^2 with 1 degree of freedom (3.84 at p = 0.05).

$$\chi^2 = \frac{(|b-c|-1)^2}{b+c}$$

For NRP and ΔNRP, report mean ± standard deviation over at least 3 seeds and a bootstrap 95% interval from 1,000 resamples of cases.

Results template by governance level

Fill one row per dataset and level; report ± values as 95% intervals.

Dataset	Level	ASR	BU	PUA	NRP	FPR	Recall	Escalation rate	p95 latency (ms)
AgentDojo banking	Off								
AgentDojo banking	Low								
AgentDojo banking	Medium								
AgentDojo banking	High								
FinVault subset	Off								
FinVault subset	Low								
FinVault subset	Medium								
FinVault subset	High								
MSB (3 attacks)	Off								

Dataset	Level	ASR	BU	PUA	NRP	FPR	Recall	Escalation rate	p95 latency (ms)
MSB (3 attacks)	High								

Hypotheses to test

- ASR falls at each level, with the largest drop between Low and High on injection and pretext attacks.
- Benign utility stays within a few points of Off at Low and Medium; High may cost more if τ is set too strictly.
- Escalation rate is highest at Low (crude keyword escalation) and lowest at High.
- False-positive rate rises from Low to Medium (more rules) and is controlled at High by threshold tuning.
- Gate latency grows with level; High must stay within an agreed p95 budget.

Regulatory alignment matrix

Each gate control maps to an expectation regulators already state, which lets the POC's metrics double as compliance evidence.

Gate control	RBI FREE-AI (Aug 2025)	MAS AIRG (consultation, Nov 2025)	EU AI Act	NIST AI RMF	Evidence metric
Agent identity and delegated scopes	Accountability sutra; board-approved AI policy	Accountable owner per AI system; AI inventory	Human oversight duties for high-risk systems	Govern	% of tool calls with a valid delegation token
Deny-by-default tool policies	AI-specific risk evaluation in product approval	Proportionate controls by risk materiality	Risk management system	Manage	ASR, privilege-bypass rate (FinVault)
Harm estimator with threshold	Safety and resilience principles	Testing and validation for higher-risk use	Accuracy, robustness, cybersecurity	Measure	Calibration error, ASR-utility curve
Human escalation	Human oversight of AI decisions	Enhanced human oversight for credit and advice	Article 14 human oversight	Manage	Escalation rate, reviewer agreement
Immutable audit log	AI incident reporting; disclosures	Monitoring and auditability across lifecycle	Record-keeping and logging	Govern / Measure	Log completeness, time to reconstruct an incident
Fairness checks on credit tools	Fairness sutra	Fairness (FEAT principles)	Credit scoring listed as high-risk	Measure	Disparate impact, equalized-odds gap

Sources: RBI FREE-AI report (7 Sutras, 26 recommendations under 6 pillars); MAS consultation coverage. The sutra names in the RBI column are paraphrased; check them against the report's chapter 4 before citing. Singapore's IMDA Model AI Governance Framework for Agentic AI (Jan 2026) is a further reference for agent-specific controls.

Governance levels and regulatory expectations

Level	Evidence it produces	Regulatory fit
Low	Decision trace, audit log, human escalation	Basic accountability and record-keeping; not sufficient alone for high-risk credit or payment agents
Medium	Delegation scopes, approvals, holds, step-up records	Human oversight and access-control expectations in RBI FREE-AI and MAS AI risk guidance
High	Calibrated risk scores, provenance, fairness checks, hash-chained log	Testing, validation, fairness and auditability expected for higher-risk use cases; aligns with EU AI Act high-risk duties

Build roadmap

Phase	Weeks	Scope	Exit criterion
0 · Fix Low	1	Restore auth and API keys; namespace context; deny by default; real redaction; persistent append-only log; escalation that releases actions	Reproduced flaws no longer occur
1 · Build Medium	2–3	Level parameter on /evaluate; step-up, constrain, defer, dual control, dry-run, allow-and-flag; delegation tokens; BFSI rule pack; tool allow-list	Scenarios B3, F1, F2, I1, I2 behave as specified at Medium
2 · Build High	3–5	Harm estimator returning P(harm) with calibration; provenance tagging; tool-metadata pinning; revoke and compensate	Scenarios B1, B2, F3, I3 behave as specified at High; ECE reported
3 · Demo harness	5–6	Dataset adapters (AgentDojo, FinVault, MSB); four run modes; OpenTelemetry traces; metrics panel and level comparison	Results table filled for all datasets and levels
4 · Write-up	7	Side-by-side demo script; paper draft	Demo rehearsed; draft complete

Caveats

- The FinVault and MSB repositories were not opened while preparing this document; confirm setup and licences before relying on them.
- MSB's public tool configurations include third-party credentials; use your own keys and isolate those servers.
- LawZero's Scientist AI is not available as a model; High governance imitates the guardrail pattern with a calibrated classifier or LLM judge.
- Scenario outcomes per level and the hypotheses are design expectations, to be confirmed by the demo runs.
- The Klover article that started this research lists several references that could not be verified; cite primary sources only.
- Approximate dataset sizes marked earlier were written from memory and should be checked on each repository.

Sources

Pages opened while preparing this document:

- Bengio et al., Superintelligent Agents Pose Catastrophic Risks: Can Scientist AI Offer a Safer Path?
- LawZero, Safety from Honesty in a Disinterested AI Predictor
- LawZero press release on the Scientist AI safety case
- Bengio, Introducing LawZero
- LawZero (Wikipedia)
- South et al., Authenticated Delegation and Authorized AI Agents
- Shi et al., Progent
- Debenedetti et al., Defeating Prompt Injections by Design (CaMeL)
- Chen, Kang & Li, ShieldAgent
- Andriushchenko et al., AgentHarm (ICLR 2025)
- Zhang et al., MCP Security Bench (ICLR 2026)
- MSB dataset on Hugging Face
- Wang et al., MCPTox (AAAI 2026)
- Yang et al., FinVault
- Ding et al., CNFinBench
- FinGuard

- RBI FREE-AI press release
- RBI FREE-AI Committee Report
- MAS AI Risk Management Guidelines consultation summary
- Chambers Fintech 2026: Singapore (MAS and IMDA agentic framework)
- Klover.ai, Responsible by Design (reviewed; see Caveats)
- Debenedetti et al., AgentDojo (arXiv 2406.13352)
- Yang et al., FinVault paper (HTML)
- MCP Security Bench benchmark summary
- PromptArmor (AgentDojo suite sizes)
- MemoryGate repository (Embergroundagents/Agentflow.ai)