

Chameleon

One codebase serving many separately branded consumer front-ends — adding a new client brand is a database row, not a copy of the project.

LIVE DEMO

chameleon-gray.vercel.app

SOURCE CODE

github.com/adilet0212/chameleon




Foundry Athletic

Coached strength training in groups of twelve or fewer.



Northaven Motors

Every vehicle inspected on a 210-point checklist before it is listed.



Rook & Ridge

Coffee roasted in small lots, a short walk from wherever you are.



The three storefronts on the live site — different photography, typefaces, palettes and page structures, with no per-brand code between them.

WHAT IT DOES

All three storefronts above are the same application. Each has its own colours, typefaces, layout and web addresses, and a button on screen switches between them instantly — but nothing about any individual brand is written into the code. The differences are stored in a database and applied when the page is requested, so a company running many client brands can add another without duplicating and re-maintaining the software.

All three brands are invented for this project. Photography is free-licence stock; some frames incidentally show real production vehicles. No affiliation is implied.

MEASURED — DATABASE INDEX

Product lookup across **15,036 rows**, with and without a composite index on (tenantId, slug).

Query time in database	Without	With
50th percentile	0.782 ms	0.041 ms
95th percentile	1.001 ms	0.048 ms

19x faster at the 50th percentile — the query plan changes from scanning and discarding 5,011 rows to a direct index lookup. Measured, not estimated: 350 timed runs plus 120 EXPLAIN ANALYZE samples. Full output in the repo.

HOW IT IS BUILT

- **Next.js 16** (App Router, server components), TypeScript
- **PostgreSQL** via Prisma — normalised schema, brand data keyed by tenant
- **Tailwind v4** — one design system, per-brand design tokens
- **Playwright** — 28 end-to-end tests on desktop and mobile, all passing
- Deployed on **Vercel**; Lighthouse mobile **100** accessibility, best practices and SEO

TWO TESTS THAT MATTER MOST

One brand's page can never render another brand's data, and one brand's item address returns "not found" under a different brand. Both are enforced by the database schema, and both are checked automatically on every run.

WHY I BUILT IT

Shipping high-craft branded experiences for many different clients out of one team is a real engineering problem, and the tempting solution — fork the codebase per client — is the one that hurts two years later. I wanted to build the version that does not fork. I built it in one evening for this conversation, and I would rather show something narrow and finished, with numbers I measured, than something broad and half-working.

Adilet Masalbekov

Software Developer

(437) 473-1202

amasalbekov12@gmail.com

github.com/adilet0212