

# Chameleon

One codebase serving many separately branded consumer front-ends — where adding a new client brand is a database row instead of a copy of the project.

## LIVE DEMO

[chameleon-gray.vercel.app](https://chameleon-gray.vercel.app)

## SOURCE CODE

[github.com/adilet0212/chameleon](https://github.com/adilet0212/chameleon)

## WHAT IT DOES

The demo runs three storefronts — a coffee roaster, a car dealership and a fitness studio. Each has its own colours, typefaces, page layout and web addresses, and a button on screen switches between them instantly.

All three are the same application. Nothing about any individual brand is written into the code; the differences are stored in a database and applied when the page is requested. That means a company running many client brands can add another one without duplicating and re-maintaining the software.

All three brands are invented for this project. Photography is free-licence stock; some frames incidentally show real production vehicles. No affiliation is implied.

## MEASURED — DATABASE INDEX

Product lookup across **15,036 rows**, with and without a composite index on (`tenantId`, `slug`).

| Query time in database | Without  | With            |
|------------------------|----------|-----------------|
| 50th percentile        | 0.782 ms | <b>0.041 ms</b> |
| 95th percentile        | 1.001 ms | <b>0.048 ms</b> |

**19x faster** at the 50th percentile. Query plan changes from scanning and discarding 5,011 rows to a direct index lookup. Measured, not estimated — 350 timed runs plus 120 EXPLAIN ANALYZE samples against Neon Postgres 17. Full output is in the repository.

## HOW IT IS BUILT

- **Next.js 16** (App Router, server components), TypeScript
- **PostgreSQL** via Prisma — normalised schema, brand data keyed by tenant
- **Tailwind v4** — one design system, per-brand design tokens
- **Playwright** — 28 end-to-end tests on desktop and mobile, all passing
- Deployed on **Vercel**
- Lighthouse mobile — **100** accessibility, best practices and SEO; 85 performance

## TWO TESTS THAT MATTER MOST

One brand's page can never render another brand's data, and one brand's item address returns "not found" under a different brand. Both are enforced by the database schema, and both are checked automatically on every run.

## WHY I BUILT IT

Shipping high-craft branded experiences for many different clients out of one team is a real engineering problem, and the tempting solution — fork the codebase per client — is the one that hurts two years later. I wanted to build the version that does not fork.

I built it in one evening specifically for this conversation, and I would rather show something narrow and finished, with numbers I actually measured, than something broad and half-working.

