Daak

Daak and 0G: the tracks we enter, and what is built

# 0G makes the decision at every bus stand: is this the right parcel, still sealed, and may the driver be paid

In 60 seconds

1. The phone is the body: NFC, camera, GPS and the person at the bus stand. 0G is the brain at each checkpoint.
2. The lid photo goes to a sealed vision model in a TEE, in private mode, so it can never fall back to an unsealed one. Its answer moves money: green releases that driver's pay, held stops it.
3. Every decision is written to 0G Storage with its request id, and each booking pays its own share of the checks into Daak's own 0G compute account.

Tracks

**Physical AI**
$2,500

**Agents That Pay for Themselves**
$1,000

Daak enters three partners, the event's limit: Hedera, 0G and Arkiv (with Swarm).

## What the track asks, and where Daak stands

| | | |
|---|---|---|
| A 0G call inside the decision loop | The handoff API sends the lid photo to 0gm-1.0-35b-a3b on Intel TDX and acts on the verdict | Live |
| An episode log on 0G Storage with a request id per decision | Each decision (verdict, reason, request id, TEE flag, photo hash, HCS id) is one record on 0G Storage | Live |
| A live hardware demo or a replayable simulation | Live on an Android phone at the stand; KNP-1204's record replays the whole day | Live |
| A safe-stop that never fakes a decision | No answer in 20 s means recorded, not checked, and no payment; a labelled backup can only hold, never release | Live |
| Money in, credit landing in the agent's compute account | 2% of each booking fee in dINR on Hedera, and the same value in 0G into Daak's Direct account, both ids on HCS | Live |
| Inference paid from that account, with tx hashes and request ids | Daak asks the sealed provider from its own account first and verifies the TEE signature; Router credit is the fallback | In progress |
| No manual top-up, a spend cap, graceful degradation | Top-ups come from bookings, capped at 1 0G a day; low funds fall back to the Router, then the safe-stop | Live |

## Every piece, where it lives, and its proof

| | | |
|---|---|---|
| Sealed vision check | 0G Router, X-0G-Provider-Trust-Mode: private, pinned to the TEE provider 0xf4FB...0B250; reads the code on the lid and the parcel's state<br>`web/lib/zg.ts, web/app/api/handoff` | KNP-7115 matched, chatcmpl-b30615d2..., 9.2 s |
| Refusal when it is wrong | The same photo checked against KNP-9999 was refused: "the code on the parcel is KNP-7115" | chatcmpl-ff00a134..., 7.2 s |
| Decision records on 0G Storage | Every decision at every checkpoint, whatever it was<br>`web/lib/zgstore.ts` | First record, root 0xe803a6bf... |
| Daak's own compute account | 0G Direct from Daak's wallet 0x575F...8901; each answer's TEE signature verified<br>`web/lib/compute.ts` | Account opened, 3 0G |
| Bookings pay for the checks | 44 paise of dINR on Hedera and 0.032 0G into the compute account for the first booking<br>`computeEarmark in web/lib/rules.ts` | 0G top-up tx |
| Recheck after an outage | "Recheck with 0G" pulls the encrypted photo from Swarm and asks again; a green answer releases the pay<br>`web/app/api/recheck` | KNP-1204: 3 stops rechecked 11:28, paid 11:44 |
| ID reading, sealed | 0G reads a driver's ID photo (type, name, last 4, bus licence class, masking, edits) for the operator; only pass or fail goes public<br>`web/app/api/kyc/[uid]/read` | |

## Honest limits

- The only sealed vision provider on mainnet has been unhealthy since about 12:40 on 6 November (still down at 16:23), so live checks fall back to the safe-stop. The first self-paid sealed check receipt waits for it.
- The exchange from rupees to 0G is the one step not on chain; in production a payment partner buys the 0G.
- Direct needs 3 0G to open an account and 1 0G per provider, which is a lot to lock up for one agent.

## To ask the mentor

- Is a second sealed vision provider coming, or can we fail over to a sealed text model with a vision preprocessing step?
- For an agent paying for itself, do you prefer Router credit or Direct, and can a server deposit into a Router account?
- How should a verifier check the TEE attestation end to end, beyond the provider's signature on each answer?
- Is one 0G Storage record per decision the right grain for an episode log, or would you batch a day?