















Comment	Description	Designator	Footprint	LibRef	Quantity
10uF		C1	SMD Capacitor 0603	Capacitor	1
22uF		C2, C17	SMD Capacitor 0603	Capacitor	2
2.2uF		C3	SMD CAP 0402	Capacitor	1
4.7uF		C4, C9, C12, C20, C27, C29	SMD CAP 0402	Capacitor	6
0.1uF		C5, C7, C10, C13, C15, C18	SMD CAP 0402	Capacitor	6
0.01uF		C6, C8, C11, C14, C16	SMD CAP 0402	Capacitor	5
0.047uF		C19	SMD CAP 0402	Capacitor	1
4.7uF		C21	SMD Capacitor 0603	Capacitor	1
.1uF		C22	SMD CAP 0402	Capacitor	1
100nF		C23, C25, C26, C28, C30, C32	SMD CAP 0402	Capacitor	6
1uF		C24	SMD CAP 0402	Capacitor	1
10nF		C31	SMD CAP 0402	Capacitor	1
LED 0603	LTST_C195TBJRKT	D1	LED_0603	LED 0603	1
	_		Coax Direct Solder		
Coax Connector		J1	ThroughHoles 2pin smd pad for LED	Coax Connector	1
2 Pin Connector		J2	connector	2 Pin Connector	1
Ferrite Bead		L1, L2	LQM21PN2R2MC0D	Ferrite Bead	2
Ferrite Bead		L3, L4, L5	BLM18KG601SN1D	Ferrite Bead	3
Ferrite Bead		L6	CIG21L4R7MNE	Ferrite Bead	1
Ferrite Bead		L7	CBC3225T101MR	Ferrite Bead	1
N Channel MOSFET	N Channel MOSFET	Q1	NTK3134N	N Channel MOSFET	1
500		R1	SMD RES 0402	Resistor	1
100k		R2, R6	SMD RES 0402	Resistor	2
49.9		R3	SMD RES 0402	Resistor	1
10k		R4, R5, R14	SMD RES 0402	Resistor	3
3.3k		R7, R8	SMD RES 0402	Resistor	2
1k		R9, R10, R11	SMD RES 0402	Resistor	3
10		R12	SMD RES 0402	Resistor	1
1.25k		R13	SMD RES 0402	Resistor	1
CNACC COLOR NATOVOSS	CMOS COMPANIATOMORA	S1	CMOS Sensor	CMOS Sensor MT9V032	1
CMO3 Sellsof Wilayous2	CMOS Sensor MT9V032 Buck Step Down Regulator with 3 to 17 V Input and 0.9 to 6 V Output, -40 to 85 degC, 8-Pin WSON (DSG), Green (ROHS &	31	MT9V032_HD	CMO2 Sell201 M134032	1
TPS62172DSGT	no Sb/Br)	U1	DSG8-1600X900TP	TPS62170DSGT	1
TPS62231DRYT	Buck Step Down Regulator with 2.05 to 6 V Input and 1.8 V Output, -40 to 85 degC, 6-Pin SON (DRY), Green (RoHS & no Sb/Br)	U2	DRY6	TPS62231DRYT	1
11 30223151(11	DS90UR913ASERIALIZE	02	WQFN32 for	11 30223151(11	
DS90UR913A	R	U3	DS90UB913A	DS90UR913A	1
LT3092EDD#PBF	200 mA Two-Terminal Programmable Current Source, 0.3 mA Isupply, 8-pin SON (DD-8), -40 to 125 degC, Pb-Free	U4	LT-DD-8_V	LT3092EDD#PBF	1
DACESTIDEVE	Low-Power, 8-Bit DAC with High-Speed I2C Input, -40 to 105 degC, 6-pin SOT23 (DBV6), Green (RoHS & no	115	TI DRV6 M	DACSS711DPVD	,
DAC5571IDBVR	Sb/Br)	U5	Π-DBV6_M	DAC5571IDBVR	1
OSC_26MHz_EPSON	OSC_26MHz_EPSON	U6	OSC SG_211SCE 26MHz	OSC_26MHz_EPSON	1