

Distributed Systems (Assignment-3):

Problem:

Design and implement a Remote Procedure Call framework to simulate the following: - Implement a single server architecture with support for multiple clients - The server maintains a list of graphs each associated with a distinct identifier. - Clients can request to add a new graph, update an existing graph and query for the total weight of the minimum weight spanning tree of a given graph. - Clients can request to add a new graph using 'add_graph \<graph_identifier> n'. This command will add a new graph on the server with the identifier 'graph_identifier' and 'n' number of nodes. The graph identifier is a string with a maximum length of 10 and it won't already exist. 'n' will be in the range: $1 \leq n \leq 100,000$. - Clients can request to add a new edge in a graph using 'add_edge \<graph_identifier> \<u> \<v> \<w>'. This will add an undirected edge between the nodes **u** and **v** with weight **w**. **u** and **v** are the node numbers of the endpoints of the edge such that $1 \leq u, v \leq n$ and $0 \leq w \leq 10,000$. **n** is the number of nodes in the specified graph. A graph with identifier graph_identifier will already exist. There can be multiple edges and self-loops added to the graph. - Clients can request for the total weight of the minimum weight spanning tree in a graph from the server using 'get_mst \<graph_identifier>'. The client will print the solution the server returns. In case the graph does not have a spanning tree, -1 should be printed. A graph with identifier graph_identifier will already exist. - All values should fit in 32-bit signed integers. - The server should be able to handle multiple clients simultaneously and should also work with clients on other machines. - You are free to use any algorithm for MST

Solution Approach

- Programming language for Client and Server - C++
- Using Apache 'thrift' package for Remote Procedure Calls.
- Create an *interface.thrift* IDL file for thrift compiler to generate the RPC service code. This file will contain the interfaces that will be exposed for the client to perform a remote procedure call to the server. Given below is the IDL file used for current assignment

```
service GraphService
{
    oneway void addGraph(1:string graphId,
                        2:i32 nodeCount)

    i32 addEdge(1:string graphId,
                2:i32 srcNode,
                3:i32 dstNode,
                4:i32 edgeWeight)

    i32 getMSTWeight(1:string graphId)
}
```

On Client Side: - Implement a menu-driven approach for performing all the above operations. A typical menu implemented in the client is as shown below:

```
| Add a Graph      ( Command: add_graph <graph_id_string> N ) |
| Add an Edge     ( Command: add_edge <graph_id_string> <u> <v> <w> ) |
| Get MST Weight  ( Command: get_mst <graph_id_string> ) |
|_____|
|                               "-1" to EXIT                               |
|_____|
Command: _
```

On Server Side: - Use a `std::map<key, value>` as a graph container. The 'key' would be a string to identify the Graph and 'value' would be a pointer to the Graph. - Implement a 'Graph' class encapsulating all the interfaces that can be called from the server. Use Kruskal's algorithm for computing the Minimum Spanning Tree for an undirected graph, using *Union-Find* data structure for better performance.

Environment Details

Operating System: *Mac OSX BigSur 11.2.2* Package Installer : *Homebrew* Compiler : *clang++* RPC Package : *Apache Thrift*

Installation Instructions: - Install CommandLineTools and Homebrew package manager on Mac OSX. Refer [this](#) link for detailed installation steps. - The C++ compiler 'clang++' would come along with the CommandLineTools package. - Using Homebrew package installer install Apache 'thrift' as follows:

```
brew install thrift
```

- Make a note of the include and the dynamic library paths in the Apache 'thrift' installation to update the Makefile. A typical include and library paths would look like:
/usr/local/Cellar/thrift/0.14.0/include
/usr/local/Cellar/thrift/0.14.0/lib
- Update the INCLUDE and LD_LIBRARY_PATH variables in the Makefile accordingly, using the above paths from your installation.

Source Tree

- Given below is the source tree for the current assignment.

```
├─ DS_Assignment3.pdf
├─ Makefile
├─ README.md
├─ bin/
├─ obj/
└─ src/
    ├─ interface.thrift
    ├─ client/
    │   ├─ Client.cpp
    │   ├─ ClientUtils.cpp
    │   └─ ClientUtils.h
    ├─ server/
    │   ├─ Graph.cpp
    │   ├─ Graph.h
    │   ├─ GraphServiceHandler.cpp
    │   ├─ GraphServiceHandler.h
    │   ├─ GraphUtils.cpp
    │   ├─ GraphUtils.h
    │   └─ Server.cpp
    └─ service/
        ├─ GraphService.cpp
        ├─ GraphService.h
        ├─ GraphService_server.skeleton.cpp
        └─ interface_types.h
```

6 directories, 18 files

- 'src/service/' : Directory containing auto generated files from Apache 'thrift' compiler.
- 'src/client/' : Directory containing all the client code & utility files.
- 'src/server' : Directory containing all the server code & utility files.
- Client.cpp : Code to instantiating a client.
- ClientUtils.* : Utility functions for displaying the menu and processing the input commands.
- Server.cpp : Code to instantiating a server.
- Graph.* : A class implementing all the interfaces to create the graph and algorithm for computing Minimum Spanning Tree weight.
- GraphUtils.* : Implementation of Union-Find data structure, used while computing MST.
- GraphServiceHandler.* : A service handler class derived from the RPC service files created by Apache 'thrift' compiler. Used by the server code to execute the RPC function calls.
- Run the command '**make clean; make**' from the parent directory to create the *client* and *server* executable binaries.

Building the *client* and *server* binaries

After updating the Makefile, build the client and server binaries as follows:

```

20173071$ make clean; make
Cleaning the object files and binaries.
rm -f core ./bin/* ./obj/*

Generating interface files.
mkdir -p ./src/service
thrift -out ./src/service --gen cpp ./src/interface.thrift

clang++ -Wall -std=c++11 -I./ -I/usr/local/Cellar/thrift/0.14.0/include -c src/client/Client.cpp -o obj/Client.o
Compiled src/client/Client.cpp successfully.
clang++ -Wall -std=c++11 -I./ -I/usr/local/Cellar/thrift/0.14.0/include -c src/client/ClientUtils.cpp -o obj/ClientUtils.o
Compiled src/client/ClientUtils.cpp successfully.
clang++ -Wall -std=c++11 -I./ -I/usr/local/Cellar/thrift/0.14.0/include -c src/service/GraphService.cpp -o obj/GraphService.o
Compiled src/service/GraphService.cpp successfully.
clang++ -lthrift ./obj/Client.o ./obj/ClientUtils.o ./obj/GraphService.o -o ./bin/client
Linking client objects complete.
To start the "Client" run --> ./bin/client

clang++ -Wall -std=c++11 -I./ -I/usr/local/Cellar/thrift/0.14.0/include -c src/server/Server.cpp -o obj/Server.o
Compiled src/server/Server.cpp successfully.
clang++ -Wall -std=c++11 -I./ -I/usr/local/Cellar/thrift/0.14.0/include -c src/server/GraphServiceHandler.cpp -o obj/GraphServiceHandler.o
Compiled src/server/GraphServiceHandler.cpp successfully.
clang++ -Wall -std=c++11 -I./ -I/usr/local/Cellar/thrift/0.14.0/include -c src/server/Graph.cpp -o obj/Graph.o
Compiled src/server/Graph.cpp successfully.
clang++ -Wall -std=c++11 -I./ -I/usr/local/Cellar/thrift/0.14.0/include -c src/server/GraphUtils.cpp -o obj/GraphUtils.o
Compiled src/server/GraphUtils.cpp successfully.
clang++ -lthrift ./obj/Server.o ./obj/GraphServiceHandler.o ./obj/Graph.o ./obj/GraphUtils.o ./obj/GraphService.o -o ./bin/server
Linking server objects complete.
To start the "Server" run --> ./bin/server

20173071$

```

Execution Run

- Instantiate ***./bin/server*** from one terminal
- Instantiate ***./bin/client*** from another terminal. Multiple client instantiations would require multiple terminals.
- Follow the menu in the client terminals to create the undirected graph and compute the MST weight.
- The log traces are categorized as below:

```

[INFO] -> Informational traces
[RPCQ] -> RPC Request traces
[RPCR] -> RPC Response traces
[ERROR] -> Error traces

```