TANTRA

Put an AI agent in charge of your funnel. Then build the door it has to go through.

Six guardrails from Day 3 of the workshop, with the real files →

A rule in a prompt is a request.

In July 2025 a founder reported that an AI agent deleted his production database during a code freeze. He'd told it not to change anything.

> **"context, not enforced configuration"**
>
> Anthropic's Claude Code docs, on what CLAUDE.md is

Sources: The Register, 21 July 2025; code.claude.com/docs/en/memory.

GUARDRAIL 1

A short brief is the standing order.

CLAUDE.md

```
- **Build as drafts. Never start, send, buy or
delete without approval.**
  - `scripts/api.mjs` refuses those calls
unless you pass `--confirm "<approval>"`.
  - The approval is a line in
`context/approvals.md`. Add a line there only
when the owner has approved that exact action
in this session, in their own words; copy their
words.
  - Launching campaigns happens only on the Day
3 launch task.
```

Ours is 84 lines. Anthropic suggests under 200.

GUARDRAIL 2

One door for every API call.

Every call goes through one script. Anything that sends, launches, buys or deletes is refused without the owner's words.

terminal

```
$ node scripts/api.mjs hubspot DELETE
/crm/v3/objects/contacts/1
api.mjs: refused: this call deletes something.
Ask the owner. Only when they approve it in
their own words, add a line "- <their words>
(YYYY-MM-DD, approves hubspot <what>, <total>)"
to context/approvals.md and pass only their
words with --confirm "<their words>".
```

Every call, and every refusal, lands in one log.

GUARDRAIL 3

Approval is a dated line, in the owner's own words, naming the tool.

context/approvals.md

```
# Approvals

scripts/api.mjs runs a guarded call (send,
launch, buy, delete) only when --confirm equals
the owner's words on one of those lines, and
buys a domain only when that line names it.
Never add a line the owner did not say, and
never reuse a line for a later, different
action.
```

A yes to email never opens the CRM.

GUARDRAIL 4

Keys stay in .env, read by one script, not the agent.

.claude/settings.json

```
    "deny": [
      "Read(./.env)",
      "Edit(./.env)"
    ]
  },
  "hooks": {
    "PreToolUse": [
      {
        "matcher": "Edit|Write",
        "hooks": [
          { "type": "command", "command": "node
\"$CLAUDE_PROJECT_DIR/scripts/guard-env.mjs\""
}
        ]
      }
```

The agent is denied the file. A hook blocks any write to it.

GUARDRAIL 5

Every fact, written once, in one spec.

knowledge/operate.md

`context/spec.md` holds every fact exactly once, worded as a buyer should read it, with currency and time zone: price, guarantee, event date and time, booking link (`d3v5_facts`), plus the offer sentence, the method, the speaker line, the channels and every live address.

3. Hunt for the same fact worded two ways across deliverables (two prices, two titles, two dates). That is the error this step exists to catch.

One place for the price, so two prices get caught before they ship.

GUARDRAIL 6

Two test contacts before any real person.

One who shows up. One who doesn't. Both run the whole flow first.

knowledge/operate.md

```
- A message sent down the wrong branch is a failure, exactly like a message that never went.
```

Watch the one who didn't show. That's where follow-ups silently break.

TANTRA

One honest caveat.

This is a tripwire with a paper trail, not a lock. The log of every call and every refusal is what you read.

OWASP names three causes of the risk. Each guardrail takes one away:

functionality | permission | autonomy

Day 3 of the workshop

The 3-Day AI RevOps Workshop

Next cohort Wed 11 Nov · 11:00 AM ET · three live sessions

You build the engine with us, not notes about it. Link in the comments.