Lab 4: Report Marking Criteria

- The reports for Lab 4 and Lab 5 will be combined into one major report worth 15% of the total grade for this subject. Please submit the report on Canvas. Only one submission is required per group.
- You may work in a group of maximum three members. Your group must be the same for Labs 4 and 5. <u>All group members must attend the same lab session</u>.
- Address the questions in the order as they appear in this document, and in your reports, clearly indicate the section that you are answering.
- Finally, please ensure that the content included in your report is your own intellectual property. Any occurrence of significant plagiarism may result in loss of partial/full credit.

The Lab 4 will contribute a maximum of [110 marks] in your combined Lab 4+5 report.

For the entire report:

- 1. Present results and diagrams clearly with explanations. Plots require a legend, title, x-axis and y-axis labels.
- 2. Have you adjusted all of your simulation parameters to the values as instructed?
- 3. Presentation quality of the Lab 4 report [10 marks]
- 4. Please answer the questions in the order suggested below.

1A: Read the temperature sensor

1. Explain the purpose of this task. In the context of the control system, what is its significance/how will it be used? [1 mark]

1B: Send an input to the Arduino

- 1. Explain the purpose of this task. In the context of the control system, what is its significance/how will it be used? [1 mark]
- 2. A saturation block was supposed to be added. Why should we add this block? What was your choice for the saturation limits, and why? [1 mark]

1C: Estimate the Plant

1. Include your Simulink diagrams, MATLAB scripts and plots [10 marks]

- 2. Explain some advantages and some disadvantages of an empirical model compared to a physics-based model. [2 marks]
- 3. Explain the formula/process you used to calculate τ . Use the variables T_1 and T_0 in your answer. [2 marks]

1D: Open-Loop Simulation

- 1. Include your Simulink diagrams, MATLAB scripts and plots [5 marks]
- 2. Compare the amplitude and the times between the open-loop simulation with the open-loop experiment. Identify major similarities or dissimilarities (if any) [2 marks]

2A: PI Controller Simulation on Simulink

- 1. Show the derivation for your calculated PI parameters [5 marks].
- 2. What ω_n was chosen? What were the calculated PI parameters? [1 mark].
- 3. Include your Simulink diagrams, MATLAB scripts and plots [10 marks].
- 4. Show that the performance criteria has been achieved, in simulation [2 marks].
- 5. For the PI controller structure that you selected, simulate the other PI controller structure that was not investigated and compare/discuss the advantages/disadvantages compared to the structure that was selected for this lab. Use simulation results and theory. [10 marks]
- 6. For the simulation that was NOT implemented in hardware, confirm that the system can reject an OUTPUT step disturbance of -5°C and is robust in the presence of measurement noise using: *Sources: Random Number with mean = 0 and variance = 0.5*. The disturbance can occur at a time of your choice, as long as it clearly supports your argument. [5 marks].

2B: PI Controller on Arduino

- 1. Include your Simulink diagrams, MATLAB scripts and plots [20 marks].
- 2. Identify if/when the control signal was limited by the saturation block either in simulation or in the experiment. [1 mark]
- 3. Explain potential source(s) of noise for this experiment? [2 marks]

- Explain the similarities of this lab experiment with a real-world equipment/appliance. [3 marks]
- 5. For your chosen real-world equipment/appliance, explain:
 - a. The consequences/impracticalities of excessive overshoot. [2 marks]
 - b. The consequences/impracticalities of a long rise time. [2 marks]
 - c. An example of an output disturbance. How would you model this disturbance in a simulation? Why? [5 marks]
- 6. Compare the simulation with the experimental results. Explain key similarities and differences (if any). [5 marks]
- 7. For your experiment or other students' experiments, what could be some sources of differences between the simulation results and the experiment? [3 marks].