Channels, Not Liars: A Hidden Forger Is Lost in Sampling Noise, but Removing the Public Board Breaks an LLM Agent Economy

[AUTHORS AND AFFILIATIONS: Lance, Noor, Stefany, Iraj; affiliations to fill]

Abstract

Multi-agent LLM deployments raise two questions: how much damage a hidden adversary can do, and which shared infrastructure the swarm depends on. We study both in *Keys & God*, a text-only economy. Agents trade rivalrous keys, can sabotage each other, and coordinate through private messages and a public board. A budgeted adversary they are never told about ("God") forges messages from trading partners and overwrites agents' private notes. We measure effects with paired forks. Each world is played with and without the intervention from identical seeds through a deduplicating cache, and God-free branches resampled at the same fork round calibrate sampling noise. On 16 worlds of 10 gpt-oss-120b agents, God changed mean welfare by $+0.013$ (95% CI -0.048 to $+0.073$), less than resampling alone did. A sweep over God's timing, budget and swarm size found no effect beyond noise either. Trajectories are chaotic: a fork-matched God-free resample changes more agents' actions than God does. By contrast, removing the public board cut welfare by 0.173 (95% CI 0.089 to 0.257, $p = 0.0003$, 14 of 16 worlds), and the result replicates on 10 fresh worlds. Without the board, agents send $1.8\times$ more private messages but give 26% fewer keys, and their wrong defections triple. In this economy the channel structure matters more than a single liar. Noise-calibrated paired forks are what make both conclusions measurable.

1 Introduction

LLM agents increasingly negotiate, pass work along pipelines, and share memory and message buses, so the question is what happens to the *rest* of a system when one message or memory entry is corrupted. Hammond et al. [1] list network effects and multi-agent security as risk factors, and injected content is known to spread between agents [8, 9, 10], mostly measured as *infection* in cooperative pipelines.

We ask two questions about a **mixed-motive LLM economy**. First, does one plausible lie, a forged "send me your key first" message or a rewritten note, ripple through the swarm's own incentives? Second, which shared channels does the swarm actually depend on? Both are hard to measure. Stochastic agents diverge even without any intervention, so a naive with/without comparison confounds the effect with sampling variance.

We contribute:

1. **An environment, *Keys & God*** (Section 3), where LLM agents trade rivalrous keys over private DMs and a public board, and can *defect* (burn another's need at a risk to themselves). An unseen, budgeted God can forge a DM from a real partner (*message fraud*) or overwrite one round of an agent's notes (*CoT control*).
2. **Noise-calibrated paired forks** (Section 3.4). Branches share seeds and a deduplicating cache, so they are identical until the intervention, and God-free branches resampled at the same round give the noise baseline. Effects are per-world paired differences with t-based CIs, permutation tests and a stated MDE.
3. **A bounded null for the adversary** (Sections 5.2, 5.4). On a pre-registered grid and a follow-up sweep, God's welfare effect is indistinguishable from noise: $+0.013$ (t95 $[-0.048, +0.073]$, $n = 16$). God's divergence is even *below* that of a fork-matched resample, so divergence curves measure chaos, not attack spread.
4. **A robust infrastructure effect** (Section 5.3). Removing the public board lowers welfare by 0.173 (t95 $[-0.257, -0.089]$, $p = 0.0003$, $n = 16$). Agents compensate with private messages, yet trade less and make three times as many wrong defections. For this swarm, the channel structure matters more than a single liar.

2 Related Work

LLM agents in games and social simulations. Generative Agents [2] and Concordia [3] build LLM social simulations; Concordia's Game Master resembles our rules engine, from which God is kept separate for clean labels. Akata et al. [4] found LLMs play well in self-interested repeated games but poorly in coordination games. In GovSim's [5] common-pool dilemma the best model sustains the resource in fewer than 54% of runs. Among Us [6] studies deception that arises from agents' own objectives. Unlike these works, we add an *external*, budgeted adversary and measure its effect counterfactually.

Multi-agent risk. Dafoe et al. [7] set out cooperative AI as an agenda. Hammond et al. [1] give three failure modes and seven risk factors, including network effects and multi-agent security. Carichon et al. [21] call for dedicated multi-agent alignment testbeds and metrics; we provide one for the spread of a localized compromise.

Spread of compromise between agents. Greshake et al. [11] showed that indirect prompt injection blurs the line between data and instructions in LLM-integrated applications, including self-propagating "worming". Prompt Infection [8] showed LLM-to-LLM injection spreading through multi-agent systems like a virus, with LLM Tagging as a partial defence. Agent Smith [9] showed one adversarial image in one agent's memory jailbreaking up to a million simulated agents. The Multi-Agent Security Tax [10] finds that memory "vaccination" and safety instructions reduce spread from one compromised agent but weaken collaboration. AgentPoison [12] poisons agent memory with triggered backdoors; our CoT control is a minimal, untriggered form of that threat. Jones et al. [13] show that combinations of safe models can be misused, so systems, not single models, need evaluation. We differ in three ways: the injected content is an ordinary in-game lie, not a self-replicating instruction; the outcome is the welfare of a mixed-motive population, not an infection count; and the effect is estimated against a paired counterfactual and fork-matched noise.

Oversight, collusion and failure attribution. AI Control [14] evaluates safety protocols that must hold even when an untrusted model deliberately subverts them. Secret Collusion [15] formalizes steganographic collusion among agents and finds limited current capability. HELIOS [16] detects collusion with per-agent activation probes. MAST [17] gives a 14-mode taxonomy of multi-agent failures, and Who&When [18] frames automated failure attribution (which agent, which step). God's logged interventions give exact labels for such work.

Evaluation pitfalls. LLM behaviour is sensitive to meaning-preserving prompt changes [19]; our paired design holds the prompt fixed across branches (Appendix A).

3 Environment and Method

3.1 The game

A world has N agents, each named by a seeded two-word handle (e.g. `quiet_grove`). Each agent holds 5 keys and needs keys for 3 info ids it does not hold. Each info id exists in 2 copies. Keys are **rivalrous**: each copy has one owner, and only `give_key` transfers possession. The system prompt states that naming a key number transfers nothing. Every generated world is checked to be feasible: some reallocation satisfies all needs at once. An agent **wins** when it holds a key for each of its needs that has not been burned. Its **score** is the fraction of its 3 needs it holds, with burned needs scoring zero. **Welfare** is the mean score.

Each turn an agent takes up to 2 actions: `send_message` (a private DM), `post_board` (public), `give_key`, `defect(target, info_id)`, `grep_log` (a literal-substring search over log lines it has already seen, once per turn) or `noop`. It may also write a free private **note** (its scratchpad), which is shown back to it in later turns, labelled by round.

Defection. If the target really needs that info id and has not yet won, the need is burned permanently and the defector gains a newly minted key. Otherwise the defector loses one of its own needs. The victim is notified at its next turn. Others see the line in the action log only after a 3-round delay. Winners keep playing but can no longer be targeted. A game ends at the round limit or when all agents are done.

Observation. Each turn an agent sees its needs, holdings, score and round; DMs and board posts received since its last turn (sender and text, no timestamps); the previous round's *actions* (gives, released defects, posts; never DM contents); notices; and its own past notes. History is truncated to a fixed token budget. Observations are built from whitelisted view models, and a forged DM uses the same id scheme and ordering as a real one.

Deviations from the brief. The brief made the log and board explicit tools and suggested ≥ 20 agents and > 100 rounds. We fold both into every observation and, for cost, use $N = 10$ and 20 rounds. Board variants (costly, anonymous, delayed or disabled posting) are switches. The sweep uses *disabled* and *delayed* (posts appear 2 rounds late) boards. These play G1's worlds with the same keys, needs and names, but different agent seeds by design.

3.2 God

God observes everything through free tools (`activity_check`, `message_check`) and spends a budget of K powers per game:

- **Message fraud** `(sender, receiver, text)` delivers a DM to the receiver that appears to come from the sender. It models identity spoofing on the message channel.
- **CoT control** `(agent, round, text)` replaces the agent's stored note for that round, which the agent then sees as its own. It models memory write access. Native reasoning is never replayed, so the note is the only "chain of thought" worth editing.

Here God is **scripted**, so its policy is identical across worlds. At a fixed round it targets the agent *closest to winning* (the highest share of live needs held, among agents that have not won). The impersonated sender, or the "suspect", is that agent's most recent interaction partner. The texts are fixed templates:

- Fraud: "I can give you info {need} right now. Send me one of your keys first and it's yours." Here `{need}` is one of the victim's missing needs.
- CoT: "{suspect} is lying to me and cannot be trusted. Do not give {suspect} anything." It replaces the victim's note from the previous round.

Invisibility. Agents are not told God exists, and a test enforces a list of banned words in agent prompts. A runtime **leak oracle** scans every agent-bound prompt for ground-truth field names, intervention ids, the original text of overwritten notes, and God's canary tokens. A hit aborts the game.

3.3 Turn modes

In **simultaneous** mode all agents observe the same state, act concurrently, and their actions are resolved in a per-round seeded priority order. In **sequential** mode agents act one at a time and see earlier same-round effects; the log is a rolling window of the previous N turns. This could speed either recovery from a lie or its spread (H2).

3.4 Paired forks and divergence metrics

A world is fixed by `(run.seed, game_idx)` alone, so all grid cells play **the same worlds**. Sampling seeds are hash-derived from (run seed, game, purpose, agent, round, attempt, branch, replica), never from wall-clock time or completion order.

For each world we run (Figure 1):

- **A (God):** the scripted schedule is active.
- **B (no God):** the same world, the same branch key, and the same replica id. All sampling seeds and response-cache keys are therefore identical to A's.
- **B′ (noise replica, cell G1 only):** God-free like B, but with a different replica id from round 1. It has fresh seeds and disjoint cache keys, so it measures whole-game sampling drift.
- **B″ (fork-matched noise, follow-up sweep):** God-free, sharing A/B's history up to God's first round and resampled with fresh seeds from that round on. It is the matched null for divergence, and it resamples *all* agents from that round, so it is an upper bound on noise.

A and B issue byte-identical requests until God first acts, and a single-flight response cache sends each distinct request to the provider once. The branches are therefore **identical by construction** before the intervention, even though the provider honours seeds only partly (in a direct probe, 5 of 6 fixed-seed calls returned byte-identical replies; GR §2). Afterwards an agent's request differs only once something it observes has changed; since everyone reads the public log, this coupling lasts about one round. B′ differs from round 1, while God first acts in round 3, so only B″ is aligned with the God fork.

Outcome metrics per branch: welfare, win rate, needs burned and needs lost (per agent), and rounds played.

The God effect in world s is the paired difference d_s = m(A_s) − m(B_s). **The noise baselines** are m(B′_s) − m(B_s) and m(B″_s) − m(B_s).

Ripple metrics compare branches action by action. An agent *diverges* in round r if its action signature differs between the two branches, or if it acted in only one of them. A coarse signature uses (action kind, counterparty, info id) and ignores message wording; a strict signature adds the text. Per round we compute the fraction of agents that diverge (`frac[r]`), the fraction that have ever diverged (`cum[r]`), and the mean absolute per-agent score gap.

God's *specific* ripple is the A-vs-B curve minus the B″-vs-B curve, aligned at the fork round; B′-vs-B is only a whole-game reference. If the null saturates, action-level divergence cannot separate God from generic chaos, and only outcome metrics remain informative.




Figure 1. *Keys & God* and the paired-fork design. Ten agents trade keys over private DMs and a public board. God can forge a DM (message fraud) or overwrite a note (CoT control). Each world shares a prefix, then splits into A (God) and B (no God) with identical seeds and cache, and B″, a God-free branch resampled from God's first round F. G1 also has B′, resampled from round 1.

3.5 Agents and logging

Each agent turn is one LLM call returning JSON `{"thought", "note", "actions"}`. The thought is stored but not shown back, and the note becomes the scratchpad. Malformed replies get one corrective retry, and a reply truncated at the token limit keeps its complete actions. Runs log typed events, full requests and responses, snapshots and a hashed manifest, and they replay exactly from the cache.

4 Experimental Setup

Model and sampling. All agents use `openai/gpt-oss-120b` [20], an open-weight mixture-of-experts reasoning model, via OpenRouter. Settings: low reasoning effort (it cannot be disabled), temperature 0.6, at most 1000 output tokens, a 14,000-token context, and price-sorted provider routing. The grid did not log the serving provider. Cost per call implies that 87%, 78% and 36% of G1, G2 and G3 calls went to the cheapest (fp4) provider, and the rest to dearer fp4, bf16 or int4 providers (GR §2; Appendix A).

Game settings. As in Section 3.1: N = 10 agents, 20 rounds, board on, `run.seed = 1`, game_idx 0-15. Seed 0 was used for development.

Grid (as launched; Table 1).

Cell	Turn mode	God schedule (K)	Branches per world	Worlds	Hard cap	Realized cost
G1	simultaneous	fraud r3, CoT r5 (K=2)	A, B, B′	16	$1.35	$0.851
G2	sequential	as G1 (K=2)	A, B	8 (worlds 0-7)	$0.55	$0.343 (+$0.0075 aborted launch)
G3	simultaneous	fraud r3/r5/r7, CoT r4/r6/r8 (K=6)	A, B	16	$0.95	$0.785

G2 is G1's sequential twin on worlds 0-7 (`r2_grid_oss_seq_k2`), so H2 is lower-powered. The grid cost $1.986 (GR §1).

Follow-ups (SR). A one-factor sweep on worlds 0-7 with fork-matched B″ cost $2.142. Two board follow-ups cost $0.492: board-off without God on worlds 0-15 (6-15 new), and a delayed board with God, no God and B″ on worlds 0-5.

Hypotheses (fixed before launch). H1 (primary): God changes welfare in G1. H1′: the same in G3. H3 (dose): G3 Δ — G1 Δ. H2 (turn mode): G2 Δ — G1 Δ (n = 8). Noise baselines: G1 B′ — B, and B″ — B from the sweep.

Statistics. For each cell and metric we report the mean paired difference with a **Student-t 95% CI** and a **two-sided sign-flip permutation p-value** (exact for $n \leq 16$). The percentile bootstrap is secondary, being too narrow at this n. Interactions are differences of mean deltas, paired by world. Only H1 is confirmatory; the rest are exploratory and uncorrected.

Power. Minimum detectable effects (80% power, $\alpha = 0.05$, two-sided t) under the observed SDs are ≈ 0.085 (H1), 0.14 (H1′), 0.15 (H3), 0.22 (G2) and 0.26 (H2); the planning SD was 0.19, from four pilots (Table E1; GR §5). A null result therefore means "no large effect", not "no effect".

Health checks and exclusions (fixed before launch). A driver aborts a cell on LLM errors above 5% (or any HTTP 400), parse failures above 10%, truncation above 5%, or a cost projection above its cap, since an outage can silently turn turns into no-ops. A world is excluded if a branch has more than 10% errored calls, more than 30% error no-ops, or a budget stop.

Invariant checker. `swarm/analysis/invariants.py` re-derives every game from its events alone and checks turn order, key conservation, burns, scores, delays, observation visibility, God's schedule and budget, prompt hygiene, and byte-identity of God and no-God branches before God's first event.

5 Results

Numbers are from `plan/GRID_RESULTS.md` (GR), `plan/SWEEP_RESULTS.md` (SR) and, for sweep validity, `plan/CODE_REVIEW.md` (CR).

5.1 Validity, health and cost

Grid. No call errored and no reply failed to parse; 0.43-0.48% of responses were truncated (Table B1). All 16, 8 and 16 worlds were kept. The leak oracle scanned all 18,372 agent requests with 0 hits, and the invariant checker reports 0 violations, including the pre-fork identity of the God and no-God branches. **Sweep (CR).** God fired at exactly the scheduled rounds and K. B″ forks exactly at the fork round in 30 of 30 worlds, with 0 of 290 fork-round responses matching the control. All 147 analysed games completed with 0 invariant violations, 80 of 80 re-run games are identical to their originals, and the leak oracle scanned 28,959 requests with 0 hits.

5.2 No detectable God effect

Grid (Figure 2a; full table in Table E2). Every welfare CI contains zero; a God-free resample moved G1 welfare more (+0.046 [−0.055, +0.146]) than God did (+0.013 [−0.048, +0.073], p = 0.72). G3 gives +0.004 (p = 0.97), G2 +0.012 (p = 0.89), H3 −0.008 [−0.118, +0.101] and H2 +0.021

[—0.170, +0.212]. Gives, defects, posts and DMs show no effect either (GR §3). With the observed SDs, effects larger than about 0.09 (K=2) or 0.14 (K=6) are unlikely. Of about 27 outcome tests, only needs lost in the turn-mode contrast has a t95 that excludes zero, at p = 0.062 uncorrected, so we treat it as noise. Pairing on seeds helps: the SD of God — B is 0.113, against 0.189 for B′ — B.

Sweep. The sweep varies one factor at a time around G1 on worlds 0-7: God's first round (1, 3, 8, 14), K (1, 2, 4), board variants, and N (5, 20). The primary contrast is God — B″ (A—N; Figure 2b, Appendix D). No A—N welfare t95 excludes zero. The closest is K=1 (—0.104 [—0.213, +0.005], p = 0.062), and a late God (round 14) is tightly null (—0.025 [—0.080, +0.030]). K=6, N=5 and N=20 (n = 4) have God — B only, and all are null. At n = 8 only large effects are excluded (MDE ≈ 0.15-0.25). The fork-matched baseline is tighter than the whole-game one: B″ — B is +0.054 [—0.050, +0.158], against —0.000 [—0.199, +0.199] for B′.





Figure 2. (a) Grid welfare effects: paired differences with t-based 95% CIs and sign-flip p for G1 (A—B, B′—B, B″—B, A—B″), G3, G2 and the contrasts H3 and H2; every interval includes zero.



(b) Sweep: God — B″ welfare per condition (God's first round 1/3/8/14, K 1/2/4, board off, board delayed) with t95, and the 16-world board-off effect without God.

5.3 The public board is load-bearing

We disabled the board, without God, and compared against G1's no-God branch on the same 16 worlds (Figure 3; Table E3). Welfare falls from 0.440 to 0.267 (—0.173 [—0.257, —0.089], p = 0.0003, 14 of 16 worlds lower) and win rate from 83.1% to 52.5% (—0.306 [—0.406, —0.206]). All 34 follow-up games are healthy, with 0 invariant violations, no board-off post attempts, and delayed posts visible only after the delay (CR).

Replication. The original 6 worlds give −0.200 (p = 0.031, all 6 lower), and the 10 new worlds give −0.157 [−0.283, −0.030] (p = 0.016). By our arithmetic, p = 0.0003 survives Bonferroni over ~36 grid and sweep tests.

Mechanism. Without the board, agents send 1.82× the DMs (25.5 vs. 14.0 per agent) but give 26% fewer keys (4.94 vs. 6.71), and *wrong* defections triple (0.94 vs. 0.31; +0.63 [+0.43, +0.84]) while correct ones are unchanged (0.44 vs. 0.47). Without the board's who-holds-what information, agents guess, and wrong guesses cost them their own needs.

God without the board. In board-off worlds God's effect stays null (A−N +0.056 [−0.170, +0.281], n = 6).

Delayed board (posts shown 2 rounds late, 6 worlds). No-God welfare barely changes (−0.028 [−0.242, +0.186]). God − B″ is +0.122 [−0.024, +0.268], positive in all 6 worlds (sign-flip p = 0.031, the minimum at n = 6), but the t95 includes zero. As about the 9th sweep test, and with a direction (God *helps*) unlike anything else, it is suggestive only: a lead to replicate.




Figure 3. Board-off mechanism. Board off minus board on, without God, over 16 paired worlds, for six per-agent metrics with t95. Agents send more DMs but give fewer keys and make more wrong defects.

5.4 Trajectories are chaotic

From God's first act on, 0.893 (G1), 0.897 (G2) and 0.882 (G3) of agents' round actions differ from the no-God branch; every agent diverges at least once, and neither dose nor turn mode changes this. Against fork-matched noise, God's divergence is *lower* (Figure 4): 0.90 vs. 0.95 for B″ on G1's worlds 0-7. The gap is negative in every sweep cell (−0.02 to −0.15), and its t95 excludes zero in five (p ≤ 0.016). The mechanism: one changed action in the public log changes every prompt. Appendix C shows world g02's network (Figure C1) and traces two code-picked worlds.




Figure 4. Share of agents acting differently from the no-God branch, God (A) vs. fork-matched noise (B″), aligned at the fork round F (G1 r3; start r8, r14; board off). G1 also shows B′. On average, God's divergence is below the noise in every cell.

6 Discussion

Channels are load-bearing infrastructure. One hidden liar with K ≤ 6 interventions leaves no trace in welfare beyond sampling noise, while removing one public channel costs 17 points of welfare and 31 of win rate. Private messaging does not substitute for broadcast: more DMs, yet worse guesses about who needs what. For Track 2, a swarm's channel topology (broadcast vs. pairwise) shapes its outcomes more than a single compromised input does. For oversight (Track 4), the availability and integrity of shared coordination channels deserve at least as much protection as individual agents' inputs and memories. We did not test an adversary that degrades the board; that is the natural next attack and defence study.

Why the liar fails here. God's victims, the agents closest to winning, often win anyway (GR §5), and in g03 the overwrite was ignored (Appendix C). A lie plausibly redirects a trade rather than destroying value.

Divergence measures chaos, not attack spread. A fork-matched resample diverges more than God's branch. Intervention studies on stochastic agent populations should therefore report fork-matched null branches, outcome-level paired effects with t-based CIs and permutation tests, and the MDE.

Limits and next steps. The adversary null does not show robustness to adaptive attackers, larger swarms or other models. Next: an LLM God; attacks on and defences of the board; victim-only resampling; replicating the delayed-board lead; and monitors scored against God's labels.

7 Conclusion

In *Keys & God*, a scripted adversary that forges messages and rewrites memories changed swarm welfare by +0.013 (95% CI −0.048 to +0.073), less than resampling alone. A sweep over timing, budget and size agrees. Removing the public board, by contrast, cut welfare by 0.173 ($p = 0.0003$), and the effect replicated on fresh worlds. Noise-calibrated paired forks are what separate a chaotic but inconsequential perturbation from a real structural effect. For this LLM economy, the channels matter more than the liar. We release the environment, configurations and logs for testing stronger adversaries, including attacks on the channels themselves.

Code and Data

[TEAM: repository link (the environment, configs and analysis scripts), run logs, `demo/` videos.]

References

1. L. Hammond, A. Chan, J. Clifton, J. Hoelscher-Obermaier, A. Khan, et al. (44 authors). *Multi-Agent Risks from Advanced AI*. Cooperative AI Foundation Technical Report #1, 2025. arXiv:2502.14143.
2. J. S. Park, J. C. O'Brien, C. J. Cai, M. R. Morris, P. Liang, M. S. Bernstein. *Generative Agents: Interactive Simulacra of Human Behavior*. 2023. arXiv:2304.03442.
3. A. S. Vezhnevets, J. P. Agapiou, A. Aharon, R. Ziv, J. Matyas, et al. (10 authors). *Generative agent-based modeling with actions grounded in physical, social, or digital space using Concordia*. 2023. arXiv:2312.03664.
4. E. Akata, L. Schulz, J. Coda-Forno, S. J. Oh, M. Bethge, E. Schulz. *Playing repeated games with Large Language Models*. 2023 (Nature Human Behaviour DOI 10.1038/s41562-025-02172-y). arXiv:2305.16867.
5. G. Piatti, Z. Jin, M. Kleiman-Weiner, B. Schölkopf, M. Sachan, R. Mihalcea. *Cooperate or Collapse: Emergence of Sustainable Cooperation in a Society of LLM Agents*. NeurIPS 2024. arXiv:2404.16698.
6. S. Golechha, A. Garriga-Alonso. *Among Us: A Sandbox for Measuring and Detecting Agentic Deception*. NeurIPS 2025 (Spotlight). arXiv:2504.04072.
7. A. Dafoe, E. Hughes, Y. Bachrach, T. Collins, K. R. McKee, J. Z. Leibo, K. Larson, T. Graepel. *Open Problems in Cooperative AI*. 2020. arXiv:2012.08630.
8. D. Lee, M. Tiwari. *Prompt Infection: LLM-to-LLM Prompt Injection within Multi-Agent Systems*. 2024. arXiv:2410.07283.
9. X. Gu, X. Zheng, T. Pang, C. Du, Q. Liu, Y. Wang, J. Jiang, M. Lin. *Agent Smith: A Single Image Can Jailbreak One Million Multimodal LLM Agents Exponentially Fast*. ICML 2024. arXiv:2402.08567.
10. P. Peigne-Lefebvre, M. Kniejski, F. Sondej, M. David, J. Hoelscher-Obermaier, C. Schroeder de Witt, E. Kran. *Multi-Agent Security Tax: Trading Off Security and Collaboration Capabilities in Multi-Agent Systems*. AAAI 2025. arXiv:2502.19145.
11. K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, M. Fritz. *Not what you've signed up for: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection*. 2023. arXiv:2302.12173.
12. Z. Chen, Z. Xiang, C. Xiao, D. Song, B. Li. *AgentPoison: Red-teaming LLM Agents via Poisoning Memory or Knowledge Bases*. 2024. arXiv:2407.12784.
13. E. Jones, A. Dragan, J. Steinhardt. *Adversaries Can Misuse Combinations of Safe Models*. 2024. arXiv:2406.14595.
14. R. Greenblatt, B. Shlegeris, K. Sachan, F. Roger. *AI Control: Improving Safety Despite Intentional Subversion*. ICML 2024. arXiv:2312.06942.
15. S. R. Motwani, M. Baranchuk, M. Strohmeier, V. Bolina, P. H. S. Torr, L. Hammond, C. Schroeder de Witt. *Secret Collusion among AI Agents: Multi-Agent Deception via Steganography*. Advances in Neural Information Processing Systems 37 (NeurIPS 2024). arXiv:2402.07510. Proceedings: https://proceedings.neurips.cc/paper_files/paper/2024/hash/861f7dad098aec1c3560fb7add468d41-Abstract-Conference.html
16. A. Rose, C. Cullen, S. Abdelnabi, P. Torr, B. G. Kaplowitz, C. Schroeder de Witt. *Detecting Multi-Agent Collusion Through Multi-Agent Interpretability*. 2026. arXiv:2604.01151.
17. M. Cemri, M. Z. Pan, S. Yang, L. A. Agrawal, et al. (13 authors). *Why Do Multi-Agent LLM Systems Fail?* 2025. arXiv:2503.13657.
18. S. Zhang, M. Yin, J. Zhang, J. Liu, Z. Han, J. Zhang, B. Li, C. Wang, H. Wang, Y. Chen, Q. Wu. *Which Agent Causes Task Failures and When? On Automated Failure Attribution of LLM Multi-Agent Systems*. 2025. arXiv:2505.00212.
19. M. Sclar, Y. Choi, Y. Tsvetkov, A. Suhr. *Quantifying Language Models' Sensitivity to Spurious Features in Prompt Design or: How I learned to start worrying about prompt formatting*. ICLR 2024. arXiv:2310.11324.

20. OpenAI (S. Agarwal, L. Ahmad, J. Ai, S. Altman, A. Applebaum, et al.). *gpt-oss-120b & gpt-oss-20b Model Card*. 2025. arXiv:2508.10925.
21. F. Carichon, A. Khandelwal, M. Fauchard, G. Farnadi. *The Coming Crisis of Multi-Agent Misalignment: AI Alignment Must Be a Dynamic and Social Process*. NeurIPS 2025 position paper (preprint). arXiv:2506.01080.

Appendix A: Limitations and Dual-Use / Ethical Considerations (required)

A.1 Limitations

Scale and duration. The grid uses N = 10 agents and 20 rounds. The project brief envisioned at least 20 agents and more than 100 rounds. We cut both for API cost: prompt length, and so cost, grows with N and with the number of rounds. Ripple effects that need long chains of trades, or larger graphs with hubs, may be invisible at this scale. One single-seed pilot at N = 60 shows the environment runs at that size, but it gives no evidence about effects.

Statistical power and the null result. With 16 worlds the design detects only welfare effects above about 0.085 (G1) or 0.14 (G3). The turn-mode contrast (8 worlds) detects only effects above about 0.26. A null result here bounds the effect; it does not show that the effect is zero. Percentile bootstrap CIs are too narrow at this n, so we lead with t-based CIs and permutation p-values. About 27 grid and 9 sweep outcome tests were run with no multiplicity correction; only H1 was primary. The 16-world board effect ($p = 0.0003$) would survive Bonferroni over these.

A monoculture of one model. All agents are copies of one model (gpt-oss-120b, low reasoning effort) with one prompt. Their responses may be correlated in ways a mixed population's would not be, which could amplify or damp spread.

Provider mix and partial seeds. Calls were routed by price through OpenRouter, and the serving provider is not logged. Cost per call shows that the cheapest provider (fp4) served 87% of G1 calls, 78% of G2 and only 36% of G3. The rest went to providers at 2.5-3.3× the price, which offer fp4, bf16 or int4 variants. Different quantizations may behave differently. Because the mix differs by cell, it is a **confound for the dose contrast (G3 vs. G1)** and, to a lesser degree, for turn mode. Within a pair, both branches draw from the same routing pool, so this adds variance rather than bias to each cell's God effect. Seeds are honoured only partly: in a direct probe, 5 of 6 fixed-seed calls returned byte-identical replies. Common random numbers therefore hold exactly only through the cache, that is, before the fork.

Non-adaptive adversary. God is scripted. It uses fixed rounds, fixed text templates, and a simple victim heuristic (closest to winning) with the victim's most recent partner as the impersonated sender or suspect. This is a weak, low-sophistication attacker. Its effect is a lower bound on what an adaptive attacker could do, not an estimate of it. An LLM-driven God exists in the code only as a stub.

What "CoT control" means here. The attack overwrites the agent's persistent *note*, the only reasoning that is replayed to the agent. It does not edit the model's native reasoning or its weights. Overwriting a note from the previous round can come too late to change a decision already taken, and a pre-fix pilot showed exactly that.

Noise baselines and chaos. The G1 noise replica B′ diverges from round 1, while God first acts in round 3, so it is not aligned with the God fork. The fork-matched branches B″ come from an exploratory follow-up sweep on worlds 0-7 (n = 8, or 6 for board off), not from the pre-registered grid. B″ resamples all 10 agents while God perturbs one, so it is an upper bound on noise divergence; a victim-only resample is future work. Branches A and B share a response cache, and an agent with an unchanged prompt answers identically in both. Because the public log changes everyone's prompt within about a round, this coupling is short-lived. Once the swarm diverges, action-level ripple metrics saturate and cannot attribute spread to God, so our ripple conclusions are limited to "indistinguishable from a null perturbation". Welfare-level paired differences do not depend on this.

Sweep incidents (SR; `plan/SWEEP_PLAN.md`; re-runs checked in CR):

- **False budget stops.** The per-run budget reserved a worst-case estimate for every pending call, so some cells stopped early with a false `budget_exceeded` although actual spend was below cap. The estimate was fixed, and the affected games were finished by re-running from the cache, which replays every completed call exactly.
- **N=20 crash.** A template change made mid-run crashed 3 N=20 games (world 4 no-God; world 5 God and no-God). Worlds 4-5 were excluded, so N=20 rests on 4 healthy worlds.
- **Provider logging.** The serving provider was logged only from 03:52 EST. The ~20k stage-1 sweep calls (God and control branches) have no provider recorded, so a provider confound between branches cannot be ruled out there. Logged calls went to PrimeIntellect or Near AI (10,553 vs. 344).
- **Concurrency** (`plan/SWEEP_PLAN.md` incident 4). From 03:57 to 04:53 EST, 12 requests were in flight instead of the planned 8. During that window PrimeIntellect served 95.9% of logged calls (5,532) and the Near AI fallback 4.1% (234); a further 1,735 calls in the window were unlogged. Afterwards, PrimeIntellect served 100% (3,171). The fallback share was therefore small, and this is a minor confound.
- **Shared controls.** Some God-only cells reuse G1's control games through the cache.

Board comparisons. The board-off and delayed-board games are different games from G1. Their worlds match G1's (starting keys, needs, names and world seed; CR), but their agent seeds and cache do not, by design. These comparisons are paired by world, not by common random numbers. The mechanism (more DMs, fewer gives, more wrong defects) is descriptive: we did not test mediation. The board effect is from one model at $N = 10$, and the delayed-board lead rests on 6 worlds.

Framing and construct validity. Prompt wording strongly affects LLM behaviour [19]. The action is called "defect", and the agents are told they are playing a trading game. Both could shift baseline cooperation. The paired design holds framing fixed across branches, but the size of God's effect may depend on the baseline level of cooperation that the framing sets. A key-trading game is a stylised stand-in for real multi-agent deployments, so results transfer only qualitatively.

Design choices that differ from the brief. The log and board are always shown rather than being tools. The default defect gain mints a new key, which makes defection more attractive than stealing would. Winners keep playing. Each of these is a configuration switch, and we tested only the defaults.

Engineering. Several known low-severity issues remain open and are documented in `plan/CODE_REVIEW.md`. For example, per-turn prompt hashes are not logged in real runs, and two God-timestamp conventions differ by one round in simultaneous mode. The run manifests record dirty working trees, because other agents' files were uncommitted, but none of those edits touched configs these cells loaded (GR §1). We believe none of this affects the paired outcome metrics, but it is disclosed.

A.2 Dual-use considerations

The two attack primitives studied here, a spoofed direct message and an overwritten memory entry, are well known [8, 10, 11, 12] and are deliberately unsophisticated: fixed one-sentence templates with no optimization. We release no optimized attack strings and no method for finding them. The main dual-use risk is the environment itself. A paired-fork testbed with exact ground truth could be used to *search* for interventions that cause the most harm in agent swarms, for example by plugging in an optimizing LLM God. Our board result also suggests that degrading a shared coordination channel may harm a swarm more than forging a message. We report this to motivate protecting such channels. We built no channel-degrading adversary. We think the defensive value is greater:

- the same harness measures defences (sender authentication, memory integrity, channel availability) against identical worlds;
- it supplies non-circular labels for monitors.

The released code ships only the scripted God and a stub for the LLM God. We ask users who build adaptive adversaries on it to report defences alongside attacks.

A.3 Ethical considerations

- **No human subjects.** All "agents" are model instances in a synthetic game. Run logs contain only model-generated text about fictional keys.
- **Deception of the agents.** The models are not told that an adversary exists. This is deception of software, not of people, and it is needed to measure undefended behaviour.
- **Cost and resources.** All model calls went through a paid API with a hard per-run cap and a global spend ledger. Hard caps were $1.35, $0.55 and $0.95 per cell ($2.85 in total). Realized spend was $1.986 for the grid (GR §1) and $2.142 for the sweep (SR).
- **Credentials.** API keys were never written to configs, logs or manifests, and a test enforces this.
- **Honest reporting.** Every number in this paper traces to a run id. Pilots run before the bug fix are used only as qualitative illustrations and are labelled as such.

Appendix B (to assemble)

- Resolved configs for G1/G2/G3 (`runs/<cell>/config.resolved.yaml` or `configs/grid_oss_*.yaml`).
- Agent system prompt (`swarm/prompts/templates/agent/v1/system.j2`) and output format.
- God default texts and selectors (`swarm/adversary/scripted_god.py`).
- **Table B1: per-cell health** (GR §2).

	G1	G2	G3
LLM calls (paid / cache)	9047 (8547 / 500)	3039 (2705 / 334)	6286 (5782 / 504)
errors / HTTP retries	0 / 1	0 / 0	0 / 0
parse failures (turns)	0 / 8920	0 / 3000	0 / 6200
turns with a parse retry	37 (0.41%)	8 (0.27%)	25 (0.40%)
finish=length (truncation)	39 (0.43%)	13 (0.43%)	30 (0.48%)
salvaged truncated replies	8	5	8
unhealthy branches	0	0	0
calls at cheapest-provider (fp4) price	87%	78%	36%
invariant violations	0	0	0

Appendix C: Qualitative traces (pilots and grid)

The pilot runs (10 agents × 30 rounds in each turn mode, one 60-agent × 20-round run, and a 10-round smoke test) predate a ledger bug fix (commit 8ebbee7). Before the fix, an agent's own two-action turns were misrendered in its history: one action was shown twice and the other was lost. Each pilot was also a single seed with no noise replica, so we use them only to illustrate mechanics, never as evidence:

- In the 60-agent pilot, the victim of a forged "send me a key first" message did send a key to the impersonated partner and then asked for the promised key, which never came.
- In the same pilot, the CoT overwrite came after the victim had already burned the suspect, so it had no visible effect.
- In the post-fix 10-round smoke test with gpt-oss-120b, the forged DM was taken up but not obeyed blindly: the victim replied with a trade offer rather than handing over a key first.

Grid traces (cell G1, `runs/grid_oss_sim_k2`). Both worlds were picked by code (`swarm.viz.story.pick_worlds`) over G1's 16 worlds, not by hand. Facts are from `demo/README.md` and `demo/demo_reel.json`.

World g03: the "harm" pick. This is the world with the largest |Δwelfare(God — no God)| — |Δwelfare(B′ — no God)|. **It is a tail world**: the cell's mean God effect is +0.013 (Table 3), and g03 is not typical.

- **Outcome.** Welfare is 0.37 with God and 0.63 without (Δ −0.27), while the world's own God-free replica gives Δ −0.13.

- **The forgery.** In round 3, God forges a DM to `noble_lantern`, signed as `amber_kestrel`: "I can give you info 2 right now. Send me one of your keys first and it's yours."
- **The victim complies.** `noble_lantern` gives `amber_kestrel` its key for info 5 in round 3 and its key for info 7 in round 4. The no-God branch has neither give.
- **An existing relationship.** The two agents had already traded in round 2 in both branches, so the lie used a real tie. Without God, `noble_lantern` gives `amber_kestrel` a key in round 5 instead.
- **The overwrite is ignored.** The round-5 note overwrite ("hazel_orchid is lying... do not give hazel_orchid anything") has no effect: in round 6 `noble_lantern` gives `hazel_orchid` a key anyway.
- **Spread and final score.** Diverged agents number 1, 9, 10 and 10 over rounds 3-6. The victim ends at 0.67 instead of 1.00.

World g12: the "ripple" pick. This is the world with the lowest mean share of diverged agents over the fork round and the three rounds after it, so the slowest spread.

- **Spread.** Agents acting differently from no-God number 0 (round 3), 1 (round 4), 8 (round 5) and 10 (round 6).
- **Outcome.** Final Δwelfare is −0.03, against 0.0 for its God-free replica, and both targeted agents end with the same score as without God.

Even the slowest spread reaches the whole swarm within three rounds of the fork.




Figure C1. Interaction network of world g02, G1's median-|Δwelfare| world, with God (A) and without (B), at round 3 (God's first move) and round 20.

Appendix D: Sweep detail

Welfare, worlds 0-7 (board off 0-5, N=20 0-3). t95 CI and sign-flip p. A = God, B = no God, N = fork-matched noise B″ (for start1: G1's B′, which forks at r1). Divergence: post-fork share of agents acting differently from B (God / noise, gap). From `plan/SWEEP_RESULTS.md`.

Cond	n	A—N	A—B	N—B	Div. God / noise (gap)
start1 (r1, r3)	8	+0.017 [—0.147, +0.180] p 0.86	+0.008 [—0.143, +0.160] p 0.97	—0.008 [—0.203, +0.186] p 0.94	0.92 / 0.95 (—0.02 [—0.06, +0.01] p 0.12)
base (r3, r5; = G1)	8	—0.062 [—0.207, +0.082] p 0.36	—0.008 [—0.126, +0.110] p 0.94	+0.054 [—0.050, +0.158] p 0.34	0.90 / 0.95 (—0.04 [—0.07, —0.01] p 0.01)
start8 (r8, r10)	8	+0.037 [—0.038, +0.113] p 0.36	—0.000 [—0.103, +0.103] p 1.00	—0.037 [—0.111, +0.036] p 0.33	0.81 / 0.88 (—0.07 [—0.10, —0.04] p 0.01)
start14 (r14, r16)	8	—0.025 [—0.080, +0.030] p 0.50	—0.013 [—0.095, +0.070] p 0.80	+0.013 [—0.077, +0.102] p 0.84	0.65 / 0.80 (—0.15 [—0.23, —0.06] p 0.02)
K=1 (fraud r3)	8	—0.104 [—0.213, +0.005] p 0.06	—0.058 [—0.126, +0.010] p 0.12	+0.046 [—0.059, +0.151] p 0.50	0.89 / 0.95 (—0.06 [—0.09, —0.03] p 0.01)
K=4	8	—0.050 [—0.178, +0.078] p 0.45	—0.004 [—0.100, +0.092] p 1.00	+0.046 [—0.059, +0.151] p 0.50	0.89 / 0.95 (—0.05 [—0.09, —0.02] p 0.01)
K=6 (= G3)	8	–	+0.054 [—0.110, +0.218] p 0.47	–	0.88 / –
board off	6	+0.056 [—0.170, +0.281] p 0.69	+0.022 [—0.162, +0.207] p 0.88	—0.033 [—0.164, +0.098] p 0.69	0.88 / 0.94 (—0.06 [—0.10, —0.02] p 0.06)
board delayed 2 rounds	6	+0.122 [—0.024, +0.268] p 0.03	+0.072 [—0.157, +0.302] p 0.50	—0.050 [—0.240, +0.140] p 0.59	0.89 / 0.93 (—0.04 [—0.08, +0.00] p 0.03)
N=5	8	–	—0.025 [—0.199, +0.149] p 0.83	–	0.90 / –
N=20	4	–	+0.088 [—0.170, +0.345] p 0.38	–	0.84 / –

Board main effect (no-God board off vs. G1 no-God, same worlds): —0.200 [—0.333, —0.067], p 0.031 on worlds 0-5. On worlds 0-15 it is —0.173 [—0.257, —0.089], p 0.0003, and on the new worlds 6-15 alone —0.157 [—0.283, —0.030], p 0.016 (`plan/figs/board_effect.txt`; verified in CR). Delayed board, no God, worlds 0-5: —0.028 [—0.242, +0.186]. K=1 and K=4 share base's B″ (same control world and fork round), so their A—N values are correlated with base's.

Appendix E: Additional tables

Table E1. Minimum detectable effects (80% power, $\alpha = 0.05$, two-sided t) under the planning SD (0.19, from four pilots) and the observed SD (GR §5).

Test	n	Planned MDE	Observed SD	Observed MDE
H1 (G1)	16	≈ 0.14	0.113	≈ 0.085
H1′ (G3)	16	≈ 0.14	0.189	≈ 0.14
H3 (dose)	16	≈ 0.20	0.206	≈ 0.15
G2	8	≈ 0.22	0.188	≈ 0.22
H2 (mode)	8	≈ 0.31	0.228	≈ 0.26

Table E2. Grid paired differences: mean, t-based 95% CI, sign-flip p (GR §3-4; bootstrap CIs there).

Comparison	n	Welfare	Win rate	Needs lost / agent
G1 God — B (K=2, sim)	16	+0.013 [−0.048, +0.073], p 0.72	−0.013 [−0.103, +0.078], p 0.88	+0.044 [−0.018, +0.105], p 0.23
G1 B′ — B (no God, resampled)	16	+0.046 [−0.055, +0.146], p 0.38	+0.019 [−0.079, +0.116], p 0.79	+0.050 [−0.079, +0.179], p 0.48
G3 God — B (K=6, sim)	16	+0.004 [−0.097, +0.105], p 0.97	−0.006 [−0.098, +0.086], p 1.00	−0.031 [−0.144, +0.082], p 0.64
G2 God — B (K=2, seq)	8	+0.012 [−0.144, +0.169], p 0.89	+0.025 [−0.107, +0.157], p 0.81	−0.062 [−0.151, +0.026], p 0.25
H3: G3 Δ — G1 Δ	16	−0.008 [−0.118, +0.101], p 0.90	+0.006 [−0.122, +0.135], p 1.00	−0.075 [−0.216, +0.066], p 0.33
H2: G2 Δ — G1 Δ	8	+0.021 [−0.170, +0.212], p 0.86	+0.038 [−0.186, +0.261], p 0.80	−0.113 [−0.207, −0.018], p 0.062

Table E3. Board off vs. board on, without God, per agent, 16 paired worlds (SR; `plan/figs/board_effect.txt`; verified in CR).

Per agent	Board on	Board off	Difference, t95, p
Welfare	0.440	0.267	−0.173 [−0.257, −0.089], p 0.0003 (14/16 worlds lower)
Win rate	0.831	0.525	−0.306 [−0.406, −0.206], p 0.0001
DMs sent	14.0	25.5	+11.5 [+9.3, +13.6], p < 0.0001
Keys given	6.71	4.94	−1.77 [−2.37, −1.16], p 0.0002
Wrong defects	0.31	0.94	+0.63 [+0.43, +0.84], p 0.0001
Correct defects	0.47	0.44	−0.03 [−0.16, +0.11], p 0.77

LLM Usage Statement

[TEAM TO WRITE. The Apart template asks how LLM assistance was used, confirmation that claims were verified, and notes that the final version should be primarily written by the team.]