

B561 Assignment 6

Data Generation

Sorting

Indexing

Dirk Van Gucht

For this assignment, you will need the material covered in the lectures

- Lecture 14: External Merge Sorting
- Lecture 15: Indexing
- Lecture 16: B⁺ trees and Hashing

In addition, you should read the following sections in Chapter 14 and 15 in the textbook *Database Systems The Complete Book* by Garcia-Molina, Ullman, and Widom:

- Section 14.1: Index-structure Basics
- Section 14.2: B-Trees
- Section 14.3: Hash Tables
- Section 14.7: Bitmap Indexes

In the file `performingExperiments.sql` supplied with this assignment, we have include several PostgreSQL functions that should be useful for running experiments. Of course, you may wish to write your own functions and/or adapt the functions in this `.sql` to suite the required experiments for the various problems in this assignment.

The problems that need to be included in the `assignment6.sql` are marked with a blue bullet •. The problems that need to be included in the `assignment6.pdf` are marked with a red bullet •. (You should aim to use Latex to construct your `.pdf` file.) In addition, submit a file `assignment6Code.sql` that contains all the sql code that you developed for this assignment.

1 Data generation

PostgreSQL functions and clauses In this assignment, you will need to conduct experiments with random data generated relations of various sizes. PostgreSQL provides useful functions and clauses to generate such relations:

<code>random()</code>	returns a random real number between 0 and 1 using the uniform distribution
<code>floor(random() * (u - l + 1) + l) :: int</code>	returns a random integer in the range $[l, u]$ using the uniform distribution
<code>generate_series(m,n)</code>	generates the set of integers in the range $[m, n]$
<code>order by random()</code>	randomly orders the tuples that are the result of a query
<code>limit(n)</code>	returns the first n tuples from the result of a query
<code>offset(n)</code>	returns all but the first n tuples from the result of a query
<code>row_number()</code>	is a <i>window function</i> that assigns a sequential integer to each row in a result set
<code>vacuum</code>	is a <i>garbage collection</i> function to clean and reclaim secondary memory space

For more detail, consult the manual pages

<https://www.postgresql.org/docs/13/functions-math.html>
<https://www.postgresql.org/docs/current/functions-srf.html>
<https://www.postgresql.org/docs/current/queries-limit.html>
<https://www.postgresql.org/docs/8.4/functions-window.html>
<https://www.postgresql.org/docs/9.5/routine-vacuuming.html>

Generating sets To generate a set, i.e., a unary relation, of n randomly selected integers in the range $[l, u]$, you can use the following function:¹

```
create or replace function SetOfIntegers(n int, l int, u int)
    returns table (x int) as
$$
    select floor(random() * (u-l+1) + l)::int from generate_series(1,n);
$$ language sql;
```

Example 1 To generate a unary relation with 3 randomly selected integers in the range 5 to 10, do the following:

```
select x from SetofIntegers(3,5,10);
```

Of course, running this query multiple times, result in different sets.

¹Typically the function `SetOfIntegers` returns a bag (multiset) but this is fine for this assignment. In case we want a set, we can always eliminate duplicates.

Generating binary relations The idea behind generating a set can be generalized to that for the generation of a binary relation.² To generate a binary relation of n randomly selected pairs of integers (x, y) with $x \in [l_1, u_1]$ and $y \in [l_2, u_2]$, you can use the following function:

```
create or replace function
BinaryRelationOverIntegers(n int, l_1 int, u_1 int, l_2 int, u_2 int)
returns table (x int, y int) as
$$
select floor(random() * (u_1-l_1+1) + l_1)::int as x,
       floor(random() * (u_2-l_2+1) + l_2)::int as y
from   generate_series(1,n);
$$ language sql;
```

Example 2 To generate a binary relation with 20 randomly selected pairs with first components in the range $[3, 8]$ and second components in the range $[2, 11]$, do the following:

```
select x, y from BinaryRelationOverIntegers(20,3,8,2,11);
```

Generating functions A relation generated by `BinaryRelationOverIntegers` is in general not a function since it is possible that the relation has pairs (x, y_1) and (x, y_2) with $y_1 \neq y_2$. To create a (partial) function $f : [l_1, u_1] \rightarrow [l_2, u_2]$ of n randomly selected function pairs, we can use the following function:³

```
create or replace function
FunctionOverIntegers(n int, l_1 int, u_1 int, l_2 int, u_2 int)
returns table (x int, y int) as
$$
select x, floor(random() * (u_2-l_2+1) + l_2)::int as y
from   generate_series(l_1,u_1) x order by random() limit(n);
$$ language sql;
```

Example 3 To generate a partial function $[1, 20] \rightarrow [3, 8]$ of 15 randomly selected function pairs, do the following:⁴

```
select x, y from FunctionOverIntegers(15,1,20,3,8);
```

²Clearly, all of this can be generalized to higher-arity relations.

³Observe that when $n \geq (u_1 - l_1)$, f is a total function.

⁴When using this function, it is customary to use n such that $n \in [0, u_1 - l_1 + 1]$.

Generating relations with categorical (non-numeric) data Thus far, the sets, binary relations, and functions have all just involved integer ranges. It is possible to include ranges that have different types including categorical data such as text strings. The technique to accomplish this is to first associate with a categorical range an integer range that associate with each element in the categorical range a unique value of the integer range. The following example illustrates this.

Example 4 Consider the `jobSkill` relation and assume that it contents is

skill
AI
Databases
Networks
OperatingSystems
Programming

Suppose that we want to generate a `personSkill(pid, skill)` relation. Let us assume that the `pid`'s are integers in the range $[1, m]$.

There are 5 skills in the `jobSkill` and it is therefore natural to associate with each skill a separate integer (index value) in the range $[1, 5]$. This can be done with a query involving the `row_number()` window function:

```
select skill, row_number() over (order by skill) as index
from Skill;
```

The result is the following relation:

skill	index
AI	1
Databases	2
Networks	3
OperatingSystems	4
Programming	5

Using this technique, we can write a PostgreSQL function that generates a `personSkill` relation with n randomly selected $(pid, skill)$ tuples, with `pid`'s in the range $[l, u]$:

```
create or replace function GeneratepersonSkillRelation(n int, l int, u int)
returns table (pid int, skill text) as
$$
with skillNumber(skill, index) as (select skill, row_number() over (order by skill)
                                   from Skill),
    pS as (select x, y
           from BinaryRelationOverIntegers(n,l,u,1, (select count(1) from Skill)::int))
select x as pid, skill
from pS join skillNumber on y = index
group by (x, skill) order by 1,2;
$$ language sql;
```

In this function, the `skillNumber` view associates with each job skill an integer index in the range $[1, |\text{Skill}|]$. The `pS` view is a randomly generated binary relation with n tuples, with `pid`'s in the range $[l, u]$, and skill numbers in the range $[1, |\text{Skill}|]$. The `join` operation associates the numeric range with the `Skill` range. The `'group by (x, skill) order by 1,2'` clause eliminates duplicate tuples and orders the result.

The query

```
select * from GeneratepersonSkillRelation(10,1,15);
```

may make the `personSkill` relation:

pid	skill
1	AI
2	Programming
3	Databases
4	Databases
6	Networks
6	OperatingSystems
6	Programming
9	Databases
14	Databases
14	Networks

Problems We now turn to the problems in this section.

1. • Given a discrete probability mass function P , as specified in a relation $P(\text{outcome: int, probability: float})$, over a range of possible outcomes $[u_2, l_2]$, design a PostgreSQL function

`RelationOverProbabilityFunction(n, l_1, u_1, l_2, u_2)`

that generates a relation of up to n pairs (x, y) such that

- x is uniformly selected in the range $[l_1, u_1]$; and
- y is selected in accordance with the probability mass function P in the range $[l_2, u_2]$.

An example of a possible P as stored in relation P is as follows:⁵

P	
outcome	probability
1	0.25
2	0.10
3	0.40
4	0.10
5	0.15

Note that when P is the uniform probability mass function, then

`RelationOverProbabilityFunction`

and

`BinaryRelationOverIntegers`

are the same binary-relation-producing functions.

Hint: For insight into this problem, consult the method of *Inverse Transform Sampling* for discrete probability mass functions.

Test your function for the following cases:

- (a) Test case 1: uniform mass function

P	
outcome	probability
1	0.125
2	0.125
3	0.125
4	0.125
5	0.125
6	0.125
7	0.125
8	0.125

⁵Notice that the sum of the probabilities in the `probability` column in P sum to 1.

```
select * from RelationOverProbabilityFunction(100, 1, 150, 1, 8);
```

You actually may wish to run the above query multiple times to test that your function works as expected.

(b) Test case 2: non-uniform function

outcome	P probability
1	0.25
2	0.05
3	0.10
4	0.10
5	0.15
6	0.05
7	0.10
8	0.20

```
select * from RelationOverProbabilityFunction(100, 1, 150, 1, 8);
```

You actually may wish to run the above query multiple times to test that your function works as expected.

2. • Use the technique in Problem 1 and the method for generating categorical data discussed above to write a PostgreSQL function that generates a **personSkill** relation, given a probability mass function over the **Skill** relation.

Your function should work for any **Skill** relation and any probability distribution defined over it.

Provide test cases and run test to demonstrate that your solution works.

2 Sorting

We have learned about *external sorting*. The problems in this section are designed to look into this sorting method as it implemented in PostgreSQL.

3. • Create successively larger sets of n randomly selected integers in the range $[1, n]$. You can do this using the following function.⁶

```
create or replace function makeS (n integer)
returns void as
$$
begin
    drop table if exists S;
    create table S (x int);
    insert into S select * from SetOfIntegers(n,1,n);
end;
$$ language plpgsql;
```

This function generates a bag S of size n , with randomly select integers in the range $[1, n]$. Now consider the following SQL statements:

```
select makeS(10);
explain analyze select x from S;
explain analyze select x from S order by 1;
```

- The ‘`select makeS(10)`’ statement makes a bag S with 10 elements;
- The ‘`explain analyze select x from S`’ statement provides the query plan and **execution time** in milliseconds (ms) for a simple scan of S ;
- The ‘`explain analyze select x from S order by 1`’ statement provides the query plan and **execution time** in milliseconds (ms) for sorting S .⁷

QUERY PLAN

```
-----
Sort  (cost=179.78..186.16 rows=2550 width=4) (actual time=0.025..0.026 rows=10 loops=1)
  Sort Key: x
  Sort Method: quicksort  Memory: 25kB
  -> Seq Scan on s  (cost=0.00..35.50 rows=2550 width=4) (actual time=0.004..0.005 rows=10 loops=1)
Planning Time: 0.069 ms
Execution Time: 0.034 ms
```

Now construct the following timing table:⁸

⁶You should make it a habit to use the PostgreSQL `vacuum` function to perform garbage collection between experiments.

⁷Recall that 1ms is $\frac{1}{1000}$ second.

⁸It is possible that you may not be able to run the experiments for the largest S . If that is the case, just report the results for the smaller sizes.

size n of relation S	avg execution time to scan S (in ms)	avg execution time to sort S (in ms)
10^1		
10^2		
10^3		
10^4		
10^5		
10^6		
10^7		
10^8		

- (a) What are your observations about the query plans for the scanning and sorting of such differently sized bags S ? In particular, discuss the different sorting algorithms that appear in the query plans and why they can or must be used.
- (b) What do you observe about the execution time to sort S as a function of n and the buffer (working memory) size? In particular, explain if/why these conform with the formal time complexity of (external) sorting?

To answer this question, you should construct the above table for different *working memory* sizes.⁹

The default working memory size for PostgreSQL is 4MB and the smallest possible working memory is 64kB.

We suggest that you consider the following working memory sizes: 64kb, 4MB, 32MB, and 256MB.

We also suggest that you do not use parallel workers. This can be accomplished by issuing the PostgreSQL interpreter command `set max_parallel_workers = 0`.¹⁰

- (c) Now create a relation `indexedS(x integer)` and create a Btree index on `indexedS` and insert into `indexedS` the sorted relation S .¹¹

```
create table indexedS (x integer);
create index on indexedS using btree (x);
insert into indexedS select x from S order by 1;
```

Then run the range query

```
select x from indexedS where x between 1 and n;
```

⁹For example, the PostgreSQL interpreter command `set work_mem = '16MB'` sets the working memory to 16MB. Consult <https://www.postgresql.org/docs/14/runtime-config-resource.html> for more information.

¹⁰Consult <https://www.postgresql.org/docs/14/runtime-config-resource.html> for more information about parallel workers.

¹¹For information about *indexes* in PostgreSQL consult the manual page <https://www.postgresql.org/docs/14/indexes.html>.

where n denotes the size of S .

Then construct the following table which contains (a) the average execution time to build the btree index and (2) the average time to run the range query.

size n of relation S	avg execution time to create index <code>indexedS</code>	avg execution time for range query (in ms)
10^1		
10^2		
10^3		
10^4		
10^5		
10^6		
10^7		
10^8		

What are your observations about the query plans and execution times to create `indexedS` and the execution times for sorting the differently sized bags `indexedS`? Compare your answer with those for the above sorting problems.

4. • Typically, the `makeS` function returns a bag instead of a set. In the problems in this section, you are to conduct experiments to measure the execution times to eliminate duplicates.
 - (a) Write a SQL query that uses the `DISTINCT` clause to eliminate duplicates in S and report you results in a table such as that in Problem 3a.
 - (b) Write a SQL query that uses the `GROUP BY` clause to eliminate duplicates in S and report you results in a table such as that in Problem 3a.
 - (c) Compare and contrast the results you have obtained in problems 4a and 4b. Again, consider using `explain analyze` to look at query plans.

3 Indexes and Indexing

Indexes on data (1) permit faster lookup on data items and (2) may speed up query processing on such data. Speedups can be substantial. The purpose of the problems in this section are to explore this.

Several other problems in this section are designed to understand the workings of the B^+ -tree and the *extensible hashing* data structures.

Discussion PostgreSQL permit the creation of a variety of indexes on tables. We will review such **index creation** and examine their impact on data lookup and query processing. For more details, see the PostgreSQL manual:

<https://www.postgresql.org/docs/13/indexes.html>

Example 5 *The following SQL statements create indexes on columns or combinations of columns of the `personSkill` relation.¹² Notice that there are*

$$2^{\text{arity}(\text{personSkill})} - 1 = 2^2 - 1 = 3$$

such possible indexes.

```
create index pid_index on personSkill (pid);           -- index on pid attribute
create index skill_index on personSkill (skill);       -- index on skill attribute
create index pid_skill_index on personSkill (pid,skill); -- index (pid, skill)
```

Example 6 *It is possible to declare the type of index: `btree` or `hash`. When no index type is specified, the default is `btree`. If instead of a `Btree`, a `hash` index is desired, then it is necessary to specify a `using hash` qualifier:*

```
create index pid_hash on personSkill using hash (pid); -- hash index on pid attribute
```

Example 7 *It is possible to create an index on a relation based on a scalar expression or a function defined over the attributes of that relation. Consider the following (immutable) function which computes the number of skills of a person:*

```
create or replace function numberOfSkills(p integer) returns integer as
$$
    select count(1)::int
    from   personSkill
    where  pid = p;
$$ language SQL immutable;
```

¹²Incidentally, when a primary key is declared when a relation is created, PostgreSQL will create a `btree` index on this key for the relation.

Then the following is an index defined on the `numberOfSkills` values of persons:

```
create index numberOfSkills_index on personSkill (numberOfSkills(pid));
```

Such an index is useful for queries that use this function such as

```
select pid, skill from personSkill where numberOfSkills(pid) > 2;
```

We now turn to the problems in this section.

5. • Consider a relation `Student(sid text, sname text, major, byear)`. A tuple (s, n, m, y) is in `Student` when s is the sid of a student and n, m , and y are that student's name, major, and birth year. Further, consider a relation `Enroll(sid text, cno text, grade text)`. A triple (s, c, g) is in `Enroll` when the student with sid s was enrolled in the course with cname c and obtained a letter grade g in that course.

We are interested in answering queries of the form

```
select sid, sname, major, byear
from   Student
where  sid in (select sid
               from   Enroll sid
               where  cno = c [and/or/and not] grade = g);
```

Here `c` denotes a course name and `g` denotes a letter grade.

Read Section 14.1.7 'Indirection in Secondary Indexes' in your textbook *Database Systems The Complete Book* by Garcia-Molina, Ullman, and Widom. Of particular interest are (a) the concept of *buckets* (Figure 14.7) which are sets of tids and (b) the technique of performing set operations (like intersections) on relevant buckets (Figure 14.8) to answer queries of the form as shown above.

The goal of this problem is to use object-relational SQL to simulate these concepts. To make things more concrete, consider the following `Student` and `Enroll` relations:

Student:			
sid	sname	major	byear
s100	Eric	CS	1988
s101	Nick	Math	1991
s102	Chris	Biology	1977
s103	Dinska	CS	1978
s104	Zanna	Math	2001
s105	Vince	CS	2001

Enroll:

sid	cno	grade
s100	c200	A
s100	c201	B
s100	c202	A
s101	c200	B
s101	c201	A
s101	c202	A
s101	c301	C
s101	c302	A
s102	c200	B
s102	c202	A
s102	c301	B
s102	c302	A
s103	c201	A
s104	c201	D

Now consider associating a tuple id (tid) with each tuple in **Enroll**:

tid	sid	cno	grade
1	s100	c200	A
2	s100	c201	B
3	s100	c202	A
4	s101	c200	B
5	s101	c201	A
6	s101	c202	A
7	s101	c301	C
8	s101	c302	A
9	s102	c200	B
10	s102	c202	A
11	s102	c301	B
12	s102	c302	A
13	s103	c201	A
14	s104	c201	D

Use object-relational SQL to construct two secondary indexes **indexOnCno** and **indexOnGrade** on the **Enroll** relation. These indexes should be stored in two separate relations which you can conveniently call **indexOnCno** and **indexOnGrade**, respectively. These two object-relational views should **simulate** the situation illustrated in Figure 14.8. In particular, do **not** use the **'create index'** mechanism of SQL to construct these indexes.

Then, using the **indexOnCno** and **indexOnGrade** views and the technique of *intersecting buckets*, write a function **FindStudents(booleanOperation text, cno text, grade text)** that can be used to answer queries of the form as shown above. (Here the booleanOperation is a string which can be 'and', 'or', or 'and not'.)

For example, the query

```
select * from FindStudents('and', 'c202', 'A');
```

should return the same result as that of the query

```

select sid, sname, major, byear
from Student
where sid in (select sid
              from Enroll sid
              where cno = 'c202' and grade = 'A');

```

Test your solution for the following cases on the `Student` and `Enroll` relation given for this problem:

- (a) `select * from FindStudents('and', 'c202', 'A');`
 - (b) `select * from FindStudents('or', 'c202', 'A');`
 - (c) `select * from FindStudents('and not', 'c202', 'A');`
6. • Read Section 14.7 ‘Bitmap Indexes’ in your textbook *Database Systems The Complete Book* by Garcia-Molina, Ullman, and Widom. In particular, look at Example 14.39 for an example of a bitmap index for a secondary index.

Next, revisit Problem 5. There, we considered two secondary indexes `indexOnCno` and `indexOnGrade`. We will now consider the corresponding bitmap indexes `bitmapIndexOnCno` and `bitmapIndexOnGrade`:

```

bitmapIndexOnCno
cno | bit-vector
-----+-----
c200 | 10010000100000
c201 | 01001000000011
c202 | 00100100010000
c301 | 00000010001000
c302 | 00000001000100

```

and

```

bitmapIndexOnGrade
grade | bit-vector
-----+-----
A      | 10101101010110
B      | 01010000101000
C      | 00000010000000
D      | 00000000000001

```

Use object-relational SQL to construct two secondary indexes `bitmapIndexOnCno` and `bitmapIndexOnGrade` as two object-relational relations in a manner that simulates the situation just illustrated above.

Then, using the `bitmapIndexOnCno` and `bitmapIndexOnGrade` relations and the technique of forming the bitmap-AND, bitmap-OR, and bitmap-AND NOT of two bit-vectors, write a function `FindStudents(booleanOperation text, cno text, grade text)` that can be used to answer queries of the form as shown in Problem 5.

For example, the query

```

select * from FindStudents('and', 'c202', 'A');

```

should return the same result as that of the query

```
select sid, sname, major, byear
from Student
where sid in (select sid
              from Enroll sid
              where cno = 'c202' and grade = 'A');
```

Test your solution for the following cases on the `Student` and `Enroll` relation given for this problem:

- (a) `select * from FindStudents('and', 'c202', 'A');`
- (b) `select * from FindStudents('or', 'c202', 'A');`
- (c) `select * from FindStudents('and not', 'c202', 'A');`

7. • Consider the following parameters:


block size	=	8192 bytes
block-address size	=	10 bytes
block access time (I/O operation)	=	15 ms (micro seconds)
record size	=	200 bytes
record primary key size	=	8 bytes

Assume that there is a B^+ -tree, adhering to these parameters, that indexes 10 billion (10^{10}) records on their primary key values.

Provide answers to the following problems and show the intermediate computations leading to your answers.

- (a) Specify (in ms) the minimum time to determine if there is a record with key k in the B^+ -tree. (In this problem, you can not assume that a key value that appears in a non-leaf node has a corresponding record with that key value.)
- (b) Specify (in ms) the maximum time to insert a record with key k in the B^+ -tree assuming that this record was not already in the data file.
- (c) How large must main memory be to hold the first two levels of the B^+ -tree? How about the first three levels? In what manner does storing these levels in main memory affect the answers in Problem 7a and Problem 7b.

8. • Consider the following B⁺-tree of order 2 that holds records with keys 2, 8, and 11.¹³




- (a) Show the contents of your B⁺-tree after inserting records with keys 5, 7, 10, 4, 10, 12, and 1 in that order.

Strategy for splitting leaf nodes: when a leaf node n needs to be split into two nodes n_1 and n_2 (where n_1 will point to n_2), then use the rule that an even number of keys in n is moved into n_1 and an odd number of keys is moved into n_2 . So if n becomes conceptually $\boxed{k_1|k_2|k_3}$ then n_1 should be $\boxed{k_1|k_2}$ and n_2 should be $\boxed{k_3|}$ and $n_1 \rightarrow n_2$.

- (b) Starting from your answer in question 8a, show the contents of your B⁺-tree after deleting records with keys 12, 2, and 4 in that order.
- (c) Starting from your answer in question 8b, show the contents of your B⁺-tree after deleting records with keys 10, 7, 1, and 5 in that order.

¹³Recall that (a) an internal node of a B⁺-tree of order 2 can have either 1 or 2 keys values, and 2 or 3 sub-trees, and (b) a leaf node can have either 1 or 2 key values.

9. • Consider an extensible hashing data structure wherein (1) the initial global depth is set at 1 and (2) all directory pointers point to the same **empty** bucket which has local depth 0. So the hashing structure looks like this: Assume that a bucket can hold at most two records.



- (a) Show the state of the hash data structure after each of the following insert sequences:¹⁴
- records with keys 9 and 4.
 - records with keys 1 and 2.
 - records with keys 8 and 3.
 - records with keys 6 and 7.
- (b) Starting from the answer you obtained for Question 9a, show the state of the hash data structure after each of the following delete sequences:
- records with keys 4 and 1.
 - records with keys 9 and 6.
 - records with keys 7 and 3.

As in the text book, the bit strings are interpreted starting from their left-most bit and continuing to the right subsequent bits.

¹⁴You should interpret the key values as bit strings of length 4. So for example, key value 7 is represented as the bit string 0111 and key value 2 is represented as the bit string 0010.

The goal in the next problems is to study the behavior of indexes for various different sized instances¹⁵ of the **Person**, **personSkill**, **worksFor**, and **Knows** relations and for various queries:

10. • Create an appropriate index on the **personSkill** relation that speeds up the lookup query

```
select pid from personSkill where skill = s;
```

Here **s** is a skill.

Illustrate and discuss this speedup by finding the execution times for this query for 3 different but sufficiently large sizes of the **personSkill** relation.

You should compare the execution times for running the query without the index versus the the execution times for running the query with indexes.

11. • Create an appropriate index on the **worksFor** relation that speeds up the range query

```
select pid
from   worksFor
where  s1 <= salary and salary <= s2;
```

Here **s1** and **s2** are two salaries with $s1 \leq s2$.

Illustrate and discuss this speedup by finding the execution times for this query for 3 different but sufficiently large sizes of the **worksFor** relation.

In addition, consider different size ranges $[s1, s2]$: (a) a small range $[s1, s1]$, (b) an intermediate range $[\text{lowest salary}, \text{average salary}]$, and (3) the maximum range $[\text{smallest salary}, \text{highest salary}]$.

You should compare the execution times for running the query without the index versus the the execution times for running the query with indexes.

12. • Create indexes on the **personSkill** relation that speedup the multiple conditions query

```
select pid, skill
from   personSkill
where  pid = p and skill = s;
```

¹⁵(Three different sizes, small, medium, large suffice for your experiment.

Here **p** is a pid and **s** is a skill.

Illustrate and discuss this speedup by finding the execution times for this query for 3 different but sufficiently large sizes of the **personSkill** relation.

You should compare the execution times for running the query without the index versus the the execution times for running the query with indexes.

13. • Create indexes on the appropriate relations that speedup the semi-join [anti semi-join] query

```
select pid, pname
from   Person
where  pid [not] in (select pid from personSkill where skill = s);
```

Here **s** is a skill.

Illustrate and discuss this speedup by finding the execution times for this query for various, but sufficiently large sizes of the **Person** and **personSkill** relations.

You should compare the execution times for running the query without the index versus the the execution times for running the query with indexes.

14. • Create indexes that speedup the path-discovery query

```
select distinct k1.pid1, k3.pid2
from   knows k1, knows k2, knows k3
where  k1.pid2 = k2.pid1 and k2.pid2 = k3.pid1;
```

Illustrate this speedup by finding the execution times for this query for various sizes of the **Knows** relation.