

CO202 – Software Engineering – Algorithms

String Matching - Solutions

Exercise 1: Prefix Function - Example 3

Complete the prefix function table

$$\pi[q] = \max\{k : k < q \text{ and } P_k \sqsupseteq P_q\}$$

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$\pi[i]$											

Exercise 1: Prefix Function - Example 3

Complete the prefix function table

$$\pi[q] = \max\{k : k < q \text{ and } P_k \sqsupseteq P_q\}$$

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$\pi[i]$	0	0	0	1	0	1	0	1	2	3	4

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$					

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$											

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$											

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$											1

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$										3	1

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$									10	3	1

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$								10	10	3	1

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$							7	10	10	3	1

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$						7	7	10	10	3	1

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$					7	7	7	10	10	3	1

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$				7	7	7	7	10	10	3	1

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$			7	7	7	7	7	10	10	3	1

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$		7	7	7	7	7	7	10	10	3	1

Exercise 2: Boyer-Moore Preprocessing

BCR Table

c	a	b	c	d	r
$bcr[c]$	11	9	5	7	10

GSR Table

i	1	2	3	4	5	6	7	8	9	10	11
$P[i]$	a	b	r	a	c	a	d	a	b	r	a
$gsr[i]$	7	7	7	7	7	7	7	10	10	3	1

Exercise 3: Worst-Case of Boyer-Moore

Show that the worst-case running time of the BM-MATCHER algorithm is $O(nm)$.

Exercise 3: Worst-Case of Boyer-Moore

Show that the worst-case running time of the BM-MATCHER algorithm is $O(nm)$.

It is easy to see when both P and T contain only one unique character, e.g. $P = a^m$ and $T = a^n$.

Exercise 4: Prefix Function as String Matcher

- 1) Devise an algorithm PF-MATCHER that uses the prefix function directly to find all occurrences of P in T ?
- 2) What is the running time complexity of this method?

Exercise 4: Prefix Function as String Matcher

1) Devise an algorithm PF-MATCHER that uses the prefix function directly to find all occurrences of P in T ?

PF-MATCHER(T, P)

1: $n = T.length$

2: $m = P.length$

3: $\pi = \text{PREFIX-FUNCTION}(P + \text{'\#'} + T)$

4: **for** $i = 2*m+1$ **to** $n+m+1$

5: **if** $\pi[i] == m$

6: PRINT($i-2*m-1$)

Exercise 4: Prefix Function as String Matcher

2) What is the running time complexity of this method?

See discussion on the running time of the prefix function which yields $O(m)$ with m being the length of the pattern.

So for PF-MATCHER, we get $O(m + n)$.