

Sensor	Parameter	Safe (Green)	Watch (Yellow)	Danger (Red)	
MQ5	lpg_ppm	< 400	400 - 1000	> 1000	
	rs_kohm	Depends on calibration	Monitor for sudden change	N/A	
MICS5524	co_ppm	0 - 9	10 - 50	> 50	
	ch4_ppm	0 - 500	500 - 1000	> 1000	
	h2_ppm	0 - 100	100 - 400	> 400	
	ethanol_ppm	0 - 100	100 - 500	> 500	
BME280	temperature_c	20 - 28	15 - 19 OR 29 - 35	< 15 OR > 35	
	humidity_pct	30 - 60	20 - 29 OR 61 - 70	< 20 OR > 70	
	pressure_hpa	1000 - 1025	980 - 999	< 980 (Storm Alert)	
BMP280	altitude_m	N/A (Just position)	N/A	N/A	
UV	voltage_v / index	0 - 2	3 - 7	> 7	
Dust	density_ugm3	0 - 50	51 - 100	> 100	
Rain	adc (Analog)	> 2000 (Dry)	1000 - 2000	< 1000 (Heavy Rain)	
	status	"DRY"	"RAIN"	"HEAVY RAIN"	
Windspeed	speed_kmh	0 - 20	21 - 40	> 40	
	speed_ms	0 - 5.5	5.6 - 11	> 11	
Wind Direction	angle_degrees	N/A (Directional change)	N/A	N/A	
MPU6050	accel_x / accel_y	-2.0 to 2.0 m/s ²	> 2.0 or < -2.0	> 5.0 or < -5.0 (Fall/Impact)	
	accel_z	8.8 to 10.8 (Gravity)	N/A	Sudden drop to 0 (Freefall)	
	gyro_x, y, z	-5.0 to 5.0 deg/s	> 5.0 or < -5.0	> 45.0 or < -45.0	